

MINI AQUARIUM SYSTEM USING IOT

Submitted in partial fulfillment of the
requirements for the award of
Bachelor of Technology in Information Technology

By

AARTHI.N (Reg.No - 39120002)

ESTHER.D (Reg.No – 39120029)



**DEPARTMENT OF INFORMATION TECHNOLOGY
SCHOOL OF COMPUTING**

SATHYABAMA

**INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)**

Accredited with Grade “A” by NAAC | 12B Status by UGC | Approved by AICTE

JEPPIAAR NAGAR, RAJIV GANDHISALAI,

CHENNAI – 60

MAY - 2023



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)

Accredited with —All grade by NAAC


Jeppiaar Nagar, Rajiv Gandhi Salai, Chennai – 600 119
www.sathyabama.ac.in




DEPARTMENT OF INFORMATION TECHNOLOGY

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of **Aarthi N(39120002)** and **Esther D(39120029)** who carried out the Project Phase-2 entitled "**MINI AQUARIUM SYSTEM USING IOT**" under my supervision from November 2022 to May 2023.



Internal Guide


Dr. S.GOWRI, M.E., Ph.D


Head of the Department

Dr. R.SUBHASHNI, M.E., Ph.D.

Submitted for Viva voce Examination held on 10-05-2023


Internal Examiner



External Examiner

DECLARATION

I, AARTHI N (Reg.No-39120002) hereby declare that the Project Phase-2 Report entitled "MINI AQUARIUM SYSTEM USING IOT" done by me under the guidance of Dr.S.GOWRI, M.E.,Ph.D is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in **Information Technology**.

DATE: 10/5/23

PLACE: Chennai



SIGNATURE OF THE CANDIDATE

ACKNOWLEDGEMENT

I am pleased to acknowledge my sincere thanks to **Board of Management of SATHYABAMA** for their kind encouragement in doing this project and for completing it successfully. I am grateful to them.

I convey my thanks to **Dr. T. SASIKALA M.E., Ph. D, Dean**, School of Computing, **Dr. R. SUBHASHNI M.E., Ph.D.**, Head of the Department of Information Technology for providing me necessary support and details at the right time during the progressive reviews.

I would like to express my sincere and deep sense of gratitude to my Project Guide **Dr. S. GOWRI M.E., Ph.D.**, for her valuable guidance, suggestions and constant encouragement paved way for the successful completion of my phase-1 project work.

I wish to express my thanks to all Teaching and Non-teaching staff members of the **Department of Information Technology** who were helpful in many ways for the completion of the project.

ABSTRACT

Many people feed the pet fish in the aquarium tanks that need to be properly set up and maintained, or the fish will be destined to an unpleasant and short life. Therefore, it is critical to monitor water condition closely and improve the water quality for the mini aquarium tanks. Based on an IoT solution called Mini Aquarium System that utilizes the aquarium sensors and the actuators in real time. We describe the relationship between the aquarium sensors and actuators and give concrete examples about the threshold setting. Our solution allows the designer to quickly deploy intelligent control for various water conditions. As an example, we implement an intelligent fish feeding mechanism such that the fish is neither over nor under fed, and at the same time, the fish owner can enjoy watching fish feeding remotely. We have also developed the analytic model, simulation, and measurement experiments to investigate the effects of the IoT message delays and loss on water condition control.

Chapter No	TITLE		Page No.
	ABSTRACT		v
	LIST OF FIGURES		viii
	LIST OF TABLES		vi
1	INTRODUCTION		9
	1.1	Aim and Objective	9
2	LITERATURE SURVEY		12
	2.1	Inference from Literature Survey	13
3	METHODOLOGY		15
	3.1	Existing System	15
	3.2	Proposed System	16
4	REQUIREMENT ANALYSIS		18
	4.1	Modules	18
	4.2	Modules Description	18
	4.3	ARDUINO UNO DESCRIPTION	20
	4.4	ATMEGA328 IC	22
	4.5	ANALOG PORTS	27
	4.6	ADC CONVERSION	28
	4.7	PWM PIN'S	28
	4.8	PWM PIN'S ARDUINO	30
	4.9	Wi-fi ESP8266	30
	4.10	MCU BLOCK DIAGRAM	34
	4.11	MCU PIN LAYOUT	35
	4.12	TEMPERATURE SENSOR	37
	4.13	TURIDITY SENSOR	38
	4.14	WATER LEVEL SENSOR	41
	4.15	PH SENSOR	42
	4.16	LED	44
	4.17	SERVO MOTOR	46
	4.18	WATER PUMP MOTOR	47
	4.19	SINGLE CHANNEL RELAY	49
	4.20	BUZZER	51

	4.21	POWER SUPPLY UNIT	53
	4.22	FOOD FEEDER	56
5	SOTWARE DESCRIPTION		57
	5.1	ARDUINO IDE	57
	5.2	PROGRAMMING LANGUAGE	58
6	CONCLUSION		60
	REFERENCES		61
	APPENDIX		64
	A. SOURCE CODE		64
	B. SCREENSHOTS		65
	C. RESEARCH PAPER		72

LIST OF FIGURES

FIGURE NO	FIGURE NAME	Page No.
3.1	Receiver Side	16
3.2	Architecture Diagram	17
4.1	Arduino UNO	20
4.2	ATmega 328P IC	22
4.3	ATmega 328P IC Pin Layout	23
4.4	ATmega 328P IC Architecture Diagram	23
4.5	.ADC Conversion	28
4.6	PWM Pin	27
4.7	PWM Pin Arduino	29
4.8	Wi-fi ESP8266	31
4.9	MCU Block Diagram	34
4.10	MCU Pin Layout	35
4.11	Temperature Sensor	37
4.12	Turbidity Sensor	39
4.13	Connection Diagram	40
4.14	Schematic Diagram	41
4.15	Water Level Sensor	41
4.16	PH Sensor	43
4.17	LED	44
4.18	LED Circuit Diagram	45
4.19	Servo Motor	47
4.20	Water Pump Motor	48
4.21	Single Channel relay	50
4.22	Single Channel relay Circuit Diagram	50
4.23	Buzzer	52
4.24	Buzzer Circuit Diagram	52
4.25	Power Supply Unit	54
4.26	Power Supply Unit Circuit Diagram	55

CHAPTER 1

INTRODUCTION:

In the recent years, mini aquarium tanks in various shapes and sizes are replacing classic goldfish bowls for small apartments or college dorm rooms. For example, college students in a dorm, where no-pet rules do not apply to fish, have space for a mini aquarium. At any university, they will encourage students to watch fish for relaxation and to care for them in the dorms where larger pets are not allowed. However, the aquarium tanks need to be properly set up and maintained, or the fish will be destined to unpleasant and short life. Specifically, when the water volume in the tank is small, key water parameters change very quickly, leaving no room for error. Therefore it is critical to monitor water conditions closely and perform water changes faithfully for the mini aquarium tanks. Many commercial aquarium tanks under one gallon claim that no maintenance is required. However, such products are actually not healthy for fish, and therefore are not recommended. Several studies indicate that small aquarium tanks are not suitable for maintaining healthy fish. The bigger the tank, the less impact a mistake will have on fish, and aquarium tanks of at least five gallons are suggested. In this paper, we consider mini tanks with sizes larger than $60 \times 45 \times 60 \text{ cm}^3$. Even so, key water parameters of a mini aquarium tank should be closely watched, and proper actions should be quickly taken when some were proposed to automate the detection of abnormal aquarium situations. However, few of them have provided intelligent mechanisms to automatically activate the actuators to fix the problems. We have developed an IoT solution called Mini Aquarium for smart dorm, smart garden and other smart campus applications. Based on Mini Aquarium, this paper proposes the Mini Aquarium system that allows the aquarium sensors to drive the actuators in real time.

1.1.AIM AND OBJECTIVE

right In the new years, scaled back aquarium tanks in different shapes and sizes are exchanging exemplary goldfish bowls for little condos or school lofts. For instance, understudies in a quarters, where no-pet principles don't significantly affect fish, have space for a little aquarium. At Public Chiao Tung School (NCTU), we request that understudies watch fish for relaxing and to genuinely focus in on them in the homes where more prominent pets are not permitted. In any case, the aquarium tanks

should be reasonably set up and remained mindful of, or the fish will be bound to horrendous and short life. In particular, when the water volume in the tank is almost nothing, key water limits change rapidly, blocking bungle. Thus it is key to screen water conditions enthusiastically and perform water changes reliably for the more unassuming than common aquarium tanks. Different business aquarium tanks under one gallon guarantee that no assistance is required. Anyway, such things are genuinely not profitable for fish, and in this way are not suggested. A several appraisals, show that little aquarium tanks are not reasonable for remaining mindful of solid fish. The more noticeable the tank, the less effect a bumble will have on fish, and aquarium tanks of something like five gallons are proposed. In this paper, we think about little tanks with sizes more prominent than $60 \times 45 \times 60 \text{ cm}^3$. Considering everything, key water cutoff points of a little aquarium tank ought to be unflinchingly watched, and certifiable activities ought to be expeditiously taken at the point when two or three dangerous circumstances are recognized. Since understudy residences are a large part of the time void during class hours, nobody could have the decision to recognize the remarkable states of the tank. Along these lines, two or three courses of action taking into account Web of Things (IoT) were proposed to automate the disclosure of uncommon aquarium conditions. By and by, not very many of them have given sharp parts to along these lines authorize the actuators to fix the issues. In NCTU, we have developed an IoT blueprint called More modest than expected Aquarium for sharp quarters, awesome nursery and other sharp grounds applications. In context on IoT, this paper proposes the Aquarium framework that permits the aquarium sensors to drive the actuators sensibly

Little Aquarium and the past blueprints. In thing, Limited scope Aquarium utilizes a more noteworthy number of sensors than the previous strategies with the exception of. In thing, Little Aquarium obliges a more imperative number of actuators than the past plans. Thing 3 shows that plans gave sensor seeing yet no actuator control. Blueprints gave manual control of actuators as of now can't ordinarily control the actuators by the sensors. Plan gives insignificant actuator control taking into account direct sensor edges. Obviously, Limited scope Aquarium gives both manual control and altered actuator control by the sensors with non-unimportant data other than direct "edge control". This sharp part permits much better control of the water climate. Moreover, through the time series graphs of sensors/actuators in More modest than normal Aquarium highlight (to be made sense of in Section V), the fish proprietor can

no ifs, ands or buts figure out how the water factors collaborate with one another. Hence, the sensors don't simply give unpleasant information (as the past blueprints do) yet additionally permit the fish proprietors to find out about their aquarium ecological components.

CHAPTER 2

LITERATURE SURVEY

2.1.INFERENCE FROM LITERATURE SURVEY:

TITLE: SMART FISH TALK AN IOT BASED MINI AQUARIUM SYSTEM

AUTHOR: Ahire Laxman Gajanan

DESCRIPTION:

Many people feed the pet fish in the aquarium tanks that need to be properly set up and maintained, or the fish will be destined to an unpleasant and short life. Therefore, it is critical to monitor water conditions closely and improve the water quality for the mini aquarium tanks. Based on an IoT solution called IoT talk, this paper proposes the Fish Talk system that utilizes the aquarium sensors to drive the actuators in real time. We describe the relationship between the aquarium sensors and the actuators and give concrete examples about the threshold setting. Our solution allows the designer to quickly deploy intelligent control for various water conditions. As an example, we implement an intelligent fish feeding mechanism such that the fish is neither over nor under fed, and at the same time, the fish owner can enjoy watching fish feeding remotely. We have also developed the analytic model, simulation, and measurement experiments to investigate the effects of the IoT message delays and loss on water condition control.

TITLE: IOT BASED AUTOMATIC AQUARIUM SYSTEM

AUTHOR: Nilima S.

DESCRIPTION:

It is not feasible for fish owners to leave extra food in their fish's tank before leaving for an extended period. This creates the need for a device that can automatically and reliably feed a fish. The purpose of this project is to design an automated fish feeder for household use. The device can be developed to feed a single goldfish for at least 14 days without any additional input from the user. We will be using Node MCU which is latest microcontroller and having in-built Wi-Fi technology. Using Node MCU, we will be able to control water motor, Food motor, oxygen bubble motor and LED

TITLE: Arduino based Fish Monitoring System

AUTHOR: 5 Samir Sherki

DESCRIPTION:

Fish monitoring system is essential because many people love to grow fishes as their pet in the home. In our day-to-day life, it is difficult to monitor the aquarium tank regularly. As a consequence, it causes mortality of the fishes. The quality of water might be the main issue. It mainly depends upon parameters such as carbonates, ammonia, nitrates, salt, pH, temperature, turbidity, dissolved oxygen, etc. To maintain these parameters, various sensors are used in the fish monitoring system. This will increase the production of fishes and decrease mortality. Many researchers had proposed various methods for maintaining the water quality in the aquarium and the fish ponds. The main purpose of this paper is to review the sensors used in the fish monitoring system and the critical comparison of various sensors with other research papers.

TITLE: Arduino based Automated Fish Tank

AUTHOR: Saravanaraj D M.

DESCRIPTION:

Fish keeping is popular these days, people from all age group like to keep fish in their home, office etc. in the aquarium tank that needs to be properly set up and maintained, or the fish will be destined to an unpleasant and short life. Hence it is difficult to monitor and control water conditions closely and enhance the water quality. Based on Arduino the Automated Fish Tank system that utilizes the aquarium sensors to monitor and control the water conditions. Proposed solution gives quick access to utilize the smart system to control various water parameters. The system contains automatic feeder which will ensure the food is to be fed adequate and at right interval of time, Turbidity sensor which is deployed alongside filter for maintaining clean water, pH sensor will display pH of water, Temperature sensor and heater, cooler is used to maintain water temperature and Bubbler will operate as a consequence of dissolved oxygen sensor to retain oxygen level.

LITERATURE SURVEY:

S.No	Topic	Author(S)	Focus
01	SMART FISH TALK AN IOT BASED MINI AQUARIUM SYSTEM	Ahire Laxman Gajanan	In this paper, It fails to improvise the water quality of the fish tank remotely
02	IOT BASED AUTOMATIC AQUARIUM SYSTEM	Nilima S. Gite*4	We tackle the problem by feeding many fish in one Aquarium.
03	Arduino based Fish Monitoring System	Samir Sherki	We connected the sensors with mobile application to verify
04	Arduino based Automated Fish Tank	Saravananaraj D M.	Moreover, we included mobile application connected with food feeder and sensors.

CHAPTER 3

METHODOLOGY

Classic goldfish bowls are being replaced in recent years by miniature aquarium tanks in a variety of sizes and forms for tiny apartments or college dorm rooms. For instance, college students living in dorms have space for a small aquarium since fish are exempt from the no-pet policy. At National Chiao Tung University (NCTU), we encourage students to take care of fish in the dorms where larger pets are not permitted as a form of leisure. To avoid an uncomfortable and brief life for the fish, the aquarium tanks must be correctly set up and maintained. Particularly, important water parameters vary rapidly when the tank's water capacity is limited, leaving no room for mistake. The water in the micro aquarium tanks must thus be carefully monitored, and water changes must be made consistently. The argument that care is not necessary is made by many commercial aquarium tanks under one gallon. It is not advised to use such things because they are genuinely unhealthy for fish. Small aquarium tanks don't work well for keeping healthy fish, according to a number of studies . A mistake will have less of an effect on the fish the larger the tank is, thus at least five gallons of aquarium space is advised

3.1.Existing System:

However, the aquarium tanks need to be properly set up and maintained, or the fish will be destined to unpleasant and short life. Specifically, when the water volume in the tank is small, key water parameters change very quickly, leaving no room for error. Therefore it is critical to monitor water conditions closely and perform water changes faithfully for the mini aquarium tanks. Many commercial aquarium tanks under one gallon claim that no maintenance is required.

3.2. Proposed System:

As per the proposed system in our day-to-day life, it is difficult to monitor the aquarium tank regularly. As a consequence, it causes mortality of the fishes. The quality of water might be the main issue. It mainly depends upon parameters such as carbon, pH, temperature, water level, turbidity, dissolved oxygen, etc. To maintain these parameters, various sensors are used in the fish monitoring system. This will increase the production of fishes and decrease mortality. Many researchers had proposed various methods for maintaining the water quality in the aquarium and the fish ponds. The main purpose of this paper is to review the sensors used in the fish monitoring system

Receiver Side:




Fig.3.1.Receiver Side

BLOCK DIAGRAM:




Fig.3.2.Architecture Diagram

CHAPTER 4

REQUIREMENT ANALYSIS

4.1. MODULES:

1. SENSOR INTERFACING
2. PREPARING POWER SUPPLY UNIT
3. MICRO-CONTROLLER PROGRAMMING
4. READING ANALOG DATA
5. TEST AND DEBUG
6. SUBMISSION

4.2. MODULE DESCRIPTION:

1. SENSOR INTERFACING

Sensor interfacing is a mix of amplification, filtering, and other signal conditioning as well as analog-to-digital conversion. The analog-to-digital converter (ADC) may be in your microcontroller, but you will still need to make the sensor compatible with the ADC input.

2. PREPARING POWER SUPPLY UNIT

A power supply unit (or PSU) converts mains AC to low-voltage regulated DC power for the internal components of a controller. A power supply is used to reduce the mains electricity at 240 volts AC down to something more useable, say 12 volts DC. There are two types of power supply, linear and switch mode. A linear power supply uses a transformer to reduce the voltage. The AC signal is rectified and regulated to produce a high DC voltage.

An AC adapter, AC/DC adapter, or AC/DC converter is a type of external power supply, often enclosed in a case similar to an AC plug. Adapters for battery-powered equipment may be described as chargers or rechargers (see

also battery charger). AC adapters are used with electrical devices that require power but do not contain internal components to derive the required voltage and power from main power. The internal circuitry of an external power supply is very similar to the design that would be used for a built-in or internal supply.

3. MICRO-CONTROLLER PROGRAMMING

A microcontroller is a programmable IC, capable of multiple functions depending on how it's programmed. Many different kinds of microcontrollers exist that offer a wide range of functionality. The versatility of the microcontroller is what makes it one of the most powerful tools in modern design. This guide will explain the basics of microcontrollers and how they are programmed.

4. READING ANALOG DATA

The microcontroller of the board has a circuit inside called an analog-to-digital converter or ADC that reads this changing voltage and converts it to a number between 0 and 1023. When the shaft is turned all the way in one direction, there are 0 volts going to the pin, and the input value is 0. When the shaft is turned all the way in the opposite direction, there are 5 volts going to the pin and the input value is 1023. In between, `analog Read()` returns a number between 0 and 1023 that is proportional to the amount of voltage being applied to the pin.

5. TEST AND DEBUG

Testing means verifying correct behavior. Testing can be done at all stages of module development: requirements analysis, interface design, algorithm design, implementation, and integration with other modules. In the following, attention will be directed at implementation testing. Implementation testing is not restricted to execution testing. An implementation can also be tested using correctness proofs, code tracing, and peer reviews, as described below.

Debugging is a cyclic activity involving execution testing and code correction. The testing that is done during debugging has a different aim than final module testing. Final module testing aims to demonstrate correctness, whereas testing during debugging is primarily aimed at locating errors. This difference has a significant effect on the choice of testing strategies.

6. SUBMISSION

Submitting the prototype for the presentation to the faculty guide for review purpose

4.3.ARDUINO UNO

DESCRIPTION

Arduino is an open source, computer hardware and software company, project, and user community that designs and manufactures Single-board microcontrollers and microcontroller kits for building digital devices and interactive objects that can sense and control objects in the physical world. Arduino is an open-source electronics platform based on easy-to-use hardware and software. Arduino boards are able to read inputs - light on a sensor, a finger on a button, or a Twitter message - and turn it into an output - activating a motor, turning on an LED, publishing something online. The Arduino Uno is a microcontroller board based on the ATmega328 (datasheet). It has 14 digital input/output pins (of which 6 can be used as PWM outputs), analog inputs, a 16 MHz crystal oscillator, a USB connection, a power jack, an ICSP header, and a reset button.




FIG.4.1. Arduino UNO

Arduino is an open-source project that created microcontroller-based kits for building digital devices and interactive objects that can sense and control physical devices. The project is based on microcontroller board designs, produced by several vendors, using various microcontrollers. These systems provide sets of digital and analog input/output (I/O) pins that can interface to various expansion boards (termed shields) and other circuits. The boards feature serial communication interfaces, including Universal Serial Bus (USB) on some models, for loading programs from personal computers. For programming the microcontrollers, the Arduino project provides an integrated development environment (IDE) based on a programming language named Processing, which also supports the languages C and C++.

Arduino Uno is a microcontroller board based on the ATmega328P. It has 14 digital input/output pins (of which 6 can be used as PWM outputs), 6 analog inputs, a 16 MHz quartz crystal, a USB connection, a power jack, an ICSP header and a reset button. It contains everything needed to support the microcontroller; simply connect it to a computer with a USB cable or power it with a AC-to-DC adapter. Arduino Uno has a number of facilities for communicating with a computer, another Arduino board, or other microcontrollers.

FEATURES

- Microcontroller: ATmega328P
- Operating voltage: 5V
- Input voltage: 7-12V
- Flash memory: 32KB
- SRAM: 2KB
- EEPROM: 1KB

APPLICATIONS

- Real time biometrics
- Robotic applications
- Academic applications

4.4. ATMEGA328 IC

DESCRIPTION

The ATmega328 is a single-chip microcontroller created by Atmel in the mega AVR family. The Atmel 8-bit AVR RISC-based microcontroller combines 32 kB ISP flash memory with read-while-write capabilities, 1 kB EEPROM, 2 kB SRAM, 23 general purpose I/O lines, 32 general purpose working registers, three flexible timer/counters with compare modes, internal and external interrupts, serial programmable USART, a byte-oriented 2-wire serial interface, SPI serial port, 6-channel 10-bit A/D converter (8-channels in TQFP and QFN/MLF packages), programmable watchdog timer with internal oscillator, and five software selectable power saving modes. The device operates between 1.8-5.5 volts. The device achieves throughput approaching 1 MIPS per MHz.



FIG 4.2. ATmega328P IC




Fig.4.3.ATMega 328 ic Pin layout

- High Performance, Low Power Atmel®AVR® 8-Bit Microcontroller Family
- Advanced RISC Architecture
 - 131 Powerful Instructions
 - Most Single Clock Cycle Execution
 - 32 x 8 General Purpose Working Registers
 - Fully Static Operation
 - Up to 20 MIPS Throughput at 20MHz
 - On-chip 2-cycle Multiplier
- High Endurance Non-volatile Memory Segments
 - 4/8/16/32KBytes of In-System Self-Programmable Flash program memory
 - 256/512/1KBytes EEPROM
 - 512/1K/2KBytes Internal SRAM
 - Write/Erase Cycles: 10,000 Flash/100,000 EEPROM C(1)°C/100 years at 25°-Data retention: 20 years at 85
 - Optional Boot Code Section with Independent Lock Bits In-System Programming by On-chip Boot Program
 - True Read-While-Write Operation
 - Programming Lock for Software Security Atmel® QTouch® library support

- Capacitive touch buttons, sliders and wheels– QTouch and QMatrix® acquisition
- Up to 64 sense channels
- Peripheral Features
 - Two 8-bit Timer/Counters with Separate Prescaler and Compare Mode
 - One 16-bit Timer/Counter with Separate Prescaler, Compare Mode, and Capture Mode
 - Real Time Counter with Separate Oscillator
 - Six PWM Channels
 - 8-channel 10-bit ADC in TQFP and QFN/MLF package
 - Temperature Measurement
 - 6-channel 10-bit ADC in PDIP Package
 - Temperature Measurement
 - Programmable Serial USART–Master/Slave SPI Serial Interface
 - Byte-oriented 2-wire Serial Interface (Philips I2 C compatible)
 - Programmable Watchdog Timer with Separate On-chip Oscillator
 - On-chip Analog Comparator
 - Interrupt and Wake-up on Pin Change

Special Microcontroller Features

- Power-on Reset and Programmable Brown-out Detection
- Internal Calibrated Oscillator
- External and Internal Interrupt Sources

Six Sleep Modes: Idle, ADC Noise Reduction, Power-save, Power-down, Standby, and Extended Standby




Fig.4.4.Atmega 328 IC Architecture

FEATURES:

- I/O and Packages
- 23 Programmable I/O Lines
- 28-pin PDIP, 32-lead TQFP, 28-pad QFN/MLF and 32-pad QFN/MLF
- Operating Voltage: 1.8 – 5.5 V
- Temperature range: -40 °C to 85°
- Speed Grade: 0 - 4MHz@1.8 - 5.5V, 0 - 10MHz@2.7 - 5.5V, 0 - 20MHz @ 4.5 - 5.5V C°
- Power Consumption at 1MHz, 1.8V, 25
- Active Mode: 0.2Ma
- Power-down Mode: 0.1µA
- Power-save Mode: 0.75µA (Including 32kHz RTC)

PIN DISCRIPTION

VCC Digital supply voltage

GND Ground.

Port B (PB7:0) XTAL1/XTAL2/TOSC1/TOSC2

Port B is an 8-bit bi-directional I/O port with internal pull-up resistors (selected for each bit). The Port B output buffers have symmetrical drive characteristics with both high sink and source capability. As inputs, Port B pins that are externally pulled low will source current if the pull-up resistors are activated. The Port B pins are tri-stated when a reset condition becomes active, even if the clock is not running. Depending on the clock selection fuse settings, PB6 can be used as input to the inverting Oscillator amplifier and input to the internal clock operating circuit. Depending on the clock selection fuse settings, PB7 can be used as output from the inverting Oscillator amplifier. If the Internal Calibrated RC Oscillator is used as chip clock source, PB7..6 is used as TOSC2..1 input for the Asynchronous Timer/Counter2 if the AS2 bit in ASSR is set.

Port C (PC5:0)

Port C is a 7-bit bi-directional I/O port with internal pull-up resistors (selected for each bit). The PC5 0 output buffers have symmetrical drive characteristics with both high sink and source capability. As inputs, Port C pins that are externally pulled low will source current if the pull-up resistors are activated. The Port C pins are tri-stated when a reset condition becomes active, even if the clock is not running.

PC6/RESET

If the RSTDISBL Fuse is programmed, PC6 is used as an I/O pin. Note that the electrical characteristics of PC6 differ from those of the other pins of Port C. If the RSTDISBL Fuse is unprogrammed, PC6 is used as a Reset input. A low level on this pin for longer than the minimum pulse length will generate a Reset, even if the clock is not running. The minimum pulse length is given in Table 28-3 on page 308. Shorter pulses are not guaranteed to generate a Reset.

Port D (PD7:0)

Port D is an 8-bit bi-directional I/O port with internal pull-up resistors

(selected for each bit). The Port D output buffers have symmetrical drive characteristics with both high sink and source capability. As inputs, Port D pins that are externally pulled low will source current if the pull-up resistors are activated. The Port D pins are tri-stated when a reset condition becomes active, even if the clock is not running.

AVCC

AVCC is the supply voltage pin for the A/D Converter, PC3:0, and ADC7:6. It should be externally connected to VCC, even if the ADC is not used. If the ADC is used, it should be connected to VCC through a low-pass filter. Note that PC6..4 use digital supply voltage, VCC

AREF

AREF is the analog reference pin for the A/D Converter

ADC7:6 (TQFP and QFN/MLF Package Only)

In the TQFP and QFN/MLF package, ADC7:6 serve as analog inputs to the A/D converter. These pins are powered from the analog supply and serve as 10-bit ADC channels.

4.5.ANALOG PORTS

DESCRIPTION

In electronics, an analog-to-digital converter (ADC, A/D, A–D, or A-to-D) is a system that converts an analog signal, such as a sound picked up by a microphone or light entering a digital camera, into a digital signal. An ADC may also provide an isolated measurement such as an electronic device that converts an input analog voltage or current to a digital number proportional to the magnitude of the voltage or current.

In an embedded system, A/D conversion is very important as embedded systems deal with digital values; their surroundings usually occupy various analog signals. Analog signals need to be altered into digital before being treated by the microcontroller. At present, we can observe how to read an external analog signal using PIC microcontroller and exhibit the digital o/p conversion on an LCD display. The i/p signal can be a varying voltage between 0 to 5v.




Fig.4.5..ADC Conversion

4.6.ADC Conversion

The Arduino UNO board has five analog input pins A0 through A5. These pins can read the signal from an analog sensor like the humidity sensor or temperature sensor and convert it into a digital value that can be read by the microprocessor.

In the world of Arduino an Analog signal is simply a signal that can be HIGH (on), LOW (off) or anything in between these two states. This means an Analog signal has a voltage value that can be anything between 0V and 5V (unless you mess with the Analog Reference pin). Analog allows you to send output or receive input about devices that run at percentages as well as on and off. The Arduino does this by sampling the voltage signal sent to these pins and comparing it to a voltage reference signal (5V). Depending on the voltage of the Analog signal when compared to the Analog Reference signal the Arduino then assigns a numerical value to the signal somewhere between 0 (0%) and 1023 (100%). The digital system of the Arduino can then use this number in calculations and sketches.

4.7.PWM PIN'S

DESCRIPTION

PWM stands for Pulse Width Modulation, which in itself is not very useful if you don't know what modulation is. In the electronics world, modulation is the technique of superimposing information on a high speed signal or carrier.

verage wattage. a number of APV's use pulse width to regulate power down below

the battery's supplied voltage, since most lipo packs and all 18650 style batteries output 3.7 volts at a nominal charge level. ... DC-DC is a flat signal.




Fig.4.6.PWM Pin

Pulse width modulation (PWM) is a fancy term for describing a type of digital signal. Pulse width modulation is used in a variety of applications including sophisticated control circuitry. A common way we use them here at SparkFun is to control dimming of RGB LEDs or to control the direction of a servo motor.




Fig.4.7.PWM PIN'S ARDUINO

4.8.PWM PIN'S ARDUINO

Pulse Width Modulation, or PWM, is a technique for getting analog results with digital means. Digital control is used to create a square wave, a signal switched between on and off. This on-off pattern can simulate voltages in between full on (5 Volts) and off (0 Volts) by changing the portion of the time the signal spends on versus the time that the signal spends off. The duration of "on time" is called the pulse width. To get varying analog values, you change, or modulate, that pulse width. If you repeat this on-off pattern fast enough with an LED for example, the result is as if the signal is a steady voltage between 0 and 5v controlling the brightness of the LED.

In the graphic below, the green lines represent a regular time period. This duration or period is the inverse of the PWM frequency. In other words, with Arduino's PWM frequency at about 500Hz, the green lines would measure 2 milliseconds each. A call to `analogWrite()` is on a scale of 0 - 255, such that `analogWrite(255)` requests a 100% duty cycle (always on), and `analogWrite(127)` is a 50% duty cycle (on half the time) for example.

4.9.WI-FI ESP8266

DESCRIPTION

ESP8266 is a single 2.4 GHz Wi-Fi-and-Bluetooth combo chip designed with the TSMC ultra-low-power 40 nm technology. It is designed to achieve the best power and RF performance, showing robustness, versatility and reliability in a wide variety of applications and power scenarios.

The ESP8266 series of chips includes ESP8266-D0WD-V3, ESP8266-D0WDQ6-V3, ESP8266-D0WD, ESP8266-D0WDQ6, ESP8266-D2WD, ESP8266-S0WD, and ESP8266-U4WDH, among which, ESP8266-D0WD-V3, ESP8266-D0WDQ6-V3, and ESP8266-U4WDH are based on ECO V3 wafer.




Fig.4.8.Wi-fi ESP8266

Featured Solutions:

➤ Ultra Low Power Solution

ESP8266 is designed for mobile, wearable electronics, and Internet-of-Things (IoT) applications. It features all the state-of-the-art characteristics of low-power chips, including fine-grained clock gating, multiple power modes, and dynamic power scaling. For instance, in a low-power IoT sensor hub application scenario, ESP8266 is woken up periodically and only when a specified condition is detected. Low-duty cycle is used to minimize the amount of energy that the chip expends. The output of the power amplifier is also adjustable, thus contributing to an optimal trade-off between communication range, data rate and power consumption.

➤ Complete Integration Solution

ESP8266 is a highly-integrated solution for Wi-Fi-and-Bluetooth IoT applications, with around 20 external components. ESP8266 integrates an antenna switch, RF balun, power amplifier, low-noise receive amplifier, filters, and power management modules. As such, the entire solution occupies minimal Printed Circuit Board (PCB) area. ESP8266 uses CMOS for single-chip fully-integrated radio and baseband, while also integrating advanced calibration circuitries that allow the solution to remove external

circuit imperfections or adjust to changes in external conditions. As such, the mass production of ESP8266 solutions does not require expensive and specialized Wi-Fi testing equipment.

Wi-Fi Key Features :

- 802.11 b/g/n
- 802.11 n (2.4 GHz), up to 150 Mbps
- WMM
- TX/RX A-MPDU, RX A-MSDU
- Immediate Block ACK
- Defragmentation
- Automatic Beacon monitoring (hardware TSF)
- 4 × virtual Wi-Fi interfaces
- Simultaneous support for Infrastructure Station, SoftAP, and Promiscuous modes Note that when ESP8266 is in Station mode, performing a scan, the SoftAP channel will be changed.
- Antenna diversity

BT Key Features:

- Compliant with Bluetooth v4.2 BR/EDR and BLE specifications
- Class-1, class-2 and class-3 transmitter without external power amplifier
- Enhanced Power Control
- +12 dBm transmitting power
- NZIF receiver with –94 dBm BLE sensitivity
- Adaptive Frequency Hopping (AFH)
- Standard HCI based on SDIO/SPI/UART
- High-speed UART HCI, up to 4 Mbps
- Bluetooth 4.2 BR/EDR BLE dual mode controller
- Synchronous Connection-Oriented/Extended (SCO/eSCO)
- CVSD and SBC for audio codec
- Bluetooth Piconet and Scatternet
- Multi-connections in Classic BT and BLE
- Simultaneous advertising and scanning

MCU and Advanced Features:

CPU and Memory:

- Xtensa® single-/dual-core 32-bit LX6 microprocessor(s), up to 600 MIPS (200 MIPS for ESP8266-S0WD/ESP8266-U4WDH, 400 MIPS for ESP8266-D2WD)
- 448 KB ROM
- 520 KB SRAM
- 16 KB SRAM in RTC
- QSPI supports multiple flash/SRAM chips

Clocks and Timers:

- Internal 8 MHz oscillator with calibration
- Internal RC oscillator with calibration
- External 2 MHz ~ 60 MHz crystal oscillator (40 MHz only for Wi-Fi/BT functionality)
- External 32 kHz crystal oscillator for RTC with calibration
- Two timer groups, including 2 × 64-bit timers and 1 × main watchdog in each group
- One RTC timer
- RTC watchdog

Advanced Peripheral Interfaces:

- 34 × programmable GPIOs
- 12-bit SAR ADC up to 18 channels
- 2 × 8-bit DAC
- 10 × touch sensors
- 4 × SPI
- 2 × I²S
- 2 × I²C
- 3 × UART
- 1 host (SD/eMMC/SDIO)
- 1 slave (SDIO/SPI)
- Ethernet MAC interface with dedicated DMA and IEEE 1588 support
- Two-Wire Automotive Interface (TWA^I®, compatible with ISO11898-1)
- IR (TX/RX)
- Motor PWM
- LED PWM up to 16 channels
- Hall sensor

Security:

- Secure boot
- Flash encryption
- 1024-bit OTP, up to 768-bit for customers
- Cryptographic hardware acceleration: – AES – Hash (SHA-2)
RSA – ECC – Random Number Generator (RNG)

4.10.MCU BLOCK DIAGRAM:




Fig.4.9.MCU Block Diagram

4.11.MCU PIN LAYOUT:




Fig.4.10.MCU Pin Layout

CPU and Memory:

CPU:

ESP8266 contains one or two low-power Xtensa® 32-bit LX6 microprocessor(s) with the following features:

- 7-stage pipeline to support the clock frequency of up to 240 MHz (160 MHz for ESP8266-S0WD, ESP8266-D2WD, and ESP8266-U4WDH)
- 16/24-bit Instruction Set provides high code-density
- Support for Floating Point Unit
- Support for DSP instructions, such as a 32-bit multiplier, a 32-bit divider, and a 40-bit MAC
- Support for 32 interrupt vectors from about 70 interrupt sources The single-/dual-CPU interfaces include:
 - Xtensa RAM/ROM Interface for instructions and data
 - Xtensa Local Memory Interface for fast peripheral register access
 - External and internal interrupt sources
 - JTAG for debugging

Internal Memory:

ESP8266's internal memory includes:

- 448 KB of ROM for booting and core functions
- 520 KB of on-chip SRAM for data and instructions
- 8 KB of SRAM in RTC, which is called RTC FAST Memory and can be used for data storage; it is accessed by the main CPU during RTC Boot from the Deep-sleep mode.
- 8 KB of SRAM in RTC, which is called RTC SLOW Memory and can be accessed by the co-processor during the Deep-sleep mode.
- 1 Kbit of eFuse: 256 bits are used for the system (MAC address and chip configuration) and the remaining 768 bits are reserved for customer applications, including flash-encryption and chip-ID.
- Embedded flash

External Flash and SRAM:

ESP8266 supports multiple external QSPI flash and SRAM chips. More details can be found in Chapter SPI in the ESP8266 Technical Reference Manual. ESP8266 also supports hardware encryption/decryption based on AES to protect developers' programs and data in flash.

ESP8266 can access the external QSPI flash and SRAM through high-speed caches.

- When external flash is mapped into CPU instruction memory space, up to 11 MB + 248 KB can be mapped at a time. Note that if more than 3 MB + 248 KB are mapped, cache performance will be reduced due to speculative reads by the CPU.
- Up to 16 MB of external flash can be mapped into CPU instruction memory space and read only memory space simultaneously.
- When external flash is mapped into read-only data memory space, up to 4 MB can be mapped at a time. 8-bit, 16-bit and 32-bit reads are supported.
- External SRAM can be mapped into CPU data memory space .SPARM up to 8 MB is supported and up to 4 MB can be mapped at a time.8-bit,16-bit and 32-bit reads and writes are supported.

4.12.TEMPERATURE SENSOR

DESCRIPTION:

A temperature sensor is a device, typically, a thermocouple or RTD, that provides for temperature measurement through an electrical signal. A thermocouple (T/C) is made from two dissimilar metals that generate electrical voltage in direct proportion to changes in temperature.

The LM35 series are precision integrated-circuit temperature devices with an output voltage linearly-proportional to the Centigrade temperature. The LM35 device has an advantage over linear temperature sensors calibrated in Kelvin, as the user is not required to subtract a large constant voltage from the output to obtain convenient Centigrade scaling.




Fig.4.11.Temperature Sensor

The LM35 device does not require any external calibration or trimming to provide typical accuracies of $\pm 1/4^{\circ}\text{C}$ at room temperature and $\pm 3/4^{\circ}\text{C}$ over a full -55°C to 150°C temperature range. The low-output impedance, linear output, and precise inherent calibration of the LM35 device makes interfacing to readout or control circuitry especially easy.

LM35 is a precision IC temperature sensor with its output proportional to the temperature (in $^{\circ}\text{C}$). The sensor circuitry is sealed and therefore it is not subjected to oxidation and other processes. With LM35, temperature can be measured more accurately than with a thermistor. It also possess low self heating and does not cause more than 0.1°C temperature rise in still air.

The device is used with single power supplies, or with plus and minus supplies. As the LM35 device draws only $60\text{ }\mu\text{A}$ from the supply, it has very low self-heating of less

than 0.1°C in still air. The LM35 device is rated to operate over a -55°C to 150°C temperature range.

FEATURES :

- Calibrated Directly in Celcius(Centigrade)
- Linear + 10-mV/°C Scale Factor
- 0.5°C Ensured Accuracy(at 25°C)
- Rated for full -55°C to 150°C Range
- Suitable for Remote Applications

APPLICATIONS

- Power Supplies
- Battery Management
- HVAC
- Appliances

4.13.TURBIDITY SENSOR

DESCRIPTION:

The turbidity sensor detects water quality by measuring the levels of turbidity. It uses light to detect suspended particles in water by measuring the light transmittance and scattering rate, which changes with the amount of total suspended solids (TSS) in water. As the TTS increases, the liquid turbidity level increases. Turbidity sensors are used to measure water quality in rivers and streams, wastewater and effluent measurements, control instrumentation for settling ponds, sediment transport research and laboratory measurements. This sensor provides analog and digital signal output modes. The threshold is adjustable when in digital signal mode. You can select the mode according to your MCU.



Fig.4.12.Turbidity Sensor

SPECIFICATION:

- Operating Voltage: 5V DC
- Operating Current: 40mA (MAX)
- Response Time : <500ms
- Insulation Resistance: 100M (Min)
- Output Method: Analog output: 0-4.5V Digital Output: High/Low level signal (you can adjust the threshold value by adjusting the potentiometer)
- Operating Temperature: 5H~90H
- Storage Temperature: -10H~90H
- Weight: 30g
- Adapter Dimensions: 38mm*28mm*10mm/1.5inches *1.1inches*0.4inches.

CONNECTION DIAGRAM:

Connection Diagram




Fig.4.13.Connection Digram

INTERFACE DESCRIPTION:

1. "D/A" Output Signal Switch

"A": Analog Signal Output, the output value will decrease when in liquids with a high turbidity

"D": Digital Signal Output, high and low levels, which can be adjusted by the threshold potentiometer

2. Threshold Potentiometer: you can change the trigger condition by adjusting the threshold potentiometer in digital signal mode.

This is a reference chart for the mapping from the output voltage to the NTU according to different temperature. e.g. If you leave the sensor in the pure water, that is $NTU < 0.5$, it should output " $4.1 \pm 0.3V$ " when temperature is $10 \sim 50^{\circ}H$.

SCHEMATIC DIAGRAM:




Fig.4.14.Schematic Digram

4.14.WATER LEVEL SENSOR

DESCRIPTION:

Water Level Sensors. Level sensors are used to detect the level of substances that can flow. Such substances include liquids, slurries, granular material and powders. Level measurements can be done inside containers or it can be the level of a river or lake.



Fig.4.15.Water Level Sensor

Level sensors detect the level of liquids and other fluids and powders that exhibit an upper free surface. Substances that flow become essentially horizontal in their containers (or other physical boundaries) because of gravity whereas most bulk solids pile at an angle of repose to a peak. There are many physical and application variables that affect the selection of the optimal level monitoring method for industrial and commercial processes. The selection criteria include the physical: phase (liquid, solid or slurry), temperature, pressure or vacuum, chemistry, dielectric constant of medium, density (specific gravity) of medium, agitation (action), acoustical or electrical noise, vibration, mechanical shock, tank or bin size and shape

Level sensors detect the level of substances that flow, including liquids, Slurries, granular materials, and powders. The substance to be measured can be inside a container or can be in its natural form. The level measurement can be either continuous or point values. Continuous level sensors measure level within a specified range and determine the exact amount of substance in a certain place. While point-level sensors only indicate whether the substance is above or below the sensing point generally the latter detect levels that are excessively high or low. Selection of an appropriate type of sensor suiting to the application requirement is very important.

FEATURES:

- Input voltage: 5v
- Output: Analog.
- Output voltage: 0-3v
- Level detecting range: 0 to .2m.
- Level Determined with the resistance

APPLICATIONS:

- Movable arm.
- Air ball.

4.15.PH SENSOR

DESCRIPTION:

A pH Meter is a scientific instrument that measures the hydrogen-ion activity in water-based solutions, indicating its acidity or alkalinity expressed as pH. The

difference in electrical potential relates to the acidity or pH of the solution.

Use the pH Sensor just as you would a traditional pH meter with the additional advantages of automated data collection, graphing, and data analysis. Typical activities using our pH sensor include; Acid-base titrations, Studies of household acids and bases, Monitoring pH change during chemical reactions or in an aquarium as a result of photosynthesis, Investigations of acid rain and buffering, Analysis of water quality in streams and lakes

A pH sensor is a device that measures the hydrogen-ion concentration (pH) in a solution, indicating its acidity or alkalinity. In addition to measuring the pH of liquids, it can also measure the moisture and light level. The pH sensor has an inbuilt meter to measure the light intensity. The pH of a solution indicates how acidic or basic (alkaline) it is. The pH term translates the values of the hydrogen ion concentration - which ordinarily ranges between about 1×10^{-14} gramequivalents per litre - into numbers between 0 and 14.



Fig.4.16.PH Sensor

FEATURES:

- Supply voltage: 5VDC
- Soil Tester Moisture - Light - PH
- Output: Analog

APPLICATIONS:

- Acid-base titrations
- Analysis of water quality in streams and lakes

4.16.LIGHT EMITTING DIODE

DESCRIPTION:

A light-emitting diode (LED) is a two-lead semiconductor light source. It is a p–n junction diode that emits light when activated. When a suitable voltage is applied to the leads, electrons are able to recombine with electron holes within the device, releasing energy in the form of photons. This effect is called electroluminescence, and the color of the light (corresponding to the energy of the photon) is determined by the energy band gap of the semiconductor. LEDs are typically small (less than 1 mm²) and integrated optical components may be used to shape the radiation pattern.



Fig.4.17.LED

Appearing as practical electronic components in 1962, the earliest LEDs emitted low-intensity infrared light. Infrared LEDs are still frequently used as transmitting elements in remote-control circuits, such as those in remote controls for a wide variety of consumer electronics. The first visible-light LEDs were also of low intensity and limited to red. Modern LEDs are available across the visible, ultraviolet, and infrared wavelengths, with very high brightness.

Early LEDs were often used as indicator lamps for electronic devices, replacing small incandescent bulbs. They were soon packaged into numeric readouts in the form of seven-segment displays and were commonly seen in digital clocks. Recent developments have produced LEDs suitable for environmental and task

lighting. LEDs have led to new displays and sensors, while their high switching rates are useful in advanced communications technology.

CIRCUIT DIAGRAM:




Fig .4.18.LED Circuit Diagram

A light-emitting diode (LED) is a semiconductor device that emits visible light when an electric current passes through it. The light is not particularly bright, but in most LEDs it is monochromatic, occurring at a single wavelength. The output from an LED can range from red (at a wavelength of approximately 700 nanometers) to blue-violet (about 400 nanometers). Some LEDs emit infrared (IR) energy (830 nanometers or longer); such a device is known as an *infrared-emitting diode* (IRED).

FEATURES:

- Energy Efficiency.
- Environmentally Friendly.
- Maintenance and safety.

APPLICATIONS:

- Retail and office.
- Industrial.

- Healthcare.
- Street Lighting.

4.17.SERVO MOTOR

DESCRIPTION:

A servomotor is a rotary actuator or linear actuator that allows for precise control of angular or linear position, velocity and acceleration. It consists of a suitable motor coupled to a sensor for position feedback.

The servo motor is controlled by a signal (data) better known as a pulse-width modulator (PWM). Here are several of the more common servo motor applications in use today. Robotics: A servo motor at every "joint" of a robot is used to actuate movements, giving the robot arm its precise angle.

Servos are controlled by sending an electrical pulse of variable width, or pulse width modulation (PWM), through the control wire. There is a minimum pulse, a maximum pulse, and a repetition rate. A servo motor can usually only turn 90° in either direction for a total of 180° movement.

Servomotors are not a specific class of motor although the term servomotor is often used to refer to a motor suitable for use in a closed-loop control system. The motor is paired with some type of encoder to provide position and speed feedback. In the simplest case, only the position is measured. The measured position of the output is compared to the command position, the external input to the controller.

If the output position differs from that required, an error signal is generated which then causes the motor to rotate in either direction, as needed to bring the output shaft to the appropriate position. As the positions approach, the error signal reduces to zero and the motor stops.

A servomotor is a rotary actuator or linear actuator that allows for precise control of angular or linear position, velocity and acceleration. It consists of a suitable motor coupled to a sensor for position feedback. It also requires a relatively sophisticated controller, often a dedicated module designed specifically for use with servomotors.

A servomotor is closed-loop servomechanism that uses position feedback to control its motion and final position. The input to its control is some signal, either analog or digital, representing the position commanded for the output shaft.



Fig.4.19.Servo Motor

FEATURES:

- Supply voltage: 5VDC
- Control signal: Analog or Digital
- High-precision positioning.

APPLICATIONS:

- Conveyors
- Solar Tracking System
- Antenna Positioning
- Camera Auto Focus
- It is used to measure the speed of the output shaft

4.18.WATER PUMP MOTOR

DESCRIPTION:

The water pump, a container made of aluminum or iron, is part of the cooling system. It contains an impeller (looks like a fan) that circulates water and coolant throughout the cooling system, keeping the engine from overheating.

Jet pumps create suction in a rather novel way. The pump is powered by an electric motor that drives an impeller, or centrifugal pump. The impeller moves water, called drive water, from the well through a narrow orifice, or jet, mounted in the housing in front of the impeller.

As the name implies, water pumps pump water. Whether that be in a vehicle, at a business, in the home, or in a well, shoppers can probably find a water pump to fit their vehicle or to help them draw water from the ground in a self-dug well to be used in pressure tanks within the location.

Vehicle water pumps help regulate the flow of water through a vehicle's cooling system; when the seal on these go bad, the whole pump must be replaced. Located within the home or business, pressure water pumps regulate the water pressure year round, controlling water flow to different areas of the location.

A pump motor is a DC motor device that moves fluids. A DC motor converts direct current electrical power into mechanical power. DC or direct current motor works on the principal, when a current carrying conductor is placed in a magnetic field, it experiences a torque and has a tendency to move. This is known as motoring action. Pumps operate by some mechanism (typically reciprocating or rotary), and consume energy to perform mechanical work by moving the fluid. Pumps operate via many energy sources, including manual operation, electricity, engines, or wind power, come in many sizes, from microscopic for use in medical applications to large industrial pumps.



Fig.4.20.Water Pump Motor

FEATURES:

- Reduced noise
- Available in DC and AC
- Supply voltage: +12VDC
- Supply voltage: 230V AC

APPLICATIONS:

- Priming a pump
- To pump water supply, including pneumatic systems and in places where no suction lift is required
- Pump motor as public water supply
- In domestic water supply system

4.19.SINGLE CHANNEL RELAY**DESCRIPTION:**

A relay is an electrically operated device. It has a control system and (also called input circuit or input contactor) and controlled system (also called output circuit or output contactor). It is frequently used in automatic control circuit.

Relays are switches that open and close circuits electromechanically or electronically. Relays control one electrical circuit by opening and closing contacts in another circuit. When a relay contact is Normally Closed (NC), there is a closed contact when the relay is not energized.

Relays are simple switches which are operated both electrically and mechanically. Relays consist of an electromagnet and also a set of contacts. The switching mechanism is carried out with the help of the electromagnet. The main operation of a relay comes in places where only a low-power signal can be used to control a circuit. It is also used in places where only one signal can be used to control a lot of circuits. They were used to switch the signal coming from one source to another destination. The high end applications of relays require high power to be driven by electric motors and so on. Such relays are called contactors.



Fig.4.21.Single Channel Relay

CIRCUIT DIAGRAM:




Fig.4.22.Single Channel Relay Circuit Diagram

A relay is an electromechanical switch which is activated by an electric current. A single relay board arrangement contains driver circuit, power supply circuit and isolation circuit. A relay is assembled with that circuit. The driver circuit contains transistors for switching operations. The transistor is use for switching the relay. An

isolation circuit prevents reverse voltage from the relay which protects the controller and transistor from damage. The input pulse for switching the transistor is given from the microcontroller unit. It is used for switching of a single device.

FEATURES:

- Input voltage:12VDC
- Driver unit: ULN2003A
- Isolation unit: In4007
- Fast switching

APPLICATIONS:

- AC load Switching applications
- Dc load Switching applications
- Motor switching applications

4.20.BUZZER

DESCRIPTION:

A buzzer or beeper is a signaling device, usually electronic, typically used in automobiles, household appliances such as a microwave oven, or game shows.

A buzzer or beeper is an audio signaling device, which may be mechanical, electromechanical, or piezoelectric. Typical uses of buzzers and beepers include alarm devices, timers and confirmation of user input such as a mouse click or key stroke.

Buzzer is an integrated structure of electronic transducers, DC power supply, widely used in computers, printers, copiers, alarms, electronic toys, automotive electronic equipment, telephones, timers and other electronic products for sound devices. Active buzzer 5V Rated power can be directly connected to a continuous sound, this section dedicated sensor expansion module and the board in combination, can complete a simple circuit design, to "plug and play."



Fig.4.23.Buzzer

CIRCUIT DIAGRAM:




Fig.4.24.Buzzer Circuit Diagram

A buzzer or beeper is an audio signaling device, which may be mechanical, electromechanical, or piezoelectric. Typical uses of buzzers and beepers include alarm devices, timers, and confirmation of user input such as a mouse click or keystroke.

It generates consistent single tone sound just by applying D.C voltage. Using a suitably designed resonant system, this type can be used where large sound volumes are needed. At Future Electronics we stock many of the most common types categorized by Type, Sound Level, Frequency, Rated Voltage, Dimension and Packaging Type.

FEATURES:

- Input supply: 5 VDC
- Current consumption: 9.0 mA max.
- Oscillating frequency: 3.0 $\pm$ 0.5 KHz
- Sound Pressure Level: 85dB min

APPLICATIONS:

- Confirmation of user input (ex: mouse click or keystroke)
- Electronic metronomes
- Sporting events
- Judging Panels
- Annunciator panels

4.21.POWER SUPPLY UNIT**DESCRIPTION:**

A power supply unit (or PSU) converts mains AC to low-voltage regulated DC power for the internal components of a computer. Modern personal computers universally use switched-mode power supplies. Some power supplies have a manual switch for selecting input voltage, while others automatically adapt to the mains voltage.

A power supply is used to reduce the mains electricity at 240 volts AC down to some thing more useable, say 12 volts DC. There are two types of power supply, linear and switch mode. A linear power supply uses a transformer to reduce the voltage. The AC signal is rectified and regulated to produce a high DC voltage.

An AC adapter, AC/DC adapter, or AC/DC converter is a type of external power supply, often enclosed in a case similar to an AC plug. Adapters for battery-powered equipment may be described as chargers or rechargers (see also battery charger). AC adapters are used with electrical devices that require power but do not contain internal components to derive the required voltage and power from main power. The internal circuitry of an external power supply is very similar to the design that would be used for a built-in or internal supply.



Fig.4.25. Power Supply Unit

An adapter is a device that converts attributes of one electrical device or system to those of an otherwise incompatible device or system. Some modify power or signal attributes, while others merely adapt the physical form of one electrical connector to another. In a computer, an adapter is often built into a card that can be inserted into a slot on the computer's motherboard. The card adapts information that is exchanged between the computer's microprocessor and the devices that the card supports.

CIRCUIT DIAGRAM:

An electric power adapter may enable connection of a power plug, sometimes called, used in one region to a AC power socket used in another, by offering connections for the disparate contact arrangements, while not changing the voltage. An AC adapter, also called a "recharger", is a small power supply that changes household electric current (from distribution voltage) to low voltage DC suitable for consumer electronics.

Some modify power or signal attributes, while others merely adapt the physical form of one electrical connector to another. For computers and related items, one kind of serial port adapter enables connections between 25-contact and nine-contact connectors, but does not affect electrical power- and signalling-related




Fig.4.26.Power Supply Circuit Digram

FEATURES:

- Output current:1A
- Supply voltage: 220-230VAC
- Output voltage: 12VDC
- Reduced costs
- Increased value across front-office and back-office functions
- Access to current, accurate, and consistent data
- It generates adapter metadata as WSDL files with J2CA extension.

APPLICATIONS:

- Back-end systems which need to send purchase order data to oracle applications send it to the integration service via a integration server client.
- SMPS applications

4.22.FOOD FEEDER:

Fish are opportunistic and will seek food at all times. Overfeeding is the number one mistake made by fish owners, as uneaten food will pollute the water. In fact, fish can easily go several days without food, and there are few ill effects for slight underfeeding. When free ammonia is being built up (e.g., during the setup of a new tank), it is advised to feed fish no more than once per day to reduce the waste productions. In this, a food feeder is smartly and automatically controlled.

CHAPTER 5

SOFTWARE DESCRIPTION:

5.1.ARDUINO IDE:

The Arduino Integrated Development Environment - or Arduino Software (IDE) - contains a text editor for writing code, a message area, a text console, a toolbar with buttons for common functions and a series of menus. It connects to the Arduino and Genuino hardware to upload programs and communicate with them.

Programs written using Arduino Software (IDE) are called **sketches**. These sketches are written in the text editor and are saved with the file extension .ino. The editor has features for cutting/pasting and for searching/replacing text. The message area gives feedback while saving and exporting and also displays errors. The console displays text output by the Arduino Software (IDE), including complete error messages and other information. The bottom righthand corner of the window displays the configured board and serial port. The toolbar buttons allow you to verify and upload programs, create, open, and save sketches, and open the serial monitor.

Before uploading your sketch, you need to select the correct items from the **Tools > Board** and **Tools > Port** menus. The boards are described below. On the Mac, the serial port is probably something like **/dev/tty.usbmodem241** (for an Uno or Mega2560 or Leonardo) or **/dev/tty.usbserial-1B1** (for a Duemilanove or earlier USB board), or **/dev/tty.USA19QW1b1P1.1** (for a serial board connected with a Keyspan USB-to-Serial adapter). On Windows, it's probably COM1 or COM2 (for a serial board) or COM4, COM5, COM7, or higher (for a USB board) - to find out, you look for USB serial device in the ports section of the Windows Device Manager. On Linux, it should be **/dev/ttyACMx** , **/dev/ttyUSBx** or similar. Once you've selected the correct serial port and board, press the upload button in the toolbar or select the **Upload** item from the **Sketch** menu. Current Arduino boards will reset automatically and begin the upload. With older boards (pre-Diecimila) that lack auto-reset, you'll need to press the reset button on the board just before starting the upload. On most boards, you'll see the RX and TX LEDs blink as the sketch is uploaded. The Arduino Software (IDE) will display a message when the upload is complete, or show an error.

When you upload a sketch, you're using the Arduino **bootloader**, a small program that has been loaded on to the microcontroller on your board. It allows you to upload

code without using any additional hardware. The bootloader is active for a few seconds when the board resets; then it starts whichever sketch was most recently uploaded to the microcontroller. The bootloader will blink the on-board (pin 13) LED when it starts (i.e. when the board resets).

5.2.PROGRAMMING LANGUAGE:

Embedded C is a set of language extensions for the C programming language by the C Standards Committee to address commonality issues that exist between C extensions for different embedded systems.

Embedded C is a set of language extensions for the C programming language by the C Standards Committee to address commonality issues that exist between C extensions for different embedded systems. Historically, embedded C programming requires nonstandard extensions to the C language in order to support exotic features such as fixed-point arithmetic, multiple distinct memory banks, and basic I/O operations

An embedded system is a computer system with a dedicated function within a larger mechanical or electrical system, often with real-time computing constraints. It is embedded as part of a complete device often including hardware and mechanical parts. Embedded systems control many devices in common use today. Ninety-eight percent of all microprocessors are manufactured as components of embedded systems.

Examples of properties of typical embedded computers when compared with general-purpose counterparts are low power consumption, small size, rugged operating ranges, and low per-unit cost. This comes at the price of limited processing resources, which make them significantly more difficult to program and to interact with. However, by building intelligence mechanisms on top of the hardware, taking advantage of possible existing sensors and the existence of a network of embedded units, one can both optimally manage available resources at the unit and network levels as well as provide augmented functions, well beyond those available. For example, intelligent techniques can be designed to manage power consumption of embedded systems.

Modern embedded systems are often based on microcontrollers (i.e. CPU's with integrated memory or peripheral interfaces), but ordinary microprocessors (using

external chips for memory and peripheral interface circuits) are also common, especially in more-complex systems. In either case, the processor(s) used may be types ranging from general purpose to those specialized in certain class of computations, or even custom designed for the application at hand. A common standard class of dedicated processors is the digital signal processor (DSP).

Since the embedded system is dedicated to specific tasks, design engineers can optimize it to reduce the size and cost of the product and increase the reliability and performance. Some embedded systems are mass-produced, benefiting from economies of scale.

Embedded systems range from portable devices such as digital watches and MP3 players, to large stationary installations like traffic lights, factory controllers, and largely complex systems like hybrid vehicles, MRI, and avionics. Complexity varies from low, with a single microcontroller chip, to very high with multiple units, peripherals and networks mounted inside a large chassis or enclosure.

CHAPTER 6

CONCLUSION AND FUTURE WORK

6.1 CONCLUSION

This research offered the tiny aquarium system, which enables the aquarium sensors to operate the actuators in real time and is based on an IoT solution. One of the newest problems in aquaculture is fish monitoring, which has proven crucial to raising output. This project uses existing technologies and a water detection sensor with a unique benefit for monitoring turbidity, PH, and water temperature. The device can automatically check the quality of the water, is inexpensive, and does not need anyone to be on duty. Testing the quality of the water should thus be more affordable, practical, and quick. The method is very adaptable.

REFERENCES:

- [1] A. Dolan, "The effects of aquarium size and temperature on color vibrancy, size, and physical activity in bettasplendens," Maryville College, Maryville, TN, USA, Tech. Rep., 2015.
- [2] S. Sharpe. (2018). Aquarium Nitrogen Cycle: How an Aquarium Cycles. [Online]. Available: <https://www.thesprucepets.com/aquarium-nitrogencycle-1378370>
- [3] C. Dupont, P. Cousin, and S. Dupont, "IoT for aquaculture 4.0 smart and easy-to-deploy real-time water monitoring with IoT," in Proc. Global Internet Things Summit (GloTS), Jun. 2018, pp. 1–5.
- [4] T. I. Salim, T. Haiyunnisa, and H. S. Alam, "Design and implementation of water quality monitoring for eel fish aquaculture an examination of microbubble aeration," in Proc. Int. Symp. Electron. Smart Devices (ISESD), Nov. 2016, pp. 29–30.
- [5] K. M. Stehfest, C. G. Carter, J. D. McAllister, J. D. Ross, and J. M. Semmens, "Response of atlantic salmon salmo salar to temperature and dissolved oxygen extremes established using animal-borne environmental sensors," Nature, vol. 7, no. 1, p. 4545, 2017.
- [6] J.-H. Chen, W.-T. Sung, and G.-Y. Lin, "Automated monitoring system for the fish farm aquaculture environment," in Proc. IEEE Int. Conf. Syst., Man, Cybern., Oct. 2015, pp. 1161–1166.
- [7] C. Encinas, E. Ruiz, J. Cortez, and A. Espinoza, "Design and implementation of a distributed IoT system for the monitoring of water quality in aquaculture," in Proc. Wireless Telecommun. Symp. (WTS), Apr. 2017,
- [8] Y.-B. Lin, Y.-W. Lin, C.-M. Huang, C.-Y. Chih, and P. Lin, "IoTtalk: A management platform for reconfigurable sensor devices," IEEE Internet Things J., vol. 4, no. 5, pp. 1152–1562, Oct. 2017.
- [9] G. Farmer. (2016). CO2: Striking the Balance. Practical Fishkeeping Magazine. [Online]. Available: <https://www.practicalfishkeeping.co.uk/features/articles/co2-striking-the-balance>
- [10] F.-F. Ruth. (2013). Dissolved Oxygen for Fish Production. Texas A&M AgriLife. [Online]. Available: <https://agrilifecdn.tamu.edu/fisheries/files/2013/09/Dissolved-Oxygen-for-Fish-Production1.pdf>
- [11] J. E. Bly and W. L. Clem, "Temperature and teleost immune functions," Fish

- Shellfish Immunol., vol. 2, no. 3, pp. 159–171, 1992.
- [12] T. Masaharu, et. al., “Effect of temperature on survival, growth and malformation of cultured larvae and juveniles of the seven-band grouper *epinephelus septemfasciatus*,” Fisheries Sci., vol. 80, no. 1, pp. 69–81, 2014
- [13] Algone. (2018). The Importance of Oxygen in the Aquarium. General Aquarium & Fish Information. [Online]. Available: <https://www.algone.com/oxygen-in-the-aquarium>
- [14] Jetajockey. (2011). Your Guide to Ammonia Toxicity. Aquarium Advice. [Online]. Available: <http://www.aquariumadvice.com/forums/f12/yourguide-to-ammonia-toxicity-159994.html>
- [15] T. Sarac. (2018). Electrical Conductivity in Freshwater Aquariums. Fluval. [Online]. Available: http://fluvalaquatics.com/ca/explore/did-youknow/equipment/155-electrical-conductivity-monitoring-system-parttwo/#.XAL_hzgZ0x
- [16] Practical Fishkeeping. (2016). What You Need to Know About Reverse Osmosis. [Online]. Available: <https://www.practicalfishkeeping.co.uk/features/articles/what-you-need-to-know-about-reverse-osmosis>
- [17] Y.-B. Lin, et. al., “Easyconnect: A management system for IoT devices and its applications for interactive design and art,” IEEE Internet Things J., vol. 2, no. 6, pp. 551–561, Dec. 2015.
- [18] Y.-W. Lin, Y.-B. Lin, C.-Y. Hsiao, and Y.-Y. Wang, “IoTtalk-RC: Sensors as universal remote control for aftermarket home appliances,” IEEE Internet Things J., vol. 4, no. 4, pp. 1104–1112, Aug. 2017 .
- [19] Y.-B. Lin, H.-C. Tseng, Y.-W. Lin, and L.-J. Chen, “NB-IoTtalk: A service platform for fast development of NB-IoT applications,” IEEE Internet Things J., vol. 6, no. 1, pp. 928–939, Feb. 2019.
- [20] Y.-W. Lin, Y.-B. Lin, M.-T. Yang, and J.-H. Lin, “ArduTalk: An arduino network application development platform based on IoTtalk,” IEEE Syst. J., vol. 13, no. 1, pp. 468–476, Mar. 2019.
- [21] Y.-B. Lin, Y.-J. Shih, H.-C. Tseng, and L.-J. Chen, “LWA rate adaption by enhanced event-triggered reporting,” IEEE Trans. Veh. Technol., vol. 67, no. 11, pp. 10950–10959, Nov. 2018.
- [22] S.-P. Tseng, Y.-R. Li, and M.-C. Wang, “An application of Internet of Things on sustainable aquaculture system,” in Proc. Int. Conf. Orange Technol., Dec.

2016, pp. 17–19.

- [23] K. R. S. R. Raju and G. H. K. Varma, “Knowledge based real time monitoring system for aquaculture using IoT,” in Proc. IEEE 7th Int. Adv. Comput. Conf., Jan. 2017, pp. 318–321.

APPENDIX

CODE IMPLEMENTATION

A.SOURCE CODE:

```
#include <SoftwareSerial.h>
#include <OneWire.h>
#include <DallasTemperature.h>

#define ONE_WIRE_BUS 7
OneWire oneWire(ONE_WIRE_BUS);
DallasTemperature sensors(&oneWire);

int Water;
int Turbidity;
String phdata;
float Celcius = 0;
float temp;

#define rx 5
#define tx 6

String pH;
float PH;
SoftwareSerial NodeSerial(rx, tx); // RX |

void setup() {
  sensors.begin();
  Serial.begin(9600);
  NodeSerial.begin(9600);
  pinMode(A0, INPUT);
  pinMode(A1, INPUT);
}

void loop()
{
  sensors.requestTemperatures();
  Celcius = sensors.getTempCByIndex(0);
  temp = Celcius;
  Water = analogRead(A0);
  Turbidity = analogRead(A1);
  phdata = NodeSerial.readStringUntil('\n');
  String ph = NodeSerial.readStringUntil(' L:');
  PH = phdata.toFloat();
  if (PH > 15)
  {
    PH = 0;
  }
  // Serial.println(phdata);
```


```

Serial.print("pH:");Serial.print(PH);
Serial.print(" Waterlevel:"); Serial.print(Water);
Serial.print(" Temp:");Serial.print(temp);
Serial.print(" Turbidity:");Serial.println(Turbidity);
delay(250);
// }
// if (sensor_value > 208)
// {
//   sensor_value = 208;
// }
// turbidity = map(sensor_value, 0, 208, 300, 0);
// Serial.print("Turbidity:"); Serial.println(sensor_value); Serial.println(turbidity);
}


```

B.APPLICATION SCREEN SHOTS:

SYSTEM SETUP :



TURBIDITY SENSOR:




GOOD WATER




BAD WATER


FOOD FEEDER AND BUZZER




PH SENSOR :




AC CONVERSION :



LED :




SERVO MOTOR :




WATER PUMP MOTOR :




WATER LEVEL SENSOR:



ARDUINO UNO:



MOBILE APPLICATION :



6:21 PM

4G 20

! iotcloud22.in/1317/ε

4



S.no	Temperature	Turbidity	pH	Water Level	Date And Time
1	30	410	0.00	0	2023-04-02 18:23:45
2	30	411	0.00	0	2023-04-02 18:23:43
3	30	411	0.00	0	2023-04-02 18:23:42
4	30	411	0.00	0	2023-04-02 18:23:40
5	30	411	0.00	0	2023-04-02 18:23:39
6	30	411	0.00	0	2023-04-02 18:23:37
7	30	411	0.00	0	2023-04-02 18:23:36
8	30	411	0.00	0	2023-04-02 18:23:34
9	30	411	0.00	0	2023-04-02 18:23:33
10	31	411	0.00	0	2023-04-02 18:23:31
11	31	409	0.00	0	2023-04-02 18:23:28
12	31	409	0.00	0	2023-04-02 18:23:26
13	31	409	0.00	0	2023-04-02 18:23:25
14	31	409	0.00	0	2023-04-02 18:23:23
15	31	410	0.00	0	2023-04-02 18:23:22
16	31	410	0.00	0	2023-04-02 18:23:20
17	31	410	0.00	0	2023-04-02 18:23:11
18	31	410	0.00	0	2023-04-02 18:23:09
19	31	409	0.00	0	2023-04-02 18:23:07
20	31	410	0.00	0	2023-04-02 18:23:05
21	31	410	0.00	0	2023-04-02 18:23:04
22	31	410	0.00	0	2023-04-02 18:23:02

Mini Aquarium system using IoT

Aarthi N
UG Scholar
Department of IT
Sathyabama Institute of Science
and Technology
aarthinagsundaram02@gmail.com

Gowri S
Associate Professor
Department of IT
Sathyabama Institute of Science
and Technology

Esther D
UG Scholar
Department of IT
Sathyabama Institute of Science
and Technology
esthermagline@gmail.com

Abstract – Fish checking framework is fundamental on the grounds that many individuals love to develop fishes as their pet in the home. In our everyday life, it is hard to screen the aquarium tank routinely. As a result, it causes mortality of the fishes. The nature of water may be the central concern. It essentially relies on boundaries like carbon, pH, temperature, turbidity, broke down oxygen, and so forth. To keep up with these boundaries, different sensors are utilized in the fish observing framework. This will build the development of fishes and reduction mortality. Numerous specialists had proposed different strategies for keeping up with the water quality in the aquarium and the fish lakes. The primary reason for this paper is to survey the sensors utilized in the fish observing framework

Keywords – IDE, Arduino, PHP, Turbidity

I. INTRODUCTION

In the new years, downsized aquarium tanks in various shapes and sizes are trading commendable goldfish bowls for little townhouses or school lofts. For example, students in a quarters, where no-pet rules don't have an effect on fish, have space for a tiny aquarium. At Public Chiao Tung School (NCTU), we ask students to watch fish for loosening up and to truly zero in on them in the homes where greater pets are not allowed. Regardless, the aquarium tanks ought to be suitably set up and stayed aware of, or the fish will be bound to repulsive and short life. Specifically, when the water volume in the tank is nearly nothing, key water limits change quickly, precluding botch. Consequently it is fundamental to screen water conditions eagerly and perform water changes dependably for the more modest than typical aquarium tanks. Various business aquarium tanks under one gallon ensure that no help is required. In any case, such things are truly not gainful for fish, and in this way are not recommended. A couple of assessments, show that little aquarium tanks are not sensible for staying aware of strong fish.

The more prominent the tank, the less impact a blunder will have on

fish, and aquarium tanks of something like five gallons are proposed. In this paper, we consider little tanks with sizes greater than 60×45×60 cm³. In light of everything, key water limits of a little aquarium tank should be immovably watched, and genuine exercises should be promptly taken when a couple of perilous conditions are distinguished. Since student dorms are much of the time void during class hours, no one could have the choice to distinguish the uncommon conditions of the tank. In this way, a couple of game plans considering Web of Things (IoT) were proposed to mechanize the revelation of unusual aquarium conditions. Nevertheless, very few of them have given sharp parts to thus sanction the actuators to fix the issues. In NCTU, we have cultivated an IoT game plan called Smaller than usual Aquarium for keen quarters, splendid nursery and other astute grounds applications. In perspective on IoT, this paper proposes the Aquarium system that allows the aquarium sensors to logically drive the actuators

Little Aquarium and the previous courses of action. In thing, Small scale Aquarium uses a greater number of sensors than the past game plans except for. In thing, Little Aquarium obliges a more noteworthy number of actuators than the past plans. Thing 3 shows that plans gave sensor noticing yet no actuator control. Game plans gave manual control of actuators at this point can't normally control the actuators by the sensors. Plan gives immaterial actuator control considering direct sensor edges. Of course, Small scale Aquarium gives both manual control and modified actuator control by the sensors with non-irrelevant information other than direct "edge control". This keen part allows much better control of the water environment. Furthermore, through the time series diagrams of sensors/actuators in Smaller than usual Aquarium feature (to be explained in Fragment V), the fish owner can without a doubt sort out how the water factors

team up with each other. Thusly, the sensors don't just give rough data (as the past game plans do) yet also license the fish owners to learn about their aquarium environmental elements.

II. LITERATURE SURVEY

1. Smart Fish Talk An IOT Based Mini Aquarium

Many individuals feed the pet fish in the aquarium tanks that should be appropriately set up and kept up with, or the fish will be bound to a terrible and short life. Accordingly, it is basic to screen water conditions intently and further develop the water quality for the scaled down aquarium tanks. In view of an IoT arrangement called IoT talk, this paper proposes the Fish Talk framework that uses the aquarium sensors to drive the actuators progressively. We portray the connection between the aquarium sensors and the actuators and give substantial models about the edge setting. Our answer permits the creator to rapidly convey keen control for different water conditions. For instance, we execute a savvy fish taking care of instrument to such an extent that the fish is neither over nor starved, and simultaneously, the fish proprietor can appreciate watching fish taking care of from a distance. We have likewise fostered the insightful model, reproduction, and estimation examinations to explore the impacts of the IoT message deferrals and misfortune on water condition control

2. IOT Based Automatic Aquarium System

It isn't plausible for fish proprietors to leave additional food in their fish's tank prior to leaving for a drawn out period. This makes the requirement for a gadget that can consequently and dependably feed a fish. The reason for this venture is to plan a mechanized fish feeder for family use. The gadget can be created to take care of a solitary goldfish for something like 14 days with next to no extra contribution from the client. We will utilize Hub MCU which is most recent microcontroller and having inbuilt Wi-Fi innovation. Utilizing Hub MCU, we will actually want to control water engine, Food engine, oxygen bubble engine and Drove

3. Arduino Based Fish Monitoring System

Fish checking framework is fundamental on the grounds that many individuals love to develop fishes as their pet in the home. In our day-today life, it is challenging to screen the aquarium tank consistently. As an outcome, it causes

mortality of the fishes. The nature of water may be the central concern. It principally relies on boundaries like carbonates, alkali, nitrates, salt, pH, temperature, turbidity, broke up oxygen, and so on. To keep up with these boundaries, different sensors are utilized in the fish observing framework. This will build the creation of fishes and abatement mortality. Numerous specialists had proposed different strategies for keeping up with the water quality in the aquarium and the fish lakes. The fundamental motivation behind this paper is to audit the sensors utilized in the fish checking framework and the basic correlation of different sensors with other exploration papers.

4. Arduino Based Automated Fish Tank

Fish keeping is well known nowadays, individuals from all age bunch like to keep fish in their home, office and so on in the aquarium tank that should be appropriately set up and kept up with, or the fish will be bound to a terrible and short life. Consequently it is challenging to screen and control water conditions intently and improve the water quality. In light of Arduino the Robotized Fish Tank framework that uses the aquarium sensors to screen and control the water conditions. Proposed arrangement gives fast admittance to use the brilliant framework to control different water boundaries. The framework contains programmed feeder which will guarantee the food is to be taken care of sufficient and at right timespan, Turbidity sensor which is sent close by channel for keeping up with clean water, pH sensor will show pH of water, Temperature sensor and radiator, cooler is utilized to keep up with water temperature and Bubbler will work as a result of disintegrated oxygen sensor to hold oxygen level.

5. Aqua Monitoring System Using AWS

The method for checking and control system has a couple of features, for instance, noticing smelling salts levels and pH, components of modified control of pH, and manual control components of the actuator using cell as IoT. The assessment of pH sensor data has a commonplace mix-up of 1.88%. Testing on the structures has shown its extraordinary execution on noticing and controlling pH and smelling salts of the aquarium as object of the survey. The structure test has a concede in showing data and giving rules from a cell for 10 seconds.

6. Microcontroller Application in Feeding Fish Using Android Mobile

This work is proposed this paper presented a canny checking and controlling system for the tank-farming of Bangladesh. Via completing this structure, the farmer can easing from the aquaculture the chiefs annoys. This assessment finds a superior methodology for sagacious electronic responses for tank-farming with daylight based power. Aquafarmers can screen different aquariums with a simple to utilize mobile phone application. Control and screen from a remote distance make this system more suitable and unique. For research purposes the aquafarmer can hold the data that perceived from the structure. The usage of sun arranged power and Bluetooth correspondence makes the practical cost pretty much nothing. Modernized sensors give more definite data instead of a manual substance test. With this system the aquafarmer will really need to make a more essential number of fish to show up at the market revenue with an ideal proportion of upkeep cost secure

7. IOT based Fish Farm Using Mobile App

This work is proposed the paper portrayed the advancement of an examination community scale exploratory aquarium environment for the natural impression of crabs to add to the improvement of keen tank-farming. The environment can get different biological data, for instance, temperature and tenacity, aquarium water quality, and aquarium video data. As the continuous environment has an irrelevant plan, we will also develop this environment for state of the art tank-farming for crabs

8. Monitoring and Controlling System Koki Gold Fish using Temperature Sensor

The proposed this work is proposed this assessment has won concerning building a noticing and controlling system for koki goldfish aquariums using the DS18B20 sensor, hand-off, hotter, LCD, and different parts joined with Web of Things (IoT) advancement. Considering the exploratory results, the precision of the DS18B20 sensor in recognizing water temperature has a run of the mill botch worth of 3.60%, and that suggests it has a little screw up rate. In a goldfish aquarium with a water volume of 2000 mL from a water temperature of 16°C to 22°C, it requires 17 minutes to make water temperature in the best one, and the temperature at

steady state requires 30 minutes. Modified authorization and deactivation of the radiator works commendably because when the water is under the best temperature, the hotter turns on normally and turns off subsequently when the water is in the best one.

9. Smart Monitoring and Controlling system for Aquaculture

This work is proposed this paper presented a clever checking and controlling structure for the tank-farming of Bangladesh. By executing this structure, the farmer can easing from the aqua-farming the leaders irritates. This investigation finds a superior methodology for wise electronic solutions for tank-farming with sun based power. Aquafarmers can screen various aquariums with a straightforward cell application. Control and screen from a remote distance make this system really convincing and unique. For research purposes the aquafarmer can save the data that perceived from the system. The usage of sun arranged power and Bluetooth correspondence makes the useful cost close to nothing. Modernized sensors give more precise data rather than a manual compound test. With this structure the aquafarmer will really need to convey a more noticeable number of fish to show up at the market revenue with an ideal proportion of upkeep cost

III. PROPOSED WORK

According to the proposed framework in our everyday life, it is challenging to screen the aquarium tank routinely. As a result, it causes mortality of the fishes. The nature of water may be the main pressing concern. It mostly relies on boundaries, for example, carbon, pH, temperature, water level, turbidity, broke down oxygen, and so on. To keep up with these boundaries, different sensors are utilized in the fish checking framework. This will expand the development of fishes and lessening mortality. Numerous scientists had proposed different techniques for keeping up with the water quality in the aquarium and the fish lakes. The primary reason for this paper is to audit the sensors utilized in the fish checking framework.




Fig. System architecture

1. ARDUINO


Arduino is a microcontroller based pack that form's advanced gadgets and items that are intuitive, which can detect and control actual gadgets. These microcontroller sheets produce different arrangements of advanced and simple info/yield (I/O) sticks that can terminal to different augmentation sheets and different circuits. The sheets property sequential transmission terminals, which incorporates All inclusive Sequential Transport (USB) on a portion of the models, to stack programs from our PC. To perform programming the microcontrollers, the Arduino project outfit an incorporated improvement climate (IDE) in light of the programming language which is called Handling, where, C and C++ writing computer programs is upheld.

2. TURBIDITY SENSOR

The turbidity sensor recognizes water quality by estimating the degrees of turbidity. It utilizes light to distinguish suspended particles in water by estimating the light conveyance and dissipating rate, which changes with how much all out suspended solids (TSS) in water. As the TTS expands, the fluid turbidity level increments. Turbidity sensors are utilized to gauge water quality in streams and streams, wastewater and profluent estimations, control instrumentation for settling lakes, silt transport exploration and lab estimations. This sensor gives simple and computerized signal result modes. The limit is flexible when in advanced signal mode. You can choose the mode as per your MCU.

3. BUZZER

A buzzer or beeper is a sound flagging gadget, which might be mechanical, electromechanical, or piezoelectric. Normal purposes of ringers and beepers incorporate caution gadgets, clocks and affirmation of client information, for example, a mouse snap or key stroke. Ringer is a coordinated construction of electronic transducers, DC power supply, generally utilized in PCs, printers, copiers, cautions, electronic toys, auto electronic gear, phones, clocks and other electronic items for sound gadgets. Dynamic ringer 5V Evaluated power can be straightforwardly associated with a consistent sound, this segment devoted sensor extension module and the board in mix, can finish a basic circuit plan, to "fitting and play"



Arduino interface with sensor & buzzer

4. WATER LEVEL SENSOR

Water Level Sensors. Level sensors are utilized to distinguish the degree of substances that can stream. Such substances incorporate fluids, slurries, granular material and powders. Level estimations should be possible inside compartments.

5. PH SENSOR

A pH Meter is a logical instrument that actions the hydrogen-particle movement in water-based arrangements, showing its sharpness or alkalinity communicated as pH. The distinction in electrical potential connects with the causticity or pH of the arrangement.

6. TEMPERATURE SENSOR

A temperature sensor is a gadget, commonly, a thermocouple or RTD, that accommodates temperature estimation through an electrical sign. A thermocouple (T/C) is produced using two disparate metals that produce electrical voltage in direct extent to changes in temperature.

7. LIGHT EMITTING DIODE

A light-radiating diode (Drove) is a two lead semiconductor light source. A p-n intersection diode emanates light when enacted. At the point when a reasonable voltage is applied to

the leads, electrons can recombine with electron openings inside the gadget, delivering energy as photons. This impact is called electroluminescence, and the shade of the light (comparing to the energy of the) not set in stone by the energy band hole of the semiconductor. LEDs are regularly little (under 1 mm²) and incorporated optical parts might be utilized to shape the radiation design.

8. WATER PUMP

Water pumps, as the name suggests, pump water. Clients will probably find a water siphon to accommodate their vehicle or to help them in attracting water starting from the earliest stage self-dug well to be utilized in pressure tanks inside the area, whether that be in a vehicle, at a business, in the home, or in a well.

At the point when the seal on a vehicle water pump fizzles, the whole siphon should be supplanted. This helps control the progression of water through a vehicle's cooling framework. Pressure water siphons, which are typically found inside a structure, control the water pressure all year and the water stream to different areas.

IV. RESULT AND DISCUSSIONS

The model of this framework is utilized to distinguish the Fish in the Aquarium, go to programmed preventive lengths if necessary, recognize the Fish tank temperature, distinguish the Temperature of the water tank and to screen the water level inside the Fish tank as well as how much PH that has been estimated

V. CONCLUSION

This exploration offered the minuscule aquarium framework, which empowers the aquarium sensors to work the actuators progressively and depends on an IoT arrangement. One of the most up to date issues in hydroponics is fish observing, which has demonstrated pivotal to raising result. This task utilizes existing innovations and a water identification sensor with an extraordinary advantage for observing turbidity, PH, and water temperature. The gadget can consequently take a look at the nature of the water, is reasonable, and needn't bother with anybody to be on the job. Testing the nature of the water

ought to accordingly be more reasonable, viable, and speedy. The technique is truly versatile.

REFERENCES

- [1] A. Dolan, "The effects of aquarium size and temperature on color vibrancy, size, and physical activity in bettasplendens," Maryville College, Maryville, TN, USA, Tech. Rep., 2015.
- [2] S. Sharpe. (2018). Aquarium Nitrogen Cycle: How an Aquarium Cycles. [Online]. Available: <https://www.thesprucepets.com/aquarium-nitrogencycle1378370L>.
- [3] C. Dupont, P. Cousin, and S. Dupont, "IoT for aquaculture 4.0 smart and easy-to-deploy real-time water monitoring with IoT," in Proc. Global Internet Things Summit (GIoTS), Jun. 2018, pp. 1–5.
- [4] T. I. Salim, T. Haiyunnisa, and H. S. Alam, "Design and implementation of water quality monitoring for eel fish aquaculture an examination of microbubble aeration," in Proc. Int. Symp. Electron. Smart Devices (ISESD), Nov. 2016, pp. 29–30.
- [5] K. M. Stehfest, C. G. Carter, J. D. McAllister, J. D. Ross, and J. M. Semmens, "Response of atlantic salmon *salmo salar* to temperature and dissolved oxygen extremes established using animal-borne environmental sensors," Nature, vol. 7, no. 1, p. 4545, 2017.
- [6] J.-H. Chen, W.-T. Sung, and G.-Y. Lin, "Automated monitoring system for the fish farm aquaculture environment," in Proc. IEEE Int. Conf. Syst., Man, Cybern., Oct. 2015, pp. 1161–1166.Z.
- [7] C. Encinas, E. Ruiz, J. Cortez, and A. Espinoza, "Design and implementation of a distributed IoT system for the monitoring of water quality in aquaculture," in Proc. Wireless Telecommun. Symp. (WTS), Apr. 2017.
- [8] Y.-B. Lin, Y.-W. Lin, C.-M. Huang, C.-Y. Chih, and P. Lin, "IoTalk: A management platform for reconfigurable sensor devices," IEEE Internet Things J., vol. 4, no. 5, pp. 1152–1562, Oct. 2017.

[9] G. Farmer, (2016). CO2: Striking the Balance. Practical Fishkeeping Magazine. [Online].

Available: <https://www.practicalfishkeeping.co.uk/features/articles/co2-striking-the-balance>

[10] F.-F. Ruth. (2013). Dissolved Oxygen for Fish Production. Texas A&M AgriLife. [Online]. Available:

<https://agrilifecdn.tamu.edu/fisheries/files/2013/09/Dissolved-Oxygen-for-Fish-Production1.pdf>