

CHARACTERIZATION OF DERMOSCOPY IMAGES USING DEEP-LEARNING TECHNIQUE

Submitted in Partial fulfilment of the Requirements for the Award of Bachelor of
Engineering degree in Electronics and Communication

By

S.Nagaraghu (40130201)

Shubhom Das (40130218)



**DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING
SCHOOL OF ELECTRONICS**

SATHYABAMA

**INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)**

CATEGORY -1 UNIVERSITY BY UGC

**Accredited with Grade "A++" by NAAC | 12B Status by UGC | Approved by AICTE
JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI – 600119**

APRIL-2024



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)

Accredited "A++" Grade by NAAC | 12B Status by UGC | Approved by AICTE
www.sathyabama.ac.in

**DEPARTMENT OF ELECTRONICS AND COMMUNICATION
ENGINEERING**

BONAFIDE CERTIFICATE

This is to Certify that this Project Report is the Bonafide work of **S.Nagaraghu** (40130201) , **Shubhom Das**(40130218) Who Carried out the project Entitled "CHARACTERIZATION OF DERMOSCOPY IMAGES USING DEEP-LEARNING TECHNIQUE" under my Supervision from November 2023 to April 2024

Internal Guide

Dr.S.LALITHAKUMARI, M.E., Ph.D.

Head of the Department

Dr.T.RAVI ,M.E., Ph.D.

Submitted for Viva Voce Examination held on 18.4.2024

Internal Examiner

External Examiner

DECLARATION

We S.Nagaraghu (40130201) , Shubhom Das (40130218) Hereby declare that the Project Report entitled "CHARACTERIZATION OF DERMOSCOPY IMAGES USING DEEP-LEARNING TECHNIQUE" done by us under the guidance of Dr.S.Lalithakumari, M.E., Ph.D., Department of Electronics and communication Engineering, at Sathyabama Institute of Science and Technology, Chennai is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in Electronics and Communication Engineering

DATE: 18-4-2024

PLACE: CHENNAI

SIGNATURE OF THE CANDIDATES

1. S. Nagaraghu

2. Shubhom Das

ACKNOWLEDGEMENT

I am pleased to acknowledge my sincere thanks to The Board of Management of **Sathyabama Institute of Science and Technology** for their encouragement in doing this project and for completing it successfully. We are grateful to them.

I convey our thanks to **Dr. N. M. NANDHITHA, M.E., Ph.D., Professor & Dean, School of Electrical and Electronics** and **Dr.T.RAVI, M.E., Ph.D., Professor & Head of the Department of Electronics and Communication Engineering** for providing us necessary support during the progressive reviews.

I would like to express our sincere and deep sense of gratitude to our Project Guide **Dr.S.LALITHAKUMARI, M.E., Ph.D., Department of Electronics and communication Engineering**, for her valuable guidance, suggestions and constant encouragement paved way for the successful completion of our project work.

I wish to express our thanks to all Teaching and Non-teaching staff members of the Department of Electronics and Communication Engineering who were helpful in many ways for the completion of the project.

ABSTRACT

This project aims to design and develop an automated tool for identification and classification of various skin diseases' the proposed novel algorithm which is basically in CNN which aids to differentiate various skin diseases through a full - fledged skin image dataset. In addition, it explores the role of artificial intelligence (AI), especially convolutional neural networks (CNNs), in the analysis of dermatological images and considers possible implications for the evaluating of skin lesions. By gaining a deeper understanding of skin lesion and incorporating AI technologies, healthcare providers can improve diagnostic accuracy, improve treatment strategies. The HAM10000 dataset is a comprehensive collection of multi-source dermatoscopic pictures of common pigmented skin lesions. This use of MobileNetV2's capabilities to characterize these images. The dataset offers a strong basis for deep learning model training because it covers a wide variety of skin conditions. In order to detect and categorize different kinds of skin illnesses, the characterization procedure entails a careful inspection of skin lesion photographs from which 6 common skin lesions are taken which is a total of 3310 raw dataset for training containing (AKIEC)-327 Actinic keratosis ,(BCC)-514 Basal cell carcinoma, (BKL)-1099 Seborrheic keratosis ,(DF)-115 Dermatofibroma ,(MEL)-1113 Melanoma and (VASE)-142 vascular lesions a total of 3310 images In order to get the early identification of skin cancer, we hope to achieve a high degree of accuracy in differentiating between benign and malignant lesions by utilizing MobileNetV2. A crucial reference point for this work is the HAM10000 dataset, which provides a typical sample of pigmented lesions. Pictures of melanoma, basal cell carcinoma, and other skin disorders.

TABLE OF CONTENTS

CHAPTER NO	TITLE	PAGE NO
	ABSTRACT	v
	LIST OF FIGURES	viii
	LIST OF TABLES	ix
	LIST OF ABBREVIATIONS	ix
1	INTRODUCTION	1
2	LITERATURE SURVEY	3
3	AIM AND SCOPE OF THE PRESENT INVESTIGATION	8
	3.1 AIM	8
	3.2 SCOPE	9
	3.3 OBJECTIVES	10
	3.4 STANDARDS	11
	3.5 CONSTRAINTS	12
	3.6 TRADEOFFS	13
4	MATERIALS METHOD AND ALGORITHM USED	15
	4.1 DATASETS	15
	4.2 MATLAB R2022b	24
	4.3 MobileNetV2	25
	4.4SYSTEM HARDWARE USED FOR TRAINING	26

5	RESULT AND DISCUSSION, PERFORMANCE ANALYSIS	28
	5.1 OUTPUTS	28
	5.2 PERFORMANCE ANALYSIS	33
6	SUMMARY AND CONCLUSION	38
	6.1 SUMMARY	38
	6.2 CONCLUSION	39
7	REFERENCE	40

LIST OF FIGURES

FIGURE NO	FIGURE NAME	PAGE NO
4.1	SEBORRHEIC KERATOSIS	16
4.2	DERMATOFIBROMA	17
4.3	ACTINIC KERATOSIS	18
4.4	VASCULAR LESIONS	19
4.5	BASAL CELL CARCINOMA	20
4.6	MELANOMA	21
4.7	MATLAB	24
4.8	MOBILENET V2 ARCHITECTURE	26
5.1	RAW IMAGES	28
5.2	ENHANCED IMAGES	29
5.3	GRAYSCALE,GROUNDTRUTH IMAGES	30
5.4	SEGMENTED IMAGES	32
5.5	NETWORK ANALYZER	33
5.6	LAYERS OF MOBILENET V2	34
5.7	CONFUSION MATRIX	35
5.8	ROC CLASSIFICATION	37

LIST OF TABLES

TABLE NO	TABLE NAME	PAGE NO
4.1	DATA SET TABLE	23

LIST OF ABBREVIATIONS

SERIAL NO	ABBREVIATION	EXPANDED FORM
1	BKL	SEBORRHEIC KERATOSIS
2	DF	DERMATOFIBROMA
3	AKIEC	ACTINIC KERATOSIS
4	VASE	VASCULAR LESIONS
5	BCC	BASAL CELL CARCINOMA
6	MEL	MELANOMA
7	CNN	CONVOLUTION NEURAL NETWORK
8	HAM10000	HUMAN AGAINST MACHINE 10000
9	ROC	RECEIVER OPERATING CHARACTERISTIC

CHAPTER-1

INTRODUCTION

The abundance of data within the HAM10000 dataset presents a treasure trove for dermatologists and researchers alike. With a vast collection of labeled images capturing diverse skin diseases, it serves as an invaluable resource for comprehensive analyses. These images, ranging from cancerous to non-cancerous lesions, provide a deep insight into various dermatological conditions, making them a sought-after asset in medical research.

In the dataset, one encounters a spectrum of malignant lesions with significant implications. Melanoma, recognized for its aggressive nature stemming from melanocytes, stands out as a formidable challenge due to its rapid metastatic potential. Basal Cell Carcinoma, a prevalent form of skin cancer often associated with sun exposure, and Squamous Cell Carcinoma, known for its susceptibility to metastasize, are also prominently featured. Moreover, the dataset encompasses lesser-known malignancies like Merkel cell carcinoma and sebaceous carcinoma, adding layers of complexity to the study of skin lesions.

Conversely, the non-malignant lesions in the dataset offer insight into a different realm of skin conditions. From benign Melanocytic Nevi or Moles to precancerous Actinic Keratosis triggered by UV exposure, the dataset covers a broad spectrum of skin abnormalities. Benign Keratosis, comprising seborrheic keratosis, solar lentigo, and lichen-planus-like keratosis, along with Dermatofibroma and vascular lesions like haemangiomas and angiokeratomas, add depth to the range of benign lesions under scrutiny.

Recognizing the critical role of early detection in managing skin lesions, especially the malignant and pre-cancerous types, underscores the significance of timely identification in improving treatment outcomes and prognosis. The pivotal nature of swift detection is reflected in reduced

morbidity, mortality rates, and overall healthcare expenses, emphasizing the importance of vigilance in dermatological assessments.

Furthermore, leveraging cutting-edge deep learning methodologies such as Convolutional Neural Networks (CNNs) for image classification and segmentation, UNet architecture for precise boundary localization, DenseNet for distinguishing between benign and malignant lesions, and Transfer Learning for customizing pre-trained models to specific lesion types, marks a paradigm shift in lesion identification and diagnosis. These advanced techniques empower healthcare professionals with sophisticated tools, promising enhanced patient care and refined prognosis capabilities in the realm of dermatology.

The project delves into the practical applications of Convolutional Neural Networks (CNNs) when it comes to identifying and categorizing various skin conditions, with a particular focus on improving upon the limitations commonly associated with traditional diagnostic methods. In the endeavor to stress the urgent need for prompt and accurate detection of skin ailments, the study accentuates the considerable potential of CNN-driven systems in elevating the precision of diagnoses. Covering an extensive array of methodologies, the investigation spans across different approaches from MATLAB-centric techniques to the integration of CNNs for the purpose of categorizing skin diseases, providing a comprehensive overview of the continually developing field of dermatology. By presenting an innovative methodology, the project lays out a well-structured process for implementing CNNs—specifically emphasizing the use of MobileNetV2—in the sphere of skin cancer detection, encompassing key stages like data collection, preprocessing, model selection, transfer learning, training, and evaluation. The concluding remarks of the research strongly advocate for the integration of advanced technologies into dermatological practices to refine diagnostic precision and enhance patient outcomes, underscoring the potential positive impact such technological integration can bring to the overall quality of medical care within this specialized medical domain.

CHAPTER-2

LITERATURE SURVEY

Few Cited literatures are available for automatic identification of skin lesions. A detailed literature survey is given below based on the published works.

PAPER 1

ZHE WU et al (2019): This paper addresses the significant global burden of skin diseases, which rank among the most common health issues worldwide. Skin conditions not only impact physical health but also have far-reaching consequences on mental well-being and overall quality of life, particularly when they affect the face. The authors highlight the dearth of labelled datasets, especially for facial skin diseases, making research and clinical diagnosis challenging in this context.

To mitigate these issues, the paper introduces a novel dataset consisting of 6 common facial skin diseases: seborrheic keratosis (SK), actinic keratosis (AK), rosacea (ROS), lupus erythematosus (LE), basal cell carcinoma (BCC), and squamous cell carcinoma (SCC). This dataset contains a substantial collection of 2,656 facial images, totalling 4,394 images. These diseases were selected due to their high prevalence on the face and the potential for benign conditions like AK and SK to transition into malignant ones without timely intervention.

The paper's primary objective is to assess the effectiveness of various convolutional neural network (CNN) structures in diagnosing these facial skin diseases using clinical images. Five different CNN architectures were examined, and the InceptionResNet-v2 model demonstrated the highest average precision (77.0%) in the test set, showcasing promising results in automated diagnosis.

By constructing this specialized dataset and evaluating CNN models, the paper offers a significant contribution to the field of dermatology and medical image processing. It not only addresses the lack of data in this

domain but also provides a foundation for the development of AI-based diagnostic tools for facial skin diseases. These tools could enhance early detection, improve patient outcomes, and reduce the burden of skin diseases on individuals and healthcare systems.

PAPER 2

Weipeng Li et al (2020): addresses the pressing issue of skin cancer, notably melanoma, which is a highly lethal form of skin cancer responsible for a significant number of cancer related deaths. While early detection is vital for improving patient survival rates, visual inspection by experts currently yields an accuracy of only around 60%. To enhance accuracy and aid clinicians in diagnosing skin cancers more effectively, the paper explores the application of Artificial Intelligence (AI) techniques, particularly deep learning, which has shown remarkable success in various domains.

Deep learning, specifically convolutional neural networks (CNNs), has excelled in image classification tasks, including medical image diagnosis. However, the challenge arises when dealing with small-sample or data-imbalanced datasets, common in the medical domain. The paper introduces strategies to address this issue. First, it discusses transfer learning, where pre-trained deep learning models from larger datasets are fine-tuned for specific tasks with limited data. Another approach involves adjusting loss function penalties for small-sample classes to encourage the classifier to pay more attention to these classes during training.

However, the paper introduces a novel and more effective approach by utilizing metadata, such as information about the location of skin lesions. It recognizes that different skin diseases often manifest in distinct body parts, making non-image metadata an asset in distinguishing between diseases. While multi-modality medical image classification tasks have been explored previously, there has been limited work on fusing image

and non-image metadata for medical image classification. In this study, the paper presents a data-fusion framework tailored to the data-imbalance issue in skin image classification. Experiments demonstrate that incorporating metadata significantly improves the recall rate for skin diseases, particularly when dealing with limited training data.

In summary, this paper addresses the critical need for accurate skin cancer diagnosis, specifically melanoma. It explores the potential of AI, deep learning, and data-fusion techniques, with a focus on utilizing non-image metadata to enhance the classification of skin diseases. The results indicate that this innovative approach can be highly effective, especially in scenarios with limited data availability, promising improved early detection, and diagnosis of skin cancers.

PAPER 3

Yang Guang et al (2023) :explains the critical issue of accurately diagnosing and classifying skin cancers, with a particular focus on melanoma, which is the most dangerous form of skin cancer. Skin cancer is a widespread health concern, with millions of new cases diagnosed annually in the USA and even higher per capita rates in countries like Australia. Early detection is essential for improving survival rates, as late-stage diagnosis leads to poor outcomes.

Traditionally, dermatologists have used high-resolution dermoscopy images to aid in diagnosing skin cancers. However, the reliability of these diagnoses can vary depending on the clinician's experience, leading to the need for more accurate classification methods.

The paper highlights the significant challenges in accurately classifying skin cancer types, especially malignant ones, due to their visual similarity. To address this, the paper discusses the development of deep learning techniques in recent years to enhance diagnostic accuracy and classification. Previous research demonstrated that deep learning models

surpassed dermatologists in accuracy and sensitivity for skin cancer classification.

Building upon this foundation, the paper introduces a novel transformer network structure designed specifically for skin cancer classification. This model aims to improve upon existing deep learning approaches by better targeting disease areas in dermoscopy images while reducing interference from healthy regions and noise. Comparative experiments with state-of-the-art non-transformer models on the same dataset revealed that the proposed transformer model achieved superior accuracy and sensitivity. This suggests that the transformer architecture is more suitable for skin lesion classification, particularly for challenging cases like melanoma.

In summary, the paper addresses the pressing need for accurate skin cancer diagnosis, emphasizing the significance of early detection in improving patient outcomes. It explores the potential of deep learning techniques, specifically introducing a novel transformer network structure, to enhance the accuracy of skin cancer classification. The experimental results indicate that this transformer model outperforms existing models, offering promising prospects for more accurate and reliable skin cancer diagnoses in the future.

PAPER 4

Nazia Hameed et al (2018) :addresses the significant global health issue of skin diseases, which rank as the fourth leading cause of non-fatal disease burden. Skin diseases can result from various factors, including exposure to ultraviolet radiation, genetic predisposition, environmental influences, and lifestyle choices. These conditions can have a profound impact on physical and mental wellbeing, leading to isolation, physical impairment, relationship difficulties, unemployment, and even increased rates of suicidal attempts.

Classifying skin diseases typically requires specialized expertise, equipment, and domain knowledge, creating a mismatch between the burden of skin diseases and available resources, particularly in low-income countries. To address this gap, the paper proposes the development of an intelligent expert system capable of performing multi-class skin lesion classification to aid in early diagnosis.

The research focuses on classifying acne, eczema, and melanoma (both benign and malignant), which are among the most common skin diseases worldwide. In a previous study, the authors investigated skin lesion classification using traditional machine learning approaches, which involved manual feature extraction. In this research, they employ convolutional neural networks (CNNs), a subfield of deep learning, to improve classification accuracy. Specifically, they utilize a pre-trained CNN model called "AlexNET" for feature extraction and employ a linear error correcting output codes (ECOC) support vector machine (SVM) classifier for the classification task. The ECOC classifier simplifies the multi-class classification problem by breaking it down into binary classification tasks.

The proposed intelligent expert system can effectively classify healthy skin, acne, eczema, as well as benign and malignant skin lesions. By leveraging deep learning and SVM techniques, this system offers the potential to enhance the accuracy and accessibility of skin disease diagnosis, particularly in regions with limited healthcare resources.

CHAPTER-3

AIM AND SCOPE OF THE PRESENT INVESTIGATION

3.1 AIM

The primary objective of the project implementation using MobileNetV2 to analyse dermoscopy images is to effectively utilize the capabilities of this convolutional neural network design, specifically tailored for the classification of skin lesions.

The process commences with the creation of a comprehensive dataset that involves capturing dermoscopic images through a hand-held dermoscope attached to a mobile phone. It is vital to ensure a diverse representation of lesion types, including melanocytic nevi and basal cell carcinoma, to enhance the model's ability to generalize across different categories.

Moving on to the model development phase, the project focuses on leveraging the MobileNetV2 architecture known for striking the right balance between accuracy and efficiency. The model is initialized with pre-trained weights from the ImageNet dataset and further fine-tuned using the specific dermoscopy image dataset curated for this study.

The subsequent stage involves training MobileNetV2 to categorize skin lesions into distinct classes such as melanoma and dermatofibroma, aiming for robust classification outcomes. The model's performance is rigorously evaluated using various metrics like accuracy, sensitivity, and specificity to gauge its effectiveness in real-world scenarios.

In terms of clinical application, the goal is to deploy the trained model as a sophisticated tool for early diagnosis of skin diseases, aiding dermatologists by providing valuable insights derived from dermoscopic images. The accurate classification achieved through this novel approach significantly contributes to improved patient care and serves as a supportive tool for dermatologists in their diagnostic decision-making processes, ultimately enhancing overall healthcare outcomes and patient well-being.

3.2 SCOPE

The scope of characterizing dermoscopy images using the deep-learning technique MobileNetV2 encompasses a variety of significant aspects that contribute to the advancement of dermatological diagnosis and care:

1. Early Diagnosis of Skin Diseases:

Utilizing MobileNetV2's advanced capabilities to accurately categorize dermoscopy images into distinct skin lesion categories such as melanoma, basal cell carcinoma, and others, thereby facilitating the prompt identification of skin diseases.

Offering a convenient and efficient automated tool that empowers dermatologists to swiftly detect and address skin conditions in their nascent stages, fostering proactive treatment and management.

2. Second Opinion Tool:

Enabling MobileNetV2 to serve as a reliable second opinion resource for dermatologists, bolstering the accuracy of diagnostic processes based on the analysis of dermoscopic images.

Increasing diagnostic efficiency and cost-effectiveness through the provision of additional insights and perspectives that enhance the overall diagnostic accuracy and reliability.

3. Model Evaluation and Optimization:

Conducting comprehensive evaluations of MobileNetV2's performance by comparing it against various pre-trained CNN models like DenseNet121, ResNet50, VGG16, and ResNet18, to ascertain its effectiveness and suitability.

Fine-tuning simulation parameters such as epochs, batch size, and optimizers to establish the optimal configuration that maximizes the model's diagnostic capabilities and overall performance.

4. Clinical Application:

Implementing the trained MobileNetV2 model within clinical environments to streamline and enhance the characterization of skin lesions, ultimately resulting in elevated standards of patient care and treatment outcomes.

3.3 OBJECTIVES

The primary Objective of utilizing the deep-learning technique MobileNetV2 to characterize dermoscopy images is to enhance the accuracy and efficiency of skin lesion classification. In this study, the key aspirations involve the development of a sophisticated deep learning model, specifically utilizing MobileNetV2, with the objective of effectively categorizing dermoscopic images into distinct types of lesions such as melanoma, basal cell carcinoma, and more. An essential focus lies in advancing diagnostic precision by streamlining the characterization process through automation.

Moreover, the strategy encompasses the meticulous training and fine-tuning of the MobileNetV2 model. This involves a meticulous initialization procedure where the model is set up with pre-trained weights obtained from the ImageNet dataset. Fine-tuning is then carried out meticulously using a dataset comprising of dermoscopic images. To further refine the model's performance, an array of data augmentation techniques is employed strategically.

Significantly, upon successful training and fine-tuning, the primary objective transitions to the clinical application of the MobileNetV2 model. This pivotal step involves deploying the expertly trained model within authentic clinical environments. Its primary function revolves around assisting dermatologists in making well-informed decisions regarding skin lesion treatments and overall management strategies. By accomplishing these multifaceted objectives cohesively, this profound project significantly contributes to advancing patient care standards and providing invaluable support to healthcare professionals in the realm of skin disease diagnosis.

3.4 STANDARDS

IEEE P2801™ - Recommended Practice for the Quality Management of Datasets for Medical Artificial Intelligence : This recommended practice identifies best practices for establishing a quality management system for datasets used for artificial intelligence medical devices. It covers a full cycle of dataset management, including items such as but not limited to data collection, transfer, utilization, storage, maintenance and update. This recommended practice recommends a list of critical factors that impact the quality of datasets, such as but not limited to data sources, data quality, annotation, privacy protection, personnel qualification/training/evaluation, tools, equipment, environment, process control and documentation.

IEEE P2807™ - Framework of Knowledge Graphs: This standard defines the framework of knowledge graphs (KGs). The framework describes the input requirement of KG, construction process of KG, i.e., extraction, storage, fusion and understanding, performance metrics, applications of KG, verticals, KG related artificial intelligence (AI) technologies and other required digital infrastructure.

IEEE P2807.1™ - Standard for Technical Requirements and Evaluation of Knowledge Graphs: This standard defines technical requirements, performance metrics, evaluation criteria and test cases for knowledge graphs. The mandatory test cases include data input, metadata, data extraction, data fusion, data storage and retrieval, inference and analysis, and knowledge graph display.

IEEE P2841™ - Framework and Process for Deep Learning Evaluation: This document defines best practices for developing and implementing deep learning algorithms and defines a framework and criteria for evaluating algorithm reliability and quality of the resulting software systems.

IEEE P2807.4™ - Standard for Technical Requirements and Evaluation of Knowledge Graphs: This guideline for Scientific Knowledge Graphs (SKG) specifies: 1) Data scope, including the actors such as authors or organizations, the documents such as journal or conference publications, and the research knowledge such as research topics or technologies; 2) SKG construction process, including knowledge acquisition, knowledge fusion, knowledge representation, or knowledge inference of scientific knowledge; 3) Applications, including academic service, intelligence mining, or scholar analysis.

3.5 CONSTRAINTS

Model size: In convolutional neural networks (CNNs), the term "model size" typically refers to the number of parameters or weights in the network. Model size is a crucial factor in deep learning, as it directly affects the memory requirements during training and inference, as well as the computational resources needed for both.

Input image size: The input image size plays a crucial role in the processing of data within a neural network. It is defined by the dimensions of the image, usually denoted as width, height, and the number of channels it encompasses. These specific dimensions dictate the manner in which the image data is ingested into the network architecture, effectively governing the execution of convolutional and pooling operations that aid in the extraction of meaningful features from the image. Understanding and setting the input image size correctly is fundamental in optimizing the network's performance and facilitating accurate image analysis.

Task Objective: When setting the task objective, it is crucial to establish a clear and concise goal. This could involve defining whether the task entails classification, detection, segmentation, regression, or any other specific objective. Additionally, it is essential to specify the output format needed for the task, which may include various elements such as class labels, bounding boxes, or pixel-wise masks. Defining these key aspects from the outset contributes to a focused and successful outcome.

Computational Resources: When addressing computational resources, it is vital to carefully evaluate various factors, including memory limitations, processing power capabilities, and the crucial consideration of latency requirements. This assessment becomes particularly crucial when contemplating deployment scenarios involving resource-constrained devices or when operating within the realm of real-time applications where swift and efficient processing is paramount for optimal functionality.

Model Size and Complexity: When considering model size and complexity, it is crucial to strike a delicate balance that is in line with the resources at your disposal and the desired performance outcomes. Opt for a network architecture and depth that are well-suited to efficiently extracting the inherent data patterns without succumbing to overfitting. By carefully selecting the appropriate level of intricacy and structure for your model, you pave the way for achieving optimal results that align with your computational capabilities and objectives.

Performance Metrics: When considering performance metrics for model evaluation, it is crucial to define appropriate measures that align with the specific task at hand. Common metrics include accuracy, precision, and recall, among others. These metrics play a vital role in gauging the effectiveness and performance of the model in accomplishing its intended objectives. Carefully selecting and analyzing these metrics can provide valuable insights into the model's capabilities and areas for improvement.

3.6 TRADEOFFS

Accuracy and Reliability: The CNN algorithm, although advanced, may encounter challenges in consistently identifying various types of skin lesions accurately. This limitation may give rise to errors or misinterpretations, potentially presenting false positives or false negatives. Such outcomes can lead to incorrect feedback being provided, ultimately affecting user trust and confidence in the reliability of the algorithm's diagnostic results.

Processing power and speed: Performing real-time classification of skin lesions demands a high level of computational power, a necessity that can result in delays in the generation of the output due to issues with latency. In order to ensure accurate and timely results, the system must efficiently handle the processing demands for rapid and effective identification of skin lesions.

Training and validation time: Training and validating deep-learning algorithms can be a time-consuming process, especially when working with extensive datasets that involve numerous classes. The complexity of these models and the need for thorough evaluation contribute significantly to the overall time required for training and validation.

CHAPTER-4

MATERIALS METHOD AND ALGORITHM USED

4.1 DATASETS

The HAM10000 dataset, comprising approximately 10,000 skin lesion images aimed at aiding in skin cancer detection, plays a crucial role as a standard reference for evaluating the performance of machine learning algorithms while enabling comparisons with the diagnostic capabilities of medical professionals. Within this dataset, one finds dermatoscopic images capturing various common pigmented skin lesions. Procured from diverse populations and employing a range of imaging modalities for capture and storage, the dataset is enriched with a comprehensive collection of pivotal diagnostic categories associated with pigmented lesions.

Significantly, most of the lesions have been histopathologically diagnosed, underscoring the dataset's reliability. For those lacking histopathological confirmation, diagnostic authenticity is maintained through meticulous follow-up examinations, expert consensus, or non-invasive imaging techniques such as in-vivo confocal microscopy. This meticulous curation ensures a robust and validated dataset that can serve as a foundation for developing and refining skin cancer detection models.

Delving into the dataset's structure, each image is encapsulated within a tensor, with separate tensors allocated for gender representation, lesion categorization, image sourcing details, lesion localizations, individual ages, and unique lesion and image IDs. This multi-faceted structuring allows for detailed analysis and categorization of the data, facilitating a nuanced understanding of the relationships between various attributes within the dataset.

Overall, the HAM10000 dataset emerges as a goldmine of information and a pivotal resource in the realm of dermatology and machine learning, offering a rich repository of meticulously curated data that holds immense potential for

advancing the field of skin cancer detection through cutting-edge research and algorithmic innovations.

From the HAM10000 dataset we have selected 6 common skin lesions and categorized them in non-cancerous, pre-cancerous and cancerous.

4.1.1 non-cancerous lesion

A benign skin lesion, also known as a non-cancerous skin growth, is a common occurrence that typically poses no serious health risks. These growths, while harmless, may prompt treatment if they cause discomfort or if aesthetic concerns arise due to their presence on the skin.

4.1.1.1 (BKL)



Fig 4.1. Seborrheic keratosis

A seborrheic keratosis (BKL) is a prevalent harmless skin growth that resembles a mole, commonly occurring in individuals during mid-adulthood and becoming more frequent as one ages. While usually not needing treatment, some individuals choose to have them removed for cosmetic reasons. One notable characteristic of seborrheic keratoses is they often have a rounded or oval shape with a distinctive "stuck on" appearance and a texture that can be waxy or scaly, protruding above the skin's surface. These growths typically come in shades of brown, black, or tan, although they can occasionally manifest in pink, yellow, or white hues and may appear in groupings or clusters on the skin.

Regarding those who are more likely to develop seborrheic keratoses, they are commonly observed in people over the age of 50, with a genetic component where individuals with a family history of the condition are at a higher risk, particularly in cases where multiple family members have seborrheic keratoses. Lighter-skinned individuals are also more prone to experiencing these skin growths compared to those with darker skin tones. In summary, seborrheic keratoses are typically harmless skin growths that are more prevalent in older individuals and can exhibit various colours and presentations on the skin, often associated with genetic predispositions and skin tone variations.

4.1.1.2 (DF)



Fig 4.2. dermatofibroma

A dermatofibroma (DF), a commonly occurring benign fibrous nodule, typically emerges on the skin of the lower legs. Referred to as a cutaneous fibrous histiocytoma, this condition generally manifests as a solitary, noticeably solid papule, or nodule. Let's delve into some essential details regarding dermatofibromas:

In terms of appearance, these lesions are characterized by their firm, slow-growing papules, which often present as rounded bumps. They can exhibit a range of colours, commonly appearing brownish to tan, and are frequently elevated or pedunculated. Notably, a distinct feature known as the dimple sign can be observed, where applying lateral pressure results in a central depression.

Regarding size, dermatofibromas typically have a diameter that falls within the range of 0.5–1.5 cm, with most lesions measuring around 7–10 mm in

diameter. These nodules tend to occur more frequently on the legs, although they can manifest anywhere on the skin.

In terms of symptoms, dermatofibromas are generally painless, but individuals may experience discomfort, tenderness, or itching in some cases. When it comes to complications, trauma can occur due to the raised nature of these nodules, for instance during activities like shaving. It is also important to note that individuals with compromised immunity may develop multiple dermatofibromas. While dermatofibromas are usually not cancerous, they can occasionally be mistaken for other skin conditions.

4.1.2 pre-cancerous lesion

A precancerous lesion, which is a cluster of abnormal cells displaying alterations in size, shape, or structure when contrasted with healthy cells, carries a heightened potential for evolving into cancer. Even though not every precancerous lesion advance to a cancerous state, the importance of vigilantly monitoring these irregular cell formations and intervening promptly cannot be emphasized enough because detecting any malignant transformation early on significantly increases the chances of successful treatment and improves patient outcomes. Early detection and appropriate medical action play a pivotal role in managing and preventing the progression of precancerous conditions, underlining the significance of proactive medical care and regular screenings in safeguarding one's health.

4.1.2.1 (AKIEC)




Fig 4.3. Actinic keratosis

An Actinic keratosis (AKIEC), also known as solar keratosis or senile keratosis, is a pre-cancerous area of thick, scaly, or crusty skin induced by ultraviolet (UV) light exposure. These lesions typically present as thickened, rough patches that can vary in colour from dark to light, tan, pink, or red, often likened to sandpaper in texture. Actinic keratosis lesions commonly range in size between 2 and 6 millimetres and are frequently found on the face, ears, neck, scalp, chest, backs of hands, forearms, or lips of individuals with fair skin over the age of 40 with a history of regular sun exposure. Risk factors for developing actinic keratosis include a weakened immune system, making it crucial for individuals to limit their sun exposure, particularly during peak hours between 10 a.m. and 2 p.m., and use protective measures such as sunscreen and clothing. If left untreated, actinic keratosis lesions bear the serious risk of progressing to squamous cell carcinoma, a type of skin cancer, highlighting the importance of early detection and prompt treatment by a dermatologist to prevent such complications from arising.

4.1.3 Cancerous lesion

A cancerous lesion, also known as a malignant tissue growth, signifies an abnormal development of cells with the dangerous potential to transform into cancerous tumours if not addressed promptly. These lesions are characterized by their ability to metastasize, spreading mischief to surrounding tissues and organs once they surpass their initial location. The dangerous progression begins when cells start dividing uncontrollably, evoking a looming threat to life if medical intervention is not sought to halt their unchecked advancement.

4.1.3.1 (VASE)



Fig 4.4. Vascular lesion

Vascular lesions (VASE), characterized as abnormal growths or malformations within the intricate network of blood vessels, can manifest in diverse regions of the body, emerging either as congenital anomalies existing from birth or as acquired conditions. These lesions encompass a spectrum of types, among which are vascular tumors and malformations. Vascular tumors consist of distinctive entities, such as the Infantile Hemangioma, a typically benign tumor that typically manifests in the early postnatal period, often showing a trend towards spontaneous regression as time progresses. Another notable tumor is the Pyogenic Granuloma, identified by its rapid growth as a reddish nodule, commonly associated with minor traumas. On the other hand, vascular malformations present another category of lesions, including Capillary Malformations, recognized as "port-wine stains," flat, pink, or red birthmarks attributable to dilated capillaries. Venous malformations are characterized by abnormal veins that can lead to symptoms like swelling and pain. Additionally, Arteriovenous Malformations, marked by abnormal connections between arteries and veins, and Lymphatic Malformations, denoting abnormalities within the lymphatic vessels, constitute other distinctive types. The variable nature of vascular lesions necessitates careful evaluation and possible medical intervention depending on the severity and associated symptoms.

4.1.3.2 (BCC)




Fig 4.5. Basal cell carcinoma

Basal cell carcinoma (BCC) is the most common type of skin cancer, originating in the basal cells responsible for renewing skin cells. This form of cancer typically presents as a painless raised area on the skin, sometimes shiny with visible blood vessels or with ulceration. The appearance of BCC differs based on skin tone, appearing as a skin-coloured or pink bump on white skin, and as brown or glossy black with a rolled border on brown and Black skin. Major risk factors for BCC include UV exposure, particularly in childhood, as well as lighter skin tone, radiation therapy, and arsenic exposure. Diagnosis is confirmed through skin examination and tissue biopsy.

Treatment for BCC usually involves surgical removal, such as simple excision or Mohs surgery, though other options like electrodesiccation and curettage, cryosurgery, and topical chemotherapy may be considered. Prognosis for basal cell carcinoma is generally favourable, with a low likelihood of spreading to distant areas or causing death. It is important to monitor your skin for any changes and seek medical evaluation promptly if you notice any unusual developments.

4.1.3.3 (MEL)



Fig 4.6. Melanoma

Melanoma (MEL), a dangerous form of skin cancer originating from melanocytes that produce melanin pigment, primarily emerges on sun-exposed areas like the arms, back, face, and legs. These specialized cells are responsible for our skin coloration. When left undetected and untreated, melanoma has a

greater propensity to spread to distant body parts compared to other skin cancers. This underscores the importance of early diagnosis and intervention.



When considering the types of melanomas, two main categories are superficial spreading melanoma and nodular melanoma. The former accounts for around 70% of melanoma cases, characterized by initial outward growth on the skin surface, often manifesting as an evolving dark spot. On the other hand, nodular melanoma, comprising approximately 20% of cases, presents as raised nodules in various colours such as dark brown, black, pink, or red, tending to penetrate deeper skin layers early in their development.

Furthermore, various risk factors can increase susceptibility to melanoma, including prolonged exposure to UV radiation from the sun or tanning beds, having fair skin tones, specific genetic mutations, and compromised immune systems. Recognition of these risk factors is crucial for implementing preventive measures and regular skin monitoring practices

In terms of diagnosis and treatment, proactive measures such as regular skin examinations and biopsies are essential for early detection. Treatment modalities for melanoma encompass a range of options, including surgical interventions, radiation therapy, chemotherapy, immunotherapy, and targeted therapy. Individuals should remain vigilant about changes in their skin and promptly seek medical attention if any suspicious moles or skin abnormalities are noted.

By maintaining a proactive approach towards skin health and promptly addressing any signs of concern, individuals can increase their chances of detecting and effectively managing melanoma, a formidable form of skin cancer with potentially serious implications.

TABLE 5.1 DATA SET TABLE

TYPE OF SKIN LESION	NUMBER OF IMAGES	SAMPLE IMAGE
Seborrheic keratosis	1099	
dermatofibroma	115	
Actinic keratosis	327	
Vascular lesions	142	
Basal cell carcinoma	514	
Melanoma	1113	
Total images	3310	

4.2 MATLAB R2022b




Fig 4.7. Matlab logo

MATLAB R2022b introduces several updates and new features. Here are some highlights:

Medical Imaging Toolkit: View, register, segment, and label 2D and 3D medical images. Simscape Battery: Design and simulation of battery and energy storage systems. Main update:

AUTOSAR Blockset: Develop adaptive applications using current methodology and deploy them on embedded Linux; create data types and interfaces in architectural models. Fuzzy Logic Toolbox: Interactively design, analyze, and simulate fuzzy inference systems (FIS), including Type 2 systems, using the updated Fuzzy Logic Designer application. HDL Encoder: Generate SystemC code from MATLAB and use image-to-template conversion to optimize the model and code. HDL Verifier: Performs co-simulation with Xilinx Vivado Simulator and uses a command line interface to automate testing. Model Predictive Control Toolkit: Uses neural networks as predictive models; controller design complies with ISO 26262 and MISRA C. System identification toolkit: Uses machine learning and deep learning techniques to identify nonlinear systems, including spatial patterns, states nonlinearity using neural ODE1. Release highlights:

MATLAB Dictionary: Objects that map unique keys to values for fast lookup. Simulink Library Browser: Attach the Library Browser to a model. Deep Learning Toolkit: Directly import PyTorch models and export models to TensorFlow. MATLAB .NET Engine API: Call MATLAB from .NET applications.

App performance: faster launches and more responsive graphics. Curvefitting Toolbox: Export Curve Fitter results to a Simulink lookup table block. Device Control Toolbox: Configure the NI Vector Transceiver for wireless testing and design validation. Machine Learning and Statistics Toolkit: Reduce the dimensionality of Live Editor tasks. Computer Vision Toolkit: Automate tasks with anomaly detection and classification techniques. Embedded Encoder: Deploying and Prototyping Service Oriented Architecture (SOA) Applications on Linux¹. In summary, MATLAB R2022b delivers improvements in a variety of fields, from medical imaging to control systems and machine learning.

4.3 MobileNetV2

MobileNetV2 is a convolutional neural network (CNN) architecture that can be easily accessed within MATLAB.

When it comes to pretrained models, MobileNetV2 stands out as a sophisticated 53-layer deep CNN that offers exceptional capabilities. Leveraging a pretrained version of MobileNetV2 trained on an extensive dataset of over a million images from the ImageNet database, you gain access to a powerhouse network that can effectively classify images into a wide array of 1000 object categories, ranging from everyday items like keyboards and mice to various animals.

Moreover, with an input image size requirement of 224-by-224 pixels, MobileNetV2 provides a standardized format for data input, ensuring consistency and compatibility in your projects.

For practical applications, MobileNetV2 proves to be invaluable. Whether you are looking to perform image classification, extract essential features from your data, or engage in transfer learning scenarios, MobileNetV2 is a versatile tool that you can seamlessly integrate into your workflow.

Additionally, MobileNetV2 serves as an excellent foundation for more advanced tasks such as building custom models tailored to suit your specific needs. By exploring the untrained MobileNetV2 architecture, you open a realm of possibilities for experimentation and innovation.

Aid in the visualization and understanding of MobileNetV2's intricate architecture, MATLAB provides the Deep Network Designer tool as a user-friendly interface. By utilizing the Deep Network Designer in conjunction with MobileNetV2, you can enhance your comprehension and streamline the design process for your neural network projects.




Fig 4.8. Mobilenet V2 architecture

4.4 System hardware used for training.

Hardware components play a critical role in the efficient training of a MobileNetV2 model. Let us delve into the specifications of the AMD Ryzen 5 4600H with Radeon Graphics, a powerful processor suitable for high-performance productivity and gaming notebooks. This processor boasts 6 Zen 2 CPU cores and 12 threads, along with a base frequency of 3.0 GHz which can dynamically boost up to 4.0 GHz. With 8MB of L3 cache and a standard 45W TDP, the Ryzen 5 4600H strikes an excellent balance between performance and efficiency, making it a reliable choice for various machine learning tasks.

Moving on to the importance of RAM (Random Access Memory) in deep learning, the system is equipped with 8.00 GB of RAM, providing a solid

foundation for computational tasks. However, it's worth noting that increasing the RAM capacity can lead to a significant enhancement in performance, especially when dealing with complex machine learning algorithms and large datasets.

Ensuring optimal utilization of the hardware components, the system operates on a 64-bit Operating System (OS), crucial for leveraging the full potential of modern hardware. By supporting increased memory allocation and running 64-bit applications, the 64-bit OS enhances the system's efficiency and overall performance. Particularly in the realm of deep learning, Linux stands out as a popular choice due to its adaptability, robust community support, and performance advantages.

Additionally, the system architecture is based on x64 processors, which offer superior memory management capabilities and compatibility with 64-bit OS and applications. This architecture enables the system to handle larger datasets and execute tasks more efficiently, aligning perfectly with the requirements of training a complex model like MobileNetV2 effectively.

CHAPTER – 5

Results and Discussion, Performance Analysis

5.1 Outputs




Fig 5.1 raw images

When delving into the realm of deep learning with images, the interpretation of raw images can lead down various paths of understanding. Let's delve deeper into the nuances surrounding raw images:

Raw Sensor Data (RAW Images):

In essence, raw sensor data signifies the untouched output captured directly by an image sensor, whether it be from a digital camera or a smartphone.

Characteristics:

One key feature of raw images is the absence of any processing within the camera, meaning elements like noise reduction, sharpening, and colour corrections are not applied.

Another significant aspect of raw images is their ability to maintain a broad dynamic range, which plays an essential role in preserving details within both highlights and shadows.

Moreover, raw files tend to have a larger file size owing to the limited degree of compression they undergo during storage.

Utilization in Deep Learning:

Opting to train models using raw sensor data comes with perks such as the ability to capture intricate details while sidestepping any artifacts that could potentially be introduced through image manipulation.

Nevertheless, it's worth noting that working with raw images necessitates additional storage capacity and computational resources during the training phase.




Fig 5.2 Enhanced images

Enhancing skin images for deep learning involves the utilization of a variety of techniques aimed at enhancing their quality and suitability for effectively training neural networks. These techniques play a crucial role in empowering the skin image data to be more adaptive and refined for the demanding tasks in deep learning applications. By exploring methods that are specifically focused on colour enhancement, a deep understanding of computational colour constancy techniques can be gained to optimize the skin image datasets.

One notable method for data-driven colour augmentation involves the objective of adapting skin images for deep learning through the strategic utilization

of computational colour constancy techniques. One approach that is commonly employed is the application of shades of gray colour constancy technique to ensure the normalization of the entire training set of images, while also retaining the estimated illuminants for accurate portrayal. Additionally, drawing samples from the distribution of training set illuminants and applying them to the normalized images further refines the dataset for training deep convolutional neural networks (CNNs) in tasks such as skin lesion segmentation and classification.

Moreover, the realm of deep learning with colour enhancement pertains to an objective that seeks to refine skin images utilizing advanced deep learning models. These models, like autoencoders, significantly boost the capabilities of skin detection algorithms by enabling them to process and analyze skin images with enhanced precision. Experimenting with diverse colour spaces, such as RGB and HSV, offers new avenues for improving the representation of skin images and extracting valuable features for deep learning tasks.

Furthermore, employing techniques like High Dimensional Colour Transform (HDCT) facilitates the enhancement of contrast in skin lesion images, thereby elevating the accuracy and efficiency of skin lesion segmentation, classification, and melanoma detection processes. Each method intricately contributes to the overarching goal of refining skin images for deep learning applications, fostering a more robust and effective neural network training environment tailored to the intricacies of skin image analysis and interpretation.




Fig 5.3 Gray scale image and ground truth image

Ground truth images play a pivotal role in the field of machine learning, particularly in the realm of supervised learning algorithms that heavily rely on accurate annotations for training. The significance of ground truth lies in its ability to act as a beacon of truth, serving as a reference point against which the predictions generated by models can be compared and evaluated. In the domain of supervised learning, the availability of high-quality ground truth data is paramount as it directly influences the performance of algorithms. The more extensively annotated data sets with precise labels are, the more effectively algorithms can operate and learn from the provided information. Moreover, researchers often create meticulously curated datasets with ground truth labels to establish benchmarks for a variety of machine learning tasks, which aids in assessing the progress and effectiveness of new methodologies. Notable examples of such benchmark datasets can be found within computer vision applications, encompassing domains like facial recognition and image classification, where the usage of ground truth labels is instrumental in achieving accurate results.

When it comes to the utilization of ground truth labels by models, supervised models specifically incorporate this crucial information during their training phase. These models initially familiarize themselves with the ground truth annotated data to understand the correct outcomes associated with specific inputs. Subsequently, evaluation is carried out on unseen data sets where the model is tasked with making predictions without prior knowledge of the ground truth, allowing for a comprehensive assessment of its performance. Conversely, semi-supervised models leverage ground truth labels for select data points, with the success of these models contingent upon the nature and quality of the examples available to them. This approach proves particularly adept at identifying distinct structures within datasets, making it a valuable tool in the analysis and classification of complex data. In conclusion, the reliance on ground truth images establishes a sturdy foundation for training and evaluating machine learning models, underscoring its indispensable role in driving progress within the field.




Fig 5.4 segmented images

Image segmentation, a crucial aspect of computer vision, is the process of dividing an image into distinct regions or segments. These segments are essential as they correspond to specific objects, boundaries, or regions of interest within the image, facilitating a deeper understanding of its content.

Image segmentation involves grouping similar pixels together based on various criteria like colour, texture, or intensity, ultimately aiming to identify and delineate meaningful regions within an image for further analysis. There are different types of image segmentation techniques used for this purpose:

Semantic Segmentation assigns class labels to each pixel to specify the object or region it represents.

Instance Segmentation distinguishes between individual instances of objects within an image, enabling precise identification of multiple occurrences of the same class.

Panoptic Segmentation offers a comprehensive view by integrating semantic and instance segmentation, providing a unified representation of all objects in the scene.

Various traditional techniques such as Thresholding, Region Growing, Watershed Transform, and Graph Cuts are employed to achieve image

segmentation based on pixel properties, gradient information, and energy minimization approaches.

Moreover, modern deep learning methods like Convolutional Neural Networks (CNNs), Mask R-CNN, and U-Net have revolutionized image segmentation by employing advanced encoder-decoder architectures for pixel-wise classification and instance detection tasks.

Applications of image segmentation span across diverse fields including medical imaging for tumor detection and cell segmentation, autonomous vehicles for road segmentation and obstacle detection, object tracking, image editing, and many more. Utilizing image segmentation techniques unlocks valuable insights from images, making it a powerful tool for extracting meaningful information.

5.2 Performance Analysis




Fig 5.5 Network analyzer

In MATLAB, you can leverage the `analyzeNetwork` function to gain valuable insights into the intricate setup of a deep learning network. This function serves as an invaluable tool for analyzing the network structure, ensuring its proper configuration, and pre-emptively identifying any potential issues that could impede successful training.

When you employ the `analyzeNetwork` function, you are presented with an insightful interactive plot that vividly portrays the network architecture. This visual representation allows you to thoroughly examine and comprehend the various layers of the network, gain insights into the number of learnable parameters within each layer, and delve into the activation functions at play.

Moreover, the function's robust error detection capabilities empower you to spot and rectify issues like misaligned layer inputs or invalid network structures before they adversely impact your training endeavors. By harnessing the `analyzeNetwork` function, you can enhance the efficiency and effectiveness of your deep learning model development process.

Results of the model analysis include various valuable insights. The interactive plot not only showcases details on layer types, sizes, and activations but also provides a comprehensive overview of the network's properties. By utilizing this feature, users can delve into specific information about each layer and gain a better understanding of the network's learnable parameters. The total count of these learnable parameters is clearly presented for easy reference. Upon executing the `analyzeNetwork` function, users receive a Network Analysis object that encapsulates crucial details such as the total number of learnable parameters, a table containing layer specifics, any identified network issues, the count of errors flagged, the number of warnings generated, and the timestamp indicating when the analysis was conducted.




Fig 5.6 layers of mobilenetv2

MobileNetV2 is a lightweight convolutional neural network (CNN) known for its architecture, comprising 53 convolution layers and 1 AvgPool layer. This network is designed with specific components such as the Inverted Residual Block, featuring thin bottleneck layers for inputs and outputs, a departure from traditional residual models. Another crucial element is the Bottleneck Residual Block, which plays a significant role in the MobileNetV2 structure. Additionally, there are Stride 1 Blocks incorporating 1x1 Convolution, followed by depth wise 3x3 Convolution and another 1x1 Convolution. In comparison, Stride 2 Blocks are similar but utilize depth wise 3x3 Convolution with stride=2. The network also employs Depth wise Convolution for lightweight filtering in intermediate expansion layers. Linear Bottlenecks, another essential aspect, help maintain representational power by eliminating non-linearities in narrow layers. As for the layers in this model, each of the 53 convolution layers is configured with specific parameters, contributing to the network's overall capability. For instance, the initial layers are characterized by input size, number of channels, kernel dimension, stride values, and output sizes, presenting a comprehensive overview of the network's evolution from input to output. This detailed examination reveals the intricacies of MobileNetV2's design and functionality, showcasing its efficiency in image processing tasks.



Fig 5.7 confusion matrix

It represents the performance evaluation of a machine learning model, specifically MobileNetV2.

Matrix Structure:

The matrix is organized into rows and columns, where each row corresponds to the true class (actual ground truth), and each column represents the predicted class (model's output).

the diagonal elements (from top left to bottom right) represent correct predictions, while off-diagonal elements indicate misclassifications (errors).

. Class Labels:

the matrix includes six classes:

1. AKIEC Seg
2. BCC Seg
3. BKL Seg
4. DF Seg
5. MEL Seg
6. VASE Seg

Cell Values:

Each cell contains two values:

- The count of instances falling into that specific combination of true and predicted classes.
- The percentage (in parentheses) indicating the proportion of instances relative to the total.

Colour Coding:

- o Correct predictions are highlighted with darker green shades along the diagonal.
- o Errors are represented by red shades.

Overall Accuracy:

- o at the bottom and right side of the matrix, there are overall accuracy percentages for each class.

In summary, this confusion matrix provides insights into how well the MobileNetV2 model performs in classifying different skin disease categories. The

diagonal elements show successful predictions, while off-diagonal elements reveal areas for improvement.




Fig 5.8 ROC Classification

ROC (Receiver Operating Characteristic) is a fundamental concept in machine learning that evaluates the performance of a binary classification model. Let's break it down:

ROC Curve:

An ROC curve is a graphical representation of a model's performance across different classification thresholds.

It plots two key parameters:

True Positive Rate (TPR): Also known as recall, it measures the proportion of actual positive cases correctly predicted by the model.

False Positive Rate (FPR): It quantifies the proportion of actual negative cases incorrectly classified as positive by the model.

The ROC curve illustrates how the model's TPR and FPR change as the classification threshold varies.

Lowering the threshold classifies more items as positive, leading to an increase in both false positives and true positives.

CHAPTER – 6

Summary and Conclusions

6.1 SUMMARY

The project's primary focus lay in the precise classification of skin lesions into distinct categories, a crucial step towards facilitating early identification and diagnosis. To accomplish this, the researchers harnessed the formidable capabilities of MobileNetV2, a sophisticated pre-trained deep learning model custom-tailored for this imperative task. The overall process encompassed several key stages: an elaborate data collection effort garnered a diverse array of skin lesion images, encompassing a spectrum of conditions such as melanoma, nevus, and seborrheic keratosis. Subsequently, meticulous preprocessing measures were implemented, wherein the images were meticulously resized, normalized, and enriched through augmentation techniques to bolster the model's resilience and performance. Leveraging the power of transfer learning, MobileNetV2 underwent fine-tuning on the skin lesion dataset, capitalizing on its foundational pre-training on a comprehensive dataset. Rigorous evaluation ensued, employing a suite of critical metrics like accuracy, precision, recall, ROC-AUC, and PR-AUC to meticulously gauge the model's performance across various skin lesion types. The outcomes bore testament to the efficacy of the tailored MobileNetV2 model, showcasing remarkable proficiency in discerning between diverse skin lesion classes with a commendable level of accuracy and adaptability. Notably, the clinical ramifications of this breakthrough are profound, with the potential to significantly elevate patient outcomes through the early identification of potentially malignant lesions, particularly melanoma. By offering automated support to dermatologists in their diagnostic endeavors, advanced classification models like MobileNetV2 pave the way for streamlined healthcare practices, auguring a promising future for enhanced medical diagnostics and elevated patient care standards.

6.2 CONCLUSION

Throughout the project focusing on skin lesion classification utilizing the MobileNetV2 framework, notable advancements and valuable insights surfaced consistently. Notably, the exceptional performance exhibited by the MobileNetV2 model in effectively distinguishing between various skin lesion types underscored its adaptability and precision. Impressively high levels of accuracy, precision, and recall were consistently achieved, validating the model's robustness across a diverse range of skin conditions. Delving deeper into the analysis, the insights from exploring misclassification patterns and highlighting feature importance played a pivotal role in refining the model's predictive capabilities.

When considering the clinical implications, the significance of early detection of malignant lesions, particularly melanoma, emerged as a paramount factor influencing patient outcomes. The integration of automated classification models into dermatological practice was highlighted as a crucial tool enabling dermatologists to enhance their diagnostic accuracy and facilitate timely interventions. Noteworthy benefits such as improved patient care and a reduction in human error were distinctly evident, indicating the tangible advantages of leveraging technology in medical settings.

Looking towards future directions, the potential for further fine-tuning and optimization of the model to bolster its robustness and performance emerged as a critical area of focus. Additionally, the exploration of interpretability techniques, such as feature visualization, was deemed essential in unlocking deeper insights into model decision-making processes. Emphasizing collaboration with medical professionals for real-world deployment and validation underscored the importance of bridging the gap between AI algorithms and clinical practice to ensure the seamless integration of innovative technologies. In summation, the promising application of MobileNetV2 in skin lesion classification not only holds great potential for enhancing medical diagnostics but also signifies a significant stride towards improving patient health outcomes.

REFERENCES

- [1] A. Mahbod, G. Schaefer, C. Wang, R. Ecker, and I. Ellinge, "Skin lesion classification using hybrid deep neural networks," in Proc. IEEE Int. Conf. Acoust., Speech Signal Process. (ICASSP), May 2019, pp. 1229–1233.
- [2] A. S. Shete, A. S. Rane, P. S. Gaikwad, and M. H. Patil, "Detection of skin cancer using CNN algorithm," Int. J., vol. 6, no. 5, pp. 1–4, 2021.
- [3] C. Lee, S.-H. Jung, and H.-H. Won, "WonDerM: Skin lesion classification with fine-tuned neural networks," 2018, arXiv: 1808.03426.
- [4] DDeVries T, Ramachandram D. Skin lesion classification using deep multi-scale convolutional neural networks. arXiv:1703.01402. 2017.
- [5] Deng J, Dong W, Socher R, et al. Imagenet: A large-scale hierarchical image database. In: 2009 IEEE Conference on Computer Vision and Pattern Recognition. IEEE; 2009:248-55.
- [6] G.GRAMMATIKOPOULOS, A. HATZIGIDAS,A. PAPASTERGIOU, P. LAZARIDIS, Z. ZAHARIS, D. KAMPITAKI, G. TRYFON Automated Malignant Melanoma Detection Using MATLAB Department of Electronics, Department of Esthetics Alexander Technological Educational Institute of Thessaloniki, EPEAEK II Sindos, 57400 Thessaloniki, Macedonia, GREECE.
- [7] Hamza AB, Krim H. A variational approach to maximum a posteriori estimation for image denoising. In: International Workshop on Energy Minimization Methods in Computer Vision and Pattern Recognition. Berlin, Heidelberg: Springer Berlin Heidelberg; 2001:19-34.
- [8] H. Nahata and S. P. Singh, "Deep learning solutions for skin cancer detection and diagnosis," in Machine Learning with Health Care Perspective. Cham, Switzerland: Springer, 2020, pp. 159–182.
- [9] J. Saeed and S. Zeebaree, "Skin lesion classification based on deep convolutional neural networks architectures," J. Appl. Sci. Technol. Trends, vol. 2, no. 1, pp. 41–51, Mar. 2021

- [10] K. Pai and A. Giridharan, "Convolutional neural networks for classifying skin lesions," in Proc. TENCON IEEE Region 10 Conf. (TENCON), Oct. 2019, pp. 1794–1796.
- [11] Kamal Amity, Expert Automated System for Prediction of Multi-Type Dermatology Sicknesses Using Deep Neural Network Feature Extraction Approach February 2023 International Journal of Intelligent Systems and Applications in Engineering 11(3) Kamal Amity
- [12] Krizhevsky A, Sutskever I, Hinton GE. Imagenet classification with deep convolutional neural networks. In: Advances in Neural Information Processing Systems. 2012:1097-105.
- [13] M. Vidya and M. V. Karki, "Skin cancer detection using machine learning techniques," in Proc. IEEE Int. Conf. Electron., Comput. Commun. Technol. (CONECCT), Jul. 2020, pp. 1–5.
- [14] Nasr-Esfahani E, Samavi S, Karimi N, et al. Melanoma detection by analysis of clinical images using convolutional neural network. In: 2016 38th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC). IEEE; 2016:1373-6.
- [15] Nazia Hameed et al , Multi-Class Skin Diseases Classification Using Deep Convolutional Neural Network and Support Vector Machine Conference: 2018 12th International Conference on Software, Knowledge, Information Management & Applications (SKIMA)
- [16] P. Wight on, T. K. Lee, H. Lui, D. I. McLean, and M. S. Atkins, "Generalizing common tasks in automated skin lesion diagnosis," IEEE Trans. Inf.Technol. Biomed., vol. 15, no. 4, pp. 622–629, Jul. 2011.
- [17] Rotemberg V, Kurtansky N, Betz-Stablein B, et al. A patient-centric dataset of images and metadata for identifying melanomas using clinical context. Sci Data 2021;8:34.

- [18] Talavera-Martinez L, Bibiloni P, Gonzalez-Hidalgo M. Hair segmentation and removal in dermoscopy images using deep learning. *IEEE Access* 2020;9:2694-704.
- [19] U. Jamil, M. U. Akram, S. Khalid, S. Abbas, and K. Saleem, "Computerbased melanocytic and nevus image enhancement and segmentation," *BioMed Res. Int.*, vol. 2016, pp. 1–13, Jan. 2016.
- [20] Verma R, Kumar N, Patil A, et al. MoNuSAC2020: A multi-organ nuclei segmentation and classification challenge. *IEEE Trans Med Imaging* 2021;40:3413-23.
- [21] Vijayalakshmi M M , Melanoma Skin Cancer Detection using Image Processing and Machine Learning. *International Journal of Trend in Scientific Research and Development (IJTSRD)* Volume: 3 | Issue: 4 | May-Jun 2019
Available Online: www.ijtsrd.com e-ISSN: 2456 – 647.
- [22] Weipeng Li et al , Fusing Metadata and Dermoscopy Images for Skin Disease and diagnosis April 2020 conference: 2020 IEEE 17th International Symposium on Biomedical Imaging (ISBI).
- [23] ZHE WHU et al , Studies on Different CNN Algorithms for Face Skin Disease Classification Based on Clinical Images Received April 18, 2019, accepted May 15, 2019, date of publication May 22, 2019, date of current version June 4, 2019.
- [24] Zunair H, Ben Hamza A. Melanoma detection using adversarial training and deep transfer learning. *Phys Med Biol* 2020;65:135005