

REALTIME IMPLEMENTATION OF WATER COMMUNICATION USING WCDT MODULE

Submitted in partial fulfillment of the requirements for the award of Bachelor of
Engineering Degree in Electronics and Communication Engineering

by

CH VENU MADHAV (40130034)

CH MUKESH (40130035)



**DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING
SCHOOL OF ELECTRICAL AND ELECTRONICS**

SATHYABAMA

**INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)**

CATEGORY-1 UNIVERSITY BY UGC

**Accredited with Grade “A++” by NAAC | 12B Status by UGC | Approved by AICTE
JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI – 600119**

APRIL 2024



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)

Accredited "A++" Grade by NAAC | 12B Status by UGC | Approved by AICTE
www.sathyabama.ac.in

DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the Bonafide work of CH VENU MADHAV (40130034), CH MUKESH (40130035) who carried out the project entitled "REAL TIME IMPLEMENTATION OF WATER COMMUNICATION USING WCDT MODULE" under our supervision from Nov 2023 to Apr 2024.

Internal Guide

Dr.K.NARESH KUMAR THAPA , Ph.D.,
Assistant Professor

Head of the Department

Dr.T.RAVI ,M.E.,Ph.D.,
Professor & Head

Submitted for Viva voce Examination held on _____

Internal Examiner

External Examiner

DECLARATION

I, CH VENU MADHAV (40130035) hereby declare that the Project Report entitled "REAL TIME APPILICATIONS OF WATER COMMUNICATION USING WCDT MODULE" done by me under the guidance of Dr.K.NARESH KUMAR THAPA, Dept. of Electronics and Communication Engineering, SATHYABAMA INSTITUTE OF SCIENCE AND TECHNOLOGY, CHENNAI, is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in Electronics and Communication Engineering.

DATE: 18-04-2024

PLACE: Chennai

Venu Madhar
SIGNATURE OF CANDIDATES

DECLARATION

I, CH MUKESH (40130035) hereby declare that the Project Report entitled "REAL TIME APPLICATIONS OF WATER COMMUNICATION USING WCDT MODULE" done by me under the guidance of Dr.K.NARESH KUMAR THAPA, Dept. of Electronics and Communication Engineering, SATHYABAMA INSTITUTE OF SCIENCE AND TECHNOLOGY, CHENNAI, is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in Electronics and Communication Engineering.

DATE: 18-04-2024

PLACE: Chennai

ch. Mukesh

SIGNATURE OF CANDIDATES

ACKNOWLEDGEMENT

I am pleased to acknowledge our sincere thanks to the **Board of Management of SATHYABAMA** for their kind encouragement in doing this project and for completing it successfully. I am grateful to them.

I convey our thanks to **Dr. N. M. NANDHITHA, M.E., Ph.D., Dean, School of Electrical and Electronics Engineering** and **Dr. T. RAVI, M.E., Ph.D., Head of the Department, Department of Electronics and Communication Engineering** for providing us necessary support and details at the right time during the progressive reviews.

I would like to express my sincere and deep sense of gratitude to our Project Guide **Dr.K. NARESH KUMAR THAPPA, Ph.D** Dept. of Electronics and Communication Engineering for his valuable guidance, suggestions and constant encouragement for the successful completion of my project work.

I wish to express my thanks to all Teaching and Non-teaching staff members of the Department of Electronics and Communication Engineering who were helpful in many ways for the completion of the project.

ABSTRACT

Underwater data communication represents a promising avenue for establishing effective communication channels beneath the water's surface. However, transitioning laboratory experiments into real-world applications encounters significant challenges due to inherent limitations in scale and authenticity. While artificial scattering agents have been utilized to mimic natural water conditions, achieving reliable similarity between experimental and natural environments remains a daunting task. The accurate replication of frequency domain characteristics is paramount for successful communication, demanding advanced simulation techniques and a thorough understanding of environmental factors. Efforts are ongoing to refine experimental setups and enhance the fidelity of simulations, aiming to bridge the gap between laboratory conditions and the complexities of real-world underwater environments. Ultimately, these endeavors strive for robust and dependable underwater data communication solutions to meet the demands of diverse underwater applications. In the realm of underwater data communication, the challenge lies not only in replicating the conditions of natural water environments but also in adapting to the dynamic and unpredictable nature of underwater settings. Laboratory experiments, while valuable for initial testing, often fail to capture the full spectrum of factors at play in real-world scenarios, such as varying water depths, currents, and marine life interference.

TABLE OF CONTENTS

CHAPTER NO:	TITLE	PAGE NO:
	ABSTRACT	v
	LIST OF FIGURES	viii
1	INTRODUCTION	1
	1.1 General	1
	1.2 Overview	4
	1.3 Back ground	
	1.4 Motivation	8
2	LITERATURE SURVEY	11
3	AIM AND SCOPE OF PRESENT INVESTIGATION	14
	3.1 Aim	14
	3.2 Scope	15
4	EXPERIMENTAL METHODS	18
	4.1 Existing System	18
	4.2 Problem statement	19
	4.3 Proposed system	20
	4.4 Standards	20
	4.5 Constraints	24
	4.6 Trade – OFFS	25
	4.7 Block Diagram	27
	4.8 Arduino	27
	4.9 Pin configuration	27
	4.10 Memory	29

	4.11 Input or Output	32
	4.12 Communication	32
	4.13 Node MCU	33
	4.14 ESP8266 Specification & Features	35
	4.15 Temperature Sensor Features	39
	4.16 Heartbeat Sensor	39
	4.17 water communication module	41
	4.18 Software Description	
	4.19 Embedded & c language	
	4.20 Advantages & Disadvantages of Embedded systems	
5	RESULTS AND DISCUSSIONS	42
	5.1 Results	42
	5.2 Discussions	47
6	CONCLUSION AND FUTURE SCOPE	49
	6.1 Conclusion	49
	6.2 Future Scope	49
	REFERENCES	51

LIST OF FIGURES

FIGURE NO.	FIGURE NAME	PAGE NO.
4.1	Block diagram	17
4.2	Arduino Board	18
4.3	Node Mcu	24
4.4	View of Temperature sensor	29
4.5	Heart Beat Sensor	30
4.6	Arduino IDE Sketch Pannel	37
4.7	Select the required Arduino board	37
4.8	Sketch in Arduino IDE	38
4.9	compilation	38
5.1	Working Model	44
5.2	Things speak project management panel	45
5.3	Temperature sensor graph	46
5.4	Heart beat sensor	47
5.5	Respiratory Sensor	48
5.6	Axis sensor	49

CHAPTER 1

INTRODUCTION

1.1 GENERAL

Underwater wireless information transmission is of great importance to the military, industry, and the scientific community. To facilitate all these activities, there is a rise in the number of unmanned vehicles or devices deployed underwater, which require high bandwidth and high capacity for information transfer underwater. Within the previous couple of years, the interest in optical wireless communication has increased for terrestrial, space, and underwater links as it is capable of providing high data rates with low power and mass requirements. Many researchers have administered work for terrestrial and space links, however underwater optical wireless links are relatively less explored because it is tougher than atmospheric links. The main difficulty for reliable underwater communication is due to the wide selection of physical processes in various sorts of underwater environments starting from shallow coastal water to deep sea or oceans.

Optical communication may be a budding technology to understand underwater wireless communication. The experiment of underwater optical communication within the laboratory is different within the real water environment because the physical scale is restricted. Although in recent several decades, artificial scattering agents have been conditioned to recreate underwater optical communication channels under different water quality conditions, the similarity between experimental water and natural water isn't reliable, like the similarity in frequency domain characteristics. Facing the problem of alignment caused by uncertainty of the position of transmitter and receiver, poor mechanical stability along the complexity of the water environment, the transmission characteristics of underwater optical communication signals under alignment conditions are difficult to get within the natural seawater environment.

An acoustic communication has been developed for the underwater wireless sensor network because of its relatively low attenuation, but the bandwidth of the underwater acoustic channel is restricted, making it less favorable for data-intensive applications. Besides, the slow propagation of underwater sound also results in a considerable delay within the underwater communication link. Underwater sensors

cannot share data with those ashore, as both use different wireless signals that only labor in their respective mediums. Radio signals that travel through air die very quickly in water. Acoustic signals, or sonar, sent by underwater devices generally reflect off the surface without ever breaking through. This causes inefficiencies and other issues for a diversity of applications, such as ocean exploration and submarine-to-plane communication.

To beat the disadvantages in underwater acoustic communication, a replacement approach that is in the most rising area of research is underwater wireless optical communication. Initial research has begun to determine an immediate communication link between the satellite or aircraft and the underwater vehicle. Recently, underwater wireless optical communication using cheap light-emitting diodes and laser diodes also has been researched. Comparing the light sources utilized in these underwater wireless optical communication systems, it is apparent that the LD outperforms light-emitting diodes in terms of knowledge rate. Although it is difficult to transmit long distances, it is possible to unravel the matter of interference between symbols associated with multi-path propagation and therefore the security problem associated with eavesdropping employing a point-to-point method that exploits the laser's characteristics of strong directivity at a brief distance. The blue-green laser has the minimum energy fading within the sea, whose fading rate is approximately 0.155–0.5 dB/m. Hence, exploiting the low absorption window of seawater within the blue-green portion of the electromagnetic spectrum, underwater wireless laser communication is estimated to play an important role by offering secure, efficient, and high data rate communication within short distances.

1.2 OVERVIEW

Normally sea navigators or fishermen require additional support from the land when something uncharacteristic things happens within the sea, we have to pass the message to them. With development of the technologies our people can predict what is happening in the sea, but transferring these messages to sea navigators or fishermen is difficult. To avoid these issues we introduce an enhanced system named underwater data communication. This paper discusses the underwater data communication system used for transferring messages to sea navigators or fishermen and also how we can monitor their health conditions. We use a water data

communication module to get the text and sensor readings to the ground from the navigator and this will help us to avoid the undesirable death of navigators undersea. Since the conditions of underground water even temperature, and pressure may vary in any condition; it also contrasts the body temperature and blood pressure of navigator. So if it lowers or higher during a wide selection, it cause even the death of the navigator. It also provides the needed medical aid to the concerned person. It is applicable for staffs of forces, marine drivers and other people who participate in water entertainments. This is often what we have accomplished with wireless underwater communications. As against hardwired communications which confines you to the length of a cable, wireless communications provides you the facility to communicate with your buddy, or top side, with ease and freedom to easily dive. Wireless underwater communications are a stimulating and easy way to freely stay connected underwater.

1.3 BACKGROUND

Acoustic communications is defined as communication methods from one point to another by using acoustic signals. Acoustic signal is the only physical feasible tool that works in underwater environment. Compared with it electromagnetic wave can only travel in water with short distance due to the high attenuation and absorption effect in underwater environment. It is found that the absorption of electromagnetic energy in sea water is about $45 \times f$ dB per kilometer, where f is frequency in Hertz. In contrast, the absorption of acoustic signal over most frequencies of interest is about three orders of magnitude lower.

There are some investigations about utilizing optical signal for underwater applications. However, they find out that optical signal can only pass through limited range in very clean water environment (deep water, for example). Thus, it is not a proper tool for long-distance transmission underwater, or in a not-so-clean water, e.g., shallow water, environment. Underwater Acoustic Networks, including but not limited to, Underwater Acoustic Sensor Networks (UASNs) and Autonomous Underwater Vehicle Networks (AUVNs), are defined as networks composed of more than two nodes, using acoustic signals to communicate, for the purpose of underwater applications. UASNs and AUVNs are two important kinds of UANs. The former is composed of many sensor nodes, mostly for a monitoring purpose. The nodes are usually without or with limited capacity to move. The latter is composed

Of autonomous or unmanned vehicles with high mobility, deployed for applications that need mobility, e.g., exploration. An UAN can be an UASN, or an AUVN, or a combination of both. Fundamentals of Waves Understanding the first principles of each physical wave used in UWSN wireless communication is critically important. In this section we layout the fundamental physical properties and critical issues for each of the acoustic and optical wave propagations in underwater environments. We discuss each physical carrier's advantages and disadvantages towards efficient underwater wireless communication. Acoustic Waves Among the types of waves, acoustic waves are used as the primary carrier for underwater wireless communication systems due to the relatively low absorption in underwater environments. We start the discussion with the physical fundamentals and the implications of using acoustic waves as the wireless communication carrier in underwater environments. Physical Properties: An acoustic wave has a number of propagation characteristics that are unique from other waves, two of which are highlighted below: Propagation velocity:

The extremely slow propagation speed of sound through water is an important factor that differentiates it from electromagnetic propagation. The speed of sound in water depends on the water properties of temperature, salinity and pressure (directly related to the depth). A typical speed of sound in water near the ocean surface is about 1520 m/s, which is more than 4 times faster than the speed of sound in air, but five orders of magnitude smaller than the speed of light. The speed of sound in water increases with increasing water temperature, increasing salinity and increasing depth. Most of the changes in sound speed in the surface ocean are due to the changes in temperature. This is because the effect of salinity on sound speed is small and salinity changes in the open ocean are small. Near shore and in estuaries, where the salinity varies greatly, salinity can have a more significant effect on the speed of sound in water. As depth increases, the pressure of water has the largest effect on the speed of sound. Under most conditions the speed of sound in water is simple to understand. Sound will travel faster in warmer water and slower in colder water. Approximately, the sound speed increases 4.0 m/s for water temperature. As the depth of water (therefore also the pressure) increases 1 km, the sound speed increases roughly 17 m/s. It is noteworthy to point out that the above assessments are only for rough quantitative or qualitative

discussions, and the variations in sound speed for a given property are not linear in general. Absorption: During propagation, wave energy may be converted to other forms and absorbed by the medium. The absorptive energy loss is directly controlled by the material imperfection for the type of physical wave propagating through it. For acoustic waves, this material imperfection is the inelasticity, which converts the wave energy into heat. Optical Waves Using optical waves for communication obviously has a big advantage in data rate. However, there are a couple of disadvantages for optical communication in water. Firstly, optical signals are rapidly absorbed in water. Secondly, optical scattering caused by suspending particles and planktons is significant.

Thirdly, high level of ambient light in the upper part of the water column is another adverse effect for using optical communication. Optical Communication The present technology of acoustic underwater communication is a legacy technology that provides low-data-rate transmissions for medium-range communication. Data rates of acoustic communication are restricted to around tens of thousands of kilobits per second for ranges of a kilometer, and less than a thousand kilobits per second for ranges up to 100 km, due to severe, frequency-dependent attenuation and surface-induced pulse spread. In addition, the speed of acoustic waves in the ocean is approximately 1500 m/s, so that long-range communication involves high latency, which poses a problem for real-time response, synchronization, and multiple-access protocols. In addition, acoustic waves could distress marine mammals such as dolphins and whales. As a result, acoustic technology cannot satisfy emerging applications that require around the clock, high-data-rate communication networks in real time. Examples of such applications are networks of sensors for the investigation of climate change; monitoring biological, biogeochemical, evolutionary, and ecological processes in sea, ocean, and lake environments; and unmanned underwater vehicles used to control and maintain oil production facilities and harbors. An alternative means of underwater communication is based on optics, wherein high data rates are possible. However, the distance between the transmitter and the receiver must be short, due to the extremely challenging underwater environment, which is characterized by high multiscattering and absorption. Multiscattering causes the optical pulse to widen in

the spatial, temporal, angular, and polarization domains. Optical signal gets scattered badly underwater, and the absorption is also high.

Beside of these, optical wave transmission requires high precision in pointing the narrow laser beams. In very clean water, e.g., deep sea, blue-green wavelengths may be used for short-range connection. The advantage of optical signal lies in its high data rate up to 100 m. Up to today, the only practical solution for underwater communication with acceptable range is utilizing acoustic signal, which travels underwater with longer distance, less attenuation, and higher reliability. However, available bandwidth is extremely limited for acoustic signal. For a very long distance at the order of 1000 km, the available bandwidth falls below a kHz; while only at very short ranges below about 100 m, more than a hundred kHz of bandwidth may be available. Lack of available bandwidth is the biggest issue for underwater acoustic communication /network. High bit error rate is common in underwater channels, due to the multi path interference and time-varying nature of underwater acoustic channels.

1.4 MOTIVATION

Wireless transmission systems are performing better in the air medium than water. The underwater communication is effectively possible with the implementation of the advanced systems and use of modern equipments. The underwater communication has the impact of the factors such as salinity, turbidity, pressure, temperature, amount of light entering the water surface and their effects on waves. Application of Li-Fi technology results in improvement of communication systems for Navy and Submarine. The properties of this technology such as the high speed data transmission, high security and energy efficient behavior makes it suitable for the underwater communication. The proposed system will be effective in identification of the enemy's position and communication between the submarines. The communication will be based on the coding in order to provide the data security using different coding languages and protocols. Light Fidelity is a wireless networking system that provides data transmission through light and would reduce/eliminate EMI concerns. The Navy and industries are looking forward for the application of this technology in communication. Authors have developed the prototype of the system based on transmitter and receiver for communication.

Optical communication is a potential technology to realize long-distance high-speed underwater wireless communication. Facing the difficulty of alignment caused by uncertainty of the position of transmitter and receiver, poor mechanical stability as well as complexity of water environment, the transmission characteristics of underwater optical communication (UOC) signals under alignment conditions are difficult to obtain in the natural seawater environment. The experiments of long distance UOC in the real marine environment are difficult, that is why there are fewer such attempts [1]. At present, the related research mainly focuses on the short-range high-speed optical communication in the laboratory. In the laboratory, to create experimental environment of UOC which close to the real seawater, the requirement of hardware is rigorous. In order to make the experiment effective, it is necessary to ensure a long enough underwater optical channel. A common method is to use longer pools or pipes [2].

The other approach is to use sets of plane mirrors [3]. These ways are accurate and credible for simulating direct light communication channels. To focus on the scattering of underwater light beams, different thinking are needed. In addition to the experimental vessel, the scattering and absorption of light beams in seawater should be simulated. In UOC experiments, artificial particles of very small size, commonly known as scattering agents, are often added to water to simulate the effects of real sea water on photons. These scattering agents include: Magnesium Hydroxide ($Mg(OH)_2$), ISO 12103-1, A4-Coarse Test Dust (ATD), and Maalox antacid. Due to the different micro-components, the optical characteristics of these agents are different.

These artificial agents can significantly enhance the scattering characteristics of experimental water. But the composition of real seawater is extremely complex and varied. There are many organic and inorganic impurities in seawater with different colors, particle size and transparency. On the other hand, the seawater in different geographical areas is usually different. All of these lead to the unique optical properties of seawater optical channel. So It is a difficult task to simulate the optical channel of sea water. seawater optical channel is long.

CHAPTER 2

LITERATURE SURVEY

Pontbriand et al. (2008) provide a comprehensive review of "Diffuse high-bandwidth optical communications" in their literature survey published in *Oceans 2008. IEEE*. They delve into the challenges and advancements in achieving high-bandwidth optical communication in underwater environments, discussing key technologies, such as modulators, transmitters, and receivers. The survey highlights the importance of overcoming attenuation and scattering effects to enable reliable data transmission in turbid waters. Additionally, it explores the potential applications of high-bandwidth optical communication systems in various underwater scenarios, from scientific research to commercial ventures.

Rao et al. (2016) present a thorough examination of "Turbid-harbor demonstration of transceiver technologies for wide dynamic range undersea laser communications" in their literature survey featured in *Oceans 2016. IEEE*. They discuss the experimental setup and results of a demonstration conducted in a turbid harbor environment to test the performance of transceiver technologies for undersea laser communications. The survey outlines the challenges posed by turbidity and dynamic range requirements and evaluates the effectiveness of different modulation schemes and receiver architectures in overcoming these challenges.

Zhang et al. (2018) conduct an in-depth analysis of "Improved m-QAM-OFDM transmission for underwater wireless optical communications" in their literature survey published in *Optics Communications*. They explore the use of improved m-QAM-OFDM transmission techniques to enhance the performance of underwater wireless optical communication systems. The survey discusses the advantages of OFDM modulation in mitigating multipath distortion and improving spectral efficiency in underwater channels. Furthermore, it examines various factors affecting system performance, such as channel attenuation, scattering, and background noise, and proposes strategies for optimizing transmission efficiency.

Stramski et al. (2001) present a comprehensive overview of "Modelling the inherent optical properties of the ocean based on the detailed composition of the planktonic community" in their literature survey published in *Applied Optics*. They discuss the development of models to predict the inherent optical properties of ocean water based on the composition and distribution of planktonic organisms. The survey highlights the importance of accurately characterizing the optical properties of seawater for applications such as remote sensing and underwater optical communication. Additionally, it examines the limitations of existing models and suggests areas for further research to improve their accuracy and applicability.

Jaruwatanadilok et al.(2008) conducts a thorough investigation of "Underwater Wireless Optical Communication Channel Modelling and Performance Evaluation using Vector Radiative Transfer Theory" in their literature survey published in *IEEE Journal on Selected Areas in Communications*. They explore the use of vector radiative transfer theory to model underwater wireless optical communication channels and evaluate their performance under various environmental conditions. The survey discusses the impact of factors such as water turbidity, scattering, and absorption on channel characteristics and proposes methods for optimizing system design and performance.

Sahu Shanmugam et al. (2018) undertake a detailed study on "the impact of particle scattering on the channel characteristics of underwater optical communication system" in their literature survey published in *Optics Communications*. They investigate the effects of particle scattering on the propagation of optical signals in underwater environments and analyze its implications for the design and performance of underwater optical communication systems. The survey discusses the challenges posed by scattering-induced signal attenuation and degradation and explores techniques for mitigating these effects through signal processing and system optimization.

Stojanovic Preisig et al.(2009) provide a comprehensive analysis of "Underwater acoustic communication channels: propagation models and statistical characterization" in their literature survey published in *IEEE Communications Magazine*. They review various propagation models and statistical characterization methods for underwater acoustic communication channels, discussing their strengths, limitations, and applicability in different underwater environments. The

survey also examines the impact of environmental factors such as temperature, salinity, and ocean currents on acoustic channel characteristics and proposes strategies for improving channel modeling accuracy and communication system performance.

Kilfoyle Baggeroer et al. (2000) present an extensive overview of "The state of the art in underwater acoustic telemetry" in their literature survey published in IEEE Journal of Oceanic Engineering. They discuss the current state of underwater acoustic telemetry technology, including advancements in transducer design, signal processing algorithms, and communication protocols. The survey highlights the challenges of underwater communication, such as limited bandwidth, multipath propagation, and environmental noise, and evaluates the effectiveness of existing solutions in addressing these challenges.

Kaushal Kaddoum et al. (2016) offer a comprehensive review of "Underwater optical wireless communication" in their literature survey published in IEEE Access. They examine the principles, technologies, and applications of underwater optical wireless communication, discussing various modulation schemes, transmission techniques, and system architectures. The survey also explores the challenges and opportunities associated with underwater optical wireless communication, including channel attenuation, scattering, and system integration issues, and proposes directions for future research and development.

Zeng et al. (2017) conduct a detailed survey of "underwater optical wireless communications" in their literature review published in IEEE Communications Surveys and Tutorials. They provide an overview of recent advancements in underwater optical wireless communication technologies, including transmitter and receiver design, modulation and coding techniques, and channel modeling approaches. The survey discusses the performance metrics and challenges of underwater optical wireless communication systems and evaluates the potential applications in underwater sensing, monitoring, and data transmission.

CHAPTER 3

AIM AND SCOPE OF THE PRESENT INVESTIGATION

3.1 AIM

This project aims to implement a real-time water communication system utilizing Water Communication Data Transmission (WCDDT) modules. The primary objective is to establish efficient and reliable communication channels through water mediums, enabling seamless data transmission in diverse aquatic environments. By developing and deploying robust WCDDT modules, this endeavor seeks to address the inherent challenges associated with underwater communication, including signal attenuation, interference, and environmental factors. Through experimental validation and practical applications, the aim is to demonstrate the feasibility and efficacy of the proposed system, paving the way for advancements in underwater communication technologies and fostering innovations in aquatic research and exploration.

This project endeavors to design WCDDT modules capable of overcoming the unique hurdles posed by underwater communication. By optimizing signal processing algorithms and hardware components, we aim to mitigate signal degradation and interference, thereby enhancing the reliability and efficiency of data transmission. Additionally, the development of protocols tailored for underwater communication will ensure seamless connectivity and robust performance in varying aquatic conditions. Through iterative testing and refinement, the aim is to create WCDDT modules that not only meet the stringent requirements of underwater communication but also pave the way for future advancements in this field.

The successful implementation of this project will contribute to the advancement of underwater communication technologies, with profound implications for various domains. From environmental monitoring and underwater exploration to applications in aquatic robotics and sensor networks, the developed WCDDT system holds the potential to revolutionize how data is transmitted and collected in aquatic environments. By bridging the gap between terrestrial and aquatic communication, this project aims to unlock new opportunities for scientific research, commercial applications, and sustainable management of aquatic

resources, ultimately fostering a deeper understanding of our planet's oceans and water bodies.

3.2 SCOPE

The scope of this project encompasses the comprehensive development and implementation of a real-time water communication system utilizing Water Communication Data Transmission (WCDDT) modules. This includes designing and fabricating robust WCDDT modules capable of transmitting and receiving data through water mediums. The project will focus on optimizing the performance of these modules to ensure reliable communication in diverse aquatic environments, considering factors such as signal attenuation, interference, and environmental conditions.

Development of protocols and algorithms tailored for underwater communication, aiming to enhance the efficiency and reliability of data transmission. The project will involve conducting laboratory experiments to evaluate the performance of the WCDDT system under controlled conditions, followed by extensive field testing in real-world aquatic environments to validate its effectiveness. The project scope includes integrating the WCDDT modules into practical applications such as underwater sensor networks, aquatic robotics, and environmental monitoring systems. This entails exploring encryption and security measures to ensure the confidentiality and integrity of transmitted data, as well as optimizing energy efficiency to enable prolonged operation in remote underwater locations.

The documentation of the design process, experimental results, and findings for dissemination through publications and presentations. The project aims to contribute to advancements in underwater communication technologies, with the potential to revolutionize various domains including scientific research, commercial applications, and sustainable management of aquatic resources.

CHAPTER 4

EXPERIMENTAL METHODS

4.1 EXISTING SYSTEM

Almost no other systems to watch the health conditions of sea navigator while navigating the sea. While there is a wearable device for monitoring his/her pulse for himself/herself. But an individual within the ground cannot find about the health conditions of person underwater. So he does not realize the health conditions of the person underwater.

Diving equipment is equipment employed by underwater divers to form diving activities possible, easier, safer and comfortable. This might be equipment chiefly intended for this purpose, or equipment intended for other purposes which is found to be suitable for diving use. The fundamental item of diving equipment is an underwater breathing device, and surface supplied diving equipment. But there are no other important pieces of kit that make diving safer, more convenient or more efficient. Diving equipment employed by recreational scuba divers is usually personal equipment carried by the diver, but professional divers, particularly when functioning within the surface supplied or saturation mode, uses a good deal of support equipment not carried by the diver. Scuba diving is a mode of underwater diving. Here, the diver uses a self-contained underwater breathing device (scuba), to breathe underwater. Scuba divers carry their own source of breathing gas, usually compressed gas.

It allows them greater independence and freedom of movement. Although the utilization of compressed air is common, a new mixture called enriched air (Nitrox) has been gaining popularity due to its advantage of reduced nitrogen intake during repetitive dives. Open circuit scuba systems contains one or more diving cylinders comprising of breathing gas at high pressure which is supplied to the diver via a regulator. They may include extra cylinders for range extension, decompression gas or emergency breathing gas. Closed-circuit or semi-closed circuit rebreather scuba systems sanction the recycling of exhaled gases. The volume of gas used is reduced compared to that of open circuit, so a smaller cylinder or cylinders could also be used for equivalent dive duration. Rebreathers lengthen

the time spent underwater compared to circuit for corresponding gas consumption; they produce fewer bubbles and fewer noise than circuit scuba. It makes them attractive to hidden military divers to avoid detection, scientific divers to avoid disturbing marine animals, and media divers to avoid bubble interference.

4.2 PROBLEM STATEMENT

Disadvantages of the prevailing system are the person cannot communicate with the ground and the conditions of his health cannot be monitored in the sea. Even if he dies, the people in the ground will not be able to realize it. He also would not be able to know about anything taking place in the ground.

4.3 PROPOSED SYSTEM

Today, underwater sensors cannot share data with those ashore, as both use different wireless signals that only work in their corresponding mediums. Radio signals that travel through air die very quickly in water. Acoustic signals, or sonar, sent by underwater devices generally reflect off the surface without ever breaking through. This causes inefficiencies and other problems for a variety of applications, like ocean exploration and submarine-to-plane communication. To start, there are two selections of underwater communications: Hardwired- uses a cable to transfer the communications; Wireless- uses the water to transfer the communications. Many divers prefer the idea of freely diving where they please with the ability to communicate to their dive partner easily and quickly. This is what we have accomplished with wireless underwater communications. As opposed to hardwired communications which limits you to the length of a cable, wireless communications provides you the ability to communicate with your companion, or top side, with ease and freedom to simply dive. Wireless underwater communications are an interesting and easy way to freely stay associated underwater. Advantages of this system are a person who is in the ground can observe the health conditions of navigator, alert messages can pass to navigators from the ground, navigators/fishermen can communicate.

4.4 STANDARDS

1. **Protocol Standardization:** Establishing common communication protocols ensures interoperability among different underwater wireless communication devices and systems. Standards such as those developed by organizations like the IEEE (Institute of Electrical and Electronics Engineers) ensure compatibility and reliability.
2. **Frequency Allocation:** Standardizing frequency bands for underwater communication helps avoid interference and ensures efficient use of the limited spectrum available. Clear regulations and standards for frequency allocation are necessary to prevent communication disruptions.
3. **Data Encoding and Modulation:** Standardizing data encoding and modulation techniques ensures efficient data transmission underwater. Adopting standardized methods for encoding, modulation, and error correction enhances the reliability and performance of underwater wireless communication systems.

4.5 CONSTRAINTS

1. **Limited Bandwidth:** Underwater environments have limited bandwidth available for communication due to the high attenuation of signals in water. This constraint limits the data rates and transmission capabilities of underwater wireless communication systems.
2. **Signal Attenuation and Reflection:** Signals transmitted underwater experience attenuation and reflection due to the characteristics of water. These phenomena can degrade signal quality, reduce communication range, and introduce latency, posing significant constraints on underwater communication systems.
3. **Environmental Factors:** Underwater communication systems must contend with environmental factors such as water turbidity, temperature variations, and marine life interference. These factors can affect signal propagation, reliability, and overall system performance, imposing constraints on underwater communication technology.

4.6 TRADE-OFFS

1. **Range vs. Data Rate:** There is often a trade-off between communication range and data rate in underwater wireless communication systems. Increasing the transmission range may require sacrificing data rate, and vice versa, depending on the modulation scheme, signal power, and environmental conditions.
2. **Energy Efficiency vs. Performance:** Balancing energy efficiency with system performance is a trade-off in underwater communication design. Energy-efficient protocols and transmission techniques may sacrifice performance metrics such as throughput or latency, while optimizing for performance may consume more energy.
3. **Cost vs. Reliability:** Achieving higher reliability in underwater communication systems often involves deploying redundant hardware, advanced signal processing algorithms, and robust error correction mechanisms. However, these enhancements can increase system cost. Designing for cost-effective solutions while maintaining reliability requires careful consideration of trade-offs between hardware complexity and system performance.

4.7 BLOCK DIAGRAM




Fig 4.1 block diagram

HARDWARE REQUIREMENTS

- Arduino
- Temperature sensor
- Heart Beat sensor
- Switch
- Water communication module

SOFTWARE REQUIREMENTS

- Arduino IDE
- Embedded C Language

4.8 ARDUINO:

The Arduino microcontroller is an easy to use yet powerful single board computer that has gained considerable traction in the hobby and professional market. The Arduino is open-source, which means hardware is reasonably priced and development software is free. This guide is for students in ME 2011, or students anywhere who are confronting the Arduino for the first time. For advanced Arduino users, prowl the web; there are lots of resources.

This guide covers the Arduino Uno board (Spark fun DEV-09950, \$29.95), a good choice for students and educators. With the Arduino board, you can write programs and create interface circuits to read switches and other sensors, and to control motors and lights with very little effort. Many of the pictures and drawings in this guide were taken from the documentation on the

This is what the Arduino board looks like.



Fig 4.2 Arduino board

The Duemilanove board features an Atmel ATmega328 microcontroller operating at 5 V with 2 Kb of RAM, 32 Kb of flash memory for storing programs and 1 Kb of EEPROM for storing parameters. The clock speed is 16 MHz, which translates to about executing about 300,000 lines of C source code per second. The board has 14 digital I/O pins and 6 analog input pins. There is a USB connector for

talking to the host computer and a DC power jack for connecting an external 6-20 V power source, for example a 9 V battery, when running a program while not connected to the host computer. Headers are provided for interfacing to the I/O pins using 22 g solid wire or header connectors. The Arduino programming language is a simplified version of C/C++. If you know C, programming the Arduino will be familiar. If you do not know C, no need to worry as only a few commands are needed to perform useful functions.

An important feature of the Arduino is that you can create a control program on the host PC, download it to the Arduino and it will run automatically. Remove the USB cable connection to the PC, and the program will still run from the top each time you push the reset button. Remove the battery and put the Arduino board in a closet for six months. When you reconnect the battery, the last program you stored will run. This means that you connect the board to the host PC to develop and debug your program, but once that is done, you no longer need the PC to run the program. The Arduino Uno is a microcontroller board based on the ATmega328. It has 14 digital input/output pins (of which 6 can be used as PWM outputs), 6 analog inputs, a 16 MHz ceramic resonator, a USB connection, a power jack, an ICSP header, and a reset button. It contains everything needed to support the microcontroller; simply connect it to a computer with a USB cable or power it with a AC-to-DC adapter or battery to get started.

The Uno differs from all preceding boards in that it does not use the FTDI USB-to-serial driver chip. Instead, it features the Atmega16U2 (Atmega8U2 up to version R2) programmed as a USB-to-serial converter.

4.9 PIN CONFIGURATION

The Arduino Uno can be powered via the USB connection or with an external power supply. The power source is selected automatically. External (non-USB) power can come either from an AC-to-DC adapter (wall- wart) or battery. The adapter can be connected by plugging a 2.1mm center-positive plug into the board's power jack. Leads from a battery can be inserted in the Gnd and Vin pin headers of the POWER connector. The board can operate on an external supply of 6 to 20 volts. If supplied with less than 7V, however, the 5V pin may supply less than five volts and the board may be unstable.

The power pins are as follows:

- **VIN.** The input voltage to the Arduino board when it's using an external power source (as opposed to 5 volts from the USB connection or other regulated power source). You can supply voltage through this pin, or, if supplying voltage via the power jack, access it through this pin.
- **5V.** this pin outputs a regulated 5V from the regulator on the board. The board can be supplied with power either from the DC power jack (7 - 12V), the USB connector (5V), or the VIN pin of the board (7-12V). Supplying voltage via the 5V or 3.3V pins bypasses the regulator, and can damage your board.
- **3V3.** A 3.3 volt supply generated by the on-board regulator. Maximum current draw is 50 mA.
- **GND.** Ground pins.
- **IOREF.** This pin on the Arduino board provides the voltage reference with which the microcontroller operates. A properly configured shield can read the IOREF pin voltage and select the appropriate power source or enable voltage translators on the outputs for working with the 5V or 3.3V.

4.10 MEMORY

The ATmega328 has 32 KB (with 0.5 KB used for the bootloader). It also has 2 KB of SRAM and 1 KB of EEPROM. The ATmega328 microcontroller is widely recognized for its versatility and reliability in various embedded systems and DIY electronics projects. With its 32 KB of flash memory, developers have ample space to store their program code, allowing for the implementation of complex functionalities and algorithms. Additionally, the 2 KB of SRAM provides temporary storage for data and variables during program execution, enabling efficient processing and manipulation of information. The 1 KB of EEPROM offers non-volatile memory storage, ideal for saving configuration settings, calibration values, or other critical data that needs to be retained even when power is removed. Combined, these features make the ATmega328 a robust and flexible choice for a wide range of embedded applications, from simple LED blinking projects to more advanced robotics and automation systems. Furthermore, its compatibility with the Arduino development environment and extensive community support contribute to its popularity among hobbyists, students, and professional engineers alike.

4.11 INPUT OR OUTPUT

Each of the 14 digital pins on the Uno can be used as an input or output, using pin Mode(), digital Write(), and digital Read() functions. They operate at 5 volts. Each pin can provide or receive a maximum of 40 mA and has an internal pull- up resistor (disconnected by default) of 20-50 kohms. In addition, some pins have specialized functions:

Serial: 0 (RX) and 1 (TX). Used to receive (RX) and Transmit (TX) TTL serial data. These pins are connected to the corresponding pins of the ATmega8U2 USB-to-TTL Serial chip.

External Interrupts: 2 and 3. These pins can be configured to trigger an interrupt on a low value, a rising or falling edge, or a change in value. See the attach Interrupt () function for details.

PWM: 3, 5, 6, 9, 10, and 11. Provide 8-bit PWM output with the analog Write () function.

SPI: 10 (SS), 11 (MOSI), 12 (MISO), 13 (SCK). These pins support SPI communication using the SPI library.

LED: 13. There is a built- in LED connected to digital pin 13. When the pin is HIGH value, the LED is on, when the pin is LOW, it's off.

The Uno has 6 analog inputs, labeled A0 through A5, each of which provide 10 bits of resolution (i.e. 1024 different values). By default they measure from ground to 5 volts, though is it possible to change the upper end of their range using the AREF pin and the analog Reference () function. Additionally, some pins have specialized functionality:

TWI: A4 or SDA pin and A5 or SCL pin. Support TWI communication using the Wire library.

There are a couple of other pins on the board:

AREF. Reference voltage for the analog inputs. Used with analog Reference

Reset. Bring this line LOW to reset the microcontroller. Typically used to add a reset button to shields which block the one on the board.

4.12 COMMUNICATION

Microcontrollers depend on a host computer for developing and compiling programs. The software used on the host computer is known as an integrated development environment, or IDE. For the Arduino, the development environment is based on the open source Processing platform (www.processing.org) which is described by its creators as a “programming language and environment for people who want to program images, animation, and interactions.” The Arduino programming language leverages an open source project known as Wiring (wiring.org.co). The Arduino language is based on good old- fashioned C. If you are unfamiliar with this language, don’t worry; it’s not hard to learn, and the Arduino IDE provides some feedback when you make mistakes in your programs.

The Arduino Uno has a number of facilities for communicating with a computer, another Arduino, or other microcontrollers. The ATmega328 provides UART TTL (5V) serial communication, which is available on digital pins 0 (RX) and 1 (TX). An ATmega16U2 on the board channels this serial communication over USB and appears as a virtual com port to software on the computer. The '16U2 firmware uses the standard USB COM drivers, and no external driver is needed. However, on Windows, a inf file is required. The Arduino software includes a serial monitor which allows simple textual data to be sent to and from the Arduino board. The RX and TX LEDs on the board will flash when data is being transmitted via the USB-to-serial chip and USB connection to the computer (but not for serial communication on pins 0 and 1).

A Software Serial library allows for serial communication on any of the Uno's digital pins. The ATmega328 also supports I2C (TWI) and SPI communication. The Arduino software includes a Wire library to simplify use of the I2C bus; see the documentation for details. For SPI communication, use the SPI library.

As you go through the list of programming statements available in the Arduino IDE (choose Help->Reference), you might think there isn’t much power for doing things like running servos, operating stepper motors, reading potentiometers, or displaying text on an LCD. Like most any language based on C, the Arduino supports the notion of “libraries” code

Repositories that extend core programming functionality. Libraries let you re-use code without having to physically copy and paste it into all your programs. The standard Arduino software installation comes with several libraries you may use, and you can download others from the Arduino support pages and from third-party websites that publish Arduino library code. A good example of a library you'll use with the Robot and likely many other robot projects is Servo. This library allows you to connect one or more hobby R/C servos to the Arduino's digital I/O pins. The Servo library comes with the standard Arduino installation package Library->Servo. This adds the line.

Which tells the Arduino IDE that you wish to include the Servo library in your sketch. With the functionality of the library now available to you, you can use its various functions to control one or more servos. For example, you can use the write function to rotate a servo to a specific position, from 0 to 180 degrees. The following code Moves a servo to its midpoint, or 90 degree position. Structurally, Arduino sketches are very straightforward and are pretty easy to read and understand. The Arduino program contains two main parts: setup () and loop (). These are programming functions that do what their names suggest: setup () sets up the Arduino hardware, such as specifying which I/O lines you plan to use, and whether

They are inputs or outputs. The loop () function is repeated endlessly when the Arduino is operating. Arduino IDE (Integrated development environment) is used to write the program and dump into the Arduino board. Moves a servo to its midpoint, or 90 degree position. Structurally, Arduino sketches are very straightforward and are pretty easy to read and understand. The Arduino program contains two main parts: setup () and loop (). These are programming functions that do what their names suggest: setup () sets up the Arduino hardware, such as specifying which I/O lines you plan to use, and whether

4.13 NODE MCU

Node MCU is an open-source Lua based firmware and development board specially targeted for IoT based Applications. It includes firmware that runs on the ESP8266 Wi-Fi SoC from Espressio Systems, and hardware which is based on the ESP-12 module Programming Node MCU ESP8266 with Arduino IDE. The Node MCU Development Board can be easily programmed with Arduino IDE since it is easy to use. Programming Node MCU with the Arduino IDE will hardly take 5-10 minutes. All you need is the Arduino IDE, a USB cable and the Node MCU board itself. You can check this Getting Started Tutorial for Node MCU to prepare your Arduino IDE for Node MCU. Node MCU is an open source firmware for which open source prototyping board designs are available.

The firmware uses the Lua scripting language. The firmware is based on the eLua project, and built on the Espressif Non-OS SDK for ESP8266. It uses many open source projects, such as lua-cjson[9] and SPIFFS.[10] Due to resource constraints, users need to select the modules relevant for their project and build a firmware tailored to their needs. Support for the 32-bit ESP32 has also been implemented. The prototyping hardware typically used is a circuit board functioning as a dual in-line package (DIP) which integrates a USB controller with a smaller surface-mounted board containing the MCU and antenna. The choice of the DIP format allows for easy prototyping on breadboards. The design was initially based on the ESP-12 module of the ESP8266, which is a Wi-Fi SoC integrated with a Tensilica Xtensa LX106 core, widely used in IoT applications (see related projects).

Node MCU Dev Kit/board consist of ESP8266 wifi enabled chip. The ESP8266 is a low-cost Wi-Fi chip developed by Espress if Systems with TCP/IP protocol. For more information about ESP8266, you can refer to the ESP8266 WiFi Module. There is Version2 (V2) available for Node MCU Dev Kit i.e. Node MCU Development Board v1.0 (Version2), which usually comes in black colored PCB. For more information about Node MCU Boards available in the market refer to Node MCU Development Boards Node MCU Dev Kit has Arduino like Analog (i.e. A0) and Digital (D0-D8) pins on its board. It supports serial communication protocols i.e. UART, SPI, I2C, etc. Using such serial protocols




Fig 4.3 Node Mcu

NodeMCU was created shortly after the ESP8266 came out. On December 30, 2013, Espressif Systems[6] began production of the ESP8266.[11] NodeMCU started on 13 Oct 2015, when Hong committed the first file of nodemcu-firmware to GitHub.[12] Two months later, the project expanded to include an open-hardware platform when developer Huang R committed the gerber file of an ESP8266 board, named devkit v0.9.[13] Later that month, Tuan PM ported MQTT client library from Contiki to the ESP8266 SoC platform,[14] and committed to NodeMCU project, then NodeMCU was able to support the MQTT IoT protocol, using Lua to access the MQTT broker. Another important update was made on 30 Jan 2015, when Devsaurus ported the u8glib[15] to the NodeMCU project,[16] enabling NodeMCU to easily drive LCD, Screen, OLED, even VGA displays.

In the summer of 2015 the original creators abandoned the firmware project and a group of independent contributors took over. By the summer of 2016 the NodeMCU included more than 40 different modules. As Arduino.cc began developing new MCU boards based on non-AVR processors like the ARM/SAM MCU and used in the Arduino Due, they needed to modify the Arduino IDE so that it would be relatively easy to change the IDE to support alternate toolchains to allow Arduino C/C++ to be compiled for these new processors. They did this with the introduction of the Board Manager and the SAM Core. A "core" is the collection of software components required by the Board Manager and the Arduino IDE to

compile an Arduino C/C++ source file for the target MCU's machine language. Some ESP8266 enthusiasts developed an Arduino core for the ESP8266 WiFi SoC, popularly called the "ESP8266 Core for the Arduino IDE".[17] This has become a leading software development platform for the various ESP8266-based modules and development boards, including NodeMCUs is an open-source LUA based firmware developed for the ESP8266 wifi chip. By exploring functionality with the ESP8266 chip, NodeMCU firmware comes with the ESP8266 Development board/kit i.e. NodeMCU Development board. Since NodeMCU is an open-source platform, its hardware design is open for edit/modify/build.

NodeMCU Dev Kit/board consist of ESP8266 wifi enabled chip. The ESP8266 is a low-cost Wi-Fi chip developed by Espressif Systems with TCP/IP protocol. For more information about ESP8266, you can refer to the ESP8266 WiFi Module. There is Version2 (V2) available for NodeMCU Dev Kit i.e. NodeMCU Development Board v1.0 (Version2), which usually comes in black colored PCB. For more information about NodeMCU Boards available in the market refer to NodeMCU Development Boards. NodeMCU Dev Kit has Arduino like Analog (i.e. A0) and Digital (D0-D8) pins on its board. It supports serial communication protocols i.e. UART, SPI, I2C, etc. Using such serial protocols we can connect it with serial devices like I2C enabled LCD display, Magnetometer HMC5883, MPU-6050 Gyro meter + Accelerometer, RTC chips, GPS modules, touch screen displays, SD cards, etc.

NodeMCU Development board is featured with wifi capability, analog pin, digital pins, and serial communication protocols. To get started with using NodeMCU for IoT applications first we need to know about how to write/download NodeMCU firmware in NodeMCU Development Boards. And before that where this NodeMCU firmware will get as per our requirement. There are online NodeMCU custom builds available using which we can easily get our custom NodeMCU firmware as per our requirement. To know more about how to build custom NodeMCU firmware online and download it refer to Getting started with NodeMCU. After setting up ESP8266 with Node-MCU firmware, let's see the IDE (Integrated Development Environment) required for the development of NodeMCU. NodeMCU with ESPlorer IDE. Lua scripts are generally used to code the NodeMCU. Lua is an open-source, lightweight, embeddable scripting language built on top of C programming language. For more

information about how to write Lua script for Node MCU refer to Getting started with Node MCU using ESPlorerIDE

Node MCU with Arduino IDE Here is another way of developing Node MCU with a well-known IDE i.e. Arduino IDE. We can also develop applications on Node MCU using the Arduino development environment. This makes it easy for Arduino developers than learning a new language and IDE for Node MCU. For more information about how to write Arduino sketch for NodeMCU refer to Getting started with NodeMCU using Arduino IDE The difference in using ESPlorer and Arduino IDE Well, there is a programming language difference we can say while developing an application for NodeMCU using ESPlorer IDE and Arduino IDE.

We need to code in C\C++ programming language if we are using Arduino IDE for developing Node MCU applications and Lua language if we are using ESPlorer IDE. Basically, Node MCU is Lua Interpreter, so it can understand Lua script easily. When we write Lua scripts for Node MCU and send/upload it to Node MCU, then they will get executes sequentially. It will not build a binary firmware file of code for Node MCU to write. It will send Lua script as it is to Node MCU to get executed. In Arduino IDE when we write and compile code, the ESP8266 toolchain in the background creates a binary firmware file of code we wrote. And when we upload it to Node MCU then it will flash all Node MCU firmware with newly generated binary firmware code. In fact, it writes the complete firmware. That's the reason why Node MCU not accept further Lua scripts/code after it is getting flashed by Arduino IDE. After getting flashed by Arduino sketch/code it will be no more Lua interpreter and we got an error if we try to upload Lua scripts. To again start with Lua script, we need to flash it with Node MCU firmware. Since Arduino IDE compiles and upload/writes complete firmware, it takes more time than ESPlorer IDE.

4.14 ESP8266 SPECIFICATIONS & FEATURES

Microcontroller: Tensilica 32-bit RISC CPU Xtensa LX106

- Operating Voltage: 3.3V
- Input Voltage: 7-12V
- Digital I/O Pins (DIO): 16
- Analog Input Pins (ADC): 1
- UARTs: 1

- SPIs: 1
- I2Cs: 1
- Flash Memory: 4 MB
- SRAM: 64 KB
- Clock Speed: 80 MHz
- USB-TTL based on CP2102 is included onboard, Enabling Plug n Play
- PCB Antenna
- Small Sized module to fit smartly inside your IoT projects

4.15 TEMPERATURE SENSOR FEATURES

- Calibrated Directly in ° Celsius (Centigrade)
- Linear + 10 mV/°C Scale Factor
- 0.5°C Ensured Accuracy (at +25°C) LM35 has an advantage over linear temperature
- Rated for Full -55°C to +150°C Range
- Suitable for Remote Applications
- Low Cost Due to Wafer-Level Trimming
- Less than 60-μA Current Drain
- Low Self-Heating, 0.08°C in Still Air
- Nonlinearity Only $\pm\frac{1}{4}^{\circ}\text{C}$ Typical
- Low Impedance Output, 0.1 Ω for 1 mA Load

The LM35 series are precision integrated-circuit temperature sensors, with an output voltage linearly proportional to the Centigrade temperature. Thus the LM35 has an advantage over linear temperature sensors calibrated in ° Kelvin, as the user convenient Centigrade scaling. The LM35 does not require any external calibration or trimming to provide typical accuracies of $\pm\frac{1}{4}^{\circ}\text{C}$ at room temperature and $\pm\frac{3}{4}^{\circ}\text{C}$ over a full -55°C to +150°C temperature range. Low cost is assured by trimming and calibration at the wafer level. The low output impedance, linear output, and precise inherent calibration of the LM35 make interfacing to readout or control circuitry especially easy. The device is used with single power supplies, or with plus and minus supplies. As the LM35 draws only 60 μA from the supply, it has very low self-heating of less than 0.1°C in still air. The LM35 is rated to operate over a -55°C

to +150°C temperature range, while the LM35C is rated for a -40°C to +110°C range (-10° with improved accuracy).




Fig 4.4 View of Temperature sensor

4.16 HEARTBEAT SENSOR

A person's heartbeat is the sound of the valves in his/her's heart contracting or expanding as they force blood from one region to another. The number of times the heart beats per minute (BPM), is the heart beat rate and the beat of the heart that can be felt in any artery that lies close to the skin is the pulse.

Two Ways to Measure a Heartbeat:

Manual Way: Heart beat can be checked manually by checking one's pulses at two locations- wrist (the radial pulse) and the neck (carotid pulse). The procedure is to place the two fingers (index and middle finger) on the wrist (or neck below the windpipe) and count the number of pulses for 30 seconds and then multiplying that number by 2 to get the heart beat rate. However pressure should be applied minimum and also fingers should be moved up and down till the pulse is felt. Using a sensor: Heart Beat can be measured based on optical power variation as light is scattered or absorbed during its path through the blood as the heart beat changes.

Principle of Heartbeat Sensor: The heartbeat sensor is based on the principle of photo plethysmography. It measures the change in volume of blood through any organ of the body which causes a change in the light intensity through that organ (a vascular region). In case of applications where heart pulse rate is to be monitored, the timing of the pulses is more important. The flow of blood volume is decided by the rate of heart pulses and since light is absorbed by blood, the signal pulses are equivalent to the heart beat pulses.

There are two types of photoplethysmography:

Transmission: Light emitted from the light emitting device is transmitted through any vascular region of the body like earlobe and received by the detector.

Reflection: Light emitted from the light emitting device is reflected by the regions.



Fig 4.5 Heart Beat Sensor

Working of a Heartbeat Sensor:

The basic heartbeat sensor consists of a light emitting diode and a detector like a light detecting resistor or a photodiode. The heart beat pulses causes a variation in the flow of blood to different regions of the body. When a tissue is illuminated with the light source, i.e. light emitted by the led, it either reflects (a finger tissue) or transmits the light (earlobe). Some of the light is absorbed by the blood and the transmitted or the reflected light is received by the light detector. The amount of light absorbed depends on the blood volume in that tissue. The detector output is in form of electrical signal and is proportional to the heart beat rate.

This signal is actually a DC signal relating to the tissues and the blood volume and the AC component synchronous with the heart beat and caused by pulsatile changes in arterial blood volume is superimposed on the DC signal. Thus the major requirement is to isolate that AC component as it is of prime importance.

To achieve the task of getting the AC signal, the output from the detector is first filtered using a 2 stage HP-LP circuit and is then converted to digital pulses using a comparator circuit or using simple ADC. The digital pulses are given to a microcontroller for calculating the heart beat rate, Practical heartbeat Sensor examples are Heart Rate Sensor (Product No PC-3147). It consists of an infrared led and an Idr embedded onto a clip like structure. The clip is attached to the organ (earlobe or the finger) with the detector part on the flesh.

4.17 WATER COMMUNICATION MODULE

Water Communication Module 100W ERT modules are available in two housing designs, supporting both water pit and remote installations. The different 100W ERT modules are identified as follows 100W is to be utilized with encoder registers in a pit environment » 100WP for pulser registers in a pit environment • All new 100W ERT modules for pit applications will come standard with a red integral connector port to utilize the optional 100W Through-The-Lid (TTL) antenna 100W-R for encoder registers in remote applications 100WP-R for with pulser registers in remote applications These modules offer advanced two-way meter data collection designed specifically for Itron collection systems using handheld, mobile, fixed network and combination hybrid solutions. 100W ERT modules differentiate themselves from other devices on the market by providing true two-way communications capabilities. Engineered from the ground up to leverage the benefits of Choice Connect collection systems, 100W ERT modules enable easy migration from mobile to fixed network operations as your business needs evolve. With Itron's complementary communications technology, fixed and mobile network systems can be deployed side-by-side in hybrid configurations to ensure maximum efficiency and reliability in both high and low-density meter populations.

Water Meter Compatibility The 100W ERT module is compatible with industry-leading water meters from Itron—as well as those from all major manufacturers such as Badger, Elster AMCO, Hersey, Master Meter, Neptune and

Sensus—enabling water utilities to consolidate all their water meters under a single reading system. Powered by proven, advanced lithium battery technology; the module is designed for 20 years of battery life in both fixed network and mobile modes. Data Logging The 100W ERT module stores 40 days of hourly consumption information, which can be collected by the fixed network system to leverage real time data collection or can be read by mobile or handheld systems. This data is presented in four basic use cases Any hourly reading within the last 40 days » A set of 24 consecutive hourly readings A set of 40 daily readings » A set of 40 days of hourly interval data are available even in mobile mode Superior Performance The 100W ERT module utilizes 120 radio channels in Fixed Network and 50 radio channels in mobile and handheld modes, randomly selecting one channel for each data message. This multi-channel approach delivers higher read integrity over competing products by reducing the effect of interfering signals from other radio frequency (RF) signals in the area.

The 100W ERT module will transmit the Fixed Network consumption messages at peak radiated power greater than 1 Watt. Reliability 100W ERT modules feature a circuit assembly and battery pack that are fully encapsulated within a speciallyformulated potting material to completely protect internal components from water, contaminants, corrosion, rough handling and temperature cycling. With their straight forward, rugged design, 100W ERT modules use substantially fewer components than most competing products, resulting in greater reliability. The advanced, integrated antenna operates effectively in a wide range of meter box installations. The 100W ERT module offers peace of mind with a 20 year limited warranty. Lower Cost of Ownership 100W ERT module devices feature industry-leading battery life , ensuring your meter data collection investment achieves substantially better financial returns than competing products with batteries that typically last only ten or twelve years. When one considers the advancements in leak, reverse flow (absolute encoder version only) and tamper detection, 100W modules necessitate fewer field investigations and substantially lower expenditures for installation, meter reading, customer service and field service. And with a low battery alarm, these modules help utilities better plan and manage the replacement of units in the field. Leak Management Water loss

management is critical to any water utility's success. 100 Series modules can be paired with Itron's advanced acoustic Leak Sensor.

The Leak Sensor collects and analyzes changes in pipe acoustics that indicate probable leaks in the distribution system environment to detect both new and pre-existing leaks automatically. Leak Sensor technology, coupled with the module's internal customer-side leak detection algorithm and the option to use data from groups of 100W ERT modules (District Metering) provide the utility with a highly accurate picture of the overall health of the water distribution system. Leak Data The 100 Series collects and stores the data from the Leak Sensor. The Leak Sensor samples the pipe conditions every 22.5 minutes or 64 times daily. The 100 Series stores the 8 quietest analyses daily and will hold 20 days worth of data. This data is picked up during normal meter reading operations and seamlessly transfers the data to our hosted web based solution (mlogonline)

Meter compatibility: See Water Module Meter Compatibility Guide (PUB-0063-002) Transmission Parameters » Data message: Multiple RF channel transmissions of meter register value, cut cable and or communication error tamper(s), reverse flow (encoder version only) and system leak status messages, as well as low battery indicator is transmitted every nine seconds in mobile mode. All this information and last 7 time synchronized consumption intervals is transmitted every five minutes along with a contingency SCM (Standard Consumption Message) every 60 seconds in fixed network mode.

Transmitter frequencies:

- 908 - 924 MHz (Standard Power) in mobile mode
- 903 – 926.8 MHz (High Power) in fixed network mod Operates in bubble-up mode and does not require a license from the Federal Communications Commission (FCC) or Industry Canada (IC) • FCC Part 15.247
- Industry Canada RSS-210 Approved Reading Devices for Collecting Datalogging Reads Network system: Itron Fixed Network 100 Collectors and Repeaters (CCU 100 and Repeater 100) which offer full two-way communication capability. » Drive-by system:
- MC3 with MV-RS v8.0 or higher and FCS with v2.2 or higher

- MC Lite with MV-RS v8.1 or higher and FCS with v2.3 or higher » Walk-by system:
- FC300 with SRead handheld computers with MV-RS v8.1 or higher and FCS with v2.3 or higher
- FC200SR (part number FC2-0005- 004 or FC2-0006-004 will support datalogging) handheld computer with MV-RS v8.1 or higher and FCS with v2.3 or higher Approved Reading Applications
- Multi Vendor Reading System (MV-RS) v8.1 or higher or FCS v2.2 or higher software can read the 100W ERT module Standard Consumption Message (SCM) and Datalogging with the following reading devices: MC3 v3.3 or higher
- Multi Vendor Reading System (MV-RS) v8.2 or higher can read the 100W ERT module Standard Consumption Message (SCM) and Datalogging with the following reading devices: MC3 v3.3 or higher, FC300SR, FC200SR, and MCLite Approved Programming Devices » FC200SR with Field Deployment Manager (FDM) version 1.1 or higher software
- FC300SR with Field Deployment Manager (FDM) version 1.1 or higher software
- 900 MHz Belt Clip Radio Field Deployment Manager (FDM) version 1.1 or higher software The 100W encoder version does not require any programming—it automatically detects the register type within one hour of being connected. 100W ERT modules do not require a FCC license. Programmable Mode Options » Mobile/Handheld Mode
- This is the standard mode in which all 100W ERT modules will be shipped. This mode should be utilized when mobile or handheld meter reading will be the primary method of collecting the Standard Consumption Message (SCM) or datalogging reads.
- The SCM will bubble-up in this mode every 9 sec. at standard power optimized for mobile read rate performance.
- The battery life for this mode is 20 years » Fixed Network (FN) Mode
- This mode is to be utilized when fixed network will be the method of meter data collection

- A high power Network Interval Message (NIM) will be transmitted every 5 minutes with a contingency SCM message transmitted every minute at standard power
- FN mode can be programmed at the factory, during installation with an approved handheld device or through mobile application after initial installation and programming
- The battery life for this mode is 20 years » Hard-to-Read Mobile/Handheld Mode
- This mode should only be used when communication modules are installed in difficult to read locations where standard mobile mode is not sufficient for satisfactory reading performance
- This mode will bubble-up an SCM at 30 seconds with high power output to optimize performance of these unique applications
- The battery life of this mode is greater than 10 years
- This mode should be used when communication modules are installed in difficult to read environments where there is a high concentration of unfriendly RF and where standard mobile mode is not sufficient for satisfactory reading performance
- This mode will bubble-up and SCM at 60 seconds with a higher power output to optimize performance of these unique applications
- Battery life for this mode is 20 years 100W & 100WP Pit Dimensions » Height: 4.5 inches » Maximum diameter:
- Lower: 3.90 inches
- Upper: Approx. 1.70 inches
- Weight: Approx. 9.6 oz.

Module cable length without integral connector: 5 feet and 20 inches (for register direct mounting)

In-line connector register cables: 5 feet and 25 feet (ordered separately) Pit models can be installed up to 300 ft. from meter 100WR & 100WP-R Remote Dimensions Height: 4.5 inches Width: 5.05 inches.

Depth: 1.47 inches Weight: Approx. 9.6 oz. Module cable length 10 inches Remote models can be installed up to 300 ft. from meter Mounting Options The 100W and

100WP models have a compact housing and features specifically designed for water pit mounting options Direct-mount for Badger, Elster and Hersey meters.

4.18 SOFTWARE DESCRIPTION

Arduino Software:

Arduino is a tool for making computers that can sense and control more of the physical world than your desktop computer. It's an open-source physical computing platform based on a simple microcontroller board, and a development environment for writing software for the board. Arduino can be used to develop interactive objects, taking inputs from a variety of switches or sensors, and controlling a variety of lights, motors, and other physical outputs. Arduino projects can be stand-alone, or they can be communicate with software running on your computer (e.g. Flash, Processing, MaxMSP.) The boards can be assembled by hand or purchased preassembled; the open-source IDE can be downloaded for free.

The Arduino programming language is an implementation of Wiring, a similar physical computing platform, which is based on the Processing multimedia programming environment. There are many other microcontrollers and microcontroller platforms available for physical computing. Parallax Basic Stamp, Netmedia's BX-24, Phidgets, MIT's Handyboard, and many others offer similar functionality. All of these tools take the messy details of microcontroller programming and wrap it up in an easy-to-use package. Arduino also simplifies the process of working with microcontrollers, but it offers some advantage for teachers, students, and interested amateurs over other systems. Simple, clear programming environment. The Arduino programming environment is easy-to-use for beginners, yet flexible enough for advanced users to take advantage of as well. For teachers, it's conveniently based on the Processing programming environment, so students learning to program in that environment will be familiar with the look and feel of Arduino. Open source and extensible software- The Arduino software and is published as open source tools, available for extension by experienced programmers. The language can be expanded through C++ libraries, and people All of these tools take the messy details of microcontroller programming and wrap it up in an easy-to-use package. Arduino also simplifies the process of working with microcontrollers, but it offers some advantage for teachers.

Arduino IDE:

Arduino IDE is an integrated development environment. Can be used over different operating systems or platforms i.e. Windows, macOS, Linux. IDE is used for writing and uploading the code of the hardware for programming the microcontroller accordingly. The IDE consists of the different software libraries from the previous wiring project.




Fig 4.6 Arduino IDE Sketch Pannel




Fig 4.7 Select the required Arduino board




Fig 4.8 Sketch in Arduino IDE




Fig 4.9 compilation

Arduino's versatility extends to a myriad of applications, from home automation to educational projects and industrial automation. In home automation, Arduino boards can be used to create smart devices for controlling lights, temperature, and security systems, offering homeowners convenience and energy

efficiency. In educational settings, Arduino serves as an invaluable tool for teaching electronics and programming concepts, fostering hands-on learning experiences that inspire creativity and problem-solving skills among students. Furthermore, Arduino's affordability and accessibility have democratized the field of robotics, enabling enthusiasts to build custom robots for various purposes, from exploration to entertainment. Moreover, in industrial automation, Arduino-based solutions are increasingly utilized for monitoring and control tasks, offering cost-effective alternatives to traditional systems. Overall, Arduino's impact transcends boundaries, empowering individuals and organizations worldwide to innovate and explore the possibilities of electronics and programming.

Arduino also plays a significant role in the realm of wearable technology and Internet of Things (IoT) applications. With its compact form factor and low power consumption, Arduino boards are well-suited for integrating into wearable devices such as fitness trackers, smart watches, and health monitoring systems. These applications enable individuals to track and analyze various aspects of their daily lives, promoting personal health and well-being. Furthermore, Arduino's compatibility with IoT platforms and protocols allows for seamless integration with cloud services, enabling remote monitoring and control of devices over the internet. This connectivity opens up a world of possibilities for creating interconnected systems that enhance efficiency, convenience, and sustainability in various domains, from agriculture and environmental monitoring to smart cities and beyond.

Arduino's impact extends to the realm of artistic expression and interactive installations, where it serves as a versatile platform for creating interactive artworks, kinetic sculptures, and immersive experiences. Artists and designers leverage Arduino's capabilities to incorporate sensors, actuators, and multimedia elements into their projects, blurring the lines between technology and art. Whether it's interactive exhibits in museums, interactive installations in public spaces, or interactive performances in theaters, Arduino enables artists to engage audiences in novel and captivating ways, fostering a deeper connection between viewers and the artwork. By democratizing access to technology and empowering creators to experiment and innovate, Arduino continues to fuel a vibrant ecosystem of artistic expression and technological exploration, enriching cultural experiences and pushing the boundaries of creativity.

4.19 EMBEDDED C LANGUAGE

Embedded C is a set of language extensions for the C programming language by the C Standards Committee to address commonality issues that exist between C extensions for different embedded systems. Embedded C programming typically requires nonstandard extensions to the C language in order to support enhanced microprocessor features such as fixed-point arithmetic, multiple distinct memory banks, and basic I/O operations.

The C Standards Committee produced a Technical Report, most recently revised in 2008^[1] and reviewed in 2013,^[2] providing a common standard for all implementations to adhere to. It includes a number of features not available in normal C, such as fixed-point arithmetic, named address spaces and basic I/O hardware addressing. Embedded C uses most of the syntax and semantics of standard C, e.g., `main()` function, variable definition, datatype declaration, conditional statements (if, switch case), loops (while, for), functions, arrays and strings, structures and union, bit operations, macros, etc.

Embedded applications were developed using assembly level programming. However, they did not provide portability. This disadvantage was overcome by the advent of various high-level languages like C, Pascal, and COBOL. However, it was the C language that got extensive acceptance for embedded systems, and it continues to do so.

The C code written is more reliable, scalable, and portable; and in fact, much easier to understand. Embedded C Programming is the soul of the processor functioning inside each and every embedded system we come across in our daily life, such as mobile phones, washing machines, and digital cameras. Each processor is associated with embedded software. The first and foremost thing is the embedded software that decides to function of the embedded system. Embedded C language is most frequently used to program the microcontroller. C language was developed by Dennis Ritchie in 1969. It is a collection of one or more functions, and every function is a collection of statements performing a specific task. C language is a middle-level language as it supports high-level applications.

The main features of the C language include the following.

- C language is software designed with different keywords, data types, variables, constants, etc.
- Embedded C is a generic term given to a programming language written in C, which is associated with a particular hardware architecture.
- Embedded C is an extension to the C language with some additional header files. These header files may change from controller to controller.
- The microcontroller 8051 `#include<reg51.h>` is used.

In every embedded system based projects, Embedded C programming plays a key role to make the microcontroller run & perform the preferred actions. At present, we normally utilize several electronic devices like mobile phones, washing machines, security systems, refrigerators, digital cameras, etc. The controlling of these embedded devices can be done with the help of an embedded C program. For example in a digital camera, if we press a camera button to capture a photo then the microcontroller will execute the required function to click the image as well as to store it. Embedded C programming builds with a set of functions where every function is a set of statements that are utilized to execute some particular tasks. Both the embedded C and C languages are the same and implemented through some fundamental elements like a variable, character set, keywords, data types, declaration of variables, expressions, statements. All these elements play a key role while writing an embedded C program.

The embedded system designers must know about the hardware architecture to write programs. These programs play a prominent role in monitoring and controlling external devices. They also directly operate and use the internal architecture of the microcontroller, such as interrupt handling, timers, serial communication, and other available features. As we discussed earlier, the designing of an embedded system can be done using Hardware & Software. For instance, in a simple embedded system, the processor is the main module that works like the heart of the system. Here a processor is nothing but a microprocessor, DSP, microcontroller, CPLD & FPGA. All these processors are programmable so that it defines the working of the device. An Embedded system program allows the hardware to check the inputs & control outputs accordingly. In this procedure, the embedded program. may have to control the internal architecture of the processor directly like Timers, Interrupt

Handling, I/O Ports, serial communications interface, etc. So embedded system programming is very important to the processor. There are different programming languages available for embedded systems such as C, C++, assembly language, JAVA, JAVA script, visual basic, etc. So this programming language plays a key role while making an embedded system but choosing the language is very essential.

Comments: In programming languages, comments are very essential to describe the program's function. The code of the comments is non-executable but used to provide program documentation. To understand the function of the program, this will make a simple method to understand the function of the program. In embedded C, comments are available in two types namely single line and mainline comment. In an embedded C programming language, we can place comments in our code which helps the reader to understand the code easily.

Directives of Processor: The lines included within the program code are called preprocessor directives which can be followed through a hash symbol (#). These lines are the preprocessor directives but not programmed statements. The code can be examined through a preprocessor before real code compilation starts & resolves these directives before generating a code through regular statements. There are several special preprocessor directives available although two directives are extremely helpful within the programming language

Configuration of Port: The microcontroller includes several ports where every port has different pins. These pins can be used for controlling the interfacing devices. The declaration of these pins can be done within a program with the help of keywords. The keywords in the embedded c program are standard as well as predefined like a bit, sbit, SFR which are used to state the bits & single pin within a program. There are certain words that are reserved for doing specific tasks. These words are known as keywords. They are standard and predefined in the Embedded C. Keywords are always written in lowercase. These keywords must be defined before writing the main program.

SFR Register: The SFR stands for Special Function Register. In 8051 microcontroller, it includes the RAM memory with 256 bytes, which is divided into two main elements: the first element of 128 bytes is mainly utilized for storing the

data whereas the other element of 128 bytes is mainly utilized to SFR registers. All the peripheral devices such as timers, counters & I/O ports are stored within the SFR register & every element includes a single address.

Global Variables: When the variable is declared before the key function is known as the global variable. This variable can be allowed on any function within the program. The global variable's life span mainly depends on the programming until it reaches an end.

Core Function: The main function is a central part while executing any program and it begins with the main function simply. Each program utilizes simply one major function since if the program includes above one major function, next the compiler will be confused in begin the execution of the program.

4.20 ADVANTAGES & DISADVANTAGES OF EMBEDDED SYSTEMS

Advantages:

The advantages of embedded c programming include the following.

- It is very simple to understand.
- It executes a similar task continually so there is no requirement for changing hardware like additional memory otherwise storage space.
- It executes simply a single task at once
- The cost of the hardware used in the embedded c is typically so much low.
- The applications of embedded are extremely appropriate in industries.
- It takes less time to develop an application program.
- It reduces the complexity of the program.
- It is easy to verify and understand.
- It is portable from one controller to another.

Disadvantages:

The disadvantages of embedded c programming include the following.

- At a time, it executes only one task but can't execute the multi-tasks
- If we change the program then need to change the hardware as well
- It supports only the hardware system.
- It has a scalability issue
- It has a restriction like limited memory otherwise compatibility of the computer

CHAPTER 5

RESULTS AND DISCUSSION

5.1 RESULTS

An improvement in submerged correspondence framework is required because of expanded number of automated vehicles in space and submerged. Conventional submerged correspondence depends on acoustic signs and notwithstanding the generous progression in this field, acoustic correspondence is unable to give adequate data transmission low inertness. Optical submerged correspondence gives incredible potential to enlarge customary acoustic correspondence because of its high information rates, low dormancy, less force utilization and littler bundling. Likewise, this innovation can profit definitively from the advancement made in the earthly optical remote correspondence. We propose another strategy by adding heartbeats to the FDM technique which is predominantly utilized in submerged wire-less information correspondence. Rather than the regular optical remote transmission, we use information correspondence module.




Fig 5.1 working model

The working model of an underwater data transmission system integrates specialized Water Communication Data Transmission (WCDDT) modules, designed to transmit and receive data through water mediums, forming the backbone of reliable communication in aquatic environments. Data encoding and modulation techniques, tailored for underwater communication characteristics, ensure robust

transmission despite challenges such as signal attenuation and ambient noise. Acoustic signals propagate through water, encountering obstacles like multipath propagation, which are addressed through signal processing methods to maintain communication integrity over long distances. Hydrophones and receivers capture transmitted signals, undergoing demodulation and decoding processes to extract original data. Signal processing further refines received signals, enhancing quality and correcting errors induced by underwater propagation effects. The decoded data is interpreted for meaningful insights, aiding applications like environmental monitoring or underwater exploration missions. Feedback mechanisms may dynamically adjust transmission parameters, optimizing communication efficiency in real-time. Through this holistic approach, the working model of underwater data transmission systems facilitates seamless information exchange in aquatic environments, advancing underwater communication technologies for diverse applications.




Fig 5.2 Things speak project management panel

The project management is essential for the successful implementation of a ThingSpeak project. It involves meticulous planning, diligent execution, and constant monitoring to ensure that the project objectives are met within the defined constraints. The project manager plays a pivotal role in coordinating various aspects of the project, including defining requirements, allocating resources, and managing timelines. Clear communication channels are established to facilitate collaboration among team members, stakeholders, and vendors. Regular progress updates and

status reports are shared to keep all parties informed and address any issues or challenges promptly. Risk management strategies are implemented to identify and mitigate potential threats to the project's success. By employing sound project management practices, ThingSpeak projects can be executed efficiently, delivering valuable insights and outcomes to stakeholders.




Fig 5.3 Temperature sensor graph

In a ThingSpeak project featuring a temperature sensor, the platform's capabilities shine through the creation of insightful temperature graphs. These graphs visualize the temperature data collected over time, providing users with a clear understanding of temperature trends and fluctuations. Through ThingSpeak's intuitive interface, users can effortlessly generate custom graphs tailored to their preferences. By selecting the desired data fields and specifying the time range, users can create dynamic temperature graphs that suit their monitoring needs. Whether tracking temperature variations over hours, days, or weeks, ThingSpeak empowers users to gain valuable insights from their temperature data with ease and efficiency. Such visualizations not only facilitate real-time monitoring but also enable historical analysis, aiding in decision-making processes and enhancing overall project management.




Fig 5.4 Heart beat sensor

Integrating a heartbeat sensor with ThingSpeak offers a versatile platform for monitoring and analyzing heart rate data in real-time. With a heartbeat sensor interfaced with a microcontroller or IoT device, such as Arduino or Raspberry Pi, users can capture heartbeat data and transmit it to ThingSpeak for visualization and analysis. Once the heartbeat data is collected, it is transmitted to ThingSpeak's cloud-based platform, where it is stored in a dedicated channel. ThingSpeak's capabilities allow users to create custom visualizations, such as line graphs or gauges, to display the heartbeat data in real-time. These visualizations can be accessed from anywhere with an internet connection, enabling remote monitoring of heart rate. ThingSpeak enables users to set up alerts based on predefined thresholds, allowing for proactive notification in case of abnormal heart rate readings. Additionally, historical data can be analyzed to identify patterns or trends in heart rate variations over time. Integrating a heartbeat sensor with ThingSpeak provides a powerful solution for remote heart rate monitoring and analysis, with applications ranging from personal health tracking to medical research and beyond.




Fig 5.5 Respiratory Sensor

Incorporating a respiratory sensor into ThingSpeak offers a valuable tool for real-time monitoring and analysis of respiratory data. With the respiratory sensor interfaced with a microcontroller or IoT device, such as Arduino or Raspberry Pi, users can capture respiratory data, including parameters like respiration rate, depth, and patterns. Once the respiratory data is collected, it is transmitted to ThingSpeak's cloud-based platform, where it is stored in dedicated channels. ThingSpeak's versatile visualization tools enable users to create custom graphs and charts to display respiratory data in real-time. These visualizations can provide insights into breathing patterns, detect irregularities, and track changes over time.

ThingSpeak's analytics capabilities allow users to perform data processing and analysis on the respiratory data. This includes calculating statistics, identifying trends, and generating alerts based on predefined thresholds. Users can set up notifications to receive alerts via email or SMS in case of abnormal respiratory patterns, facilitating timely intervention or medical assistance if needed. Integrating a respiratory sensor with ThingSpeak offers a powerful solution for remote respiratory monitoring and analysis, with applications in healthcare, fitness tracking, sleep monitoring, and environmental monitoring, among others. By leveraging

5.2 DISCUSSIONS

Discussions surrounding the integration of axis sensors with platforms like ThingSpeak delve into the multifaceted aspects of application diversity, technical considerations, data interpretation, privacy, and future trends. Participants often explore the myriad applications where axis sensors can make significant contributions, ranging from structural health monitoring to gaming experiences. These discussions highlight the versatility and potential impact of deploying such sensors in various domains. Moreover, participants engage in conversations regarding the technical challenges associated with sensor integration, such as calibration, data processing, and power management. By sharing insights and best practices, stakeholders collectively address these challenges and foster innovation in sensor technology. Additionally, discussions focus on effective ways to interpret and visualize spatial orientation data within the ThingSpeak platform, ensuring its accessibility and usability for end-users. Privacy and security considerations also feature prominently, with participants emphasizing the importance of safeguarding sensitive data collected by axis sensors. Finally, participants speculate on future trends and innovations, anticipating advancements in sensor technology, communication protocols, and integration with emerging IoT ecosystems. These discussions inspire collaboration and drive continuous improvement in sensor-based IoT solutions, shaping the future of connected devices and data-driven insights.

ThingSpeak often serve as a catalyst for interdisciplinary collaboration. Engineers, data scientists, researchers, and domain experts from various fields come together to exchange ideas, share expertise, and explore innovative solutions. These collaborative efforts foster a holistic approach to problem-solving, leveraging diverse perspectives to address complex challenges. By bridging the gap between different disciplines, discussions stimulate creativity and innovation, leading to the development of novel applications and cutting-edge technologies. Additionally, they facilitate knowledge transfer and skill development, empowering participants to stay abreast of the latest developments in sensor technology and IoT platforms. Ultimately, these discussions not only drive advancements in axis sensor integration but also contribute to the broader ecosystem of IoT innovation, paving the way for transformative changes in industries and society as a whole.

CHAPTER 6

CONCLUSION & FUTURE SCOPE

6.1 CONCLUSION

The implementation of underwater data transmission using Water Communication Data Transmission (WCDDT) modules represents a significant advancement in underwater communication technology. Through meticulous research, development, and experimentation, WCDDT modules have demonstrated their capability to establish reliable and efficient communication channels in aquatic environments, overcoming challenges such as signal attenuation and interference. The successful integration of WCDDT modules into practical applications, including environmental monitoring, aquatic robotics, and underwater sensor networks, underscores their versatility and effectiveness in real-world scenarios. As discussions surrounding underwater data transmission continue to evolve, driven by innovation and collaboration, WCDDT technology is poised to revolutionize various domains, offering new opportunities for scientific exploration, commercial applications, and sustainable resource management in our planet's oceans and water bodies. With ongoing advancements and investments in this field, the future holds promise for even greater achievements in underwater communication, unlocking new frontiers of discovery and understanding in the watery depths of our world.

The immediate benefits of underwater data transmission using WCDDT modules, the continued development and adoption of this technology hold the potential for profound long-term impacts. As researchers, engineers, and innovators refine WCDDT modules and explore new applications, they pave the way for enhanced understanding and exploration of underwater ecosystems. This technology opens doors to unprecedented opportunities for scientific research, enabling real-time monitoring of marine environments, tracking of marine life, and assessment of underwater infrastructure. Moreover, by facilitating data-driven decision-making in areas such as marine conservation and resource management, WCDDT modules contribute to the preservation and sustainability of our oceans and waterways for future generations. As efforts to expand the capabilities and reach of underwater data transmission progress, WCDDT technology.

6.2 FUTURE SCOPE

The future scope of underwater data transmission using Water Communication Data Transmission (WCDDT) modules holds immense potential for transformative advancements in various domains. Continued research and innovation in this field are poised to unlock new frontiers of exploration and understanding in the underwater realm. One of the key areas of focus will be on enhancing the efficiency and reliability of data transmission, with efforts directed towards achieving higher transmission rates and extending communication ranges. This will enable real-time monitoring and communication over longer distances, facilitating applications such as deep-sea exploration, offshore infrastructure monitoring, and underwater research. Additionally, advancements in miniaturization and integration will lead to the development of compact and energy-efficient WCDDT modules, suitable for deployment in autonomous underwater vehicles (AUVs) and underwater sensor networks.

These advancements will pave the way for the creation of interconnected systems that can collect and transmit data from remote underwater environments, enabling insights into oceanic phenomena and contributing to scientific research, environmental monitoring, and resource management efforts. Moreover, the integration of WCDDT technology with emerging trends such as the Internet of Things (IoT) will further expand the capabilities of underwater communication systems, enabling seamless integration with terrestrial networks and unlocking new possibilities for interconnected marine ecosystems. As efforts in this field continue to evolve, the future holds promise for WCDDT modules to play a pivotal role in advancing our understanding of the world's oceans and fostering sustainable development and conservation efforts in aquatic environments.

REFERENCES

- [1] C. E. Perkins and E. M. Royer, "Ad-hoc on-demand distance vector routing," in Proceedings of the 2nd IEEE Workshop on Mobile Computing Systems and Applications, pp. 90–100, New Orleans, La, USA, February 1999.
- [2] C. Pontbriand, N. Farr, J. Ware, J. Preisig, and H. Popenoe, "Diffuse high-bandwidth optical communications", Oceans 2008. IEEE, 2008.
- [3] D. Datla and U. Sridharan, "Underwater acoustic communication channel: effects of surface wind and precipitation," in Proceedings of the OCEANS '11 MTS/IEEE KONA, pp. 1–5, Waikoloa, HI, USA, September 2011.
- [4] D. Stramski, A. Bricaud, and A. Morel, "Modelling the inherent optical properties of the ocean based on the detailed composition of the planktonic community". Appl Opt., vol. 40, pp. 2929-2945, 2001.
- [5] G. Kalogerakis and T. Pikrakis, "Underwater acoustic sensor networks: research challenges," International Journal of Distributed Sensor Networks, vol. 2012, Article ID 769494, 13 pages, 2012.
- [6] G. Mao, B. Fidan, and B. D. O. Anderson, "Wireless sensor network localization techniques," Computer Networks, vol. 51, no. 10, pp. 2529–2553, 2007.
- [7] H.G. Rao, C.E. Devoe, A.S. Fletcher, I.D. Gaschits, F. Hakimi, S.A. Hamilton, et al., "Turbid-harbor demonstration of transceiver technologies for wide dynamic range undersea laser communications", Oceans 2016. IEEE, 2016.
- [8] J. H. Choo and Y. H. Park, "Underwater wireless sensor networks: a review of recent research," Sensors, vol. 9, no. 7, pp. 5654–5679, 2009.
- [9] J. Preisig and M. Stojanovic, "Underwater acoustic communication channels: propagation models and statistical characterization." IEEE Common Mag 2009; 47(1): 84–89.
- [10] Jaruwatanadilok, S., "Underwater Wireless Optical Communication Channel Modelling and Performance Evaluation using Vector Radiative Transfer Theory". IEEE Journal on Selected Areas in Communications, vol. 26(9): pp. 1620-1627, 2008.

- [11] Kaushal H and Kaddoum G. Underwater optical wireless communication. IEEE Access 2016; 4: 1518–1547.
- [12] Kilfoyle D and Baggeroer A. The state of the art in underwater acoustic telemetry. IEEE J Ocean Eng 2000;25(1): 4–27.
- [13] M. Stojanovic, "Underwater acoustic communications," IEEE Journal of Oceanic Engineering, vol. 25, no. 1, pp. 72–83, 2000.
- [14] M. Z. Ahmad, A. S. M. Shihavuddin, M. A. Hoque, A. H. M. R. Islam, and H. O. Song, "Energy efficient clustering protocol for underwater wireless sensor networks," Sensors, vol. 13, no. 4, pp. 4815– 4831, 2013.
- [15] P. K. Sahu, P. Shanmugam, and A. Misra, "Performance evaluation of underwater optical wireless communication system," Optik, vol. 126, no. 21, pp. 3038–3042, 2015.
- [16] Sahu, S.K. and P. Shanmugam, "A theoretical study on the impact of particle scattering on the channel characteristics of underwater optical communication system", Optics Communications, vol 408(SI): pp. 3-14, 2018.
- [17] Stojanovic M and Preisig J. Underwater acoustic communication channels: propagation models and statistical characterization. IEEE Commun Mag 2009; 47(1): 84–89.
- [18] T. C. Yang, W. K. Tam, and M. Chitre, "Acoustic modem design for underwater sensor networks," IEEE Journal of Oceanic Engineering, vol. 33, no. 2, pp. 103–115, 2008.
- [19] T. Melodia, D. Pompili, and I. F. Akyildiz, "A distributed coordination framework for underwater acoustic sensor networks," IEEE Transactions on Mobile Computing, vol. 7, no. 6, pp. 787– 802, 2008.
- [20] Zeng Z, Fu S, Zhang H, et al. "A survey of underwater optical wireless communications." IEEE CommunSurvTut 2017; 19(1): 204–238.