

AN INTERDISCIPLINARY AND SYSTEMATIC APPROACH FOR GEOGRAPHICAL DEEP FOREST ROUTE OF COMMUNICATIONS

Submitted in partial fulfillment of the requirements for the award of Bachelor of
Engineering Degree in Electronics and Communication Engineering

by

G. SHANMUKHA SRINIVAS (40130064)

HARIHARAN V (40130076)



**DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING
SCHOOL OF ELECTRICAL AND ELECTRONICS**

SATHYABAMA

**INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)**

CATEGORY -1 UNIVERSITY BY UGC

**Accredited with Grade "A++" by NAAC | 12B Status by UGC | Approved by AICTE
JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI – 600119**

APRIL - 2024



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)

Accredited "A++" Grade by NAAC | 12B Status by UGC | Approved by AICTE
www.sathyabama.ac.in

DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of **HARIHARAN V (40130076)**, **G.SHANMUKHA SRINIVAS (40130064)** who carried out the project entitled **"AN INTERDISCIPLINARY AND SYSTEMATIC APPROACH FOR GEOGRAPHICAL DEEP FOREST ROUTE OF COMMUNICATIONS"** under our supervision from November 2023 to April 2024.

Internal Guide

Dr. E. ANNA DEVI, M.E., Ph.D.,

Head of the Department

Dr. T. RAVI, M.E., Ph.D.,

Submitted for Viva voce Examination held on 17.04.2024

Internal Examiner
External Examiner

DECLARATION

We HARIHARAN V and G. SHANMUKHA SRINIVAS hereby declare that the Project Report entitled "AN INTERDISCIPLINARY AND SYSTEMATIC APPROACH FOR GEOGRAPHICAL DEEP FOREST ROUTE OF COMMUNICATIONS" done by us under the guidance of Dr. E. ANNA DEVI, M.E., Ph.D., Department of Electronics and Communication Engineering, SATHYABAMA INSTITUTE OF SCIENCE AND TECHNOLOGY, CHENNAI, is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in ELECTRONICS AND COMMUNICATION ENGINEERING.

DATE: 17-04-2024

PLACE: Chennai

SIGNATURE OF THE CANDIDATES:

1. V. Hariharan
2. G. Shanmukh Srinivas .

ACKNOWLEDGEMENT

We are pleased to acknowledge our sincere thanks to the **Board of Management of SATHYABAMA INSTITUTE OF SCIENCE AND TECHNOLOGY** for their kind encouragement in doing this project and for completing it successfully. I am grateful to them.

We convey our sincere thanks to **Dr. N. M. NANDHITHA M.E., Ph.D., Dean, School of Electrical and Electronics Engineering** and **Dr. T. RAVI M.E., Ph.D., Head of the Department, Department of Electronics and Communication Engineering** for providing me necessary support and details at the right time during the progressive reviews.

We would like to express our sincere and deep sense of gratitude to my Project Guide **Dr. E. ANNA DEVI M.E., Ph.D.,** for her valuable guidance, suggestions and constant encouragement paved way for the successful completion of my project work.

We wish to express our thanks to all Teaching and Non-teaching staff members of the **Department of Electronics and Communication Engineering** who were helpful in many ways for the completion of the project.

ABSTRACT

Wireless Underground Sensor Networks (WUSNs) constitute one of the promising application areas of the recently developed wireless sensor networking techniques. WUSN is a specialized kind of WSN that mainly focuses on the use of sensors at the subsurface region of the soil. For a long time, this region has been used to bury sensors, usually targeting irrigation and environment monitoring applications, although without wireless communication capability; WUSNs promise to fill this gap and to provide the infrastructure for novel applications. The underground wireless channel was only available recently. COMMUNICATION through the underground medium has been a challenging research area. The applications require the deployment of sensors below the ground surface. Hence, the sensor become part of the sensed environment and might deliver more precise sensing. We send data through the Soil communication Medium based on Magnetic Rod Flux. We using Arduino RISC mechanism.

TABLE OF CONTENTS

CHAPTER No.	TITLE	PAGE No.
	ABSTRACT	V
	LIST OF ABBREVIATIONS	IX
	LIST OF FIGURES	X
	LIST OF TABLES	XI
1	INTRODUCTION	1
	1.1 NEED OF THE PROJECT	2
2	LITERATURE SURVEY	3
3	AIM AND SCOPE OF THE EXISTING DESIGN	
	3.1 AIM OF THE PROJECT	5
	3.2 FUTURE SCOPE OF THE PROJECT	6
4	METHODOLOGY AND ALGORITHM USED	
	4.1 BLOCK DIAGRAM	7
	4.1.1 Transmitter Section	7
	4.1.2 Receiver Section	8
	4.2 EXISTING SYSTEM	9
	4.3 PROPOSED SYSTEM	9
	4.4 OVERVIEW OF EMBEDDED SYSTEM	10
	4.5 BLOCK DIAGRAM OF EMBEDDED SYSTEM	11
	4.6 CHARACTERISTICS OF EMBEDDED	12

	SYSTEM	
	4.6.1 Application Specific Systems	12
	4.6.2 Reactive Systems	13
	4.6.3 Heterogeneous Architectures	13
	4.6.4 Harsh Environment	14
	4.6.5 Small and Low Weight	15
4.7	INTRODUCTION OF EMBEDDED SYSTEM	16
	4.7.1 Design of Embedded System	17
	4.7.2 Classification of Embedded System	18
4.8	HARDWARE COMPONENTS	19
	4.8.1 PIC Microcontroller	19
	4.8.1.1 Pin Diagram of PIC16F877A	22
	4.8.1.2 Instruction Sets in PIC16F877A	29
	4.8.1.3 Block Diagram of PIC	31
	4.8.2 Stepdown Transformer	33
	4.8.3 Emergency Button	33
	4.8.4 Flame Sensor Module	34
	4.8.5 PIR Sensor Module	36
	4.8.6 WUSN Module	40
	4.8.7 ESP8266 Node MCU Wifi Module	41
5	RESULTS AND DISCUSSION	
5.1	FIRE DETECTION PROCESS	42
5.2	PIR SENSOR DETECTION PROCESS	43

	5.3	DATA'S ARE STORED IN THE CLOUD	44
	5.4	FINAL OVERALL MODEL OF THE TRANSMITTER AND RECEIVER	45
6		CONCLUSION	
	6.1	CONCLUSION	46
	6.2	STANDARDS	46
	6.3	CONSTRAINTS	47
	6.4	TRADE-OFFS	48
		REFERENCES	49
		APPENDIX	50

LIST OF ABBREVIATIONS

UART	UNIVERSAL ASYNCHRONOUS RECEIVER / TRANSMITTER
ADC	ANALOG TO DIGITAL CONVERTER
DAC	DIGITAL TO ANALOG CONVERTER
SPI	SERIAL PERIPHERAL INTERFACE
IOT	INTERNET OF THINGS
GPIO	GENERAL PURPOSE INPUT/OUTPUT

LIST OF FIGURES

FIGURE NO	NAME OF THE FIGURE	PAGE NO
4.1	Block Diagram of Transmitter	7
4.2	Block Diagram of Receiver	8
4.3	Block Diagram of a typical embedded Systems	12
4.4	Embedded Systems having Heterogeneous Architectures	14
4.5	Embedded Product Development Cycle Life	17
4.6	Basic Circuit for the PIC16F877A	21
4.7	Pin diagram of PIC16F877A	23
4.8	Block diagram of PIC16F877A	32
4.9	Emergency Button	33
4.10	Flame Sensor Module	34
4.11	PIR Sensor Module Working Mechanism	38
4.12	PIR Sensor Module	39
4.13	Schematic diagram of PIR	39
4.14	Internal Schematic of PIR	40
4.15	WUSN Module	40
4.16	Node MCU Wi-Fi Module	41
5.1	Fire detection process	42
5.2	PIR sensor detection process	43
5.3	Data's are stored in the cloud	44
5.4	Final overall model transmitter and receiver	45

LIST OF TABLES

TABLE NO	TABLE NAME	PAGE NO
4.1	REGISTER FILE MAPS USED IN PIC16F877A	29
4.2	INSTRUCTION SETS IN PIC16F877A	32

CHAPTER-1

INTRODUCTION

Agricultural information has several data representation forms, including text (temperature, humidity), video (video surveillance of agricultural environment), How to rapidly acquire and wirelessly transmit multi-service agricultural information is an essential prerequisite for sustainable development of precision agriculture. Currently existing agricultural information acquisition devices used in precision agriculture have many varieties and various input/output interfaces; however, these data acquisition devices usually have a single function and are lack of the scalability of device interconnection, so they cannot collect the multi-service agricultural information at the same time. Furthermore, because of diversity of hardware interface and complexity of software structure, agricultural information acquisition devices are of low multi-function and integration, which results in the devices subject to great restriction in cost and application range. Text-form information acquisition devices can be used to collect low-volume data, such as data from temperature, humidity and gas concentration.

The output data can be classified as analog and digital according to the formats of their signal outputs. Analog signal sensors convert acquired analog signal such as voltage or current using ADC (Analog Digital Converter) to digital signal, and then get the digital output; however, these sensors usually need to be calibrated in each specific applications to meet the requirement of accuracy. Digital signal sensors can directly output digital parameters through serial interfaces such as SPI, UART and I2C. Audio acquisition devices use microphone module to collect analog audio signal, and output the digital signal after sampling signal and quantization]. The quality of audio depends on types of microphone module. Image/video acquisition devices employ microcontrollers or embedded systems with CCD or CMOS video sensor to collect video data, and then get the digital output. Sensor networks are currently a very active area of research.

The richness of existing and potential applications from commercial agriculture and geology to security and navigation has stimulated significant attention to their capabilities for monitoring various underground conditions. In particular, agriculture uses underground sensors to monitor soil conditions such as water and mineral content. Sensors are also successfully used to monitor the integrity of belowground infrastructures such as plumbing [32], and landslide and earthquake monitoring are accomplished using buried seismometers.

1.1 NEED OF THE PROJECT

In this project data is transferred through the soil without any hazards. Transferring data through the soil using low frequency. Therefore, the most important goals in fire surveillance are quick and reliable detection of fire. It is so much easier to suppress fire while it is in its early stages. The area of the forest is large, it is far away from urban area network coverage. It is a challenge for the communication between sensors and receivers to exchange data. RF transmission is not possible under the ground instead of that I am using WUSN networks to send the Data to communicate through the Receiver side.

CHAPTER 2

LITERATURE SURVEY

In 2019, Hamad ache Zemmour and Genevieve Baudoin et al. [1] Wireless Underground Sensor Networks (WUSN) consists of buried sensors nodes which are expected to communicate through the soil. The significantly high attenuation caused by the soil properties is the main challenge for their feasibility. This challenge is accentuated with Impulse Radio Ultra-Wide Band (IR-UWB) WUSN because of the very low transmitted power. This paper first studies the impact of the soil on performances of a new small UWB buried antenna and then analyzes the effect of soil properties on the communication link from underground to aboveground. This study includes the effect of soil moisture, burial depth and frequency. Measurements are achieved in a sample of soil composed of standard pebbles used in railway (railroad ballast). The simulations and measurements results show that with short distances and low soil moisture underground to aboveground UWB communication is possible.

In 2018, Dan Du and Heng Zhang et al. [2] Wireless Underground Sensor Network (WUSN) is an emerging research area. They are used in many fields from intelligent irrigation to safety and assisted navigation [1]. Wireless underground sensor networks (WUSN) also enable a wide variety of novel applications [2], [3], including soil condition monitoring, earthquake and landslide prediction, underground infrastructure monitoring, sports-field turf management, landscape management, border patrol and security, and etc.

In 2020, Hamadache Zemmour; Genevieve Baudoin; Antoine Diet et al. [3] Wireless underground sensor networks (WUSNs) are an emerging area of research. They are used in many applications from intelligent irrigation to security and assisted navigation. WUSNs mainly use narrowband systems working in the frequency range below 1 GHz and, therefore, suffer from a poor localization capability and large-sized antennas.

In 2021, Erich P. Stuntebeck; Dario Pompili; Tommaso Melodia et al. [4] The concept of a wireless underground sensor network (WUSN) is introduced and applications are discussed. The feasibility of utilizing commonly available terrestrial wireless sensor network (WSN) hardware solutions in the underground environment is examined. Experiments are run to examine the packet error rate and the received signal strength of correctly received packets for a communication link between two underground sensors and between an underground sensor and an aboveground sensor.

CHAPTER 3

AIM & SCOPE

3.1 AIM OF THE PROJECT

Forest fires are a great barrier to ecologically healthy grown forests. Back in the day, everyone concentrated on farming and growing plants in their immediate surroundings. However, due to their hectic schedules, no one has time to focus on these topics in our current situation. As a result, a lack of nutrition will lead to an unhealthy plant.

To Anti-Poaching of Animals through the sense of the PIR. WUSN is a specialized kind of WSN that mainly focuses on the use of sensors at the subsurface region of the soil.

For a long time, this region has been used to bury sensors, usually targeting irrigation and environment monitoring applications, although without wireless communication capability WUSNs promise to fill this gap and to provide the infrastructure for novel applications. The underground wireless channel was only available recently.

Communication through the underground medium has been a challenging research area. The applications require the deployment of sensors below the ground surface. Hence, the sensor becomes part of the sensed environment and might deliver more precise sensing.

3.2 FUTURE SCOPE

In recent times, with the advent of the new technical concepts such as sensor-cloud technology, big-data analytics, internet of things (IoT), new applications are envisioned. We briefly describe such concepts, and enlist a few potential futuristic applications. Sensor-cloud computing: Sensor-cloud computing refers to the on-field WSN applications empowered with cloud computing.

This integrated framework benefits the WSNs with improved processing power and storage capacity. Furthermore, sensor-cloud improves the data management and access control while increasing the resource utilization.

CHAPTER 4

METHODOLOGY & ALGORITHM USED

4.1 BLOCK DIAGRAM

4.1.1. Transmitter section




Fig:4.1 Transmitter Block Diagram

The proposed system consists of pic microcontroller, flame sensor, pir sensor emergency button wusn transmitter module, uart communication protocol and a magnetic rod which generates magnetic flux for data transmission.

4.1.2 Receiver Section




Fig:4.2 Receiver Block Diagram

The proposed system consists of pic microcontroller, signal processing section, decoder section, uart communication protocol, and a graphical user interface through which forest officials can collect data and incident happening over deep area of forest.

4.2 EXISTING SYSTEM

- a. Human effect
- b. Air communications
- c. Insecure communication
- d. Harmful radiation
- e. High level rate consumption.
- f. Crime, identity theft, hacking, viruses.
- g. With access to billions of computers, computer hackers and malicious users can hack accounts and steal personal information that could be used for identity theft.
- h. The Internet also connects all computers, so hackers can scan millions of computers and quickly identify what computers are vulnerable to attack.
- i. Hidden places also exist on the Internet and the deep web for criminals to conduct business without as much fear of being caught. A global audience also gives criminals more ways to solicit their goods. The Internet also enables students to cheat on their studies or find others on the Internet to do their homework.

4.3 PROPOSED SYSTEM

In this project data is transferring through the soil without any hazards. Transferring data through the soil using low frequency. RF transmission is not possible under the ground instead of that I am using WUSN networks send the Data to communicate through the Receiver side. In this project data is transferred through the soil without any hazards. Transferring data through the soil using low frequency. Therefore, the most important goals in fire surveillance are quick and reliable detection of fire. It is so much easier to suppress fire while it is in its early stages. The area of the forest is large, it is far away from urban area network coverage. It is a challenge for the communication between sensors and receivers to exchange data. RF transmission is not possible under the ground instead of that I am using WUSN networks to send the Data to communicate through the Receiver side.

4.4 OVERVIEW OF EMBEDDED SYSTEMS

An embedded system is a special-purpose computer system designed to perform one or a few dedicated functions, often with real-time computing constraints. It is usually embedded as part of a complete device including hardware and mechanical parts. In contrast, a general-purpose computer, such as a personal computer, can do many different tasks depending on programming. Embedded systems have become very important today as they control many of the common devices we use. Since the embedded system is dedicated to specific tasks, design engineers can optimize it, reducing the size and cost of the product, or increasing the reliability and performance. Some embedded systems are mass-produced, benefiting from economies of scale. Physically, embedded systems range from portable devices such as digital watches and MP3 players, to large stationary installations like traffic lights, factory controllers, or the systems controlling nuclear power plants. Complexity varies from low, with a single microcontroller chip. In general, "embedded system" is not an exactly defined term, as many systems have some element of programmability. For example, Handheld computers share some elements with embedded systems such as the operating systems and microprocessors which power them but are not truly embedded systems, because they allow different applications to be loaded and peripherals to be connected. Embedded systems provide several functions

- 1) Monitor the environment: Embedded systems read data from input sensors. This data is then processed and the results displayed in some format to a user or users. Control the environment; embedded systems generate and transmit commands for actuators.
- 2) Transform the information: Embedded systems transform the data collected in some meaningful way, such as data compression/decompression. Although interaction with the external world via sensors and actuators is an important aspect of embedded systems, these systems also provide functionality specific to their applications.

Embedded systems typically execute applications such as control laws, finite state machines, and signal processing algorithms. These systems must also detect and react to faults in both the internal computing environment as well as the surrounding electromechanical systems.

There are many categories of embedded systems, from communication devices to home appliances to control systems. Examples include;

- i) Communication devices
e.g.: modems, cellular phones
- ii) Home Appliances
e.g.: CD player, VCR, microwave oven
- iii) Control Systems
e.g.: Automobile anti-lock braking systems, robotics, satellite control

4.5 BLOCK DIAGRAM OF AN EMBEDDED SYSTEM

An embedded system usually contains an embedded processor. Many appliances that have a digital interface -- microwaves, VCRs, cars -- utilize embedded systems. Some embedded systems include an operating system. Others are very specialized resulting in the entire logic being implemented as a single program. These systems are embedded into some device for some specific purpose other than to provide general purpose computing. A typical embedded system is shown in Fig 4.3.




Fig:4.3 Block diagram of a typical embedded system

4.6 CHARACTERISTICS OF EMBEDDED SYSTEMS

Embedded systems are characterized by a unique set of characteristics. Each of these characteristics imposed a specific set of design constraints on embedded systems designers. The challenge to designing embedded systems is to conform to the specific set of constraints for the application.

4.6.1 Application Specific Systems

Embedded systems are not general-purpose computers. Embedded system designs are optimized for a specific application. Many of the job characteristics are known before the hardware is designed. This allows the designer to focus on the specific design constraints of a well-defined application. As such, there is limited user reprogram ability. Some embedded systems, however, require the flexibility of reprogram ability. Programmable DSPs are common for such applications.

4.6.2 Reactive Systems

As mentioned earlier, a typical embedded systems model responds to the environment via sensors and control the environment using actuators. This requires embedded systems to run at the speed of the environment. This characteristic of embedded system is called "reactive". Reactive computation means that the system (primarily the software component) executes in response to external events. External events can be either periodic or aperiodic. Periodic events make it easier to schedule processing to guarantee performance. Most embedded systems have a significant reactive component. One of the biggest challenges for embedded system designers is performing an accurate worst case design analysis on systems with statistical performance characteristics (e.g., cache memory on a DSP or another embedded processor). Real time system operation means that the correctness of a computation depends, in part, on the time at which it is delivered. Many real-time systems are also reactive system. A common characteristic of an embedded system is one that consists of communicating processes executing on several CPUs or ASICs which are connected by communication links. The reason for this is economy. Economical 4 8-bit microcontrollers may be cheaper than a 32-bit processor. Even after adding the cost of the communication links, this approach may be preferable. In this approach, multiple processors are usually required to handle multiple time-critical tasks. Devices under control of embedded systems may also be physically distributed.

4.6.3 Heterogeneous Architectures

Embedded systems often are composed of heterogeneous architectures (Fig 4.4). They may contain different processors in the same system solution. They may also be mixed signal systems. The combination of I/O interfaces, local and remote memories, and sensors and actuators make embedded system design truly unique. Embedded

systems also have tight design constraints, and heterogeneity provides better design flexibility.




Fig:4.4 Embedded Systems having Heterogeneous Architectures

4.6.4 Harsh environment

Many embedded systems do not operate in a controlled environment. Excessive heat is often a problem, especially in applications involving combustion (e.g., many transportation applications). Additional problems can be caused for embedded computing by a need for protection from vibration, shock, lightning, power supply fluctuations, water, corrosion, fire, and general physical abuse.

As embedded system complexity and computing power continue to grow, they are starting to control more and more of the safety aspects of the overall system. These safety measures may be in the form of software as well as hardware control. Mechanical safety backups are normally activated when the computer system loses control in order to safely shut down system operation. Software safety and reliability is a bigger issue. Software doesn't normally "break" in the sense of hardware. However, software may be so complex that a set of unexpected circumstances can cause software failures leading to unsafe situations. Discussion of this topic is outside the scope of this book, but the challenges for embedded designers include designing reliable software and building cheap, available systems using unreliable components.

The main challenge for embedded system designers is to obtain low-cost reliability with minimal redundancy.

One of the main reasons for embedding a computer is to interact with the environment. This is often done by monitoring and controlling external machinery. Embedded computers transform the analog signals from sensors into digital form for processing. Outputs must be transformed back to analog signal levels. When controlling physical equipment, large current loads may need to be switched in order to operate motors and other actuators. To meet these needs, embedded systems may need large computer circuit boards with many non-digital components. Embedded system designers must carefully balance system tradeoffs among analog components, power, mechanical, network, and digital hardware with corresponding software.

4.6.5 Small and low weight

Many embedded computers are physically located within some larger system. The form factor for the embedded system may be dictated by aesthetics. For example, the form factor for a missile may have to fit inside the nose of the missile. One of the challenges for embedded system designers is to develop non-rectangular geometries for certain solutions. Weight can also be a critical constraint. Embedded automobile control systems, for example, must be light weight for fuel economy. Portable CD players must be light weight for portability purposes.

Cost is an issue in most systems, but the sensitivity to cost changes can vary dramatically in embedded systems. This is mainly due to the effect of computer costs have on profitability and is more a function of the proportion of cost changes compared to the total system cost.

Embedded systems have strict constraints on power. Given the portability requirements of many embedded systems, the need to conserve power is important to maintain battery life as long as possible. Minimization of heat production is another obvious concern for embedded system.

4.7 INTRODUCTION OF EMBEDDED SYSTEM

A system is something that maintains its existence and functions as a whole through the interaction of its parts. E.g. Body, Mankind, Access Control, etc. A system is a part of the world that a person or group of persons during some time interval and for some purpose choose to regard as a whole, consisting of interrelated components, each component characterized by properties that are selected as being relevant to the purpose. Embedded System is a combination of hardware and software used to achieve a single specific task. Embedded systems are computer systems that monitor, respond to, or control an external environment. Environment connected to systems through sensors, actuators and other I/O interfaces. Embedded system must meet timing & other constraints imposed on it by environment.

An embedded system is a microcontroller-based, software driven, reliable, real-time control system, autonomous, or human or network interactive, operating on diverse physical variables and in diverse environments and sold into a competitive and cost-conscious market. An embedded system is not a computer system that is used primarily for processing, not a software system on PC or UNIX, not a traditional business or scientific application. High-end embedded & lower end embedded systems. High-end embedded system - Generally 32, 64 Bit Controllers used with OS. Examples Personal Digital Assistant and Mobile phones etc. Lower end embedded systems - Generally 8, 16 Bit Controllers used with a minimal operating systems and hardware layout designed for the specific purpose.

4.7.1 Design of embedded system

Like every other system development design cycle embedded system too have a design cycle. The flow of the system will be like as given below. For any design cycle these will be the implementation steps.




Fig:4.5 Embedded Product Development Life Cycle

From the initial state of the project to the final fabrication the design considerations will be taken like the software consideration and the hardware components, sensor, input and output. The electronics usually uses either a microprocessor or a microcontroller. Some large or old systems use general-purpose mainframe computers or minicomputers.

4.7.2 Classification of Embedded Systems

- 1) Real Time Systems.
- 2) RTS is one which has to respond to events within a specified deadline.
- 3) A right answer after the dead line is a wrong answer.
- 4) RTS classification
 - i) Hard Real Time System
 - ii) Soft Real Time System

i) Hard Real Time System

"Hard" real-time systems have very narrow response time. For Example, Nuclear power system, Cardiac pacemaker.

ii) Soft Real Time System

"Soft" real-time systems have reduced constraints on "lateness" but still must operate very quickly and repeatably. For Example, Railway reservation system takes a few extra seconds the data remains valid.

4.8 HARDWARE COMPONENTS

- i) Pic micro-controller (PIC16F877A)
- ii) Step down Transformer
- iii) Emergency Button
- iv) Flame / Fire Sensor Module
- v) PIR Sensor Module
- vi) WUSN Module
- vii) ESP8266 Node MCU Wi-Fi Module

4.8.1 PIC MICROCONTROLLER (PIC16F877A)

The term PIC, or Peripheral Interface Controller, is the name given by Microchip Technologies to its single – chip microcontrollers. These devices have been phenomenally successful in the market for many reasons, the most significant ones are mentioned below. PIC micros have grown in steadily in popularity over the last decade, ever since their inception into the market in the early 1990s. PIC micros have grown to become the most widely used microcontrollers in the 8- bit microcontroller segment. The PIC16F877A is 40 pin IC. There are six ports in this microcontroller. Namely PORT A, PORT B, PORT C, PORT D and PORT E. Among these ports PORT B, PORT C and PORT D contains 8-pins, where PORT A contains 6-pins and PORT E contains 3-pins. Each pin in the ports can be used as either input or output pins. Before using the port pins as input or output, directions should be given in TRIS register. For example setting all the bits in TRIS D register indicates all the pins in PORT D are used input pins. Clearing all the bits in TRIS D register indicates all the pins in PORT D are used as output pins. Likewise, TRIS A, TRIS B, TRIS C, TRIS E registers available for PORT A, PORT B, PORT C and PORT E.

The main factors that account for the popularity of PIC micros include the following:

i) Speed: When operated at its maximum clock rate, a PIC executes most instructions in 0.2 μ s, or five instructions in a microsecond.

ii) Instruction set simplicity: The instruction set consists of just 35 instructions.

iii) Integration of operational features: PIC micros have features like Power on Reset and Brown out protection which ensures that the chip operates only when the supply voltage is within specification. A watchdog timer resets the PIC if the chip ever malfunctions and deviates from its normal operations.

iv) Flexibility in clock sources: The PIC micros can be run with four different types of clocksources which help in cost cutting and power saving.

v) High current capabilities of ports: The ports pins on PIC micros can source and sink upto 25mA, which make them all the more versatile and economic.

vi) Serial programming via two pins: PIC micros can be programmed serially with two pins, which bring down the complexity and the cost of PIC programmers, drastically.

vii) On chip EEPROM: The on chip EEPROM helps retain critical data even if the power is down. There by reducing the cost of and external EEPROM from the overall system cost.

viii) Harvard Architecture: Apart from these features are reasons of nontechnical nature like the availability of free development software, low cost device programmers, and availability of free datasheets and application notes.

The architecture of PIC 16F877A contains 4-banks of register files such as Bank 0, Bank 1, Bank 2 and Bank 3 from 00h-07h, 80h-FFh, 100h-17Fh and 180h-1FFh respectively. And it is also having program FLASH memory, Data memory and Data EEPROM of 8K, 368 and 256 Bytes respectively.

Basic Circuit for the PIC16F877A is given below




Fig:4.6 Basic Circuit for the PIC16F877A

The Minimum basic circuit is the fundamental circuit that is required for the microcontroller to run. The above shown circuit is one of the possible minimum basic circuits for the PIC. Like most other microcontrollers, for the PIC to execute any application the following are required

- i) The Power Input
- ii) The Clock input
- iii) The Reset circuit

i) The Power Input: The microcontroller works on 5V DC and it can be given either to Pin 32 or Pin 11. Both these pins are VDD inputs or power inputs. The VSS signal on the microcontroller must be connected to the ground these are Pins 10 or Pin 31. Between the 5V and the ground a 0.1μF capacitor is connected. This capacitor is used to eliminate any noise in the 5V input to the microcontroller. This capacitor is called a Decoupling capacitor.

ii) The Clock Circuit: Any microcontroller or processor needs a clock source for it to execute a program. There are various ways of giving the clock signal to a microcontroller, the most reliable and the common method used is to use a crystal oscillator. Between the Pin number 13 and 14 a crystal oscillator is connected. When

the power is given to the microcontroller, the crystal oscillator starts producing clock signals at a frequency of 20MHz. A 20MHz crystal is used because it is the highest frequency at which the PIC can work and hence it gives the fastest program execution speed at this frequency. If required, lesser frequencies can also be used. For changing the frequency, a different crystal of a different resonant frequency must be used. To the crystal two ceramic capacitors are connected each of 33pF value. These two capacitors are called loading capacitors and are required for the crystal to produce a continuous and uniform clock signal. The values of these capacitors are specified by the manufacturer of the crystal and the microcontroller.

iii) The Reset Circuit: Pin 1 on the PIC is the RESET signal input. The RESET signal is an active low signal. When a low voltage (0V) is applied to the pin 1, the microcontroller gets reset. For the normal execution of the project the pin 1 must be maintained at a high voltage (5V). For providing the RESET signal a resistor and a switch are connected to pin 1. The resistor is connected to 5V and this will normally maintain the pin 1 at 5V and the microcontroller will function normally. When the switch is pressed pin 1 is connected to ground and the voltage at pin 1 becomes 0V. Under this condition the microcontroller gets reset. Thus, pressing the switch will reset the microcontroller.

4.8.1.1 Pin diagram of PIC16F877A

This powerful (200 nanosecond instruction execution) yet easy-to-program (only 35 single word instructions) CMOS FLASH-based 8-bit microcontroller packs Microchip's powerful PIC® architecture into a 40 package and is upwards compatible with the PIC16C5X, PIC12CXXX and PIC16C7X devices. The PIC16F877A features 256 bytes of EEPROM data memory, self-programming, an ICD, 2 Comparators, 8 channels of 10-bit Analog-to-Digital (A/D) converter, 2 capture/compare/PWM functions, the synchronous serial port can be configured as either 3-wire Serial Peripheral Interface (SPI™) or the 2-wire Inter-Integrated Circuit (I²C™) bus and a Universal Asynchronous Receiver Transmitter (USART).



Fig:4.7 Pin diagram of PIC16F877A

Some pins for these I/O ports are multiplexed with an alternate function for the peripheral features on the device. In general, when a peripheral is enabled, that pin may not be used as a general purpose I/O pin.

i) Port A and the Tris A Register

PORTA is a 6-bit wide, bidirectional port. The corresponding data direction register is TRISA. Setting a TRISA bit (= 1) will make the corresponding PORTA pin an input (i.e., put the corresponding output driver in a High-Impedance mode). Reading the PORTA register reads the status of the pins, whereas writing to it will write to the port latch. All write operations are read-modify-write operations. Therefore, a write to a port implies that the port pins are read, the value is modified and then written to the port data latch. PinRA4 is multiplexed with the Timer0 module clock input to become the RA4/T0CKI pin. The RA4/T0CKI pin is a Schmitt Trigger input and an open-drain output. All other PORTA pins have TTL input levels and full CMOS output drivers. Other PORTA pins are multiplexed with analog inputs and the analog VREF input for both the A/D

converters and the comparators. The operation of each pin is selected by clearing/setting the appropriate control bits in the ADCON1 and/or CMCON registers. The TRISA register controls the direction of the port pins even when they are being used as analog inputs. The user must ensure the bits in the TRISA register are maintained set when using them as analog inputs.

ii) Port B and the Tris B Register

PORTB is an 8-bit wide, bidirectional port. The corresponding data direction register is TRISB. Setting a TRISB bit (= 1) will make the corresponding PORTB pin an input (i.e., put the corresponding output driver in a High-Impedance mode). Clearing a TRISB bit (= 0) will make the corresponding PORTB pin an output (i.e., put the contents of the output latch on the selected pin).

Three pins of PORTB are multiplexed with the In-Circuit Debugger and Low-Voltage Programming function: RB3/PGM, RB6/PGC and RB7/PGD. The alternate functions of these pins are described in Section 14.0 "Special Features of the CPU". Each of the PORTB pins has a weak internal pull-up. A single control bit can turn on all the pull-ups. This is performed by clearing bit RBPU (OPTION_REG<7>). The weak pull-up is automatically turned off when the port pin is configured as an output. The pull-ups are disabled on a Power-on Reset.

Four of the PORTB pins, RB7:RB4, have an interruption- change feature. Only pins configured as inputs can cause this interrupt to occur. The input pins (of RB7:RB4) are compared with the old value latched on the last read of PORTB. The "mismatch" outputs of RB7:RB4 are OR 'ed together to generate the RB port change interrupt with flag bit RBIF (INTCON<0>). This interrupt can wake the device from sleep. The user, in the Interrupt Service Routine, can clear the interrupt in the following manner:

A) Any read or write of PORTB. This will end the mismatch condition.

B) Clear flag bit RBIF. A mismatch condition will continue to set flag bit RBIF. Reading PORTB will end the mismatch condition and allow flag bit RBIF to be cleared. The

interrupt-on-change feature is recommended for wake-up on key depression operation and operations where PORTB is only used for the interrupt-on-change feature. Polling of PORTB is not recommended while using the interrupt-on-change feature.

iii) Port C and the Tris C Register

PORTC is an 8-bit wide, bidirectional port. The corresponding data direction register is TRISC. Setting a TRISC bit (= 1) will make the corresponding PORTC pin an input (i.e., put the corresponding output driver in a High-Impedance mode). Clearing a TRISC bit (= 0) will make the corresponding PORTC pin an output (i.e., put the contents of the output latch on the selected pin). PORTC is multiplexed with several peripheral functions (Table 4-5). PORTC pins have Schmitt Trigger input buffers.

When the I2C module is enabled, the PORTC<4:3> pins can be configured with normal I2C levels, or with SM Bus levels, by using the CKE bit (SSPSTAT<6>). When enabling peripheral functions, care should be taken in defining TRIS bits for each PORTC pin. Some peripherals override the TRIS bit to make a pin an output, while other peripherals override the TRIS bit to make a pin an input. Since the TRIS bit override is in effect while the peripheral is enabled, read-modify write instructions (BSF, BCF, and XORWF) with TRISC as the destination, should be avoided. The user should refer to the corresponding peripheral section for the correct TRIS bit settings.

iv) Port D and Tris D Registers

PORTD is an 8-bit port with Schmitt Trigger input buffers. Each pin is individually configurable as an input or output. PORTD can be configured as an 8-bit wide microprocessor port (Parallel Slave Port) by setting control bit, PSPMODE (TRISE<4>). In this mode, the input buffers are TTL.

v) Port E and Tris E Register

PORTE has three pins (RE0/RD/AN5, RE1/WR/AN6 and RE2/CS/AN7) which are individually configurable as inputs or outputs. These pins have Schmitt Trigger input buffers. The PORTE pins become the I/O control inputs for the microprocessor port when bit PSPMODE (TRISE<4>) is set. In this mode, the user must make certain that the TRISE<2:0> bits are set and that the pins are configured as digital inputs. Also, ensure that ADCON1 is configured for digital I/O.

In this mode, the input buffers are TTL. Register 4-1 shows the TRISE register which also controls the Parallel Slave Port operation. PORTE pins are multiplexed with analog inputs. When selected for analog input, these pins will read as '0's.

vi) Register File

The term register file in PIC terminology is used to denote the locations that an instruction can access via an address. The register file consists of two components, they are

- i) General purpose register file
- ii) Special purpose register file

i) General Purpose Register File

The general-purpose register file is another name for the microcontrollers RAM. Data can be written to each 8-bit location, updated and retrieved any number of times. All control registers are coming under the general-purpose register file.

ii) Special Purpose Register File

The special purpose register file contains input and output ports as well as the control registers used to establish each bit of port as either an input or output. It contains registers that provide the data input and data output to the variety of resources on the chip, such as the timers, the serial ports and the analog-to-digital converter. It has registers that contain control bits for selecting the mode of operation of a chip resource as well as enabling or disabling its operation.

Table: 4.1 Register file maps used in PIC16F877A

NAME	FUNCTION	ADDRESS RAM ADDRESS	BIT ADDRESABLE
STATUS	Status register	03H,83H,103H,183H	Yes
FSR	File select register	04H,84H,104H,184H	Yes
PORTA	I/O latch	05H	Yes
PORTB	I/O latch	06H	Yes
PORTC	I/O latch	07H	Yes
PORTD	I/O latch	08H	Yes
PORTE	I/O latch	09H	Yes
INTCON	Interrupt control register	0BH,8BH,10BH,18BH	Yes
PIR1	Peripheral Interrupt control	0CH	Yes
RCSTA	Receive status and control register	18H	Yes
TXREG	Transmit register	19H	Yes
RCREG	Receive register	1AH	Yes
OPTION_REG	Optional register	81H	Yes
TRISA	I/O register	85H	Yes
TRISB	I/O register	86H	Yes
TRISC	I/O register	87H	Yes

TRISD	I/O register	88H	Yes
TRISE	I/O register	89H	Yes
TXSTA	Transmit status and control register	98H	Yes
SPBRG	Baud rate generator	99H	Yes

vii) Status Register

Flags are one-bit registers provided to store results of certain program instructions, other instructions can test the condition of the flags and make decisions based on the flag states. In order to address the flags conveniently flags are grouped inside the register named STATUS. The PIC16F877 has three flags such as Zero (Z), Digit Carry (DC) and Carry (C), that responds automatically to the outcomes of the mathematical operations. These flags are set to logic-0 or logic-1 according to the Arithmetic and Logical operations.

i) **INTERRUPT**: One of the methods to determine the condition that exists in internal and external circuits is to respond to the hardware signals, called interrupts which force the program to call a subroutine. Interrupts are generated by internal chip operations and provided by external sources known as Internal interrupts and External interrupts respectively. Any interrupts can cause or transfer the PIC16F877 microcontroller control to the address 0004h. By configuring the INTCON register we enable the interrupts.

ii) **SERIAL DATA COMMUNICATIONS**: Computers must be able to communicate with other computers in modern multi-processor distributed systems. One cost-effective way to communicate is to send and receive data bytes serially. The PIC16F77 micro controller has serial data communication circuits that transmit and receive the data. By configuring the SPEN in RCSTA we can enable the serial communication in PIC16F877. Similarly, by configuring the TXSTA (Transmit Status and Control Register) and RCSTA (Receive Status and Control Register) we can transmit and receive the data serially the any data in TXREG transmit the data and the data which is in RCREG is the receive data. The following figure shows the TXSTA and RCSTA.

4.8.1.2 Instruction Sets in PIC16F877A

The PIC16F877A microcontroller uses a reduced instruction set computing (RISC) architecture, with a set of instructions tailored to perform specific tasks efficiently. Some common instruction sets for the PIC16F877A includes these instructions, along with their operands, enable the microcontroller to execute a wide range of tasks efficiently. Each instruction performs a specific operation and can be used to program the microcontroller to perform various tasks.

Table: 4.2 Instruction Sets in PIC16F877A

Mnemonic	Operands	Description	Cycles	Status Affected
ADDWF	f, d	Add W and f	1	C,DC,Z
ANDWF	f, d	AND W with f	1	Z
CLRF	F	Clear f	1	Z
CLRW	-	Clear W	1	Z
COMF	f, d	Complement f	1	Z
DECF	f, d	Decrement f	1	Z
DECFSZ	f, d	Decrement f, skip if 0	1(2)	
INCF	f, d	Increment f	1	Z
INCFSZ	f, d	Increment f, skip if 0	1(2)	
IORWF	f, d	Inclusive OR W with f	1	Z

MOVF	f, d	Move f	1	Z
MOVWF	F	Move W to f	1	
NOP	-	No Operation	1	
RLF	f, d	Rotate Left f through Carry	1	C
RRF	f, d	Rotate Right f through Carry	1	C
SUBWF	f, d	Subtract W from f	1	C,DC,Z
SWAPF	f, d	Swap nibbles in f	1	Z
XORWF	f, d	Exclusive OR W with f	1	Z
BCF		Bit clear f	1	
BSF		Bit set f	1	
BTFSC		Bit Test f, Skip if Clear	1(2)	
BTFSS		Bit Test f, Skip if set	1(2)	
ADDLW		Add literal and W	1	C, DC, Z
ANDLW		AND with literal and W	1	Z
CALL		Call subroutine	2	
CLRWDT		Clear watchdog timer	1	
GOTO		Go to Address	2	---- TO
IORLW		Inclusive OR literal with W	1	Z
MOVLW		Move literal to W	1	

RETFIE	Return from Interrupt	2	
RETLW	Return with literal in W	2	
RETURN	Return from Sub routine	2	
SLEEP	Go into standby mode	1	
SUBLW	Subtract W from literal	1	Z
XORLW	Exclusive OR with literal	1	C, DC, Z

4.8.1.3 Block diagram of PIC

PIC stands for Peripheral Interface Controller. PIC microcontroller was developed by microchip technology in 1993. It was developed for supporting PDP computers to control its peripheral devices and that's why it was named Peripheral Interface Controller. PIC microcontrollers are of low cost, very fast and easy for the programming and execution of program. Their interfacing with other peripherals is also very easy. PIC Microcontrollers from Microchip Company are divided into 4 large families. In this PIC Microcontroller architecture article explain step by step about PIC Microcontroller architecture and components used in pic microcontrollers. PIC Microcontroller architecture is based on Harvard architecture and supports RISC architecture (Reduced Instruction Set Computer). PIC microcontroller architecture consists of memory organization (ram, rom, stack), CPU, timers, counter, ADC, DAC, serial communication, CCP module and I/O ports. PIC microcontroller also supports the protocols like CAN, SPI, UART for interfacing with other peripherals.




Fig:4.8 Block diagram of PIC16F877A

4.8.2 Step down Transformer

The potential transformer will step down the power supply voltage (0-230V) to (0-6V) level. Then the secondary of the potential transformer will be connected to the precision rectifier, which is constructed with the help of op-amp. The advantages of using precision rectifier are it will give peak voltage output as DC, rest of the circuits will give only RMS output.

4.8.3 Emergency Button

Emergency buttons are typically installed in various settings such as buildings, vehicles, or personal devices to quickly alert authorities or summon help in urgent situations. They are designed to provide a rapid response to emergencies such as medical crises, security threats, or accidents. This can lead to faster response times from emergency services, potentially saving lives and preventing further harm. Additionally, it can offer peace of mind to users knowing that help is just a button press away.



Fig:4.9 Emergency Button

4.8.4 Flame Sensor Module

A flame sensor module is an electronic device designed to detect the presence of a flame or fire. It typically consists of an infrared sensor that detects the infrared radiation emitted by flames. These modules are commonly used in applications such as fire detection systems, gas appliances, and industrial safety equipment to trigger alarms or shutdown mechanisms in the presence of a fire hazard. A key aspect of fire protection is to identify a developing fire emergency in a timely manner, and to alert the building's occupants and fire emergency organizations. This is the role of fire detection and alarm systems. Depending on the anticipated fire scenario, building and use type, number and type of occupants, and criticality of contents and mission, these systems can provide several main functions. First they provide a means to identify a developing fire through either manual or automatic methods and second, they alert building occupants to a fire condition and the need to evacuate. Another common function is the transmission of an alarm notification signal to the fire department or other emergency response organization. They may also shut down electrical, air handling equipment or special process operations, and they may be used to initiate automatic suppression systems.




Fig:4.10 Flame Sensor Module

Flame sensor is the most sensitive to ordinary light that is why its reaction is generally used as flame alarm purposes. This module can detect flame or wavelength in 760 nm to 1100 nm range of light source. Small plate output interface can and single-chip can be directly connected to the microcomputer IO port. The sensor and flame should keep a certain distance to avoid high temperature damage to the sensor.

The shortest test distance is 80 cm, if the flame is bigger, test it with farther distance. The detection angle is 60 degrees so the flame spectrum is especially sensitive. The detection angle is 60 degrees so the flame spectrum is especially sensitive.

Specifications:

- i) Operating Voltage: 3.3V to 5V DC
- ii) Operating Current: 15ma
- iii) Output Digital - 0V to 5V, Adjustable trigger level from preset
- iv) Output Analog - 0V to 5V based on infrared radiation from fire flame falling on the sensor.
- v) LEDs indicating output and power
- vi) PCB Size: 3.2cm x 1.4cm
- vii) LM393 based design

4.8.5 PIR Sensor Module

A PIR detector is a motion detector that senses the heat emitted by a living body. These are often fitted to security lights so that they will switch on automatically if approached. They are very effective in enhancing home security systems. The sensor is passive because, instead of emitting a beam of light or microwave energy that must be interrupted by a passing person in order to "sense" that person, the PIR is simply sensitive to the infrared energy emitted by every living thing. When an intruder walks into the detector's field of vision, the detector "sees" a sharp increase in infrared energy. A PIR sensor light is designed to turn on when a person approaches, but will not react to a person standing still. The lights are designed this way. A moving person exhibits a sudden change in infrared energy, but a slower change is emitted by a motionless body. Slower changes are also caused by gradual fluctuations in the temperature of the environment. If the light were sensitive to these slower changes, it would react to the sidewalk cooling off at night, instead of the motion of a burglar.

If you have a PIR light, you may notice that it is more sensitive on cold days than on warm days. This is because the difference in temperature between the ambient air and the human body is greater on cold days, making the rise in temperature easier for the sensor to detect. This has drawbacks, though; if the sensor is too sensitive, it will pick up things you don't want it to such as the movement of small animal. Passive infrared sensor is an electronic device, which measures infrared light radiating from objects in its field of view. PIRs are often used in the construction of PIR-based motion detectors. Apparent motion is detected when an infrared source with one temperature, such as a human, passes in front of an infrared source with another temperature, such as a wall. All objects emit what is known as black body radiation. This energy is invisible to the human eye but can be detected by electronic devices designed for such a purpose. The term 'Passive' in this instance means the PIR does not emit energy of any type but merely accepts incoming infrared radiation.

Infrared radiation enters through the front of the sensor, known as the sensor face. At the core of a PIR is a solid state sensor or set of sensors, made from approximately 1/4 inches square of natural or artificial pyroelectric materials, usually in the form of a thin film, out of gallium nitride (GaN), cesium nitrate (CsNO₃), polyvinyl fluorides, derivatives of phenyl pyrazine and cobalt phthalocyanine. (See pyroelectric crystals. Lithium tantalate (LiTaO₃) is a crystal exhibiting both piezoelectric and pyroelectric properties. The sensor is often manufactured as part of an integrated circuit and may consist of one (1), two (2) or four (4) 'pixels' of equal areas of the pyroelectric material. Pairs of the sensor pixels may be wired as opposite inputs to a differential amplifier. In such a configuration, the PIR measurements cancel each other so that the average temperature of the field of view is removed from the electrical signal; an increase of IR energy across the entire sensor is self-cancelling and will not trigger the device. This allows the device to resist false indications of change in the event of being exposed to flashes of light or field-wide illumination. (Continuous bright light could still saturate the sensor materials and render the sensor unable to register further information.)

At the same time, this differential arrangement minimizes common-mode interference; this allows the device to resist triggering due to nearby electric fields. However, a differential pair of sensors cannot measure temperature in that configuration and therefore this configuration is specialized for motion detectors. In a PIR-based motion detector, the PIR sensor is typically mounted on a printed circuit board, which also contains the necessary electronics required to interpret the signals from the chip. The complete circuit is contained in a housing, which is then mounted in a location where the sensor can view the area to be monitored. Infrared energy is able to reach the sensor through the window because the plastic used is transparent to infrared radiation (but only translucent to visible light). This plastic sheet prevents the introduction of dust and insects, which could obscure the sensor's field of view.

PIR sensors allow you to sense motion, almost always used to detect whether a human has moved in or out of the sensor's range. They are small, inexpensive, low-power, easy to use and don't wear out. For that they are commonly found in appliances and gadgets used in homes or businesses.

They are often referred to as PIR, "Passive Infrared", "Pyroelectric", or "IR motion" sensors. PIR sensors are more complicated than many of the other sensors explained in these tutorials (like photocells, FSRs and tilt switches) because there are multiple variables that affect the sensors input and output. To begin explaining how a basic sensor works, we'll use this rather nice diagram (if anyone knows where it originates, please let me know). The PIR sensor itself has two slots in it, each slot is made of a special material that is sensitive to IR. The lens used here is not really doing much and so we see that the two slots can 'see' out past some distance (basically the sensitivity of the sensor). When the sensor is idle, both slots detect the same amount of IR, the ambient amount radiated from the room or walls or outdoors. When a warm body like a human or animal passes by, it first intercepts one half of the PIR sensor, which causes a positive differential change between the two halves. When the warm body leaves the sensing area, the reverse happens, whereby the sensor generates a negative differential change. These change pulses are what is detected.




Fig:4.11 PIR Sensor Module Working Mechanism

The IR sensor itself is housed in a hermetically sealed metal can to improve noise/temperature/humidity immunity. There is a window made of IR-transmissive material (typically coated silicon since that is very easy to come by) that protects the sensing element. Behind the window are the two balanced sensors. Behind the window are the two balanced sensors.




Fig:4.12 PIR Sensor Module




Fig:4.13 Schematic diagram of PIR

You can see above the diagram showing the element window, the two pieces of sensing material.




Fig:4.14 Internal Schematic of PIR

This image shows the internal schematic. There is actually a JFET inside (a type of transistor) which is very low-noise and buffers the extremely high impedance of the sensors into something a low-cost chip (like the BIS0001) can sense.

4.8.6 WUSN module

WUSNs can be used to monitor a variety of conditions, such as soil properties for agricultural applications and toxic substances for environmental monitoring. Unlike existing methods of monitoring underground conditions, which rely on buried sensors connected via wire to the surface, WUSN devices are deployed completely belowground and do not require any wired connections. Each device contains all necessary sensors, memory, a processor, a radio, an antenna, and a power source. This makes their deployment much simpler than existing underground sensing solutions. Wireless communication within a dense substance such as soil or rock is, however, significantly more challenging than through air.



Fig:4.15 WUSN module

4.8.7 ESP8266 Node MCU Wi-Fi Module

An ESP8266 Wi-Fi module is a SOC microchip mainly used for the development of end-point IOT applications. It is referred to as a standalone wireless transceiver, available at a very low price. It is used to enable the internet connection to various applications of embedded systems. If the system designed the ESP8266 Wi-Fi module to support both the TCP/IP capability and the microcontroller access to any Wi-Fi network. It provides the solutions to meet the requirements of industries of IOT such as cost, power, performance and design. It can work as either a slave or a standalone application.

If the ESP8266 Wi-Fi runs as a slave to a microcontroller host, then it can be used as a Wi-Fi adaptor to any type of microcontroller using UART or SPI. If the module is used as a standalone application, then it provides the functions of the microcontroller and Wi-Fi network.



Fig:4.16 Node MCU Wi-Fi module

CHAPTER- 5

RESULTS & DISCUSSION

5.1 Fire detection process

The major component of a flame detector system is the detector itself. It comprises of photoelectric detective circuits, signal conditioning circuits, microprocessor systems, I/O circuits, and wind cooling systems. The sensors in the flame detector will detect the radiation that is sent by the flame, the photoelectric converts the radiant intensity signal of the flame to a relevant voltage signal and this signal would be processed in a single chip microcomputer and converted into a desired output.




Fig:5.1 Fire Detection Process

5.2 PIR Sensor detection process

PIR sensor definition is; a sensor that is used to measure infrared light radiating from objects like the human body or animals. In PIR sensor, the term PIR stands for “passive infrared sensor”. PIR sensors can detect the movement of an animal or human within a fixed range. Generally, all objects at above zero temperatures produce heat energy in the IR radiation form. So, if the object is hotter then it emits more radiation. So, this kind of radiation is not observable to the human eye as it is emitted at IR wavelengths. So, PIR sensor is particularly designed for detecting such infrared radiation levels. These sensors are most frequently utilized in motion detectors, security alarms & automatic lighting-based applications.




Fig:5.2 PIR Sensor detection process

5.3 Data's are stored in the cloud

Storage of Data on cloud. The activities that are held in forest are monitored through sensors and those data's are stored in cloud using ESP8266 Wi-Fi module where forest department officials can access the data and prevailing situation happening in forest anywhere and anytime.




Fig:5.3 Data's are stored in the cloud

5.4 Final Overall model Transmitter and Receiver

In this project data is transferred through the soil without any hazards. Transferring data through the soil using low frequency. Therefore, the most important goals in fire surveillance are quick and reliable detection of fire. It is so much easier to suppress fire while it is in its early stages. The area of the forest is large, it is far away from urban area network coverage. It is a challenge for the communication between sensors and receivers to exchange data. RF transmission is not possible under the ground instead of that I am using WUSN networks to send the Data to communicate through the Receiver side.




Fig:5.4 Overall model of Transmitter and Receiver

CHAPTER- 6

CONCLUSION

6.1 CONCLUSION

This project is about the design and implementation of a wireless sensor network for monitoring agricultural environment the nodes in this system always work under different environmental conditions and it is a real challenge in establishing a WSN. Securing this network is also an uphill task as it is necessary to establish routing and routed protocols concerned. The security framework discussed here is helpful in designing the system architecture. There are various issues and challenges while designing the architecture this model helps us to understand the basic work and interfacing of the various components used in the project, giving us an idea about how they work on a local network and to determine the flaws which must be overcome before being implemented on larger scale. We have to Send the Data and Video based on Wireless medium under on Deep Forest because sometime Signal will be Lost so We decide to change the Wireless medium such as Soil based communication of the transmitter and the receiver.

6.2 STANDARDS

Developing an interdisciplinary and systematic approach for establishing communication routes through deep forests involves collaboration between experts in geography, forestry, environmental science, civil engineering, and possibly even anthropology or sociology to consider cultural aspects. It requires detailed mapping of terrain, vegetation, and wildlife habitats, alongside environmental impact assessments to minimize ecological disruption. Additionally, employing advanced technologies like GIS (Geographic Information Systems) and remote sensing can aid in route planning and monitoring. Regular consultations with local communities and indigenous peoples are also crucial to ensure the routes respect their needs and traditions while minimizing negative impacts on the environment.

6.3 CONSTRAINTS

An interdisciplinary and systematic approach for developing a deep forest route of communications would involve various constraints:

- i) **Environmental Impact:** Ensuring minimal disruption to the ecosystem, including flora, fauna, and natural habitats, while constructing the routes.
- ii) **Topography:** Dealing with rugged terrain, steep slopes, and unpredictable natural features.
- iii) **Wildlife Preservation:** Minimizing disturbance to wildlife habitats and migration routes.
- iv) **Cultural Heritage:** Respecting indigenous peoples' rights and preserving cultural sites within the forest.
- v) **Legal and Regulatory:** Adhering to local, national, and international laws regarding land use, conservation, and indigenous rights.
- vi) **Infrastructure:** Building roads or pathways that can withstand weather conditions and facilitate communication effectively.
- vii) **Cost:** Balancing the need for connectivity with the financial resources available for construction and maintenance.
- viii) **Safety:** Ensuring the safety of workers during construction and the safety of travelers once the routes are operational.
- ix) **Long-term Sustainability:** Developing routes that are sustainable in the long term, both environmentally and economically.
- x) **Accessibility:** Ensuring that the routes are accessible to all users, including those with disabilities.

By addressing these constraints systematically and with input from various disciplines such as environmental science, engineering, sociology, and anthropology, it's possible to create deep forest routes of communication that balance human needs with environmental preservation.

6.4 TRADE-OFFS

Taking an interdisciplinary and systematic approach for establishing geographical deep forest routes for communication has its trade-offs:

i) Comprehensive Understanding: By integrating various disciplines such as geography, ecology, engineering, and sociology, you gain a more comprehensive understanding of the terrain, its ecological impact, and the societal needs. However, this approach requires significant time, resources, and expertise.

ii) Effective Planning: A systematic approach allows for thorough planning, considering factors like topography, wildlife habitats, and cultural sensitivities. This can lead to more effective route designs that minimize environmental disruption and community resistance. Yet, this meticulous planning can prolong the project timeline.

iii) Mitigating Risks: Interdisciplinary collaboration helps identify potential risks and develop mitigation strategies. For instance, ecologists can advise on preserving biodiversity, while engineers can ensure infrastructure stability. However, balancing various priorities may lead to compromises that not everyone agrees with.

iv) Long-term Sustainability: Integrating multiple perspectives enhances the likelihood of creating sustainable communication routes that endure over time. This includes factors like minimizing habitat fragmentation, ensuring minimal environmental impact, and promoting social inclusivity. Nevertheless, achieving consensus among stakeholders with differing priorities can be challenging.

v) Cost and Time: While an interdisciplinary and systematic approach may lead to more robust outcomes, it often requires more upfront investment in terms of time and resources. Detailed surveys, consultations, and analyses can extend project timelines and increase costs. However, these investments can potentially yield long-term benefits by avoiding costly mistakes and conflicts down the line.

REFERENCES

- [1] Ala G, Buccheri P.L, Romano P, and Viola F, "Finite difference time domain simulation of earth electrodes soil ionization under lightning surge condition," *Sci. Meas. Technol.*, vol. 2, no. 3, pp. 134–145, May 2008.
- [2] Alley W.M., Healy R.W., La Baugh J.W., Reilly T.E. *Hydrology - flow and storage in groundwater systems*. Science. 2002; 296:1985–1990.
- [3] Beeson S and Neuber A, "Electron density evolution of post pulse high power microwave plasma," in *Proc. Abstract. IEEE Int. Conf. Plasma Sci.*, Edinburgh, U.K., Jul 1994. Jul 2012, pp. 2B–5.
- [4] Liew A. C and Davinia M, "Dynamic model of impulse characteristics of concentrated earths," *Proc. IEE*, vol.121, no.2, pp.123–135, Feb 1974.
- [5] Liu Z, Theethayi N, Gonzalez R. M, and Thottappillil R, "The residual resistivity in soil ionization region around grounding system for different experimental results," in *Proc. IEEE Int. Symp. Electromagnet. Compat.*, 2003.
- [6] Mouse A. M, "The soil ionization gradient associated with discharge of high currents into concentrated electrodes," *IEEE Trans. Power Del.*, vol.9, no. 3, pp. 1669–1677.
- [7] Packer I.J., Chapman G.A., Lawrie J.W. *On-ground extension of soil information to improve land management*. *Soil Use Manag.* 2019; 35:75–84.
- [8] Russinovich G. S, Kashan D. G, and Antonsen T. M, "Effect of metallic dust on operation of repetition-rate high-power microwave devices," *IEEE Trans. Plasma Sci.*, vol. 39, no. 8, pp.1680–1683, Aug 2011.
- [9] Tang T and Wang B, "Numerical modeling for high power microwave propagation in soil," *IEEE Antennas Wireless Propagation. Lett.*, vol. 13, pp. 1660–1662, 2014.
- [10] Tang T, Liao C, and Lin W. B, "Characteristics analysis of repetition frequency high- power microwave pulses in atmosphere," *Prog. Electromagnet. Res. M*, vol. 14, pp. 207–220, Nov 2010.

APPENDIX

A. PLAGARISM REPORT OF PAPER

RE-2022-229750-plag-report

ORIGINALITY REPORT

8%

SIMILARITY INDEX

4%

INTERNET SOURCES

7%

PUBLICATIONS

3%

STUDENT PAPERS

PRIMARY SOURCES

1

K. Srilatha, R. Roshini, R. Choshmitha. "Image Reconstruction Method For Ultrafast Ultrasonic Imaging Based On Convolutional Neural Network(CNN)", 2023 2nd International Conference on Vision Towards Emerging Trends in Communication and Networking Technologies (ViTECoN), 2023

Publication

1%

2

www.jpier.org

Internet Source

1%

3

Pavan Kumar Paruchuri, V. Gomathy, E. Anna Devi, Shweta Sankhwar, S.K. Lakshmanaprabu. "An intelligent COVID-19 classification model using optimal grey-level co-occurrence matrix features with extreme learning machine", International Journal of Computer Applications in Technology, 2021

Publication

1%

B. PAPER SUBMISSION TO THE CONFERENCE

**2024 2nd World Conference on Communication & Computing 2024:
Submission (1222) has been created.**

Inbox

Search for all messages with label Inbox

Remove label Inbox from this conversation

10:11 (9
minutes ago)

Microsoft CMT <email@msr-cmt.org>

to me

Hello,

The following submission has been created.

Track Name: WCONF2024

Paper ID: 1222

Paper Title: AN INTERDISCIPLINARY AND SYSTEMATIC APPROACH FOR GEOGRAPHICAL DEEP
FOREST ROUTE OF COMMUNICATIONS

Abstract:

Wireless Underground Sensor Networks (WUSNs) constitute one of the promising application areas of the recently developed wireless sensor networking techniques. WUSN is a specialized kind of WSN that mainly focuses on the use of sensors at the subsurface region of the soil. For a long time, this region has been used to bury sensors, usually targeting irrigation and environment monitoring applications, although without wireless communication capability; WUSNs promise to fill this gap and to provide the infrastructure for novel applications. The underground wireless channel was only available recently. Communication through the underground medium has been a challenging research area. The applications require the deployment of sensors below the ground surface. Hence, the sensor become part of the sensed environment and might deliver more precise sensing. We send data through the Soil communication Medium based on Magnetic Rod Flux. We using Arduino RISC mechanism.

Created on: Mon, 15 Apr 2024 04:41:16 GMT

Last Modified: Mon, 15 Apr 2024 04:41:16 GMT

Authors:

- shanmukhagarapati8614@gmail.com (Primary)

Secondary Subject Areas: Not Entered

Submission Files: shanm.pdf (296 Kb, Mon, 15 Apr 2024 04:41:09 GMT)

Submission Questions Response: Not Entered

Thanks,

CMT team.

Author Console

Create new submission

1 - 1 of 1

Show 25 50 100 All

Clear All Filters

Paper ID	Title	Files	Actions
1222	AN INTERDISCIPLINARY AND SYSTEMATIC APPROACH FOR GEOGRAPHICAL DEEP FOREST ROUTE OF COMMUNICATIONS View abstract Wireless Underground Sensor Networks (WUSNs) constitute one of the promising application areas of the recently developed wireless sensor networking techniques. WUSN is a specialized kind of WSN that mainly focuses on the use of sensors at the subsurface region of the soil. For a long time, this region has been used to bury sensors, usually targeting irrigation and environment monitoring applications, although without wireless communication capability. WUSNs promise to fill this gap and to provide the infrastructure for novel applications. The underground wireless channel was only available recently. Communication through the underground medium has been a challenging research area. The applications require the deployment of sensors below the ground surface. Hence, the sensor becomes part of the sensed environment and might deliver more precise sensing. We send data through the Soil communication Medium based on Magnetic Root Flux, Via using Arduino RISC exchanges.	Submission files: sharm.pdf	Submission: Edit Submission Edit Conflicts Delete Submission