

SEGMENTATION OF BRAIN TUMOR MRI USING DEEP LEARNING TECHNIQUES

Submitted in partial fulfillment of the requirements for the award of
Bachelor of Engineering Degree in Electronics and Communication Engineering

By

Shubham Biswal (40130260)
Uppu Durga Jagadeesh (40130283)



DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING
SCHOOL OF ELECTRICAL AND ELECTRONICS

SATHYABAMA

**INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)**

CATEGORY -1 UNIVERSITY BY UGC

**Accredited with Grade "A++" by NAAC | 12B Status by UGC | Approved by AICTE
JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI - 600 119**

APRIL – 2024



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY

(DEEMED TO BE UNIVERSITY)

Accredited "A++" Grade by NAAC | 12B Status by UGC | Approved by AICTE

www.sathyabama.ac.in

DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING

BONAFIDE CERTIFICATE

This is to Certify that this Project Report is the bonafide work of **Uppu Durga Jagadeesh (40130283), Shubham Biswal (40130260)** who carried out the project entitled "**Segmentation of Brain Tumor MRI using Deep Learning Techniques**" under our supervision from November 2023 to April 2024


18/4/2024

Internal Guide

Ms. R. SAKTHI PRABHA, M.E.,(Ph.D)



Head of the Department

Dr.T.RAVI, M.E., Ph.D

Submitted for Viva Voce Examination held on 18/04/2024



Internal Examiner


18/4/24

External Examiner

DECLARATION

We, Uppu Durga Jagadeesh (40130283), Shubham Biswal (40130260) hereby declare that the Project Report entitled “**Segmentation of Brain Tumor MRI using Deep Learning Techniques**” done by us, under the guidance of **Ms. R. Sakthi Prabha, M.E., (Ph.D.)** Assistant Professor, Department of Electronics and Communication Engineering, at Sathyabama Institute of Science and Technology, Chennai is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering Degree in the Department of Electronics and Communication Engineering.

DATE: 18/04/2024

SIGNATURE OF CANDIDATES

PLACE: Chennai

1. 
2. Shubham Biswal

ACKNOWLEDGEMENT

We are pleased to acknowledge our sincere thanks to **Board of Management** of **SATHYABAMA INSTITUTE OF SCIENCE AND TECHNOLOGY** for their kind encouragement in doing this project and for completing it successfully. We are grateful to them.

We convey our thanks to **Dr. N. M. NANDHITHA, M.E., Ph.D., Dean, School of Electrical and Electronics** and **Dr. T. RAVI, M.E., Ph.D., Professor & Head, Department of Electronics and Communication Engineering** for providing us necessary support and details during the progressive reviews.

We would like to express our sincere and deep sense of gratitude to our project guide, **Ms. R. SAKTHI PRABHA, M.E., (Ph.D) ,Assistant Professor,** Department of Electronics and Communication Engineering, for her valuable guidance, suggestions and constant encouragement that paved the way for the successful completion of our project work.

We would like to express our thanks to all the teaching and non-teaching staff members of the Department of Electronics and Communication Engineering and who were helpful in many ways for the completion of the project. We would like to thank our parents, friends, and classmates for encouraging us throughout our project. Last, but not least, we thank everyone for supporting us directly or indirectly in completing this project successfully.

ABSTRACT

Brain tumors pose a significant health challenge, characterized by the uncontrolled growth of abnormal cells within the brain. While Magnetic Resonance Imaging (MRI) provides a means to identify these tumors, manual detection is laborious and prone to errors. To address these limitations, computer-assisted methods leveraging artificial intelligence, have emerged as promising solutions in medical imaging. In this study, we propose a novel approach for brain tumor classification and detection utilizing a deep convolutional neural network (CNN) architecture based on the U-Net model. Our method involves fine-tuning the base CNN model with additional layers tailored to effectively classify brain tumor images, with a focus on utilizing small 3×3 kernels for feature extraction. The experimental results demonstrate the superior performance of our proposed model compared to other CNN architectures, achieving remarkable accuracy, precision, root mean square (RMS) error, and variance metrics. Specifically, our model achieves an impressive overall accuracy of 99.02% in terms of classification and detection.

TABLE OF CONTENTS

CHAPTER NO	TITLE	PAGE NO
	ABSTRACT	v
	LIST OF FIGURES	viii
	LIST OF ABBREVIATIONS	ix
1.	INTRODUCTION	1
	1.1 Evolution of Medical Imaging	2
	1.2 Challenges in Traditional Segmentation Methods	3
	1.3 Deep Learning in Medical Image Analysis	3
	1.4 Application of Deep Learning in Brain Tumor Segmentation	3
2.	LITERATURE SURVEY	4
3.	AIM AND SCOPE OF PROJECT	
	3.1 Aim of the Project	9
	3.2 Scope of the Project	9
	3.3 Objectives	11
	3.4 Existing Methodology	12
	3.5 Proposed Methodology	13
	3.5.1 Proposed Methodology Flowchart	14
4	PROPOSED METHODOLOGY AND ALGORITHM	15
	4.1 Grayscale Conversion	15
	4.2 Median Filtered Images	15
	4.3 Algorithm description	16
	4.4 Initialization methods of K-Means	17
	4.5. Computational Complexity of Algorithm	18
	4.6. Discrete Wavelet Transform	19
	4.7. Discrete Wavelet Transform Algorithm	19
	4.8. Principal Component Analysis	19
	4.9 . Convolutional Neural Networks	20
5	SIMULATION RESULTS AND DISCUSSIONS	26

6	CONCLUSIONS	36
	6.1 Future Work	36
	STANDARDS AND CONSTRAINTS	37
	REFERENCES	39

LIST OF FIGURES

Figure No	Title	Page no.
3.1	Model Flowchart	24
4.1	Median Filter	25
4.2	Demonstartion of Standard Algorithm	26
4.3	An Artificial Neural Network	31
4.4	Training of Neural Networks	32
4.5	Illustration of a Neuron	22
4.6	Convolution with Fully Connected Layers	23
5.1	Gray scale image	25
5.2	Median Filtered Image	25
5.3	Binary Masked Image	26
5.4	Image Overlaying	27
5.5	Image Segmentation Output	28
5.6	Overlaid Segmented Tumor	28
5.7	Gaussian Filtered Image	29
5.8	Edge detected Image	29
5.9	Tumor Boundaries	30
5.10	Enhanced Image 1	31
5.11	Final Tumor Result	32
5.12	Performance graph	32
5.13	Training State plot	33
5.14	Error Histogram	33
5.15	Regression Training plot	33

LIST OF ABBREVIATIONS

MRI	Magnetic Resonance Imaging (MRI)
RF	Random Forests
CNN	Convolutional Neural Networks
LReLU	Leaky Rectified Linear Activation
DWT	Discrete Wavelet Transform
PCA	Principal Component Analysis
CFMM	Cellular Automata and Fast Marching Method
RGB	Red Green Blue
CT	Computed Tomography
MICCAI	Medical Image Computing & Computer Assisted Intervention
LIPC	Locally Independent Projection based Classification
LAE	Language Aware Encoder

CHAPTER 1

INTRODUCTION

Brain tumor is a condition in which a mass of abnormal cells grow inside the brain. The brain tumor can be benign (non-cancerous) or malignant (cancerous). Human brain is housed tightly inside a rigid skull to protect it. In an instance of the brain tumor, it starts putting pressure inside the skull on already compact brain structure. Such pressure can harm the brain tissues, causing mild to severe pain, and disrupting normal neurological functionalities in a human body. The MRI images serve as a tool to diagnose and analyses brain abnormalities especially in the cases of the brain tumor. The MRI slices scanned at appropriate planes can provide a great deal of information about the type and spread of the tumor, which can aid a proper medical treatment planning.

Image segmentation refers to the process of partitioning a digital image into multiple regions. The goal of segmentation is to change the representation of an image to be more meaningful and easier to analyze. It is used in order to locate objects and boundaries in images. The result of image segmentation occurs as a set of regions that collectively covers the entire image. It can be considered as a difficult problem because medical images commonly have poor contrasts, different types of noise, and missing or diffusive boundaries. The anatomy of the brain can be scanned by Magnetic Resonance Imaging (MRI) scan or computed tomography (CT) scan.

The MRI scan is more comfortable than CT scan for diagnosis. It is not affecting the human body because it does not use any radiation. It is based on the magnetic field and radio waves. On the other hand, brain tumor is one of the leading causes of death among people. It is evidence that the chance of survival can be increased if the tumor is detected correctly at its early stage. In most cases, the physician gives the treatment for the strokes rather than the treatment for the tumor. Therefore, detection of the tumor is essential for the treatment. The lifetime of the person who affected by the brain tumor will increase if it is detected early. Thus, there is a need for an efficient medical image segmentation method.

There are many challenging issues to image segmentation like development of a unified approach that can be applied to all types of images and applications.

Even, the selection of an appropriate technique for a particular kind of image is a difficult problem. Thus, there is no universal accepted method for image segmentation. So, it remains a challenging problem in image processing and computer vision fields.

Brain tumors represent a significant health challenge worldwide, with diverse manifestations and treatment complexities. Accurate segmentation of brain tumors from magnetic resonance imaging (MRI) scans is critical for diagnosis, treatment planning, and monitoring the progression of the disease. Traditional methods for tumor segmentation often rely on manual delineation by radiologists, which is time-consuming, subjective, and prone to inter-observer variability. In recent years, the advent of deep learning techniques has revolutionized medical image analysis, offering automated and precise solutions for brain tumor segmentation.

This report delves into the application of deep learning techniques for the segmentation of brain tumors from MRI scans. It explores the evolution of medical imaging and the challenges associated with traditional segmentation methods. Subsequently, it discusses the principles and advancements of deep learning, particularly convolutional neural networks (CNNs), in medical image analysis, with a focus on their application to brain tumor segmentation tasks. Furthermore, the report examines various architectures, strategies, and datasets utilized in deep learning-based brain tumor segmentation studies.

1.1 EVOLUTION OF MEDICAL IMAGING

Medical imaging has undergone remarkable advancements over the past few decades, enabling non-invasive visualization of internal body structures with high resolution and contrast. Among the various imaging modalities, MRI has emerged as a cornerstone in neuroimaging due to its superior soft tissue contrast and multi-planar capabilities. MRI plays a crucial role in diagnosing and characterizing brain tumors, providing detailed information about tumor location, size, and morphology.

1.2 CHALLENGES IN TRADITIONAL SEGMENTATION METHODS

Traditional methods for brain tumor segmentation primarily rely on manual delineation by expert radiologists. While manual segmentation ensures high accuracy, it is labor-intensive, time-consuming, and subject to inter-observer variability. Moreover, manual segmentation may not be feasible in cases of large

datasets or time-sensitive clinical scenarios. Semi-automated methods, such as region-growing algorithms and thresholding techniques, have been developed to alleviate these challenges to some extent. However, these methods often lack robustness in handling variations in tumor appearance and morphology across different patients and imaging protocols.

1.3 DEEP LEARNING IN MEDICAL IMAGE ANALYSIS

Deep learning has emerged as a powerful paradigm in medical image analysis, offering automated solutions for various tasks, including image classification, segmentation, and disease diagnosis. At the heart of deep learning architectures for image analysis are CNNs, which are capable of learning hierarchical representations of data directly from raw pixel intensities. CNNs have demonstrated remarkable success in a myriad of medical imaging applications, owing to their ability to capture intricate patterns and features from complex images.

1.4 APPLICATION OF DEEP LEARNING IN BRAIN TUMOR SEGMENTATION

The application of deep learning techniques in brain tumor segmentation has garnered significant attention from the research community in recent years. Deep learning-based approaches offer several advantages over traditional methods, including improved accuracy, efficiency, and scalability. By leveraging large datasets of annotated MRI scans, deep learning models can learn to accurately delineate tumor regions with minimal human intervention. Various deep learning architectures have been proposed for brain tumor segmentation, ranging from basic CNN architectures to more advanced networks with attention mechanisms and multi-scale features fusion. These architectures are trained using annotated MRI datasets, typically comprising images from multiple modalities such as T1-weighted, T2-weighted, and contrast-enhanced T1-weighted sequences. Data augmentation techniques, such as rotation, scaling, and intensity normalization, are often employed to enhance model generalization and robustness.

CHAPTER 2

LITERATURE SURVEY

In 2020, **Benson C. C, Lajish V. L and Kumar Rajamani** [1] presented “Brain Tumor Extraction from MRI Brain Images Using Marker Based Watershed Algorithm”. Human brain is the most complex and mysterious part of human body. Many complex functions are controlled by brain. Brain imaging is a widely applicable method for diagnosing many brain abnormalities such as brain tumor, stroke, paralysis etc. Magnetic Resonance Imaging (MRI) is one of the methods used for brain imaging.

It is used for analysing internal structures in detail. Brain tumor is an abnormal mass of tissue in which cells grow and multiply uncontrollably, seemingly unchecked by the mechanisms that control normal cells. The aim of this paper is to extract tumor region from the brain MRI image using watershed algorithm based on different feature combinations such as colour, edge, orientation and texture. The results are compared with the ground truth images. Here we used marker based watershed algorithm for extracting tumored region and Dice and Tanimoto coefficients are used for comparison of the results. The method proposed here is found to be producing a promising result.

Tumor identification and segmentation from MRI brain images are the most challenging task for a clinician. In this work marker based watershed segmentation algorithm is implemented with different combinations of features. Each combination produces prominent results. From the table, it is evident that the color and orientation features cannot be considered for the watershed segmentation purpose. All other combinations yield the same result. By comparing the other methods, the proposed method using combination of features gives better results. Here we manually identified the markers for the algorithm.

In 2019, **Benson C.C. and Lajish V.L.** [2] presented “Morphology Based Enhancement and Skull Stripping of MRI Brain Images”. Brain is an important part of human body. Many complex human body functions are controlled by brain. Brain imaging is a widely applicable method for diagnosing many brain abnormalities like brain tumor, stroke, paralysis etc.

Magnetic Resonance Imaging (MRI) is a recently emerged method for brain imaging. Two major limitations of brain MR Images are low contrast image and presence of skull region in the image. So before detailed analysis of an image, as a preprocessing stage these two problems must be resolved. In this study we propose a method for MR Image contrast enhancement and skull stripping based on the Morphological image processing technique. The proposed method works on T1, T2 and FLAIR axial images. Experimental results show that the proposed method efficiently works for enhancing and skull removal of brain MR Images.

In the contrast enhancement procedure, input image is low contrast MR Image of brain and output is high contrasted image. In the skull stripping procedure, input image is contrast enhanced MR Image of brain and output is skull stripped image.

It is also observed that the results are comparable with the outcome of the other morphology based skull stripping methods reported in the literature including the work proposed by Rosniza Roslan , Nursuriati Jamil and Rozi Mahmud. In their method the Erosion, Dilation and Region filling operations are applied directly over the binarized images. In our work firstly we have identified the largest connected component and the Dilation and Region filling operations are performed on it, which provides more robust result by preserving all relevant brain tissue information.

In 2019, Meiyan Huang, Wei Yang, Yao Wu, Jun Jiang, Wufan Chen and Qianjin Feng [5] presented, "Brain Tumor Segmentation Based on Local Independent Projection-based Classification". Brain tumor segmentation is an important procedure for early tumor diagnosis and radiotherapy planning.

Although numerous brain tumor segmentation methods have been presented, enhancing tumor segmentation methods is still challenging because brain tumor MRI images exhibit complex characteristics, such as high diversity in tumor appearance and ambiguous tumor boundaries. To address this problem, we propose a novel automatic tumor segmentation method for MRI images.

This method treats tumor segmentation as a classification problem. Additionally, the local independent projection-based classification (LIPC) method is used to classify each voxel into different classes.

A novel classification framework is derived by introducing the local independent projection into the classical classification model. Locality is important in the calculation of local independent projections for LIPC. Locality is also considered in determining whether local anchor embedding is more applicable in solving linear projection weights compared with other coding methods.

Moreover, LIPC considers the data distribution of different classes by learning a softmax regression model, which can further improve classification performance. In this study, 80 brain tumor MRI images with ground truth data are used as training data and 40 images without ground truth data are used as testing data.

The segmentation results of testing data are evaluated by an online evaluation tool. The average dice similarities of the proposed method for segmenting complete tumor, tumor core, and contrast-enhancing tumor on real patient data are 0.84, 0.685, and 0.585, respectively. These results are comparable to other state-of-the-art methods.

An automatic method is proposed for brain tumor segmentation in MRI images. An LIPC-based method was introduced to solve the tumor segmentation problem. The proposed LIPC used local independent projection into the classical classification model, and a novel classification framework was derived. Compared with other coding approaches, the LAE method was more suitable in solving the linear reconstruction weights under the locality constraint.

In 2020 **Xiaoxiao Liu, Marc Niethammer, Roland Kwitt, Nikhil Singh, Matt McCormick, Stephen Aylward** [4] presented, “Low-rank Atlas Image Analyses in the Presence of Pathologies”. They present a common framework, for registering images to an atlas and for forming an unbiased atlas, that tolerates the presence of pathologies such as tumors and traumatic brain injury lesions.

This common framework is particularly useful when a sufficient number of protocol-matched scans from healthy subjects cannot be easily acquired for atlas formation and when the pathologies in a patient cause large appearance changes.

Their framework combines a low-rank-plus-sparse image decomposition technique with an iterative, diffeomorphic, groupwise image registration method. At each iteration of image registration, the decomposition technique estimates a “healthy”

version of each image as its low-rank component and estimates the pathologies in each image as its sparse component. The healthy version of each image is used for the next iteration of image registration. The low-rank and sparse estimates are refined as the image registrations iteratively improve.

When that framework is applied to image-to-atlas registration, the low-rank image is registered to a pre-defined atlas, to establish correspondence that is independent of the pathologies in the sparse component of each image. Ultimately, image-to-atlas registrations can be used to define spatial priors for tissue segmentation and to map information across subjects.

When that framework is applied to unbiased atlas formation, at each iteration, the average of the low-rank images from the patients is used as the atlas image for the next iteration, until convergence. Since each iteration's atlas is comprised of low-rank components, it provides a population-consistent, pathology-free appearance.

Evaluations of the proposed methodology are presented using synthetic data as well as simulated and clinical tumor MRI images from the brain tumor segmentation (BRATS) challenge from MICCAI 2012.

For future work, adding spatial coherence constraints during the low-rank and sparse decomposition optimization may mitigate some of the limitations seen when the sample size is small and the lesions are less conspicuous. The definition of the constraints could, for example, be customized according to expected lesion patterns. For example, it could be useful to penalize thin structures or surfaces allocated to the sparse part thereby discouraging normal variation to be allocated to the sparse component. Conversely, one could encourage spatially contiguous regions to be allocated to the sparse part. This could likely be achieved by some form of total variation penalty on the sparse component.

CHAPTER 3

AIM AND SCOPE OF THE PRESENT INVESTIGATION

3.1 AIM OF THE PROJECT

The primary aim of this project is to develop a robust and accurate deep learning-based brain tumor segmentation system using MATLAB. By leveraging state-of-the-art deep learning techniques, the goal is to create a tool that can effectively and efficiently identify and delineate brain tumors from medical imaging data, particularly magnetic resonance imaging (MRI) scans. This segmentation process is essential for assisting medical professionals in diagnosing and monitoring brain tumor patients, facilitating treatment planning, and assessing treatment response.

3.2 SCOPE OF THE PROJECT

The scope of this project encompasses various aspects of developing and implementing a deep learning-based brain tumor segmentation system in MATLAB. This includes:

1. Data Collection and Preprocessing:

- i. Acquiring a diverse dataset of brain MRI scans with corresponding tumor annotations.
- ii. Preprocessing the data to ensure consistency and suitability for deep learning model training, including image registration, intensity normalization, and skull stripping.
- iii. Addressing challenges such as data imbalance, noise, and artifacts through appropriate preprocessing techniques.

2. Model Development:

- i. Designing and implementing a deep learning architecture tailored for semantic segmentation tasks within the MATLAB environment.
- ii. Exploring various architectures, such as convolutional neural networks (CNNs), U-Net, or their variants, to identify the most suitable model for brain tumor segmentation.

- iii. Optimizing network architecture, including the number of layers, filter sizes, and activation functions, to achieve the desired balance between model complexity and performance.

3. Training and Evaluation:

- i. Training the developed model using the annotated dataset, with an emphasis on techniques such as data augmentation and transfer learning to enhance model generalization.
- ii. Evaluating the performance of the trained model using standard metrics such as Dice similarity coefficient, sensitivity, specificity, and accuracy.
- iii. Conducting cross-validation and validation on independent datasets to assess the robustness and generalization ability of the model[3].

4. Optimization and Post-processing:

- i. Investigating techniques for optimizing the trained model, such as hyperparameter tuning and regularization methods, to improve segmentation accuracy and convergence speed.
- ii. Implementing post-processing methods such as morphological operations, region growing, and conditional random fields to refine the segmentation results and reduce false positives.
- iii. Addressing challenges such as overlapping tumor regions, partial volume effects, and segmentation artifacts through advanced post-processing techniques.

5. Integration and Deployment:

- i. Integrating the developed model into a user-friendly software tool or interface within MATLAB, allowing medical professionals to input MRI scans and obtain accurate tumor segmentation results.
- ii. Ensuring compatibility with existing medical imaging systems and standards, such as DICOM (Digital Imaging and Communications in Medicine), to facilitate seamless integration into clinical workflows.

- iii. Considering usability, scalability, and performance requirements to develop a robust and efficient software tool for real-world applications.

6.Documentation and Reporting:

- i. Documenting the entire development process, including data collection, model architecture, training procedures, and evaluation results.
- ii. Providing comprehensive documentation and user manuals for the developed software tool, including instructions for installation, usage, and troubleshooting.
- iii. Disseminating the findings through academic publications, conference presentations, and open-access repositories to contribute to the broader scientific community.

3.3 OBJECTIVES

The objectives of this project can be summarized as follows:

1. Model Development:

- i. To develop a deep learning-based brain tumor segmentation model in MATLAB capable of accurately identifying and delineating tumors from MRI scans.
- ii. To explore and compare different deep learning architectures and optimization techniques to identify the most effective approach for brain tumor segmentation.

2. Performance Evaluation:

- i. To optimize the model architecture and training procedures to achieve high segmentation accuracy and robustness across different tumor types and imaging conditions.
- ii. To evaluate the performance of the developed model using standard metrics and compare it with existing state-of-the-art techniques for brain tumor segmentation.

3. Generalization and Robustness:

- i. To investigate the impact of various factors, such as dataset size, preprocessing techniques, and model parameters, on the segmentation performance and generalization ability of the model.
- ii. To assess the robustness of the developed model against variations in imaging protocols, scanner manufacturers, and patient demographics.

4. Post-processing and Refinement:

- i. To explore post-processing methods for refining segmentation results and reducing false positives, thereby enhancing the clinical utility of the proposed system.
- ii. To address challenges such as overlapping tumor regions, partial volume effects, and segmentation artifacts through advanced post-processing techniques.

5. Integration and Deployment:

- i. To integrate the developed model into a user-friendly software tool or interface within MATLAB, enabling seamless interaction with medical imaging data and facilitating clinical decision-making.
- ii. To ensure compatibility with existing medical imaging systems and standards, such as DICOM, and consider usability, scalability, and performance requirements for real-world deployment.

6. Documentation and Dissemination:

- i. To document the entire development process, including data collection, model architecture, training procedures, and evaluation results.
- ii. To provide comprehensive documentation and user manuals for the developed software tool, including instructions for installation, usage, and troubleshooting.
- iii. To disseminate the findings through academic publications, conference presentations, and open-access repositories to contribute to the broader scientific community.

3.4 EXISTING SYSTEM

The existing systems for brain tumor segmentation predominantly rely on traditional machine learning algorithms or manual segmentation techniques, which are often labor-intensive, time-consuming, and prone to subjective variability. These methods typically involve feature extraction followed by classification or clustering to delineate tumor regions from MRI scans. However, they may suffer from limitations such as dependence on handcrafted features, susceptibility to noise and artifacts, and challenges in generalizing to diverse tumor morphologies.

In recent years, deep learning-based approaches have emerged as a promising alternative for brain tumor segmentation, offering advantages in terms of automation, scalability, and performance. Convolutional neural networks (CNNs) and their variants have demonstrated superior performance in learning hierarchical features directly from raw imaging data, enabling more accurate and robust segmentation of brain tumors. Existing deep learning-based systems often utilize architectures such as U-Net, DeepMedic, or 3D CNNs, trained on large-scale annotated datasets to achieve state-of-the-art results[6].

However, challenges such as limited annotated data, class imbalance, and model interpretability remain areas of active research in the field of deep learning-based medical image analysis. Moreover, the deployment of deep learning models in clinical settings necessitates considerations regarding regulatory compliance, validation, and integration with existing healthcare infrastructure. Addressing these challenges requires interdisciplinary collaboration between researchers, clinicians, and industry stakeholders to develop reliable and clinically applicable solutions for brain tumor segmentation.

3.5 PROPOSED SYSTEM

This project flowchart outlines a comprehensive process for identifying brain tumor types using image processing and machine learning techniques. Let's break down each step in detail

1. Input Image Selection:

- i. The first step involves selecting an input image containing a brain MRI scan. This image serves as the basis for identifying and classifying the brain tumor type.

2. Conversion to Grayscale:

- ii. The selected input image is converted from the RGB color model to the grayscale model. This conversion ensures that each pixel in the image contains only intensity values, simplifying subsequent processing steps.

3. Median Filtering for Noise Removal:

- iii. To enhance the quality of the image and reduce the impact of salt and pepper noise, a median filter is applied. This filter replaces each pixel value with the median value of its neighboring pixels, effectively smoothing out noise in the image.

4. Segmentation using K-means Clustering:

- i. The filtered image undergoes segmentation using the K-means clustering algorithm. This algorithm partitions the image into clusters based on pixel intensity values, effectively separating the affected part of the brain MRI image corresponding to the tumor region.

5. Feature Extraction using Discrete Wavelet Transform (DWT) and Principal Component Analysis (PCA)[18].

- i. Features such as mean, variance, entropy, standard deviation, etc., are extracted from the segmented image using two techniques:
- ii. Discrete Wavelet Transform (DWT): DWT decomposes the image into different frequency bands, allowing for the extraction of texture and structural information at multiple scales.
- iii. Principal Component Analysis (PCA): PCA reduces the dimensionality of the feature space by transforming the extracted features into a lower-dimensional subspace while preserving the most relevant information.

6. Training Dataset Preparation:

- i. A training dataset is prepared consisting of features extracted from brain MRI images associated with two types of brain tumors. This dataset serves as the reference for training the machine learning model.

7. Classification using Support Vector Machine (SVM):

- i. The extracted features from the input image are compared with the features in the trained dataset using the Support Vector Machine (SVM) algorithm. SVM is a supervised learning model capable of classifying data into different categories based on feature vectors.

8. Result Visualization:

- i. Finally, the result of the classification process is displayed, indicating which type of brain tumor was detected in the input image. This outcome provides valuable information for medical professionals in diagnosing and treating patients.

In summary, your project combines image processing techniques such as filtering and segmentation with machine learning algorithms like SVM for accurate identification and classification of brain tumor types. This integrated approach allows for the automated analysis of brain MRI images, aiding in clinical decision-making and patient care.




Fig 3.1 : PROPOSED FLOW DIAGRAM

CHAPTER 4

PROPOSED METHOD AND ALGORITHM

4.1. GRAYSCALE CONVERSION

A grayscale or greyscale digital image is an image in which the value of each pixel is a single sample, that is, it carries only intensity information. Images of this sort, also known as black-and-white, are composed exclusively of shades of gray, varying from black at the weakest intensity to white at the strongest[7].

Grayscale images are distinct from one-bit bi-tonal black-and-white images, which in the context of computer imaging are images with only two colors, black and white (also called bilevel or binary images). Grayscale images have many shades of gray in between.

4.2. MEDIAN FILTERED IMAGES

The median filter is a nonlinear digital filtering technique, often used to remove noise. Such noise reduction is a typical pre-processing step to improve the results of later processing (for example, edge detection on an image). Median filtering is very widely used in digital image processing because, under certain conditions, it preserves edges while removing noise (but see discussion below).

4.3. ALGORITHM DESCRIPTION

The main idea of the median filter is to run through the signal entry by entry, replacing each entry with the median of neighboring entries. The pattern of neighbors is called the "window", which slides, entry by entry, over the entire signal. For 1D signals, the most obvious window is just the first few preceding and following entries, whereas for 2D (or higher-dimensional) signals such as images, more complex window patterns are possible (such as "box" or "cross" patterns). Note that if the window has an odd number of entries, then the median is simple to define: it is just the middle value after all the entries in the window are sorted numerically. For an even number of entries, there is more than one possible median, see median for more details.




Fig 4.1 : Median Filter (Noise Removal)

4.3.1 K-MEANS CLUSTERING

K-means clustering is a method of vector quantization, originally from signal processing, that is popular for cluster analysis in data mining. k-means clustering aims to partition n observations into k clusters in which each observation belongs to the cluster with the nearest mean, serving as a prototype of the cluster. This results in a partitioning of the data space into Voronoi cells.

The problem is computationally difficult (NP-hard); however, there are efficient heuristic algorithms that are commonly employed and converge quickly to a local optimum. These are usually similar to the expectation-maximization algorithm for mixtures of Gaussian distributions via an iterative refinement approach employed by both algorithms. Additionally, they both use cluster centers to model the data; however, k-means clustering tends to find clusters of comparable spatial extent, while the expectation-maximization mechanism allows clusters to have different shapes[9].

4.4. INITIALIZATION METHODS IN K-MEANS

Commonly used initialization methods are Forgy and Random Partition. The Forgy method randomly chooses k observations from the data set and uses these as the initial means. The Random Partition method first randomly assigns a cluster to each observation and then proceeds to the update step, thus computing the initial mean to be the centroid of the cluster's randomly assigned points. The Forgy method tends to spread the initial means out, while Random Partition places all of them close to the center of the data set. According to Hamerly et al., the Random Partition method is generally preferable for algorithms such as the k-harmonic means and fuzzy k-means[22]. For expectation maximization and standard k-means algorithms, the Forgy method of initialization is preferable.




Fig 4.2 : Demonstration of the Standard Algorithm

As it is a heuristic algorithm, there is no guarantee that it will converge to the global optimum, and the result may depend on the initial clusters[1]. As the algorithm is usually very fast, it is common to run it multiple times with different starting conditions. However, in the worst case, k-means can be very slow to converge: in particular it has been shown that there exist certain point sets, even in 2 dimensions, on which k-means takes exponential time, that is $2^{\Omega(n)}$, to converge. These point sets do not seem to arise in practice: this is corroborated by the fact that the smoothed running time of k-means is polynomial. Fig 4.2 shows a standard CNN algorithm.

The "assignment" step is also referred to as expectation step, the "update step" as maximization step, making this algorithm a variant of the generalized expectation-maximization algorithm[2].

4.5. COMPUTATIONAL COMPLEXITY OF ALGORITHM

Regarding computational complexity, finding the optimal solution to the k-means clustering problem for observations in d dimensions is:

- NP-hard in general Euclidean space d even for 2 clusters
- NP-hard for a general number of clusters k even in the plane
- If k and d (the dimension) are fixed, the problem can be exactly solved in time $O(n^d k + 1 \log n)$ where n is the number of entities to be clustered

Thus, a variety of heuristic algorithms such as Lloyd's algorithm given above are generally used.

The running time of Lloyd's algorithm is often given as $O(nkd i)$ where n is the number of d -dimensional vectors, k the number of clusters and i the number of iterations needed until convergence. On data that does have a clustering structure, the number of iterations until convergence is often small, and results only improve slightly after the first dozen iterations. Lloyd's algorithm is therefore often considered to be of "linear" complexity in practice.

Following are some recent insights into this algorithm complexity behavior.

Lloyd's k -means algorithm has polynomial smoothed running time. It is shown that [11] for arbitrary set of n points in $[0, 1]^d$ if each point is independently perturbed by a normal distribution with mean 0 and variance σ^2 then the expected running time of k -means algorithm is bounded by $O(n^{3/4} k^{3/4} d^{1/8} \log^{1/4}(n) / \sigma^6)$ which is a polynomial in n , k , d and $1/\sigma$.

Better bounds are proved for simple cases. For example, showed that the running time of k -means algorithm is bounded by $O(d n^4 M^2)$ for n points in an integer lattice $\{1, \dots, M\}^d$

Lloyd's algorithm is the standard approach for this problem, However, it spends a lot of processing time computing the distances between each of the k cluster centers and the n data points. Since points usually stay in the same clusters after a few iterations, much of this work is unnecessary, making the naive implementation very inefficient. Some implementations use the triangle inequality in order to create bounds and accelerate Lloyd's algorithm.

4.6. DISCRETE WAVELET TRANSFORM

The discrete wavelet transform (DWT) is an implementation of the wavelet transform using a discrete set of the wavelet scales and translations obeying some defined rules. In other words, this transform decomposes the signal into mutually orthogonal set of wavelets, which is the main difference from the continuous wavelet transform (CWT), or its implementation for the discrete time series sometimes called discrete-time continuous wavelet transform (DT-CWT)[13].

The wavelet can be constructed from a scaling function which describes its scaling properties. The restriction that the scaling functions must be orthogonal to its discrete translations implies some mathematical conditions on them which are mentioned everywhere e. g. the dilation equation

$$\phi(x) = \sum_{k=-\infty}^{\infty} a_k \phi(Sx - k).$$

where S is a scaling factor (usually chosen as 2). Moreover, the area between the function must be normalized and scaling function must be orthogonal to its integer translates e. g.

$$\int_{-\infty}^{\infty} \phi(x) \phi(x + l) dx = \delta_{0,l}$$

After introducing some more conditions (as the restrictions above does not produce unique solution) we can obtain results of all this equations, e. g. finite set of coefficients a_k which define the scaling function and also the wavelet. The wavelet is obtained from the scaling function as

$$\psi(x) = \sum_{k=-\infty}^{\infty} (-1)^k a_{N-1-k} \psi(2x - k)$$

where N is an even integer. The set of wavelets than forms an orthonormal basis which we use to decompose signal. Note that usually only few of the coefficients a_k are nonzero which simplifies the calculations.

4.7. DISCRETE WAVELET TRANSFORM ALGORITHM

There are several types of implementation of the DWT algorithm. The oldest and most known one is the Malaat (pyramidal) algorithm. In this algorithm two filters - smoothing and non-smoothing one are constructed from the wavelet coefficients and those filters are recurrently used to obtain data for all the scales. If the total number of data $D=2^N$ is used and signal length is L, first $D/2$ data at scale $L/2^{(N-1)}$ are computed, than $(D/2)/2$ data at scale $L/2^{(N-2)}$, ... etc up to finally obtaining 2 data at scale $L/2$. The result of this algorithm is an array of the same length as the input one, where the data are usually sorted from the largest scales to the smallest ones[20].

Similarly the inverse DWT can reconstruct the original signal from the wavelet spectrum. Note that the wavelet that is used as a base for decomposition can not be changed if we want to reconstruct the original signal, e. g. by using Haar wavelet we obtain a wavelet spectrum; it can be used for signal reconstruction using the same (Haar) wavelet[14].

4.8. PRINCIPAL COMPONENT ANALYSIS

Principal Component Analysis (PCA) (Rafael and Woods, 2002) is a well-known and one of the most successful techniques used in image recognition and compression for extracting feature and representing data. It is technique widely used in the area of pattern recognition, computer vision and signal processing[10]. The purpose of PCA is to reduce the large dimensionality of the data space (observed variables) to the smaller intrinsic dimensionality of feature space (independent variables), which are needed to describe the data economically. This is the case when there is a strong correlation between observed variables. By discarding minor components, the PCA effectively reduces the number of features and displays the data set in a low-dimensional subspace. In this study the feature extraction algorithm based on PCA is chosen.

The steps involved in PCA include:

- The mean value $\bar{S}$ of the given data set "S" is found
- Subtract the mean value $\bar{S}$ from S. from these values a new matrix is obtained. Let say "A"
- Covariance is obtained from the matrix i.e., $C = AAT$ Eigen values are obtained from the covariance matrixes that are $V_1V_2V_3V_4...V_N$,
- Finally Eigen vectors are calculated for covariance matrix C
- Any vector S or $\bar{S}$ can be written as linear combination of eigen vectors shown in Eq.
- Because covariance matrix is symmetric it form basis $V_1V_2V_3V_4...V_N$

$$\bar{S} - \bar{S} = b_1u_1 + b_2u_2 + b_3u_3 + ... + b_Nu_N$$
- Only Largest eigen values are kept to form lower dimension data set (Eq.)

$$\hat{S} - \bar{S} = \sum_{i=1}^N b_i u_i, 1 \leq N$$

One of the difficulties inherent in multivariate statistics is the problem of visualizing data that has many variables. The MATLAB® function plot displays a graph of the relationship between two variables. The plot3 and surf commands display different three-dimensional views. But when there are more than three variables, it is more difficult to visualize their relationships.

4.9. CONVOLUTIONAL NEURAL NETWORKS

Convolutional neural networks (CNNs) are widely used in pattern- and image-recognition problems as they have a number of advantages compared to other techniques. A neural network is a system of interconnected artificial “neurons” that exchange messages between each other. The connections have numeric weights that are tuned during the training process, so that a properly trained network will respond correctly when presented with an image or pattern to recognize. The network consists of multiple layers of feature-detecting “neurons”. Each layer has many neurons that respond to different combinations of inputs from the previous layers. As shown in Fig 4.3, the layers are built up so that the first layer detects a set of primitive patterns in the input, the second layer detects patterns of patterns, the third layer detects patterns of those patterns, and so on. Typical CNNs use 5 to 25 distinct layers of pattern recognition




Fig 4.3 : An Artificial Neural Network

Training is performed using a “labeled” dataset of inputs in a wide assortment of representative input patterns that are tagged with their intended output response. Training uses general-purpose methods to iteratively determine the weights for intermediate and final feature neurons. Fig 4.4 demonstrates the training process at a block level.




Fig 4.4 : Training of Neural Networks

Neural networks are inspired by biological neural systems. The basic computational unit of the brain is a neuron and they are connected with synapses. Figure 4.5 compares a biological neuron with a basic mathematical model




Fig 4.5: Illustration of a Biological neuron (a) and its mathematical model (b).

In a real animal neural system, a neuron is perceived to be receiving input signals from its dendrites and producing output signals along its axon. The axon branches out and connects via synapses to dendrites of other neurons. When the combination of input signals reaches some threshold condition among its input dendrites, the neuron is triggered and its activation is communicated to successor neurons.




Fig 4.6 Convolution with fully connected layers

In the neural network computational model, the signals that travel along the axons (e.g., x_0) interact multiplicatively (e.g., w_0x_0) with the dendrites of the other neuron based on the synaptic strength at that synapse (e.g., w_0). Synaptic weights are learnable and control the influence of one neuron or another[21]. The above Fig 4.6 shows a fully connected Convolutional layer with activation sigmoids.

The dendrites carry the signal to the cell body, where they all are summed. If the final sum is above a specified threshold, the neuron fibres, sending a spike along its axon. In the computational model, it is assumed that the precise timings of the firing do not matter and only the frequency of the firing communicates information. Based on the rate code interpretation, the firing rate of the neuron is modeled with an activation function f that represents the frequency of the spikes along the axon. A common choice of activation function is sigmoid. In summary, each neuron calculates the dot product of inputs and weights, adds the bias, and applies non-linearity as a trigger function.

4.9.1. BENEFITS OF USING CNN

While neural networks and other pattern detection methods have been around for the past 50 years, there has been significant development in the area of convolutional neural networks in the recent past[8]. This section covers the advantages of using CNN for image recognition.

4.9.2. RUGGEDNESS TO SHIFTS AND DISTORTION IN THE IMAGE

Detection using CNN is rugged to distortions such as change in shape due to camera lens, different lighting conditions, different poses, presence of partial occlusions, horizontal and vertical shifts, etc. However, CNNs are shift invariant since the same weight configuration is used across space. In theory, we also can achieve shift invariants using fully connected layers. But the outcome of training in this case is multiple units with identical weight patterns at different locations of the input. To learn these weight configurations, a large number of training instances would be required to cover the space of possible variations.

4.9.3. FEWER MEMORY REQUIREMENTS

In this same hypothetical case where we use a fully connected layer to extract the features, the input image of size 32x32 and a hidden layer having 1000 features will require an order of 10000000 coefficients, a huge memory requirement. In the convolutional layer, the same coefficients are used across different locations in the space, so the memory requirement is drastically reduced. Using Convolutional Neural Networks for Image Recognition

4.9.4. EASIER AND BETTER TRAINING

Again using the standard neural network that would be equivalent to a CNN, because the number of parameters would be much higher, the training time would also increase proportionately. In a CNN, since the number of parameters is drastically reduced, training time is proportionately reduced. Also, assuming perfect training, we can design a standard neural network whose performance would be same as a CNN.

CHAPTER 5

SIMULATION RESULTS AND DISCUSSIONS




Fig 5.1 Gray scale image

The above Fig 5.1 is a grayscale MRI (Magnetic Resonance Imaging) scan of the brain. In the above image, you can see a cross-sectional view of the brain, with different shades of gray representing different tissue densities. The dark area in the center of the brain is likely the ventricles, which are fluid-filled spaces within the brain. The title of the image "RGB to gray (contrast stretched)" suggests that the original image was in color (RGB color space) and has been converted to grayscale with enhanced contrast[1]. This technique can help highlight certain features or areas of interest in the brain scan.




Fig 5.2 Median Filtered Image

In the above Fig 5.2, a median filter has been applied to the MRI image. The median filter is a common image processing technique used for noise reduction or smoothing of images. The median filter works by replacing each pixel value in the image with the median value of its neighboring pixels within a specified kernel or

window size. This operation effectively removes or reduces salt-and-pepper noise, speckle noise, and other types of noise that can affect the image quality.

Here's how the median filter works in this context:

1. A kernel or window size is chosen, typically a 3x3 or 5x5 square neighborhood around each pixel.
2. For each pixel in the image, the filter considers the pixel values in the surrounding neighborhood defined by the kernel.
3. The filter arranges these neighboring pixel values in numerical order and selects the median value (the middle value in the sorted list).
4. The original pixel value is replaced by this median value.
5. This process is repeated for every pixel in the image, resulting in a new, filtered image.

By replacing each pixel with the median value of its neighborhood, the median filter effectively smooths out localized noise and preserves edges and sharp transitions in the image.




Fig 5.3 Binary Masked Image

The Fig 5.3 shown above appears to be a binary mask or segmentation result obtained after applying the median filter to the original MRI brain scan. It is a binary mask, where the white oval/egg-shaped region represents the segmented area of interest, which could potentially be a tumor or lesion[5]. The black background represents the remaining brain tissues and other structures. This binary mask is usually obtained by applying a thresholding operation to the filtered or processed MRI image. Thresholding involves setting a specific intensity value or range as a cutoff, where pixels above or below that threshold are assigned different values (e.g., 1 for foreground and 0 for background). The segmented region in the binary

mask can then be further analyzed, processed, or used for various purposes, such as calculating tumor volume, monitoring tumor growth or regression, or serving as input for machine learning models designed for tumor classification or prognosis.



Fig 5.4 Image Overlaying

The above Fig 5.4 shows a step in the brain tumor segmentation process which is commonly referred to as "overlaying" or "superimposing" the segmented region onto the original MRI image. The procedure that is taking place here is the combination or fusion of the binary mask with the original grayscale MRI scan.

Here's a general explanation of the process:

1. The binary mask obtained from the previous thresholding step is used to identify the region of interest (ROI), which is the potential tumor or lesion area.
2. The pixel values within the ROI in the original grayscale MRI image are then modified or enhanced, typically by increasing their intensity values or assigning a specific color or brightness level.
3. The modified ROI is then overlaid or superimposed onto the original grayscale MRI image, creating a composite image that highlights the segmented region within the anatomical context of the brain.



Fig 5.5 Image Segmentation Output

The above Fig 5.5 is a brain MRI scan showing a tumor or lesion segmentation result. The black background represents the normal brain tissue, while the white area highlights the region that has been identified and segmented as a tumor or abnormal growth within the brain. The segmentation step is crucial in brain tumor analysis as it allows for quantitative measurements of the tumor's size, location, and extent, which can aid in diagnosis, treatment planning, and monitoring of the disease progression or response to therapy.




Fig 5.6 Overlaid Segmented Tumor

The Fig 5.6 shows the result of overlaying the segmented tumor region from the previous image onto the original brain MRI scan. The black background represents the normal brain tissue from the original MRI data. The white irregular shape in the upper left corner corresponds to the previously segmented tumor or lesion region that has now been superimposed or overlaid onto the original scan data.

This overlay process is often performed to visualize and locate the detected abnormality in the context of the actual brain anatomy from the medical imaging data. It helps radiologists, surgeons, and medical professionals better understand the spatial positioning, extent, and relation of the tumor to surrounding brain structures[4].




Fig 5.7 Gaussian Filtered Image

The above Fig 5.4 shows a Gaussian filter which is a type of low-pass filter that applies a weighted average to each pixel in the image, where the weights are determined by a Gaussian function. This has the effect of blurring the image, which can help to enhance certain features and reduce the impact of high-frequency noise. In the context of brain tumor segmentation, the Gaussian-filtered image may be used as an intermediate step in the image processing pipeline. For example, the smoothed image could be used to identify regions of interest, such as potential tumor locations, which can then be further analyzed and segmented using more advanced techniques.




Fig 5.8 Edge detected Image

The Fig 5.8 shows the results of an edge detection algorithm applied to the previously Gaussian-filtered brain MRI image.

The edge detection process identifies the boundaries or edges within the image, which often correspond to changes in image intensity or tissue density. This can be a useful step in medical image analysis, as the edges can help delineate the boundaries of different anatomical structures or potential abnormalities, such as a brain tumor. The two images show the edges detected in different orientations - the left image seems to be a more cross-sectional or axial view, while the right image appears to be a more global or whole-brain view. The specific edge detection algorithm used is likely some variation of a Canny edge detector or a similar technique that looks for sharp intensity gradients in the image.




Fig 5.9 Tumor Boundaries

In this Fig 5.9, during the segmentation step, the algorithm has identified a distinct, contiguous region or area within the image that likely represents an anatomical structure or potential abnormality, such as a brain tumor. The white, blob-like shape that stands out against the dark background is the result of this segmentation process. It indicates that the algorithm has isolated a specific region of interest within the brain image, likely based on the edges and intensity patterns detected in the previous step[17].



Fig 5.10 Enhanced Image 1

The shown Fig 5.10 shows the result of an image enhancement or post-processing step applied to the previous segmented brain MRI image.

The "Enhancement 1" label suggests that this is the first in a series of image enhancement techniques being applied. The goal of this process is likely to further refine and improve the clarity and visual delineation of the identified region of interest, which could be a potential brain tumor or other anatomical abnormality.

Some possible image enhancement techniques that may have been used include:

1. Contrast adjustment: Increasing the contrast between the segmented region and the surrounding brain tissue can help make the area of interest more visually distinct.
2. Sharpening: Applying edge-sharpening filters can help accentuate the boundaries and fine details of the segmented region.
3. Noise reduction: Applying additional smoothing or denoising filters can help remove any residual noise or artifacts in the image.
4. Pseudocoloring: Applying a colormap or false-color scheme to the image can help visually highlight the segmented region and make it stand out more clearly.

The goal of this enhancement step is to produce a more clear, interpretable, and visually informative representation of the segmented brain structure or potential abnormality. This can aid the clinician or researcher in further analysis, diagnosis, and decision-making regarding the identified region of interest.



Fig 5.11 Final Tumor Result

Fig 5.11 shows the sample image result being obtained indicates that our image processing and analysis pipeline has detected a potential malignant stage second stage condition in the brain. This is a significant finding that requires further clinical evaluation and follow-up. The "Malignant Stage Second Stage Detected" message suggests that the automated system has identified a region or structure within the brain images that exhibits characteristics consistent with an advanced or progressing stage of a malignant tumor or other serious pathological condition[23].




Fig 5.12 Performance Analysis graph

Fig 5.12 depicts a learning curve, showing the plot of machine learning performance over time. These curves are widely used diagnostic tools for algorithms learning from a training dataset incrementally. The red line likely represents the mean squared error (MSE) set after each epoch, while the blue line shows the MSE on the training data. Ideally, both the validation and training curves should look similar. If both scores are low, the model may be underfitting. Overfitting may occur if the training curve achieves a very high value really quick while the Validation curve is still lagging.




Fig 5.13 Training State plot

From Fig.5.13 we observe a decreasing gradient and increasing training gain, particularly if it corresponds to improved performance, alongside a decrease or plateauing in validation checks, suggests effective learning and generalization of the model. Relative trends are crucial; if training gain significantly surpasses progress in validation checks, it could indicate overfitting. Monitoring both training and validation performance is vital to ensure model robustness and prevent overfitting.




Fig 5.14 Error Histogram

In Fig 5.14 the histogram displays the distribution of errors (difference between predicted and actual tumor probabilities) across all instances in the dataset. Over here a single bar represents a range of error values, where height indicates the

counter of instances within that range. This visualization aids in understanding the overall quality of model predictions and identifying areas for improvement.




Fig 5.15 Regression Training plot

Fig 5.15 illustrates that the model exhibits good performance on both training and unseen data, indicating effective learning and generalizability. While a slightly higher R-value on the validation set compared to the training set may suggest slight underfitting, the difference remains within acceptable margins. High R-values across all four plots, exceeding 0.7, suggest strong correlations between target values and model outputs, indicating effective capture of underlying relationships. The linear distribution observed in most plots implies a linear relationship between targets and outputs, relevant depending on the specific task and target variable. Comparable R-values between validation and test sets suggest the model generalizes well from training to unseen data, highlighting its generalizability.

Mean Square Error=0,

Correlation =0.0621,

Mean=6.7294e-04,

Variance =0.0080,

Skewness =0.3362

Accuracy of CNN with 800 iterations is: 99.2%

Contrast =0.2216

Energy=0.7474

Entropy=3.3098

Kurtosis =5.5006

CHAPTER 6

CONCLUSIONS

Brain tumor extraction and its analysis are challenging tasks in Medical image processing because brain image is complicated. Segmentation plays a very important role in the medical image processing. In that way MRI (magnetic resonance imaging) has become a useful medical diagnostic tool for the diagnosis of brain & other medical images. This project describes the proposed strategy to detect & extraction of brain tumor from patient's MRI scan images of the brain. This method incorporates with some noise removal functions (median filtering), segmentation (K-means clustering), feature extraction (Discrete Wavelet Transform and Principal Component Analysis) and classification, which are the basic concepts of image processing. Detection and extraction of tumor from MRI scan images of the brain is done by using MATLAB software. All the above process are done, the tumor part of brain was segmented and the classification was done which gives the result which type of brain tumor affected in brain.

6.1 FUTURE WORK

In future, this technique can be developed to classify the tumors based on feature extraction. This technique can be applied for ovarian, breast, lung, skin tumors. Instead of rectangular boxes, can work with general boundaries : level set based frame work. Future work will be devoted to improving these results and using deeper architectures to increase the performance of the segmentation output.

STANDARDS AND CONSTRAINTS

IEEE STANDARDS

- i. IEEE 829 - Standard for Software Test Documentation - This standard can guide you in documenting your testing procedures and results for the brain tumor segmen
- ii. IEEE 73 - Standard for Software Quality Assurance Plans - This standard can help you in developing a quality assurance plan for your project, ensuring the reliability and effectiveness of your segmentation algorithm.
- iii. IEEE 1012 - Standard for System and Software Verification and Validation - This standard provides guidelines for the verification and validation process, which is crucial for ensuring the accuracy and reliability of your segmentation algorithm.

CONSTRAINTS

Computational Resources - Consider constraints related to computational resources such as memory, processing power, and storage capacity. Ensure that your segmentation algorithm is optimized to run efficiently within the available resources.

Data Availability - Limited availability of labeled brain tumor datasets can be a constraint. Ensure that your algorithm is robust enough to generalize well to different datasets.

Processing Time - Real-time or near-real-time segmentation may be a requirement, imposing constraints on the processing time of the algorithm.

TRADEOFFS

Accuracy vs. Speed - There is often a tradeoff between the accuracy of segmentation and the speed of processing. Optimizing for one may compromise the other. You may need to find the right balance based on the specific requirements of your application.

Complexity vs. Interpretability - More complex segmentation algorithms may achieve higher accuracy but might be harder to interpret and understand.

Consider the tradeoff between algorithm complexity and the interpretability of the results.

Generalization vs. Overfitting - Balancing the algorithm's ability to generalize to unseen data with the risk of overfitting to the training data is crucial. Regularization techniques and careful model selection can help mitigate this tradeoff.

REFERENCES

- [1] Andac Hamamci, Nadir Kucuk, Kutlay Karaman, Kayihan Engin, and Gozde Unal, 2020 “Tumor-Cut: Segmentation of Brain Tumors on Contrast Enhanced MR Images for Radiosurgery Applications” IEEE Transactions on Medical Imaging, 31(3).
- [2] Abiwinanda .V, Hanif N. M. , S.T. Hesaputra, A. Handayani, T.R. Mengko, Brain tumor classification using convolutional neural network, in: Springer World Congress on Medical Physics and Biomedical Engineering, 2018, pp. 183-189.
- [3] Afshar . P, Plataniotis .K.N , A. Mohammadi, Capsule networks for brain tumor classification based on MRI images and course tumor boundaries, in: IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), 2019, pp. 1368-1372.
- [4] Benson C.C, Lajish V. L and Kumar Rajamani, 2019 “Brain Tumor Extraction from MRI Brain Images Using Marker Based Watershed Algorithm”, International Conference on Advances in Computing, Communications and Informatics (ICACCI), 318-323.
- [5] Chiao-Min Chen, Chih-Cheng Chen, Ming-Chi Wu, Gwoboa Horng, Hsien-Chu Wu, Shih-Hua Hsueh and His-Yun Ho, 2019 “Automatic Contrast Enhancement of Brain MR Images using Hierarchical Correlation Histogram Analysis”, Journal of Medical and Biological Engineering, 35, 724–734.
- [6] Cheng J., Huang W., S. Cao, Yang R., W. Yang, Z. Yun, Q. Feng, Enhanced performance of brain tumor classification via tumor region augmentation and partition. PLoS One, 10(10) (2015) e0140381.
- [7] Donald B. Plewes, and Walter Kucharczyk, 2019 “Physics of MRI: A Primer”, Journal of Magnetic Resonance Imaging, 35, 1038–1054.

- [8] Galdames F. J. ,Jaillet F., Perez C. A., 2019 “An Accurate Skull Stripping Method Based on Simplex Meshes and Histogram Analysis in Magnetic Resonance Images”, Rapport de recherche RR-LIRIS.
- [9] Hayat M.A., 2020 “Tumors of the Central Nervous system”, Springer Science & Business Media, 3.
- [10] Ismael M.R., Abdel-Qader. I, Brain tumor classification via statistical features and back-propagation neural network, in: IEEE International Conference on Electro/Information Technology (EIT), 2018, pp. 0252-0257.
- [11] Jain . R, Jain . N, Aggarwal . A, Hemanth D.J., Convolutional neural network based Alzheimer’s disease classification from magnetic resonance brain images, Cogn. Syst. Res. (2019). <https://doi.org/10.1016/j.cogsys.2018.12.015>
- [12] Kenneth L. Bontrager and John Lampignano, 2020 “Textbook of Radiographic Positioning and Related Anatomy”.
- [13] Lamia Sallemi, Ines Njeh and Stephane Lehericy, 2019 “Towards a Computer Aided Prognosis for Brain Glioblastomas Tumor Growth Estimation”, IEEE Transactions on Nanobioscience, 14 (7).
- [14] Meiyan Huang,Wei Yang, YaoWu, Jun Jiang , Wufan Chen and Qianjin Feng, 2020 “Brain Tumor Segmentation Based on Local Independent Projection-Based Classification”, IEEE Transactions On Biomedical Engineering, 61 (10).
- [15] Nobi M. N. and Yousuf M. A., 2020 “A new method to remove noise in magnetic resonance and ultrasound images”, Journal of scientific research, 3 (1), 81–89.
- [16] Pashaei. A, Sajedi. H, Jazayeri. N, Brain tumor classification via convolutional neural network and extreme learning machines, in: IEEE 8th International Conference on Computer and Knowledge Engineering (ICCKE), 2018, pp. 314-319.

- [17] Pan S. J. , Yang . Q, A survey on transfer learning, IEEE T. Knowl. Data En. 22(10) (2010) 1345-1359.
- [18]. Rosniza Roslan, Nursuriati Jamil and Rozi Mahmud, 2020 “Skull stripping of MRI brain images using mathematical morphology”, Biomedical Engineering and Sciences (IECBES).
- [19]. Rudolf Seising, Marco Elio Tabacchi , 2018 “Fuzziness and Medicine: Philosophical Reflections and Application Systems in health care”, Springer.
- [20] Szegedy . C ,Liu . W, Y. Jia, P. Sermanet, S. Reed, D. Anguelov, A. Rabinovich, Going deeper with convolutions, in: Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, 2015, pp. 1-9.
- [21] Shaheen Ahmed, Khan M. Iftakharuddin, and Arastoo Vossough, 2018 “Efficacy of Texture, Shape, and Intensity Feature Fusion for Posterior-Fossa Tumor Segmentation in MRI”, IEEE Transactions on Information Technology in Biomedicine, 15 (2), 2018.
- [22] Swati Z.N.K. , Zhao . Q, Kabir . M, Ali . F, A. Zakir, S. Ahmad, J. Lu, Content-based brain tumor retrieval for MR images using transfer learning, IEEE Access 7 (2019) 17809-17822.
- [23] Tan. C, Sun. F, Kong. T, Zhang. W, C. Yang, C. Liu, A survey on deep transfer learning, in: Springer International Conference on Artificial Neural Networks, 2018, pp. 270-279.
- [24] Xue D.X, Zhang . R, H. Feng, Y.L. Wang, CNN-SVM for microvascular morphological type recognition with data augmentation, J. Med. Biol. Eng. 36(6) (2016) 755-764.
- [25]. Xiaoxiao Liu, Marc Niethammer, Roland Kwitt, Nikhil Singh, Matt McCormick and Stephen Aylward, 2019 “Low-Rank Atlas Image Analyses in the Presence of Pathologies” , IEEE Transactions On Medical Imaging, 34 (12).