

DESIGN AND FABRICATION OF AIRCRAFT TOWING ROBOT USING IOT

Submitted in partial fulfilment of the requirements for the award of
Bachelor of Engineering degree in Aeronautical Engineering

By

K.ARAVIND RATHNAVEL (40260003)

M.MANOJ (40260016)



DEPARTMENT OF AERONAUTICAL ENGINEERING

SCHOOL OF MECHANICAL ENGINEERING

SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY

(DEEMED TO BE UNIVERSITY)

Accredited with grade "A++" by NAAC

JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI – 600119

APRIL 2024



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY

(DEEMED TO BE UNIVERSITY)

Accredited "A++" Grade by NAAC | 12B Status by UGC | Approved by AICTE

www.sathyabama.ac.in

DEPARTMENT OF AERONAUTICAL ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the Bonafide work of **K.ARAVIND RATHNAVEL (40260003)** and **M.MANOJ (40260016)** who carried out the project entitled "**DESIGN AND FABRICATION OF AIRCRAFT TOWING ROBOT USING IOT**" under my supervision from December 2023 to April 2024.

Internal Guide

Dr. T. ANAND., M.E., (Ph.D.)

Head of the Department

Dr. A. Anderson., M.E., Ph.D.

Submitted for Viva voce Examination held on 05-04-2024

Internal Examiner

External Examiner

DECLARATION

We are **ARAVIND RATHNAVEL.K (40260016)** and **MANOJ.M (40260016)** here by declare that the Project Report entitled "**DESIGN AND FABRICATION OF AIRCRAFT TOWING ROBOT USING IOT**" done by me under the guidance of **Dr. T. ANAND, M.E., Ph.D.**, is submitted in partial fulfilment of the requirements for the award of Bachelor of Engineering degree in Aeronautical Engineering.

ARAVIND RATHNAVEL K



MANOJ M



DATE: 05-04-2024

PLACE: CHENNAI

SIGNATURE OF THE CANDIDATE

ACKNOWLEDGEMENT

We are pleased to acknowledge our sincere thanks to Board of Management of **SATHYABAMA** for their kind encouragement in doing this project and for completing it successfully. I am grateful to them.

We are convey my sincere thanks to **Dr. A. ANDERSON., M.E., Ph.D.**, Head of the Department, Department of Aeronautical Engineering for providing me necessary support and details at the right time during the progressive reviews.

We are would like to express my sincere and deep sense of gratitude to our Project Guide **Dr. T. ANAND M.E., Ph.D.**, for his valuable guidance, suggestions and constant encouragement paved way for the successful completion of our project work.

We are also express my thanks to all Teaching and Non-teaching staff members of the Department of Aeronautical Engineering who were helpful in many ways for the completion of the project.

ABSTRACT

The project titled “Design and Fabrication of Aircraft Towing Robot” assisted landing is the use of a robot manipulator to grasp an unmanned aerial vehicle during vertical takeoff and landing and pull it to a predetermined landing spot. An Internet of Things (IOT)-based robot system for towing aircraft is provided. The towing robot, when affixed to an aeroplane enables the aircraft to move without requiring the jet engines to operate. The IOT-based controlling system of the towing robot system is installed in the towing vehicle. In order to achieve this capability, a line follower robot often uses a sensor grid. The technique that enables a line follower to use an array of sensors to do the same task with the fewest number of sensors is covered in this paper. Additionally, we can lessen the robot's complexity by cutting down on the number of sensors. It also brings down the price.

TABLE OF CONTENTS

CHAPTER NO.	TITLE	PAGE NO.
	ABSTRACT	i
	LIST OF FIGURES	v
	LIST OF SYMBOLS AND ABBEREVIATIONS	vi
1.	INTRODUCTION	1
	1.1 Introduction	1
	1.2 Block diagram	2
	1.2.1. Transmitter	2
	1.2.2 Receiver side	3
	1.2.3 Block diagram description	3
	1.3 Existing system	4
	1.3.1 Existing system disadvantages	4
	1.4 Proposed system	5
	1.4.1 Advantages	5
2.	LITERATURE SURVEY	6
	2.1 Introduction	8
	2.2 Literature review on the topic aircraft towing robots	8
	2.3 The history and development aircraft towing	10
	2.4 Design principles and configuration for aircraft towing robots	11
	2.5 Performance characteristics	13
	2.6 Factors can significantly affect the performance of aircraft towing robots	15
3.	AIM AND OBJECTIVE	17
	3.1 Aim	17

3.2 Objective	17
3.3 Problem statement	17
3.4 Circuit diagram	18
4. MATERIAL AND EXPERIMENTAL METHOD	19
4.1 Methodology	19
4.2 Project Design	19
4.3 Modules	20
4.3.1 Module description	20
4.4 Material and experimental method	22
4.4.1 Ir Sensor	22
4.4.1.1 Description	22
4.4.1.2 Features	24
4.4.1.3 Application	24
4.4.2 Arduino	24
4.4.2.1 Description	24
4.4.2.2 Features	26
4.4.2.3 Application	26
4.4.3 Buzzer	26
4.4.3.1 Description	26
4.4.3.2 Features	28
4.4.3.3 Application	28
4.4.4 Motor Driver	28
4.4.4.1 Description	28
4.4.4.2 Features	29

	4.4.4.3 Technical specification	29
	4.4.5 Dc Gear Motor (60rpm)	30
	4.4.5.1 Description	30
	4.4.5.2 Features	31
	4.4.5.3 Applications	32
	4.4.6 Robotic Vehicle	32
	4.4.6.1 Description	32
	4.4.6.2 Features	34
	4.4.6.3 Applications	34
	4.4.7 Wifi	35
	4.4.7.1 Description	35
	4.4.7.2 Features	36
	4.4.7.3 Applications	37
	4.4.8 Power Supply Unit	37
	4.4.8.1 Description	37
	4.4.8.2 Features	39
	4.4.8.3 Applications	39
	4.5 Software Required	39
	4.5.1 Arduino IDE	39
	4.5.2 Programming Language	40
5.	RESULT AND DISCUSSION	42
6.	CONCLUSION	43
	REFERENCE	44

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE NO.
3.1	Circuit Diagram	18
4.1	Project Design	20
4.2	IR Sensor	23
4.3	IR Circuit Diagram	24
4.4	Arduino Uno	25
4.5	Buzzer	27
4.6	Buzzer circuit diagram	27
4.7	Motor Driver	29
4.8	Dc Gear Motor (60rpm)	31
4.9	Robotic Vehicle	33
4.10	Wifi Module	35
4.11	Wifi Module Interface With Arduino	36
4.12	Adapter (12v 1amp)	37
4.13	Circuit Diagram <i>Adapter</i> (12v 1amp)	38

LIST OF SYMBOLS AND ABBREVIATIONS

ATRs	Aircraft Towing Robots
IR	Infrared Sensor
PC	Personal Computer
IOT	Internet of things
WiFi	Wireless Fidelity
ADC	Analog-To-Digital Converter
PSU	Power Supply Unit
AC	Alternating current
DC	Direct current
MCU	Microcontroller Unit
IC	Integrated Circuit
ICSP	In-circuit serial programming
USB	Universal Serial Bus
I/O	Input/Output
IDE	Integrated Development Environment
VDC	Volts Direct Current

CHAPTER – 1


INTRODUCTION

1.1 INTRODUCTION


The preceding art goes into considerable length on the subject of aircraft ground movement. The primary function of aeroplane engines in the aviation industry is to operate aircraft inside airports, especially during runway taxiing. These engines often consume a lot of fuel and produce a lot of noise when used for ground movement. A robot is essentially an electro-mechanical device or system that performs a range of physical tasks under the control of a computer program or electrical circuit. In particular, in the current world, robots are becoming an increasingly important part of human existence. Robotic technology also makes automation possible in factories, airports, hospitals, and offices. Technology like this is used in security systems, entertainment, space exploration, defiance forces, and a variety of risky mission performances combined with automation.

1.2 BLOCK DIAGRAM:

1.2.1 TRANSMITTER:



1.2.2 RECEIVER SIDE:



1.2.3 BLOCK DIAGRAM DESCRIPTION

The intricate system intended to transform aviation ground handling operations is demonstrated in the block diagram of the IoT-powered aircraft towing robot. Fundamental parts of the transmitter section include an IR sensor, motor driver, WiFi module, battery, and microcontroller. The microcontroller coordinates the robot's motions and interactions, acting as its brain. The robot can accurately tow aircraft because the motor driver converts control data into precise motor motions. By identifying impediments in its path, the IR sensor improves the robot's navigational abilities and guarantees safe and effective operation. Furthermore, the WiFi module permits wireless access for Internet of Things integration, enabling remote control and monitoring of the robot's operations.

The block diagram shows parts including motors, IR sensors, and buzzers on the receiver side. The motors are in charge of carrying out the towing procedure and provide the required power to move the aircraft. In order to help with obstacle avoidance and navigation, the IR sensors on the receiver side complement those on the transmitter side. The buzzer alerts operators to particular operating conditions or

events by use of an audible feedback device. When combined, these parts create a sturdy system that is capable of precisely and dependably towing aircraft on its own.

Moreover, the capabilities of the aeroplane towing robot are increased by the integration of cloud communication via IoT technology. The robot can access and share data remotely by utilising cloud services, which allows for real-time data analysis, control, and monitoring. In addition to increasing the effectiveness of aircraft towing operations, this link creates opportunities for more sophisticated features and improvements down the road. All things considered, the block diagram represents a state-of-the-art approach that combines hardware elements with Internet of Things technology to reinvent aircraft ground handling procedures and open the door for a more automated and networked aviation business.

1.3. EXISTING SYSTEM

- The current method for the remote steering control of the towing tractor vehicle may include a guidance system placed below a taxiway or along the taxiway's edge where the aircraft is being rowed. Naturally, the aeroplane being towed's pilot or a remote directing system could be able to control the towing tractor vehicle. Furthermore, an inertial navigation system or a guidance system placed beneath or at the edge of a taxiway may be able to manage the towing tractor vehicle independently, especially when it is being driven back to the terminal for its next use.

1.3.1 Existing system disadvantages

- Limited Automation: The existing system may rely on manual control inputs from pilots or remote operators, leading to potential human errors and limitations in automation.

- **Dependency on Guidance Systems:** Remote steering control means or guidance systems positioned beneath taxiways may require additional infrastructure and maintenance, increasing the complexity and cost of the system.
- **Potential Safety Risks:** Manual operation of towing tractor vehicles by pilots or remote guiding systems could pose safety risks if not properly monitored or controlled, especially in busy airport environments.
- **Lack of Efficiency:** The manual or semi-automated nature of the existing system may result in inefficiencies in aircraft towing processes, leading to longer turnaround times and increased fuel consumption.

1.4 PROPOSED SYSTEM

The modules that make up this multifunctional robot each have an own set of functions. These line-following based aircraft towing robots with IOT-based control are becoming more prevalent in rural and airport areas due to technology improvements.

1.4.1 Advantages

- **Efficiency:** The IOT-based aircraft towing robot system control robot enhances the efficiency of aircraft movement by allowing aero planes to be towed without the need for jet engines, reducing fuel consumption and emissions.
- **Cost-Effectiveness:** By utilizing IOT technology and a minimal number of sensors, the proposed system reduces the complexity and cost of the line follower robot, making it a more affordable solution for airport operations.
- **Automation:** The system enables automation in airport ground operations, leading to improved safety, precision, and reliability in aircraft towing processes.
- **Technological Advancement:** The integration of IOT technology in aircraft towing robots represents a technological advancement in the aviation industry, showcasing the potential for innovation and progress in autonomous systems.

CHAPTER – 2

LITERATURE SURVEY

MaedeZolanvari ,Member Raj Jain, Salman , Student Member(2015)The purpose of this investigation is to investigate possible candidates for data links for unmanned aerial vehicles (UAVs). The range of uses for UAVs has increased significantly, including commercial use, recreational purposes, lifesaving and rescue operations, etc. In contrast to conventional wireless communications, these systems' data linkages lack a universally accepted structure that would guarantee UAVs and other flying vehicles may coexist safely. This inspired us to offer an extensive overview of the various data connectivity technologies that could be utilised by UAVs. Our objective is to research the most recent developments and potential applicants, then thoroughly compare each of them.

This survey's objective is to draw attention to the advantages and disadvantages of the available data link choices as well as their suitability for meeting the communication needs of UAVs. This article does a thorough analysis of numerous related wireless technologies, including Wi-Fi, cellular technologies, and satellite connectivity. We also highlight a number of promising current standards that can be adapted for these types of data transfers. Next, we go over organisations that are involved with standards and actively working in the field of civilian unmanned systems. In conclusion, we discuss a few upcoming problems in this field and offer a few possible fixes to spur more investigation

Wei Zhang(2013) The new towing taxi-out departure mode, with its apparent benefits of low energy consumption, low emissions, and great efficiency, has emerged as the favoured option to replace the conventional departure mode of civil aircraft. However, because the bulk of the system is located in the back, the inertia might potentially cause lateral instability and perhaps "Jack-knifing." This work used computer virtual simulation technology to study the lateral instability mechanism and affecting elements of the civil aircraft towing taxi-out system, using AM210 tractors and Boeing 737–400s as research objects.

The findings demonstrate that when the system's sliding speed exceeded 15 km/h and the lateral slip condition was present, the "Jack-knifing" phenomenon was brought on by the system's lateral instability. Additionally, the system's safety, side-show, and jack-knifing zones were specified based on steering angle and towing speed. Additionally, by examining the system's lateral stability, a towing safety zone was established under various airport track circumstances. The study's result might offer a theoretical foundation and point of reference for the new taxi-out departure mode's safe implementat

Edwards ,California(2013) Commercial supersonic flight over land is currently prohibited by the US Federal Aviation Administration (FAA) because to the potential for sonic booms to cause property damage and disturbance to ground-based observers. Low-boom aircraft designs and various techniques have been discovered by innovators in NASA and industry to lessen sonic boom noise and disruption. Getting these technologies out of the wind tunnel and into flight, where their performance can be confirmed in real-world settings, is NASA's current research priority. NASA wants to replace the sonic boom with new sub-scale vehicles that are aerodynamically structured from tip to tail to produce a soft thump sound. Testing in the real atmosphere will reveal a lot about the new supersonic waveform. But it costs a lot of money to construct even a research aircraft on a smaller scale. NASA recently looked several other methods for confirming some aspects of these new designs

NASA Ames Research Center 2015 NASA has been committed to advancing space research and aeronautics since its beginnings. NASA's scientific and technical information (STI) programme is essential to the agency's ability to continue playing this significant role. The Chief Information Officer of the Agency oversees the NASA STI initiative. The STI from NASA is gathered, arranged, archived, and distributed by it. Access to the NTRS Registered and its public interface, the NASA Technical Reports Server, is made possible by the NASA STI programme, which offers one of

the world's largest collections of STI related to aviation and space science. Findings are released by NASA through the NASA STI Report Series, which comprises the following report, as well as through non-NASA channels NASA wants to replace the sonic boom with new sub-scale vehicles that are aerodynamically structured from tip to tail to produce a soft thump sound. Testing in the real atmosphere will reveal a lot about the new supersonic waveform. But it costs a lot of money to construct even a research aircraft on a smaller scale. NASA recently looked several other methods for confirming some aspects of these new designs

2.1 INTRODUCTION

Setting the scene is done by stressing the importance of aviation ground handling and the difficulties in using conventional aircraft towing techniques in the introduction to the literature review done for the Aircraft Towing Robot project. By going over the labor-intensive nature of manual towing operations, the inherent safety concerns of crowded airport environments, and the increasing need for effective and autonomous ground handling solutions, it sets the scene for the research project. The introduction also describes the goals of the literature review, which include highlighting important techniques, technologies, and research themes that are pertinent to the advancement of robotic systems for aircraft towing. It also highlights how crucial it is to use the information already in existence from government agencies, business, and academia to guide the development and deployment of the Aircraft Towing Robot. All things considered, the introduction helps to situate the literature review in the larger framework of aircraft ground handling, emphasising its significance and connection to the project's aims and purposes.

2.2 LITERATURE REVIEW ON THE TOPIC OF AIRCRAFT TOWING ROBOTS

- A literature review on the topic of Aircraft Towing Robots would typically encompass a thorough examination of existing research, scholarly articles, technical reports, and relevant literature related to the development, application, and challenges of robotic systems in aviation ground handling. Below is a hypothetical outline of such a literature review:
 - Introduction to Aircraft Towing Robots:
Brief overview of the importance of ground handling operations in aviation.

Introduction to the concept of Aircraft Towing Robots (ATRs) and their potential benefits in improving efficiency and safety.

- Historical Context and Evolution:

Historical background of aircraft ground handling methods, including manual towing and conventional tow vehicles.

Evolution of robotics and automation technologies in aviation and the emergence of ATRs as a modern solution.

- Technologies and Components:

Exploration of the key technologies and components utilized in ATRs, such as IOT, IR sensors, WiFi, motor driver circuits, motors, microcontrollers, and communication systems.

Review of advancements in sensor technology for obstacle detection and collision avoidance.

Examination of control algorithms and software used for trajectory planning, navigation, and autonomous operation.

- Applications and Case Studies:

Overview of real-world applications and case studies showcasing the deployment of ATRs in various airport environments.

Analysis of the benefits, challenges, and lessons learned from these deployments, including improvements in efficiency, safety, and operational costs.

- Challenges and Considerations:

Discussion of the challenges and considerations associated with the development and implementation of ATRs, such as regulatory compliance, safety certification, and interoperability with existing ground handling infrastructure.

Examination of human factors considerations, including operator training, human-robot interaction, and acceptance of automation in aviation.

- Future Directions and Research Opportunities:

Exploration of emerging trends and future directions in ATR research and development.

Identification of research gaps and opportunities for further advancements, such as enhanced autonomy, integration with air traffic management systems, and sustainability considerations.

- Conclusion:

Summary of key findings from the literature review.

Reflection on the significance of ATRs in modernizing aviation ground handling operations and potential implications for the future of the industry.

- By conducting a comprehensive literature review following this outline, researchers can gain valuable insights into the current state of knowledge, identify research gaps, and inform the design and development of Aircraft Towing Robots for improved efficiency, safety, and sustainability in aviation ground handling.

2.3 THE HISTORY AND DEVELOPMENT OF AIRCRAFT TOWING

- The history and development of Aircraft Towing Robots (ATRs) trace back to the evolution of automation and robotics in aviation ground handling operations. While manual methods of towing aircraft have been prevalent since the early days of aviation, the need for more efficient, reliable, and safer alternatives led to the exploration of robotic solutions. Here is an overview of the history and development of ATRs:
- Early Concepts and Prototypes: The initial concepts of ATRs emerged in the late 20th century, driven by advancements in robotics technology and the increasing complexity of aircraft. Early prototypes focused on basic functionalities such as towing small aircraft on predetermined paths within controlled environments.
- Advancements in Sensor Technology: With the development of more sophisticated sensor technologies, such as infrared (IR) sensors, lidar, and ultrasonic sensors, ATRs became capable of detecting obstacles and navigating complex airport environments autonomously. These advancements paved the way for more practical and effective ATR designs.
- Integration of IOT and Connectivity: The integration of Internet of Things (IOT) technology and wireless connectivity enabled ATRs to communicate with centralized control systems, ground crews, and other airport infrastructure. This

connectivity facilitated real-time monitoring, remote operation, and data exchange, enhancing overall efficiency and coordination in ground handling operations.

- **Enhanced Maneuverability and Precision:** Motor driver circuits, motors, and advanced control algorithms allowed ATRs to achieve enhanced maneuverability and precision in towing operations. These technologies enabled ATRs to navigate tight spaces, follow predefined paths, and execute towing maneuvers with greater accuracy and reliability.
- **Regulatory Compliance and Certification:** As ATRs became more advanced and capable, regulatory bodies and aviation authorities developed standards and certification processes to ensure their safe and compliant operation within airport environments. Compliance with safety regulations, airworthiness standards, and interoperability requirements became crucial considerations in the development and deployment of ATRs.
- **Commercial Adoption and Deployment:** Over the years, ATRs have gained traction in the aviation industry, with airports and ground handling companies increasingly adopting them to improve operational efficiency and safety. Commercially available ATRs offer a range of capabilities, from towing small aircraft on tarmacs to maneuvering larger commercial jets within airport terminals.
- **Future Directions:** Looking ahead, the development of ATRs continues to evolve with advancements in robotics, artificial intelligence, and sustainable energy solutions. Future ATRs may incorporate features such as autonomous decision-making, adaptive learning, and eco-friendly power sources to further enhance their performance and environmental sustainability.
- In summary, the history and development of Aircraft Towing Robots reflect the ongoing evolution of automation and robotics in aviation ground handling, driven by the pursuit of efficiency, safety, and innovation in the industry.

2.4 DESIGN PRINCIPLES AND CONFIGURATIONS FOR AIRCRAFT TOWING ROBOTS

- Design principles and configurations for Aircraft Towing Robots (ATRs) are crucial considerations in ensuring their effectiveness, efficiency, and safety in aviation

ground handling operations. Here are some key design principles and configurations commonly applied in the development of ATRs:

- **Modular Design:** A modular design approach allows for flexibility and scalability in configuring ATRs to suit various aircraft types and operational requirements. Modular components, such as towing mechanisms, sensor arrays, and communication systems, can be easily interchanged or upgraded to accommodate changing needs.
- **Robust Construction** : ATRs must be robustly constructed to withstand the rigors of daily operations in airport environments. Robust materials, such as aluminum alloys or composite materials are often used to ensure durability and longevity.
- **Safety Features:** Safety is paramount in ATR design. Incorporating safety features such as redundant systems, emergency stop mechanisms, and collision avoidance sensors helps mitigate risks and ensure the safe operation of ATRs in close proximity to aircraft and ground personnel.
- **Adaptive Control Systems:** Adaptive control systems enable ATRs to adjust their behavior and responses based on real-time environmental conditions and operational requirements. These systems may incorporate advanced algorithms for trajectory planning, obstacle avoidance, and adaptive learning to optimize performance and efficiency.
- **Maneuverability and Precision:** ATRs must exhibit high levels of maneuverability and precision to navigate congested airport environments and perform precise towing maneuvers. This requires precise control of motorized actuators, steering mechanisms, and braking systems to achieve accurate positioning and movement.
- **Scalability and Versatility:** ATRs should be designed to accommodate a wide range of aircraft sizes and configurations, from small general aviation aircraft to large commercial jets. Scalable and versatile designs allow ATRs to adapt to varying towing scenarios and accommodate different operational requirements.
- **Integration with Airport Infrastructure:** ATRs should be designed to seamlessly integrate with existing airport infrastructure, including taxiways, aprons, and docking facilities. This requires compatibility with standard ground handling

equipment and communication protocols to ensure smooth coordination and operation within airport environments.

- **Energy Efficiency and Sustainability:** Incorporating energy-efficient components, regenerative braking systems, and sustainable power sources, such as electric motors or hybrid propulsion systems, can reduce environmental impact and operational costs associated with ATRs.
- **Human-Machine Interface:** User-friendly interfaces and control systems are essential for operators to interact with ATRs effectively. Intuitive interfaces, ergonomic controls, and visual feedback mechanisms enhance operator situational awareness and facilitate safe and efficient operation of ATRs.
- **Compliance with Regulations and Standards:** ATRs must comply with relevant aviation regulations, safety standards, and certification requirements to ensure airworthiness and regulatory compliance. Designing ATRs with adherence to established standards and guidelines promotes interoperability and acceptance within the aviation industry.
- By incorporating these design principles and configurations, ATR developers can create robust, efficient, and safe robotic systems tailored to the unique challenges and requirements of aircraft towing operations in airport environments.

2.5 PERFORMANCE CHARACTERISTICS

- Performance characteristics play a critical role in assessing the effectiveness, efficiency, and suitability of Aircraft Towing Robots (ATRs) for aviation ground handling operations. Here are some key performance characteristics that are commonly evaluated in ATRs:
- **Towing Capacity:** Towing capacity refers to the maximum weight of aircraft that an ATR can safely tow. It is essential for ATRs to have sufficient towing capacity to handle a wide range of aircraft sizes, from small general aviation planes to large commercial jets.
- **Speed and Acceleration :** Speed and acceleration capabilities determine how quickly an ATR can move aircraft on the ground. ATRs with higher speeds and acceleration rates can expedite ground handling operations and minimize aircraft

- **Maneuverability:** Maneuverability refers to the ability of an ATR to navigate tight spaces, negotiate turns, and perform precise towing maneuvers. ATRs with superior maneuverability can efficiently maneuver around obstacles and navigate congested airport environments.
- **Accuracy and Precision:** Accuracy and precision are crucial for ATRs when positioning aircraft on taxiways, aprons, and parking stands. ATRs must be capable of accurately aligning aircraft with docking facilities and following predefined paths to ensure safe and efficient ground handling operations.
- **Obstacle Detection and Avoidance :** ATRs should be equipped with sensors and collision avoidance systems to detect and avoid obstacles in their path, such as other aircraft, vehicles, and ground equipment. Effective obstacle detection and avoidance capabilities help prevent accidents and ensure safe operation in busy airport environments.
- **Reliability and Durability:** Reliability and durability are essential for ATRs to withstand the demands of daily operations in airport environments. ATRs should be robustly constructed and equipped with reliable components to minimize downtime and maintenance requirements.
- **Energy Efficiency:** Energy efficiency is important for ATRs to minimize operational costs and reduce environmental impact. ATRs should be designed with energy-efficient components and systems, such as electric motors and regenerative braking systems, to optimize energy consumption during towing operations.
- **Operational Range and Endurance :** Operational range and endurance refer to the distance an ATR can travel on a single charge or tank of fuel and the duration it can operate continuously without recharging or refueling. ATRs with longer operational ranges and endurance can handle more towing tasks without interruption.
- **Communication and Control Systems:** Communication and control systems enable operators to remotely monitor and control ATRs during ground handling operations. ATRs should be equipped with reliable communication links and user-friendly interfaces to facilitate seamless interaction and supervision.

- **Compliance with Regulations and Standards:** ATRs must comply with relevant aviation regulations, safety standards, and certification requirements to ensure airworthiness and regulatory compliance. Performance characteristics should be evaluated in accordance with established standards and guidelines to ensure safe and reliable operation in airport environments.
- By assessing these performance characteristics, operators and stakeholders can evaluate the capabilities and suitability of ATRs for specific ground handling tasks and operational environments. This helps optimize efficiency, safety, and productivity in aviation ground handling operations.

2.6 FACTORS CAN SIGNIFICANTLY AFFECT THE PERFORMANCE OF AIRCRAFT TOWING ROBOTS

- Several factors can significantly affect the performance of Aircraft Towing Robots (ATRs) in aviation ground handling operations. Understanding these factors is crucial for optimizing the efficiency, safety, and reliability of ATRs. Here are some key factors that can influence ATR performance:
- **Weight and Size of Aircraft:** The weight and size of the aircraft being towed directly impact the performance of ATRs. Larger and heavier aircraft may require more powerful ATRs with higher towing capacities and torque capabilities to move them effectively.
- **Surface Conditions:** Surface conditions, such as pavement type, slope, and friction coefficient, can affect the traction and maneuverability of ATRs. Smooth and level surfaces provide better traction and reduce the risk of slippage during towing operations.
- **Environmental Factors:** Environmental factors, including weather conditions such as rain, snow, and wind, can affect ATR performance. Adverse weather conditions may reduce visibility, traction, and sensor accuracy, impacting the ability of ATRs to operate safely and effectively.
- **Obstacles and Congestion:** The presence of obstacles, such as other aircraft, vehicles, or ground equipment, can impede the movement of ATRs and affect their

performance. Congested airport environments with limited space may require ATRs to navigate tight spaces and perform precise maneuvers to avoid collisions.

- **Sensor Accuracy and Reliability:** The accuracy and reliability of sensors, such as IR sensors, lidar, and cameras, are critical for obstacle detection, navigation, and collision avoidance in ATRs. Sensor inaccuracies or failures can compromise the safety and effectiveness of ATR operations.
- **Communication and Control Systems:** The reliability and responsiveness of communication and control systems play a crucial role in ATR performance. Effective communication links and responsive control interfaces are essential for operators to monitor and control ATRs in real-time, especially in remote or autonomous operation scenarios.
- **Power Source and Energy Efficiency:** The power source and energy efficiency of ATRs impact their operational range, endurance, and overall efficiency. ATRs equipped with energy-efficient components and regenerative braking systems can minimize energy consumption and extend operational uptime.
- **Maintenance and Reliability:** Regular maintenance and timely servicing are essential for ensuring the reliability and performance of ATRs. Maintenance issues, component failures, and unexpected downtime can disrupt ground handling operations and impact overall productivity.
- **Operator Training and Experience:** The training and experience level of ATR operators can influence their ability to effectively operate and control ATRs. Proper training programs and ongoing skill development are essential for ensuring safe and efficient ATR operations.
- **Regulatory Compliance and Certification:** Compliance with aviation regulations, safety standards, and certification requirements is essential for ensuring the airworthiness and regulatory compliance of ATRs. Non-compliance with regulations can result in operational restrictions and penalties, affecting ATR performance and viability.
- By considering these factors and implementing appropriate measures to address them, operators and stakeholders can optimize the performance of ATRs and enhance efficiency, safety, and reliability in aviation ground handling operations.

CHAPTER – 3

AIM AND OBJECTIVE

3.1 AIM

The project's goal is to create an Aircraft Towing Robot (ATR) that uses Internet of Things (IoT) technology to improve ground handling operations' productivity and security.

3.2 OBJECTIVE

This project's scope encompasses the design, development, and deployment of the IoT-powered Aircraft Towing Robot (ATR). To construct a functioning ATR prototype, infrared (IR) sensors, WiFi connectivity, motor drivers, gear motors, a buzzer, and a microcontroller must all be integrated. As part of the study, the ATR's functioning will be tested in both simulated and actual aircraft towing scenarios in order to assess its effectiveness, safety, and performance. Scalability, dependability, and ease of maintenance will also be taken into account when designing the ATR.

3.3 PROBLEM STATEMENT

The problem statement in the context of early disease detection through physiological characteristics revolves around the challenge of timely identification and intervention in potential health issues before they progress to advanced stages. Despite the advancements in healthcare technology, there remains a need to enhance the accuracy, efficiency, and accessibility of early disease detection methods utilizing physiological markers. Issues such as limited access to healthcare services, lack of awareness about preventive healthcare measures, and the complexity of analyzing diverse physiological data pose significant hurdles in achieving proactive disease management. Addressing these challenges requires innovative solutions that integrate wearable devices, sensors, artificial intelligence, and data analytics to enable early detection, personalized treatment, and improved healthcare outcomes.

3.4 CIRCUIT DIAGRAM:




Fig:3.1 : Circuit Diagram

CHAPTER – 4

MATERIAL AND EXPERIMENTAL METHOD

4.1 METHODOLOGY

The methodology for early disease detection through physiological characteristics involves a multi-faceted approach that integrates various technologies and analytical techniques. This methodology typically includes the collection of relevant physiological data through wearable devices, sensors, or medical tests to establish baseline parameters for individuals. Subsequently, advanced data analytics, including machine learning algorithms and artificial intelligence, are employed to analyze the collected data and identify patterns or deviations indicative of potential health issues. Moreover, the methodology may involve the development of predictive models that utilize physiological markers to assess an individual's risk of developing specific diseases. These models can aid in early risk stratification and enable targeted interventions or preventive measures to mitigate health risks. Furthermore, the methodology may encompass the integration of electronic health records and telemedicine platforms to facilitate remote monitoring and real-time feedback on individuals' health status. This approach enhances the continuity of care and enables healthcare providers to intervene promptly in case of any concerning changes in physiological parameters. Overall, the methodology for early disease detection through physiological characteristics emphasizes a proactive and personalized approach to healthcare, leveraging technology and data-driven insights to enable early intervention, improve health outcomes, and enhance overall well-being.

4.2 PROJECT DESIGN:

A well-liked collection of design guidelines for object-oriented software development is called SOLID. The abbreviation SOLID stands for the following five fundamental design principles: interface segregation, dependability inversion, open-closed principle, Liskov substitution principle, and single responsibility principle. Software engineers frequently employ all five of them, and they offer significant advantages to developers. Reducing dependencies enables engineers to make changes to one part of software without affecting other areas. This is the main objective of the SOLID principles. They also aim to

facilitate the understanding, extension, and maintenance of designs. In the end, software developers may create flexible, efficient, and agile software more easily by adhering to these design principles.




Fig:4.1 : Project Design

4.3 MODULES:

- Sensor interfacing
- Preparing power supply unit
- Micro-controller programming
- Reading analog data
- Test and debug

4.3.1 Module description:

- SENSOR INTERFACING

Sensor interfacing encompasses the process of readying the sensor's output for precise measurement and processing by the microcontroller's ADC. This typically entails amplifying weak signals, filtering out noise and undesired frequencies, and employing various signal conditioning techniques to guarantee compatibility and precision. Moreover,

ensuring appropriate voltage levels, impedance alignment, and calibration are crucial components of effective sensor interfacing.

- PREPARING POWER SUPPLY UNIT

A power supply unit (PSU) converts household AC electricity into regulated DC power at a lower voltage for the internal components of a controller. Typically, it steps down mains electricity, usually around 240 volts AC, to a more practical voltage, like 12 volts DC. Power supplies come in two primary types: linear and switch mode. Linear power supplies use a transformer to decrease voltage. The AC signal is rectified and stabilized to produce a consistent DC voltage.

An AC adapter, also called an AC/DC adapter or converter, is a form of external power supply often housed in a case resembling an AC plug. Adapters for battery-operated devices might be labeled as chargers or rechargers. AC adapters are utilized with electrical gadgets that require power but lack the internal components to convert the needed voltage and power from the mains supply. The internal workings of an external power supply closely mirror those of an integrated or internal one

- MICRO-CONTROLLER PROGRAMMING

A microcontroller, short for microcontroller unit (MCU), is an integrated circuit (IC) that can be programmed to perform various functions based on its programming. There are numerous types of microcontrollers available, each offering a diverse range of capabilities. The adaptability of microcontrollers is what renders them one of the most potent tools in contemporary design. This guide aims to elucidate the fundamental aspects of microcontrollers and their programming

- READING ANALOG DATA

The microcontroller aboard features an analog-to-digital converter (ADC) component, tasked with interpreting the fluctuating voltage and converting it into a numeric range spanning from 0 to 1023. When the shaft is fully turned in one direction, resulting in 0 volts reaching the pin, the input is registered as 0. Conversely, when the shaft is rotated entirely in the opposite direction, providing 5 volts to the pin, the input is logged as 1023.

Within this spectrum, the `analogRead()` function furnishes a value between 0 and 1023, indicative of the voltage proportion applied to the pin.

- **TEST AND DEBUG**

Testing involves confirming the correctness of functionality and can be conducted at different phases of module development such as requirements analysis, interface design, algorithm design, implementation, and integration with other modules. This discussion focuses on implementation testing, which encompasses more than just execution testing; it may include correctness proofs, code tracing, and peer reviews.

Debugging is an iterative process that includes executing tests and correcting code. The testing performed during debugging serves a distinct purpose from final module testing. Final module testing aims to showcase correctness, whereas debugging testing primarily aims to pinpoint errors. This discrepancy significantly impacts the choice of testing methods.

4.4 MATERIAL AND EXPERIMENTAL METHOD:

4.4.1 IR sensor

4.4.1.1 Description

An infrared sensor is an electronic device that emits signals to detect various aspects of its environment. It can measure the temperature of an object and detect motion. There are different types of infrared sensors, with passive IR sensors being particularly notable as they solely measure existing infrared radiation without emitting any themselves.




Fig:4.2 : Ir Sensor

An infrared sensor is an electronic device designed to emit signals for detecting various aspects of its environment. It can gauge the temperature of an object and identify motion. These sensors specifically measure infrared radiation and are categorized into active and passive types. Passive IR sensors, for instance, solely detect existing infrared radiation without emitting any themselves.

Ordinarily, all objects emit thermal radiation within the infrared spectrum, which is invisible to the human eye but can be detected by an infrared sensor. An IR sensor typically comprises an IR LED (Light Emitting Diode) emitter and an IR photodiode detector sensitive to the same wavelength as the emitted IR light. Upon reaching the photodiode, changes in resistances and output voltages occur in proportion to the intensity of the received IR light.




Fig:4.3 : Circuit Diagram

4.4.1.2 Features

- Input voltage : 3.3v
- Output : analog

4.4.1.3 Application

- Radiation Thermometers
- Flame Monitor
- Moisture Analyzers
- Gas Analyzers

4.4.2. Arduino

4.4.2.1 Description

Arduino is a multifaceted entity encompassing a company, project, and community focused on open-source computer hardware and software. Its primary focus lies in crafting and delivering single-board microcontrollers and microcontroller kits tailored for crafting digital devices and interactive objects capable of monitoring and controlling physical elements in the real world.

The foundation of the Arduino platform rests on intuitive hardware and software solutions, ensuring accessibility to a diverse user base. Arduino boards possess the ability to interpret a variety of inputs, ranging from light sensed by a sensor to a button press or even a message from Twitter. These inputs are then translated into corresponding outputs, such as activating a motor, illuminating an LED, or disseminating content online.

Among the array of Arduino boards, the Arduino Uno stands out as one of the most sought-after options. Built upon the ATmega328 microcontroller, it boasts 14 digital input/output pins (including 6 with PWM support), 6 analog inputs, a 16 MHz crystal oscillator, a USB connection, a power jack, an ICSP header for programming, and a reset button.




Fig:4.4 : ARDUINO UNO

Arduino, an open-source endeavor, develops microcontroller-based kits for crafting digital devices and interactive objects that can sense and manipulate physical elements. These kits utilize microcontroller board designs sourced from various vendors and employing diverse microcontrollers. Equipped with sets of digital and analog input/output (I/O) pins, these systems can interface with expansion boards termed shields and other circuits. Some boards come with serial communication interfaces, including Universal Serial Bus (USB), facilitating program loading from personal computers. For microcontroller

programming, the Arduino project furnishes an integrated development environment (IDE) based on Processing, a programming language that also supports C and C++.

Among the notable products of the Arduino project is the Arduino Uno, powered by the ATmega328P microcontroller. It boasts 14 digital input/output pins, 6 of which support PWM outputs, along with 6 analog inputs, a 16 MHz quartz crystal, a USB connection, a power jack, an ICSP header, and a reset button. All essential components for microcontroller support are integrated into the Arduino Uno, enabling connection to a computer via USB cable or powering with an AC-to-DC adapter. Additionally, it offers multiple communication options for interaction with computers, other Arduino boards, or additional microcontrollers.

4.4.2.2 Features

- Microcontroller: ATmega328P
- Operating voltage: 5V
- Input voltage: 7-12V
- Flash memory: 32KB
- SRAM: 2KB
- EEPROM: 1KB

4.4.2.3 Applications

- Real time biometrics
- Robotic applications
- Academic applications

4.4.3 Buzzer

4.4.3.1 Description

A buzzer or beeper is a signaling device, usually electronic, typically used in automobiles, household appliances such as a microwave oven, or game shows.



Fig:4.5 : Buzzer

A buzzer or beeper serves as an audio signaling device, available in mechanical, electromechanical, or piezoelectric forms. Its common uses include alarm systems, timers, and providing feedback for user interactions like mouse clicks or keystrokes.

Typically, a buzzer comprises electronic transducers and is powered by a DC power supply. It finds wide application across various electronic devices such as computers, printers, alarms, toys, automotive electronics, telephones, timers, and other products requiring sound functionality. An active buzzer with a 5V rating can emit continuous sound when directly connected to power. When paired with sensor expansion modules and boards, it simplifies circuit design, enabling a hassle-free "plug.



Fig: 4.6 : Circuit Diagram

A buzzer or beeper functions as an audio signaling tool, coming in mechanical, electromechanical, or piezoelectric forms. It finds frequent use in alarm systems, timers, and offering feedback for user interactions such as mouse clicks or keystrokes. By

applying DC voltage, this device can emit a constant single-tone sound. When equipped with an appropriately designed resonant system, it becomes suitable for applications requiring loud sound volumes. Future Electronics provides a diverse selection of buzzer types, sorted by type, sound level, frequency, rated voltage, dimensions, and packaging type.

4.4.3.2 Features

- Input supply: 5 VDC
- Current consumption: 9.0 mA max.
- Oscillating frequency: 3.0 ± 0.5 KHz
- Sound Pressure Level: 85dB min

4.4.3.3 Applications

- Confirmation of user input (ex: mouse click or keystroke)
- Electronic metronomes
- Sporting events
- Judging Panels
- Annunciator panels

4.4.4 Motor driver

4.4.4.1 Description

The L293D is a widely used motor driver IC, engineered to enable the movement of DC motors in both forward and reverse directions. With 16 pins, it can simultaneously control two DC motors, allowing for the management of a pair of motors using just one L293D IC. Acting as a dual H-bridge motor driver integrated circuit (IC), this component serves as a crucial element in motor control systems. Motor drivers function as current amplifiers, taking a low-current control signal and boosting it to generate a higher-current output signal, essential for driving the motors effectively.



Fig:4.7 : Motor Driver

The L293D is a widely used motor driver IC, engineered to manage the movement of DC motors in forward and reverse directions. With 16 pins, it can control two DC motors concurrently, allowing for the management of a pair of motors using just one L293D IC. Serving as a dual H-bridge motor driver integrated circuit (IC), it holds significant importance in motor control systems. Motor drivers act as current amplifiers by enhancing a low-current control signal to generate a higher-current output signal, essential for driving the motors efficiently.

4.4.4.2 Features

- Easily compatible with any of the system
- Easy interfacing through FRC (Flat Ribbon Cable)
- External Power supply pin for Motors supported
- Onboard PWM (Pulse Width Modulation) selection switch
- 2pin Terminal Block (Phoenix Connectors) for easy Motors Connection
- Onboard H-Bridge base Motor Driver IC (L293D)

4.4.4.3 Technical Specification

- Power Supply : Over FRC connector 5V DC
- External Power 9V to 24V DC
- Dimensional Size : 44mm x 37mm x 14mm (l x b x h)
- Temperature Range : 0°C to +70 °C.

4.4.5 DC gear motor (60rpm)

4.4.5.1 Description

The DC gear motor rated at 600 RPM is a versatile and efficient component suitable for a myriad of applications across various industries. Featuring a robust DC motor integrated with a gearbox, this motor offers precise control over rotational motion while delivering substantial torque. Its compact form factor makes it ideal for space-constrained environments, enabling seamless integration into robotics, automation systems, and small-scale machinery. With a speed rating of 600 RPM, this gear motor strikes a balance between velocity and torque, ensuring optimal performance across a wide range of tasks.

Designed for durability and reliability, this gear motor excels in demanding environments where consistent and smooth operation is paramount. Its sturdy construction enables it to withstand rigorous use, making it a dependable choice for industrial machinery, conveyor systems, and electric vehicles. The 600 RPM speed rating provides ample versatility, allowing for precise control over rotational speed to suit specific application requirements. Whether driving mechanical assemblies, powering actuators, or controlling rotational movements in various devices, this gear motor offers the performance and durability needed to excel in diverse scenarios.

Furthermore, the integration of a gearbox enhances the motor's efficiency by providing torque multiplication and speed reduction, optimizing its performance for various tasks. This feature makes the motor particularly well-suited for applications that demand both high torque and controlled rotational speed, such as winches, lifts, and precision positioning systems. Additionally, the gear motor's compatibility with different voltage and current specifications further enhances its versatility, allowing for seamless integration into a wide array of electronic systems and projects. In essence, the DC gear motor rated at 600 RPM stands as a reliable and adaptable solution for powering a multitude of mechanisms with precision and efficiency.



Fig:4.8 : Dc Gear Motor (60rpm)

The graph on the left illustrates a linear relationship between torque, speed, and current. When the load on a motor increases, its speed decreases accordingly. This graph represents the typical behavior of a motor. To ensure optimal performance and longevity, it's advisable to operate the motor within the high-efficiency region depicted by the shaded area. Using the motor outside of this range can result in higher temperatures and wear on motor components. The motor's basic rating point is slightly below its maximum efficiency point. Determining the load torque can be achieved by measuring the current drawn when the motor is connected to a machine with a known actual load value..

4.4.5.2 Features

High Torque Output : The DC gear motor provides significant torque, making it suitable for applications requiring robust power delivery.

600 RPM Speed Rating : Offers a balanced speed suitable for various tasks, ensuring efficient operation without compromising torque.

Compact Design : Its small form factor makes it easy to integrate into space-constrained setups such as robotics and automation systems.

Durable Construction : Built to withstand rigorous use, ensuring longevity and reliability in demanding environments.

Smooth Operation : Delivers consistent and precise rotational motion, essential for applications requiring controlled movements.

Versatile Applications : Suitable for a wide range of uses including conveyor systems, electric vehicles, robotic platforms, and more.

Efficiency Optimization : Integrated gearbox enhances efficiency by providing torque multiplication and speed reduction, optimizing performance for different tasks.

Wide Voltage Compatibility : Compatible with various voltage and current specifications, allowing for flexible integration into diverse electronic systems and projects.

4.4.5.3 Applications

- Robotics : Ideal for powering joints, manipulators, and mobile platforms in robotic systems, offering precise control over movement.
- Automation Systems : Suitable for driving conveyor belts, sorting mechanisms, and automated machinery, ensuring reliable operation.
- Electric Vehicles : Used in electric bicycles, scooters, and small vehicles for propulsion, providing efficient torque delivery.
- Industrial Machinery : Employed in machinery such as lifts, winches, and cranes for controlled lifting and movement of heavy loads.
- DIY Projects : Popular choice for hobbyists and DIY enthusiasts for various projects requiring motorized motion control.
- Camera Systems : Used to rotate cameras for surveillance, photography, or cinematography, enabling smooth and controlled panning and tilting.

4.4.6 Robotic vehicle

4.4.6.1 Description

The realm of robotics encompasses a diverse range of technologies, integrating computational intelligence into physical machines to create systems with capabilities surpassing their individual components. These robotic systems excel at tasks that conventional machines or even humans using traditional tools find challenging or impossible. One such capability is autonomous movement, which unlocks a wide array of applications tailored to robotic systems. This chapter offers an overview of unmanned and autonomous vehicles, delving into their development and global applications.

Robotic vehicles traverse various terrains, such as ground, air, underwater, and space, autonomously. Operating without human presence onboard, these vehicles rely on their own power and are equipped with sensors and computational resources to guide their movements. Despite being unmanned, robotic vehicles often integrate some level of human oversight or supervision for motion and task execution, tailored to different environments and applications.

Supervisory control is a common approach for observing and monitoring vehicle motion at a high level. Alternatively, in certain scenarios, a remotely operated vehicle (ROV) interface allows for continuous human input. ROVs are typically connected via cable or wireless communications, offering operators enhanced bandwidth for communication input. The evolution of robotic vehicle technology indicates a shift towards higher autonomy, with supervisory control gradually replacing the ROV mode of operation in autonomous missions.



Fig:4.9 : ROBOTIC VEHICLE

The realm of robotics encompasses a diverse array of technologies where computational intelligence is integrated into physical machines, resulting in systems that greatly exceed the capabilities of their individual components.

These vehicles, known as "unmanned," operate autonomously without human presence onboard. They navigate independently, propelled by their own mechanisms and equipped with sensors and computational resources to guide their movements. Robotic vehicles excel in traversing environments that are inaccessible to humans or pose significant risks to human safety.

A complete robotic vehicle assembly typically includes two DC gear motors. These machines are engineered with minimal mechanical complexity to ensure optimal performance. The motors can be controlled through two modes: either via pulses from a microcontroller or through a relay switch. This enables the vehicle to move in both forward and reverse directions for object detection purposes.

Robotic vehicles play a vital role in exploring environments beyond human reach. For example, reaching the surface of Mars requires a spacecraft to travel for more than a year. Upon arrival, the Martian surface lacks essential resources such as air, water, and sustenance, making it inhospitable for human life.

4.4.6.2 FEATURES

- DC gear motor
- Human-Robot Vehicles
- High speed
- Less noise
- Multivehicle Systems

4.4.6.3 APPLICATIONS

- Industrial products.
- Lab automation.
- Military and law enforcement.

- Recreation and hobby.

4.4.7 Wifi

4.4.7.1 Description

Wi-Fi stands as a widely recognized wireless networking technology, employing radio waves to establish rapid Internet and network connections sans physical cables. Contrary to popular belief, "Wi-Fi" does not stand for "wireless fidelity"; rather, it is simply a trademarked term representing the IEEE 802.11x standard.

The LWIFI functions as an embedded module operating via the Uart serial interface, designed in accordance with WiFi wireless WLAN standards. It adheres to both the IEEE802.11 protocol stack and TCP/IP protocol stack, enabling smooth data conversion between user serial devices and wireless network modules. With the Uart-WiFi module, traditional serial devices can seamlessly connect to wireless networks.




Fig:4.10 : Wifi Module

The WU105 is tailored for client applications across various sectors like smart home, enterprise, smart grid, and home automation, where lower data rates are typically required for data transmission or reception. Moreover, it expedites the development of ultra-low-power devices by incorporating comprehensive application software directly onboard.

This WiFi module, known as the WU105, boasts a compact form-factor and supports single-stream 802.11b/g/n WiFi communication. It houses an onboard low-power application processor and serves as a cost-efficient solution for serial WiFi communication, facilitating UART-WiFi data transmission. Powered by the versatile and low-power MT7681 WiFi System-on-Chip (SOC), it offers flexibility for diverse applications.




Fig: 4.11 : Wifi Module Interface With Arduino

- The WU105 WiFi module is highly suitable for low-power automation and sensor solutions due to its outstanding efficiency and minimal power usage. It consumes less than 10uA of current in standby mode while still monitoring peripherals. Moreover, its encryption and tamper detection capabilities make it a fitting choice for security applications.

4.4.7.2 Features

- 2*4 pins of Interface:HDR254M-2X4
- The range of baud rate:1200~ 115200bps
- RTS / CTS Hardware flow control
- Single 3.3V power supply
- IEEE 802.11b/g/n Single Stream @ 2.4GHz

- Supports 1T1R mode with data rate up to 150 Mbps

4.4.7.3 Applications

- Network Consumer Device
- Building Automation
- Home Automation
- Smart Remote Control
- Smart Lighting

4.4.8 Power supply unit

4.4.8.1 Description

A power supply unit (PSU) is responsible for transforming mains AC into regulated low-voltage DC power to operate the internal components of a computer. Modern personal computers typically employ switched-mode power supplies. Some PSUs offer a manual switch to select input voltage, while others automatically adapt to the mains voltage. Power supplies are vital for reducing mains electricity from 240 volts AC to a more practical voltage, like 12 volts DC. There are two main types of power supplies: linear and switch mode. Linear power supplies use a transformer to decrease the voltage, and the AC signal is rectified and regulated to produce high DC voltage. Conversely, an AC adapter, also referred to as an AC/DC adapter or converter, acts as an external power supply, often resembling an AC plug in appearance. Adapters for battery-powered devices may be called chargers or rechargers. AC adapters are utilized with electrical devices lacking internal components to obtain the required voltage and power from mains electricity.



Fig:4.12 : Adapter (12v 1amp)

An adapter functions as a device that changes the attributes of one electrical device or system to suit those of another that would otherwise be incompatible. While some adapters modify power or signal characteristics, others merely modify the physical form of one electrical connector to fit another. In computer systems, adapters are often integrated into cards that can be inserted into slots on the motherboard. These cards enable the exchange of information between the computer's microprocessor and the devices supported by the card.




Fig: 4.13 : Circuit Diagram

An electric power adapter serves to link a power plug, often designed for use in one geographical region, to an AC power socket found in another region. This is achieved by accommodating the varying contact arrangements without changing the voltage. Conversely, an AC adapter, also known as a "recharger," is a compact power supply that converts standard household electric current from distribution voltage to low-voltage DC, which is suitable for powering consumer electronics.

While certain adapters adjust power or signal characteristics, others merely adapt the physical configuration of one electrical connector to fit another. In the domain of computers and associated devices, a specific type of serial port adapter facilitates connections between 25-contact and nine-contact connectors without affecting electrical power and signaling attributes.

4.4.8.2 Features

- Output current: 1A
- Supply voltage: 220-230VAC
- Output voltage: 12VDC
- Reduced costs
- Increased value across front-office and back-office functions
- Access to current, accurate, and consistent data
- It generates adapter metadata as WSDL files with J2CA extension.

4.4.8.3 Applications

- Back-end systems which need to send purchase order data to oracle applications send it to the integration service via a integration server client.
- SMPS applications.

4.4.9 Software required:

4.4.9.1 Arduino IDE:

The Arduino Integrated Development Environment (IDE), or Arduino Software (IDE), includes various components such as a text editor for coding, a message area, a text console, a toolbar with common function buttons, and menus. It facilitates communication and program uploading with Arduino and Genuino hardware.

Programs written in the Arduino Software (IDE) are known as sketches and are saved with the .ino file extension. The text editor offers features like cutting/pasting and searching/replacing. The message area provides feedback during tasks like saving and exporting and displays errors, while the console shows text output from the Arduino Software (IDE), including detailed error messages. The bottom right corner indicates the configured board and serial port. Toolbar buttons enable functions such as program verification, upload, sketch creation, opening, saving, and launching the serial monitor.

Before uploading a sketch, it's crucial to select the correct options from the Tools > Board and Tools > Port menus, which provide descriptions of various boards. Serial ports may have different names on different operating systems (e.g., /dev/tty.usbmodem241 on Mac, COM1 or COM2 on Windows, and /dev/ttyACMx or /dev/ttyUSBx on Linux). After

selecting the appropriate serial port and board, the upload process can be initiated by clicking the upload button or selecting Upload from the Sketch menu. Newer Arduino boards reset automatically during upload, while older ones may require manual reset. LEDs on the board typically blink during upload, with the Arduino Software (IDE) providing feedback upon completion.

During sketch uploading, the Arduino bootloader, a small program loaded onto the microcontroller, is used, allowing code uploading without additional hardware. It remains active for a short period after board reset before initiating the most recently uploaded sketch, typically blinking the onboard LED (pin 13) upon activation.

4.4.6.2 Programming language:

Embedded C encompasses a set of language extensions for the C programming language, devised by the C Standards Committee to tackle common challenges encountered in C extensions for diverse embedded systems. Traditionally, programming in embedded C has necessitated nonstandard extensions to the C language to accommodate specialized features like fixed-point arithmetic, multiple distinct memory banks, and basic I/O operations.

An embedded system denotes a computer system engineered for a specific function within a larger mechanical or electrical system, often constrained by real-time computing requirements. It integrates seamlessly as part of a comprehensive device, typically comprising hardware and mechanical elements. Embedded systems play a pivotal role in controlling numerous devices widely used today, with the bulk of microprocessors manufactured as integral components of embedded systems.

Typical embedded computers boast characteristics such as low power consumption, compact size, robust operating capabilities, and economical per-unit cost compared to their general-purpose counterparts. However, these advantages are offset by their limited processing resources, rendering them more intricate to program and interact with. Nonetheless, by incorporating intelligent mechanisms atop the hardware and leveraging existing sensors and network connections, optimal resource management can be

achieved at both unit and network levels, paving the way for enhanced functionalities beyond the standard capabilities.

Modern embedded systems predominantly rely on microcontrollers, which feature CPUs with integrated memory or peripheral interfaces. However, conventional microprocessors, utilizing external chips for memory and peripheral interface circuits, are also prevalent, especially in more intricate systems. Processors utilized in embedded systems span from general-purpose to specialized types tailored for specific computations, including digital signal processors (DSPs).

Thanks to their dedicated nature, embedded systems can be fine-tuned by design engineers to minimize product size and cost while enhancing reliability and performance. Some embedded systems undergo mass production, capitalizing on economies of scale.

Embedded systems find application across a broad spectrum, ranging from portable devices like digital watches and MP3 players to large stationary installations such as traffic lights, factory controllers, and highly complex systems like hybrid vehicles, MRI machines, and avionics. The complexity of embedded systems varies, ranging from those featuring a single microcontroller chip to those incorporating multiple units, peripherals, and networks housed within a sizable chassis or enclosure

CHAPTER – 5

RESULT

An important turning point in the history of aircraft ground handling has been reached with the completion of the Aircraft Towing Robot project. The resulting robotic system is a marvel of efficiency and innovation thanks to careful design and integration efforts. By utilising advanced technology including Internet of Things (IOT), infrared sensors, WiFi connectivity, and a microprocessor, the robot exhibits unmatched proficiency in manoeuvring intricate settings while pulling an aircraft. Its capacity to identify impediments, carry out accurate motions, and communicate with ease has been thoroughly tested, guaranteeing improved safety and dependability in ground handling activities.

The Aircraft Towing Robot's effective installation also highlights how revolutionary it has the potential to be in the aviation industry's traditional methods. The robot claims to drastically lower operating costs and improve overall efficiency by automating and optimising the aircraft towing process. Its capacity to function independently or under remote supervision creates new opportunities for streamlining workflow and allocating resources at airfields and airports. A new era of efficiency and safety in aircraft ground handling operations could be ushered in by the robot's intelligent characteristics and strong performance.

In the long run, this project's output creates the foundation for future developments and improvements in robotic systems for use in aviation. The Aircraft Towing Robot's capabilities can be further improved through ongoing research and development, opening the door for widespread application in the aviation sector. The field of aviation ground handling has enormous potential for transformation as automation and robotics advance, offering increased productivity, security, and dependability for airports, airlines, and travellers alike.

CHAPTER – 6

CONCLUSION

To sum up, the creation of the Aircraft Towing Robot is a major advancement in the field of aircraft ground handling. The robot provides an advanced solution for optimising aircraft towing operations by integrating cutting-edge technology like Internet of Things (IOT), infrared sensors, WiFi connectivity, and precise control mechanisms. Its potential to improve safety and efficiency in airport environments is enormous due to its ability to manoeuvre around barriers, communicate with ease, and function either independently or under remote supervision.

Looking back at this project's accomplishments, it's evident that the Aircraft Towing Robot represents innovation and advancement in the aviation sector. We've shown that we can transform conventional methods and usher in a new era of dependability and efficiency by utilising automation and robots. Still, we have a long way to go before the whole revolutionary potential of robotics in aviation is realised.

It is essential that we keep funding research and development projects in order to enhance and maximise the Aircraft Towing Robot's potential going forward. To fully realise its potential and promote broad adoption, cooperation between academic institutions, industry players, and technology providers will be essential. In the end, we can create a future where aircraft ground handling operations are safer, more effective, and more sustainable than ever before by embracing new technologies and an innovative mindset.

REFERENCE

1. Airbus MoU with IAI to Explore Eco-Efficient “Engines-Off” Taxiing[EB/OL]. Available Postorino, M.N.; Mantecchini, L.; Paganelli, F. Improving taxi-out operations at city airports to reduce CO2 emissions. *Transp. Policy* 2019, 80, 167–176.
2. Ashley, L.D. Jackknife Stability of Articulated Tractor Semitrailer Vehicles With High-Output Brakes and Jackknife Detection on Low Coefficient Surfaces; The Ohio State University: Columbus, OH, USA, 2003.
3. Chieh, C. Lateral Control of Commercial Heavy Vehicles. *Veh. Syst. Dyn.* 2000, 33, 91–420.
4. Deng, S.W.; Bin, Y.P.; Ren, Y. Research on Lean Operation Management Methods for Large Airports. *J. Civ. Aviat.* 2022, 6, 18–21+46. Coetzee, E.; Krauskopf, B.; Lowenberg, M. Analysis of Medium-Speed Runway Exit Maneuvers. *J. Aircr.* 2011, 48, 1553–1564.
5. Gu, Y.M. Development and Research of Train Jack-Knifing Instability Simulation System for Semitrailer; Chang’an University: Xi’An, China, 2019.
6. Gu, Y.M. Development of a Simulation System for Jack-Knifing Instability of Semi-Trailer Train; Chang’an University: Xi’an, China, 2019.
7. Guo, R.; Zhang, Y.; Wang, Q. Comparison of emerging ground propulsion systems for electrified aircraft taxi operations. *Transp. Res. Part C* 2014, 44, 98–109.
8. Hayhoe, G.F. Braking Performance of Towbarless Towing Vehicles During Maintenance Tows. In Proceedings of the First Congress of Transportation and Development Institute (TDI), Chicago, IL, USA, 13–16 March 2011.
9. Huang, M.; Nie, H.; Zhang, M. Analysis of ground handling characteristic of aircraft with electric taxi system. *Proc. Inst. Mech. Eng. Part D J. Automob. Engineering.* 2019, 233, 1546–1561.
10. Hyun, D. Predictive Modeling and Active Control of Rollover in Heavy Vehicles; Texas A&M University: Texas, TX, USA, 2001.
11. Liu, H.F. Simulation and Control Strategy Research on Lateral Dynamics of Semi-Trailer Train; Jilin University: Changchun, China, 2005.
12. Ministry of Transport of the People’s Republic of China. Statistical Bulletin on the Development of Civil Aviation Industry in 2019; Development Planning Division Beijing: Beijing, China, 2019

13. Rankin, J.; Coetzee, E.; Krauskopf, B.; Lowenberg, M. Bifurcation and Stability Analysis of Aircraft Turning on the Ground. *J. Guid. Control. Dyn.* 2009, 32, 500–511.
14. Shi, H.T. Braking Analysis of Aircraft Tractor; Harbin Engineering University: Harbin, China, 2011.
15. Wang, L.W.; Liu, B.; Sun, Y.K.; Zhang, W. Load simulation of landing gear under uneven road condition of rod-less traction system. *J. Civ. Aviat. Univ. China* 2019, 37, 33–37+43.
16. Wang, L.W.; Wu, Z.H.; Zhang, W. Kinematic analysis of clamping lifting mechanism of bar aircraft tractor. *Mach. Tools Hydraul.* 2015, 43, 54–57+15.
17. Wang, N.; Liu, H. Research on trajectory tracking behavior in traction task for tractor-aircraft system. In *IEEE International Conference on Mechatronics & Automation*; IEEE: Piscataway, NJ, USA, 2013; pp. 1251–1255.
18. Winkle, C.B. Rollover of Heavy Commercial Vehicles; SAE Paper: Warrendale, PA, USA, 2001; ISBN 0-7680-0626-0.
19. Xiao, H. Research on Traction Operation Simulation Technology of Traction Aircraft System; Huazhong University of Science and Technology: Wuhan, China, 2008.
20. Xie, B.M.; Zhu, J.W.; Wang, W.; Zhang, W. Ride comfort simulation and optimization of aircraft tractor under multi working conditions. *Mech. Des. Manuf.* 2020, 10, 15
21. Zhang, J.H.; Li, G.Y. Simulation analysis of ride comfort of aircraft tractor based on ADAMS. *Mach. Des.* 2005, 3, 68–70.
22. Zhang, W.; Ning, Z.H.; Wang, W.; Wang, L.W. Study on the influence of airport pavement depression on the dynamic performance of aircraft and tractor wheel holding system. *Mech. Des. Manuf. Eng.* 2019, 48, 15–19.
23. Zhao, G.; Xing, W. Research on Airport Operation Efficiency Based on Big Data Analysis Technology. *J. Civ. Aviat.* 2022, 6, 33–37+97.
24. Zhou, L.J. Study on Stability of Tractor Aircraft System on Ship; Harbin Engineering University: Harbin, China, 2012
25. Zhu, H.; Li, J.F. Braking stability analysis of aircraft tractor under turning traction condition. *Mach. Des.* 2020, 37, 72–76.
26. Zhu, T.J. Research on Rollover Warning and Multi-Objective Stability Control Algorithm of Heavy Vehicle Based on Improved TTR; Jilin University: Changchun, China, 2010.
27. Zhuo, K.M.; Wei, D.B. Lateral stability test and simulation analysis of semitrailer train.

DESIGN AND FABRICATION OF AIRCRAFT TOWING ROBOT USING IOT

ORIGINALITY REPORT

18%

SIMILARITY INDEX

13%

INTERNET SOURCES

6%

PUBLICATIONS

15%

STUDENT PAPERS

PRIMARY SOURCES

1

Submitted to Udayana University

Student Paper

1%

2

pdfcoffee.com

Internet Source

1%

3

Submitted to University of North Texas

Student Paper

1%

4

Submitted to College of Science and
Technology, Bhutan

Student Paper

1%

5

Submitted to Indian Institute of Technology
Jodhpur

Student Paper

1%

6

Submitted to M S Ramaiah University of
Applied Sciences

Student Paper

1%

7

www.slideshare.net

Internet Source

1%

8

Submitted to Colorado Technical University
Online

Student Paper

1%

9	ijsret.com Internet Source	1 %
10	www.coursehero.com Internet Source	1 %
11	Submitted to Green University Of Bangladesh Student Paper	1 %
12	Submitted to Amity University Student Paper	1 %
13	swslhd.libguides.com Internet Source	<1 %
14	Submitted to Universiti Malaysia Perlis Student Paper	<1 %
15	Submitted to Sri Sairam Engineering College Student Paper	<1 %
16	Submitted to Orissa University of Agriculture & Technology Student Paper	<1 %
17	Submitted to Liverpool John Moores University Student Paper	<1 %
18	Submitted to The Manchester College Student Paper	<1 %
19	Submitted to University of Portsmouth Student Paper	<1 %

20	Submitted to Vel Tech University Student Paper	<1 %
21	technodocbox.com Internet Source	<1 %
22	www.psychosocial.com Internet Source	<1 %
23	www.ijert.org Internet Source	<1 %
24	A.R. Aravind, Rithubharathan S, Sanjaikumar P.V.M, Sharad Kumar Rathore, Chorieva Durdonga, N. Vasudevan, T. Avudaiappan. "Medibot for Emergency Vehicle", E3S Web of Conferences, 2023 Publication	<1 %
25	ijtre.com Internet Source	<1 %
26	idoc.pub Internet Source	<1 %
27	projectonly.files.wordpress.com Internet Source	<1 %
28	Submitted to Georgia Southern University Student Paper	<1 %
29	www.ijeat.org Internet Source	<1 %

30	www.ijraset.com Internet Source	<1 %
31	Submitted to Technological University Dublin Student Paper	<1 %
32	ijireeice.com Internet Source	<1 %
33	ijsrset.com Internet Source	<1 %
34	kme.com.vn Internet Source	<1 %
35	magnascientiapub.com Internet Source	<1 %
36	Submitted to Global Banking Training Student Paper	<1 %
37	Submitted to South Bank University Student Paper	<1 %
38	Submitted to Delhi Metropolitan Education Student Paper	<1 %
39	nou.edu.ng Internet Source	<1 %
40	Baoli Liu, Yadong Wang, Zhi-Chun Li, Jianfeng Zheng. "An exact method for vessel emission monitoring with a ship-deployed heterogeneous fleet of drones",	<1 %

Transportation Research Part C: Emerging Technologies, 2023

Publication

-
- 41** U S Rajani, Anish Sathyan, Anju Mohan, A A Kadar. "Design architecture of autonomous precision farming system", 2017 International Conference on Intelligent Computing, Instrumentation and Control Technologies (ICICICT), 2017 <1 %
- Publication
-

- 42** ijisrt.com <1 %
- Internet Source
-

- 43** www.lumisense.in <1 %
- Internet Source
-

- 44** Submitted to University of Teesside <1 %
- Student Paper
-

- 45** answersdrive.com <1 %
- Internet Source
-

- 46** Maurizio Di Paolo Emilio. "Embedded Systems Design for High-Speed Data Acquisition and Control", Springer Science and Business Media LLC, 2015 <1 %
- Publication
-

- 47** www.iseerobot.com <1 %
- Internet Source
-

- 48** www.rdnutritionconsultants.com
- Internet Source

<1 %

49

www.research-collection.ethz.ch

Internet Source

<1 %

50

Bharath Singh Jebaraj, Selvalakshmi Sekar, Sushmitha S, Priyadharshini S, Jayapriya Yu, Gnanasekaran T. "IoT-based Automatic LPG Refilling and Leakage Detection System", 2023 International Conference on Innovative Data Communication Technologies and Application (ICIDCA), 2023

Publication

<1 %

51

Submitted to Henley College Coventry, Coventry

Student Paper

<1 %

52

Submitted to Segi University College

Student Paper

<1 %

53

Submitted to Taylor's Education Group

Student Paper

<1 %

54

mdpi-res.com

Internet Source

<1 %

55

Michal Kelemen, Ľubica Miková, Darina Hroncová, Filip Filakovský, Peter Ján Sinčák. "EMBEDDED SYSTEMS - CONTROL OF POWER SUBSYSTEMS", Acta Mechatronica, 2020

Publication

<1 %

56 Singla, Raman Kumar. "Perception of Doctors and Chemists Towards HepaPro - A Newly Launched Liver Protein by British Biologicals", Rajiv Gandhi University of Health Sciences (India), 2023

Publication

<1 %

57 Clifton A. Ericson. "Concise Encyclopedia of System Safety", Wiley, 2011

Publication

<1 %

Exclude quotes On

Exclude matches Off

Exclude bibliography On