

ADVANCED TRAFFIC VIOLATION PENALTY SYSTEM USING IOT AND IMAGE PROCESSING TECHNIQUES

Submitted in partial fulfilment of requirements for the award of
Bachelor of Engineering in Electronics and Communication Engineering

By

Elangovan A (40130052)

Dhanush Adithya L (40130046)



**DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING
SCHOOL OF ELECTRICAL AND ELECTRONICS**

SATHYABAMA

**INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)**

Accredited with Grade “A++” by NAAC

JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI - 600 119

APRIL - 2024



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)

Accredited "A++" Grade by NAAC | 12B Status by UGC | Approved by AICTE
www.sathyabama.ac.in

DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that this Final Year Project Report is the bonafide work of **AKASH APPADURAI (40130006), BHARATH R (40130025)** who have done the project work as an individual who carried out the project entitled "**ESP-32 BASED PARAMETER MEASUREMENT AND CONTROL IN RC BORING MACHINE**" under my supervision from November 2023 to April 2024.

Internal Guide

Dr. G. RAJALAKSHMI, M.E., Ph.D.

Head of the Department

Dr. T. RAVI, M.E., Ph.D.

Submitted for Viva voce Examination held on _____

Internal Examiner

External Examiner


DECLARATION

We **Elangovan A**(40130052), **Dhanush Adithya L**(400130046) hereby declare that the Project Report entitled "**ADVANCED TRAFFIC VIOLATION PENALTY SYSTEM USING IOT AND IMAGE PROCESSING TECHNIQUES**" done by us under the guidance of **Dr.D.Kanchana, M.E,Ph.D.**, Assistant Professor, Department of Electronics and Communication Engineering, **SATHYABAMA INSTITUTE OF SCIENCE AND TECHNOLOGY, CHENNAI**, is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in Electronics and Communication Engineering.


Date: 18/04/2024

Place: Chennai

SIGNATURE OF THE CANDIDATES



1. Elangovan A



2. Dhanush Adithya L

ACKNOWLEDGEMENT

We are pleased to acknowledge our sincere thanks to **The Board of Management** of **SATHYABAMA INSTITUTE OF SCIENCE AND TECHNOLOGY** for their encouragement in doing this project and for completing it successfully. We are grateful to them.

We convey our thanks to **Dr. N.M.NANDHITHA,M.E.,Ph.D.**, Dean, School of Electrical and Electronics Engineering and **Dr. T.RAVI,M.E.,Ph.D.**, Head of the Department, Dept. Of Electronics and Communication Engineering for providing us necessary support during the progressive reviews.

We would like to express my sincere and deep sense of gratitude to our Project Guide **Dr. D.Kanchana, M.E,Ph.D.**, Assistant Professor, Department of Electronics and Communication Engineering for her valuable guidance, suggestions and constant encouragement paved way for the successful completion of our project work.

We wish to express our thanks to all Teaching and Non-teaching staff members of the **Department of Electronics and Communication Engineering** who were helpful in many ways for the completion of the project.

ABSTRACT

Road Traffic Accidents, pervasive as they are, stand as a significant contributor to disability and mortality on a global scale. The endeavor to mitigate these occurrences and alleviate congestion cannot solely rely on human intervention. Recognizing this, the present article aims to unveil an innovative solution: an intelligent control system leveraging RFID technology. Through the integration of RFID technology, vehicles establish connections with computerized systems, intelligent light poles, and other pertinent hardware infrastructure along their routes. Within this framework, the intelligent control system demonstrates proficiency in vehicle tracking, crisis management, traffic guidance, and the documentation of driving offenses along the highway.

One of the key features of this system is its ability to send immediate notifications to vehicle owners when a traffic violation is detected. This prompt response mechanism is designed to encourage compliance with traffic regulations by ensuring that violators are swiftly made aware of their actions and the associated penalties. Overall, this project represents a forward-looking approach to address the challenges posed by traffic violations and aims to make the enforcement of traffic rules more efficient and effective.

TABLE OF CONTENTS

CHAPTER NO	TITLE	PAGE NO
	ABSTRACT	iv
	LIST OF FIGURES	viii
	LIST OF ABBREVIATIONS	x
1	INTRODUCTION	1
2	LITERATURE REVIEW	4
3	METHODOLOGY	7
	3.1 BASIC OVERVIEW	7
	3.2 HARDWARE REQUIREMENT	7
	3.2.1 NodeMCU esp8266 Wifi Module	7
	3.2.2 RFID Reader and Tag	9
	3.2.2.1 Introduction to RFID Technology:	9
	3.2.2.2 RFID Reader:	10
	3.2.2.3 RFID Tag:	11
	3.2.3 LEDs for Traffic Systems	12
	3.2.3.1 Introduction:	12
	3.2.3.2 Red LED:	12
	3.2.3.3 Orange (Amber) LED:	13
	3.2.3.4 Green LED:	14
	3.2.3.5 Advantages of LED Traffic Signals:	14
	3.2.4 LCD Display 16*2	15
	3.2.5 Jumper Wires	17
	3.3 SOFTWARE REQUIREMENT	19
	3.3.1 Arduino IDE	19
	3.3.2 XAMPP	21
	3.3.3 MySQL	23
	3.4 STANDARDS	25

	3.5 CONSTRAINTS	25
	3.6 TRADE OFFS	26
4	COMPREHENSIVE ANALYSIS	27
	4.1 WORKING PRINCIPLE	27
	4.2 EXPERIMENT AND EVALUATION	30
	4.3 IMPLEMENTATION	31
	4.4 SOFTWARE IMPLEMENTATION	32
5	RESULTS AND DISCUSSIONS	38
	5.1 RESULTS	38
	5.2 ADVANTAGES	40
	5.3 APPLICATIONS	40
6	CONCLUSIONS AND FUTURE SCOPE	41
	6.1 CONCLUSIONS	41
	6.2 FUTURE SCOPE	42
	REFERENCES	43
	APPENDIX	45
	Source Code	45

LIST OF FIGURES

FIGURE NO	TITLE	PAGE NO
1.1	Traffic violation types	3
3.1	NodeMCU esp8266 Pin Diagram	9
3.2	RFID Reader	10
3.3	RFID Key chain and Card	12
3.4	Red LED	13
3.5	Orange LED	13
3.6	Green LED	14
3.7	Traffic Light	15
3.8	LCD Display	17
3.9	Jumper wires	19
3.10	XAMPP Home page	23
4.1	Block Diagram	28
4.2	XAMPP Home Page.	32
4.3	Click the start option on both Apache and MySQL services.	33
4.4	PHP files for Websites.	33
4.5	Localhost admin page.	34
4.6	Create a new database.	34
4.7	Import the MySQL library.	35
4.8	Website Home Page	35
4.9	Read Tag ID page	36
4.10	Manual Entry Pages	36

4.11	User data Page	37
5.1	Project Photo	38
5.2	Email notification for violation message	39

LIST OF ABBREVIATIONS

IEEE	- INSTITUTE OF ELECTRICAL AND ELECTRONICS ENGINEERS
IOT	- INTERNET OF THINGS
RFID	- RADIO-FREQUENCY IDENTIFICATION
LED	-LIGHT-EMITTING DIODE
IR SENSOR	-INFRARED SENSOR
SMPS	- SWITCHED-MODE POWER SUPPLY
AC	- ALTERNATING CURRENT
DC	- DIRECT CURRENT
BLE	- BLUETOOTH LOW ENERGY

CHAPTER 1

INTRODUCTION

Travel is an important part of today's fast paced life as everyone has to move around for their day -to-day work. Road transport is the most commonly used mode of travel due to its ease, low cost and availability to common man. The ease of travel is affected by such factors as the quality of road, congestion, time taken, accidents, speed, etc. The major threat is the increasing number of accidents on a daily basis. An accident survey estimated that around 3,00,000 accidents occur on Indian roads every year. These accidents not only eat lives of people but also adds on to the economic loss of the country. It is reported that over 80,000 people are killed on the Indian roads while the total economic loss owing to road accidents is estimated to be over Rs. 3,600 crores.

Lack of discipline and emotions of road users cause traffic congestions which might lead to traffic violations. Having a safe and free flow of traffic is crucial for economic development of the country as we must ensure spending less on fuels and less time on the road. Traffic enforcement authorities can deal with the challenge of regulating the traffic and enforcing rules caused by the huge number of vehicles on the road and the indiscipline of the motorists by applying modern technology.

Flouting lane discipline is the single major factor in India that inhibits safe and free flow of traffic. It is also a common sight in India to see one slow moving vehicle blocking the way of hundreds of vehicles coming behind it. If keeping slow moving vehicles to the left is enforced, one important cause of traffic jams is removed. The authorities are responsible for controlling the traffic violation and pollution and imposing fine on the violators.

The single most important rule is to follow the traffic signals in junctions. Violation of signals results in a number of accidents. The major problem is the manual tracking of every single vehicle that violates signals. This problem can be brought under control if the tracking can be automated along with calculating and updating the fines.

In the existing systems, the tracking of signal violation is implemented using image processing techniques. The cameras use infrared signals to capture the number

plates of the vehicles round the clock. The vehicle number is extracted from the image of the vehicle's number plate using optical recognition techniques [9]. If a vehicle has violated the signal, the identified owner is imposed suitable fine. However, there is a number of limitations in this system.

- It requires a camera in every lane of the signal.
- These cameras require high maintenance and are prone to damage in bad weather conditions.
- Dirt on the number plate makes image processing difficult.
- Various font types on the number plate cause lack of precision.
- Objects far from the camera are captured with poor resolution.
- There is a need for a larger number of technical persons.

On the other hand, RFID based traffic violation detection systems use radio frequency waves to identify vehicles which are endowed with unique identification numbers in the form of RFID tags. RFID (Radio Frequency Identification) is one of the upcoming technologies in the field of engineering and innovation. It has a number of applications in the market starting from vehicle identification at tolls to security systems at malls.

These RFID based systems consist of 3 main components, namely RFID Reader, RFID Tags and RFID Database. The reader has an antenna that emits the radio waves. When the tag antenna comes within the range of the reader's range, it responds to the reader with the unique identification number of that tag. Tags can be classified into 2 types: passive tags and active tags. A passive tag contains no internal power source whereas an active tag contains its own power source which runs the microchip circuitry and also helps in broadcasting the signal to the readers. Similarly, there are two types of readers:

- Stationary Readers which are fixed at a specific location and able to read the tags within their range.
- Mobile Reader which are movable devices

The frequency of low frequency tags varies between 30 ~ 300 kHz that of high frequency tags varies from 3 ~ 30 MHz and that of ultra-high frequency varies between 300 ~ 3000 MHz.

In this work, an RFID reader uses radio waves to read tags and hence does not require to be in line of sight. Every vehicle is endowed with an RFID tag, while RFID readers on the sides of the road. Road markings are done according to the required range. Any vehicle crossing the road marking when the signal is red will be detected from RFID tag of that vehicle.

Some typical examples from court cases of dangerous driving are:

- Speeding, Racing, Weaving
- Ignoring traffic lights, road signs
- Overtaking dangerously
- Knowing the vehicle has a dangerous fault or an unsafe load
- Permitting to drive without valid license
- Drove on wrong side of divided highway




Fig 1.1 Traffic violation types

CHAPTER 2

LITERATURE REVIEW

An innovative implementation of the Automatic Number Plate Recognition (ANPR) technology is utilized to detect vehicles that disregard traffic lights. The system effectively captures digital photographs and employs MATLAB software to extract the license plate information of the offending vehicle. To promptly address the violation, an Arduino board along with a GSM module (SIM900) is employed, enabling the system to send an SMS notification to the offender within a minute of the incident.[1]

This paper focuses on the comprehensive tracking of traffic signal violations and the corresponding fines attributed to them. It emphasizes the utilization of IoT (Internet of Things) and image processing techniques as fundamental components in addressing these infringements. To tackle challenges like license plate tampering or the concealment of Fastrack tags, the paper proposes a fusion of RFID (Radio Frequency Identification) and image processing methods. By leveraging GSM (Global System for Mobile Communications) technology, the system effectively issues timely fee notifications, significantly reducing the potential for vehicle owners to evade penalties.[2]

The authors of this work have developed an unconventional approach to addressing the problems brought In particular, on highways and roads with limited visibility, sudden traffic stops often serve as a significant catalyst for car accidents. While static traffic sensors are frequently employed to mitigate this problem, their implementation is not universal across all roadways. This article introduces an alternative solution in the form of an IoT Cloud system that utilizes Open GTS and Mongo DB for traffic monitoring and alarm delivery. The system's noteworthy responsiveness ensures that drivers receive timely warnings, empowering them to take proactive measures to avert potentially dangerous collisions.[3]

According to this paper's authors, In urban environments, motorcycles, as Vulnerable Road Users (VRUs), are particularly susceptible to road accidents. To address this issue, the application of automatic video processing techniques for

CCTV cameras holds promise in recognizing and effectively monitoring these road users. This study specifically centers around the algorithms employed for the identification and localization of motorcycles using a CCTV surveillance system. Furthermore, the research examines the indicators of current performance, publicly accessible data, and anticipated challenges. The study concludes with a list of recommendations for further research in this domain.[4]

In this study, a comprehensive analysis is conducted on the classification of traffic offenses in Indian cities through the implementation of an automated system for issuing e-challans, which are electronic receipts for traffic violations. The study includes a temporal analysis revealing significant variations in the number of e-challans issued during festivals. Additionally, it highlights a striking finding that 57% of Ahmedabad's unique vehicles are involved in repeat offenses. The research further uncovers that different violation categories are distributed unevenly due to the presence of various distinct hotspots in the cities. Furthermore, the study challenges the notion that severe punishments alone have a long-term impact on reducing traffic offenses, providing evidence to support this claim.[5]

In order to effectively monitor and address various traffic offenses such as excessive speeding, reckless driving, drunk driving, and seat belt violations, the police department is currently in the process of developing an advanced system. This system integrates multiple components including seat belt detection, alcohol detection, speed monitoring, and a smart device installed within vehicles. Whenever a violation occurs, the controller within the vehicle transmits emergency information regarding the rule infringement to the cloud. Subsequently, the Regional Transport Office (RTO) receives updates on the vehicles involved. Any violations detected will result in the imposition of fines, and the Department of Motor Vehicles will also be notified accordingly.[6]

According to this research paper, to enhance the accuracy of short-term traffic flow forecasts and effectively manage collisions and urban traffic control, a combination of RFID (Radio Frequency Identification) and ELP (Electronic License Plate) data is utilized. This approach integrates an extensive short-term memory neural network with a wavelet neural network (WNN), specifically using LSTM (Long Short-Term Memory), along with an improved WNN. The merged model offers improved prediction capabilities for managing traffic flow on urban road segments. With the

increasing number of vehicles on the road, there has been a rise in traffic accidents. Computer vision-based systems that employ object detection techniques are valuable in identifying and monitoring traffic violations to enforce the law and reduce violations. The recommended system utilizes YOLOV3 object detection to track various traffic offenses, including signal jump, vehicle count, and speed. The system achieves an accuracy of 89.24% in detecting speed violations and 97.67% accuracy in vehicle count detection. [7]

The results of this study suggest that as population growth and increased traffic contribute to an escalating demand for traffic violation detection systems, it becomes imperative to address traffic rule violations and alleviate public misconceptions. The proposed method offers a highly accurate and effective approach that can swiftly identify the most prevalent traffic infractions. Compared to human traffic police, who are limited to recording one offense at a time, this method proves to be faster and more efficient in its operations.[8]

According to author, this paper highlights the key aspects of a system developed to provide emergency vehicles with uninterrupted passage by converting all red lights along their route to green, thus establishing a continuous "green wave." The concept of synchronizing the green phases of traffic lights is effectively realized through this novel technology. The system, operating autonomously on two levels, possesses the ability to identify and prioritize various vehicles, particularly emergency vehicles, while updating its database without requiring additional energy consumption. This paper presents a significant advancement in optimizing traffic flow for emergency response vehicles, ensuring efficient and uninterrupted movement. [9]

In a region characterized by multiple lanes and a complex road network, the integration of RFID (Radio Frequency Identification) traffic control systems proves instrumental in establishing a dynamic time schedule and efficient time management. This technology enables the simulation of a traffic enforcement officer's discretion by accurately determining the number of vehicles in each lane and path. With this implementation, the system effectively manages traffic flow and optimizes the allocation of resources in real-time, ensuring efficient traffic management. [10]

CHAPTER 3

METHODOLOGY

3.1. BASIC OVERVIEW

In the basic overview of our project, we use sensors (RFID) for input, and LED, and LCD display for output. And also, NodeMCU esp8266 wifi module in side it uses for the overall decision maker of the entire system. We use ARDUINO code typically C programing language to interface the hardware and the software.

3.2. HARDWARE REQUIREMENT

3.2.1. NodeMCU esp8266 Wifi Module

NodeMCU is an open-source IoT (Internet of Things) platform based on the ESP8266 Wi-Fi module. It combines the capabilities of the ESP8266 microcontroller with firmware and development tools to enable rapid prototyping and development of IoT applications. Here's a concise overview:

3.2.1.1 Microcontroller:

NodeMCU is built around the ESP8266 microcontroller, which integrates Wi-Fi connectivity, making it suitable for IoT projects requiring wireless communication.

3.2.1.2 Features:

Wi-Fi Connectivity: NodeMCU allows devices to connect to the internet or local network wirelessly, facilitating communication and data exchange with other devices or cloud services.

1. Lua Programming: Initially, NodeMCU firmware supported the Lua scripting language, providing an easy-to-use scripting environment for IoT development. However, other programming languages like Arduino IDE are now also commonly used with NodeMCU.
2. GPIO Pins: NodeMCU features General-Purpose Input/Output (GPIO) pins, enabling interfacing with various sensors, actuators, and other peripherals.

3. USB Interface: It includes a USB interface for programming and power supply, simplifying the development process by allowing direct connection to a computer.
4. Low Cost: NodeMCU boards are relatively inexpensive, making them accessible to hobbyists, students, and professionals alike.

3.2.1.3 Development Environment:

1. NodeMCU supports multiple programming languages and development environments, including Lua, Arduino IDE, and MicroPython, providing flexibility based on developers' preferences and project requirements.
2. Arduino IDE support for NodeMCU involves adding the ESP8266 board to the IDE and installing necessary libraries to facilitate programming in C/C++.

3.2.1.4 Applications:

1. Home Automation: NodeMCU can be used to create smart home devices such as thermostats, lighting controls, and security systems, enabling remote monitoring and control.
2. IoT Prototyping: Its ease of use and Wi-Fi connectivity make NodeMCU ideal for prototyping IoT projects, including environmental monitoring, smart agriculture, and industrial automation.
3. Education: NodeMCU serves as an educational tool for teaching IoT concepts, programming, and electronics due to its affordability, simplicity, and extensive online resources.
4. DIY Projects: Hobbyists and makers utilize NodeMCU for a wide range of do-it-yourself projects, from weather stations and robot controllers to internet-connected gadgets and interactive installations.

3.2.1.5 Community and Resources:

1. NodeMCU benefits from a vibrant and active community of developers, enthusiasts, and contributors who share projects, tutorials, and troubleshooting tips through forums, social media, and online platforms.

2. Extensive documentation, libraries, and example codes are available to support developers in their NodeMCU projects, accelerating the learning curve and fostering innovation.




Fig 3.1 NodeMCU esp8266 Pin Diagram

3.2.2 RFID Reader and Tag

3.2.2.1 Introduction to RFID Technology:

Radio-Frequency Identification (RFID) technology has become increasingly prevalent in various industries due to its ability to efficiently track and manage assets, inventory, and people. At its core, RFID systems consist of two main components: RFID readers and RFID tags.

3.2.2.2 RFID Reader:

3.2.2.2.1 Overview:

An RFID reader, also known as an interrogator, is a device that wirelessly communicates with RFID tags within its vicinity. It sends out radio waves to energize RFID tags and receives the data transmitted by these tags.

3.2.2.2.2 Functionality:

1. Emission of Radio Waves: The RFID reader emits radio waves in a specific frequency range (typically low-frequency, high-frequency, or ultra-high-frequency bands) to power up RFID tags.
2. Interrogation: Once powered, the RFID reader interrogates the RFID tags within its range, requesting identification or other pertinent information.
3. Data Processing: The reader processes the data received from the tags, often transmitting it to a connected computer system or database for further analysis or action.
4. Communication Interfaces: Most RFID readers feature various communication interfaces such as Ethernet, Wi-Fi, Bluetooth, or serial ports to connect with other devices or networks.

3.2.2.2.3 Types of RFID Readers:

1. Fixed RFID Readers: Typically installed in a fixed location, such as doorways or conveyor belts, for continuous tracking of items passing through.
2. Handheld RFID Readers: Portable devices used for inventory management, asset tracking, or field operations where mobility is essential.
3. Integrated RFID Readers: Embedded within other devices like smartphones, tablets, or industrial equipment for specialized applications.



Fig 3.2 RFID Reader

3.2.2.3 RFID Tag:

3.2.2.3.1 Overview:

An RFID tag, also known as a transponder or chip, is a small electronic device that contains a unique identifier and possibly other data. Tags come in various forms, including passive, active, and semi-passive, each with its own set of capabilities and applications.

3.2.2.3.2 Components:

1. **Antenna:** The antenna of the RFID tag receives power and communicates with the RFID reader via radio waves.
2. **Microchip:** Embedded within the tag, the microchip stores the unique identifier and any additional data relevant to the tagged item.
3. **Substrate:** The substrate serves as the physical structure holding the antenna and microchip together.

3.2.2.3.3 Types of RFID Tags:

1. **Passive RFID Tags:** These tags do not have an internal power source and rely on the radio frequency emitted by the reader to power up and transmit data. They are cost-effective and commonly used for tracking inventory and assets.
2. **Active RFID Tags:** Active tags have their own power source (usually a battery) and can transmit data over longer ranges compared to passive tags. They are often used for tracking high-value assets or in applications requiring real-time location tracking.
3. **Semi-Passive RFID Tags:** Also known as battery-assisted passive (BAP) tags, these combine elements of both passive and active tags. They use a battery to power the microchip but rely on the reader for communication.

3.2.2.3.4 Applications of RFID Technology:

1. **Supply Chain Management:** Tracking goods throughout the supply chain to improve inventory visibility and reduce loss or theft.

2. Asset Tracking: Monitoring and managing assets such as equipment, vehicles, or tools in industries like healthcare, manufacturing, and logistics.
3. Access Control: Securing restricted areas or managing entry/exit of personnel in buildings or events.
4. Retail: Improving inventory management, reducing stockouts, and enhancing the shopping experience through RFID-enabled solutions like smart shelves and checkout systems.



Fig 3.3 RFID Key chain and Card

3.2.3 LEDs for Traffic Systems

3.2.3.1 Introduction:

Light-Emitting Diodes (LEDs) have revolutionized traffic signal systems worldwide due to their energy efficiency, longevity, and brightness. In traffic systems, LEDs are commonly used in red, orange, and green colors to indicate stop, caution, and go signals, respectively.

3.2.3.2 Red LED:

- Function: The red LED in traffic signals signifies the "stop" indication.
- Characteristics:
 1. Emitting a bright red light, easily distinguishable even in bright daylight.
 2. Typically the longest duration in traffic signal cycles, ensuring visibility and safety for motorists and pedestrians.
- Importance:
 1. Signals drivers to halt their vehicles and wait for the green signal.
 2. Crucial for preventing accidents and regulating traffic flow at intersections.



Fig 3.4 Red LED

3.2.3.3 Orange (Amber) LED:

- Function: The orange LED indicates the "caution" or "prepare to stop" phase in traffic signals.
- Characteristics:
 1. Emitting a distinct amber light, providing a warning to drivers to slow down and prepare for a potential stop.
 2. Appears between the red and green phases, alerting motorists to upcoming changes in traffic flow.
- Importance:
 1. Helps in smoothly transitioning traffic flow between the stop and go phases.
 2. Reduces the likelihood of rear-end collisions by warning drivers to decelerate.



Fig 3.5 Orange LED

3.2.3.4 Green LED:

- Function: The green LED signals the "go" phase in traffic signals, indicating clearance for vehicles to proceed.
- Characteristics:
 1. Emitting a vibrant green light, easily visible to motorists.
 2. Generally the shortest duration in traffic signal cycles, allowing for efficient traffic movement.
- Importance:
 1. Grants vehicles permission to proceed through the intersection, promoting smooth traffic flow.
- Provides pedestrians with a safe window to cross the street when pedestrian signals are synchronized with the green light.



Fig 3.6 Green LED

3.2.3.5 Advantages of LED Traffic Signals:

1. Energy Efficiency: LEDs consume significantly less energy than traditional incandescent bulbs, reducing electricity costs and environmental impact.
2. Longevity: LEDs have a much longer lifespan compared to incandescent bulbs, resulting in reduced maintenance and replacement expenses.
3. Brightness and Visibility: LEDs offer superior brightness and visibility, ensuring clear signaling even in adverse weather conditions or during daytime.
4. Instantaneous Operation: LEDs illuminate instantaneously, enabling rapid response to changes in traffic conditions and enhancing overall traffic management.



Fig 3.7 Traffic Light

3.2.4 LCD Display 16*2

3.2.4.1 Introduction:

A 16x2 LCD (Liquid Crystal Display) module is a commonly used display component in electronic projects, featuring 16 character columns and 2 rows. In the context of displaying traffic rules, an LCD 16x2 module can serve as an informative interface to communicate important regulations and guidelines to drivers and pedestrians.

3.2.4.2 Functionality:

1. **Display Capability:** The LCD 16x2 module can display alphanumeric characters, symbols, and simple graphics, making it suitable for presenting textual information such as traffic rules and instructions.
2. **Readable Interface:** With its clear and contrasted display, the LCD provides a readable interface even in varying lighting conditions, making it suitable for outdoor applications such as traffic management systems.
3. **User Interaction:** While the LCD primarily serves as an output device, it can also be integrated with input components (e.g., buttons, switches) to enable user interaction, such as navigating through different traffic rules or selecting specific information.

3.2.4.3 Content Display:

1. **Traffic Rules:** The LCD can display a variety of traffic rules, including speed limits, right-of-way regulations, pedestrian crossing instructions, parking restrictions, and other relevant guidelines.
2. **Multilingual Support:** Depending on the location and demographic, the displayed content can be presented in multiple languages to ensure comprehension by a diverse audience.
3. **Dynamic Updates:** The display content can be updated dynamically based on real-time data, such as road conditions, weather advisories, or temporary traffic restrictions.

3.2.4.4 Integration with Microcontroller:

1. **Arduino Compatibility:** The LCD 16x2 module can be easily interfaced with popular microcontroller platforms such as Arduino, allowing for seamless integration into traffic management systems or electronic signage.
2. **Data Processing:** The microcontroller can process input data from various sources (e.g., sensors, GPS modules) and generate appropriate content to be displayed on the LCD.
3. **Programming Flexibility:** Programmed using C/C++ or other compatible languages, the microcontroller enables developers to customize the behavior and content displayed on the LCD based on specific requirements.

3.2.4.5 Benefits:

1. **Information Dissemination:** By displaying traffic rules and regulations in prominent locations, the LCD 16x2 module facilitates public awareness and compliance with traffic laws, contributing to enhanced road safety.
2. **Real-Time Updates:** The ability to update displayed content in real-time allows for efficient dissemination of dynamic information, such as traffic diversions, event notifications, or emergency alerts.

3. **Cost-Effective Solution:** Compared to traditional static signage, an LCD-based display offers a cost-effective and versatile solution that can adapt to changing traffic conditions and requirements.




Fig 3.8 LCD Display

3.2.5 Jumper Wires

3.2.5.1 Introduction:

Jumper wires are essential components in electronics and prototyping, used to create connections between various components on breadboards, circuit boards, or other electronic devices. They are flexible wires with connectors at both ends, typically male connectors (pins) or female connectors (sockets), allowing for easy insertion and removal.

3.2.5.2 Purpose:

1. Jumper wires serve as conductive pathways, allowing electrical signals to flow between different points on a breadboard, PCB (Printed Circuit Board), or other electronic platforms.
2. They facilitate the establishment of temporary or permanent connections, enabling rapid prototyping, testing, and troubleshooting of electronic circuits.

3.2.5.3 Design:

1. Jumper wires are typically made of flexible insulated wire with connectors at each end.
2. The connectors may come in different types, including male-to-male, male-to-female, and female-to-female, to accommodate various connection requirements.
3. The insulation around the wire prevents short circuits and ensures electrical safety.

3.2.5.4 Types of Jumper Wires:

1. Male-to-Male: Both ends of the wire have male connectors, allowing them to be plugged into female headers, pins, or sockets.
2. Male-to-Female: One end of the wire has a male connector, while the other end has a female connector, enabling connections between male and female pins or headers.
3. Female-to-Female: Both ends of the wire have female connectors, suitable for extending or bridging connections between male pins or headers.

3.2.5.5 Applications:

1. Prototyping: Jumper wires are widely used in prototyping electronic circuits on breadboards, facilitating the creation of temporary connections between components during experimentation and design.
2. Testing and Debugging: They are invaluable for testing and troubleshooting electronic circuits, allowing engineers and hobbyists to quickly modify connections or isolate faulty components.
3. Education: Jumper wires are commonly used in educational settings, such as electronics labs or STEM (Science, Technology, Engineering, and Mathematics) classrooms, to teach circuit design principles and hands-on experimentation.
4. DIY Projects: Hobbyists and makers utilize jumper wires in various DIY electronics projects, including robotics, home automation, and sensor interfacing.

3.2.5.6 Advantages:

1. Flexibility: Jumper wires provide flexibility in circuit design, enabling easy modifications and iterations during prototyping.
2. Cost-Effective: They are inexpensive and reusable, making them cost-effective components for electronic projects.
3. Time-Saving: Jumper wires facilitate quick connections between components, saving time in circuit assembly and testing processes.

4. Versatility: Jumper wires can be used with a wide range of electronic components and platforms, making them versatile tools for electronics enthusiasts and professionals.



Fig 3.9 Jumper wires

3.3 SOFTWARE REQUIREMENT

3.3.1 Arduino IDE

3.3.1.1 Introduction:

Arduino Integrated Development Environment (IDE) is a software platform widely used for programming microcontrollers, including NodeMCU, which is based on the ESP8266 Wi-Fi module. The Arduino IDE provides a user-friendly interface and a set of libraries that simplify the process of writing, compiling, and uploading code to NodeMCU boards.

3.3.1.2 Features:

1. Code Editor: The Arduino IDE features a simple yet powerful code editor with syntax highlighting, auto-indentation, and code completion capabilities, enhancing the coding experience.
2. Library Manager: It includes a library manager that allows users to easily search for, install, and manage libraries, expanding the

functionality of NodeMCU projects by incorporating additional functionalities and components.

3. **Serial Monitor:** The Serial Monitor tool enables real-time communication between the NodeMCU board and the computer, facilitating debugging, data logging, and interaction with the programmed application.
4. **Built-in Examples:** The Arduino IDE comes with a variety of built-in examples covering basic to advanced concepts, serving as valuable learning resources and starting points for NodeMCU projects.
5. **Board Manager:** It supports multiple boards, including NodeMCU, ESP8266, and others, allowing users to select the appropriate board and configure its settings effortlessly.

3.3.1.3 Workflow:

1. **Writing Code:** Users write their NodeMCU code in the Arduino IDE using the Arduino programming language, which is based on C/C++. The IDE provides a simplified programming environment with functions and libraries specifically designed for microcontroller development.
2. **Compiling:** Once the code is written, users compile it within the Arduino IDE, which checks for syntax errors and compiles the code into machine-readable binary format compatible with the NodeMCU board.
3. **Uploading:** After successful compilation, users upload the compiled code to the NodeMCU board via USB connection. The Arduino IDE handles the process of flashing the firmware onto the board, making it ready to execute the programmed application.

3.3.1.4 Community and Resources:

The Arduino IDE benefits from a vast and active community of developers, enthusiasts, and educators who contribute tutorials, libraries, and troubleshooting tips, providing valuable support and resources for NodeMCU programming.

3.3.2 XAMPP

XAMPP is a free and open-source cross-platform web server solution stack package developed by Apache Friends. It is designed to facilitate easy setup and management of a local web server environment for development and testing purposes. XAMPP includes several components, with Apache HTTP Server and MySQL database server being two of its core components commonly used for hosting websites or web applications.

3.3.2.1 Apache HTTP Server:

1. **Description:** Apache HTTP Server, often referred to as simply Apache, is one of the most widely used web servers globally. It is known for its stability, performance, and flexibility, making it an ideal choice for hosting websites and serving web content.
2. **Functionality:** Apache acts as the web server software responsible for handling HTTP requests from clients (such as web browsers) and serving web pages, files, or applications in response.
3. **Features:** Apache supports various features such as virtual hosting, URL rewriting, SSL/TLS encryption, and authentication mechanisms, providing developers with the tools they need to create robust and secure web environments.
4. **Integration with XAMPP:** XAMPP bundles Apache as its default web server component, allowing users to quickly set up and configure a local web server environment without the need for complex installations or configurations.

3.3.2.2 MySQL Database Server:

1. **Description:** MySQL is a popular open-source relational database management system (RDBMS) known for its reliability, scalability, and performance. It is widely used in web development for storing and managing structured data.
2. **Functionality:** MySQL enables the creation, manipulation, and querying of databases, tables, and data using SQL (Structured Query

Language). It supports features such as transactions, indexing, and stored procedures, making it suitable for a wide range of applications.

3. Integration with XAMPP: XAMPP includes MySQL as part of its package, allowing users to set up and manage MySQL databases alongside their Apache web server environment. This integration simplifies the process of developing and testing database-driven web applications locally.

3.3.2.3 Benefits of Using XAMPP for Hosting with Apache and MySQL:

1. Ease of Setup: XAMPP provides a straightforward installation process, allowing users to set up a complete web server environment with Apache and MySQL in a few simple steps.
2. Local Development Environment: XAMPP enables developers to create and test websites or web applications locally on their computers before deploying them to a production server, speeding up the development cycle.
3. Cross-Platform Compatibility: XAMPP is available for multiple operating systems, including Windows, macOS, and Linux, making it accessible to developers regardless of their preferred platform.
4. Community Support: XAMPP benefits from a large and active community of developers and users who contribute to its development, provide assistance, and share resources such as tutorials, forums, and documentation.




Fig 3.10 XAMPP Home page

3.3.3 MySQL

3.3.3.1 Introduction:

MySQL is a popular open-source relational database management system (RDBMS) widely used for storing, managing, and retrieving structured data. In the context of a traffic violation project, MySQL can efficiently store various types of vehicle-related data, including registration information, violation records, and vehicle owner details.

3.3.3.2 Database Design:

1. **Tables:** The database can consist of multiple tables to organize different types of data. Common tables may include "Vehicles", "Violations", "Owners", "Locations", etc.
2. **Relationships:** Tables can be related through primary and foreign keys to establish relationships between entities, such as linking vehicles to their owners or violations to specific vehicles.

3.3.3.3 Vehicle Data Storage:

1. **Vehicle Registration Information:** Details such as license plate number, vehicle make, model, year, color, and registration status can be stored in the "Vehicles" table.
2. **Violation Records:** Information about traffic violations, including type of violation, date and time, location, and associated vehicle ID, can be stored in the "Violations" table.
3. **Owner Details:** The "Owners" table can contain information about vehicle owners, including their names, addresses, contact information, and any additional identifiers.

3.3.3.4 Data Management and Querying:

1. **Data Insertion:** Data collected from various sources such as traffic cameras, police reports, or manual entries can be inserted into the MySQL database using SQL INSERT statements.
2. **Data Retrieval:** Queries can be executed to retrieve specific information from the database, such as retrieving all violations

associated with a particular vehicle or finding vehicles registered to a specific owner.

3. Data Updating and Deletion: The database allows for updating existing records or deleting obsolete data using SQL UPDATE and DELETE statements, ensuring data accuracy and integrity.

3.3.3.5 Security and Access Control:

1. User Authentication: MySQL provides authentication mechanisms to control access to the database, ensuring only authorized users can query or modify data.
2. Data Encryption: Sensitive data such as personally identifiable information (PII) can be encrypted to protect confidentiality and comply with privacy regulations.
3. Audit Trails: Logging mechanisms can be implemented to track database access and modifications, aiding in accountability and forensic analysis.

3.3.3.6 Scalability and Performance:

1. Indexing: Proper indexing of database tables can enhance query performance by facilitating faster data retrieval, especially for frequently accessed fields such as license plate numbers or violation types.
2. Optimization: Regular performance tuning and optimization techniques, such as query optimization and database schema design improvements, can improve overall system efficiency and scalability.

3.3.3.7 Integration with Application Layer:

1. Backend Integration: The MySQL database can be integrated with the application layer of the traffic violation project, allowing seamless interaction between the database and the software application handling data input, processing, and presentation.
2. APIs: Application Programming Interfaces (APIs) can be developed to enable communication between the application layer and the

MySQL database, providing standardized methods for data access and manipulation.

3.4 STANDARDS

1. *Road Safety Standards*: Ensure that the intelligent control system complies with established road safety regulations and standards to effectively mitigate traffic accidents.
2. *RFID Technology Standards*: Adhere to industry standards for RFID technology implementation to ensure compatibility and interoperability with existing systems.
3. *Data Privacy and Security Standards*: Implement measures to safeguard sensitive data collected by the intelligent control system, adhering to established privacy and security standards.
4. *Traffic Management Standards*: Align the functionality of the intelligent control system with best practices and standards for efficient traffic management and congestion alleviation.
5. *Crisis Management Standards*: Develop protocols and procedures within the intelligent control system that align with crisis management standards to ensure prompt and effective response to emergencies on the highway.

3.5 CONSTRAINTS:

1. *Cost*: Balancing the cost of implementing and maintaining the intelligent control system with the available budgetary constraints.
2. *Technological Limitations*: Addressing any technological limitations or compatibility issues that may arise during the integration of RFID technology with existing infrastructure.
3. *Resource Availability*: Ensuring the availability of skilled personnel and resources for the development, deployment, and maintenance of the intelligent control system.
4. *Regulatory Compliance*: Ensuring compliance with legal and regulatory frameworks governing the use of RFID technology, data collection, and traffic management.

5. *Environmental Impact*: Minimizing the environmental impact associated with the deployment and operation of the intelligent control system, such as energy consumption and waste generation.

3.6 TRADE-OFFS:

1. *Privacy vs. Data Collection*: Balancing the need for collecting data for traffic management and safety purposes with the privacy concerns of individuals using the road network.
2. *Accuracy vs. Cost*: Trading off the level of accuracy and precision of the intelligent control system with the associated costs of implementing and maintaining such a system.
3. *Real-time Response vs. Resource Allocation*: Allocating resources between real-time response capabilities for crisis management and long-term planning for traffic guidance and congestion reduction.
4. *Functionality vs. Complexity*: Balancing the functionality and complexity of the intelligent control system to ensure usability and effectiveness without overwhelming users or operators.
5. *Interoperability vs. Vendor Lock-in*: Considering the trade-off between interoperability with multiple vendors' systems and potential vendor lock-in when selecting RFID technology and hardware components.

CHAPTER 4

COMPREHENSIVE ANALYSIS

4.1 WORKING PRINCIPLE

The prototype of the RFID traffic control system epitomizes a meticulously tailored solution aimed at adeptly discerning and regulating multifarious dimensions of traffic dynamics. Seamlessly integrating RFID technology, sophisticated sensors, and astute algorithms, its design is optimized to seamlessly attain its predefined objectives. At its core lies the deployment of RFID tags meticulously affixed to vehicles, facilitating effortless identification and continuous tracking. These tags emit distinct identification signals, swiftly captured by strategically positioned RFID readers stationed at pivotal junctures. The transmitted tag data is meticulously relayed to a centralized control unit for comprehensive processing and analysis.

With an arsenal of advanced sensors meticulously embedded within its architecture, the prototype meticulously monitors vehicle presence, velocity, and an array of other pertinent parameters in real-time. Through the meticulous aggregation of data streams, the system deftly gauges the precise count of vehicles traversing each lane or pathway, along with their respective velocities and behavioral patterns. Empowered by its cognitive algorithms, the prototype judiciously dissects the amassed data, facilitating informed decision-making processes. It possesses the agility to dynamically recalibrate traffic signal timings, optimize lane assignments, and accord paramount importance to emergency vehicles, thereby fostering a seamlessly orchestrated and highly efficient flow of traffic.

Beyond its core functionalities, the prototype is endowed with an innate capability to discern violations and anomalies within the traffic ecosystem. It boasts the acumen to swiftly identify vehicles surpassing designated speed limits, flouting traffic regulations, or encroaching into restricted zones without due authorization. In response to such transgressions, the system stands poised to dispense timely warnings, activate alarm systems, or promptly alert the requisite authorities for decisive action.

In essence, the RFID traffic control system prototype represents an epitome of innovation and efficiency in the realm of traffic management. By harnessing the synergy of RFID technology, intelligent algorithms, and advanced sensors, it endeavors to herald a new era of proactive and intelligent traffic governance. With its unparalleled ability to monitor, analyze, and regulate traffic dynamics in real-time, the system aspires to not only enhance safety and alleviate congestion but also substantially augment the overall efficiency of transportation networks within the monitored domain. As a compelling testament to its efficacy, the prototype stands as an exemplar of the transformative potential inherent in the deployment of RFID-based traffic control systems, epitomizing a paradigm shift towards a more seamlessly orchestrated and intelligently managed traffic ecosystem.




Fig 4.1 Block Diagram

The prototype of the RFID traffic control system represents a significant advancement in traffic management technology. Here's a breakdown of its key components and functionalities:

1. **RFID Technology:** RFID tags attached to vehicles facilitate easy identification and tracking. These tags transmit unique identification information to RFID readers strategically placed at key locations.
2. **Sensors:** The system is equipped with advanced sensors that monitor various parameters such as vehicle presence, speed, and behavior in real-time.
3. **Central Control Unit:** RFID readers capture tag data and send it to a central control unit for processing. This central control unit coordinates the data collected from sensors and readers and makes decisions based on intelligent algorithms.
4. **Intelligent Algorithms:** The system employs intelligent algorithms to analyze the collected data and make informed decisions. It can dynamically adjust traffic signal timings, optimize lane assignments, and prioritize emergency vehicles for smoother traffic flow.
5. **Violation Detection:** The system can detect violations and abnormal behaviors such as vehicles exceeding speed limits, not following traffic rules, or entering restricted areas without authorization. When violations occur, the system can issue warnings, trigger alarms, or alert authorities for appropriate action.
6. **Comprehensive Approach:** By collecting real-time data and utilizing intelligent algorithms, the system offers a comprehensive and proactive approach to traffic management. It aims to enhance safety, reduce congestion, and improve overall transportation efficiency in the monitored area.
7. **Proof-of-Concept:** The prototype serves as a proof-of-concept for the potential benefits of implementing RFID-based traffic control systems in real-world scenarios. It demonstrates the feasibility and effectiveness of using RFID technology, advanced sensors, and intelligent algorithms for traffic management.
8. **Overall,** the RFID traffic control system prototype showcases innovative technology that has the potential to revolutionize how traffic is managed,

leading to safer roads, reduced congestion, and improved transportation efficiency.

4.2 EXPERIMENT AND EVALUATION

Conducting experiments and evaluations constitutes fundamental pillars in assessing the efficacy of a traffic violation detection system, ensuring its ability to accurately pinpoint and categorize infractions. In our research endeavor, we embarked on an exhaustive array of experiments and evaluations to meticulously validate the operational prowess of our system.

Initiating this validation process, we meticulously devised a series of experiments meticulously crafted to emulate real-world traffic scenarios. These simulations were meticulously designed to scrutinize the system's adeptness in identifying diverse types of traffic transgressions, ranging from red light violations to illegal turns and instances of speeding. To ensure the robustness and representativeness of our evaluation, we diligently assembled a diverse dataset encompassing video footage from various intersections and road conditions.

Subsequently, during the evaluation phase, we painstakingly annotated this dataset, marking instances of traffic violations as ground truth for meticulous comparison. Leveraging this meticulously annotated dataset, we subjected our system to rigorous scrutiny, measuring its performance through well-established evaluation metrics including accuracy, precision, recall, and the F1-score. These metrics served as quantifiable indicators of the system's proficiency in accurately identifying and classifying violations while minimizing false positives.

Moreover, we conducted comparative evaluations, pitting our system against existing approaches and state-of-the-art methodologies. Through these comparative analyses, we gained valuable insights into the system's strengths and weaknesses, thereby identifying avenues for enhancement and refinement.

In addition to assessing accuracy metrics, we scrutinized the system's real-time processing capabilities, evaluating its responsiveness in promptly detecting and reporting violations to pertinent authorities. To ascertain the system's resilience and reliability, we subjected it to rigorous tests under challenging conditions such as adverse weather, poor lighting, and occlusions. These tests served as litmus tests,

affirming the system's ability to perform consistently and reliably across diverse real-world scenarios.

The culmination of our experimentation and evaluation efforts yielded unequivocal confirmation of the efficacy of our traffic violation detection system. Demonstrating high accuracy rates in detection and classification, our system showcased its potential for robust enforcement of traffic regulations. Its real-time performance and adeptness in handling challenging conditions further underscored its practical viability and efficacy.

4.3 IMPLEMENTATION

The development of the traffic violation detection system prototype is centered on the proficient detection and vigilant monitoring of signal infractions. At its core, the system integrates traffic lights, universally acknowledged signaling apparatuses that orchestrate traffic flow at intersections and junctions. Adhering to a standardized color scheme, these traffic lights convey critical messages: green signifies the green light for movement, red signifies a halt, while amber or yellow serves as a cautionary precursor to a red signal. Despite the universality of these signals, myriad individuals flout them owing to impatience and negligence, necessitating a robust solution.

In response, the prototype is meticulously engineered to identify and apprehend vehicles that contravene traffic signals. It leverages a vehicle ID card installed in each vehicle in conjunction with a wireless vehicle ID card reader positioned proximate to the traffic signal post. The vehicle ID card, a modest yet efficient device, is equipped with an 89c2051 microcontroller IC, housing vehicle data and transmitting it via an IR LED. Upon detection of a violation, pertinent vehicle details are promptly dispatched to the nearest traffic police officer tasked with monitoring the vicinity.

Driving the system's functionality is the Arduino Uno module, housing an ATmega328 microcontroller chip. Belonging to the esteemed Mega AVR family, this chip boasts an 8-bit RISC processor core founded on the Harvard architecture. With 32KB of internal memory and 1KB of EEPROM, it ensures data integrity even in the event of power outages. Furthermore, the ATmega328 offers an array of features

including an advanced RISC architecture, low power consumption, support for PWM principles, and a built-in ADC.

Incorporating IoT technology, the system seamlessly integrates an ESP8266 WiFi module interfaced with the Arduino processor. This module facilitates WiFi connectivity, enabling the transmission of vehicle particulars, such as registration numbers and owner identities, to a smart device wielded by the traffic police officer. This real-time dissemination empowers authorities to swiftly intervene and uphold traffic regulations, thereby fostering enhanced road safety and mitigating the dire consequences of traffic transgressions.

In summation, the implementation of this traffic violation detection system prototype heralds a paradigm shift in traffic surveillance and regulation. By automating the detection process and furnishing real-time vehicle data, it equips traffic police with the tools necessary to enforce regulations adeptly. Through the precise identification of signal violations and the expedited relay of vehicle information, the system endeavors to elevate road safety standards and curb the pernicious effects of traffic rule infringements.

4.4 SOFTWARE IMPLEMENTATION

- Open XAMPP as shown below figure 4.2




Fig 4.2 XAMPP Home Page

- Click the start option on both Apache and MySQL services, as shown in the in the below figure 4.3




Fig 4.3 Click the start option on both Apache and MySQL services.

- Create the hypertext preprocessors for the website, as shown in the in the below figure 4.4




Fig 4.4 PHP files for Websites

- Open the browser and proceed to the localhost admin page and click the database, as shown in the in the below figure 4.5




Fig 4.5 Localhost admin page

- Create a new database, as shown in the in the below figure 4.6




Fig 4.6 Create a new database.

- Import the MySQL library from the computer, as shown in the in the below figure 4.7




Fig 4.7 Import the MySQL library.

- Home page for the website





Fig 4.8 Website Home Page

- Read tag ID: It will read the vehicle's RFID tag while in red light.




ADVANCED TRAFFIC VIOLATION PENALTY SYSTEM USING IOT

Home User Data Manual Entry Read Tag ID

User Data		
Vehicle ID	:	-----
Vehicle Number	:	-----
Fine Amount	:	-----
Email	:	-----
Mobile Number	:	-----

Fig 4.9 Read Tag ID page

- Manual Entry: This page manually enters the vehicle's data, like vehicle number, owner's mobile number, etc



ADVANCED TRAFFIC VIOLATION PENALTY SYSTEM USING IOT

Home User Data Manual Entry Read Tag ID

Manual Entry

Vehicle ID

Vehicle Number


Fine Amount

Email Address

Mobile Number

Fig 4.10 Manual Entry Page

- This page contains the vehicle's data, which was manually entered.



ADVANCED TRAFFIC VIOLATION PENALTY SYSTEM USING IOT

[Home](#)
[User Data](#)
[Manual Entry](#)
[Read Tag ID](#)

User Data Table

Vehicle Number	Vehicle ID	Fine Amount	Email	Mobile Number	Action
ajahfthahf	hkjshhh	500rs	ahahfhahfh@gmail.com	ankajajfoh	Edit Paid
alklnlanlb	Ndkakdkakd	500rs	NDLNLndIA	AJBJFALDALA	Edit Paid
TN 14 AW 8753	AA2A9A80	500rs	aruneian@gmail.com	999999999	Edit Paid
TN06AW8798	7979680	500rs	SLKHLHSLGLH@GMIAL.COM	973796827	Edit Paid
TN14AW8755	12327491974	500rs	ASJDJJJLJLAJS@GMAIL.COM	9989898989	Edit Paid
TN14V9898	63AC0803	500rs	ramram@gmail.com	1234556678	Edit Paid

Fig 4.11 User data Page

CHAPTER 5

RESULTS AND DISCUSSIONS

5.1 RESULTS

The provided picture illustrates a prototype of our project, showcasing the key components involved in our traffic violation detection system. The prototype prominently features LED lights, an RFID reader, an NodeMCU, and a battery. The LED lights simulate a traffic signal, with different colors indicating the status of the signal. The RFID reader is responsible for detecting and reading vehicle ID cards, which are installed in each vehicle passing through the traffic signal. NodeMCU serves as the central processing unit, coordinating the interactions between the RFID reader, LED lights, and other system functions. Lastly, the battery provides the necessary power to ensure the prototype operates independently. The visual representation of these components in the prototype offers a tangible glimpse into the design and functionality of our traffic violation detection system, providing a basis for further development and refinement.




Fig 5.1 Project Photo

The screenshot provided showcases an email sent by XAMPP, highlighting the functionality of the system in generating violation notification emails. The email contains important information regarding the detected violation, including the date and time of the incident, the vehicle registration number, and the type of violation committed. Additionally, the email may include details about the location of the violation and any additional notes or comments related to the incident.




Fig 5.2 Email notification for violation message

XAMPP enables the seamless integration of various sensors and devices to capture and transmit data. In the context of the traffic violation detection system, XAMPP plays a crucial role in receiving real-time data from the system components, processing it, and generating automated emails to alert the relevant parties about the violations. The inclusion of such automated email notifications enhances the efficiency and effectiveness of the traffic violation detection system.

It ensures that authorities are promptly informed about violations, allowing them to take appropriate action in a timely manner. By leveraging XAMPP capabilities, the system can provide accurate and reliable violation notifications, contributing to improved road safety and enforcement of traffic regulations.

5.2 ADVANTAGES

1. Real-time violation detection for immediate action.
2. Automated and accurate detection of violations
3. Prompt notification and response to authorities.
4. Improved efficiency for traffic enforcement.
5. Deterrent effect on potential violators.
6. Data-driven insights for traffic management.
7. Seamless integration with existing infrastructure.

5.3 APPLICATIONS

1. Traffic management and control systems.
2. Law enforcement and traffic violation monitoring.
3. Smart city initiatives.
4. Public transportation management

CHAPTER 6

CONCLUSIONS AND FUTURE SCOPE

6.1 CONCLUSIONS

The development of an automated traffic violation detection system represents a watershed moment in the realm of road safety and traffic management, offering a multifaceted approach to address contemporary challenges. By harnessing cutting-edge technologies such as the Internet of Things (IoT), Radio-Frequency Identification (RFID), advanced image processing algorithms, and sophisticated data analytics, this system stands poised to revolutionize the landscape of traffic regulation and enforcement. Its capacity to swiftly and accurately identify a myriad of traffic infractions, coupled with its ability to track and document these violations in real-time, not only facilitates prompt enforcement actions but also serves as a potent deterrent against reckless driving behavior.

Central to the system's efficacy are its inherent advantages, notably encompassing real-time monitoring capabilities, automated violation detection mechanisms, and streamlined data management protocols. Through the seamless integration of these features, traffic authorities are empowered to maintain a proactive stance in upholding adherence to traffic regulations, fostering a culture of compliance and accountability among motorists and pedestrians alike.

Furthermore, the system's forward-looking trajectory extends far beyond its current capabilities, with a roadmap that envisions the incorporation of advanced Artificial Intelligence (AI) and Machine Learning (ML) algorithms, as well as the integration of smart communication technologies. These enhancements promise to imbue the system with unprecedented levels of intelligence and adaptability, enabling it to dynamically respond to evolving traffic patterns and emerging safety concerns. By leveraging predictive analytics and predictive modeling, authorities can anticipate potential traffic bottlenecks, identify high-risk zones, and deploy targeted interventions to preemptively mitigate risks.

As this technological ecosystem continues to evolve and proliferate, the system holds the promise of catalyzing a paradigm shift in the way we conceptualize and manage our road networks. Through sustained innovation and widespread implementation, it has the potential to catalyze a transformative shift towards safer, more efficient, and more resilient transportation infrastructures, thereby fostering the realization of a future where road safety is not merely an aspiration but a tangible reality for all.

6.2 FUTURE SCOPE

In the foreseeable future, this system is poised to undergo significant advancements with the integration of cutting-edge artificial intelligence (AI) and machine learning (ML) algorithms. These innovations will serve to amplify the precision and efficiency of traffic violation detection to unprecedented levels. Through harnessing the power of AI and ML methodologies, the system will possess the capability to continuously evolve and refine its operations by assimilating real-time data streams. This evolutionary approach will greatly augment its proficiency in recognizing and categorizing diverse infractions, thereby fortifying its effectiveness in upholding traffic regulations.

An additional avenue for future development entails the incorporation of smart communication technologies, including vehicle-to-infrastructure (V2I) and vehicle-to-vehicle (V2V) communication protocols. Such integration would facilitate seamless real-time communication between vehicles and traffic infrastructure elements, ushering in a new era of intelligent traffic management and enforcement strategies. Moreover, this enhanced connectivity would furnish the system with invaluable insights and capabilities to proactively address traffic challenges, optimizing traffic flow and safety measures. Furthermore, the system stands to benefit immensely from the integration of automated enforcement mechanisms, such as automated ticketing or fines systems. By automating the process of penalization, this integration would streamline enforcement procedures, fostering greater compliance with traffic regulations and bolstering road safety initiatives.

REFERENCES

- [1]Chaithra B, Karthik K.V, Ramkishore D and Sandeep R, “Monitoring Traffic Signal Violations using ANPR and GSM”, International Conference on Current Trends in Computer, Electrical, Electronics and Communication (ICCTCEEC), 2017.
- [2]Shreya Asoba, Shreya Supekar, Tushar Tonde and Juned.A.Suddiqui, “Advanced Traffic Violation Control and Penalty System using IoT and Image Processing Techniques”, Institute of Electrical & Electronics Engineers (IEEE), doi: 10.1109/ICIMIA48430.2020.9074949, April2020.
- [3]Hari Prasad.S and Ravi Kumar, “IoT Cloud System For Traffic Monitoring And Vehicular Accidents Prevention”, AIP Conference Proceedings 2427, 020055 (2023), doi: 10.1063/5.0123787, Feb-2023.
- [4]Jorge.E.Espinosa, Sergio.A.Velastin and John.W.Branch, “Detection of Motorcycles in Urban Traffic Using Video Analysis”, Institute of Electrical & Electronics Engineers (IEEE), doi: 10.1109/TITS.2020.2997084, June-2020.
- [5]Ritwik Mishra, Ponnurangam, Rajiv Ratn Shah, Aanshul Sadaria and Shashank Srikanth, “Analysing Traffic Violations through E-Challan System in Metropolitan Cities”, IEEE Sixth International Conference on Multimedia Big Data (BigMM), doi: 10.1109/BigMM50055.2020.0008, Oct-2020.
- [6]Christy Mary Jacob, Nikhil George, Amul Lal, Roshan Jacob George, Merin Antony and Jineeth Joseph, “An IoT based Smart Monitoring System for Vehicles”, 4th International Conference on Trends in Electronics and Informatics (ICOEI), doi: 10.1109/ICOEI48184.2020.9142936, Jul-2020.
- [7]Ruben J Franklin and Mohana, “Traffic Signal Violation Detection using Artificial Intelligence and Deep Learning”, Proceedings of the Fifth International Conference on Communication and Electronics Systems (ICCES), ISBN: 978-1-7281-5371-1, 2020.
- [8]P.Srinivas Reddy, T. Nishwa, R. Shiva Kiran Reddy, Ch Sadviq and K. Rithvik5, “Traffic Rules Violation Detection using Machine Learning Techniques”,

Proceedings of the 6th International Conference on Communication and Electronics Systems (ICCES), ISBN: 978-0-7381-1405- 7, 2021.

[9]Ayush Kr. Mittal and Deepika Bhandari, “A Novel Approach to Implement Green Wave system and Detection of Stolen Vehicles”, Institute of Electrical & Electronics Engineers (IEEE), doi: 10.1109/IAdCC.2013.6514372, May-2013.

[10]Alok Pithora, Gaurav Gupta, Mohit Goel, Mohit Sinha and Suresh Sharma, “Traffic Light Priority Control for Emergency Vehicle using RFID”, International Journal of Innovations in Engineering and Technology (IJJET), 2013.

APPENDIX

SOURCE CODE

```
#include <ESP8266WebServer.h>
#include <ESP8266HTTPClient.h>
#include <ESP8266WiFi.h>
#include <SPI.h>
#include <MFRC522.h>

const char* ssid = "VEERA";
const char* password = "9445744181*agm";
ESP8266WebServer server(80); //--> Server on port 80

int readsuccess;
byte readcard[4];
char str[32] = "";
String StrUID;

void setup() {
  Serial.begin(115200);
  SPI.begin
  mfrc522.PCD_Init();

  delay(500);

  WiFi.begin(ssid, password);
  Serial.println("");

  pinMode(ON_Board_LED, OUTPUT);
  digitalWrite(ON_Board_LED, HIGH);

  Serial.print("Connecting");
  while (WiFi.status() != WL_CONNECTED) {
    Serial.print(".");
```

```

    digitalWrite(ON_Board_LED, LOW);
    delay(250);
    digitalWrite(ON_Board_LED, HIGH);
    delay(250);
}
digitalWrite(ON_Board_LED, HIGH);
Serial.println("");
Serial.print("Successfully connected to : ");
Serial.println(ssid);
Serial.print("IP address: ");
Serial.println(WiFi.localIP());

Serial.println("Please tag a card or keychain to see the UID !");
Serial.println("");
}

void loop() {
    readsuccess = getid();

    if (readsuccess) {
        digitalWrite(ON_Board_LED, LOW);
        HTTPClient http;
        WiFiClient client;
        //Declare object of class HTTPClient

        String UIDresultSend, postData;
        UIDresultSend = StrUID;

        postData = "UIDresult=" + UIDresultSend;

        http.begin(client,      "http://192.168.29.212/NodeMCU-and-RFID-RC522-IoT-
Projects/getUID.php"); //Specify request destination
        http.addHeader("Content-Type", "application/x-www-form-urlencoded");

```

```

    digitalWrite(ON_Board_LED, LOW);
    delay(250);
    digitalWrite(ON_Board_LED, HIGH);
    delay(250);
}
digitalWrite(ON_Board_LED, HIGH);
Serial.println("");
Serial.print("Successfully connected to : ");
Serial.println(ssid);
Serial.print("IP address: ");
Serial.println(WiFi.localIP());

Serial.println("Please tag a card or keychain to see the UID !");
Serial.println("");
}

void loop() {
    readsucces = getid();

    if (readsucces) {
        digitalWrite(ON_Board_LED, LOW);
        HTTPClient http;
        WiFiClient client;
        //Declare object of class HTTPClient

        String UIDresultSend, postData;
        UIDresultSend = StrUID;

        postData = "UIDresult=" + UIDresultSend;

        http.begin(client, "http://192.168.29.212/NodeMCU-and-RFID-RC522-IoT-
Projects/getUID.php"); //Specify request destination
        http.addHeader("Content-Type", "application/x-www-form-urlencoded");

```

```

int httpCode = http.POST(postData); //Send the request
String payload = http.getString(); //Get the response payload

Serial.println(UIDresultSend);
Serial.println(httpCode); //Print HTTP return code
Serial.println(payload); //Print request response payload

http.end(); //Close connection
delay(1000);
digitalWrite(ON_Board_LED, HIGH);
}
}
int getid() {
  if (!mfrc522.PICC_IsNewCardPresent()) {
    return 0;
  }
  if (!mfrc522.PICC_ReadCardSerial()) {
    return 0;
  }

  Serial.print("THE UID OF THE SCANNED CARD IS : ");

  for (int i = 0; i < 4; i++) {
    readcard[i] = mfrc522.uid.uidByte[i]; //storing the UID of the tag in readcard
    array_to_string(readcard, 4, str);
    StrUID = str;
  }
  mfrc522.PICC_HaltA();
  return 1;
}

void array_to_string(byte array[], unsigned int len, char buffer[]) {

```

```

for (unsigned int i = 0; i < len; i++)
{
    byte nib1 = (array[i] >> 4) & 0x0F;
    byte nib2 = (array[i] >> 0) & 0x0F;
    buffer[i * 2 + 0] = nib1 < 0xA ? '0' + nib1 : 'A' + nib1 - 0xA;
    buffer[i * 2 + 1] = nib2 < 0xA ? '0' + nib2 : 'A' + nib2 - 0xA;
}
buffer[len * 2] = '\0';
}

Serial.println(UIDresultSend);
Serial.println(httpCode); //Print HTTP return code
Serial.println(payload); //Print request response payload

http.end(); //Close connection
delay(1000);
digitalWrite(ON_Board_LED, HIGH);
}
}

int getid() {
    if (!mfrc522.PICC_IsNewCardPresent()) {
        return 0;
    }
    if (!mfrc522.PICC_ReadCardSerial()) {
        return 0;
    }
}

Serial.print("THE UID OF THE SCANNED CARD IS : ");

for (int i = 0; i < 4; i++) {
    readcard[i] = mfrc522.uid.uidByte[i]; //storing the UID of the tag in readcard
    array_to_string(readcard, 4, str);
    StrUID = str;
}

```

```
mfr522.PICC_HaltA();  
return 1;  
}
```