

IRON RODS SURFACE CRACK DETECTION USING DEEP LEARNING AND IMAGE PROCESSING TECHNIQUE

Submitted in partial fulfilment of requirements for the award of
Bachelor of Engineering in Electronics and Communication Engineering

By

PALLAPOTHU KARTHIK CHOWDARY (Reg no:40130161)

PALLE VENKATA BHUVANA CHANDRA REDDY (Reg no:40130162)



DEPERTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING

SCHOOL OF ELECTRICAL AND ELECTRONICS

SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY

**(DEEMED TO BE UNIVERSITY)
CATEGORY-1 UNIVERSITY BY UGC**

Accredited with Grade “A++” by NAAC | 12B Status by UGC | Approved by AICTE

JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI - 600 119

APRIL - 2024



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY

(DEEMED TO BE UNIVERSITY)


Accredited "A++" Grade by NAAC | 12B Status by UGC | Approved by AICTE

www.sathyabama.ac.in

DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING


BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of **PALLAPOTHU KARTHIK CHOWDARY(40130161)** and **PALLE VENKATA BHUVANA CHANRA REDDY (40130162)** who carried out the project entitled "**IRON RODS SURFACE CRACK DETECTION USING DEEP LEARNING AND IMAGE PROCESSING TECHNIQUE**" under our supervision from November 2023 to April 2024.



Internal Guide

Dr.V.J.K.KISHOR SONTI M.Tech, Ph.D.



Head of the Department

Dr.T.RAVI M.E., Ph.D.

Submitted for Viva voce Examination held on

Internal Examiner

External Examiner

DECLARATION


I, **PALLAPOTHU KARTHIK CHOWDARY(40130161)** hereby declare that the Project Report entitled **"IRON RODS SURFACE CRACK DETECTION USING DEEP LEARNING AND IMAGE PROCESSING TECHNIQUE"** done by me under the guidance of **Dr. V. J. K. KISHORE SONTI MTech, Ph.D.**, is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in Electronics and Communication Engineering.

DATE: 17.04.2024

PLACE: CHENNAI

SIGNATURE OF THE CANDIDATE

1.



DECLARATION


I, **PALLE VENKATA BHUVANA CHANDRA REDDY(40130162)** hereby declare that the Project Report entitled **"IRON RODS SURFACE CRACK DETECTION USING DEEP LEARNING AND IMAGE PROCESSING TECHNIQUE"** done by me under the guidance of **Dr. V. J. K. KISHORE SONTI MTech, Ph.D.**, is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in Electronics and Communication Engineering.

DATE: 17.04.2024

PLACE: CHENNAI

SIGNATURE OF THE CANDIDATE

1.



ACKNOWLEDGEMENT

we are pleased to acknowledge our sincere thanks to Board of Management of **Sathyabama Institute of Science and Technology** for their kind encouragement in doing this project and for completing it successfully. We are grateful to them.

We convey my thanks to **Dr. N. M. NANDHITHA MTech, Ph.D.** Dean, School of Electronics and Communication Engineering and **Dr. T. RAVI M.E, Ph.D.** Head of the Department, Department of Electronics and Communication Engineering for providing me necessary support and details at the right time during the progressive reviews.

We would like to express my sincere and deep sense of gratitude to our Project Guide **Dr. V. J. K. Kishor Sonti MTech, Ph.D.** for his valuable guidance, suggestions, and constant encouragement paved way for the successful completion of our project work.

We wish to express our thanks to all Teaching and Non-teaching staff members of the Department of **Electronics and Communication Engineering** who were helpful in many ways for the completion of the project.

ABSTRACT

In this system, we use VGG16 to detect the faults in the railway tracks by images. And acquire their characteristics to extract the default of the railway track. This model will help to reduce the manual working for inspection. While performing the task it lowers the time utilization and cost and increases the safety of passengers. To train and validate the VGG16 algorithm we use the ground truth database on images of masks. To This end, This VGG16 maintains the both space and time coherence of the defects in the tracks, and the final output throw of the false prediction effectively. To this end, This VGG16 maintains both space and time coherence of the defects in the tracks, and the final output throw of the false prediction effectively. It emphasizes the importance of collecting a diverse dataset comprising images of both damaged and undamaged metallic rods across various environments. A deep learning model, such as a convolutional neural network (CNN), is trained on the segmented images to recognize complex patterns indicative of cracks. Evaluation metrics such as recall, accuracy, precision, and F1-score are employed to assess the model's performance. By CNN we detect crack up to 85-90%. Post-processing techniques are employed to refine predictions and mitigate noise or false positives. Experimental results demonstrate the practicality and effectiveness of the proposed methodology, with this model we detect iron surface cracks by using VGG16 and deep learning CNN technique.

INDEX

CHAPTER No.	TITLE	PAGE No.
	ABSTRACT	V
	LIST OF FIGURES	Viii
	LIST OF TABLES	Viii
1	INTRODUCTION	1
	1.1 INTRODUCTION	1
	1.2 SYSTEM STUDY	2
	1.3 OBJECTIVE	3
2	LITERATURE SURVEY	4
	2.1 LITERATURE SURVEY	4
	2.2 PROBLEM STATEMENT	10
3	AIM AND SCOPE	11
	3.1 PROPOSED WORK	11
	3.1.1 MERITS OF PROPOSED WORK	11
	3.2 ARCHITECTURE	12
	3.2.1 BLOCK DIAGRAM	13
	3.3 MODULES	14
	3.4 EXISTING SYSTEM	16
	3.4.1 DE-MERITS OF EXISTING SYSTEM	17

4	ALGORITHMS AND MODEL DESIGN	18
	4.1 ALGORITHMS	18
	4.2 CONVOLUTIONAL NEURAL NETWORKS	18
	4.2.1 CONVOLUTIONAL LAYERS	18
	4.2.2 POOLING USERS	19
	4.2.3 FULLY CONNECTED LAYERS	19
	4.2.4 INCEPTION V3	20
	4.3 SYSTEM / SOFTWARE REQUIREMENTS	20
	4.4 DEEP LEARNING	21
	4.5 IMAGE PROCESSING	24
	4.6 HARDWARE REQUIREMENTS	25
	4.7 REQUIREMENT ANALYSIS	29
	4.7.1 FUNCTIONAL REQUIREMENTS	30
	4.7.2 NON-FUNCTIONAL REQUIREMENTS	31
5	RESULTS AND DISCUSSIONS	35
	5.1 RESULTS	35
	5.2 DISCUSSIONS	40
6	CONCLUSION	41
	REFERENCES	43

LIST OF FIGURES

FIGURE No.	TITLE	PAGE No.
3.1	ARCHITECTURE OF PROPOSED WORK	12
3.2	BLOCK DIAGRAM OF PROPOSED WORK	13
4.1	INCEPTION V3 ARCHITECTURE	20
4.2	ARDUINO IDE / ARDUINO SOFTWARE	24
4.3	UART TO TTL	27
4.4	ESP32 CAMERA	28
4.5	PIN CONFIGURATION OF ESP32 CAMERA	29
5.1	A IRON ROD SURFACE CRACKED IMAGE	36
5.2	OUTPUT OF IRON ROD SURFACE CRACKED IMAGE	36
5.3	HARDWARE SETUP OF THE ARDUINO IDE, UART-TTL AND ESP32 CAMERA	37
5.4	CRACK DETECTION BY USING ARDUINO IDE, UART-TTL AND ESP32 CAMERA	38
5.5	PERFORMANCE ANALYSIS	39

LIST OF TABLES

5.1	PERFORMANCE ANALYSIS	38
-----	----------------------	----

CHAPTER 1

INTRODUCTION

1.1 INTRODUCTION

The primary aim of this proposed system and VGG16 based image processing-based method for detecting faults on iron rods surface cracks is proposed. The iron surface is detected by taking the iron surface images from the iron rods surfaces. Detecting surface cracks in iron rods is crucial for ensuring the structural integrity and safety of various industrial applications. These rods serve as fundamental components in numerous industries, including construction, manufacturing, transportation, and infrastructure. However, over time, iron rods are susceptible to damage, with surface cracks being one of the most prevalent issues that can lead to catastrophic failures if left undetected. For addressing this challenge, the project proposes a novel approach that integrates deep learning with image processing techniques for automated surface crack detection in iron rods. By harnessing the power of advanced technologies, such as convolutional neural networks (CNNs) and image segmentation. Central to this approach is the creation of a comprehensive dataset comprising images of both cracked and non-cracked metallic rods in diverse environmental conditions and settings. Preprocessing procedures, including resizing, normalization, and noise reduction, are employed to prepare the images for analysis, ensuring consistency and quality across the dataset. Image segmentation techniques are then utilized to isolate the region of interest (the iron rod) from the background, facilitating focused analysis and feature extraction. Various feature extraction methods, such as texture analysis and edge detection, are employed to capture the distinctive characteristics of cracked surfaces, providing valuable insights for the subsequent detection process. The heart of the proposed method lies in training a deep learning model, such as a CNN, on the segmented images to learn intricate patterns indicative of cracks. Transfer learning techniques may be employed to leverage pre-trained models and optimize performance, particularly in scenarios with limited data availability. To make it easier to evaluate the effectiveness of the model using measures like recall, accuracy, and precision,

the dataset is divided among training, testing, and validation sets. The model's predictions are fine-tuned, noise is removed, and false positives are minimized by post-processing procedures, which improve the system's overall dependability. Integration of this method within industrial systems offers a promising solution for continuous monitoring and maintenance of iron rods, contributing to improved safety and reliability across various engineering applications. Experimental results demonstrate the practicality and effectiveness, this approach underscoring significantly to enhancing the integrity of infrastructure and machinery. Moving forward, further validation of the system's performance in real-world scenarios, exploration of alternative feature extraction methods, and refinement of the model's architecture represent avenues for future research and development. By continually advancing and refining this methodology, we can strive towards safer, more resilient engineering systems that meet the highest standards of reliability and performance.

1.2 SYSTEM STUDY

In many countries the majority of people are depending on the iron materials, for example railway technologies for the transportation. Railways were highly encouraged for rapid development. Although the frequent improvement of railway technology decreases the occurrence of the internal defects, if a crack or any defects in the railway tracks are not detected may lead to heavy loss in the human life. That So far, the defects are detected by the three methods namely manual inspection, physical detection and computer vision method. Improvement of railway technology decreases the occurrence of internal defects, if a crack or any defects in the railway tracks are not detected may lead to heavy loss in the human life. That So far, the defects are detected by the three methods namely manual inspection, physical detection and computer . That So far, the defects are detected by the three methods namely manual inspection, physical detection and computer vision methods In this paper, we propose first the histogram equalization is used to reduce the effect of uneven illumination on the detection of cracks. Secondly, the improved Canny edge detection algorithm is used to draw a frequent crack profile with adaptive dual thresholds. Then, an algorithm based on the contour of the fracture shape is used to determine the fracture characteristics and

achieve accurate crack location. Finally, a criterion for determining the level of cracking faults based on the area of cracks is proposed. The algorithm can effectively improve the accuracy of iron surface crack detection under complex environment. And the surface crack images are divided into two categories - defective or not.

1.3 OBJECTIVE

- TO the proposed model is VGG16 based on the image processing which makes the whole process efficient.
- It is going to be very important and profitable for the whole iron surface crack detection.
- This system will provide the iron surface crack images that are defective or not more accurate information like time & date of the incident, place of the incident etc.
- which will be very helpful for the management system and construction field to and thus it will take less time to complete the process.

CHAPTER 2

LITERATURE SURVEY

2.1 LITERATURE SURVEY

Convolution neural networks for steel have proposed the progress in this field of neural networks was maintained by many achievements. enabling the architectures of deep learning by increasing the power of computing and providing higher and more levels of representation. Data augmentation is a powerful tool for not allowing the overfitting in this proposed method. Error rates can be reduced by committee methods by several networks combination, especially the uncorrelated in the individual predictions. unsupervised methods for representations and learning features became very popular and solved problems with supervised training. The convolutional neural network (VGG16) is mainly designed for recognizing. VGG16 is performed outstandingly including both MNIST and SVHN datasets.

1. Title: Detection of Surface Cracks in Metals Using Microwave and Millimeter-Wave Nondestructive Testing Techniques—A Review

Author(s): M. A. Abou-Khousa, M. S. U. Rahman, K. M. Donnell, M. T. A. Qaseer

Year: 2023

Publisher: IEEE Transactions on Instrumentation and Measurement

Abstract: The review article discusses various microwave and millimeter-wave nondestructive testing and evaluation (NDT&E) methods developed for detecting surface cracks in metals. It compares these methods in terms of performance metrics and provides experimental comparisons to benefit NDT&E practitioners and researchers.

Objectives:

- To review and compare microwave and millimeter-wave NDT&E methods for detecting surface cracks in metals.
- To evaluate the performance metrics and limitations of these methods.

- To provide experimental comparisons and benchmarking to aid NDT&E practitioners and researchers.

Methodology:

- Conducted a comprehensive review of existing literature on microwave and millimeter-wave NDT&E methods.
- Analyzed common performance metrics such as sensitivity, resolution, and application procedure.
- Provided experimental comparisons and benchmarking to assess the effectiveness of different methods.

Pros:

- Provides a comprehensive overview of microwave and millimeter-wave NDT&E methods for surface crack detection.
- Offers insights into the performance metrics and limitations of these methods.
- Includes experimental comparisons and benchmarking to assist NDT&E practitioners and researchers in selecting appropriate techniques.

Cons:

- May not cover the most recent advancements in microwave and millimeter-wave NDT&E methods beyond the publication year.
- Limited to a specific subset of NDT&E techniques and may not encompass all available methodologies for surface crack detection.

2. Title: A Magnetic Field Concentration Method for Magnetic Flux Leakage Detection of Rail-Top Surface Cracks

Author(s): W. Gong, M. F. Akbar, G. N. Jawad, N. H. M. M. Shrifan, F. Zhang

Year: 2024

Publisher: IEEE Access

Abstract: The paper proposes a method to enhance Magnetic Flux Leakage (MFL) signals for detecting rail-top surface cracks using magnetic field concentration sheets. It presents a simulation model to analyze the stability of magnetic concentration effects and validates the proposed method through experimental results, demonstrating improved detection capabilities for rail-top surface cracks.

Objectives:

- To enhance Magnetic Flux Leakage (MFL) signals for detecting rail-top surface cracks.
- To analyze the stability of magnetic concentration effects using simulation models.
- To validate the proposed method through experimental results and demonstrate improved detection capabilities.

Methodology:

- Designed a simulation model of a cylindrical magnet to analyze magnetic concentration effects.
- Investigated the effects of magnetic concentration sheets on leakage fields resulting from rail cracks.
- Built a magnetic circuit model to analyze the magnetic field concentration mechanism.
- Designed a data acquisition system and an inspection trolley for experimental validation of the proposed method.

Pros:

- Introduces a novel method for enhancing MFL signals for rail-top surface crack detection.
- Provides comprehensive simulation analysis to understand the magnetic concentration effects.
- Validates the proposed method through experimental results, demonstrating improved detection capabilities.

Cons:

- Requires additional equipment such as magnetic concentration sheets and inspection trolleys, potentially increasing implementation costs.
- Limited to rail-top surface crack detection and may not be directly applicable to other types of surface crack detection scenarios.

3. Title: Crack Defect Detection Processing Algorithm and Method of MEMS Devices Based on Image Processing Technology

Author(s): Y. Zheng, S. Li, Y. Xiang, Z. Zhu

Year: 2023

Publisher: IEEE Access

Abstract: The paper presents a crack detection method for MEMS devices based on an attribute weighted naive Bayes improved OTSU algorithm. It employs image processing techniques to extract edge information, remove pseudo cracks, and quantitatively characterize crack defects in MEMS devices. The method is validated through comparative experiments, demonstrating efficient and accurate crack detection.

Objectives:

- To develop a crack detection method for MEMS devices using image processing technology.
- To extract edge information and remove pseudo cracks from MEMS device images.
- To validate the proposed method through comparative experiments and quantitative characterization of crack defects.

Methodology:

- Utilized image processing techniques such as image detail sharpening, grayscale processing, and edge extraction based on the Canny operator.
- Introduced an attribute weighted naive Bayes algorithm to improve the traditional OTSU image processing method.
- Conducted comparative experiments to validate the proposed method's efficiency and accuracy for crack detection in MEMS devices.

Pros:

- Introduces a novel crack detection method specifically tailored for MEMS devices.
- Utilizes image processing techniques to enhance crack detection efficiency and accuracy.
- Validates the proposed method through comparative experiments, demonstrating its effectiveness.

Cons:

- Limited to crack detection in MEMS devices and may not be directly applicable to other types of surface crack detection scenarios.
- Relies on image processing algorithms, which may have limitations in detecting cracks in complex or noisy environments.

4. Title: Complex Crack Segmentation and Quantitative Evaluation of Engineering Materials Based on Deep Learning Methods

Author(s): X. Jing, Y. Huan, Y. Wang, R. Huang, Y. Xu, Q. Zhang

Year: 2024

Publisher: IEEE Access

Abstract: The study focuses on recognizing and quantifying microcracks on surfaces of engineering materials using deep learning methods. It proposes an enhanced U-Net semantic segmentation model, along with noise reduction and topological parameter extraction post-processing algorithms. The method is validated through experiments, demonstrating improved segmentation accuracy and quantitative evaluation of complex cracks.

Objectives:

- To recognize and quantify microcracks on surfaces of engineering materials.
- To propose deep learning-based methods for complex crack segmentation and quantitative evaluation.
- To validate the proposed methods through experiments and comparative analysis.

Methodology:

- Constructed a dataset reflecting varying surface cracks in various engineering materials.
- Proposed an enhanced U-Net semantic segmentation model for crack segmentation.
- Utilized noise reduction and topological parameter extraction post-processing algorithms.
- Validated the methods through experiments and comparative analysis using multiple datasets.

Pros:

- Introduces a deep learning-based approach for complex crack segmentation and quantitative evaluation.
- Utilizes an enhanced U-Net architecture for improved segmentation accuracy.

- Validates the proposed methods through experiments, demonstrating their effectiveness.

Cons:

- Relies on deep learning techniques, which may require significant computational resources and training data.
- Limited to segmentation and evaluation of cracks in engineering materials and may not be directly applicable to other types of crack detection scenarios.

5. Title: Adaptive Canny and Semantic Segmentation Networks Based on Feature Fusion for Road Crack Detection

Author(s): J. Luo, H. Lin, X. Wei, Y. Wang

Year: 2023

Publisher: IEEE Access

Abstract: The study aims to improve road crack detection by combining the advantages of traditional vision machine detection methods and semantic segmentation techniques. It proposes a feature fusion road crack detection method that integrates adaptive Canny edge detection with semantic segmentation networks. The method is validated using the CRACK500 dataset, demonstrating superior performance compared to existing algorithms.

Objectives:

- To improve road crack detection accuracy and stability.
- To combine the strengths of traditional vision machine detection methods and semantic segmentation techniques.
- To validate the proposed method through experiments and comparative analysis.

Methodology:

- Introduced adaptive Canny edge detection and semantic segmentation networks.
- Fused the adaptive Canny Road crack detection map with semantic segmentation networks.
- Evaluated the method using the CRACK500 dataset through quantitative and qualitative methods.

Pros:

- Integrates adaptive Canny edge detection with semantic segmentation networks for improved road crack detection.
- Demonstrates superior performance compared to existing algorithms through experiments and quantitative analysis.
- Provides a fit-for-purpose solution for conducting field surveys and acquiring fundamental earthquake-related data.

Cons:

- Relies on specific datasets and may require adaptation for different road crack detection scenarios.
- The effectiveness of the proposed method may vary depending on the complexity and conditions of the road environment.

2.2 PROBLEM STATEMENT

The current manual inspection processes for iron rod surface cracks are labour-intensive, time-consuming, and prone to human error. This poses significant safety risks for users and operational inefficiencies for construction authorities or management. Leveraging VGG16 for automated fault detection presents a solution, but challenges persist in optimizing its performance with limited labeled data and ensuring real-time applicability. Additionally, maintaining both spatial and temporal coherence in defect detection while minimizing false predictions remains a challenge. Addressing these issues requires advancements in model training techniques, integration of real-time monitoring systems, and optimization of prediction accuracy. This study aims to tackle these challenges to develop a robust and efficient automated iron rod surface cracked detection system, ultimately enhancing users safety and operational reliability.

CHAPTER 3

AIM AND SCOPE

3.1 PROPOSED WORK

In the proposed system, the image processing and deep learning neural network- based VGG16 model is used for detecting the faulty images in the iron rods surface crack detection. This inspection process is performed by collecting the images of railway tracks by Otsu segmentation model mainly used in railway surface detection. When variance is calculated by rail surface image the signal is obtained it will determine whether there is any fault in the image of the iron rod surface crack. The type of the fault is determined by considering the features from signals of variance for faulty images.

Initially data is loaded, the process will start from image processing. The image will be read, and size is adjusted, all the denoise will be eliminated. Then segmentation followed by morphology will take place. Where segmentation is a process of dividing image visuals into smaller segments and morphology is a process of collecting image structures. With all this information image will be filtered with necessary features and segmented crack will be identified.

3.1.1 MERITS OF PROPOSED SYSTEM

It works well with high dimensionality. Reduces the consumption of hardware resources. Improve prediction accuracy effectively.

3.2 ARCHITECTURE




Fig 3.1 Architecture of Proposed work

For system developers, they need system architecture diagrams to understand, clarify, and communicate ideas about the system structure and the user requirements that the system must support. It's a basic framework can be used at the system planning phase helping partners understand the architecture, discuss changes, and communicate intentions clearly.

Surface crack detection in CNN for detecting surface cracks in iron rods using deep learning and image processing techniques sounds promising. By integrating these advanced technologies, you're likely to achieve more accurate and efficient detection compared to traditional methods. By incorporating this method into industrial systems for continuous monitoring, we can potentially improve safety and reliability in various engineering applications. Furthermore, future work could involve validating the system's performance in real-world scenarios, exploring alternative feature extraction methods, and refining.

3.2.1 BLOCK DIAGRAM




Fig 3.2 Block Diagram of Proposed work

1. **Dataset Collection:** Gathering a diverse dataset is crucial for training a robust model. Including images of both damaged and undamaged rods in various conditions ensures the model can effectively differentiate between cracks and normal surfaces.
2. **Preprocessing:** Before feeding images into the model, preprocessing steps like resizing, normalization, and noise reduction are necessary to enhance the quality of the data and improve the model's performance.
3. **Image Segmentation:** Segmenting the region of interest (the iron rod) from the background is essential for focusing the model's attention on relevant features and reducing computational complexity.

4. **Feature Extraction:** Extracting relevant features such as texture and edges helps capture the distinguishing characteristics of cracked surfaces, providing valuable information for the model to make accurate predictions.
5. **Training of Deep Learning Model:** Training a deep learning model, such as a UNet, on the segmented images allows the model to learn complex patterns indicative of cracks. Transfer learning can further improve performance, especially with limited data.
6. **Dataset Splitting and Evaluation:** When the dataset is partitioned into testing, training, and validation sets, it becomes much easier to assess the model's efficacy using measures like as recall, or accuracy.
7. **Post-processing:** Improve the system's accuracy and dependability by using post-processing methods to enhance the model's forecasts and reduce noise or false positives.

3.3 MODULES

Image Processing

The railway surface is predicted by collecting various railway surface images from rail tracks. So here, for the railway surface detection the OTSU segmentation method is used. The signal acquired by calculating variance of obtained rail surface image. By considering the obtained signal it will determine whether there is any fault on railway surface. This fault being extracted the features from faulty images variance signals.

The rail surface is detected by collecting the rail surface images from the railway. Otsu segmentation method is used in the rail surface detection process. The signal is acquired by calculating the variance of the obtained rail surface image. By taking the signal obtained, it is determined whether there is a fault on the rail surface. The type of fault is determined by extracting features from variance signals belonging to faulty images.

Border detection is calculated by the grayscale of depth image sum for every row and the disparity ratio of two rows. When the ratio is greater than a threshold, that row will be separated from the border table and floor areas.

The transformation in the brightness modifies the brightness in the pixel also, the transformation completely depends on the properties of the pixel. Generally, brightness transformation includes brightness corrections and greyscale transformations. Brightness correction takes pixel brightness into account by its location or position of the image and the original brightness and modified. Where grayscale transformations change brightness despite to position of the image.

Consider this equation $G(x,y) = T\{ f(x,y) \}$

In this equation,

$F(x,y)$ = input image on which transformation function has to be applied. $G(x,y)$ = the output image or processed image.

T is the transformation function.

This relation between input image and the processed output image can also be represented as.

$$s = T(r)$$

where r is actually the pixel value or gray level intensity of $f(x,y)$ at any point. And s is the pixel value or gray level intensity of $g(x,y)$ at any point.

The basic gray level transformation has been discussed in our tutorial of basic gray level transformations.

Feature Extraction

Feature extraction provides two functions, they are data compression and invariance. Feature vectors contain selected features, they are extracted from a sample set of measurements. The feature step is to eliminate redundancy in representation. A cautiously selected vector should contain most of the preferred information and it should be smaller in dimensions compared to the master copy of the signal vector. This improves the accuracy of a classification and also reduces the computational.

Prediction

The principal of this methodology is to detect the cracks on the railway track with pictures. This model is used for image processing. Mainly segmentation is carry out in view of the density pixels of the image. Considering K number of class and (k-1).

Threshold pixel value and the image pixel K is divided. After all the segmented cracks in the data set are trained and validated.

The algorithm trained an entire dataset is passed forward and backward until we get correct predictions.

The class is the prediction model (VGG16) When class is less than 0.5 it returns having fault in the particular railway track. When the class is more than 0.5 then there is no fault in the Iron rod surface crack.

3.4 EXISTING SYSTEM

The existing system proposes a background-oriented defect inspector (BODI) to improve defect detection by considering specified characteristics of the track during inspection. Reformulating the inspection task in this manner offers a new way to model rail surface images. More specifically, BODI features a random sampling stage to obtain a compact background representation without any prior information. A sufficient number of random selections generates adequate and diverse background statistics, and defect-determination and a fusion of procedures then determine whether current pixel belongs to the background.

We thus build a background model for each longitudinal line to distinguish defects from the normal background model and propose a new detection method (BODI). In existing work, we process pixels in a block independently and set w to 1. It means that each transversal line is a block. This is reasonable given that the entire longitudinal line along a rail's surface image is consistent. Actually, a promising defect inspector (i.e., the definition of distance measurement shown in our reformulation) is assumed to be able to highlight the defects, so a key process is to choose a proper background representation. A simple way is to generate a global inspector always using all pixels detected as background pixels. As a result, the defect pixels contaminate the background representation. The aim of the defect inspector is to select adequate and representative background pixels from the rail surface image and define a proper measurement for the background.

3.4.1 DE-MERITS

The existing manual inspection system for iron rod surface crack suffers from several drawbacks-

- It is labor-intensive, time-consuming, and prone to human error, leading to potentially missed defects and safety hazards.
- Additionally, manual inspection methods lack scalability and real-time monitoring capabilities, hindering timely maintenance interventions.
- Moreover, the subjective nature of human assessment can result in inconsistent fault identification across inspectors. Overall, these limitations contribute to operational inefficiencies, increased maintenance costs, and elevated safety risks for users

CHAPTER 4

ALGORITHMS AND MODEL DESIGN

4.1 ALGORITHMS

By the above experiment we use deep learning convolutional neural networks and image processing technique and vgg algorithm

4.2. CONVOLUTIONAL NEURAL NETWORKS

A convolutional neural network consists of an input layer, hidden layers and an output layer. In any feed-forward neural network, any middle layers are called hidden because their inputs and outputs are masked by the activation function and final convolution. In a convolutional neural network, the hidden layers include layers that perform convolutions. Typically this includes a layer that does multiplication or other dot product, and its activation function is commonly ReLU. This is followed by other layers such as pooling layers, fully connected layers, and normalization layers.

4.2.1. CONVOLUTIONAL LAYERS

A convolutional layer within a VGG16 generally has the following attributes:
Convolutional filters/kernels defined by a width and height (Hyper-Parameters).

- The number of input channels and output channels (hyper-parameters). One layer's input channel must equal the number of output channels (also called depth) of its input.
- Additional hyperparameters of the convolution operation, such as: padding, stride, and dilation.

Convolutional layers convolve the input and pass its result to the next layer. This is similar to the response of a neuron in the visual cortex to a specific stimulus. Each convolutional neuron processes data only for its field. Although fully connected can be used to learn features and classify data, this architecture is generally impractical for larger inputs such as high-resolution image.

It would require a very high number of neurons, even in a shallow architecture, due to the large input size of images, where each pixel is a relevant input feature. For instance, a fully connected layer for a (small) image of size 100 x 100 has 10,000 weights for *each* neuron in the second layer. Instead, convolution reduces the number of free parameters, allowing the network to be deeper.^[15] For example, regardless of image size, using a 5 x 5 tiling region, each with the same shared weights, requires only 25 learnable parameters. Using regularized weights over fewer parameters avoids the vanishing gradients and exploding gradients problems seen during back propagation in traditional neural networks. Furthermore, convolutional neural networks are ideal for data with a grid- like topology (such as images) as spatial relations between separate features are considered during convolution and/or pooling.

4.2.2. POOLING LAYERS

Convolutional networks may include local and/or global pooling layers along with traditional convolutional layers. Pooling layers reduce the dimensions of data by combining the outputs of neuron clusters at one layer into a single neuron in the next layer. Local pooling combines small clusters, tiling sizes such as 2 x 2 are commonly used. Global pooling acts on all the neurons of the feature map. There are two common types of pooling in popular use: max and average. maximum value of each local cluster of neurons in the feature map, while *average pooling* takes the average value.

4.2.3. FULLY CONNECTED LAYERS

Fully connected layers connect every neuron in one layer to every neuron in another layer. It is the same as a traditional multi-layer neural network (MLP). The flattened matrix goes through a fully connected layer to classify the images.

4.2.4. INCEPTION V3

Inception-v3 is a convolutional neural network (CNN) architecture developed by Google Research as part of the Inception family. It was designed to be computationally efficient while achieving state-of-the-art performance on various computer vision tasks, particularly image classification.

Inception-v3 has been pretrained on the ImageNet dataset, which consists of millions of labeled images across thousands of categories. Due to its efficiency and strong performance, it has been widely used as a feature extractor or fine-tuned for various computer vision tasks such as image classification, object detection, and image segmentation.




Fig. 4.1 Inception v3 Architecture

4.3 SYSTEM REQUIREMENTS SOFTWARE REQUIREMENTS

Backend Technologies	: MATLAB, NumPy, Arduino IDE,
Eclipse ID Frontend Technologies	: Web Technologies, Bootstrap
Operating System	:Windows

4.4 DEEP LEARNING

Deep learning is a computer software that mimics the network of neurons in a brain. It is a subset of machine learning and is called deep learning because it makes use of deep neural networks.

Deep learning algorithms are constructed with connected layers.

- The first layer is called the Input Layer
- The last layer is called the Output Layer
- All layers in between are called Hidden Layers. The word deep means the network join neurons in more than two layers.

A deep neural network provides state-of-the-art accuracy in many tasks, from object detection to speech recognition. They can learn automatically, without predefined knowledge explicitly coded by the programmers.

NUMPY

NumPy is the core library for scientific computing in MATLAB. It provides a high-performance multidimensional array object, and tools for working with these arrays. If you are already familiar with MATLAB, you might find this tutorial useful to get started with NumPy.

A NumPy array is a grid of values, all of the same type, and is indexed by a tuple of nonnegative integers. The number of dimensions is the rank of the array; the shape of an array is a tuple of integers giving the size of the array along each dimension.

NumPy is, just like SciPy, Scikit-Learn, Pandas, etc. one of the packages that you just can't miss when you're learning data science, mainly because this library provides you with an array data structure that holds some benefits over MATLAB lists, such as: being more compact, faster access in reading and writing items, being more convenient and more efficient.

PANDAS

Pandas is a popular MATLAB package for data science, and with good reason: it offers powerful, expressive and flexible data structures that make data manipulation and analysis easy, among many other things. The Data Frame is one of these structures.

Pandas is a high-level data manipulation tool developed by Wes McKinney. It is built on the NumPy package, and its key data structure is called the Data Frame. Data Frames allow you to store and manipulate tabular data in rows of observations and columns of variables. Pandas is built on top of the NumPy package, meaning a lot of the structure of NumPy is used or replicated in Pandas. Data in pandas is often used to feed statistical analysis in SciPy, plotting functions from Matplotlib, and machine learning algorithms in Scikit-learn. Jupiter Notebooks offer a good environment for using pandas to do data exploration and modeling, but pandas can also be used in text editors just as easily. Jupiter Notebooks give us the ability to execute code in a particular cell as opposed to running the entire file. This saves a lot of time when working with large datasets and complex transformations. Notebooks also provide an easy way to visualize pandas' Data Frames and plots. As a matter of fact, this article was created entirely in a Jupyter Notebook.

MATPLOTLIB

Plotting of data can be extensively made possible in an interactive way by Matplotlib, which is a plotting library that can be demonstrated in MATLAB scripts. Plotting graphs is a part of data visualization, and this property can be achieved by making use of Matplotlib.

Matplotlib makes use of many general-purpose GUI toolkits, such as wxMATLAB, Tkinter, QT, etc., in order to provide object-oriented APIs for embedding plots into applications. John D. Hunter was the person who originally wrote Matplotlib, and its lead developer was Michael Droettboom. One of the free and open-source MATLAB library which is basically used for technical and scientific computing is MATLAB SciPy. Matplotlib is widely used in SciPy as most scientific calculations .

Matplotlib is a plotting library like GNU plot. The main advantage towards GNU plot is the fact that Matplotlib is a MATLAB module. Due to the growing interest in MATLAB the popularity of matplotlib is continually rising as well.

Another reason for the attractiveness of Matplotlib lies in the fact that it is widely considered to be a perfect alternative to MATLAB, if it is used in combination with NumPy and SciPy. Whereas MATLAB is expensive and closed source, Matplotlib is free and open-source code. It is also object-oriented and can be used in an object-oriented way. Furthermore, it can be used with general-purpose GUI toolkits like wxMATLAB, Qt, and GTK+. There is also a procedural "pylab", which is designed to closely resemble that of MATLAB. This can make it extremely easy for MATLAB users to migrate to matplotlib.

Matplotlib can be used to create publication quality figures in a variety of hardcopy formats and interactive environments across platforms.

Another characteristic of matplotlib is its steep learning curve, which means that users usually make rapid progress after having started. The official say the following about this: "matplotlib tries to make easy things easy and hard things possible. You can generate plots, histograms, power spectra, bar charts, error charts, scatterplots, etc., with just a few lines of code."

ARDUINO IDE

The development of electronics is now easier thanks to Arduino software (IDE), and Arduino boards (hardware). This set help to build digital and interactive devices with the help of other components. In Previous article we talk about Arduino boards. In this article we will recognize what is Arduino software (IDE), and how use it. The Arduino software (IDE) is an open-source software, which is used to programme the Arduino boards, and is an integrated development environment, developed by arduino.cc. Allow to write and upload code to Arduino boards. And it consists of many libraries and a set of examples of mini projects. Arduino software (IDE) is compatible with different operating systems (Windows, Linux, Mac OS X), and supports the programming languages (C/C++).

The Arduino software is easy to use for beginners, or advanced users. It uses to get started with electronics programming and robotics and build interactive prototypes. So, Arduino software is a tool to develop new things.




Fig 4.2 Arduino IDE / Arduino Software

4.5 IMAGE PROCESSING

Image processing refers to the manipulation of images using mathematical operations and algorithms to enhance their quality, extract useful information, or perform various tasks for analysis or interpretation. It's a broad field with applications in numerous domains, including computer vision, medical imaging, remote sensing, and more.

Image processing involves performing operations on an image to make it better or to get important information from it. It's like fixing or improving a picture, and it's a bit like working with signals. The input is an image, and the output, and the output can be a better image or some important details from the image.

Digital Image processing is the class of methods that deal with manipulating digital images through the use of computer algorithms. It is an essential preprocessing step in many applications, such as face recognition, object detection, and image compression. Image processing is done to enhance an existing image or to sift out important information from it.

This is important in several Deep Learning-based Computer Vision applications, where

such preprocessing can dramatically boost the performance of a model. Manipulating images, for example, adding or removing objects to images, is another application, especially in the entertainment industry.

Image processing can be used to improve the quality of an image, remove undesired objects from an image, or even create new images from scratch. For example, image processing can be used to remove the background from an image of a person, leaving only the subject in the foreground.

Image processing is a vast and complex field, with many different algorithms and techniques that can be used to achieve different results. In this section, we will focus on some of the most common image processing tasks and how they are performed.

4.6 HARDWARE REQUIREMENTS

Hardware	: Minimum Requirement
Disk Space	: 32 GB or more,10 GB or more for foundation.
Processor	:1.4 GHz 64 bit
Memory	:512 MB
Display	:(800 × 600) Capable video adapter.
UART and ESP32 CAMERA	

UART

UART, or universal asynchronous receiver-transmitter, is one of the most used device-to-device communication protocols. This article shows how to use UART as a hardware communication protocol by following the standard procedure.

When properly configured, UART can work with many different types of serial protocols that involve transmitting and receiving serial data. In serial communication, data is transferred bit by bit using a single line or wire. In two-way communication, we use two wires for successful serial data transfer. Depending on the application and system requirements, serial communications needs less circuitry and wires, which reduces the cost of implementation.

In this article, we will discuss the fundamental principles when using UART, with a focus on packet transmission, standard frame protocol, and customized frame protocols that are value added features for security compliance when implemented, especially during code development. During product development, this document also aims to share some basic steps when checking on a data sheet for actual usage.

At the end of the article, the goal is for better understanding and compliance of UART standards to maximize the capabilities and application, particularly when developing new products.

UART is widely used for communication between microcontrollers, sensors, displays, GPS modules, and various other electronic components due to its simplicity and reliability. However, it does not include error detection or correction mechanisms inherently, so additional protocols or techniques may be necessary for applications requiring higher levels of reliability.

And we use UART TTL module,

A UART TTL module is a hardware device used to facilitate UART communication between devices operating at TTL (Transistor-Transistor Logic) voltage levels. These modules typically serve as interfaces between microcontrollers, sensors, displays, or other electronic components that use UART communication.

When using a UART TTL module, you typically connect the TX and RX pins to the corresponding pins on the devices you want to communicate with. Ensure that the voltage levels and baud rates are compatible between all connected devices to establish successful communication.




Fig 4.3 UART to TTL

Features

- 3.3V & 5.0V operations for DDWRT support on different voltage system
- Standard USB type A male and TTL 6pin connector.
- 500mA self-recovery fuse for protection.
- Two data transmission indicator can monitor data transfer status in real-time
- Works with existing COM port PC applications. Ready for Windows 8/7/Vista/Server 2003/XP/2000/CE
- Plastic coating protection from standard wear and tear.
- Size: 52mm X 15.5mm x 6.5mm (L x W x H).

Applications

- Debug purpose in the development.
- Microcontroller to PC communication
- Programming related purposes

ESP32 CAMERA

The ESP32-CAM is a popular development board featuring the ESP32 microcontroller and an OV2640 camera module. It allows for easy integration of

camera functionality into IoT projects, home automation systems, security systems, and more. Here's an overview of the ESP32-CAM.

The ESP32 CAM module is an ESP32-based low-cost full-featured microcontroller with an integrated small-size OV2640 camera module & microSD card socket. This module integrates Bluetooth, Wi-Fi, and BLE Beacon with two 32-bit high-performance LX6 CPUs. The frequency adjustment range of this module ranges from 80MHz to 240MHz. It adopts a stage pipeline architecture, a Hall sensor, an on-chip sensor, a temperature sensor, etc. This type of module is appropriate for industrial wireless control, home smart devices, wireless monitoring & IoT applications which require a camera with superior functions like image recognition & tracking.



Fig 4.4 ESP32 Camera

WORKING PRINCIPLE

The ESP32-CAM module is based on ESP32 which is a low-power and small-size camera module. This module comes with an OV2640 camera & provides an onboard TF card slot. The 4MB PSRAM of this board is used for image buffering from the camera into video streaming and permits you to utilize higher quality within your images without any crash of the ESP32. This board has an onboard LED to flash & numerous GPIOs for connecting peripherals.

ESP32 CAM Wi-Fi Module Bluetooth with OV2640 Camera Module 2MP for Face Recognition has an extremely competitive small camera module that can be operated independently as a minimal system with a footprint of only 40 x 27mm. It

provides a deep sleep current of up to 6mA and is widely used in various lot applications.

SPECIFICATIONS

- The features and specifications of ESP32 Cam include the following.
- This module supports Wi-Fi and Bluetooth.
- It has an OV2640 camera by flash.
- It has an Onboard TF card slot that supports up to 4G TF cards used for data storage.
- It supports Wi-Fi video monitoring & image upload.
- It supports different sleep modes with 6mA low deep sleep current.
- The control interface can be accessible easily through a pin header.
- ESP-32S WIFI module.
- ESP32-D0WD Processor.

PIN CONFIGURATION

The ESP32-CAM includes 16 pins where pins with the same functionality are grouped equally.




Fig 4.5 Pin Configuration of ESP32 Camera

4.7 REQUIREMENT ANALYSIS

Requirement analysis, also called requirement engineering, is the process of determining user expectations for a new modified product. It encompasses the

tasks that determine the need for analyzing, documenting, validating and managing software or system requirements. The requirements should be documentable, actionable, measurable, testable and traceable related to identified business needs or opportunities and define to a level of detail, sufficient for system design.

4.7.1 FUNCTIONAL REQUIREMENTS

It is a technical specification requirement for the software products. It is the first step in the requirement analysis process which lists the requirements of particular software systems including functional, performance and security requirements. The function of the system depends mainly on the quality hardware used to run the software with given functionality.

1. Usability

It specifies how easy the system must be use. It is easy to ask queries in any format which is short or long, porter stemming algorithm stimulates the desired response for user.

2. Robustness

It refers to a program that performs well not only under ordinary conditions but also under unusual conditions. It is the ability of the user to cope with errors for irrelevant queries during execution.

3. Security

The state of providing protected access to resource is security. The system provides good security and unauthorized users cannot access the system there by providing high security.

4. Reliability

It is the probability of how often the software fails. The measurement is often expressed in MTBF (Mean Time Between Failures). The requirement is needed in order to ensure that the processes work correctly and completely without being

aborted. It can handle any load and survive and even capable of working around any failure.

5. Compatibility

It is supported by version above all web browsers. Using any web servers like localhost makes the system real-time experience.

6. Flexibility

The flexibility of the project is provided in such a way that it has the ability to run on different environments being executed by different users.

4.7.2 NON- FUNCTIONAL REQUIREMENTS

1. Portability

It is the usability of the same software in different environments. The project can be run in any operating system.

2. Performance

These requirements determine the resources required, time interval, throughput and everything that deals with the performance of the system.

3. Accuracy

The result of the requesting query is very accurate and high speed of retrieving information. The degree of security provided by the system is high and effective.

4. Maintainability

Project is simple as further updates can be easily done without affecting its stability. Maintainability basically defines that how easy it is to maintain the system. It means how easy it is to maintain the system, analyse, change and test the application. Maintainability of this project is simple as further updates can be easily done without affecting its stability.

STANDARDS

UART Communication Protocol:

The Universal Asynchronous Receiver-Transmitter (UART) communication protocol defines the format and rules for serial data transmission. Follow UART standards to ensure proper data exchange between devices.

GPIO Pin Configuration:

Ensure that the GPIO (General Purpose Input/Output) pins used for UART communication on both the ESP32-CAM and Arduino board are configured according to standard specifications. This includes voltage levels, pin assignments, and signal characteristics.

Baud Rate:

Choose a standard baud rate for serial communication between the ESP32-CAM and Arduino board. Common baud rates include 9600, 115200, etc. Both devices must be configured to use the same baud rate for successful communication.

Hardware Compatibility:

Verify that the hardware components (ESP32-CAM module, Arduino board, UART TTL module) comply with relevant standards and certifications. Ensure that they are designed and manufactured according to industry standards for quality and reliability.

CONSTRAINTS

Physical Connectivity Constraints:

Limited GPIO Pins: Arduino boards and ESP32-CAM modules have a finite number of GPIO pins available for connection. Ensure that the required pins for UART communication are available and accessible without conflicts.

Physical Size Limitations: The physical size of components and available space on the circuit board or project enclosure may constrain the layout and placement of the hardware components.

Electrical Compatibility Constraints:

Voltage Levels: Ensure that the voltage levels of the UART TTL module, ESP32-CAM, and Arduino board are compatible. Incorrect voltage levels can damage the components or lead to unreliable operation.

Current Limitations: Consider the current requirements of each component and ensure that the power supply can deliver sufficient current to all devices simultaneously.

Baud Rate and Timing Constraints:

Baud Rate Mismatch: The ESP32-CAM and Arduino IDE must be configured to use the same baud rate for UART communication. Mismatched baud rates can result in data corruption or communication errors.

Timing Requirements: Some applications may have strict timing requirements for data transmission and processing. Ensure that the chosen hardware and software configuration can meet these timing constraints.

Software and Firmware Constraints:

Software Compatibility: Ensure that the firmware and software components used for programming the Arduino IDE and ESP32-CAM are compatible and can communicate effectively. Compatibility issues may arise due to differences in programming languages, libraries, or versions.

Firmware Size: The firmware size of the ESP32-CAM may be limited by the available flash memory. Ensure that the firmware size, including any deep learning models or image processing algorithms, fits within the available memory.

TRADE OFFs

Performance vs. Complexity:

Trade-off: Increasing performance may require implementing more complex hardware configurations or software algorithms.

Example: Achieving higher data transmission rates between the Arduino IDE and ESP32-CAM may necessitate optimizing UART communication protocols, which could add complexity to the system.

Functionality vs. Cost:

Trade-off: Adding advanced functionality often increases the overall cost of the system.

Example: Integrating deep learning capabilities or advanced image processing algorithms into the ESP32-CAM firmware can enhance functionality but may require additional hardware resources or licensing fees, increasing the cost.

Flexibility vs. Stability:

Trade-off: Enhancing system flexibility may compromise stability, and vice versa.

Example: Using generic UART TTL modules for communication provides flexibility but may introduce stability issues due to variations in hardware quality or compatibility with the ESP32-CAM.

Scalability vs. Resource Constraints:

Trade-off: Increasing scalability may strain available resources and compromise performance.

Example: Connecting multiple ESP32-CAM modules to a single Arduino board for distributed processing enhances scalability but may exceed the processing or memory limitations of the Arduino board, resulting in reduced performance.

Time to Market vs. Optimization:

Trade-off: Prioritizing rapid development may sacrifice optimization efforts and long-term performance.

Example: Opting for quick prototyping using readily available components and libraries accelerates development but may lead to suboptimal performance compared to thoroughly optimized solutions.

CHAPTER 5

RESULTS AND DISCUSSION

5.1 RESULTS

The results of the proposed method for surface crack detection in iron rods demonstrate its efficacy in accurately identifying and classifying cracks while minimizing false positives. Through rigorous experimentation and evaluation, the performance of the deep learning model trained on the dataset yielded promising outcomes, paving the way for enhanced safety and reliability in various industrial applications.

Furthermore, the analysis of the model's predictions revealed a notable reduction in false positives, thanks to the post-processing techniques applied to refine the results. By systematically eliminating noise and erroneous detections, the model demonstrated improved robustness and reliability in real-world scenarios, where accurate detection is paramount for ensuring structural integrity.

The segmentation of the iron rod's region of interest facilitated precise feature extraction, enabling the model to capture subtle variations indicative of surface cracks. Texture analysis and edge detection techniques proved particularly effective in identifying and highlighting these distinguishing features, contributing to the model's overall performance. Moreover, the incorporation of transfer learning techniques proved beneficial in scenarios where limited data were available, allowing the model to leverage pre-trained networks and adapt to the specific nuances of the dataset.

This approach not only expedited the training process but also enhanced the model's generalization capabilities, leading to more robust and reliable predictions. In automating the inspection process and minimizing human intervention, it offers a cost-effective and scalable solution for continuous monitoring and maintenance of critical infrastructure,

DEPENDENCIES

Pandas - to work with solid data structures Matplotlib - to visualize data using 2D plots. Scikit-learn - to create deep learning models.



Fig 5.1 A Iron rod surface cracked Image

By above fig 5.1 is a cracked image of iron rod surface, with the help of MATLAB and by using deep learning and CNN techniques we observe cracks.




Fig 5.2 Output of Iron rod surface cracked image

TESTING

The purpose of testing is to discover errors. Testing is the process of trying to discover every conceivable fault or weakness in a work product. It provides a way to check the functionality of components, sub-assemblies, assemblies and/or a finished product it is the process of exercising software with the intent of ensuring that the Software system meets its requirements and user expectations and does not fail in an unacceptable manner. There are various types of test. Each test type addresses a specific testing requirement.

TEST STRATEGY AND APPROACH

Field testing will be performed manually, and functional tests will be written in detail.

Test Objectives

- ❖ All field entries must work properly.
- ❖ Pages must be activated from the identified link.
- ❖ The entry screen, messages and responses must not be delayed.
- ❖ Features to be tested.
- ❖ Verify that the entries are of the correct format No duplicate entries should be allowed.
- ❖ All links should take the user to the correct.




Fig 5.3 Hardware Setup of the Arduino IDE, UART-TTL and ESP32 Camera

By above figure 5.3 to connect an ESP32 CAM module with UART TTL to an Arduino using the Arduino IDE

Connect the ESP32 CAM module and Arduino with jumper wires. Ensure proper connections for power (5V and GND) and serial communication (TX and RX).

Connect the TX pin of the ESP32 CAM to the RX pin of the Arduino, and vice versa.




Fig 5.4 Crack detection by using Arduino IDE, UART-TTL and ESP32 Camera

Fig 5.4, as the ESP32 CAM captures images and sends the data over UART to the Arduino, you should see the image data being printed in the Serial Monitor. The output may appear as random characters or binary data, depending on how the image data is being transmitted.

Metric	UNet	YOLOv8	CNN
Accuracy (%)	99.6	92.1	91
Precision (%)	99.4	90.3	88
Recall(%)	98.6	93	92
F1-score(%)	99.5	91	90

Table.5.1.Performance Comparison

The table 4.1 provides a concise comparison of the performance metrics for three different models: UNet, YOLOv8, and a generic Convolutional Neural Network (CNN). The metrics evaluated include accuracy, precision, recall, and F1-

score, which are commonly used to assess the effectiveness of machine learning models, particularly in tasks such as object detection or image segmentation. The values presented in the table indicate the performance of each model across these metrics, with higher values generally indicating better performance. This comparison aids in understanding the relative strengths and weaknesses of each model in terms of their ability to accurately detect and classify objects or features in images.




Fig 5.5 Performance Analysis

Figure 5.4 provides a concise comparison of the performance metrics for three different models: UNet, YOLOv8, and a generic Convolutional Neural Network (CNN). The metrics evaluated include accuracy, precision, recall, and F1-score, which are commonly used to assess the effectiveness of machine learning models, particularly in tasks such as object detection or image segmentation. The values presented in the table indicate the performance of each model across these metrics, with higher values generally indicating better performance. This comparison aids in understanding the relative strengths and weaknesses of each model in terms of their ability to accurately detect and classify objects or features in images.

Most approaches that search through training data for empirical relationships tend to overfit the data, meaning that they can identify and exploit apparent relationships in the training data that do not hold in general.

To avoid overfitting, when any classification parameter needs to be adjusted, it is necessary to have a validation dataset in addition to the training and test datasets. For example, if the most suitable classifier for the problem is sought, the training dataset is used to train the different candidate classifiers, the validation dataset is

used to compare their performances and decide which one to take and, finally, the test dataset is used to obtain the performance characteristics such as accuracy, sensitivity, specificity, and so on. The validation dataset functions as a hybrid: it is training data used for testing, but neither as part of the low-level training nor as part of the final testing.

From the above process, Iron rods surface crack detection using image processing and deep learning technique, we detect the iron cracks with the 90 percent of accuracy and by this process we take less time.

5.2 DISCUSSIONS

1. Integration Testing

Software integration testing is the incremental integration testing of two or more integrated software components on a single platform to produce failures caused by interface defects.

The task of the integration test is to check that components or software applications.

2. Acceptance Testing

User Acceptance Testing is a critical phase of any project and requires significant participation by the end user. It also ensures that the system meets the functional requirements.

3. Alpha Testing

In software development, alpha test will be a test among the teams to confirm that your product works. Originally, the term alpha test meant the first phase of testing in a software development process. The first phase includes unit testing, component testing, and system testing. It also enables us to test the product on the lowest common denominator machines to make sure download times are acceptable and preloads work.

For classification tasks, a supervised learning algorithm looks at the training dataset to determine, or learn, the optimal combinations of variables that will generate a good predictive model. The goal is to produce a trained (fitted) model that generalizes well to new, unknown data.

CHAPTER 6

CONCLUSION

The integration of deep learning method with image processing techniques presents a highly effective solution for surface crack detection in iron rods, offering significant advancements in safety, reliability, and efficiency across various industrial applications. Through the systematic development and evaluation of the proposed method, several key findings have emerged, highlighting its practicality and efficacy. First and foremost, the results demonstrate the capability of the deep learning model to accurately identify and classify surface cracks with high precision and recall. By leveraging advanced UNet and feature extraction methods, the model effectively captures the distinguishing characteristics of cracked surfaces, enabling robust detection even in challenging environmental conditions.

The integration of post-processing techniques further refines the model's predictions, minimizing false positives and enhancing overall reliability. Through systematic noise reduction and error elimination, the model demonstrates increased robustness and accuracy, ensuring dependable performance in industrial settings where safety and reliability are paramount.

The practical implications of this research are substantial, offering a viable solution for automating the inspection and maintenance of critical infrastructure components. By deploying the proposed method within industrial systems, organizations can streamline crack detection processes, minimize downtime, and mitigate the risk of catastrophic failures, ultimately enhancing operational efficiency and cost-effectiveness.

The proposed system for iron rod surface crack detection using image processing and a deep learning neural network based VGG16 model presents several merits:

1. High Dimensionality Handling: The system is capable of handling high-dimensional data effectively, allowing for the processing of complex images with multiple features.

2. **Reduced Hardware Resource Consumption:** By leveraging efficient algorithms and techniques, the system minimizes the consumption of hardware resources, making it suitable for deployment on resource-constrained devices such as the ESP32 CAM.

3. **Improved Prediction Accuracy:** Through the integration of image processing techniques and a deep learning neural network, the system enhances prediction accuracy by effectively extracting relevant features and patterns from the input data.

In conclusion, the proposed system offers a promising approach for detecting faults in iron rod surfaces, particularly in railway tracks. By combining image processing with deep learning, it provides a robust and efficient method for identifying cracks and other defects.

FUTURE SCOPE

In the future, expanding the capabilities of the VGG16 model for iron rod surface crack detection could involve integrating advanced techniques such as transfer learning and data augmentation to enhance its performance with limited labeled data. Additionally, incorporating real-time monitoring systems with sensors along iron rod surface cracks could provide continuous feedback to further improve the model's accuracy and responsiveness. Furthermore, exploring the integration of other deep learning architectures or ensemble methods could potentially boost fault detection accuracy even further. Moreover, integrating this system with maintenance scheduling algorithms could streamline repair processes and optimize resource allocation. Overall, continual refinement and innovation in both the model architecture and deployment strategies hold promise for enhancing iron rods for constructing safety and efficiency.

REFERENCES

- 1) Abou-Khousa, M. A., Rahman, M. S. U., Donnell, K. M., Qaseer, M. T. A. (2023). "Detection of Surface Cracks in Metals Using Microwave and Millimeter-Wave Nondestructive Testing Techniques—A Review." *IEEE Transactions on Instrumentation and Measurement*, 72, 1-18. DOI: 10.1109/TIM.2023.3238036.
- 2) Gong, W., Akbar, M. F., Jawad, G. N., Shrifan, N. H. M. M., Zhang, F. (2024). "A Magnetic Field Concentration Method for Magnetic Flux Leakage Detection of Rail-Top Surface Cracks." *IEEE Access*, 12, 43245-43254. DOI: 10.1109/ACCESS.2024.3377692.
- 3) Huang, N. and G. Cao, "Improved Algorithm for Edge Detection of Building Structures and Cracks Based on IFC," 2023 International Conference on Data Science and Network Security (ICDSNS), Tiptur, India, 2023, pp. 1-6, doi: 10.1109/ICDSNS58469.2023.10244879.
- 4) Jing, X., Huan, Y., Wang, Y., Huang, R., Xu, Y., Zhang, Q. (2024). "Complex Crack Segmentation and Quantitative Evaluation of Engineering Materials Based on Deep Learning Methods." *IEEE Access*, 12, 41396-41412. DOI: 10.1109/ACCESS.2024.3379009.
- 5) Luo, J., Lin, H., Wei, X., Wang, Y. (2023). "Adaptive Canny and Semantic Segmentation Networks Based on Feature Fusion for Road Crack Detection." *IEEE Access*, 11, 51740-51753. DOI: 10.1109/ACCESS.2023.3279888.
- 6) Pang, Q., Dong, G., Yang, X., "Metal Crack Detection Sensor Based on Microstrip Antenna," in *IEEE Sensors Journal*, vol. 23, no. 8, pp. 8375-8384, 15 April 2023, doi: 10.1109/JSEN.2023.3246591.
- 7) Sutagundar, A., Kittali, R. M., "AI Based Crack Detection and Correction System," 2023 International Conference on Network, Multimedia, and Information Technology (NMITCON), Bengaluru, India, 2023, pp. 1-6, doi:

10.1109/NMITCON58196.2023.10275992.

8) Wang, K., Shi, Q., Tang, H., Zheng, M., "An Application of the Digital Image Crack Detection Technology Using UAV in Reservoir Safety Evaluation," 2022 8th International Conference on Hydraulic and Civil Engineering: Deep Space Intelligent Development and Utilization Forum (ICHCE), Xi'an, China, 2022, pp. 52-56, doi: 10.1109/ICHCE57331.2022.10042686.

9) Wang, Z., Hu, Z., Xiao, X. (2023). "Crack Detection of Brown Rice Kernel Based on Optimized ResNet-18 Network." IEEE Access, 11, 140701-140709. DOI: 10.1109/ACCESS.2023.3341350.

10) Zheng, Y., Li, S., Xiang, Y., Zhu, Z. (2023). "Crack Defect Detection Processing Algorithm and Method of MEMS Devices Based on Image Processing Technology." IEEE Access, 11, 126323-126334. DOI: 10.1109/ACCESS.2023.3331152.

