

DESIGN AND DEVELOPMENT WRITING ROBOT USING SPEECH PROCESSING FOR MEDICAL PRESCRIPTION

Submitted in partial fulfillment of the requirements for the award of Bachelor
of Engineering Degree in Electronics and Communication Engineering

by

A. SUBBA REDDY (40130008)

B. INDRASENA REDDY (40130027)



**DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING
SCHOOL OF ELECTRICAL AND ELECTRONICS**

SATHYABAMA

**INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)**

CATEGORY -1 UNIVERSITY BY UGC

**Accredited with Grade "A++" by NAAC | 12B Status by UGC | Approved by AICTE
JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI – 600119**

APRIL - 2024



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY

(DEEMED TO BE UNIVERSITY)

Accredited "A++" Grade by NAAC | 12B Status by UGC | Approved by AICTE

www.sathyabama.ac.in

**DEPARTMENT OF ELECTRONICS AND COMMUNICATION
ENGINEERING**

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of **B. INDRASENA REDDY (40130027), A. SUBBA REDDY (40130008)** who carried out the project entitled "**DESIGN AND DEVELOPMENT WRITING ROBOT USING SPEECH PROCESSING FOR MEDICAL PRESCRIPTION**" under our supervision from November 2023 to April 2024.

11-11-2023
16/04/2024
Internal Guide

Dr. V. VIJAYAKUMAR, M.TECH., Ph.D.,
Associate Professor

[Signature]
Head of the Department

Dr. T. RAVI, M.E., Ph.D.,
Professor & Head

Submitted for Viva voce Examination held on 17-04-2024

Internal Examiner

External Examiner

DECLARATION

I, B. INDRASENA REDDY (40130027) here by declare that the Project Report entitled "DESIGN AND DEVELOPMENT WRITING ROBOT USING SPEECH PROCESSING FOR MEDICAL PRESCRIPTION" done by us under the guidance of Dr.V.VIJAYAKUMAR, M.E., Ph.D., Dept. of Electronics and Communication Engineering, at SATHYABAMA INSTITUTE OF SCIENCE AND TECHNOLOGY, CHENNAI, is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in Electronics and Communication Engineering.

DATE:

PLACE: Chennai

SIGNATURE OF THE CANDIDATES

1.



DECLARATION

I, A. SUBBA REDDY (40130008) here by declare that the Project Report entitled "DESIGN AND DEVELOPMENT WRITING ROBOT USING SPEECH PROCESSING FOR MEDICAL PRESCRIPTION" done by us under the guidance of Dr.V.VIJAYAKUMAR, M.E., Ph.D., Dept. of Electronics and Communication Engineering, at SATHYABAMA INSTITUTE OF SCIENCE AND TECHNOLOGY, CHENNAI, is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in Electronics and Communication Engineering.

DATE:

PLACE: Chennai

SIGNATURE OF THE CANDIDATES

1.



ACKNOWLEDGEMENT

I am pleased to acknowledge my sincere thanks to the Board of Management of **SATHYABAMA INSTITUTE OF SCIENCE AND TECHNOLOGY**, for their kind encouragement in doing this project and for completing it successfully. I am grateful to them.

I convey my thanks to **Dr. N. M. NANDHITHA, M.E., Ph.D., Dean, School of Electrical and Electronics Engineering** and **Dr. T. RAVI, M.E., Ph.D., Head of the Department, Department of Electronics and Communication Engineering** for providing me necessary support and details at the right time during the progressive reviews.

I would like to express my sincere and deep sense of gratitude to our Project Guide **Dr.V.VIJAYAKUMAR, M.E., Ph.D., Associate Professor**, Dept. of Electronics and Communication Engineering for his valuable guidance, suggestions and constant encouragement for the successful completion of my project work.

I wish to express my thanks to all Teaching and Non-teaching staff members of the Department of Electronics and Communication Engineering who were helpful in many ways for the completion of the project.

ABSTRACT

The main goal is to outline the direction and the process for creating swift, fluid movements for a universal robot that can write like a doctor signs a prescription. The majority of consumers and certain pharmacists find it difficult to understand a handwritten prescription from a doctor; this issue can have unfavorable consequences if the prescription is misread. Prescriptions can be confusing since doctors often employ Latin and medical phrases that are abbreviated and difficult for the general public to understand. But this innovative automatic writing pen is a wholesome approach where the pen assures flawless and accurate writing according to the voice recognition. In this System, the input voice will be given to System using Bluetooth module via the Bluetooth Voice Controller Mobile Application. The writing mechanism fully comprises with servo motor and stepper motor for the Movement of pen. Finally, the output as pen writes according to the voice received by Bluetooth, to complete the work, online human signature criteria must first be devised. Robot signatures are then produced as a result of writing robots in compliance with these recommendations. Finally, suggestions for improving robot movement are provided.

TABLE OF CONTENTS

CHAPTER NO	TITLE	PAGE NO
	ABSTRACT	V
	LIST OF FIGURES	vii
1	INTRODUCTION	1
	1.1 General	1
	1.2 Technologies Used	2
	1.3 History of Embedded system	3
	1.3.1 Characteristics of an Embedded system	3
	1.3.2 Basic structure of an Embedded system	4
	1.3.3 Important Terminologies used in Embedded system	5
2	LITERATURE SURVEY	6
3	AIM AND SCOPE OF PRESENT INVESTIGATION	
	3.1 Aim	10
	3.2 Scope of the Project	11
	3.2.1 Technological Integration	11
4	EXPERIMENTAL METHODS	13
	4.1 Existing System	13
	4.2 Proposed System	13
	4.3 Standards	14
	4.4 Constraints	14
	4.5 Trade-offs	14
	4.6 Working	15
	4.7 Module description	16
	4.7.1 Power supply module	16
	4.7.2 Bluetooth module	17
	4.7.3 HC-05 Bluetooth Module	17
	4.7.4 Pin Description	18
	4.7.5 HC-05 module Information	19

	4.7.6 Bluetooth communication	20
	4.7.7 Servo motor	20
	4.7.8 Servo Mechanism	21
	4.7.9 Working principle of Servo Motors	22
	4.7.10 Controlling Servo Motor	22
	4.7.11 Stepper Motor	27
	4.7.12 Operation of Stepper Motor	27
	4.7.13 Avr microcontroller	28
4.8	Software Requirement	31
	4.8.1 embedded c	31
	4.8.2 characteristics of an embedded system	32
	4.8.3 Arduino ide	36
	4.8.4 Arduino Software	35
	4.8.5 Android App	36
	4.8.6 Visual studio code	41
5	RESULT AND DISCUSSIONS	43
	5.1 Result	43
	5.2 Discussion	43
	CONCLUSION AND FUTURE SCOPE	45
6	6.1 Conclusion	45
	6.2 Future Scope	45
	REFERENCES	49

LIST OF FIGURES

FIGURE NO	FIGURES NAME	PAGE NO.
1.1	Characteristics of embedded system	4
1.2	Structure of Embedded system	4
4.1	Architecture Diagram	15
4.2	Power Supply	17
4.3	HC-05 Bluetooth	18
4.4	Pin Description	18
4.5	Bluetooth communication	20
4.6	Servo Motor	21
4.7	Working of servo motor	23
4.8	Electrical pulse	24
4.9	Stepper Motor	26
4.10	Operation of Stepper Motor	28
4.11	Pin Diagram	31
4.12	Character of Embedded system	33
4.13	Structure of Embedded System	34
4.14	Open Arduino IDE	35
4.15	Select the Arduino board	35
4.16	Sketch the Arduino IDE	36
4.17	Compile and Upload to Board	36
4.18	Application for Speech Recognizer	38
4.19	Application Interface	39
4.20	Visual studio	41
5.1	Writing Robot	43
5.2	Robot Writing Words	44
5.3	Output of Robot Writing Medical prescription	44

CHAPTER-1

INTRODUCTION

1.1 GENERAL

The design and development of a writing robot utilizing speech processing for medical prescription represent a significant innovation in the field of healthcare technology. In contemporary medical practice, the process of writing prescriptions can be time-consuming and prone to errors, which can have serious consequences for patients. By employing speech processing technology, this project aims to streamline and automate the prescription writing process, thereby enhancing efficiency and accuracy. This project report delves into the design considerations, development process, and potential impact of this novel solution in the healthcare domain.

The fundamental concept behind the writing robot is to create a seamless interface between healthcare providers and prescription writing through speech processing. The design involves integrating advanced speech recognition algorithms with robotic writing mechanisms capable of transcribing verbal prescriptions into written form accurately and efficiently.

Key design considerations include the robot's physical structure, speech processing software, ergonomic features for ease of use, and compatibility with existing electronic medical record (EMR) systems. Additionally, ensuring compliance with medical regulations and patient privacy standards is paramount in the design process.

The development of the writing robot encompasses multiple stages, starting from conceptualization to prototype testing and refinement. Initially, extensive research is conducted to understand the requirements and challenges associated with medical prescription writing. Subsequently, software engineers and robotics experts collaborate to develop the speech processing algorithms and robotic mechanisms. The integration of these components is followed by rigorous testing to validate Accuracy, reliability, and usability.

Throughout the development process, iterative improvements are made based on feedback from healthcare professionals and end-users. Upon successful development and testing, the writing robot is implemented in clinical settings to

assess its practical functionality and effectiveness. Healthcare providers interact with the robot by dictating prescriptions verbally, which are then transcribed into written format in real-time. The robot's intuitive interface and seamless integration with existing EMR systems facilitate smooth adoption into medical workflows. Furthermore, the robot is equipped with safety features and fail-safes to prevent errors and ensure patient safety. Continuous monitoring and updates are performed to optimize performance and address any issues that may arise during usage.

The deployment of the writing robot using speech processing for medical prescriptions holds immense potential to revolutionize prescription writing practices in healthcare. By automating this aspect of clinical documentation, healthcare providers can devote more time to patient care, leading to improved efficiency and productivity. Moreover, the enhanced accuracy of prescriptions reduces the risk of medication errors, ultimately enhancing patient safety and outcomes.

Looking ahead, future iterations of the writing robot may incorporate artificial intelligence for advanced decision support, expand compatibility with diverse EMR systems, and explore integration with telemedicine platforms to extend its reach beyond traditional clinical settings. In conclusion, this project represents a pioneering effort in leveraging technology to address critical challenges in healthcare delivery, with far-reaching implications for patient care and medical practice.

1.2 TECHNOLOGIES USED

Embedded means something that is attached to another thing. An embedded system can be thought of as a computer hardware system having software embedded in it. An embedded system can be an independent system or it can be a part of a large system. An embedded system is a microcontroller or microprocessor-based system which is designed to perform a specific task. For example, a fire alarm is an embedded system; it will sense only smoke.

An embedded system has three components –

- It has hardware.
- It has application software.
- It has Real Time Operating system (RTOS) that supervises the application software and provide mechanism to let the processor run a process as per scheduling by following a plan to control the latencies. It sets the rules during the

execution of application program. So we can define an embedded system as a Microcontroller based, software driven, reliable, real-time control system.

1.3 HISTORY OF EMBEDDED SYSTEM

Here, are important milestones from the history of embedded system:

1. In 1960, embedded system was first used for developing Apollo Guidance System by Charles Stark Draper at MIT.
2. In 1965, Autonetics, developed the D-17B, the computer used in the Minuteman missile guidance system.
3. In 1968, the first embedded system for a vehicle was released.
4. Texas Instruments developed the first microcontroller in 1971.
5. In 1987, the first embedded OS, VxWorks, was released by Wind River.
6. Microsoft's Windows embedded CE in 1996.
7. By the late 1990s, the first embedded Linux system appeared.
8. The embedded market reach \$140 billion in 2013.
9. Analysts are projecting an Embedded market larger than \$40 billion by 2030.

1.3.1 *Characteristics of an Embedded System*

Single-functioned – An embedded system usually performs a specialized operation and does the same repeatedly. For example: A pager always functions as a pager.

Tightly constrained – All computing systems have constraints on design metrics, but those on an embedded system can be especially tight. Design metrics is a measure of an implementation's features such as its cost, size, power, and performance. It must be of a size to fit on a single chip, must perform fast enough to process data in real time and consume minimum power to extend battery life.

Reactive and Real time – Many embedded systems must continually react to changes in the system's environment and must compute certain results in real time without any delay. Consider an example of a car cruise controller; it continually monitors and reacts to speed and brake sensors.

It must compute acceleration or de-accelerations repeatedly within a limited time; a delayed computation can result in failure to control of the car.

Microprocessors based – It must be microprocessor or microcontroller based.

Memory – It must have a memory, as its software usually embeds in ROM. It does not need any secondary memories in the computer.

Connected – It must have connected peripherals to connect input and output devices.

HW-SW systems – Software is used for more features and flexibility. Hardware is used for performance and security.




Figure: 1.1 Characteristics of embedded system

1.3.2 Basic Structure of an Embedded System

The following illustration shows the basic structure of an embedded system




Figure: 1.2 Structure of Embedded system

Sensor – It measures the physical quantity and converts it to an electrical signal which can be read by an observer or by any electronic instrument like an A2D converter. A sensor stores the measured quantity to the memory.

A-D Converter – An analog-to-digital converter converts the analog signal sent by the sensor into a digital signal.

Processor & ASICs – Processors process the data to measure the output and store it to the memory.

D-A Converter – A digital-to-analog converter converts the digital data fed by the processor to analog data

1.3.3 Important Terminologies used in Embedded System

Reliability: This measure of the survival probability of the system when the function is critical during the run time.

Fault-Tolerance: Fault-Tolerance is the capability of a computer system to survive in the presence of faults.

Real-Time: Embedded system must meet various timing and other constraints. They are imposed on it by the real-time natural behavior of the external world.

Flexibility: It's building systems with built-in debugging opportunities which allows remote maintenance.

Portability: Portability is a measure of the ease of using the same embedded software in various environments. It requires generalized abstractions between the application program logic itself and the low-level system interfaces.

CHAPTER-2

LITERATURE SURVEY

Erdogan, Hakan et al. (2016) This research explores a joint training framework for enhancing the robustness of automatic speech recognition systems. The study delves into methods that enable the recognition system to perform effectively in various adverse conditions such as noisy environments or speaker variations. By jointly optimizing acoustic and language models, the proposed framework aims to improve recognition accuracy and generalization capabilities. Experimental results demonstrate significant performance gains compared to traditional single-model approaches. The findings suggest the effectiveness of incorporating joint training techniques for improving the resilience of speech recognition systems in real-world scenarios. This research contributes to the ongoing efforts in developing more reliable and robust automatic speech recognition technologies, which are essential for applications ranging from virtual assistants to automotive speech interfaces.

Wu, Minhua et al. (2018) novel approaches to unsupervised auditory filter bank learning utilizing Convolutional Restricted Boltzmann Machines (RBM) for enhancing speech recognition systems. Their study focuses on improving feature extraction techniques to better represent speech signals. By leveraging the capabilities of RBMs, the proposed method aims to learn hierarchical representations of speech features in an unsupervised manner. Experimental evaluations on benchmark datasets demonstrate the effectiveness of the proposed approach in improving the discriminative power of the learned features for speech recognition tasks. The findings highlight the potential of leveraging deep learning techniques for unsupervised feature learning in speech processing applications.

Qian, Yanmin et al. (2019) propose a neural network-based multi-factor aware joint training method to enhance the robustness of speech recognition systems. Their research aims to address challenges such as environmental noise and speaker variability through innovative training strategies. By considering

multiple factors that influence speech recognition performance, including noise type, speaker characteristics, and channel variations, the proposed approach seeks to adaptively adjust the model parameters during training. Experimental results on standard benchmark datasets demonstrate significant improvements in recognition accuracy under various adverse conditions compared to conventional training methods. The findings underscore the importance of incorporating multi-factor awareness into the training process to improve the robustness of speech recognition systems in practical applications. This research contributes to advancing the understanding of robust training techniques for speech recognition models, with implications for improving system performance in real-world scenarios.

Tu, Ming et al. (2017) study on speech emotion recognition using deep convolutional neural networks and discriminant temporal pyramid matching techniques. Their research explores the integration of deep learning models to accurately recognize emotional cues in speech signals. By leveraging the hierarchical representation learning capabilities of convolutional neural networks (CNNs) and the discriminative temporal pyramid matching method, the proposed approach aims to capture both spectral and temporal features indicative of different emotional states. Experimental evaluations on benchmark datasets demonstrate the effectiveness of the proposed method in accurately classifying various emotions expressed in speech. The findings highlight the potential of deep learning techniques for improving the performance of speech emotion recognition systems, with implications for applications such as affective computing and human-computer interaction. This research contributes to advancing the state-of-the-art in speech emotion recognition, with implications for developing more empathetic and context-aware intelligent systems.

Du, Yong et al. (2020) investigate the efficacy of a gating neural network for large vocabulary audiovisual speech recognition tasks. Their study focuses on leveraging both auditory and visual information for improved speech recognition performance, particularly in challenging scenarios. By incorporating a gating mechanism that dynamically adjusts the contribution of auditory and visual

modalities based on their reliability, the proposed approach aims to enhance robustness and accuracy in audiovisual speech recognition. Experimental evaluations on benchmark datasets demonstrate significant improvements in recognition performance compared to conventional single-modality approaches. The findings highlight the complementary nature of auditory and visual information in improving speech recognition accuracy, with implications for applications such as human-robot interaction and audiovisual speech processing. This research contributes to advancing the state-of-the-art in audiovisual speech recognition, with implications for developing more effective and versatile multimodal interfaces.

Zhang, Zixing et al. (2018) propose a methodology for spontaneous speech emotion recognition employing multiscale deep convolutional Long Short-Term Memory (LSTM) networks. Their research aims to accurately detect and classify emotions expressed in natural, unscripted speech. By leveraging the hierarchical and sequential learning capabilities of deep convolutional LSTM networks, the proposed approach aims to capture both local and global dependencies in speech features for robust emotion recognition. Experimental evaluations on benchmark datasets demonstrate superior performance compared to traditional shallow models and other deep learning architectures. The findings underscore the potential of multiscale deep learning techniques for capturing complex patterns in spontaneous speech, with implications for applications such as affective computing, healthcare, and entertainment. This research contributes to advancing the state-of-the-art in spontaneous speech emotion recognition, with implications for developing more empathetic and context-aware intelligent systems.

Xu, Chenglin et al. (2019) introduce a speech enhancement approach based on teacher-student deep learning utilizing improved speech presence probability for noise-robust speech recognition. Their study explores techniques to enhance speech signals in noisy environments to improve recognition accuracy. By leveraging the teacher-student learning framework and incorporating improved speech presence probability estimation, the proposed approach aims to suppress noise while preserving important speech information. Experimental evaluations on benchmark datasets demonstrate significant improvements in speech recognition

accuracy under various noise conditions compared to baseline methods. The findings highlight the effectiveness of the proposed speech enhancement approach in improving the robustness of automatic speech recognition systems in real-world noisy environments. This research contributes to advancing the state-of-the-art in noise-robust speech recognition, with implications for improving the usability and performance of speech-based applications in adverse conditions.

Zhu, Peidong et al. (2020) investigate unsupervised speech enhancement techniques based on multichannel Non-Negative Matrix Factorization (NMF)-informed beamforming for noise-robust automatic speech recognition. Their research focuses on improving speech quality and intelligibility in noisy environments. By leveraging multichannel NMF-informed beamforming techniques, the proposed approach aims to enhance the signal-to-noise ratio and suppress interfering noise sources for improved speech recognition performance. Experimental evaluations on benchmark datasets demonstrate significant improvements in speech quality and recognition accuracy compared to traditional single-channel methods. The findings underscore the potential of unsupervised speech enhancement techniques for improving the robustness of automatic speech recognition systems in real-world noisy environments. This research contributes to advancing the state-of-the-art in noise-robust speech processing, with implications for various applications such as telecommunication, voice-controlled devices, and automatic transcription systems.

CHAPTER-3

AIM AND SCOPE OF THE PRESENT INVESTIGATION

3.1.AIM

The primary aim of designing and developing a writing robot utilizing speech processing for medical prescription is to enhance the efficiency of the prescription writing process within healthcare settings. Traditional methods of handwritten prescriptions are often time-consuming and prone to errors, leading to potential risks for patients. By leveraging speech processing technology, the aim is to automate and streamline this process, allowing healthcare providers to dictate prescriptions verbally. This not only saves time but also reduces the administrative burden on healthcare professionals, enabling them to allocate more time to direct patient care.

The writing robot project is to improve the accuracy of medical prescriptions while minimizing the risk of errors. Handwritten prescriptions can sometimes be illegible or contain mistakes due to human error, which can have serious consequences for patient safety. Through the implementation of speech processing technology, prescriptions can be transcribed accurately and reliably, reducing the likelihood of misinterpretation or transcription errors. This contributes to safer medication administration practices and ultimately enhances patient outcomes.

The project also aims to facilitate seamless integration between the writing robot and existing electronic health record (EHR) systems used in healthcare facilities. By ensuring compatibility with EHR platforms, the writing robot can directly input prescriptions into patients' electronic records, eliminating the need for manual data entry and reducing the risk of data entry errors. This integration enhances the continuity of care by providing healthcare providers with access to accurate and up-to-date medication information, thereby improving clinical decision-making and patient management. Lastly, the aim of the project is to promote accessibility and usability by developing a user-friendly interface for the writing robot.

The includes compatibility testing with various EMR platforms to ensure interoperability and adherence to industry standards. interfaces must adhere to industry standards such as HL7 (Health Level Seven) to facilitate smooth integration with different EMR platforms. Compatibility testing will be conducted rigorously to ensure interoperability across various EMR systems, guaranteeing that prescriptions are accurately and efficiently inputted into patients' electronic records.

3.2 SCOPE OF THE PROJECT

3.2.1 Technological Integration

The scope of a Design and Development writing robot using Speech Processing for Medical Prescription encompasses a wide range of functionalities and applications aimed at optimizing various aspects of residential living. This includes but is not limited to:

- 1. Speech Recognition and Transcription:** The project will focus on implementing robust speech recognition algorithms capable of accurately transcribing verbal prescriptions dictated by healthcare providers. This involves research into state-of-the-art speech processing technologies and the selection of appropriate algorithms that can reliably convert spoken words into text with high accuracy. The scope includes developing methods to handle medical terminology and context-specific language to ensure accurate transcription of prescriptions.
- 2. Robotic Writing Mechanism:** The project will encompass the design and development of a robotic mechanism capable of physically transcribing the transcribed prescriptions onto paper or electronic forms. This involves engineering considerations such as selecting suitable actuators, precision mechanisms, and writing instruments. The scope includes prototyping and testing various robotic designs to determine the most efficient and reliable solution for accurately reproducing written prescriptions.
- 3. Integration with Electronic Medical Records (EMR) Systems:** The writing robot will be designed to seamlessly integrate with existing electronic medical record (EMR) systems commonly used in healthcare settings. This involves developing interfaces and protocols for data exchange between the writing robot and EMR systems to ensure that prescriptions are directly inputted into patients' electronic records. The scope includes compatibility testing with various EMR platforms to ensure interoperability and adherence to industry standards. interfaces must adhere to industry standards such as HL7 (Health Level Seven) to facilitate smooth integration with different EMR platforms. Compatibility testing will be conducted rigorously to ensure interoperability across various EMR systems, guaranteeing that prescriptions are accurately and efficiently.
- 4. User Interface and Interaction Design:** The project will include the design and

implementation of a user-friendly interface for interacting with the writing robot. This involves designing intuitive voice commands or interfaces that enable healthcare providers to dictate prescriptions easily. Additionally, ergonomic considerations will be taken into account to ensure that the interaction with the writing robot is comfortable and efficient for users. The scope encompasses user testing and refinement of the interface to optimize usability and user satisfaction.

- 5. Safety and Regulatory Compliance:** Ensuring patient safety and compliance with regulatory standards are paramount considerations in the project. The writing robot will be designed with built-in safety features to prevent errors or malfunctions that could compromise patient care. Additionally, the project will involve adherence to relevant regulatory requirements for medical devices, including obtaining necessary certifications and approvals. The scope includes conducting risk assessments, safety testing, and documentation to demonstrate compliance with regulatory standards.
- 6. Pilot Testing in Clinical Settings:** A crucial aspect of the project involves pilot testing the writing robot in real clinical settings to evaluate its performance, usability, and impact on workflow efficiency. This will involve collaborating with healthcare providers to deploy the writing robot in simulated or actual patient care scenarios and collecting feedback on its functionality and usability. The scope includes analyzing the results of pilot testing to identify areas for improvement and refinement of the writing robot before wider deployment.

CHAPTER-4

EXPERIMENTAL METHODS

4.1 EXISTING SYSTEM

In existing systems, we don't have any automatic monitoring controlling of building. In existing system, manual monitoring of building are required which is dangerous and it requires lots of time to monitor and controlling Building Energy Management systems are critical in many regions, being used over several decades. In the Existing System, meter reading taken manually Errors occurred due

to less concentration Meter reading not accurate Huge Manpower needed Delayed work due to external conditions Power cut manually due to lack of payment. In proposed system Meter reading taken automatically using GSM technology Power cut achieved from EB office through wireless work happen at any time.

4.2 PROPOSED SYSTEM

In proposed system Machine learning method has been applied to analyze the data. Word embedding method in unsupervised learning using large dataset. The feature set is integrated into a Linear Regression for training and predicting classification labels. Linear Regression architecture is capable of overcoming the performance of traditional machine learning models. For easy access the server maintains a database for each node, and hence each node will have a unique id for addressing it. Proposed system, the various building data are collected from sensors like co2, LDR, DHT11, motion sensors. The data collected by the IOT sensors are given to the Arduino Microcontroller. Based on PIR and LDR then lights will ON. Based on DHT11 Values the speed of fan will be changed. Based on CO2 Values a DC Motor will rotate. The values are continuously sent to the cloud server where user can continuously checks the sensors parameters. The sensors are placed in acceptable places of buildings to gather needed features.

4.3 STANDARDS

1. Medical Prescription Guidelines: Adherence to established medical prescription standards ensuring accuracy, completeness, and compliance with regulatory requirements.
2. Bluetooth Connectivity Standards: Utilization of standardized Bluetooth protocols to facilitate seamless communication between the mobile device and the writing robot.
3. Speech-to-Text Accuracy Standards: Integration of speech recognition algorithms meeting industry standards for accuracy and reliability in converting spoken instructions into text format.

4.4 CONSTRAINTS

1. Hardware Limitations: The writing robot's hardware capabilities, including writing speed, precision, and compatibility with different writing surfaces, may pose constraints on the overall performance and functionality.
2. Power Consumption: Balancing the power requirements of both the writing robot and the mobile device to ensure optimal battery life and sustained operation.
3. Cost Constraints: Ensuring the affordability of the solution for healthcare facilities of varying sizes and budgets, considering the costs associated with hardware, software development, and maintenance.

4.5 TRADE-OFFS

1. Speed vs. Accuracy: Balancing the need for quick prescription generation with the importance of maintaining accuracy in transcription and interpretation of prescription details.
2. Complexity vs. Usability: Striking a balance between incorporating advanced features and maintaining user-friendly design and interface for healthcare professionals utilizing the Android application.
3. Interoperability vs. Security: Trade-offs between enhancing interoperability with existing healthcare systems and maintaining stringent security measures to protect patient data and ensure regulatory compliance.

4.6 WORKING




Figure: 4.1 Architecture Diagram

Robot Operation and Writing Process Once the prescription details are transmitted, the writing robot springs into action, utilizing its designated writing mechanism to meticulously transcribe the information onto the prescribed medium. Whether it's a traditional paper prescription or an electronic format, the robot's precision-engineered hardware ensures accurate placement and legibility of the text. With each stroke, the robot navigates the intricacies of the prescription, adjusting its speed and pressure to adapt to different writing surfaces and maintain consistency throughout the document.

Moreover, advanced sensors embedded within the robot's system continuously monitor the writing process, promptly detecting and rectifying any potential errors to uphold the highest standards of accuracy. As the robot gracefully maneuvers, it embodies the convergence of technology and healthcare, embodying the promise of streamlined processes and enhanced patient care.

Data Integration and Workflow Enhancement Beyond its writing prowess, the system facilitates seamless integration of prescription data into broader healthcare

workflows. Once the prescription is finalized and verified, it can be effortlessly integrated into electronic health record systems or other healthcare databases, eliminating the need for manual data entry and reducing the risk of transcription errors. This integration not only enhances the efficiency of healthcare operations but also ensures the continuity of patient care by providing comprehensive and up-to-date medical records.

Furthermore, the system's versatility allows healthcare professionals to customize prescription formats and incorporate patient-specific information, empowering personalized care delivery. With each prescription generated, the system reaffirms its role as a transformative force in modern healthcare, driving efficiency, accuracy, and patient-centricity to new heights.

The writing process may involve the robot adjusting its speed and pressure based on the writing surface's characteristics, such as paper thickness or texture, to achieve optimal results. Additionally, the writing robot may incorporate feedback mechanisms to detect and correct any errors in real-time, further enhancing the accuracy of the prescription transcription. Overall, the robot's efficient operation and precise writing capabilities contribute to the reliability and quality of the generated prescriptions, ensuring that healthcare professionals can trust the output for patient care.

4.7 MODULE DESCRIPTION

- Power Supply Module
- Bluetooth Module
- Servo Motor
- Stepper Motor
- AVR Microcontroller

4.7.1 Power Supply Module

The power supply circuit consists of step-down transformer which is 230v step down to 12v. In this circuit 4 diodes are used to form bridge rectifier which delivers pulsating dc voltage & then fed to capacitor filter the output voltage from rectifier is fed to filter to eliminate any ac components present even after rectification.

The filtered DC voltage is given to regulator to produce 12v constant DC voltage. 230V AC power is converted into 12V AC (12V RMS value wherein the peak value is around 17V), but the required power is 5V DC; for this purpose, 17V AC power must be primarily converted into DC power then it can be stepped down to the 5V DC. AC power can be converted into DC using one of the power electronic converters called as Rectifier. There are different types of rectifiers, such as half-wave rectifier, full-wave rectifier and bridge rectifier. Due to the advantages of the bridge rectifier over the half and full wave rectifier, the bridge rectifier is frequently used for converting AC to DC.

The following fig shows the circuit of a power supply that converts an ac source to a dc source




Figure: 4.2 Power Supply

4.7.2 Bluetooth Module

It is used for many applications like wireless headset, game controllers, wireless mouse, wireless keyboard and many more consumer applications. It has range up to <100m which depends upon transmitter and receiver, atmosphere, geographic & urban conditions. It is IEEE 802.15.1 standardized protocol, through which one can build wireless Personal Area Network (PAN). It uses frequency-hopping spread spectrum (FHSS) radio technology to send data over air. It uses serial communication to communicate with devices. It communicates with microcontroller using serial port (USART).

4.7.3 HC-05 Bluetooth Module

- HC-05 is a Bluetooth module which is designed for wireless communication. This module can be used in a master or slave configuration.

- It is used to bring Bluetooth module in AT commands mode. If Key/EN pin is set to high, then this module will work in command mode.
- Otherwise by default it is in data mode. The default baud rate of HC-05 in command mode is 38400bps and 9600 in data mode.




Figure: 4.3 HC-05 Bluetooth

4.7.4 Pin Description



Figure: 4.4 Pin Description

Bluetooth serial modules allow all serial enabled devices to communicate with each other using Bluetooth.

It has 6 pins:

1. Key/EN: It is used to bring Bluetooth module in AT commands mode. If Key/EN pin is set to high, then this module will work in command mode. Otherwise by default it is in data mode.
2. The default baud rate of HC-05 in command mode is 38400bps and 9600 in data mode.
3. HC-05 module has two modes:
4. Data mode: Exchange of data between devices.
5. Command mode: It uses AT commands which are used to change setting of HC-05. To send these commands to module serial (USART) port is used.
6. VCC: Connect 5 V or 3.3 V to this Pin.
7. GND: Ground Pin of module.
8. TXD: Transmit Serial data (wirelessly received data by Bluetooth module transmitted out serially on TXD pin)
9. RXD: Receive data serially (received data will be transmitted wirelessly by Bluetooth module).
10. State: It tells whether module is connected or not.

4.7.5 HC-05 module Information

HC-05 has red LED which indicates connection status, whether the Bluetooth is connected or not. Before connecting to HC-05 module this red LED blinks continuously in a periodic manner. When it gets connected to any other Bluetooth device, its blinking slows down to two seconds.

This module works on 3.3 V. We can connect 5V supply voltage as well since the module has on board 5 to 3.3 V regulator.

As HC-05 Bluetooth module has 3.3 V level for RX/TX and microcontroller can detect 3.3 V level, so, no need to shift transmit level of HC-05 module. But we need to shift the transmit voltage level from microcontroller to RX of HC-05 module. E.g. Send data from Smartphone terminal to HC-05 Bluetooth module and see this data on PC serial terminal and vice versa.

4.7.6 Bluetooth Communication between Devices

E.g. Send data from Smartphone terminal to HC-05 Bluetooth module and see this data on PC serial terminal and vice versa.

To communicate smartphone with HC-05 Bluetooth module, smartphone requires Bluetooth terminal application for transmitting and receiving data. You can find Bluetooth terminal applications for android and windows in respective app. store.




Figure: 4.5 Bluetooth communication

So, when we want to communicate through smartphone with HC-05 Bluetooth module, connect this HC-05 module to the PC via serial to USB converter. Before establishing communication between two Bluetooth devices, 1st we need to pair HC-05 module to smartphone for communication.

4.7.7 Servo Motor

A servo motor is an electrical device which can push or rotate an object with great precision. If you want to rotate an object at some specific angles or distance, then you use servo motor. It is just made up of simple motor which runs through a servo mechanism.

If a motor is used is DC powered then it is called DC servo motor, and if it is AC powered motor then it is called AC servo motor. We can get a very high torque servo motor in a small and light weight package.

Due to these features they are being used in many applications like toy car, RC helicopters and planes, Robotics, Machine etc.



Figure: 4.6 Servo Motor

Servo motors are rated in kg/cm (kilogram per centimetre) most hobby servo motors are rated at 3kg/cm or 6kg/cm or 12kg/cm. This kg/cm tells you how much weight your servo motor can lift at a particular distance. For example, A 6kg/cm Servo motor should be able to lift 6kg if the load is suspended 1cm away from the motors shaft, the greater the distance the lesser the weight carrying capacity. The position of a servo motor is decided by electrical pulse and its circuitry is placed beside the motor as shown in Figure 4.6 Servo Motor

4.7.8 Servo Mechanism

It consists of three parts:

- Controlled device
- Output sensor
- Feedback system

It is a closed loop system where it uses positive feedback system to control motion and final position of the shaft. Here the device is controlled by a feedback signal generated by comparing output signal and reference input signal. Here reference input signal is compared to reference output signal and the third signal is produced by feedback system. And this third signal acts as input signal to control device.

This signal is present as long as feedback signal is generated or there is difference between reference input signal and reference output signal. So the main task of servomechanism is to maintain output.

4.7.9 Working Principle of Servo Motors

A servo consists of a Motor (DC or AC), a potentiometer, gear assembly and a controlling circuit. First of all we use gear assembly to reduce RPM and to increase

torque of motor. Say at initial position of servo motor shaft, the position of the potentiometer knob is such that there is no electrical signal generated at the output port of the potentiometer. Now an electrical signal is given to another input terminal of the error detector amplifier.

Now difference between these two signals, one comes from potentiometer and another comes from other source, will be processed in feedback mechanism and output will be provided in term of error signal. This error signal acts as the input for motor and motor starts rotating. Now motor shaft is connected with potentiometer and as motor rotates so the potentiometer and it will generate a signal. So as the potentiometer's angular position changes, its output feedback signal changes.

After sometime the position of potentiometer reaches at a position that the output of potentiometer is same as external signal provided. At this condition, there will be no output signal from the amplifier to the motor input as there is no difference between external applied signal and the signal generated at potentiometer, and in this situation motor stops rotating.

4.7.10 Controlling Servo Motor:

All motors have three wires coming out of them. Out of which two will be used for Supply (positive and negative) and one will be used for the signal that is to be sent from the MCU.

Servo motor is controlled by PWM (Pulse with Modulation) which is provided by the control wires. There is a minimum pulse, a maximum pulse and a repetition rate. Servo motor can turn 90 degree from either direction from its neutral position. The servo motor expects to see a pulse every 20 milliseconds (ms) and the length of the pulse will determine how far the motor turns. For example, a 1.5ms pulse will make the motor turn to the 90° position, such as if pulse is shorter.




Figure: 4.7 Working of servo motor

Figure 4.7 Working of servo motor ,Servo motor works on PWM (Pulse width modulation) principle, means its angle of rotation is controlled by the duration of applied pulse to its Control PIN. Basically, servo motor is made up of DC motor which is controlled by a variable resistor (potentiometer) and some gears.

High speed force of DC motor is converted into torque by Gears. We know that $WORK = FORCE \times DISTANCE$, in DC motor Force is less and distance (speed) is high and in Servo, force is High and distance is less. Potentiometer is connected to the output shaft of the Servo, to calculate the angle and stop the DC.

The potentiometer, connected to the output shaft of the servo, acts as a feedback device, providing information about the current position of the motor shaft. This feedback mechanism allows the control circuit to accurately position the motor shaft to the desired angle, correcting any deviations caused by external forces or mechanical limitations.

One of the key advantages of servo motors is their ability to maintain position accuracy even under varying loads or external disturbances. The feedback mechanism continuously monitors the position of the motor shaft and makes real-time adjustments to ensure that it remains at the desired angle, making servo motors ideal for applications requiring precise control and stability. In addition to their exceptional position accuracy, servo motors offer high torque at low speeds, enabling smooth and precise movement in robotics, CNC machines, and industrial automation.




Figure: 4.8 Electrical pulse

Servo motor can be rotated from 0 to 180 degree, but it can go up to 210 degree, depending on the manufacturing. This degree of rotation can be controlled by applying the Electrical Pulse of proper width, to its Control pin. Servo checks the pulse in every 20 milliseconds. Pulse of 1 ms (1 millisecond) width can rotate servo to 0 degree, 1.5ms can rotate to 90 degree (neutral position) and 2 ms pulse can rotate it to 180 degree as shown as Figure 4.8: Electrical pulse.

All servo motors work directly with your +5V supply rails but we have to be careful on the amount of current the motor would consume, if you are planning to use more than two servo motors a proper servo shield should be designed.

Advantages:

- If a heavy load is placed on the motor, the driver will increase the current to the motor coil as it attempts to rotate the motor. Basically, there is no out-of-step condition.
- High-speed operation is possible. Servomotors are used in applications requiring rapid variations in speed without the motor getting overheated.
- In Industries they are used in machine tools, packaging, factory automation, material handling, printing converting, assembly lines, and many other demanding applications robotics, CNC machinery or automated manufacturing.
- They are also used in radio-controlled airplanes to control the positioning and movement of elevators.

- They are used in robots because of their smooth switching on and off and accurate positioning.
- They are also used by aerospace industry to maintain hydraulic fluid in their hydraulic systems.
- They are used in many radio-controlled toys.
- They are used in electronic devices such as DVDs or Blue ray Disc players to extend or replay the disc trays.

4.7.11 Stepper Motor

A stepper motor is an electromechanical device it converts electrical power into mechanical power. Also, it is a brushless, synchronous electric motor that can divide a full rotation into an expansive number of steps. The motor's position can be controlled accurately without any feedback mechanism, as long as the motor is carefully sized to the application. Stepper motors are similar to switched reluctance motors.

The stepper motor uses the theory of operation for magnets to make the motor shaft turn a precise distance when a pulse of electricity is provided. The stator has eight poles, and the rotor has six poles. The rotor will require 24 pulses of electricity to move the 24 steps to make one complete revolution. Another way to say this is that the rotor will move precisely 15° for each pulse of electricity that the motor receives.

Servo motors come in various sizes and torque ratings to suit different applications, from small hobby servos used in model airplanes to large industrial servos used in CNC machines and robotic arms. In addition to their exceptional position accuracy, servo motors offer high torque at low speeds, enabling smooth and precise movement in robotics, CNC machines, and industrial automation. Their compact size and lightweight design make them suitable for space-constrained applications without sacrificing performance. Furthermore, servo motors can easily interface with various control systems, facilitating seamless integration into diverse machinery and processes.

Overall, their versatility, reliability, and responsiveness make servo motors a preferred choice across industries for demanding motion control tasks.



Figure: 4.9 Stepper Motor

From Figure 4.9: Stepper Motor There are three main types of stepper motors, they are:

- Permanent magnet stepper
- Hybrid synchronous stepper
- Variable reluctance stepper

Permanent Magnet Stepper Motor: Permanent magnet motors use a permanent magnet (PM) in the rotor and operate on the attraction or repulsion between the rotor PM and the stator electromagnets.

Variable Reluctance Stepper Motor: Variable reluctance (VR) motors have a plain iron rotor and operate based on the principle that minimum reluctance occurs with minimum gap, hence the rotor points are attracted toward the stator magnet poles.

Hybrid Synchronous Stepper Motor: Hybrid stepper motors are named because they use a combination of permanent magnet (PM) and variable reluctance (VR) techniques to achieve maximum power in a small package size.

Advantages of Stepper Motor

- The rotation angle of the motor is proportional to the input pulse.
- The motor has full torque at standstill.
- Precise positioning and repeatability of movement since good stepper motors have an accuracy of 3 – 5% of a step and this error is non-cumulative from one step to the next.
- Excellent response to starting, stopping and reversing.

- Very reliable since there are no contact brushes in the motor. Therefore the life of the motor is simply dependant on the life of the bearing.
- The motors response to digital input pulses provides open-loop control, making the motor simpler and less costly to control.
- It is possible to achieve very low speed synchronous rotation with a load that is directly coupled to the shaft.
- A wide range of rotational speeds can be realized as the speed is proportional to the frequency of the input pulses.
- **Industrial Machines** – Stepper motors are used in automotive gauges and machine tooling automated production equipment's.
- **Security** – new surveillance products for the security industry.
- **Medical** – Stepper motors are used inside medical scanners, samplers, and also found inside digital dental photography, fluid pumps, respirators and blood analysis machinery.
- **Consumer Electronics** – Stepper motors in cameras for automatic digital camera focus and zoom functions and also have business machines applications, computer peripherals applications.

4.7.12 Operation of Stepper Motor

Stepper motors operate differently from DC brush motors, which rotate when voltage is applied to their terminals. Stepper motors, on the other hand, effectively have multiple toothed electromagnets arranged around a central gear-shaped piece of iron. The electromagnets are energized by an external control circuit, for example a microcontroller.

Atmel says that the name AVR is not an acronym and does not stand for anything in particular.

The creators of the AVR give no definitive answer as to what the term However, it is commonly accepted that AVR stands for Alf and Vegard's RISC processor, note that the use of "AVR" in this article generally refers to the 8-bit RISC line of Atmel AVR Microcontrollers.




Figure: 4.10 Operation of Stepper Motor

To make the motor shaft turn, first one electromagnet is given power, which makes the gear's teeth magnetically attracted to the electromagnet's teeth. The point when the gear's teeth are thus aligned to the first electromagnet, they are slightly offset from the next electromagnet. So, when the next electromagnet is turned ON and the first is turned OFF, the gear rotates slightly to align with the next one and from there the process is repeated. Each of those slight rotations is called a step, with an integer number of steps making a full rotation. In that way, the motor can be turned by a precise. Stepper motor doesn't rotate continuously; they rotate in steps as shown as Figure 4.10: Operation of Stepper Motor.

There are 4 coils with 90° angle between each other fixed on the stator. The stepper motor connections are determined by the way the coils are interconnected. In stepper motor, the coils are not connected together. The motor has 90° rotation step with the coils being energized in a cyclic order, determining the shaft rotation direction. The working of this motor is shown by operating the switch. The coils are activated in series in 1 sec intervals. The shaft rotates 90° each time the next coil is activated.

4.7.13 Avr Microcontroller

AVR Microcontroller is used as processing module and it is used as send data to LCD Screen and Gate way module. AVR is a of microcontrollers developed by Atmel beginning in 1996. These are modified Harvard architecture 8-bit RISC single-chip microcontrollers. AVR was one of the first microcontroller

families to use on-chip flash memory for program storage. As opposed to one-time programmable ROM, EPROM, or EEPROM used by other microcontrollers at the time.

The AVR architecture was conceived by two students at the Norwegian Institute of Technology (NTH), Alf-Egil Bogen and Vegard Wollan. The original AVR MCU was developed at a local ASIC house in Trondheim, Norway, called Nordic VLSI at the time, now Nordic Semiconductor,

where Bogen and Wollan were working as students. It was known as a μ RISC Micro RISC and was available as silicon IP/building block from Nordic VLSI. When the technology was sold to Atmel from Nordic VLSI, the internal architecture was further developed by Bogen and Wollan at Atmel Norway, a subsidiary of Atmel. The designers worked closely with compiler writers at IAR Systems to ensure that the AVR instruction set provided efficient compilation of high-level languages

Atmel says that the name AVR is not an acronym and does not stand for anything in particular. The creators of the AVR give no definitive answer as to what the term "AVR" stands for. However, it is commonly accepted that AVR stands for Alf and Vegard's RISC processor. Note that the use of "AVR" in this article generally refers to the 8-bit RISC line of Atmel AVR Microcontrollers.

The AT90S8515 marked the beginning of the AVR microcontroller family, offering advanced features and performance compared to traditional microcontrollers like the 8051. With its compatibility with the 8051 pinout, transitioning from 8051-based designs to AVR-based ones became more accessible, allowing developers to leverage the enhanced capabilities of AVR architecture.

Features

- Multifunction, bi-directional general-purpose I/O ports with configurable, built-in pull-up resistors
- Multiple internal oscillators, including RC oscillator without external parts
- Internal, self-programmable instruction flash memory up to 256 KB (384 KB on X-Mega)
- In-system programmable using serial/parallel low-voltage proprietary interfaces or JTAG

- Optional boot code section with independent lock bits for protection
- On-chip debugging (OCD) support through JTAG or debug WIRE on most devices
- The JTAG signals (TMS, TDI, TDO, and TCK) are multiplexed on GPIOs. These pins can be configured to function as JTAG or GPIO depending on the setting of a fuse bit, which can be programmed via ISP or HVSP. By default, AVRs with JTAG come with the JTAG interface enabled.
- Debug WIRE uses the /RESET pin as a bi-directional communication channel to access on-chip debug circuitry. It is present on devices with lower pin counts, as it only requires one pin.
- Internal data EEPROM up to 4 KB
- Internal SRAM up to 16 KB (32 KB on X-Mega)
- External 64 KB little endian data space on certain models, including the Mega8515 and Mega162.
- The external data space is overlaid with the internal data space, such that the full 64 KB address space does not appear on the external bus and accesses to e.g. address 0100₁₆ will access internal RAM, not the external bus.
- In certain members of the X-Mega series, the external data space has been enhanced to support both SRAM and SDRAM. As well, the data addressing modes have been expanded to allow up to 16 MB of data memory to be directly addressed.
- AVRs generally do not support executing code from external memory. Some ASSPs using the AVR core do support external program memory.
- 8-bit and 16-bit timers
- PWM output (some devices have an enhanced PWM peripheral which includes a dead-time generator)
- Input capture that record a time stamp triggered by a signal edge
- Analog comparator
- 10 or 12-bit A/D converters, with multiplex of up to 16 channels
- 12-bit D/A converters
- A variety of serial interfaces, including
- I²C compatible Two-Wire Interface (TWI)

- Synchronous/asynchronous serial peripherals (UART/USART) (used with RS-232, RS-485, and more)
- Serial Peripheral Interface Bus (SPI)
- Universal Serial Interface (USI): a multi-purpose hardware communication module that can be used to implement an SPI, I²C or UART interface.
- Lighting and motor control (PWM-specific) controller models
- CAN controller support
- USB controller support



Figure: 4.11 Pin Diagram

4.8 SOFTWARE REQUIREMENT

4.8.1 Embedded C

As its name suggests, Embedded means something that is attached to another thing. An embedded system can be thought of as a computer hardware system having software embedded in it. An embedded system can be an independent system or it can be a part of a large system. An embedded system is a microcontroller or microprocessor-based system which is designed to perform a

specific task. For example, a fire alarm is an embedded system; it will sense only smoke.

An embedded system has three components –

- It has hardware.
- It has application software.
- It has Real Time Operating system (RTOS) that supervises the application software and provide mechanism to let the processor run a process as per scheduling by following a plan to control the latencies. RTOS defines the way the system works. It sets the rules during the execution of application program. A small scale embedded system may not have RTOS.

So we can define an embedded system as a Microcontroller based, software driven, reliable, real-time control system.

4.8.2 Characteristics of an Embedded System

Single-functioned – An embedded system usually performs a specialized operation and does the same repeatedly. For example: A pager always functions as a pager.

Tightly constrained – All computing systems have constraints on design metrics, but those on an embedded system can be especially tight. Design metrics is a measure of an implementation's features such as its cost, size, power, and performance. It must be of a size to fit on a single chip, must perform fast enough to process data in real time and consume minimum power to extend battery life.

Reactive and Real time – Many embedded systems must continually react to changes in the system's environment and must compute certain results in real time without any delay. Consider an example of a car cruise controller; it continually monitors and reacts to speed and brake sensors. It must compute acceleration or de-accelerations repeatedly within a limited time; a delayed computation can result in failure to control of the car.

Microprocessors based – It must be microprocessor or microcontroller based.

Memory – It must have a memory, as its software usually embeds in ROM. It does not need any secondary memories in the computer.

Connected – It must have connected peripherals to connect input and output devices.

HW-SW systems – Software is used for more features and flexibility. Hardware is used for performance and security.




Figure: 4.12 Character of Embedded system

Advantages

- Easily Customizable
- Low power consumption
- Low cost
- Enhanced performance

Disadvantages

- High development effort
- Larger time to market

An embedded system is a specialized computer system that is designed to perform dedicated functions within a larger system or device. Typically, it is embedded into a larger piece of hardware and operates with minimal user intervention. These systems are characterized by their compact size, low power consumption, and real-time operation, making them ideal for applications such as consumer electronics, automotive systems, industrial automation, and medical devices.

From Figure 5.2: Structure of Embedded System the following illustration shows the basic structure of an embedded system




Figure 4.13 Structure of Embedded System

Sensor – It measures the physical quantity and converts it to an electrical signal which can be read by an observer or by any electronic instrument like an A2D converter. A sensor stores the measured quantity to the memory.

A-D Converter – An analog-to-digital converter converts the analog signal sent by the sensor into a digital signal.

Processor & ASICs – Processors process the data to measure the output and store it to the memory.

D-A Converter – A digital-to-analog converter converts the digital data fed by the processor to analog data

Actuator – An actuator compares the output given by the D-A Converter to the actual (expected) output stored in it and stores the approved output.

4.8.3 Arduino IDE

The Arduino Integrated Development Environment (IDE) is an open-source software platform that is used to write, compile, and upload code to Arduino microcontroller boards. It provides a user-friendly interface for both beginners and experienced developers to create and develop projects involving Arduino boards. Here are some key details about the Arduino IDE. for both beginners and experienced developers to create and develop projects involving Arduino boards. Here are some key details about the Arduino IDE. It provides a user-friendly interface for both beginners and experienced developers to create and develop projects involving Arduino boards. Here are some key details about the Arduino IDE Its user-friendly interface, powerful features, and extensive ecosystem of plugins and extensions make it a preferred choice among developers .

4.8.4 Arduino Software

From Fig 4.5.3.a Open Arduino IDE It provides a user-friendly interface for both beginners and experienced developers to create and develop projects involving Arduino boards. Here are some key details about the Arduino IDE.




Figure: 4.14 Open Arduino IDE




Figure 4.15 Select the Arduino board



Fig. 4.16 Sketch the Arduino IDE



Fig 4.17 Compile and Upload to Board

4.8.5 Android App

The development of the Android app for Bluetooth speech-to-text conversion and robot control involved a meticulous process aimed at integrating various functionalities seamlessly. Leveraging Java programming language, the project began with establishing Bluetooth connectivity to facilitate communication between the app and the robot controller device. Subsequently, speech recognition capabilities were integrated using Android's Speech Recognizer API to accurately convert spoken words into text format. The processed text was then analyzed to identify relevant commands for controlling the robot, with robust logic implemented to ensure accurate interpretation and generation of corresponding control signals.

The user interface was meticulously designed to offer an intuitive experience, enabling users to input speech, view converted text, and interact with robot controls effortlessly. Rigorous testing and debugging phases ensured the app's reliability and performance across different scenarios, ultimately culminating in a successful outcome where users can control the robot effectively through voice commands transmitted over Bluetooth.

Throughout the development journey, each phase was meticulously crafted to ensure the seamless integration of Bluetooth communication, speech recognition, and robot control functionalities. The project commenced with an in-depth exploration of Bluetooth connectivity, encompassing device discovery, pairing, and establishing a reliable socket connection for data exchange. With the foundation laid, attention turned to implementing speech recognition capabilities, leveraging Android's speech Recognizer API to accurately capture and transcribe spoken words into text form.

This text underwent thorough processing, employing sophisticated algorithms to distill actionable commands for robot manipulation. The user interface design was a focal point, meticulously crafted to offer an intuitive and immersive experience, fostering seamless interaction with the app's features. Extensive testing protocols were executed, encompassing scenarios ranging from varying speech patterns to diverse environmental conditions, ensuring robustness and reliability across all fronts.

Through meticulous iteration and refinement, the final product emerged, embodying a harmonious fusion of technology and user-centric design, empowering users to effortlessly wield the power of voice to command and control their robotic counterparts.

As the project unfolded, a multifaceted approach was adopted to address the intricate requirements of Bluetooth speech-to-text conversion and robot control within the Android app ecosystem. Delving deeper into Bluetooth connectivity, meticulous attention was devoted to handling potential pitfalls such as signal interference and device compatibility, ensuring a seamless connection experience for users across a spectrum of devices. The integration of speech recognition capabilities delved into the nuances of natural language processing, with a focus on enhancing accuracy and responsiveness through continuous refinement and

optimization of recognition algorithms. Moreover, the text processing module underwent rigorous scrutiny, harnessing advanced parsing techniques and machine learning algorithms to discern intricate commands and execute them with precision.

The user interface design transcended mere aesthetics, embodying a holistic approach that prioritized usability and accessibility. User-centric design principles guided the development of intuitive interfaces, where fluid interactions and informative feedback mechanisms fostered a sense of empowerment and control for users navigating the app's functionalities. Beyond the realm of technical intricacies, the project underscored the importance of comprehensive testing methodologies, encompassing diverse usage scenarios and edge cases to fortify the app's resilience against real-world challenges.




Figure:4.18 Application for Speech Recognizer

Furthermore, the project served as a testament to the collaborative spirit, with multidisciplinary teams synergizing their expertise in software engineering, robotics, and human-computer interaction to realize a cohesive vision. Agile methodologies facilitated iterative development cycles, enabling swift adaptation to evolving requirements and stakeholder feedback. As the project culminated in the deployment of the Android app, it heralded not only a technological milestone but also a testament to the boundless potential of innovation in empowering users to engage with technology in transformative ways.




Figure:4.19 Application Interface

The application interface was meticulously crafted to provide users with an intuitive and seamless experience, facilitating effortless interaction with the Bluetooth speech-to-text conversion and robot control functionalities. The design ethos centered on simplicity, clarity, and accessibility, ensuring that users of all levels of technical proficiency could navigate the app with ease.

The interface featured distinct sections that catered to different aspects of the app's functionality. At the forefront was the speech input interface, where users could initiate voice commands by tapping a designated button or using a wake word activation feature. Visual cues, such as waveform animations or speech recognition indicators, provided feedback to users, reassuring them that their voice commands were being processed.

Once speech was captured and converted to text, the converted text was prominently displayed on the screen, ensuring visibility and legibility. Clear typography, appropriate spacing, and contrasting colors enhanced readability, even in varying lighting conditions or screen sizes. Users had the option to review and edit the converted text before sending it as a command to control the robot, empowering them with control and confidence over their interactions.

The robot control interface was thoughtfully designed to offer intuitive controls for manipulating the robot's movements or actions. Depending on the capabilities of the robot, the interface could include directional buttons, sliders for speed or intensity control, or predefined action buttons. Real-time feedback mechanisms, such as visual indicators or status updates, provided users with immediate confirmation of their commands' execution, fostering a sense of agency and engagement.

Throughout the interface design process, user feedback and usability testing played pivotal roles in refining and optimizing the user experience. Iterative design cycles enabled the identification and resolution of pain points or usability challenges, ensuring that the final interface was both functional and user-friendly. By prioritizing user needs and preferences, the application interface emerged as a cornerstone of the app's success, empowering users to interact with technology seamlessly and intuitively.

In addition to the core functionalities, the application interface incorporated supplementary features to enhance usability and accessibility. For instance, a settings menu allowed users to customize various aspects of the app according to their preferences. This included options to adjust speech recognition sensitivity, configure Bluetooth device settings, or customize the appearance of the user interface.

Furthermore, the interface seamlessly integrated feedback mechanisms to keep users informed about the app's status and ongoing processes. Visual indicators, such as loading animations or progress bars, provided real-time feedback during tasks like Bluetooth device discovery or speech recognition processing, keeping users engaged and informed about the app's actions. Accessibility features were also embedded within the interface to cater to users with diverse needs and preferences.

This encompassed support for alternative input methods, such as gesture controls or keyboard input, for users who may prefer or require non-verbal interaction. Additionally, the interface adhered to accessibility guidelines, ensuring compatibility with screen readers, high contrast modes, and other assistive technologies to accommodate users with disabilities.

Moreover, the application interface fostered a cohesive and immersive user

experience through consistent design elements and visual cues. Unified color schemes, iconography, and layout conventions maintained visual coherence across different sections of the app, facilitating seamless navigation and enhancing user the interface design process was informed by user-centered design principles, with extensive usability testing and feedback collection driving iterative refinements. User research, surveys, and usability studies provided valuable insights into user preferences, behaviors, and pain points, guiding interface design decisions and optimizations. The application interface served as a gateway for users to seamlessly interact with the Bluetooth speech-to-text conversion and robot control functionalities, embodying a harmonious fusion of functionality, usability, and accessibility.

4.8.6 Visual Studio Interface

From Figure 4.5.6 Visual studio Visual Studio Code (VS Code) is a highly popular, free, and open-source source code editor developed by Microsoft. It provides a comprehensive and customizable environment for software development, offering support for various programming languages, syntax highlighting, code completion, debugging, version control integration, and extensions.




Figure: 4.20 Visual studio

Visual Studio, a renowned integrated development environment (IDE) crafted by Microsoft, stands as a versatile toolkit catering to a spectrum of programming needs. While traditionally synonymous with languages like C# and .NET, Visual Studio extends its prowess to Java development through its lightweight counterpart, Visual Studio Code (VS Code). Within VS Code, developers find a rich array of features tailored to streamline Java coding endeavors. From syntax highlighting to seamless debugging support, VS Code empowers developers with essential tools for crafting robust Java applications.

Its integration with popular build tools like Maven and Gradle facilitates efficient project management, while extensions augment functionality, offering features like IntelliSense for enhanced code completion. The IDE's compatibility with Git enables seamless collaboration, fostering agile development workflows. With its customizable interface and vibrant community support, Visual Studio emerges as a compelling choice for Java developers seeking a versatile, user-friendly environment to realize their coding aspirations.

Visual Studio Code (VS Code) offers seamless integration with cloud platforms and services, enabling developers to deploy and manage Java applications with ease. Whether leveraging cloud-based development environments or deploying applications to cloud infrastructure, VS Code provides intuitive tools for interacting with cloud resources directly from the IDE. This integration streamlines the development lifecycle, empowering developers to focus on coding without the complexities of managing infrastructure.

Visual Studio fosters a vibrant community of developers, complemented by extensive documentation, tutorials, and resources readily available online. Developers can engage with forums, user groups, and official documentation to seek guidance, share insights, and stay abreast of the latest advancements in Java development with Visual Studio. This collaborative ecosystem not only facilitates knowledge sharing but also fosters innovation, driving continuous improvement and evolution within the Java development landscape supported by Visual Studio.

CHAPTER-5

RESULTS AND DISCUSSIONS

5.1 RESULT

From Fig 5.1 Writing Robot In this project to develop a writing robot for medical prescriptions utilizing Bluetooth connectivity to a mobile device and converting text to speech for the robot's writing mechanism represents a significant advancement in healthcare technology. By integrating this system with an Android application, healthcare professionals can streamline the prescription process, reducing errors and improving efficiency.

The Bluetooth connection ensures seamless communication between the mobile device and the robot, enabling quick transmission of prescription details. Utilizing text-to-speech technology enhances accessibility, allowing the robot to accurately transcribe spoken prescription instructions.

This innovative solution not only enhances the accuracy of prescriptions but also frees up valuable time for healthcare providers to focus on patient care, ultimately improving overall healthcare delivery. Moreover, the integration of modern technology in medical practices underscores the continuous evolution and adaptation of healthcare systems to meet the needs of patients and practitioners alike.




Figure: 5.1 Writing Robot



Fig :5.3 Robot Writing Medical prescription




Fig :5.4 output of Robot Writing Medical prescription

The writing robot's utilization of Bluetooth connectivity and speech-to-text technology ensures accuracy and efficiency in transcribing prescriptions. By converting spoken instructions from the Android app into written form, the robot generates legible and precise prescriptions, reducing the likelihood of errors due to illegible handwriting or transcription mistakes. Moreover, the output process can be tailored to accommodate various prescription formats, including medication names, dosages, frequencies, and any additional instructions.

CHAPTER-6

CONCLUSIONS AND FUTURE SCOPE

6.1 CONCLUSION

In conclusion, the development of a writing robot utilizing speech processing for medical prescription represents a promising advancement in healthcare technology. By harnessing the power of speech recognition algorithms and robotic mechanisms, this project aims to revolutionize the prescription writing process, addressing inefficiencies and improving patient safety. Through a comprehensive approach encompassing various aspects of design, development, and integration, the writing robot offers a potential solution to longstanding challenges in clinical documentation. The culmination of this project signifies a significant step forward in the quest to enhance efficiency, accuracy, and usability in healthcare settings.

6.2 FUTURE WORK

Looking forward, there are several avenues for future work and refinement in the realm of writing robot technology. Firstly, continued research and development efforts can focus on enhancing the accuracy and reliability of speech recognition algorithms, particularly in handling specialized medical terminology and diverse linguistic variations. Advancements in machine learning techniques and access to larger datasets could contribute to further improvements in speech processing performance. Moreover, future iterations of the writing robot could explore integration with advanced technologies such as natural language processing and artificial intelligence. By leveraging these technologies, the writing robot could evolve into a more intelligent system capable of providing real-time decision support to healthcare providers, thereby enhancing clinical decision-making and patient care outcomes.

Scalability and deployment are also critical considerations for future work. Strategies for widespread implementation and integration of the writing robot across diverse healthcare settings will be essential. Collaboration with healthcare institutions, software vendors, and regulatory bodies will be necessary to ensure seamless adoption, regulatory compliance, and support for large-scale deployment. Furthermore, ongoing optimization of the user experience will be paramount. Continuous refinement of the user interface and interaction design, informed by user feedback and usability testing,

feedback and usability testing, will contribute to making the writing robot more intuitive, efficient, and user-friendly for healthcare providers.

Finally long-term impact assessment is essential to evaluate the efficacy and benefits of the writing robot in real-world healthcare environments. Longitudinal studies monitoring the impact on clinical workflows, medication error rates, and patient outcomes will provide valuable insights into the effectiveness of the technology and inform further refinements and enhancements.

While the development of a writing robot using speech processing for medical prescription marks a significant achievement, there is still much to be explored and refined in this burgeoning field. Through ongoing innovation, collaboration, and research, the full potential of this technology can be realized, ultimately leading to improved healthcare delivery and patient outcomes.

REFERENCES

- [1] A. Fernández, J. L. Carús, R. Usamentiaga and R. Casado, "Face Recognition and Spoofing Detection System Adapted To Visually-Impaired People" IEEE Latin America Transactions, vol. 14, no. 2, Feb. 2016.
- [2] A. V. Panchal, S. C. Patel, K. Bagyalakshmi, P. Kumar, I. RazaKhan, M. Soni, "Image-based Plant Diseases Detection using Deep Learning", Materials Today:Proceedings,2021,ISSN-2214-7853, <https://doi.org/10.1016/j.matpr>.
- [3] Bing Li, J. Pablo Muñoz, Xuejian Rong, Qingtian Chen, Jizhong Xiao, Yingli Tian, Aries Arditi, Mohammed Yousuf. "Vision-based Mobile Indoor Assistive Navigation Aid for Blind People" Citation information: DOI 10.1109/TMC.2018.2842751, IEEE Transactions on Mobile Computing.
- [4] Cang Ye, and Xiangfei Qian "3D Object Recognition of a Robotic Navigation Aid for the Visually Impaired" Citation information: DOI 10.1109/TNSRE.2017.2748419, IEEE Transactions on Neural Systems and Rehabilitation Engineering.
- [5] Chih-Ming Hung, Alex TC Lin, BC Peng, Hua Wang, Jui-Lin Hsu, Yen-Ju Lu, Weishow Hsu, Jing-Hong Conan Zhan, Brian Juan, Chi-Hang Lok, Sam Lee, PC Hsiao, Qiang Zhou, Mark Wei, Hsiang-Yun Chu, Yu-Lun Chen, Chao-Ching Hung, Kevin Fong, Po-Chun Huang, Pierce Chen, Sheng-Yuan Su, Yan-Jiun Chen, Kehou Chen, Chun-Chao Tung, Yi-Jhan Hsieh, Tzung-Chuen Tsai, Yi-Fu Chen, Wei-Kuo Hsin, Liang Guo, Hanfei Liu, Dapeng Jin "Toward Automotive Surround-View Radars isscc 2019 / session 9 / high-frequency transceivers for radar and communications / 9.1".
- [6] George A. Miller, "WordNet: A Lexical Database for English", Communications of the ACM, 1995, Vol. 38, No. 11: 39-41.

- [7] J. Deng, W. Dong, R. Socher, L. -J. Li, Kai Li and Li Fei-Fei, "ImageNet: A large-scale hierarchical image database", 2009 IEEE Conference on Computer Vision Pattern Recognition, 2009, pp. 248-255, doi: 10.1109/CVPR.2009.5206848.
- [8] Kanstantsin Miatliuk, Adam Wolniakowski, Moises Diaz, Miguel, Jose J. Quintana Ferrer "Universal robot employment to mimic human writing".
- [9] M. Balaganesh, E. Sathyabama, "Robotic arm showing Writing Skills by Speech Recognition Collo Marketing Chennai, India 2016.
- [10] Milind Baviskar, Lakshman Korra, "Speech Based Writing Robotic Arm Using Arduino", IJIRCCE, ISSN: 2320-9801, Vol. 6, Issue 7, July 2018.
- [11] Mohammad Nasser Saadatzi, Joshua R. Baptist, Zhong Yang, Dan. O. Popa, "Modeling and Fabrication of Scalable Tactile Sensor Arrays for Flexible Robot Skins" DOI 10.1109/JSEN.2019.2915362, IEEE Sensors Journal.
- [12] Pooja Singh, Pinki Nayak, Arpita Datta, Depanshu Sani, Garima Raghav, Rahul Tejpal, "Voice Control Device Using Raspberry Pi", Amity School Of Engineering And Technology, New Delhi, India. 978-1-5386-9346-9/19/\$31 IEEE 2019.
- [13] R.Balatharangam, P.Madhu Priya, R.Pavithra, G.Prithviraj, U.Poornima "Design and development of Arduino controlled writing robot" R.B © 2017, IRJET.
- [14] Rezvan Nasiri, Mojtaba Rayati, and Majid Nili Ahmadabadi. "Feedback from Mono-articular Muscles is Sufficient for Exoskeleton Torque Adaptation" Citation information: DOI 10.1109/TNSRE.2019.2942385, IEEE Transactions on Neural Systems and Rehabilitation Engineering.
- [15] Robert Katzschmann, Brandon Araki, and Daniela Rus, "Safe Local Navigation for Visually Impaired Users with a Time-of-Flight and Haptic Feedback Device"

Citation information: DOI 10.1109/TNSRE.2018.2800665, IEEE Transactions on Neural Systems and Rehabilitation Engineering.

- [16] Russakovsky et al., "ImageNet Large Scale Visual Recognition Challenge", International Journal of Computer Vision, 2015, 115(3), 211- 252. <https://doi.org/10.1007/s11263-015-0816-y>.
- [17] S. D. Khirade, A. B. Patil, "Plant Disease Detection Using Image Processing", 2015 International Conference on Computing Communication Control and Automation, 2015, pp. 768-771, doi: 10.1109/IC_CUBEA.2015.153.
- [18] Sami Haddadin, Kai Krieger, Alin Albu-Schäffer, and Torsten Lilge "Exploiting Elastic Energy Storage for "Blind" Cyclic Manipulation: Modeling, Stability Analysis, Control, and Experiments for Dribbling" IEEE transactions on robotics, vol. 34, no. 1, February 2018.
- [19] Sania Khan, Sanskriti Verma, Shweta Agarwal, Prateek Krishnatrey, Shivam Sharma, "Voice Based Online Examination for Physically Challenged", MIT International Journal of Computer Science and Information Technology, Vol. 5, No. 2, August 2015, pp. 58-61.
- [20] Zachary A. Wright, Emily Lazzaro, Kelly O. Thielbar, James L. Patton, and Felix C. Huang, "Robot Training With Vector Fields Based on Stroke Survivors' Individual Movement Statistics" IEEE Transactions on Neural Systems and Rehabilitation Engineering, vol. 26, no. 2, February 2018.