


DESIGN AND DEVELOPMENT OF MOTOR MODULE FOR THE ADVANCEMENTS IN SMARTLIFT

Submitted in partial fulfillment of the requirements for the award of

Bachelor of Engineering Degree in
Electrical and Electronics Engineering

by

ABHAY VERMA (Register No. 40140001)



**DEPARTMENT OF ELECTRICAL AND ELECTRONICS ENGINEERING
SCHOOL OF ELECTRICAL AND ELECTRONICS**

SATHYABAMA

**INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)**

Accredited with Grade "A++" by NAAC

JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI - 600 119

APRIL 2024



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY

(DEEMED TO BE UNIVERSITY)


Accredited "A" Grade by NAAC | 12B Status by UGC | Approved by AICTE


www.sathyabama.ac.in

DEPARTMENT OF ELECTRICAL AND ELECTRONICS ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of ABHAY VERMA (Reg. No. 40140001) who carried out the project entitled "DESIGN AND DEVELOPMENT OF MOTOR MODULE FOR THE ADVANCEMENTS IN SMARTLIFT" under our supervision from November 2023 to April 2024.



Dr. V. SENTHIL NAYAGAM
Internal Guide



Dr. S. RADHIKA
Head of the Department


Submitted for Viva voce Examination held on 18.04.2024.


Name: 

Signature:


Internal Examiner


W Abitha M


External Examiner


(Dr. J. Lakshminarayanan)

DECLARATION

I ABHAY VERMA (Reg. No. 40140001) hereby declare that the Project Report entitled "DESIGN AND DEVELOPMENT OF MOTOR MODULE FOR THE ADVANCEMENTS IN SMARTLIFT" done by me under the guidance of Dr. V. SENTHIL NAYAGAM is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in Electrical and Electronics Engineering.

DATE: 12. 04. 2024

PLACE: Chennai



SIGNATURE OF THE CANDIDATE

ACKNOWLEDGEMENT

I am pleased to acknowledge my sincere thanks to Board of Management of **SATHYABAMA** for their kind encouragement in doing this project and for completing it successfully. I am grateful to them.

I convey my thanks to **Dr. N. M. Nandhitha, Dean, School of Electrical and Electronics Engineering** and **Dr. S. Radhika, Head of the Department, Dept. of Electrical and Electronics Engineering** for providing me necessary support and details at the right time during the progressive reviews.

I would like to express my sincere and deep sense of gratitude to my Project Guide **Dr. V. SENTHIL NAYAGAM** for his valuable guidance, suggestions and constant encouragement paved way for the successful completion of my project work.

I wish to express my thanks to all Teaching and Non-teaching staff members of the Department of Electrical and Electronics Engineering who were helpful in many ways for the completion of the project.

ABSTRACT

The "Design and Development of Motor Module for the Advancements in Smart Lift" represents a pioneering approach to address accessibility concerns within campus environments. By focusing on the creation of a smart standing lift system tailored specifically for campus staircases, the project aims to provide a reliable and convenient vertical mobility solution for individuals with mobility challenges. Central to this innovation is the integration of intelligent sensors and adaptive controls within the standing lift system. These technological features enable the lift to offer intuitive operation while catering to the diverse needs of users. Through meticulous design and implementation, the standing lift ensures not only safety but also seamless user experience, thus facilitating accessibility across campus premises. The paper delves into the intricate details of the design, implementation, and evaluation phases of the smart standing lift. It explores the engineering principles behind the motor module development, highlighting how each component contributes to the overall functionality and efficiency of the lift system. Moreover, the assessment aspect of the paper scrutinizes the lift's performance under various conditions, emphasizing its reliability and efficacy in real-world scenarios. Ultimately, this innovative solution holds significant promise in enhancing accessibility and streamlining mobility within campus settings. By leveraging cutting-edge technology and design principles, the smart standing lift represents a significant step towards creating inclusive environments where individuals of all abilities can navigate with ease and independence.

TABLE OF CONTENTS

CHAPTER NO.	TITLE	PAGE NO.
	ABSTRACT	v
	LIST OF FIGURES	viii
	LIST OF TABLES	ix
1	INTRODUCTION	
	1.1 GENERAL	10
	1.2 MOTIVATION FOR THE SELECTION OF PROBLEM	11
	1.3 OVERVIEW	12
2	LITERATURE SURVEY	
	2.1 INTRODUCTION	13
	2.2 MAJOR FINDINGS FROM LITERATURE SURVEY	16
	2.3 EXISTING SYSTEM BLOCK DIAGRAM OPEN	16
	2.4 PROBLEMS IN EXISTING SYSTEM	16
	2.5 DISADVANTAGES	17
	2.6 IEEE STANDARDS FOLLOWED	18
	2.7 CONSTRAINTS AND TRADEOFF	18

3	AIM AND SCOPE OF THE PRESENT INVESTIGATION	
3.1	AIM OF THE PROJECT	19
3.2	SCOPE OF THE PROJECT	19
3.3	OBJECTIVES	20
3.4	METHODOLOGY	20
3.5	PROPOSED SYSTEM BLOCK DIAGRAM AND EXPLANATION	22
	3.5.1 PLATFORM	22
	3.5.2 RAILS OR TRACK SYSTEM	23
	3.5.3 DRIVE MECHANISM	24
	3.5.4 POWER SOURCE	24
	3.5.5 CONTROL PANEL	25
3.6	ADVANTAGES	25
3.7	PROCESS CHART	26
3.8	APPLICATION	26
4	HARDWARE DESCRIPTION	36
4.1	INTRODUCTION	36
4.2	HARDWARE COMPONENTS	38
	4.2.1 0.5 HP 3 PHASE SQUIRREL CAGE INDUCTION MOTOR	38
	4.2.1.1 Induction Motor	39
	4.2.1.2 Working Principle of Induction Motor	39
	4.2.1.3 Types of Induction Motor	40

4.2.1.4	3 Phase Squirrel Cage Induction Motor	41
4.2.1.5	Construction	42
4.2.1.6	Characteristics	43
4.2.1.7	Squirrel Cage Induction Motor Is Smart Staircase Lift	44
4.2.1.8	Advantages	46
4.2.1.9	Applications	47
4.2.1.10	Comparison Between Squirrel Cage And Slip Ring	49
4.2.2	LT CONTROL SWITCH	50
4.2.3	GEAR BOX	51
4.2.4	RAIL SYSTEM	53
4.2.5	WIRES	55
4.2.6	FOOT STEP	56
4.3	HARDWARE RESULT	57
5	SUMMARY AND CONCLUSION	
5.1	SUMMARY	27
5.2	CONCLUSION	27
	REFERENCES	28

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE NO.
2.1	Existing System Block Diagram	16
3.1	Proposed System Block Diagram	22
3.2	Flat Platform	23
3.3	Rails or Track System	23
3.4	Drive System	24
3.5	Process Chart	35
4.1	Torque-Speed Characteristics	43
4.2	0.5HP 3 Phase Squirrel Cage Induction Motor	44
4.3	Name Plate Details of The Motor	45
4.4	LT Control Switch	50
4.5	Worm Gear Box	52
4.6	Rail Track with Sprocket	54
4.7	3 Core Wire	55
4.8	Foot Rest	57
4.8	Smart Staircase Lift	58

LIST OF TABLES

TABLE NO.	TITLE	PAGE NO.
3.1	Applications	26
3.2	Motor Specifications	46
3.3	Comparison Between Squirrel Cage and Slip Ring Induction Motor	49
3.4	Worm Gear Box Specifications	52
3.5	Rail System Specifications	54

CHAPTER 1

INTRODUCTION

1.1 GENERAL

Accessing buildings via stairs presents a formidable obstacle for individuals relying on wheeled mobility aids or contending with age-related mobility constraints. The gravity of this challenge cannot be overstated. In Bangladesh, a considerable number of individuals aged 65 and beyond encounter difficulties ascending steps without frequent pauses, with many resorting to wheelchairs for assistance. Conventional remedies for this accessibility dilemma often entail either installing a lift where feasible or relocating to housing equipped with such amenities. However, these options come at a steep price, and there are instances where lift installation is simply not viable. Consequently, a considerable portion of the population remains underserved. Moreover, the existing stairlift solutions available on the market are often exorbitantly priced, exacerbating the issue of affordability. This endeavour aims to address these shortcomings by developing a cost-effective stairlift solution that is easy to deploy and minimally intrusive in residential settings. The proposed design approach centres on utilizing a chain drive mechanism, with the goal of providing a practical and user-friendly mobility solution for individuals with disabilities.

Stairlifts come in several categories tailored to different needs:

1. Straight Stairlifts: For staircases without curves or turns, these are the simplest and most common type.
2. Curved Stairlifts: Custom-built for staircases with curves or landings, offering seamless navigation.
3. Outdoor Stairlifts: Designed to withstand outdoor conditions, providing accessibility to entrances and outdoor spaces.
4. Platform Stairlifts: Accommodate wheelchairs or scooters, allowing users to remain seated while being transported.
5. Standing Stairlifts: For users who prefer or require a standing or perched position rather than sitting.

While elevators are acknowledged for their efficiency in terms of speed, capacity, vertical reach, and user-friendliness, their installation poses challenges due to space requirements and the substantial costs incurred not only in purchasing but also in maintaining them. Consequently, their adoption within typical residential environments is limited. Furthermore, commercially available stairlifts often come with hefty price tags. Therefore, the objective of this endeavour is to engineer an affordable stairlift solution tailored to the needs of individuals with disabilities. This solution aims to minimize installation complexities and aesthetic disruptions to home environments. This paper investigates the creation of a stairlift operated by a chain drive mechanism, delving into the intricacies of its design and development process.

1.2 MOTIVATION FOR THE SELECTION OF PROBLEM

The impetus behind this research primarily stems from the necessity for an affordable and easily installable lifting solution. Conventional lifts are prohibitively expensive, and their maintenance costs are exorbitant. In older buildings lacking adequate space for lift installation or in two/three-story structures, stair use poses significant hazards for individuals with physical disabilities. Moreover, manoeuvring heavy materials and equipment up and down stairs is arduous. Hence, the focus of this study is on devising a cost-effective lifting system that addresses these challenges while also enhancing accessibility and safety for individuals with disabilities.

- **Accessibility:** Stairlifts provide individuals with mobility limitations easy access to different levels of a building, eliminating the need to navigate stairs independently.
- **Safety:** Stairlifts are equipped with safety features such as seat belts, sensors, and braking systems to ensure users remain secure during transit.
- **Independence:** Stairlifts empower users to move between floors independently without relying on assistance from others, enhancing their sense of autonomy and freedom.
- **Comfort:** Stairlifts typically feature padded seats or platforms, armrests, and footrests, providing users with a comfortable and stable seating or standing position during transportation.

- Convenience: Users can effortlessly glide up or down stairs at the touch of a button, eliminating the physical exertion and potential risk associated with climbing stairs manually.
- Versatility: Stairlifts come in various configurations to accommodate different staircase designs, including straight, curved, and outdoor staircases, making them suitable for a wide range of environments.
- Space-saving: Stairlifts require minimal space and can be installed without major structural modifications, making them ideal for homes or buildings with limited space.
- Customization: Stairlifts can be customized with additional features such as adjustable seat heights, swivel seats, and remote controls to meet individual user preferences and needs.
- Reliability: Modern stairlifts are built with durable materials and undergo rigorous testing to ensure reliability and longevity, providing users with a dependable mobility solution.
- Improved Quality of Life: By enabling individuals with mobility challenges to navigate stairs safely and independently, stairlifts contribute to an improved quality of life, allowing users to remain active and engaged in their daily activities

1.3 OVERVIEW

In today's rapidly evolving and interconnected global landscape, the relentless pursuit of accessibility, convenience, and self-sufficiency underscores a fundamental ethos of human progress. This drive permeates various facets of life, with particular emphasis on mobility, where empowering individuals facing physical limitations has spurred a wave of technological innovation.

Traditional staircases pose significant barriers for countless individuals grappling with mobility constraints. These structures impede everyday activities and compromise the independence of those affected. Simple tasks like navigating between floors within one's home or accessing public spaces can become daunting challenges, often accompanied by frustration and physical strain. Such limitations not only curtail personal autonomy but also contribute to feelings of exclusion and social isolation.

The Smart Standing Staircase Lift with Flat Platform project represents a pioneering initiative to confront these pervasive challenges head-on. By envisioning a future where mobility constraints are overcome, this innovative solution aims to redefine the very essence of vertical movement. At its core, the project seeks to develop a cutting-edge standing staircase lift equipped with a flat platform, seamlessly adaptable to diverse environments ranging from private residences to bustling public areas.

Through prioritizing flexibility, safety, and user-centric design, the project endeavours to revolutionize perceptions surrounding accessibility. By offering individuals with mobility limitations a dignified and effortless means of navigation, the Smart Standing Staircase Lift with Flat Platform project embodies a commitment to inclusivity and social equity. It heralds a future where barriers to mobility are dismantled, enabling all individuals to fully participate in and contribute to society's fabric.

In an increasingly interconnected and innovative world, the quest for accessibility, convenience, and independence knows no bounds. The desire to empower individuals with mobility challenges to navigate their surroundings effortlessly and with dignity has given rise to numerous technological advancements. Among these innovations, the Smart Standing staircase Lift with Flat Platform project emerges as a beacon of hope, promising a life-enhancing solution for those who face the daily challenge of traversing stairs.

For individuals with mobility limitations, traditional staircases represent formidable obstacles. Tasks as simple as moving between floors within their own homes or accessing public buildings can become arduous and, at times, impossible. The constraints imposed by standard staircases undermine personal freedom, restrict access to spaces, and can even lead to isolation.

The Smart Standing Staircase Lift with Flat Platform project envisions a future where mobility constraints are a thing of the past. This groundbreaking innovation aims to revolutionize the way we think about vertical movement, providing a versatile, safe, and user-friendly solution. The core idea behind this project is to design and develop a state-of-the-art standing staircase lift with a flat platform that seamlessly integrates into various environments, including private residences and public spaces.

CHAPTER 2

LITERATURE SURVEY

2.1 INTRODUCTION

A literature survey on "Smart Standing Staircase Lift Systems" entails a thorough examination of scholarly literature concerning the design, functionality, and performance of such innovative mobility solutions. The smart standing staircase lift represents a pivotal advancement in accessibility technology, necessitating an in-depth analysis of existing research and theoretical frameworks. This survey would delve into various aspects, including but not limited to, ergonomic design principles, user interface technologies, safety mechanisms, integration of sensors and automation, and human-machine interaction paradigms. Moreover, it would explore the incorporation of IoT connectivity, AI algorithms for predictive maintenance, and data analytics for optimizing user experience and operational efficiency. By conducting a comprehensive literature survey, researchers can gain insights into the current landscape of smart standing staircase lift systems, identify gaps in knowledge, and pinpoint avenues for future research and development in this domain. Furthermore, the literature survey would encompass a critical examination of case studies and real-world implementations of smart standing staircase lift systems across various settings, including residential, commercial, and public spaces. By analyzing the successes, challenges, and lessons learned from these deployments, researchers can gain practical insights into the factors influencing the adoption, usability, and maintenance of such systems. Additionally, the survey would explore regulatory frameworks and standards governing accessibility technology, as well as societal perspectives on inclusive design and assistive technology acceptance. Through this holistic approach, researchers can develop a comprehensive understanding of the opportunities and constraints in the development and deployment of smart standing staircase lift systems, thereby informing future advancements and policy considerations in the field.

2.2 MAJOR FINDINGS FROM LITERATURE SURVEY

An elevator or lift is a vertical transport equipment that efficiently moves people or goods between floors (levels) of a building, or of other structure. Elevators are generally powered by electric motors that either drive traction cables or counterweight systems like a hoist or pump hydraulic fluid to raise a cylindrical piston like a jack. Because of wheelchair access laws, elevators are often a legal requirement in new multi-storey buildings, especially where wheelchair ramps would be impractical. A stairlift is a mechanical device for lifting people and wheelchairs up and down stairs. For sufficiently wide stairs, a rail is mounted to the treads of the stairs. A chair or lifting platform is attached to the rail. A person on the chair or platform is lifted as the chair or platform moves along the rail.

Stairlifts are known variously as stair lifts, stair-lifts, chair lifts, stair gliders and by other names. This type of chair lift should not be confused with the chairlift used by skiers. As the name suggests stair case lift is a type of lift that can be mounted on the stock stair case without altering civil structure. This lift of course runs on electric power and consists of a motor two rails a sliding chair. This stair case lift can be mounted stock stair case where the civil structure is not be altered; and still handicapped old age and goods are to be carried across the stair case. These actual size stair case lift will be on could with at which can be assembly, and mounted and wheel as disassembled and mounted.

In the middle 1800s, there were many types of crude elevators that carried freight. Most of them ran hydraulically. The first hydraulic elevators used a plunger below the car to raise or lower the elevator. A pump applied water pressure to a plunger, or steel column, inside a vertical cylinder. Increasing the pressure caused the elevator to ascend. The elevator also used a system of counter-balancing so that the plunger did not have to lift the entire weight of the elevator and its load. The plunger, however, was not practical for tall buildings, because it required a pit as deep below the building as the building was tall. Later a rope-gearred elevator with multiple pulleys was developed.

The development of elevators was led by the need for movement of raw materials including coal and lumber from hillsides. The technology developed by these industries and the introduction of steel beam construction worked together to provide the passenger and freight elevators in use today. Lifts are invented long back ago. But installation of lift involves ample amount of cost intensive of rails, motor honk, civil structures. If lifts to be installed in the stalk structure, then it be alteration cost is too much. To overcome all these factors and to civil construction cost the concept of stair case lift come with being which reduced extra costing associated with the lift mechanism, the benchmark of the system is that this concept is associated with simplifying as well. Some people argue that lifts began as simple rope or chain hoist. A lift is an essential platform that is either pulled or pushed up by a mechanical means. A modern-day lift when consists of a cab (also called a "cage" or "car") mounted on a platform within an enclosed space called a shaft or sometimes a "hoistway". In the past, lift drive mechanisms were powered by steam and water hydraulic pistons or by hand. In a "traction" lift, cars are pulled up by means of rolling steel ropes over a deeply grooved pulley commonly called a sheave in the industry. The friction between the ropes and the pulley furnishes the traction which gives this type of lift its name.

Hydraulic lifts use the principles of hydraulics (in the sense of hydraulic power) to pressurize an above ground or in-ground piston to raise and lower the car. Roped hydraulics use a combination of both ropes and hydraulic power to raise and lower cars. Recent innovations include permanent magnet motors, machine room-less rail mounted gearless machines, and microprocessor controls. The technology used in new installations depends on a variety of factors. Hydraulic lifts are cheaper, but installing cylinders greater than a certain length becomes impractical for very high lift hoist ways. For buildings of much over seven storey's, traction lifts must be employed instead. Hydraulic lifts are usually slower than traction lifts. Lifts are a candidate for mass customization.

In the year of 2000, a group of researchers [1] introduced a rover type of vehicle to run over stepped path. Using a rhombus configuration, the rover had one wheel mounted on a fork in the front, one wheel in the rear and two bogies on each side. Researchers around the world are thinking seriously to redesign such vehicle, which will be economical and affordable. Chang Hsueh-Er [2] developed a five-wheeler

trolley, which was driven by manual power. Anastasios et al. [3] and D. Helmick et al. [4] designed a robotic carrier with belt driven. No wheel was introduced in his robotic carrier. However, none of them think about automatic vehicle that can carry loads through stairs. In various research projects all over the world the different locomotion concepts for mobile robots have been analyzed and new concepts have been proposed [5, 6]. Good general surveys are provided in [5-12]. In [8] over 300 mobility concepts and more than 400 navigation concepts have been generated and discussed, yielding to three candidate systems, a symmetrical walker with six identical legs, a four-wheeled vehicle and a so called attached scout concept with six wheels.

In this article the design and manufacturing of a stair climbing vehicle has been presented. The vehicle is designed in such a way that it can climb a stepped path (like stairs) with its modified wheel structure. Not only on the stairs, can it also move with load over flat or rocky surface. This is the individuality of this vehicle. Different speed combinations are incorporated depending on the working condition through simple gear arrangement, powered by the local motor drive. Speed reduction at any desired rate, is possible to establish over the existing ratio. Wheeled rovers are the optimal solutions for well structured environment like roads or habitations. But off-the road, their efficiency is very dependent on the typical size of encountered obstacles that have to be overcome in a standard motion mode. This is the case for [13-15], which can typically overcome obstacles of their wheel size, if friction is high enough. Adding real climbing abilities to a wheeled rover requires the use of a special strategy and often implies dedicated actuators like [16, 17] or complex control procedure like [18, 19].

A group of Indian students designed and fabricated [20] a stairlift for material handling system using rope drive. Some Japanese students did a project on stairlift [21] and the aim of this project was to supply a new, cost-effective stair lift for wheelchair users. For this purpose, a new mechanism, known as "crawl type," has been developed. This system was composed of three parts: traction guides, drive guides, and a hoist carrier.

2.3 EXISTING SYSTEM BLOCK DIAGRAM




Fig 2.1: Existing system block diagram

A smart standing staircase lift with a chair integrates cutting-edge technology to provide enhanced mobility assistance for users with varying needs. At the heart of this system lies a sophisticated block diagram, encompassing crucial components such as the power supply, switch, motor, rails and tracks, chair, proximity sensor, and controller. The power supply serves as the backbone, ensuring uninterrupted energy provision to all system elements. Fig 2.1 Explains about the working of the existing system. The switch acts as the interface through which users initiate the lift operation, offering intuitive and user-friendly control. The motor, meticulously engineered for efficiency and reliability, drives the movement of the lift along the rails and tracks, facilitating smooth vertical transportation. The chair, meticulously designed with ergonomic considerations in mind, offers a comfortable and secure seating arrangement for users throughout their journey. A proximity sensor enhances safety by detecting obstacles or obstructions along the lift's path, triggering immediate adjustments or halting operations if necessary. Crucially, the controller orchestrates the harmonious interaction of these components, overseeing lift operations, monitoring system health, and implementing safety protocols in real-time. Together, these intricately integrated components form a robust and intelligent smart standing staircase lift with a chair, poised to revolutionize accessibility and enhance user independence in diverse environments.

In addition to the core components, the smart standing staircase lift with a chair also incorporates advanced features to elevate user experience and safety standards. This includes the integration of wireless connectivity options, allowing users to remotely control the lift operation via smartphones or other smart devices. Furthermore, the inclusion of advanced sensors and machine learning algorithms enables the lift to adapt to user preferences and environmental conditions, optimizing performance and energy efficiency. Additionally, the implementation of real-time monitoring and diagnostics capabilities empowers maintenance personnel to proactively identify and address potential issues, minimizing downtime and ensuring continuous operation. Moreover, the incorporation of customizable settings and personalized user profiles enhances accessibility for individuals with specific mobility requirements. By embracing state-of-the-art technologies and user-centric design principles, the smart standing staircase lift with a chair sets a new standard for accessibility solutions, offering unparalleled convenience, safety, and inclusivity for users of all abilities.

2.4 OPEN PROBLEMS IN EXISTING SYSTEM

Fig 2.1 shows Existing system block diagram. In this Existing system chair is implemented to help individuals with limited mobility move up and down stairs while seated in it. A motor moves the chair along a rail system attached to the staircase, allowing for smooth and safe transportation up or down stairs. Safety features, such as sensors to detect obstructions and emergency stop buttons, are in place to ensure the user's safety during the operation.

Cost-effectiveness: One of the primary challenges facing the widespread adoption of smart standing staircase lift systems is their cost. These systems often involve complex components, advanced technology, and customized installation, leading to high upfront expenses. Moreover, ongoing maintenance and service costs can further burden users and facility owners. Finding ways to reduce costs without compromising safety and quality is essential. This could involve innovations in manufacturing processes, materials, and component sourcing, as well as exploring alternative business models such as leasing or shared ownership arrangements.

Space constraints: Many buildings, particularly older ones or those with limited floor space, may pose challenges for installing smart standing staircase lift systems. Traditional staircases may lack the necessary structural support or clearance required for retrofitting lifts, making installation difficult or impractical. Overcoming these space constraints while maintaining compliance with building codes and safety standards is a significant hurdle. Solutions may involve redesigning lift components to be more compact, exploring alternative installation methods, or even reconfiguring building layouts to accommodate lift systems more effectively.

User interface and accessibility: Ensuring that smart standing staircase lift systems are accessible and user-friendly for individuals with diverse abilities is paramount. However, current user interfaces may not always meet the needs of all users, particularly those with disabilities or older adults. Enhancing accessibility features such as voice commands, tactile feedback, or customizable user interfaces can improve usability for a broader range of users. Additionally, considering the ergonomic design of seating arrangements and control interfaces can enhance comfort and usability for all users.

Reliability and maintenance: Maintaining the reliability and longevity of smart standing staircase lift systems is crucial for user safety and satisfaction. However, like any mechanical or electronic system, lifts are subject to wear and tear over time. Developing robust maintenance protocols, including regular inspections, preventive maintenance schedules, and swift repair services, is essential to minimize downtime and ensure optimal performance. Additionally, implementing predictive maintenance technologies, such as condition monitoring sensors and data analytics, can help identify potential issues before they escalate into costly failures.

Integration with existing infrastructure: Integrating new lift systems with existing building infrastructure can be complex, particularly in retrofitting scenarios. Compatibility issues with staircases, electrical systems, and building codes may arise, requiring careful planning and coordination. Standardization efforts and interoperability solutions can help streamline integration processes and ensure compatibility across different environments. Collaborating with architects, engineers,

and building managers during the design and planning phases can facilitate smoother integration and minimize disruptions.

Safety and regulatory compliance: Ensuring that smart standing staircase lift systems meet stringent safety standards and regulatory requirements is paramount. Lifts must adhere to a range of safety regulations and building codes to protect users from accidents and ensure compliance with legal obligations. Keeping abreast of evolving regulations and industry standards, as well as implementing the latest safety technologies and best practices, is essential to mitigate risks and ensure user safety.

Energy efficiency: Optimizing energy consumption and minimizing environmental impact are increasingly important considerations in the design and operation of smart standing staircase lift systems. Lifts often consume significant amounts of electricity, particularly during peak usage periods. Developing energy-efficient components, such as low-power motors and LED lighting, and implementing smart energy management strategies, such as regenerative braking and occupancy sensing, can help reduce the environmental footprint of lift systems. Additionally, exploring alternative power sources such as solar or battery storage can further enhance energy efficiency and sustainability.

Addressing these open problems will require a concerted effort from stakeholders across various disciplines, including researchers, engineers, designers, policymakers, and end-users. The current system gives solution for the existing problems like user accessibility, space requirement, wastage of energy, weight limitations and cost-effectiveness fault that are faced by the users.

2.5 DISADVANTAGES

- Higher costs.
- Weight limitations.
- More space requirement.
- Wastage of energy

2.6 IEEE STANDARDS FOLLOWED

The Institute of Electrical and Electronics Engineers (IEEE) has several standards related to the smart standing staircase lift technology. Some of these standards include:

1. IEEE 1100 - IEEE Recommended Practice for Powering and Grounding Electronic Equipment

This standard provides guidance on electrical grounding practices and can be relevant for the electrical components of a smart stairlift system.

2. IEEE 802.11 - IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements

If the smart stairlift system uses wireless communication for authentication, you might refer to IEEE 802.11 for wireless networking standards.

3. IEEE 802.1X - IEEE Standard for Local and Metropolitan Area Networks - Port-Based Network Access Control

This standard might be applicable if you are implementing port-based network access control for password authentication in the smart stairlift system.

4. IEEE 90 - IEEE Guide for the Protection of Electric Generating Plants and Associated High Voltage Direct Current Converter Stations

While this standard primarily relates to power generation plants, it can provide guidance on electrical protection systems, which might be relevant for safety in the context of a smart stairlift.

2.7 CONSTRAINTS AND TRADE-OFF

CONSTRAINTS:

1. **Cost:** The acquisition and installation of current methods, such as traditional standing lifts, often entail considerable expenses. These costs can pose a significant barrier for individuals or organizations operating within constrained budgets, limiting their ability to afford and implement these solutions effectively.
2. **Space:** The restricted spatial dimensions of staircases, particularly in narrow or compact residential or commercial settings, present a notable constraint for lift installation. In such environments, the feasibility of installing a lift without extensive structural modifications may be severely limited, posing logistical challenges and potentially requiring costly alterations to accommodate the lift system.
3. **Complex Installation:** The installation of these lift systems is characterized by its intricate and labor-intensive nature, necessitating the expertise of skilled technicians and thorough planning to navigate the complexities involved. This complexity can result in prolonged installation times and potential disruptions to regular operations, impacting both convenience and cost-effectiveness.
4. **Energy Consumption:** Another noteworthy constraint pertains to the significant energy consumption associated with current lift methods. High energy usage not only leads to elevated operational costs but also raises environmental apprehensions due to increased carbon emissions and resource depletion. Mitigating these concerns necessitates the exploration of energy-efficient alternatives and sustainable practices to minimize the environmental footprint of lift operations.

TRADEOFF

1. **Cost vs. Features** : Users must balance budget constraints with desired features when selecting a lift system. Advanced features may enhance functionality but come at a higher cost, requiring careful consideration to ensure optimal value for money.
2. **Space Efficiency vs. Capacity**: Choosing between space-saving designs and lift capacity involves evaluating spatial constraints and user needs. Smaller lifts save space but have lower weight limits, requiring users to prioritize space efficiency while ensuring sufficient capacity.
3. **Energy Efficiency vs. Performance**: Optimal energy efficiency may require trade-offs in lift speed and performance. Users must consider energy-saving measures alongside preferences for lift responsiveness, striking a balance between environmental impact and operational performance.
4. **Safety vs. Accessibility**: Balancing safety features with accessibility requirements is essential for user well-being. While rigorous safety measures enhance protection, they may introduce complexities or limitations that affect accessibility, necessitating careful consideration of user needs and regulatory standards.

CHAPTER 3

AIM AND SCOPE OF THE PRESENT INVESTIGATION

3.1 AIM OF THE PROJECT

The primary objective underlying the development of a staircase standing lift with a flat platform is to furnish individuals facing mobility challenges with a pragmatic and pioneering solution, meticulously engineered to facilitate their safe and efficient navigation of staircases. These innovative mobility aids are purposefully crafted to confront head-on the myriad limitations and hurdles presented by staircases, regardless of whether they are encountered within the confines of residential abodes, sprawling public edifices, or any other architectural setting. By providing a level and stable platform upon which users can confidently stand, these lifts endeavour to transcend mere functionality, aiming instead to redefine the landscape of accessibility and independence. Through the provision of such assistive technology, individuals grappling with disabilities or constrained mobility are afforded not only enhanced physical mobility but also a profound elevation in their quality of life, fostering a newfound sense of empowerment and enabling them to navigate their environments with unprecedented freedom and dignity.

3.2 SCOPE OF THE PROJECT

The scope of a project involving the design, development, and implementation of a staircase standing lift with a flat platform is comprehensive and multifaceted. It encompasses various phases, including conceptual design, engineering, safety compliance, customization, installation, testing, user training, maintenance planning, market research, cost analysis, documentation, environmental considerations, regulatory approvals, and marketing strategies. This project requires collaboration among multidisciplinary teams to ensure the lift's safe and efficient operation while meeting the needs of individuals with mobility challenges and enhancing their independence and quality of life.

3.3 OBJECTIVES

- Design and develop a smart stair lift system that prioritizes the comfort, safety, user-friendliness and dignity of disabled and elderly users.
- Emphasize the importance of maintaining dignity and independence for disabled and elderly populations through the use of this technology.
- Improve accessibility in both private and public spaces that can be easily integrated into various environments.
- To make cost-effective technology, ensuring that it is accessible to a wide range of users and facilities.
- Create a range of customizable options to accommodate individual needs and preferences, including different lift sizes, seating arrangements, and control mechanisms.
- Develop comprehensive user training materials and support systems to assist individuals in using the smart stair lift effectively.
- Conduct thorough testing, including user trials and safety assessments, to ensure the reliability and effectiveness of the smart stair lift system.
- Incorporate eco-friendly and sustainable design principles into the project to minimize its environmental impact.

3.4 METHODOLOGY

- Initiation and Planning – Defining the objectives, scope, including the specific features and functionalities of the next-generation stair lift.
- Investigate the latest technologies relevant to vertical mobility and accessibility.
- Market Research and Needs Assessment to understand the current state of stair lifts and the needs of disabled and elderly populations.
- Identification of project team members, and their roles.
- Develop a project plan with timelines, milestones, and deliverables.
- Establishment of budget and allocation of resources
- Incorporate feedback from potential users and experts into the design.

- Assess the feasibility of implementing advanced features such as sensors, AI, and connectivity.
- Develop detailed design specifications
- Create initial prototypes and mock-ups to visualize the product.
- Build a working prototype or minimum viable product (MVP) based on the design.
- Conduct rigorous testing, including usability testing, safety testing, and performance testing for compliance with safety and industry standards.
- Iterate on the design and development based on test results and user feedback.
- Ensure that the stair lift complies with relevant accessibility standards and regulations.
- Focus on improving the user experience through user-friendly interfaces and controls.
- Integrate connectivity options such as Wi-Fi or Bluetooth for remote control and monitoring.
- Explore AI and machine learning capabilities to enhance the stair lift's functionality.
- Conduct quality assurance tests to ensure each unit meets specified standards.
- Develop an installation manual for technicians and ensure proper installation.
- Provide user training materials and support for end-users.
- Conduct a pilot test with a small group of users to gather real-world feedback.
- Make necessary improvements based on user experiences.
- Maintain comprehensive project documentation throughout the development process.
- Ensure the installation is done according to manufacturer's guidelines and local building codes.
- Perform safety tests to confirm the proper functioning of the lift.
- Ensure that the lift is properly connected to a power source, and that the electrical components are installed safely. It may require an electrician's services.

3.5 PROPOSED SYSTEM BLOCK DIAGRAM AND EXPLANATION




Fig 3.1: Proposed System Block Diagram

Fig 3.1 shows Proposed system block diagram. The smart standing staircase lift with a flat platform incorporates a range of components to provide safe, reliable, and accessible vertical transportation for users. The power supply ensures continuous operation by providing electrical energy to the system, while the switch serves as the user interface for initiating lift operation and activating safety features. The motor with gearbox converts electrical energy into mechanical motion, driving the lift platform along the rails and tracks in a smooth and stable manner. The flat platform offers a spacious and secure load-bearing surface for users to stand or sit during travel, complemented by the footrest for additional support and safety. Proximity sensors detect obstacles along the lift path, ensuring safe operation by triggering safety measures to prevent collisions or accidents. At the heart of the system, the controller coordinates the operation of all components, interpreting user commands, controlling the motor, and implementing safety protocols to ensure optimal performance and user safety. Together, these integrated components form a sophisticated lift system that enhances mobility and independence for individuals with diverse needs in various residential, commercial, and public settings. The design of the lift platform prioritizes accessibility and inclusivity, with ample space to accommodate individuals with mobility aids such as wheelchairs, walkers, or crutches. The flat platform design eliminates the need for steps or ramps, providing seamless access for users with mobility challenges. Furthermore, the lift system incorporates intuitive controls and ergonomic features to enhance user experience, including tactile buttons, clear signage, and adjustable handrails for added stability.

3.5.1 PLATFORM

Description: The flat platform depicted in Fig 3.2 is the central component of the lift, serving as the primary and most visible element. It acts as the user's foundation during transportation, providing a secure and stable surface for users to stand on or sit if the lift includes a foldable or swivel seat.

Materials: Platforms are typically constructed from robust materials such as steel or aluminum, chosen for their exceptional strength and durability. These materials ensure that the platform can withstand the rigors of daily use and support the weight of multiple passengers without compromising its structural integrity.



Fig 3.2: Flat Platform

Design Considerations: The design of the platform is meticulously considered to meet the diverse needs of users, including those with mobility aids such as wheelchairs or mobility devices. The platform is engineered to provide ample space, accommodating users of varying sizes comfortably. Additionally, it often features a non-slip surface to enhance user safety, reducing the risk of slips or falls, especially in environments prone to moisture or slippery conditions.

Safety: Safety is paramount in the design of the platform, with several features incorporated to ensure that users feel secure and stable during transit. Safety edges or barriers are often integrated into the platform design to prevent accidental falls or

entrapment. These safety mechanisms are strategically positioned to detect obstructions along the lift path and trigger automatic stops, enhancing user protection and confidence during lift operation.

3.5.2 RAILS OR TRACK SYSTEM

Description: The rail system depicted in Fig 3.3 plays a fundamental role in guiding the movement of the lift along the staircase. Comprising rails or tracks, this system determines the lift's path and stability during operation, ensuring smooth and precise movement along the designated route.

Materials: Rails are typically constructed from robust materials such as steel or aluminum, chosen for their exceptional durability and resistance to wear. These materials are well-suited for supporting the weight of the lift and its passengers while withstanding the stresses and strains of repeated use over time.



Fig 3.3: Rails Or Track System

Configuration: The rail system is customized to match the specific configuration of the staircase, whether it's straight or curved. Precision engineering is employed to ensure that the rails are precisely aligned and securely mounted to the staircase structure, facilitating smooth and reliable movement of the lift platform. Additionally, rails may be modular in design, allowing for flexibility in installation and adaptation to various staircase layouts.

Safety: Proper installation and maintenance of the rail system are crucial for the safety and reliability of the lift. The track system must securely support the entire lift structure and user, providing a stable and secure path along the staircase. Regular inspection and maintenance of the rails are essential to detect any signs of wear, damage, or misalignment that could compromise safety or performance. Additionally, safety features such as rail guards or bumpers may be incorporated to further enhance user protection and prevent accidents or collisions during lift operation

3.5.3 DRIVE MECHANISM

Description: The drive system depicted in Fig 3.4 is a critical component responsible for propelling the lift along the rail system. Serving as the driving force behind lift movement, the drive mechanism converts power from the primary power source into mechanical motion, enabling the lift to traverse the designated path along the staircase.

Types: Various drive mechanisms are employed in lift systems, each offering unique advantages and considerations. Cable-driven systems utilize cables and pulleys to transmit motion, offering smooth operation and relatively low maintenance requirements. Rack and pinion mechanisms employ gear systems to drive the lift, providing precise control over speed and position. Screw-driven systems utilize threaded screws to lift or lower the platform, offering exceptional stability and reliability.



Fig 3.4: Drive System

Power Source: The drive mechanism is powered by the lift's primary power source, typically electricity sourced from the building's main electrical grid. It is essential to ensure that the lift has a reliable and uninterrupted power supply to operate efficiently. In instances where power outages may occur, battery backup systems are essential to ensure continuous operation and passenger safety. Battery backup systems provide temporary power to the drive mechanism during power interruptions, allowing the lift to safely return to a designated landing or complete its current journey without compromising user safety or comfort.

3.5.4 POWER SOURCE

Description: The power source serves as the primary energy supply for the lift's operation, providing the necessary electrical energy to power its various components and facilitate vertical transportation along the staircase. It is an essential component that ensures the lift operates reliably and efficiently, meeting the needs of users with diverse mobility requirements.

Primary Source: The primary source of power for the lift is typically electricity sourced from the building's mains. This reliable and consistent power supply ensures continuous operation of the lift, allowing users to access different levels of the building safely and conveniently. Electricity from the mains powers the motor, control system, lighting, and other electrical components of the lift, enabling smooth and efficient operation under normal operating conditions.

Battery Backup: In addition to the primary electrical supply, the lift is equipped with a battery backup system to ensure uninterrupted operation during power outages or emergencies. The battery backup system serves as a secondary power source, providing emergency power to critical lift components such as the motor, control system, and safety features when mains power is unavailable. This ensures that the lift can continue to function safely and reliably, preventing users from becoming stranded on the stairs during power disruptions. Battery backup systems are designed to automatically activate in the event of a power outage, prioritizing user safety and ensuring uninterrupted vertical transportation until normal power supply is restored.

In summary, the power source is a crucial component of the lift system, providing the necessary energy for its operation. With electricity from the building's mains serving as the primary power source and a battery backup system ensuring uninterrupted operation during power outages, the lift system can reliably meet the mobility needs of users while prioritizing their safety and convenience.

3.5.5 CONTROL PANEL

Description: The control panel serves as the primary user interface for operating the lift, providing users with the means to initiate movement, stop the lift, and control its direction. It is an essential component that enables users to interact with the lift system and control its functions according to their needs and preferences.

Ergonomics: Control panels are meticulously designed with user convenience and comfort in mind. They feature intuitive layouts and easy-to-use interfaces, allowing users to operate the lift effortlessly. The placement of buttons or switches is carefully considered to ensure ergonomic accessibility for users of all abilities. Additionally, control panels may incorporate features such as tactile feedback or color-coded buttons to enhance usability and facilitate navigation. Some control panels may also offer remote control options, allowing users to operate the lift from a distance for added convenience and accessibility.

Safety: Safety is a paramount consideration in the design of the control panel, with several features incorporated to enhance user safety and control during transit. Emergency stop functions are integrated into the control panel, allowing users to halt lift movement immediately in case of emergencies or unforeseen circumstances. These emergency stop buttons are prominently located and easily accessible to ensure quick response times and minimize potential risks to user safety. Additionally, control panels may include other safety features such as key locks or password protection to prevent unauthorized access and ensure that only authorized personnel can operate the lift system.

In summary, the control panel is a critical component of the lift system, providing users with intuitive controls and essential safety features for operating the lift safely and efficiently. With ergonomic design considerations and robust safety features, control panels enhance user experience and confidence during vertical transportation, ensuring a seamless and secure journey for users of all abilities.

3.6 ADVANTAGES

1. **Space Saving Design:** Staircase lifts are typically engineered with a compact design, making them ideal for homes with limited space or narrow staircases. By utilizing minimal space, these lifts ensure that staircases remain accessible without impeding movement or obstructing pathways within the home.
2. **Energy Efficiency:** Many staircase lifts are designed to be energy efficient, consuming power only when in operation. This not only reduces electricity consumption but also leads to lower energy costs for users over time. By optimizing energy usage, these lifts contribute to sustainability efforts and help minimize environmental impact.
3. **Foldable Platforms:** Some staircase lifts feature foldable platforms, which can be conveniently stowed away when the lift is not in use. This innovative design allows for additional space-saving benefits, particularly in tight or crowded stairwell spaces. By folding the platform, the staircase remains accessible for others, ensuring maximum flexibility and convenience.
4. **Cost-Effectiveness:** Staircase lifts are often more affordable to purchase and install compared to more complex mobility solutions. This lower initial cost makes them an attractive option for individuals or businesses on a budget, providing accessibility without breaking the bank. Additionally, reduced installation expenses mean that staircase lifts can be a cost-effective solution for improving accessibility in various settings.

3.7 PROCESS CHART




Fig 3.5: Process Chart

3.8 APPLICATIONS

Table 3.1: Applications

Application	Description
1. Residential Homes	Provide accessibility for individuals with mobility issues within private residences.
2. Public Buildings	Offer access to different levels in public spaces, such as schools, libraries, and community centers
3. Hospitals and Clinics	Facilitate mobility for patients, visitors, and medical staff within healthcare facilities.
4. Educational Institutions	Assist students, faculty, and staff in accessing different floors in schools and universities.

CHAPTER 4

HARDWARE DESCRIPTION

4.1 INTRODUCTION

In an era where accessibility and mobility are paramount, innovative solutions continue to emerge to empower individuals with physical challenges. Among these solutions, the standing staircase lift stands out as a pioneering advancement in assistive technology. This hardware implementation seamlessly combines engineering ingenuity with user-centric design to redefine the way individuals navigate vertical spaces. The standing staircase lift addresses a critical need for individuals with mobility impairments who face challenges in ascending or descending staircases. Traditional stairlifts provide seated transportation, but they may not be suitable for those who prefer or require standing positions due to their unique mobility requirements. Recognizing this gap, engineers and designers have collaborated to develop a transformative solution that prioritizes both safety and comfort.

At its core, the hardware implementation of the standing staircase lift comprises several essential components, each contributing to its functionality and reliability. The rail system serves as the backbone of the lift, providing a stable path for vertical movement. Mounted securely along the staircase, these rails guide the lift's platform smoothly and safely. The heart of the lift's propulsion system lies in the squirrel cage induction motor, a robust and efficient motor type renowned for its reliability and performance. Coupled with a gearbox, this motor provides the necessary torque to drive the lift's movement along the rails. The gearbox ensures optimal speed and power transmission, allowing for smooth and controlled ascent or descent.

Safety features are paramount in the design of the standing staircase lift. The spracket with chain mechanism, integrated with the motor and gearbox assembly, ensures precise and secure movement of the platform. This mechanism, combined with advanced sensors and control systems, enables smooth transitions and prevents

sudden stops or jerks. User interaction and control are facilitated through the forward-reverse LT control switch, a user-friendly interface that allows individuals to initiate and control the lift's movement with ease. Whether ascending or descending, users can effortlessly maneuver the lift to their desired position, enhancing both convenience and independence.

Moreover, safety remains a paramount concern in the design and implementation of the standing staircase lift. Advanced sensor technologies continuously monitor the surrounding environment, detecting obstacles and adjusting the lift's trajectory accordingly. Emergency stop mechanisms and fail-safe protocols provide additional layers of protection, offering peace of mind to users and caregivers alike. Beyond its functional benefits, the standing staircase lift symbolizes a broader commitment to inclusivity and empowerment. By enabling individuals with mobility impairments to navigate staircases with ease, this innovative hardware implementation promotes independence and enhances quality of life. Whether in residential settings, public buildings, or commercial spaces, its presence signifies a step towards a more accessible and inclusive society.

In conclusion, the hardware implementation of the standing staircase lift represents a remarkable fusion of engineering prowess and human-centered design. Through its seamless integration of cutting-edge technology and user-centric features, it transcends mere functionality to become a symbol of empowerment and inclusivity. As we continue to push the boundaries of assistive technology, solutions like the standing staircase lift stand as shining examples of innovation's power to transform lives.

4.2 HARDWARE COMPONENTS

The hardware implementation of a standing staircase lift encompasses several crucial components, each meticulously designed to ensure seamless functionality and user safety. At the core of the system is the Forward/Reverse Lift Control Switch, offering users intuitive command over the lift's movement along the staircase. Working alongside this control switch is the durable Squirrel Cage Induction Motor, serving as the powerhouse propelling the lift's motion. Its consistent performance ensures steady torque delivery, facilitating seamless traversal along the Rail System. This rail system, meticulously crafted for stability and alignment, forms the foundation of the lift's structure, ensuring safe and comfortable transportation. Complementing the motor and rails is the Sprocket with Chain assembly, enabling the transfer of rotational motion to drive the lift platform with accuracy and effectiveness. Meanwhile, the Gearbox optimizes motor performance, fine-tuning torque and speed to suit the lift's specific needs, thereby improving overall functionality and dependability. Together, these elements collaborate to empower individuals with mobility challenges, granting them the independence to navigate staircases autonomously and with assurance.

4.2.1 0.5 HP 3 PHASE SQUIRREL CAGE INDUCTION MOTOR

The integration of three-phase squirrel cage induction motors into smart standing staircase lift systems represents a significant advancement in accessibility technology. These motors, renowned for their robustness, reliability, and efficiency, play a pivotal role in facilitating the vertical transportation of individuals within residential, commercial, and public buildings. As the demand for mobility solutions that prioritize safety, efficiency, and user experience continues to rise, the incorporation of three-phase squirrel cage induction motors in smart lifts offers unparalleled benefits. This introduction explores the fundamental principles, advantages, and applications of three-phase squirrel cage induction motors within the context of smart standing staircase lifts, setting the stage for a comprehensive examination of their role and significance in modern accessibility solutions.

4.2.1.1 INDUCTION MOTOR

The induction motor, a cornerstone of electrical engineering, epitomizes simplicity and efficiency in motion. Functioning on the principle of electromagnetic induction, this motor features a stationary stator encompassing three-phase windings energized with alternating current. Upon activation, these windings produce a rotating magnetic field, inducing currents in the rotor—an assembly of conductive bars arranged in a "squirrel cage" configuration. The resulting interaction between the stator's magnetic field and the induced current in the rotor generates torque, propelling the rotor into motion. Renowned for its self-starting capability, rugged construction, and minimal maintenance requirements, the induction motor finds widespread use across industries. From powering conveyor belts and pumps to driving fans and compressors, its versatility and reliability make it indispensable in myriad applications. Moreover, advancements in motor design and control techniques continue to enhance its efficiency and performance, reaffirming its status as a foundational element of modern machinery. In essence, the induction motor stands as a testament to the ingenuity of electrical engineering, providing efficient and dependable motion for countless industrial and commercial endeavours.

4.2.1.2 WORKING PRINCIPLE OF INDUCTION MOTOR

We need to give double excitation to make a DC motor to rotate. In the DC motor, we give one supply to the stator and another to the rotor through brush arrangement. But in induction motor, we give only one supply, so it is interesting to know how an induction motor works. It is simple, from the name itself we can understand that here, the induction process is involved. When we give the supply to the stator winding, a magnetic flux gets produced in the stator due to the flow of current in the coil. The rotor winding is so arranged that each coil becomes short-circuited. The flux from the stator cuts the short-circuited coil in the rotor.

As the rotor coils are short-circuited, according to Faraday's law of electromagnetic induction, the current will start flowing through the coil of the rotor. When the current through the rotor coils flows, another flux gets generated in the rotor. Now there are

two fluxes, one is stator flux, and another is rotor flux. The rotor flux will be lagging with respect to the stator flux. Because of that, the rotor will feel a torque which will make the rotor to rotate in the direction of the rotating magnetic field. This is the working principle of both single and three-phase induction motors.

4.2.1.3 TYPES OF INDUCTION MOTOR

A 3-phase induction motor includes two essential components namely the stator & the rotor. In this motor, the stationary part is the stator whereas the rotating part is the rotor. In this motor, the load is connected to the shaft. Three-phase armature winding can be wound over the stator. Once balanced 3- phase current supplies throughout this winding, then a stable amplitude rotary magnetic field can be formed within the air gap. This armature winding can be connected toward the three-phase power supply & carries the load current. This kind of motor is classified into two types based on its construction like Squirrel Cage Rotor & Wound Rotor.

SQUIRREL CAGE INDUCTION MOTOR

The squirrel cage induction motor construction is extremely simple. In this motor, the rotor includes a cylindrical core that can be laminated & includes some slots on the external periphery. These slots are not comparable & they are twisted by some angles. These slots assist to stop magnetic locking among the teeth of the stator & rotor so that smooth operation can be achieved and humming noise can be reduced. These motors include rotors of bars in place of the rotor winding where these bars are fabricated with brass, aluminum otherwise copper.

In this type of motor, the winding of the rotor includes an aluminum bar otherwise uninsulated copper fixed into semi-closed rotor slots. At both ends of this motor, these conductors are short-circuited through similar material's end ring. As a result, this type of rotor is similar to a squirrel cage, so this is known as a squirrel cage induction motor.

SLIP RING INDUCTION MOTOR

The slip-ring induction motor is also called a wound rotor motor. In this motor, the rotor includes a laminated cylindrical core. Similar to the squirrel cage, there are some slots on the outer periphery. The rotor winding is placed inside the slots. In the wound rotor, the insulated windings are wound on top of the rotor similarly like on the stator. The winding of this rotor can be distributed uniformly & usually connected in the STAR model. The three terminals of this STAR connection can be taken out throughout the slip ring. So this is the reason to call this motor a slip ring induction motor.

4.2.1.4 3 PHASE SQUIRREL CAGE INDUCTION MOTOR

The squirrel cage induction motor stands as a cornerstone of electrical engineering, renowned for its simplicity, robustness, and versatility. Within the realm of electric motors, it serves as a ubiquitous workhorse, powering a myriad of industrial, commercial, and residential applications with unmatched reliability. At its core, this motor operates on the principle of electromagnetic induction, harnessing the interaction between magnetic fields to generate motion. Its design features a stationary stator housing a set of three-phase windings, which, when energized with alternating current, produce a rotating magnetic field. This magnetic field induces currents in the rotor a cylindrical assembly of conductive bars arranged in a "squirrel cage" configuration propelling it into motion. The resulting rotational force drives myriad mechanical systems, from conveyor belts to pumps, fans, and compressors, with remarkable efficiency and efficacy. Notably, the squirrel cage induction motor's self-starting capability, rugged construction, and minimal maintenance requirements render it indispensable across diverse industries and environments. In this introduction, we embark on a journey to explore the inner workings, applications, and significance of the squirrel cage induction motor an enduring symbol of engineering ingenuity and practicality in the modern era.

4.2.1.5 CONSTRUCTION

The squirrel cage induction motor comprises several key components that collectively enable its operation. Here's a breakdown of its constructional details:

1. **Stator:** The stator is the stationary part of the motor and is typically made of laminated steel sheets to minimize eddy current losses. It consists of a cylindrical core with evenly spaced slots to accommodate the stator windings.
2. **Stator Windings:** These windings are typically made of copper or aluminum and are placed in the slots of the stator core. They are connected in a three-phase configuration and carry alternating current to produce a rotating magnetic field.
3. **Rotor:** The rotor is the rotating part of the motor and is also made of laminated steel sheets to reduce eddy current losses. In a squirrel cage induction motor, the rotor consists of a cylindrical core with conductive bars (usually made of aluminum or copper) arranged in a "squirrel cage" configuration.
4. **End Rings:** The rotor bars are short-circuited at both ends by conducting end rings. These rings ensure that the induced currents in the rotor bars can circulate freely, generating the necessary magnetic fields for motor operation.
5. **Bearings:** Bearings support the rotor shaft within the motor housing, allowing it to rotate freely. These bearings are typically ball or roller bearings, designed to withstand the radial and axial loads encountered during operation.
6. **Motor Housing:** The motor housing encloses the stator, rotor, and bearings, providing mechanical protection and housing for the motor components. It is often made of cast iron or aluminum to provide durability and heat dissipation.
7. **Cooling Fan:** Some squirrel cage induction motors are equipped with a cooling fan mounted on the rotor shaft. This fan helps dissipate heat generated during operation by circulating air through the motor housing, thus preventing overheating and ensuring optimal performance.

4.2.1.6 CHARACTERISTICS




Fig 4.1: Torque – Speed Characteristics

Torque Characteristics:

- ❖ Starting Torque: Squirrel cage motors typically exhibit low starting torque, making them suitable for applications where the load is relatively light at startup. Fig 4.1 Explains the characteristics through graph.
- ❖ Pullout Torque: As the motor accelerates, the torque increases until it reaches the pullout torque, which is the maximum torque that the motor can produce without stalling or losing synchronism.
- ❖ Breakdown Torque: Beyond the pullout torque, the motor enters a region where the torque decreases, reaching a point called the breakdown torque. At this point, the motor may stall if the load exceeds the available torque.
- ❖ Full Load Torque: The torque required to maintain rated speed and power output under full load conditions.

Speed Characteristics:

- ❖ Synchronous Speed: The speed at which the rotating magnetic field of the stator rotates, determined by the frequency of the power supply and the number of poles in the motor.
- ❖ Slip: The difference between synchronous speed and rotor speed. It indicates the amount of slip necessary for the rotor to produce torque.
- ❖ Speed-Torque Curve: A graph illustrating the relationship between motor speed and torque. It shows how the motor's speed decreases as the torque increases.
- ❖ Operating Speed: The speed at which the motor operates under load conditions. It lies between synchronous speed and the speed at which the motor produces maximum torque.

4.2.1.7 SQUIRREL CAGE INDUCTION MOTOR IN SMART STAIRCASE LIFT



Fig 4.2: 0.5hp 3 Phase Squirrel Cage Induction Motor

Squirrel cage induction motors are commonly chosen for stairlift applications due to their reliability, high torque capabilities, efficiency, low maintenance requirements, and quiet operation. Fig 4.2 Shows the prime mover of the foot stand. These motors boast a simple yet robust design, featuring fewer moving parts which enhances their

reliability and minimizes the risk of mechanical failure. Their ability to deliver high starting torque is crucial for smoothly lifting and lowering the stairlift along the staircase, accommodating various loads without compromising performance or stability.




Fig 4.3: Name Plate Details of The Motor

Additionally, squirrel cage induction motors are highly efficient, converting electrical energy into mechanical energy with minimal waste, leading to cost savings for users and reduced environmental impact. Fig 4.3 gives the name plate details of the prime mover. Their simple design also translates to lower maintenance needs, as they are less prone to wear and tear compared to other motor types. Furthermore, the quiet operation of these motors ensures a smooth and peaceful ride for users, particularly important in residential settings where noise levels can affect comfort. Table 4.1 have all the specifications of the prime mover. Overall, the combination of reliability, high torque, efficiency, low maintenance, and quiet operation makes squirrel cage induction motors an optimal choice for powering stairlifts, effectively meeting the unique demands of mobility assistance devices.

Table 4.1: Motor Specifications

Specifications	Value
SKU	MOT.GEA.88114183
Phase	Three Phase
Model No	1-102-2T
Type of Product	Gear Head
Adapter	160-14
Insulation Class	F
Pole	4
Voltage	415 V $\pm$ 5%
Frequency	50Hz $\pm$ 5%
Mount Type	Flange Mount
Protection Degree	IP55
Duty	S1
Power	0.37 KW
Frame Size	71
Efficiency Class	IE2

4.2.1.8 ADVANTAGES

- ✓ **Simple and Robust Construction:** Squirrel cage induction motors have a simple design with fewer moving parts, which enhances their reliability and durability. They are less prone to mechanical failures and require minimal maintenance, reducing downtime and operating costs.
- ✓ **Cost-Effective:** Compared to other types of motors, such as synchronous motors or wound rotor induction motors, squirrel cage induction motors are generally more cost-effective to manufacture and maintain. This makes them an economical choice for a wide range of applications.

- ✓ **Self-Starting Capability:** Squirrel cage induction motors have inherent self-starting capability, meaning they can start and accelerate to their operating speed without the need for external starting devices. This simplifies the motor control system and improves reliability.
- ✓ **High Efficiency:** Squirrel cage induction motors are known for their high efficiency, especially when operating at or near full load. This helps reduce energy consumption and operating costs, making them environmentally friendly and economically advantageous.
- ✓ **Wide Range of Sizes and Power Ratings:** Squirrel cage induction motors are available in a wide range of sizes and power ratings, making them suitable for various applications, from small household appliances to large industrial machinery.
- ✓ **Low Maintenance:** Due to their simple construction and robust design, squirrel cage induction motors require minimal maintenance throughout their lifespan. This reduces the need for downtime and servicing, resulting in increased productivity and cost savings.
- ✓ **Smooth and Quiet Operation:** Squirrel cage induction motors typically operate smoothly and quietly, providing a comfortable working environment and enhancing user experience in residential and commercial settings.
- ✓ **Suitability for Variable Speed Applications:** Although squirrel cage induction motors are primarily designed for fixed-speed applications, they can also be used in variable speed applications with the help of variable frequency drives (VFDs). This adds versatility to their usage in various industrial processes.

4.2.1.9 APPLICATIONS

- ❖ **Industrial Machinery:** Squirrel cage induction motors are extensively used in industrial machinery such as pumps, compressors, fans, conveyors, and mixers due to their reliability, durability, and ability to handle heavy loads.
- ❖ **HVAC Systems:** These motors are commonly employed in heating, ventilation, and air conditioning (HVAC) systems for air handling units, blowers, and air compressors, where they provide efficient and reliable operation.

- ❖ **Water Treatment Plants:** Squirrel cage induction motors are utilized in water treatment plants for applications such as pumps, agitators, and mixers, where they provide continuous and dependable operation for water purification processes.
- ❖ **Material Handling Equipment:** They are used in material handling equipment such as cranes, hoists, and lifts for moving heavy loads in warehouses, manufacturing facilities, and construction sites, where reliability and robustness are crucial.
- ❖ **Agricultural Machinery:** Squirrel cage induction motors find applications in agricultural machinery such as irrigation pumps, grain conveyors, and crop processing equipment, where they provide efficient and durable operation in challenging outdoor environments.
- ❖ **Mining Equipment:** In the mining industry, these motors are employed in crushers, conveyor belts, and pumps for extracting, transporting, and processing minerals, where they offer reliable performance in harsh and demanding conditions.
- ❖ **Petrochemical Plants:** Squirrel cage induction motors are used in petrochemical plants for various applications including pumps, compressors, and blowers, where they provide continuous and efficient operation for processing and transporting fluids and gases.
- ❖ **Oil and Gas Industry:** They are utilized in the oil and gas industry for powering drilling rigs, pumps, and compressors, where they offer dependable performance in remote and rugged environments.
- ❖ **Food and Beverage Industry:** In the food and beverage industry, these motors are employed in processing equipment such as mixers, grinders, and conveyors, where they provide hygienic and efficient operation for food processing and packaging.
- ❖ **Commercial and Residential Applications:** Squirrel cage induction motors are also used in various commercial and residential applications such as household appliances (e.g., washing machines, refrigerators, air conditioners), garage door openers, and pool pumps, where they offer reliable and energy-efficient operation.

4.2.1.10 COMPARISON BETWEEN SQUIRREL CAGE AND SLIP RING

Table 4.2: Comparison Between Squirrel Cage and Slip Ring Motor

Aspect	Squirrel Cage	Slip Ring
Rotor Construction	Cylindrical core with conductive bars in squirrel cage	Laminated core with insulated windings and slip rings
Starting Torque	Lower	Higher
Speed Regulation	Poor	Better
Maintenance	Minimal Maintenance	Periodic Maintenance
Cost	More cost-effective	Typically more expensive
Starting Torque	Self-starting	External starting devices may be required
Speed Control	Limited	Precise through varying rotor resistance
Applications	Constant speed operations like pumps, fans, compressors	Adjustable speed and high starting torque for cranes, elevators, industrial machinery

4.2.2 LT CONTROL SWITCH

The LT (Low Tension) forward and reverse switch is an essential component utilized in electrical circuits to control the rotation direction of motors, particularly in applications where bidirectional movement is required. It functions by altering the connection of electrical power to the motor, thereby dictating whether the motor rotates clockwise or counterclockwise. Fig 4.4 has the 3 phase electrical connections of the switch. Typically, the switch comprises multiple poles, each associated with a specific function such as forward, reverse, stop, and neutral. These poles enable the switch to facilitate smooth and efficient operation, allowing operators to seamlessly transition between forward and reverse motor rotation modes.




Fig 4.4: LT Control Switch

In operation, when the switch is toggled to the forward position, electrical power is directed to the motor in a manner that induces clockwise rotation. Conversely, when the switch is shifted to the reverse position, the electrical connections are rearranged to induce counterclockwise rotation. This bidirectional control capability is invaluable in numerous industrial and commercial applications, ranging from conveyor systems and winches to cranes and hoists. By providing a simple yet effective means of controlling motor direction, the LT forward and reverse switch enhances operational

flexibility, productivity, and safety, enabling operators to precisely manoeuvre equipment and machinery according to specific task requirements.

- Reverse Forward L.T.Control ON-OFF-ON Switch 32 Amp, 3 - Phase, 415-Volts.
- Heavy duty Bakelite moulded industrial change over switch Heavy duty MS powder coated body
- Our Reverse Switches Forward Switches are very good in performance and are widely used with compound direct current motors, squirrel cage motors and Three phase motors.
- Forward Reverse switch is used in Lathes & Machines where forward and reverse operations are frequently done. Contacts made of pure cold rolled electrolytic copper, electroplated to withstand considerable overload without overheating to increase the life of switching cycle.
- Switch Operation Manual

4.2.3 GEAR BOX

Gearboxes are commonly attached to 3-phase induction motors to modify their output speed and torque characteristics. Fig 4.5 depicts the outer structure of the gear box. By utilizing different gear ratios, these attachments enable motors to operate at varying speeds while maintaining optimal efficiency. This versatility makes them indispensable in applications where precise control over rotational speed and torque is essential, such as in conveyors, pumps, and machinery requiring variable speeds.





Fig 4.5: Worm Gear Box

ALMO 40 worm gearbox stands as a pivotal component in the realm of mechanical power transmission, renowned for its robustness, versatility, and efficiency. Designed to meet the demands of diverse industrial applications, the ALMO 40 gearbox embodies a synthesis of innovative engineering and precision manufacturing. At its core lies a worm gear mechanism meticulously engineered to convert rotational motion into linear motion, thereby facilitating the seamless transfer of power from one component to another. The ALMO 40 gearbox offers a plethora of benefits, ranging from its compact design and high torque capacity to its smooth operation and reliability in challenging operating conditions.

Table 4.3: Worm Gear Box Specifications

Type	ALMO40
Ratio	1:10
Sr.No	HXM110877
Flange	71B5

In terms of design and construction, the ALMO 40 worm gearbox boasts a compact and space-efficient form factor, making it well-suited for installations where space constraints are a consideration. The gearbox housing is typically constructed from high-quality materials such as cast iron or aluminium, ensuring durability and resistance to wear and tear. Within the gearbox, precision-machined worm gears and worm wheels interact to transmit power efficiently while minimizing friction and energy losses. This meticulous attention to design detail results in a gearbox that delivers consistent performance and longevity, even in demanding industrial environments. One of the key advantages of the ALMO 40 worm gearbox is its high torque capacity, which makes it suitable for applications requiring the transmission of large amounts of power.

Table 4.3 have all the specifications of the gear box used. The worm gear mechanism inherent in the gearbox provides excellent torque multiplication, enabling the gearbox to handle heavy loads with ease. This feature is particularly advantageous in industries such as mining, construction, and material handling, where equipment must withstand significant stresses and strains. Additionally, the ALMO 40 gearbox offers precise control over rotational speed and direction, allowing for seamless integration into various industrial processes and machinery.

4.2.4 RAIL SYSTEM

The rail system utilized in a standing stairlift with a sprocket represents a sophisticated infrastructure engineered to provide seamless and secure movement along staircases, catering to individuals with mobility challenges. Fig 4.6 represents the rail system with sprocket to move the foot stand. Constructed from robust materials like steel or aluminium, these rail systems are meticulously designed to withstand the rigors of daily operation while ensuring precise guidance and support for the stairlift. In real-world applications, companies like Acorn Stairlifts, Bruno, and Handicare manufacture and install rail systems for standing stairlifts with sprockets. These rail systems often undergo rigorous testing and quality assurance processes to meet safety standards and regulations set forth by organizations such as the Occupational Safety and Health Administration or the European Committee for Standardization.



Fig 4.6: Rail Track with Sprocket

The rail system typically consists of two main components: the rail tracks and the sprocket mechanism. The rail tracks are securely anchored to the staircase structure, providing a stable pathway for the stairlift to traverse. These tracks may be straight, curved, or custom-designed to accommodate various staircase configurations, ensuring a perfect fit for each installation.

Table 4.4: Rail System Specifications

NAME	DETAILS
Rail Track	75 x 42 mm 20 Feet 3 mm thick
Chain	40 Feet
Foot Rest	16 x 12 inches 5 mm thick

The sprocket mechanism, integrated into the stairlift assembly, engages with the rail tracks to facilitate movement along the staircase. Table 4.4 portray the dimensional details of the rail system used to move the foot stand. This mechanism is often powered by a motorized chain or belt drive system, offering the necessary traction

and propulsion for smooth and controlled ascent or descent. Companies like Standing Stairlifts utilize advanced engineering techniques to ensure the sprocket mechanism operates with precision and reliability, delivering a safe and comfortable ride for users. Moreover, modern rail systems for standing stairlifts with sprockets often incorporate additional safety features such as obstruction sensors, emergency stop mechanisms, and backup power systems. These features help mitigate risks and enhance user confidence by ensuring the lift can respond promptly to any unforeseen circumstances or obstacles encountered during operation.

Overall, the rail system in a standing stairlift with a sprocket exemplifies a harmonious fusion of cutting-edge engineering and real-world practicality. By providing robust support, precise guidance, and advanced safety features, these rail systems empower individuals with limited mobility to navigate staircases with ease and confidence, improving their quality of life and promoting independence in their daily activities.

4.2.5 WIRES

A 3-core wire with a cross-sectional area of 3 square millimeters (mm^2) is another common type of electrical cable used in various applications, including for smart standing stairlifts.



Fig 4.7: 3 Core Wire

1. 3-core: This indicates that the wire contains three individual conductors within its insulation. Each core serves a specific purpose:

- Live (also known as Line or Phase): Carries the electrical current to the load.
- Neutral: Returns the current to the power source, completing the circuit.
- Earth (also known as Ground): Provides a path for fault currents to safely dissipate to the ground, enhancing safety.

2. 3 square millimeters: This refers to the cross-sectional area of each conductor in the wire. It's a measure of the thickness of the conductor and determines its current-carrying capacity and resistance. Fig 4.7 shows all the wires arrangement used to rotate the prime mover A larger cross-sectional area generally allows for the transmission of higher currents and reduces voltage drop over longer distances.

The 3-core wire with a cross-sectional area of 3mm² is suitable for carrying electrical power and signals in various low to medium voltage applications, including for smart standing stairlifts. It provides a higher current-carrying capacity compared to smaller wire sizes, which may be necessary for powering the motor and other components of the stairlift system.

4.2.6 FOOT REST

The footrest used in standing stairlifts is a crucial component designed to enhance user comfort, stability, and safety during transportation along staircases. These footrests are carefully engineered to accommodate various user preferences and ergonomic requirements while ensuring reliable performance and ease of use. In real-world applications, companies like Handicare, Standing Stairlifts, and Bruno manufacture and install footrests for standing stairlifts. These footrests undergo rigorous testing and quality assurance procedures to meet industry standards and regulations, ensuring they can withstand the demands of daily use and provide a secure platform for users.




Fig 4.8: Foot Rest

The footrest typically consists of a sturdy platform made from durable materials such as aluminium or reinforced plastic. This platform is designed to support the user's weight comfortably while providing ample space for their feet to rest securely during transportation. Fig 4.8 represents the place which will be used for mobility. Additionally, the surface of the footrest may feature non-slip textures or coatings to prevent slipping and enhance user safety. Furthermore, the footrest may incorporate additional features for convenience and customization, such as adjustable height settings or folding mechanisms. These features allow users to tailor the footrest to their individual preferences, ensuring optimal comfort and support throughout the journey.

Safety is a paramount consideration in the design of footrests for standing stairlifts. Companies integrate features like safety edges or sensors to detect obstructions and automatically stop the lift if any obstacles are encountered during operation. Additionally, footrests are engineered to remain stable and securely locked in place throughout the journey, minimizing the risk of accidents or injuries.

Overall, the footrest in standing stairlifts represents a vital element in ensuring user comfort, stability, and safety during transportation along staircases. By providing a

sturdy platform with customizable features and advanced safety mechanisms, these footrests contribute to a positive user experience and empower individuals with limited mobility to navigate their environments with confidence and independence.

4.3 HARDWARE RESULT

In the hardware setup of a smart standing staircase lift, several key components work together to ensure smooth and safe operation. At its core is the robust 3 Phase Squirrel Cage Induction Motor, chosen for its durability and efficiency in providing the necessary power to move the lift along the rail system. Fig 4.9 portray the final result of the staircase standing lift. The rail system itself is meticulously engineered to guide the lift's movement along the staircase securely. Supporting the motor, the chain with sprocket mechanism efficiently transfers motion, ensuring synchronized movement between the motor and the lift carriage. Electrical connections within the system are facilitated by the 3 Core Wire, crucial for transmitting power and control signals reliably throughout the setup. Complementing these components, the LT Control Switch acts as the user interface, enabling intuitive control over lift operations such as starting, stopping, and adjusting speed. Together, this hardware configuration forms a robust and reliable system, offering not only seamless transportation between different levels of a building but also incorporating smart functionalities for enhanced user experience and safety.



Fig 4.9: Smart Staircase Lift

CHAPTER 5

SUMMARY AND CONCLUSIONS

5.1 SUMMARY

This project embodies a holistic approach towards enhancing the mobility and accessibility of individuals facing diverse mobility impediments. It presents an innovative solution in the form of a smart standing lift tailored specifically for staircases, offering a safe and autonomous means of vertical transportation within indoor spaces. Central to the project's design are key components such as a robust platform, meticulously engineered rails or tracks, a dependable drive system, a power source equipped with backup functionality, and an intuitive interface for user control. Safety remains paramount, with the incorporation of advanced features including sensors, harnesses, and brakes to ensure secure passage. The operation of this lift is characterized by user-initiated movement, precise navigation, continuous safety monitoring, and optional seating arrangements to enhance user comfort. The project endeavors to empower individuals with mobility challenges, enabling them to navigate indoor environments with confidence, independence, and peace of mind.

5.2 CONCLUSION

Smart Standing Staircase Lift project has provided a comprehensive overview of staircase lifts with flat platforms, highlighting their role in advancing accessibility and mobility solutions for individuals with limited mobility. The lifts' versatile design and space efficient characteristics cater to a broad user base, accommodating wheelchair users and individuals who prefer to stand, thus promoting user comfort and safety. These lifts have demonstrated their practical utility in diverse settings, spanning residential, commercial, and public environments, thereby contributing to inclusivity and convenience. Furthermore, the advantages of space efficiency, enhanced accessibility, and reduced initial costs underscore their significance in addressing the needs of individuals with mobility challenges.

REFERENCES

1. Balmer D. Impact of the A18.1 ASME Standard on platform lifts and stairway chairlifts on accessibility and usability. *Assist Technol* 2010; 22:46–50.
2. Burdick, J.W., Radford, J., and Chirikjian, G.S., 1993, “A ‘Sidewinding’ Locomotion Gait for Hyper Redundant Robots,” *Proc. IEEE International Conference on Robotics and Automation*.
3. Canada Mortgage and Housing Corporation. Accessible housing by design- lifts and residential elevators, <http://www.cmhcschl>.
4. Davey J. Ageing in place: The views of older home owner on maintenance, renovation and adaptation. *Soc Policy J NZ* 2006; 27: 128–141.
5. Desai, R.S., Wilcox, B., Bedard, R., 1992, “JPL Robotic Vehicle Overview,” in *AUVS*.
6. Helmick, D., Roumeliotis, S., McHenry, M., Matthies, L., 2002, “multi-sensor, high speed autonomous stair climbing”, *IEEE/RSJ Conference on Intelligent Robots and Systems (IROS)*, September.
7. Hsueh-Er, C., “Stair-climbing vehicle, 2008, “Patent No. US2008164665(A1)”, Jan 24.
8. Iwarsson S, Nygren C, Oswald F, et al. Environmental barriers and housing accessibility problems over a one-year period in later life in three European countries *J. Hous Elderly* 2006; 20: 23–43.
9. Johansson K, Lilja M, Petersson I, et al. Performance of activities of daily living in a sample of applicants for home modification services *Scand J Occup Ther* 2007; 14: 44–53.
10. Jung Y, Bridge C and Mills’ S. Cost-benefit analysis of ramps versus lifts. Sydney: Home Modification Information Clearinghouse, University of New South Wales, 2010.
11. Jungius, C., 1996. “Mobile Robots for Planetary Exploration,” *Control Engineering Practice*, Vol. 4, No. 4.

12. Kemurdjian, L., Gromov, V., Mishkinyuk, V., Kucherenko, V., Sologub, P., 1992, "Small Marsokhod Configuration," International Conference on Robotics & Automation, Nice.
13. Mourikis, A.I., Trawny, N., Roumeliotis, S.I., Helmick, D.M., and Matthies, L., 2007, "Autonomous Stair Climbing for Tracked Vehicles," International Journal of Computer Vision & International Journal of Robotics Research - Joint Special Issue on Vision and Robotics, 26(7), 737-758.
14. Nasarwanji MF, Paquet VL, Feathers DJ, et al. Usability study of a powered lift for wheelchair users. In: Proceedings of the Human Factors and Ergonomics Society Annual Meeting. Santa Monica, CA: Human Factors and Ergonomics Society, 2008, pp.719–722.
15. Ruturaj Kulkarni, Bhumin Patel, Chinmesh Mulay, Prathamesh Musale and Rohit V. Bhaskar, Design of Stairlift for Curved Path, (2018) International Journal of Current Engineering and Technology,
16. Schilling, K., Jungius, C., 1996. "Mobile Robots for Planetary Exploration," Control Engineering Practice, Vol. 4, No. 4.
17. Scotts M, Saville-Smithe K and James B. International trends in accessible housing for people with disabilities: A selected review of policies and programs in Europe, North America, United Kingdom, Japan and Australia. Report no. Working paper 2, cited June 2014.
18. Siegwart, R., Lauria, M., Mäusli, P., Winnendael, M., 1998, "Design and Implementation of an Innovative Micro-Rover," Proceedings of Robotics 98, the 3rd Conference and Exposition on Robotics in Challenging Environments, April 26-30, Albuquerque, New Mexico.
19. Smith SK, Rayer S and Smith EA. Aging and disability: Implications for the housing industry and public policy in the United States. J Am Plann Assoc 2006; 74: 289–306.
20. The Center for Universal Design. Wood ramp design: How to add a ramp that looks good and works too. Raleigh, NC: North Carolina State University, 2004.