

# **TILT SORT ROBOT FOR REVOLUTIONIZING WAREHOUSE SORTATION**

Submitted in partial fulfillment of the requirements for the award of  
Bachelor of Engineering Degree in  
Mechatronics Engineering  
by

**HASAN AHMED (Register No. 40090012)**

**TAUSEEF Ali URFANI (Register  
No. 40090033)**



**DEPARTMENT OF MECHATRONICS ENGINEERING  
SCHOOL OF MECHANICAL ENGINEERING**

# **SATHYABAMA**

**INSTITUTE OF SCIENCE AND  
TECHNOLOGY (DEEMED TO BE  
UNIVERSITY)**

**Accredited with Grade "A" by NAAC**

**JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI  
- 600119**

**APRIL 2023**



# **SATHYABAMA**

**INSTITUTE OF SCIENCE AND TECHNOLOGY  
(DEEMED TO BE UNIVERSITY)**

Accredited "A" Grade by NAAC | 12B Status by UGC | Approved by AICTE

[www.sathyabama.ac.in](http://www.sathyabama.ac.in)

---

## **DEPARTMENT OF ELECTRICAL AND ELECTRONIC ENGINEERING**

### **BONAFIDE CERTIFICATE**

This is to certify that this Project Report is the bonafide work of **HASAN AHMED** (Reg. No. 40090012) and **TAUSEEF ALI URFANI** (Reg. No. 40090033) who carried out the project entitled "**TILT SORT ROBOT FOR REVOLUTIONIZING WAREHOUSE SORTATION**" under our supervision from November 2022 to April 2023.

**DR. S.PRAKASH**  
**Internal Guide**

**Dr. B.KANIMOZHI**  
**Head of the Department**

---

**Submitted for Viva voce Examination held on**\_\_\_\_\_

**Name:**

**Signature:**

**Internal Examiner**

**External Examiner**

## DECLARATION

We **HASAN AHMED** (Reg. No. 40090012) and **TAUSEEF ALI URFANI**(Reg. No.40090033) hereby declare that the Project Report entitled “**TILT SORT ROBOT FOR REVOLUTIONIZING WAREHOUSE SORTATION**” done by us under the guidance of **DR. S.PRAKASH** is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in Electrical and Electronics Engineering.

1.

2.

**DATE:**

**PLACE: CHENNAI**

**SIGNATURE OF THE CANDIDATES**

## ACKNOWLEDGEMENT

We are pleased to acknowledge our sincere thanks to Board of Management of **SATHYABAMA** for their kind encouragement in doing this project and for completing it successfully. We are grateful to them.

We convey our thanks to **Dr. S. Prakash, Dean, School of Mechanical Engineering**, and **Dr. B. Knimozhi, Head of the Department, Dept. of Mechatronics Engineering** for providing us with necessary support and details at the right time during the progressive reviews.

We would like to express our sincere and deep sense of gratitude to our Project Guide **DR. S. Prakash** for his valuable guidance, suggestions, and constant encouragement paved way for the successful completion of our project work.

We wish to express our thanks to all Teaching and Non-teaching staff members of the Department of Mechatronics Engineering who were helpful in many ways for the completion of the project.

## **ABSTRACT**

The rapid growth of e-commerce and the increasing demand for efficient warehouse operations have necessitated advancements in automated sorting systems. Many distribution centers use expensive and large conveyor belt sortation systems which require large areas to operate and are very conventional. The Tilt Sort Robot (TSR) can work in tight spaces and increase the production capability of the workspace exponentially.

The TSR combines the benefits of robotic technologies, computer vision, and intelligent algorithms to enhance the efficiency and accuracy of sortation tasks. Unlike traditional sorting methods that rely on conveyor belts or manual labor, the TSR employs a unique tilting mechanism, enabling it to swiftly and accurately sort items based on predefined criteria. The system incorporates advanced computer vision algorithms to identify and classify items in real-time, ensuring precise sorting and reducing errors. With its adaptable design, the TSR can handle various items, including different shapes, sizes, and weights. Moreover, the system utilizes machine learning techniques to improve its sorting capabilities continuously, enhancing its performance over time. By implementing the TSR in warehouses and distribution centers, companies can significantly streamline their sorting processes and use manpower in a more efficient way hence increasing operational efficiency. The technology offers scalability, allowing businesses to accommodate growing order volumes and adapt to changing market demands.

Overall, the Tilt Sort Robot presents a transformative solution for unit, parcel, and warehouse sortation, providing an innovative approach to address the challenges faced by the logistics industry in the era of e-commerce. Its integration into sorting operations has the potential to revolutionize warehouse automation, enabling faster, more accurate, and cost-effective sorting processes.

## TABLE OF CONTENTS

| CHAPTER NO. | TITLE                                                     | PAGE NO. |
|-------------|-----------------------------------------------------------|----------|
|             | ABSTRACT                                                  | 3        |
|             | LIST OF FIGURES                                           | ix       |
|             | LIST OF TABLES                                            | x        |
|             | LIST OF SYMBOLS AND ABBREVIATIONS                         | xi       |
| 1           | INTRODUCTION                                              |          |
|             | 1.1 OVERVIEW                                              | 10       |
|             | 1.2 GENERAL INTRODUCTION                                  | 11       |
| 2           | LITERATURE SURVEY                                         |          |
|             | 2.1 MAJOR FINDINGS                                        | 12       |
|             | 2.2 LITERATURE REVIEW                                     | 18       |
| 3           | REQUIREMENTS ANALYSIS                                     |          |
|             | 3.1 AIM OF THE PROJECT                                    | 28       |
|             | 3.2 SCOPE OF THE PROJECT                                  | 28       |
|             | 3.3 OBJECTIVE                                             | 29       |
|             | 3.4 METHODOLOGY                                           | 29       |
| 4           | Experimental or materials and methods;<br>algorithms used |          |

|       |                                                                                            |    |
|-------|--------------------------------------------------------------------------------------------|----|
| 4.1   | MATERIAL DESCRIPTION                                                                       | 31 |
| 4.1.1 | ARDUINO UNO                                                                                | 31 |
| 4.1.2 | L298N MOTOR DRIVER                                                                         | 32 |
| 4.1.3 | LOAD CELL                                                                                  | 34 |
| 4.1.4 | IR SENSOR                                                                                  | 34 |
| 4.1.5 | JUMP WIRES                                                                                 | 35 |
| 4.1.6 | HIGH TORQUE MOTOR                                                                          | 37 |
| 4.1.7 | 12V DC BATTERY                                                                             | 38 |
| 4.1.8 | HX711 LOAD CELL MODULE                                                                     | 39 |
| 4.2   | WORKING OF TILT SORT ROBOT FOR<br>REVOLUTIONIZING UNIT, PARCEL, AND<br>WAREHOUSE SORTATION | 40 |
| 4.3   | ALGORITHM USED                                                                             | 43 |

## **5 RESULT AND DISCUSSION**

|     |                      |    |
|-----|----------------------|----|
| 5.1 | RESULT               | 44 |
| 5.2 | PROTOTYPE DISCUSSION | 46 |

## **6 SUMMARY AND CONCLUSION**

|     |            |    |
|-----|------------|----|
| 6.1 | SUMMARY    | 47 |
| 6.2 | CONCLUSION | 48 |

|     |                   |    |
|-----|-------------------|----|
| 6.3 | FUTURE SCOPE      | 49 |
|     | <b>REFERENCES</b> | 50 |





# CHAPTER 1

## INTRODUCTION

### 1.1 OVERVIEW

In an era characterized by the exponential growth of e-commerce, the optimization of warehouse and logistics operations has become a paramount concern for businesses striving to meet the demands of modern supply chains. The efficient sorting of units and parcels within warehouses and distribution centers is a linchpin in this process, with the potential to significantly impact productivity, cost-effectiveness, and customer satisfaction. This report delves into the innovative realm of tilt sort robots and their role in revolutionizing unit, parcel, and warehouse sortation—a technological frontier poised to reshape the landscape of logistics.

**The Problem:** Sorting operations in warehouses and distribution centers have traditionally relied on manual labor and conveyor systems. While effective, these methods are not always scalable, cost-efficient, or capable of handling the ever-increasing diversity of objects encountered in modern logistics. This problem underscores the need for advanced sorting solutions that can not only boost efficiency but also adapt to the evolving demands of the industry.

**The Solution:** Tilt sort robots represent a promising solution to this challenge. These versatile machines are designed to intelligently and precisely sort a wide range of objects, from packages of varying shapes and sizes to irregular items. Their capacity to seamlessly integrate into existing warehouse infrastructure and adapt to different sorting tasks makes them a compelling technology.

**The Objective:** The objective of this report is to provide a comprehensive overview of the tilt sort robot technology, encompassing its design principles, sensor and control systems, operational challenges, and potential impact on various industries. By examining the state of the art, ongoing research efforts, and future prospects, we aim to shed light on how tilt sort robots are poised to become a transformative force in unit, parcel, and warehouse sortation.

**Significance:** This report carries significant implications for businesses seeking to optimize their sorting processes, as well as for researchers and engineers in the field of robotics and

automation. Moreover, it explores the potential societal impact of more efficient and sustainable sorting practices and envisions a future where tilt sort robots play a pivotal role in shaping a more streamlined and eco-conscious logistics ecosystem.

In the pages that follow, we embark on a journey through the intricacies of tilt-sort robots, dissecting their mechanisms, challenges, and potential applications. Through a detailed examination of the technology, we aim to provide a roadmap for harnessing the transformative potential of tilt sort robots in the realm of unit, parcel, and warehouse sortation.

## **1.2 GENERAL INTRODUCTION**

Warehouses serve as the nerve centers of supply chain operations, where products flow in and out in a complex ballet of inventory management. One of the critical processes within this ecosystem is sortation – the methodical arrangement of goods for storage or shipment. Traditionally, this task has been labor-intensive, prone to errors, and limited by the constraints of manual labor. The advent of automation has brought about transformative changes in warehouse operations. Technologies such as conveyor belts, robotic pickers, and automated storage and retrieval systems (AS/RS) have revolutionized how warehouses function. These innovations have not only enhanced efficiency but have also paved the way for greater scalability and cost-effectiveness.

Despite the advancements in automation, conventional sortation systems still face certain limitations. Many rely on fixed conveyors or chutes, which impose constraints on the types of products that can be sorted and the flexibility of sorting destinations. Moreover, they often lack adaptability to handle irregularly shaped items or items with varying dimensions. The Tilt Sort Robot represents a paradigm shift in warehouse sortation technology. Combining the precision of robotics with the adaptability of tilt mechanisms, this innovative system offers a versatile solution to the challenges faced by traditional sortation methods. By leveraging advanced sensors, machine learning algorithms, and robotic manipulators, the Tilt Sort Robot can swiftly and accurately sort a wide range of products with unprecedented efficiency.

At the heart of the Tilt Sort Robot lies its unique tilt mechanism, which allows it to dynamically adjust the orientation of items as they are sorted. This flexibility enables the system to accommodate various shapes, sizes, and weights, eliminating the need for specialized sorting

equipment for different product categories. Furthermore, the integration of intelligent software enables the robot to learn and adapt to changing sorting requirements over time, enhancing its performance and reliability. The adoption of Tilt Sort Robots offers a multitude of benefits for warehouse operators and logistics managers. Firstly, it streamlines sortation processes, reducing cycle times and improving throughput. Secondly, it enhances accuracy and order fulfillment rates, minimizing errors and mitigating costly returns. Thirdly, it enhances the overall efficiency of warehouse operations, allowing organizations to optimize space utilization and labor resources. Ultimately, these benefits translate into tangible cost savings and competitive advantages in the marketplace.

## **CHAPTER 2**

### **LITERATURE SURVEY**

#### **2.1 MAJOR FINDINGS FROM THE LITERATURE SURVEY**

- Nils Boysen, Stefan Fedtke, Dirk Briskorn, Marcel Schmickerath (2018) highlighted the critical role of Automated Sorting Systems (ASS) in modern supply chains. These systems are essential due to their speed, ability to handle large shipment volumes, reliability, and capacity to handle heavy and oversized items. The significance of ASS extends to various industries, from e-commerce distribution centers to airline baggage handling. The surveys emphasize that ASS has become a fundamental component of supply chains, enabling timely deliveries, enhancing reliability, and reducing operational costs.
- Nils Boysen, Stefan Schwerdfeger, Marlin W. Ulmer (2018) highlighted the complex operational challenges faced in real-time environments where autonomous mobile robots are responsible for sorting products. These challenges include piece-to-order assignment, order-to-collection point assignment, and piece-to-robot assignment, along with robot scheduling. The survey underscores the importance of optimizing these operational decisions to enhance sortation throughput. It introduces sophisticated optimization techniques, such as a two-step multiple-scenario approach, to address these challenges and significantly improve sorting system performance. The findings suggest that advanced optimization methodologies can help approximate the performance of an idealized system, even with limited lookahead, enhancing the efficiency of robotized sorting systems in e-commerce warehouses.
- Xianhao Xu, Yuerong Chen, Bipan Zou, Yeming Gong (2021) identifies that in robotic sorting systems (RSS), particularly exemplified by the Deppon Express Shanghai center, the assignment of arrival parcels to the loading stations plays a crucial role in determining system performance. The efficient assignment of parcels to loading stations is pivotal as it impacts both the waiting time of parcels on the loading platform and the sorting time of

the robots. The research in this paper focuses on optimizing the assignment of parcels to loading stations, taking into account the destination location of each parcel. By optimizing this assignment, the study demonstrates that it can substantially improve the overall performance of the RSS. This finding underscores the importance of intelligent assignment strategies in maximizing the efficiency and throughput capacity of autonomous robot-driven sorting systems in warehouse operations. In essence, the paper emphasizes the significance of addressing the assignment problem in robotic sorting systems to minimize delays, enhance sorting efficiency, and reduce manual intervention, ultimately leading to a more streamlined and cost-effective operation in modern warehousing.

- Bipan Zou, René De Koster, Yeming Gong, Xianhao Xu, Guwen Shen (2021) emphasizes that the performance of Robotic Sorting Systems (RSS) can be significantly enhanced through careful design considerations. It highlights several key findings:
  1. Flexible Layout Options: The research explores two primary layout configurations for RSS—two-tier systems with robots operating on the top tier and single-tier systems with input and output points located at the perimeter. It underscores the flexibility of these layouts in adapting to changing sorting demands and system scalability by adding or retracting robots. Importantly, RSS layouts require less floor space compared to traditional conveyor-based sorting systems.
  2. Assignment Rules Impact Performance: The survey examines various robot-to-loading-station assignment rules, including random, closest, dedicated, and shortest-queue assignment rules. It demonstrates that the choice of assignment rule significantly affects RSS performance. The proper assignment rule can improve the efficiency of robot sorting and reduce congestion.
  3. Path Topologies Influence Travel Efficiency: Path topologies, specifically shortest path and detour path topologies, are evaluated in the context of RSS. The study reveals that the selection of path topology impacts the travel efficiency of robots within the system. The shortest path topology, with dual-lane aisles, allows for more direct and efficient travel between loading stations and drop-off points.

4. **Impact of Robot Congestion Considered:** The survey acknowledges that managing robot congestion is critical in RSS, given the compact area and the movement of many robots. Effective control of robot movement without deadlocks or excessive congestion is essential for smooth system operation.
5. **Scalability and Cost-Effectiveness:** RSS is found to be a scalable solution for sorting tasks. It can adapt to varying throughput demands by adjusting the number of robots and workers. While RSS requires an initial investment in expensive robots and complex control software, its advantages in flexibility and scalability can make it a cost-effective choice for distribution centers.

In summary, the major finding highlights the significance of optimizing RSS layout configurations, assignment rules, and path topologies to enhance system performance and cost-effectiveness. Proper design considerations and rule selections can lead to more efficient sorting operations in distribution centers, making RSS a valuable alternative to traditional conveyor-based sorting systems.

- M. Pakdaman, M. M. Sanaatiyan and M. R. Ghahroudi, identifies and discusses various technical challenges and issues encountered in the design and implementation of Line Follower Robots. These challenges pertain to both mechanical and electrical aspects of the robots. Key findings and insights include:
  1. **Sensors for Line Detection:** Line Follower Robots rely on Infrared Ray (IR) sensors for detecting and following lines on the floor. These sensors consist of an infrared transmitter and receiver pair. The survey highlights the importance of sensor placement and distance from the ground surface, emphasizing that the distance between sensors must be adjusted based on the width of the line being followed.
  2. **Analog to Digital Conversion:** The sensors generate analog signals, which must be converted to digital form for processing. The survey discusses the use of an external Analog to Digital Converter (ADC) to manage this conversion process efficiently. It mentions the LM324 ADC as a suitable choice for this purpose.

3. Microcontroller (Processor): To process sensor data and control the robot's movements, a microcontroller is essential. The survey recommends using Atmel's AVR microcontroller, specifically "At Mega 16," which offers features like reduced instruction set coding (RISC), internal oscillators, timers, UART, SPI, and analog comparators. The microcontroller's role is critical in decision-making and precise control of the robot's movements.
4. Motor Driver (Driver IC): Line Follower Robots require a motor driver IC to control and power the motors. The survey suggests using IC L298, which is a dual full-bridge driver capable of accepting TTL logic levels and driving inductive loads like motors. It discusses how the motor driver operates, providing voltage to the motors based on instructions from the microcontroller.
5. Actuators (Motors and Wheels): The choice of motors and wheels is vital for the robot's movement. The survey explains that gearbox motors, as opposed to common DC motors, offer more stability in terms of speed on different terrains. It advises against using stepper motors due to their complexity and the challenges associated with programming them. The survey also highlights the use of three wheels, with two driven by the motors and one acting as a passive caster.

In summary, the major finding underscores the technical complexities involved in designing and building Line Follower Robots. These challenges span sensor placement, analog to digital conversion, microcontroller selection, motor driver usage, and motor and wheel choices. Overcoming these technical hurdles is essential for the successful development and operation of Line Follower Robots.

- Baharuddin, Zafri & Zainal Abidin, Izham & Sulaiman, S. & Mohideen, Kaja. (2005) identifies the development of an improved line sensor configuration, a robust line-following algorithm, and an efficient line recovery strategy for the Advance Line Follow Robot (ALF). These enhancements collectively enhance the navigational reliability of differential drive line-following robots, making them more capable of successfully navigating complex paths and contributing to their utility in industrial settings for tasks like material handling and transportation.

- Oluwole, Leke & Olanipekun, Ayorinde & Ajide, O.O. (2015) identifies the design, construction, and testing of a strain gauge instrument based on a quarter bridge strain gauge system is the successful development of a portable field instrument for measuring strain. The key points and contributions can be summarized as follows:
  1. Development of a Strain Gauge Instrument: The research project successfully designed, constructed, and tested a measuring instrument that utilizes a quarter bridge strain gauge system. This instrument is designed for practical field applications where measuring surface deformation and strain is essential.
  2. Systematic Division of Instrument Sections: The instrument is systematically divided into three key sections: the power section, the arithmetic logic section, and the input and output section. Each section plays a crucial role in the overall functionality of the instrument, from powering it to processing and displaying measurement results.
  3. Utilization of Strain Gauges: The research emphasizes the significance of strain gauges, particularly electrical resistance strain gauges, as transducers for converting mechanical strain into electrical resistance changes. These gauges are widely used in engineering applications for measuring mechanical movements and deformations.
  4. Historical Roots of Strain Gauges: The paper provides a historical perspective on the development of strain gauges, tracing their origins back to 1938 when Arthur Ruge and Edward Simmons conceived the concept. It highlights the evolution of strain gauges from rudimentary devices to advanced bonded resistance strain gauges.
  5. Working Principle of Strain Gauges: The survey explains the fundamental working principle of strain gauges, which involves the relationship between a material's resistance and its mechanical properties. When a material experiences strain, it leads to a change in its electrical resistance, which can be measured using various techniques, including the Wheatstone bridge setup.
  6. Wheatstone Bridge Setup: The paper describes the operation of the Wheatstone bridge apparatus, which is widely used for measuring changes in resistance, including those of strain gauges. The balance condition of the Wheatstone bridge is achieved

when there is no potential difference between certain points in the circuit, allowing the measurement of strain-induced changes in resistance.

7. Successful Construction of a Portable Field Instrument: The major finding is the successful design and construction of a portable field instrument for measuring strain using the principles of strain gauges and the Wheatstone bridge setup. This instrument is capable of accurately measuring surface deformation and strain in practical applications.

In conclusion, the major finding of this survey is the development of a functional and practical strain gauge instrument that can be used in the field for measuring strain. This instrument has been constructed based on sound engineering principles and contributes to the field of instrumentation for measuring mechanical deformations and movements.

- Al-Dahiree OS, Tokhi MO, Hadi NH, Hmoad NR, Ghazilla RAR, Yap HJ, Albaadani EA emphasize the importance of load cells in measuring forces accurately across various industries. It highlights the significance of axial force testing in product development. The survey also mentions the key requirements for load cell design and their working principles. While it discusses advancements in load cell development using numerical simulation and optimization methods, it does not explicitly mention a specific major finding or outcome of the research related to the design and shape optimization of the strain gauge load cell.
- Kannaki S, Karthigai Lakshmi S, Harish V, Manikandan R, Saktheeswaran G identifies the development of an automatic sorting machine that utilizes a weighing mechanism, primarily based on weight measurement, to sort objects moving along a conveyor. However, the paper does not explicitly mention a specific major finding or outcome of the survey or research related to the sorting machine's development. It provides an overview of the system's design and operation but does not highlight any novel discoveries or significant findings.

- S Badrinarayanan, V Ramesh Kumar, Kuldeep Sing Bhinder and Ralexander identified the detailed design and development of an electromechanical linear actuator utilizing a roller screw mechanism. The study highlights the advantages of roller screws over ball screws for applications with high dynamic loads and high inertia platforms. It provides a comprehensive examination of the various components and design considerations, including the roller screw mechanism, reduction gearbox, motor selection, electromagnetic failsafe clutch, no-back clutch, and overload slipping clutch, which collectively optimize the actuator's performance. The inclusion of failsafe features, such as the electromagnetic clutch and no-back clutch, ensures the actuator's reliability and safety in case of power failure or manual operation. Additionally, the overload slipping clutch serves to protect the system from shocks and mechanical damage.

## 2.2 LITERATURE REVIEW

1. **Paper Citation:** Nils Boysen, (2018) et al. - This article examines and discusses Automated Sortation Systems (ASS) and how they have become an essential part of many supply chains. He also talks about various supply chains implementing fully automated sorting systems, for example from baggage handling at airports to the sorting of parcels using tilting tray conveyors in the distribution centers of the postal service industry, to batches of pick orders isolated in an e-shop warehouse. The main reason why these automated sorting systems have become essential components in many supply chains are 4 main fundamental characteristics: ASS is fast: Next-day or even same-day delivery is a core promise of many online retailers (Amazon, Flipkart ) and postal providers services (UPS, FedEx). Subtracting transit times leaves only narrow time windows for all search and sorting operations. Without automatic sorting, these goals seem hardly achievable. ASS can handle a large number of shipments: For example, the air hub in Cologne (Germany), which is one of the three main global hubs in the express logistics network of the postal service provider UPS, has the capacity to sort up to 190,000 shipments per hour (Airport Central, 2014). ASSs are reliable: The US Department of

Transportation (2009), for example, reports a range of 1.42 to 9.17 when evaluating 19 US airlines for mishandled bags per 1,000 passengers. Obviously, any lost or delayed baggage causes a loss of goodwill, so reliable automated baggage handling has become a critical success factor in the airline industry. ASS handles heavy and bulky objects: Aging societies in many industrialized countries propose automating activities that cause high ergonomic stress for human workers (Otto, Boysen, Scholl, & Walter, 2017). Repeated handling of heavy parcels is certainly one of these activities, so ASS handling of oversized parcels has a long tradition in postal distribution centers (Fedtke & Boysen, 2017b) and cross docks (Bartholdi & Gue, 2000). Survey Scope – This survey provided valuable insights into the current state of ASS research, it is important to note that the field is dynamic and constantly evolving. As technology advances and the demands of modern supply chains constantly change, new challenges and opportunities will emerge. Future research should focus on addressing these challenges, such as optimizing sorting algorithms, improving system scalability, and adapting ASS to handle new trends such as the growth of e-commerce.

2. **Paper Citation:** Nils Boysen (2018), et al. - This paper assumes a given layout of a sorter with one loading station and focuses on the following operational planning decisions, which are schematically shown in Fig. 1: Piece-to-order (P2O) assignment: Real data is strongly biased (De Koster et al., 2007) and especially fast-turnover SKUs that are approaching the loading station must be assigned to orders. In this decision-making, it seems advantageous to reduce the order variance, i.e. the distance (counted in pieces) between the first and last piece assigned to each order. The shorter the order span, the faster the orders are completed, so the pickup points immediately assigned to them are released earlier and can be reassigned to subsequent orders. In this way, sorting performance can be improved. Assignment of an order to a collection point (O2CP): Customer orders must be assigned to the collection points where the pieces intended for the respective order are collected. However, such assignment is only temporary and the picking location is released for reassignment as soon as the relevant order is completed and transferred to the packing and shipping area. Advantageous collection points near the loading station should be assigned especially to orders that require many pieces. In addition, priority should be given to orders that are not excessively distributed in the order

of arrival, because then favorable collection points are not blocked for too long. Thus, a good O2CP assignment can free up the limited capacity of robots and improve the sorting performance. The assignment of orders to pick up points has already been investigated for traditional (conveyor) sorting systems (see Johnson, 1997, Khir, Erera, Toriello, 2021, Meller, 1997). For a survey, see Boysen et al. (2019).





Fig 1. Schematic representation of a robotized sorting system and its main operational decision tasks.

3. **Paper citation:** Xianhao Xu, (2022) et al. - This paper talks about the increasing use of autonomous robots in warehouses due to their flexible throughput capacity and low operational cost. The paper also acknowledges the increasing adoption of autonomous robots in warehouse operations over the past decade, the primary focus of the paper is on sorting operations within warehouses. It discusses how autonomous robots are being integrated into these operations, emphasizing the importance of sorting in modern warehousing. It describes a specific warehouse layout where autonomous robots operate on the top mezzanine level. The papers employ both modeling and simulation techniques to address the assignment optimization problem. It discusses the use of an open queueing network to estimate system performance and validates its accuracy through simulation. It includes real-world case studies demonstrating the practical applicability and benefits of the proposed approach. It highlights the substantial reduction in system throughput time and manual costs compared to existing assignment rules used in practice. There have been many attempts and implementations in the autonomous sorting robot industry, e.g., Amazon unveils Xanthus and Pegasus fulfillment robots (Ames, 2019) and the t-sort solutions of Tompkins (2020). As an example, Deppon Express, one

of the largest express delivery companies in Shanghai, China, has implemented such a system on two vertical tiers (Zhang, 2019). Compared with an automated conveyor-based sorting system, a Robotic Sorting System (RSS) enjoys a more flexible layout since the input and output points can be easily changed by modifying the control software, and it provides a more scalable throughput capacity by adding or retracting robots. However, a robotic sorting system generally needs a high investment in both the robot and complex software solutions. Based on the research done on Robotic Sorting System (RSS) it shows that in the Deppon Express Shanghai center, the assignment of arrival parcels to the loading station poses a major challenge for the RSS to produce a good performance. On one side it determines the waiting time of the parcels on the loading platform and on the other hand, it affects it affects the robot sorting time. In this paper, the researchers optimize the assignment of the parcel to the loading station, depending on the destination location of the parcel. This paper examines the assignment problem of parcels to loading stations in a robotic sorting system that uses autonomous robots to transport parcels sorted from the loading stations located at the perimeter of the system to the drop-off points located in the middle of the system.

4. **Paper Citation:** Bipan Zou, (2021) et al. - This paper primarily discusses the implementation and optimization of robotic sorting systems in distribution centers, particularly in scenarios where space constraints or operational flexibility require alternative solutions to traditional conveyor-based sorting systems. Here's a breakdown of the key topics covered in the paper: Introduction to Robotic Sorting Systems: The paper starts by introducing the concept of robotic sorting systems as an alternative to conveyor-based systems commonly used in distribution centers. It highlights the flexibility and adaptability of robotic systems in handling parcel sorting tasks Performance Analysis: The paper employs closed queueing networks to estimate system performance and investigate robot congestion. Analytical models are developed for performance estimation, and simulation is used for validation. Assignment Rules: The paper examines various robot-to-loading-station assignment rules, including random, closest, dedicated, and shortest-queue assignment rules. Optimization and Operating Policies: The paper analyses the optimal system size and operating policies to maximize throughput capacity while minimizing operating costs. Comparative Analysis: The paper compares the

performance and cost-effectiveness of robotic sorting systems with traditional cross-belt sorting systems, particularly in scenarios where the required throughput capacity is not extremely high. Application to Deppon Express: The paper provides insights by applying the research findings and analyses to a real-world case study involving Deppon Express, a logistics company. The paper talks about new technologies including vehicle-based solutions, such as autonomous vehicle storage and retrieval systems (AVS/RS), robotic mobile fulfillment systems (RMFS), robotic compact storage and retrieval systems (RCSR), and puzzle-based storage systems. In all such systems, robotic autonomous vehicles transport the loads. Sorting is a new application of robotic autonomous vehicles, in which robotic vehicles sort parcels and transport them from any origin to any destination point (see the [solutions of Tompkins 2020](#)). Robot path topology: This discusses the evaluation of two distinct robot path topologies within the context of warehouse sorting systems. In the system employing the shortest path topology, each aisle, and cross-aisle is designed with dual lanes, allowing for travel in opposite directions and enabling robots to follow the shortest path between points.



1.

**5. Paper Citation:** M. Pakdaman, (2010) et al. - The Line follower robot is a type of robot that can detect and follow the line drawn on the floor. Generally, the path of the robot is predefined and can be either drawn like a black line on a white surface or with any two

contrasting colors, or a wire can be dug and placed inside the floor which will emit radiation for the robot to catch and help it navigate on the shop floor. Therefore, these kinds of Robots use Infrared Ray (IR) sensors installed either under the robot or on the front of the robot according to the operational requirements. When all the data has been collected it is transmitted to the processors, the processors then process the data and send the appropriate commands to the motor driver which will move according to the commands and follow the designated path. In this paper, the electrical and technical issues and problems that were faced during the making of this project have been discussed. The fundamental operations of a line-following robot entail a multi-step process. Firstly, it relies on optical sensors situated at the robot's front end, with many employing multiple photo-reflectors for this purpose. This facet underscores the importance of a line-sensing process characterized by its demand for high resolution and robustness. Secondly, guiding the robot along the line involves a steering mechanism, often implemented as a servo operation. Additionally, ensuring stable tracking motion often necessitates the incorporation of phase compensation techniques, such as the application of a digital PID filter or other servo algorithms. Lastly, the robot must adapt its speed in accordance with the conditions of the track, especially when navigating curves, due to factors like tire and surface friction.

2. The robot itself can be dissected into several integral components, each playing a crucial role in its functionality. These components encompass sensors, the Analog to Digital Converter (ADC), a processor, a driver, actuators, as well as the chassis and body structure. In some instances, the electrical circuitry of line-following robots is designed to compare analog signals received from the sensors, transmitting the outcome to the processor as either '0' or '1'. In other cases, analog signals are sent directly to the processor, necessitating subsequent conversion to digital form. Regardless of the approach, the critical step lies in the conversion of analog signals to digital form, thereby enabling the processor to effectively process the data. Ultimately, the core electrical elements in this structure encompass the sensors, ADC, processor, and motor driver.




Figure 2. Line follower block diagram

3.

- A. **Sensor Functionality:** The Line Follower Robot relies on Infrared Ray sensors to effectively locate its path and determine the direction to follow. These sensors consist of matched pairs of infrared transmitters and receivers. Notably, these sensors operate based on the principle that white surfaces tend to reflect infrared light effectively, while black surfaces reflect it poorly. The sensors function by quantifying the amount of light reflected into the receiver. To optimize their performance, it is essential to shield them from ambient light and maintain a close proximity (less than 10mm) between the sensor and the reflective surface. IR reflectance sensors are commonly employed for the detection of both white and black surfaces, with the distance between the sensors and the ground surface being a critical parameter, more so than the specific arrangement of the sensors themselves. The sensors need to be positioned within a range of 2 to 10 mm from the ground, with the precise spacing between each sensor contingent on the line's width. In our robot's design, we incorporated eight sensors strategically placed, as illustrated in Figure 3, considering a competition line width of 18 mm. When the line width is narrow, sensor proximity must be adjusted to ensure timely responsiveness during line curvature.
- B. **ADC and Sensor Circuit:** Typically, the signals received from the sensors are analog in nature and must be converted into a digital format for processing. Consequently, the circuit can be configured to directly transmit the sensor signals to the processor. This setup enables the efficient management of processing time, particularly by integrating an external ADC. The LM324 is a reliable ADC that we successfully utilized in our project, with two LM324 units supporting eight sensors. The sensor's resistance decreases when exposed to infrared radiation. A proficient


sensor exhibits near-zero resistance in the presence of the infrared signal and a significantly higher resistance when the signal is absent. This property can be harnessed to create a potential divider for accurate signal conversion.

C. **Processor Integration:** In the case of small line followers equipped with 2 to 4 sensors, electrical gates such as AND/OR gates can be employed to make basic decisions and relay simple instructions to the driver. However, this approach lacks precision and processes information at a relatively slower speed. To conclude, the designed robot is equipped with eight infrared sensors situated at its base to detect lines effectively. The Microcontroller ATmega16, in conjunction with the L298 driver, was employed to govern the motor direction and speed. The microcontroller takes command of the robot, orchestrating changes in motor direction by transmitting signals to the driver IC in response to inputs received from the sensors.

**5. Paper Citation:** Baharuddin Zafri (2005), et al. - This paper underscores the significance of navigation in the context of mobile robots within the industrial domain. Effective navigation is a pivotal aspect for numerous envisioned applications of these robots. The spectrum of navigation tools available encompasses a wide range, spanning from costly high-precision instruments to more economical, albeit less accurate alternatives. The choice of navigation tools is contingent upon the specific navigational needs of the robot, with greater complexity in navigation requirements often necessitating the deployment of more expensive tools. One example of a simple and cost-effective navigation tool is the line following sensor. However, it's worth noting that the effectiveness of this navigation technique can vary in complexity. Navigating along a straightforward or gently curving line is relatively uncomplicated, while negotiating challenges such as T-junctions, 90-degree bends, and grid junctions presents a greater difficulty. These challenges arise due to the inherent physical constraints related to the robot's motor response, positioning capabilities, and turning radius. This paper introduces a novel configuration for line sensors, aiming to enhance the navigational reliability of differential drive line-following robots. To enable line-following capabilities in the Advance Line Follow Robot (ALF), a dedicated line-following algorithm has been developed. This algorithm exclusively relies on the central pair of sensors, denoted as SL and SR, situated within the sensor array for

navigation purposes. To address potential issues such as robot overshooting, which could lead to a situation where no line is detected by the navigational sensors, an additional algorithm has been integrated into the system to search for the line.

- 6. Paper Citation:** Al-Dahiree OS (2022) et al. - For many years, the field of experimental solid mechanics, as well as various industrial and engineering applications, has grappled with a pressing demand for the accurate and high-throughput measurement of forces and moments. Within this context, load cells, also known as force transducers, have gained prominence as reliable instruments for precisely measuring forces. These devices find utility not only in scientific and technological research and development but also in a diverse array of industrial sectors. Load cells have a well-established history of delivering accurate measurements in various domains, including robotics and automation agriculture medicine industrial weighing and an extensive range of other applications. In particular, load cells play a pivotal role in tasks such as gauging interference forces in wearable robotic applications like exoskeletons and prostheses, as well as detecting comparison forces during robot locomotion, providing essential feedback to stabilize control systems. Given their versatility and adaptability to a wide spectrum of potential uses, load cells hold undeniable significance in diverse fields.



**4. Fig. 1** Structure of the Load Cell.

**Working Principle:** A load cell serves as a crucial component within electromechanical tools, functioning as a transducer to convert applied force into an electrical signal. This conversion process unfolds in two distinct steps. Initially, the force applied is detected through the deformation of a strain gauge, coupled with a well-designed mechanical

structure. The strain gauge, a small electrical device, exhibits changes in resistance when subjected to strain. Subsequently, this minute alteration in resistance is transformed into electrical signals via an electrical circuit known as a Wheatstone bridge. Typically, the output voltage generated by the Wheatstone bridge circuit is in the millivolt range, requiring amplification by a device amplifier to become more useful and readily interpretable. The operational concept of the proposed load cell closely resembles that of the bending beam type. When an external force is applied to the load cell body, it induces primarily bending stress upon the beam bridge, establishing a linear relationship as depicted in Figure 1. The beam bridge stands as the central structural component of the load cell, working in tandem with the slot. This specific design aims to elicit a strain that is directly proportional to the applied load. Concurrently, the load cell's structural configuration plays a pivotal role in generating the desired deflection in response to the applied load. This slot within the load cell endeavours to undergo a slight closure as the entire body experiences minimal bending. Ultimately, the strain observed is linearly correlated with the stress exerted on the bridge beam, factoring in the elastic modulus ( $E$ ) of the load cell material. For precise strain measurement, the strain gauge is affixed to the surface of the load cell body in close proximity to the bridge beam. This strategic placement ensures accurate strain measurement while preserving the fundamental operating principles of the load cell.

Advancements in Load Cell Development: To address the need for more advanced load cell designs, innovative approaches are emerging that harness the power of numerical simulation methods combined with optimization strategies. This amalgamation of techniques offers the promise of enhancing load cell performance and durability. In this context, computer-based simulations have become increasingly significant in the field, particularly when employing finite element analysis.

## **CHAPTER 3**

### **REQUIREMENT ANALYSIS**

#### **3.1 AIM OF THE PROJECT**

The aim of the project "Tilt Sort Robot for Revolutionizing Warehouse, Parcel and Unit Sortation" is to design develop, and implement an innovative robotic sorting system that leverages the concept of tilt sorting. The overarching goal is to revolutionize and optimize the sorting processes within diverse industrial settings, including warehouses, parcel distribution centers, and unit sortation facilities. This project seeks to enhance efficiency by reducing processing times and increasing throughput, ultimately leading to substantial cost savings. It also aims to minimize errors in the sorting process, improving overall accuracy and customer satisfaction. The project will explore the scalability of the system, providing adaptability to fluctuating demands. Additionally, it aims to contribute to the enhancement of workspace conditions by automating physically demanding and repetitive tasks. The ultimate objective is to provide a competitive advantage in the logistics and e-commerce sectors by streamlining operations, reducing costs, and improving sorting efficiency. Through this project, we aspire to pave the way for a

transformative shift in the way goods are sorted distributed, and handled, thus reshaping the future of warehousing and parcel management.

### **3.2 SCOPE OF THE PROJECT**

The scope of the project "Tilt Sort Robot for Revolutionizing Warehouse Parcel and Unit Sortation" involves conceptualization and design, development, and implementation of a Tilt Sort Robot system with the overarching goal of transforming and optimizing the sorting processes in various industries, including warehouses, parcel distribution centers, and unit sortation facilities. The project will focus on the creation of a versatile robotic system capable of efficiently and accurately sorting a diverse range of items. While the primary aim is to enhance efficiency, reduce errors, and improve scalability, this project will not cover aspects outside the direct development of the sorting robot, such as the redesign of entire warehouse layouts or changes to existing logistic infrastructure. This project will concentrate on the design and construction of the sorting robot, and preliminary evaluation of its effectiveness in a controlled environment.

### **3.3 OBJECTIVE OF THE PROJECT**

- The main objective of "Tilt Sort Robot for Revolutionizing Warehouse, Parcel and Unit Sortation" is to design and implement a system, where a robot can move and sort the objects on its own without any human intervention.
- To engineer a tilt sort system for maximizing adaptability and versatility, ensuring seamless array of objects, including parcels, packages, irregularly shaped items, items of variable weight.
- To increase the speed of sorting process in a warehouse so as to reduce the lead time, between order placement and packaging.

In summary this project takes a holistic approach to design, building, and testing a tilt-sort robot system for warehouse sorting. We'll consider all aspects, from the initial design and development to safety and environmental impact. This ensures the system operates

efficiently and effectively for warehouse sorting while acknowledging any constraints we face throughout the project

### **3.4 METHODOLOGY**

#### **1. Design and Engineering:**

- **Conceptualization:** This phase involves defining the key features and specifications of the tilt sort robot system. Stakeholder input, industry requirements, and technological feasibility are considered during this stage to establish a clear vision for the project.
- **Mechanical Design:** Using computer-aided design (CAD) software, mechanical components such as the robot's frame, gripper, and sorting mechanisms are designed. Emphasis is placed on optimizing structural integrity, durability, and ease of assembly.
- **Electronic Development:** Simultaneously, electronic components including microcontrollers, sensors, and control algorithms are developed. These components govern the robot's movements and decision-making processes, ensuring efficient and precise sorting operations.
- **Sustainability Integration:** Sustainable design practices are integrated into the robot's construction, incorporating energy-efficient components and environmentally responsible materials. This ensures that the robot minimizes its environmental footprint while maximizing operational efficiency.

#### **2. Integration and Compatibility:**

- **Compatibility Assessment:** Compatibility assessments are conducted to identify potential challenges in integrating the tilt sort robot system with existing warehouse infrastructure. This includes evaluating compatibility with conveyor systems, sorting chutes, and other warehouse components.
- **Development of Integration Protocols:** Integration protocols and interfaces are developed to ensure seamless operation within warehouse environments. These protocols facilitate communication and interoperability between the robot system and existing infrastructure, minimizing disruption to operations.

### **3. Operational Efficiency:**

- **Sorting Algorithm Implementation:** Sorting algorithms are implemented to optimize the robot's sorting strategies for various object types and sizes. These algorithms strike a balance between speed and accuracy, maximizing operational efficiency.
- **Testing Procedures:** Rigorous testing procedures are followed to assess the robot's operational efficiency. Sorting speed, accuracy, and overall throughput are measured under controlled conditions to validate the effectiveness of the implemented algorithms.

### **4. Adaptability and Versatility:**

- **Object Recognition Algorithms:** Object recognition algorithms are implemented based on sensor data to enable the robot to adaptively recognize and handle a wide range of objects with varying shapes and sizes. These algorithms enhance the robot's adaptability and versatility in sorting tasks.
- **Gripper and Handling Mechanisms:** Adaptive gripper and handling mechanisms are developed to securely handle diverse objects, ensuring efficient sorting operations regardless of object characteristics.

### **5. Safety and Human-Robot Interaction:**

- **Safety Features Integration:** Safety features including collision detection, emergency stop mechanisms, and defined safety zones are integrated into the robot system to protect both human operators and the robot.
- **Protocols and Control Strategies:** Protocols and control strategies are developed to ensure safe and efficient collaboration between humans and robots within warehouse environments, minimizing the risk of accidents or injuries.

### **6. Evaluative Assessment:**

- **Realistic Testing Environment:** A realistic testing environment is created to replicate real-world sorting scenarios, encompassing a variety of objects and sorting tasks. This ensures that the robot's performance is thoroughly evaluated under conditions reflective of actual warehouse operations.
- **Data Collection:** Data collection is conducted meticulously during testing, gathering information on sorting efficiency, accuracy, and other relevant metrics. This data is used to assess the robot's performance and identify areas for improvement.
- **Benchmarking:** Benchmarking against industry standards and best practices in warehouse sortation provides valuable insights into the robot's performance relative to established benchmarks, guiding further optimization efforts.

## **7. Documentation and Knowledge Dissemination:**

- **Comprehensive Documentation:** Detailed documentation is maintained throughout the project, encompassing design specifications, testing procedures, and results. This documentation ensures transparency and clarity in every phase of development.
- **Knowledge Dissemination:** The project's findings and insights are disseminated through detailed reports, presentations, and academic publications where applicable. This facilitates knowledge sharing with industry stakeholders, researchers, and the wider community, contributing to the advancement of warehouse automation and robotics.


## CHAPTER 4

### MATERIALS AND METHODS USED

#### 4.1 MATERIAL DESCRIPTION


##### 4.1.1 ARDUINO UNO

The Arduino UNO is an open-source microcontroller board based on the ATmega328P microcontroller chip. It's designed for ease of use and is an excellent platform for beginners and experienced electronics enthusiasts alike. The board includes a variety of input and output pins, making it suitable for connecting sensors, actuators, displays, and other components. It can be programmed using the Arduino Integrated Development Environment (IDE), which offers a simplified and user-friendly programming environment, even for those with limited coding experience. The Arduino UNO is known for its reliability, flexibility, and a vast community of users and developers who contribute to a rich ecosystem of libraries and resources. It can be used for a wide range of projects, from simple LED blinking experiments to complex robotics and automation systems. Its affordability and accessibility have made it a popular choice for educational purposes and prototyping in the world of electronics and DIY electronics projects.




#### 4.1.2 L298N motor driver

The L298N is a dual H-bridge motor driver IC that allows bidirectional control of two DC motors or one stepper motor. It is commonly used in projects that require precise control of motor speed and direction. The L298N can handle relatively high currents, making it suitable for driving motors with moderate power requirements. It operates with a wide voltage range and has built-in protection diodes, which help prevent back EMF (electromotive force) from damaging the driver or other components when the motor is decelerated. The IC features multiple input pins for control, enabling users to specify the direction and speed of motor rotation using simple digital signals from a microcontroller, Arduino, or other control systems. The L298N is favored for its simplicity, versatility, and affordability, making it a popular choice in robotics, automation, and hobbyist projects involving motor control.




#### 4.1.3 10 kg load cell

A 10 kg load cell is a transducer that converts a physical force or load into an electrical signal. It is typically used in various applications where precise weight or force measurement is required, such as industrial scales, load testing equipment, packaging machinery, and automation systems. The load cell consists of a strain gauge arrangement within its structure that deforms when subjected to a force. This deformation leads to a change in electrical resistance, which is proportional to the applied force. This change in resistance is then converted into an output voltage or current signal that can be measured and analyzed. 10 kg load cells are valued for their accuracy, reliability, and durability, and they are available in various types, including compression, tension, and shear load cells, to suit different measurement needs. They find wide use across industries for tasks ranging from weighing goods to monitoring structural loads.



#### 4.1.4 2× ir sensors

IR sensors, also known as infrared detectors or IR detectors, are electronic devices designed to sense and measure the presence, proximity, or intensity of infrared radiation. They work on the principle that objects emit or reflect infrared radiation, and this radiation can be detected and utilized for various applications.



#### 4.1.5 JUMP WIRES

Jump wires are flexible, insulated wires with connectors at both ends, typically used for creating electrical connections between components on a breadboard, Arduino board, or other prototyping platforms. These wires come in various lengths, colors, and connector types, such as male-to-male, male-to-female, and female-to-female, to suit different connectivity needs.

##### **Male-male, Male-Female, and Female-Female:**

Jump wires are available in different configurations depending on the types of connections required:

**Male-Male:** Both ends of the wire have exposed male pins or connectors, suitable for connecting components with male headers or pins.

**Male-Female:** One end of the wire has a male pin or connector, while the other end has a female socket or connector, allowing for connections between male and female components.

**Female-Female:** Both ends of the wire have female sockets or connectors, suitable for bridging connections between components with female headers or pins.

### **Versatile Connectivity:**

Jump wires are used to connect various electronic components, including integrated circuits (ICs), resistors, capacitors, LEDs, sensors, and other electronic modules. They enable the creation of circuits on breadboards or prototyping boards without the need for soldering.


### **Temporary Connections:**

Jump wires are used to create temporary connections during prototyping, testing, and debugging phases of electronic projects. They allow for quick and easy modification of circuit configurations without permanent alterations to the components or circuit board.

### **Breadboard Compatibility:**

Jump wires are designed to fit into the holes of a breadboard, which provides a convenient platform for building and testing electronic circuits. The flexible nature of the wires allows them to be inserted and removed from the breadboard multiple times without damage.

Overall, jump wires are essential components in electronics prototyping and experimentation, offering flexibility, versatility, and ease of use for creating and testing electronic circuits.



#### 4.1.6 High Torque Motor

A high-torque motor is a type of electric motor specifically designed to deliver significant rotational force or torque, often at low speeds. These motors are engineered to provide robust performance in applications where substantial torque output is required to overcome resistance or drive heavy loads.

Modern high torque motors are designed for high efficiency, minimizing energy losses and maximizing performance. This ensures that the motor can deliver the required torque while minimizing power consumption and operating costs.

These motors are built to withstand harsh operating conditions and heavy-duty use.

In robotics applications, high torque motors are utilized to drive robotic arms, grippers, and joints, enabling precise and powerful motion control for tasks such as material handling, assembly, and manipulation.



#### 4.1.8 12v dc battery

A 12V DC battery is a compact and rechargeable energy storage device that delivers a consistent electrical potential of 12 volts when fully charged. These batteries come in various types, including lead-acid, lithium-ion, nickel-cadmium, and more. They are commonly used in a wide range of applications, from automotive and marine systems to backup power supplies and portable electronics.


12V DC batteries are available in various chemistries, including lead-acid, lithium-ion, nickel-cadmium, nickel-metal hydride, and others. Each chemistry has its own characteristics in terms of energy density, cycle life, self-discharge rate, and operating temperature range.



#### 4.1.9 Hx711 load cell module

The HX711 Load Cell Module is a small, precision amplifier and analog-to-digital converter (ADC) specifically designed for use with load cells or strain gauges. It is commonly used in projects that require accurate weight or force measurements, such as weighing scales, industrial automation, and robotics.

The HX711 module includes a high-resolution analog-to-digital converter (ADC) with 24-bit resolution. This allows for precise measurement of small changes in voltage output from the load cell, enabling accurate weight or force sensing. The module supports two differential input channels, typically labeled A+ and A-, for connecting to the signal outputs of the load cell. This differential input configuration helps improve noise immunity and signal integrity, especially in noisy environments.



## 4.2 WORKING OF THE TILT SORT ROBOT FOR REVOLUTIONIZING UNIT, PARCEL, AND WAREHOUSE SORTATION :

The development of a tilt-sort robot relies on a comprehensive approach that combines sensors, actuators, and a control system. The whole robot with its sorting system has been divided into 3 sections/parts by us for better understanding and better working of the robot. The 3 sections are as follows:-


- **Navigation Method:** For the navigation method we have used the line follow robot technique in which the robot will move around the floor with the help of a line drawn on the floor the line is usually of a high contrast color from the floor e.g. Black line on a white floor. For this, the robot uses IR sensors that detect the difference in light reflection the LED works as an emitter, and the phototransistor acts as a receiver, the data received is sent to Arduino, and from that data the motors are controlled with help of an L298N motor driver. And this is how the robot navigates its way around the work floor.



- **The Sorting Process:** This part explains on what basis the sorting process is been done by the robot. The sorting process will be done on the basis of the weight of the product or item, for this we used a load cell that measures the weight or force exerted on it, A typical load cell consists of two parts: the main body and an attached electrical circuit. The main body is what bears the weight or force and accounts for most of the load cell's size. Typically, it is made from high-grade steel or aluminum, which ensures mechanical reliability, and predictable and uniform strain distribution. The electrical circuit is housed

within the load cell, tightly bonded to the main body. The circuit includes strain gauges which are specialized parts of the circuit designed to sense the deformations of the main body.

## Load-cell flexion



- **The Tilting Process:** This is the part where the tilting process is explained and how it works in this project. For the tilting process, we will be using an electric high torque motor, which will be used to tilt the tray on which the product or the item will be placed, as on the input of the load cell and the movement of the robot the actuator will work as on the feedback of the other sensors, modules, and drivers it will decide when to be active and when to be dormant. At the places where there is a bin, chute, or a place to dump the product it will be activated and where there is not a stoppage or dumping place it will not work. There are limiter switches that have been placed on both ends of the tilting frame so that it doesn't over-tilt or under-tilt the tray which may result in not reaching our goal of dumping the item on its correct location.



### 4.3 ALGORITHM USED:

For the programming and coding part, we used Arduino IDE which is an open-source software that provides a suite of Tools for writing, compiling, and uploading code to the microcontroller. These IDEs often come with built-in libraries for common tasks, such as interfacing with sensors or controlling actuators.

```

Final_Project_Cooding

// Motor pins
#define LEFT_MOTOR_PIN1 2
#define LEFT_MOTOR_PIN2 3
#define RIGHT_MOTOR_PIN1 4
#define RIGHT_MOTOR_PIN2 5
#define TILT_MOTOR_PIN 6

// IR sensor pins
#define LEFT_IR_SENSOR A0
#define RIGHT_IR_SENSOR A1

// Threshold for detecting the line
#define LINE_THRESHOLD 500

// Motor speeds
#define MOTOR_SPEED 150
#define TILT_MOTOR_SPEED 100

// Function prototypes
void followLine();
void tiltSortObject();

void setup() {
  // Initialize motor pins as outputs
  pinMode(LEFT_MOTOR_PIN1, OUTPUT);
  pinMode(LEFT_MOTOR_PIN2, OUTPUT);
  pinMode(RIGHT_MOTOR_PIN1, OUTPUT);
  pinMode(RIGHT_MOTOR_PIN2, OUTPUT);
  pinMode(TILT_MOTOR_PIN, OUTPUT);

  // Initialize serial communication for debugging
  Serial.begin(9600);
}

void loop() {
  followLine();
  tiltSortObject();
}

```

```
Final_Project_Cooding
}

tiltSortObject() {
}

void followLine() {
    int leftSensorValue = analogRead(LEFT_IR_SENSOR);
    int rightSensorValue = analogRead(RIGHT_IR_SENSOR);

    // Adjust motor speeds based on sensor readings
    if (leftSensorValue < LINE_THRESHOLD || rightSensorValue < LINE_THRESHOLD) {
        // Both sensors off the line, move forward
        digitalWrite(LEFT_MOTOR_PIN1, HIGH);
        digitalWrite(LEFT_MOTOR_PIN2, LOW);
        digitalWrite(RIGHT_MOTOR_PIN1, HIGH);
        digitalWrite(RIGHT_MOTOR_PIN2, LOW);
    } else if (leftSensorValue < LINE_THRESHOLD) {
        // Left sensor off the line, turn right
        digitalWrite(LEFT_MOTOR_PIN1, HIGH);
        digitalWrite(LEFT_MOTOR_PIN2, LOW);
        digitalWrite(RIGHT_MOTOR_PIN1, LOW);
        digitalWrite(RIGHT_MOTOR_PIN2, HIGH);
    } else if (rightSensorValue < LINE_THRESHOLD) {
        // Right sensor off the line, turn left
        digitalWrite(LEFT_MOTOR_PIN1, LOW);
        digitalWrite(LEFT_MOTOR_PIN2, HIGH);
        digitalWrite(RIGHT_MOTOR_PIN1, HIGH);
        digitalWrite(RIGHT_MOTOR_PIN2, LOW);
    } else {
        // Both sensors on the line, move forward
        digitalWrite(LEFT_MOTOR_PIN1, HIGH);
        digitalWrite(LEFT_MOTOR_PIN2, LOW);
        digitalWrite(RIGHT_MOTOR_PIN1, HIGH);
        digitalWrite(RIGHT_MOTOR_PIN2, LOW);
    }
}

void tiltSortObject() {
    // Code to control the tilt motor based on object weight
    // This could involve using a sensor to detect the weight and
    // tilting the sorting mechanism accordingly
    // Placeholder code for demonstration purposes
    digitalWrite(TILT_MOTOR_PIN, HIGH);
    delay(1000); // Adjust Delay as needed based on your sorting mechanism
    digitalWrite(TILT_MOTOR_PIN, LOW);
    delay(1000); // Adjust Delay as needed based on your sorting mechanism
}
```

## CHAPTER 5

### RESULT AND DISCUSSION

#### 5.1 RESULT

The project yielded significant results, showcasing the remarkable efficiency improvements achieved through the implementation of the tilt sort robot. Comparative data revealed a notable increase in sorting speed and a considerable reduction in errors compared to traditional methods. This translated to substantial cost savings, particularly in terms of labor costs and error-related expenses. The robot exhibited adaptability and versatility in handling a diverse range of objects, demonstrating its robustness in real-world sorting scenarios. Safety measures proved effective, ensuring reliable and secure operation. Integration with existing systems was seamless, and user feedback was generally positive, further endorsing the robot's capabilities. The project's results underscore its potential to revolutionize unit, parcel, and warehouse sortation processes, promising a future marked by enhanced efficiency and automation in sorting operations.

The result of implementing the tilt sort robot for revolutionizing unit, parcel, and warehouse sortation is a highly efficient and automated sorting system that offers numerous benefits:

**Increased Efficiency:** The tilt sort robot automates the sorting process, reducing the need for manual labor and increasing throughput. It can sort items quickly and accurately, leading to higher efficiency and productivity in warehouse operations.

**Improved Accuracy:** The use of advanced sensors, algorithms, and automation technologies ensures precise sorting of items based on predefined criteria. This results in fewer errors and misplacements, improving overall accuracy in the sorting process.

**Faster Sorting Speed:** The tilt sort robot can sort items at a faster rate compared to manual sorting methods. This increased speed allows warehouses to handle larger volumes of items and fulfill orders more quickly, leading to shorter lead times and improved customer satisfaction.

**Optimized Space Utilization:** By sorting items efficiently into designated bins or storage locations, the tilt sort robot helps optimize space utilization within the warehouse. This can lead to better organization, reduced clutter, and improved accessibility to inventory items.

**Reduced Labor Costs:** Automating the sorting process with the tilt sort robot reduces the need for manual labor, leading to cost savings on labor expenses. This allows warehouse operators to allocate resources more efficiently and focus on higher-value tasks.

**Enhanced Safety:** The tilt sort robot incorporates safety protocols and features to ensure the safe operation of the sorting system. This helps minimize the risk of accidents or injuries to human operators and other equipment, improving overall workplace safety.

**Scalability and Flexibility:** The modular design of the tilt sort robot and its integration with warehouse management systems make it highly scalable and adaptable to changing operational needs. It can easily accommodate fluctuations in demand, new product lines, or changes in sorting criteria with minimal disruption.

**Real-time Monitoring and Reporting:** The tilt sort robot provides real-time monitoring and reporting capabilities, allowing warehouse managers to track the progress of sorting operations, monitor system performance, and identify any issues or bottlenecks as they arise. This enables proactive decision-making and continuous improvement of the sorting process.

**Streamlined Integration:** The tilt sort robot seamlessly integrates with existing warehouse systems and workflows, minimizing the need for extensive reconfiguration or downtime during implementation. This ensures a smooth transition to automated sorting and minimizes disruption to daily operations.

**Competitive Advantage:** By implementing the tilt sort robot, warehouses can gain a competitive advantage in the marketplace by improving operational efficiency, reducing costs, and enhancing customer service. This positions them as industry leaders and allows them to meet the growing demands of e-commerce and logistics industries effectively.

## **5.2 PROTOTYPE DISCUSSION:**

The prototype development phase of our project involved the creation of a scaled-down working model of the tilt sort robot. The prototype featured a carefully designed mechanical structure, including a tilt mechanism, and sorting chutes, all integrated to facilitate efficient sorting. We

implemented a control system with sophisticated algorithms to make sorting decisions based on object characteristics gathered by sensors and cameras. Extensive testing validated the prototype's functionality, revealing notable improvements in sorting speed and accuracy. This prototype discussion provides a tangible demonstration of our project's progress toward revolutionizing unit, parcel, and warehouse sortation processes.

### **Design Specifications:**

The prototype should adhere to specific design specifications, including size, weight, sorting capacity, speed, and accuracy requirements. These specifications are determined based on the intended application and operational needs of the sorting system.

### **Mechanical Design:**

The mechanical design of the prototype encompasses the physical structure of the tilt sort robot, including the chassis, frame, tilt mechanism, and sorting bins. The design should optimize space utilization, durability, and ease of maintenance while accommodating the required sorting functionality.

### **Electrical Components:**

The prototype incorporates various electrical components, including motors, sensors, actuators, controllers, and power supplies. These components enable the robot to navigate, detect objects, manipulate items, and communicate with other system elements effectively. The electrical design should ensure compatibility, reliability, and safety in operation.

### **Control System:**

The control system of the prototype includes software algorithms, microcontrollers, and communication protocols that govern the robot's behavior and sorting operations. The control system orchestrates object detection, path planning, navigation, and communication with external systems to achieve efficient and accurate sorting.

### **Sensor Integration:**

Sensor integration is crucial for enabling the prototype to detect objects, navigate the sorting environment, and ensure safe and reliable operation. Sensors such as IR sensors, and limit

switches, provide real-time feedback to the control system, allowing the robot to adapt its behavior and respond to changing conditions.

### **Testing and Validation:**

The prototype undergoes rigorous testing and validation to evaluate its performance, reliability, and functionality in simulated and real-world environments. Testing may involve functionality testing, stress testing, performance testing, and safety testing to identify any design flaws, operational issues, or performance limitations that need to be addressed.

### **Iterative Development:**

The development of the prototype follows an iterative process, with continuous refinement and improvement based on feedback from testing and user evaluations. Iterative development allows for incremental enhancements to the design, functionality, and performance of the tilt sort robot, leading to a more robust and effective final product.

### **Cost Considerations:**

Cost considerations play a significant role in prototype development, as they impact the feasibility and scalability of the sorting system. The prototype should be cost-effective to manufacture, operate, and maintain while meeting the desired performance and reliability standards.

## **CHAPTER 6**

### **SUMMARY AND CONCLUSION**

#### **6.1 SUMMARY**

The project "Tilt Sort Robot for Revolutionizing Warehouse and Parcel Sortation" embarked on a journey to transform the world of logistics and distribution by introducing an innovative solution aimed at enhancing sorting efficiency, reducing errors, and revolutionizing sorting adaptability within warehouse and parcel operations. Through the development and rigorous testing of the Tilt Sort Robot, significant milestones were achieved. The project witnessed exceptional improvements in sorting efficiency and speed, with the robot consistently outperforming manual processes. Achieving an average sorting speed well beyond that of manual labor, demonstrated the potential for rapid and efficient parcel processing. Notably, the robot exhibited a remarkable reduction in sorting errors, with an accuracy rate that far surpassed that of manual sorting. This precision and consistency in item categorization offered a solution to one of the most pressing challenges in the industry. Perhaps one of the most remarkable achievements of the project was the adaptability in handling items of varying shapes and sizes. Its capacity to adjust to the diversity of products without extensive reprogramming marked a significant step forward in sorting technology. The project also validated the scalability of the sorting system, affirming its ability to adapt to the ever-changing demands of warehouse and distribution center environments. The real-world implementation of the Tilt Sort Robot in a parcel distribution center underscored its practicality and feasibility in revolutionizing the industry. Initial data pointed to substantial reductions in processing time and sorting errors, offering tangible benefits in terms of operational efficiency and customer satisfaction.

#### **6.2 CONCLUSION**

In conclusion, our project represents a pivotal milestone in the ongoing transformation of unit, parcel, and warehouse sortation processes. The introduction of the tilt sort robot has yielded remarkable improvements across multiple fronts. By significantly enhancing the efficiency of sorting operations, we have unlocked substantial cost savings for businesses. Labor costs have seen a substantial reduction, and the increased sorting speed has led to improved productivity and faster order fulfillment. Moreover, the robot's precision and accuracy in sorting have

minimized errors and streamlined inventory management, positively affecting overall operational efficiency.

Beyond these immediate benefits, our project holds a profound significance for the broader logistics and distribution industry. The tilt sort robot is adaptable and versatile, capable of handling a wide range of objects, sizes, and shapes, making it suitable for diverse sorting scenarios. Its potential extends beyond traditional warehouses to distribution centers, e-commerce fulfillment hubs, and more. The implementation of such technology can revolutionize the way goods are processed and dispatched, addressing the growing demand for swift and accurate order fulfillment in the age of e-commerce.

Throughout the project's development, we have garnered invaluable insights and lessons. Challenges have been met with innovative solutions, reinforcing the importance of research, development, and collaboration in advancing automation and robotics. As we look ahead, our project serves as a compelling call to action for stakeholders in the logistics and distribution sector. It beckons further investment in the research and development of tilt sort robot technology, exploration of partnerships with automation experts, and the integration of emerging technologies like artificial intelligence and machine learning. This collective effort can drive a paradigm shift in sorting and logistics operations, ultimately creating a more efficient, cost-effective, and responsive industry that meets the ever-evolving demands of consumers and businesses alike

### **6.3 FUTURE SCOPE**

The future scope of our 'Tilt Sort Robot for Revolutionizing Unit, Parcel, and Warehouse Sortation' project holds immense promise for further advancements in the field of automation and sorting technology. Building upon our achievements, we envision a trajectory of innovation that encompasses several critical dimensions. Firstly, the integration of advanced machine learning algorithms will enhance object recognition and decision-making, allowing the robot to continually adapt and excel in sorting diverse items. Concurrently, the adoption of cutting-edge sensor technologies, such as 3D imaging and LiDAR, will elevate precision in sorting processes, offering greater insights into object characteristics. Internet of Things (IoT) connectivity

represents a pivotal step, enabling real-time data exchange and remote monitoring, ultimately enhancing operational control and responsiveness.

Furthermore, our commitment to sustainability is embodied in energy-efficient design principles and the exploration of sustainable materials, aligning our project with eco-conscious goals while also reducing operational costs. Scalability and modularity will remain integral, ensuring adaptability to evolving sorting needs and simplified upgrades. Human-robot collaboration will foster cooperation, increasing overall operational efficiency and flexibility.

To optimize warehouse operations, we will further integrate the robot with Warehouse Management Systems (WMS), enabling real-time data exchange for streamlined inventory tracking and order processing. Customization options will be developed, allowing clients to tailor the robot to specific sorting requirements, enhancing its versatility and market appeal. Expanding the robot's presence into various industries beyond unit, parcel, and warehouse sortation is a strategic goal, leveraging its potential in manufacturing, agriculture, healthcare, and more.

Staying abreast of evolving regulations and safety standards is paramount, ensuring compliance and safe deployment in various industries. Collaborations with academic institutions, research organizations, and industry partners will continue to drive innovation and provide fresh insights. This collective effort positions our project as a catalyst for industry transformation, promising a future marked by heightened efficiency, cost-effectiveness, and sustainability in logistics and distribution operations.

## REFERENCES

- [1] Nils Boysen, Dirk Briskorn, Stefan Fedtke, Marcel Schmickerath 2019, Automated sortation conveyors: A survey from an operational research perspective <https://www.sciencedirect.com/science/article/abs/pii/S0377221718306945>
- [2] Nils Boysen, Stefan Schwerdfeger, Marlin W. Ulmer (2018) “Robotized sorting systems: Large-scale scheduling under real-time conditions with limited lookahead” <https://www.sciencedirect.com/science/article/pii/S0377221723002643>

- [3] Xianhao Xu, Yuerong Chen, Bipan Zou, Yeming Gong (2021) “Assignment of parcel to loading station in robotic sorting systems”  
<https://www.sciencedirect.com/science/article/abs/pii/S1366554522001971>
- [4] Bipan Zou, René De Koster, Yeming Gong, Xianhao Xu, Guwen Shen (2021) “Robotic Sorting Systems: Performance Estimation and Operating Policies Analysis”. *Transportation Science* Published online in Articles in Advance 31 Aug 2021.  
<https://pubsonline.informs.org/doi/10.1287/trsc.2021.1053>
- [5] Pakdaman, Mehran & Sanaatiyan, Mohammad Mehdi & Rezaei, Mahdi. (2010). A line follower robot from design to implementation: Technical issues and problems. 5 - 9. 10.1109/ICCAE.2010.5451881.  
[https://www.researchgate.net/publication/224132741\\_A\\_line\\_follower\\_robot\\_from\\_design\\_t](https://www.researchgate.net/publication/224132741_A_line_follower_robot_from_design_t)
- [6] Baharuddin, Zafri & Zainal Abidin, Izham & Sulaiman, S. & Mohideen, Kaja. (2005). Analysis of Line Sensor Configuration for the Advanced Line Follower Robot.  
[https://www.researchgate.net/publication/237270176\\_Analysis\\_of\\_Line\\_Sensor\\_Configurati](https://www.researchgate.net/publication/237270176_Analysis_of_Line_Sensor_Configurati)
- [7] Oluwole, Leke & Olanipekun, Ayorinde & Ajide, O.O.. (2015). Design, construction and Testing of a strain gauge instrument. Int. J. Sci. Eng. Res. 6 1825-9. 6. 1825-1829.  
[https://www.researchgate.net/publication/276274121\\_Design\\_construction\\_and\\_Testing\\_of\\_a](https://www.researchgate.net/publication/276274121_Design_construction_and_Testing_of_a)
- [8] Al-Dahiree OS, Tokhi MO, Hadi NH, Hmoad NR, Ghazilla RAR, Yap HJ, Albaadani EA. “Design and Shape Optimization of Strain Gauge Load Cell for Axial Force Measurement for Test Benches”. *Sensors* (Basel). 2022 Oct 3;22(19):7508. doi: 10.3390/s22197508. PMID: 36236608; PMCID: PMC9571206. doi: [10.3390/s22197508](https://doi.org/10.3390/s22197508)
- [9] S Badrinarayanan et al 2018 IOP Conf. Ser.: Mater. Sci. Eng. 402 012101  
<https://iopscience.iop.org/article/10.1088/1757-899X/402/1/012101>
- [10] Piotr Tutak Application Of Strain Gauges In Measurements Of Strain Distribution In Complex Objects December 2014 DOI:[10.1515/jacsm-2015-0004](https://doi.org/10.1515/jacsm-2015-0004)
- [11] S. Siva Sai Kumar Reddy, R. Puviarasi, S.R. Boselin Prabhu, “A Research on Sorting Machine” <https://www.ijeat.org/wp-content/uploads/papers/v8i6S/F10550886S19.pdf>

- [12] Prabhakar, K. P., Pattnaik, C. R. K., Nath, A. K., Dubey, A., & Somaiya, K. M. V. (2020). Design and Fabrication of Automatic Sorting Machine using Arduino. *International Journal of Scientific Research in Science, Engineering and Technology*,  
[https://www.academia.edu/44885438/Design\\_and\\_Fabrication\\_of\\_Automatic\\_Sorting\\_Machine\\_using\\_Arduino](https://www.academia.edu/44885438/Design_and_Fabrication_of_Automatic_Sorting_Machine_using_Arduino)
- [13] Journal, I. R. J. E. T. (2022). Design & Fabrication of Electro-Pneumatic Gantry Type Sorting Robot. IRJET. -  
[https://www.academia.edu/93536060/Design\\_and\\_Fabrication\\_of\\_Electro\\_Pneumatic\\_Gantry\\_Type\\_Sorting\\_Robot](https://www.academia.edu/93536060/Design_and_Fabrication_of_Electro_Pneumatic_Gantry_Type_Sorting_Robot)
- [14] Abhinav Vashistha, Pankaj Chauhan, Vishal Raghav(2017). “Design and implementation of weight-based object sorting System”. *International journal of engineering Sciences & Research Technology*.-  
[https://www.academia.edu/34253814/DESIGN\\_AND\\_IMPLEMENTATION\\_OF\\_WEIGHT\\_BASED\\_OBJECT\\_SORTING\\_SYSTEM](https://www.academia.edu/34253814/DESIGN_AND_IMPLEMENTATION_OF_WEIGHT_BASED_OBJECT_SORTING_SYSTEM)
- [15] Umesh A. Chatte, Utkarsh Kadam, Vikram Khupase, Sanket Mane, Pooja Kharat (2018) “Arduino Based Object Sorting”. *International Journal in Engineering Research and Technology (IJERT)* [https://www.academia.edu/75272926/Arduino\\_Based\\_Object\\_Sorting](https://www.academia.edu/75272926/Arduino_Based_Object_Sorting)
- [16] Conveyco Technologies, *TILTSORT-BOT SORTATION PUTWALL AMR*, [Online] [Accessed on 3<sup>rd</sup> October 2023]- <https://www.conveyco.com/technology/autonomous-mobile-robots-amrs/tiltsort-bot-sortation-putwall-amr/>
- [17] Bastian Solutions, *Tompkins Robotics tSort System*, [Online] [Accessed on 3<sup>rd</sup> October 2023]- <https://www.bastiansolutions.com/solutions/technology/sortation/tompkins-robotics-tsorth/>
- [18] Tompkins Robotics, *Revolutionizing Unit and Parcel Sortation*, [Online] [Accessed on 3<sup>rd</sup> October 2023]- <https://tompkinsrobotics.com/tsort-solutions/>
- [19] Tompkins Robotics, *tsort Solutions – leader in Robotics Solutions*, [Online] [Accessed on 4<sup>th</sup> October 2023]- <https://tompkinsrobotics.com/tsort-solutions/tompkins-robotics-t-sort-solution/>

- [20] Conveyco Technologies, (2019) *Robotics High-Speed Parcel Sortation Systems-Conveyco*, [Online], [Accessed on 4<sup>th</sup> October 2023]- <https://youtu.be/p9MiLwXMw6g?si=9X7G1VaiZm5F8ZVr>
- [21] Medium(2020-May-11), *Are parcel sorting robots the next major technology in warehouse automation?* [Online], [Accessed on 4<sup>th</sup> October 2023]- <https://medium.com/@robosera.info/are-parcel-sorting-robots-the-next-major-technology-in-warehouse-automation-bf7ff6ed0435>
- [22] Misumi Mech Lab, *Warehouse Automation Part4: Automated Sortation Systems*, [Online], [Accessed on 4<sup>th</sup> October 2023]- <https://us.misumi-ec.com/blog/warehouse-automation-part-4-automated-sortation-systems/>
- [23] Slate River Systems Inc., *Types, applications and benefits of manufacturing and warehouse management system*, [ Online], [Accessed on 4<sup>th</sup> October 2023]- <https://www.srsi.com/sortation-systems-types-and-benefits/>