

DESIGN AND MANUFACTURING OF AN INDUSTRIAL MOBILE ROBOT USING ACCELEROMETER FOR VIBRATIONAL ANALYSIS

Submitted in partial fulfilment of the requirements for the award of

Bachelor of Engineering degree in

Mechatronics

By

SUDESH.V(Reg.No.40090031)

VINAY.V (Reg. No. 40090036)



DEPARTMENT OF MECHATRONICS

SCHOOL OF MECHANICAL ENGINEERING

SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY

(DEEMED TO BE UNIVERSITY)

Accredited with grade “A++” by NAAC

JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI – 600119

APRIL 2024



SATHYABAMA
INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)
Accredited with "A++" grade by NAAC
Jeppiaar Nagar, Rajiv Gandhi Salai, Chennai - 600 119
www.sathyabama.ac.in



DEPARTMENT OF MECHATRONICS

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of VINAY.V (Reg. No. 40090036) and SUDESH.V (Reg. No. 40090031) who carried out the project entitled **"DESIGN AND MANUFACTURING OF AN INDUSTRIAL MOBILE ROBOT USING ACCELEROMETER FOR VIBRATIONAL ANALYSIS"** Under our supervision from November 2023 to April 2024.

Internal Guide

Dr. M. Sangeetha., M.E., Ph.D.,

Head of the Department

Dr. B. Kanimozhi., M.E., Ph.D.,

Submitted for Viva voce Examination held on _____

Internal Examiner

External Examiner

DECLARATION

We, VINAY.V (40090036) and SUDESH.V(40090031), hereby declare that the Project Report entitled “**DESIGN AND MANUFACTURING OF AN INDUSTRIAL MOBILE ROBOT USING ACCELEROMETER FOR VIBRATIONAL ANALYSIS**” done by me under the guidance of **Dr. M. Sangeetha, M.E., Ph.D.**, is submitted in partial fulfilment of the requirements for the award of Bachelor of Engineering degree in Mechatronics.

DATE:



1. VINAY. V

PLACE:

SIGNATURE OF THE CANDIDATE



2. SUDESH V

SIGNATURE OF THE CANDIDATE

ACKNOWLEDGEMENT

I am pleased to acknowledge my sincere thanks to Board of Management of **SATHYABAMA** for their kind encouragement in doing this project and for completing it successfully. I am grateful to them.

I convey my sincere thanks **Dr. B. Kanimozhi., M.E., Ph.D.,** Head of the Department, Department of Mechatronics for providing me necessary support and details at the right time during the progressive reviews.

I would like to express my sincere and deep sense of gratitude to my Project Guide **Dr. M. Sangeetha., M.E., Ph.D.,** for her valuable guidance, suggestions and constant encouragement paved way for the successful completion of my project work.

I also express my thanks to all Teaching and Non-teaching staff members of the Department of Mechatronics who were helpful in many ways for the completion of the project.

ABSTRACT

This project explores the integration of vibration analysis techniques into a mobile robot equipped with a robotic arm, aiming to enhance the capabilities of non-destructive testing in industrial environments. The system utilizes accelerometers as vibration sensors to capture dynamic data from machinery under operation. The mobile robot, designed for versatility and adaptability, navigates through diverse environments, while the robotic arm provides the ability to manipulate and interact with the surroundings. Vibration data collected during the robot's traversal is analyzed using signal processing techniques to extract relevant parameters such as velocity, displacement, and acceleration. The results are presented through a user-friendly interface for real-time monitoring and comprehensive analysis. Now, data collected during inspections can be analyzed and interpreted in real-time, accelerating decision-making and streamlining maintenance procedures. It can pinpoint flaws more quickly, predict potential failures, and optimize the use of resources, ultimately leading to a greater return on investment.

TABLE OF CONTENTS

CHAPTER No.	TITLE	PAGE No.
	ABSTRACT	v
	LIST OF FIGURES	viii
	LIST OF TABLES	ix
1	INTRODUCTION	1
1.1	PREVENTIVE AND PREDICTIVE MAINTANCE	2
1.2	PREVENTIVE AND MAINTANCE METHODS	3
1.2.1	Ultrasonic Testing (UT)	3
1.2.2	Oil Analysis	3
1.2.3	Infrared Thermography	3
1.2.4	Electrical Testing	3
1.3	VIBRATION ANALYSIS AS AN NDT TECHNIQUE	4
1.4	ENHANCING ACCELEROMETER-BASED VIBRATIONAL ANALYSIS WITH MOBILE ROBOTS	4
2	LITERATURE SURVEY	6
3	AIM AND SCOPE	15
3.1	AIM AND SCOPE	15
3.2	SCOPE OF THE PROJECT	15
3.2.1	Reduced Human Exposure to Hazard	15
3.2.2	Real-time Analysis	15
3.2.3	Enhanced Data Accuracy	16
3.2.4	Communication and Reporting	16
3.2.5	Integration with Maintenance Systems	16
3.2.6	Predictive Maintenance Analytics	16
3.2.7	Cost Savings	16
4	MATERIALS AND EXPERIMENTAL METHOD	17

CHAPTER No.	TITLE	PAGE No.
	4.1.2 Data Collection	18
	4.1.3 Real-time Analysis and Decision Making	18
4.2	FAST FOURIER TRANSFORM	18
	4.2.1 Formula and Basic Concept	19
	4.2.2 Time-Domain to Frequency-Domain	19
	4.2.3 Frequency Analysis of Vibration Signals	19
	4.2.4 Sampling Rate and Data Length	20
	4.2.5 Aliasing and Frequency Folding	20
4.3	MATERIALS USED	21
	4.3.1 Arduino Uno	21
	4.3.2 L298N Motor Driver	22
	4.3.3 ADXL345 Accelerometer Sensor	23
	4.3.4 DC Motor	24
	4.3.5 Tank drive chassis	25
	4.3.6 Power Supply	25
	4.3.7 LM7805	26
	4.3.8 SD Card Reader Module	26
	4.3.9 Servo Moto	27
	4.3.10 HC-05	28
	4.3.11 Relay Module Wireless with RF	28
	4.3.12 Miscellaneous Components	29
4.4	DESIGN OF A 3D MODEL	29
	4.4.1 Identification of Design Objectives	30
	4.4.2 In-depth Problem Analysis	30
	4.4.3 Formulation of Design Specifications	30
	4.4.4 Exploration of Potential Solutions	30
	4.4.5 Comprehensive Evaluation	30
	4.4.6 Detailed Design	30
	4.4.7 Implementation and Testing	30
4.5	FABRICATION IMAGES	32
4.6	DATA PROCESSING USING MATLAB	35
5	RESULTS AND DISCUSSION	37

5.1	RESULTS	37
5.1.1	Real-time Data Analysis	37
5.1.2	Communication and Reporting	38
5.1.3	Scalability and Versatility	38
5.1.4	Data Logging	38
5.1.5	Real-time Alerts	39
5.1.6	Cost Saving	39
5.1.7	Preventive Maintenance	39
6	SUMMARY AND CONCLUSION	40
6.1	SUMMARY	40
6.2	CONCLUSION	40
	REFERENCES	42
7	APPENDIX	45

LIST OF FIGURES

FIGURE No	TITLE	PAGE No.
1.1	Basic Principle of Vibration analysis	4
4.1	Arduino Uno	21
4.2	L298N	22
4.3	ADXL345 Accelerometer Sensor	23
4.4	DC Motor	24
4.5	Tank drive chassis	25
4.6	LM7805	26
4.7	SD Card Reader Module	26
4.8	Servo Motor	27
4.9	HC-05	28
4.10	Relay Module Wireless with RF Remote Control	29
4.11	Design of proposed robot	31
4.12	Design of proposed robot using SolidWorks	31
4.13	This picture has taken during 3D printing	32
4.14	3D Printed parts	33
4.15	3D Printed parts	33
4.16	3D Printed parts	33
4.17	3D Printed parts	33
4.18	3D Printed parts	33
4.19	This picture was taken after assembling the 3d printed parts in the moving robot	34
4.20	MATLAB Program for Vibrational analysis	36
4.21	FFT Result using MATLAB	36

LIST OF TABLES

TABLE No	TITLE	PAGE No.
4.1	Specification of Arduino Uno R3	22

LIST OF SYMBOLS AND ABBEREVIATIONS

- **$X(k)$** : The discrete Fourier transform (DFT) of the input signal, representing the frequency domain.
- **$x(n)$** is the original signal value at index n
- **j** is the imaginary unit
- **e** is Euler's number
- **π** is 3.14
- N is the signal length.

CHAPTER 1

INTRODUCTION

Vibrational analysis, a cornerstone of modern maintenance practices, is a sophisticated technique employed to ensure the health and longevity of machinery and equipment. In the intricate oscillation of moving parts within industrial systems, vibrations speak a language of their own—a language that, when decoded through careful analysis, reveals invaluable insights into the condition of the machinery. At its core, vibrational analysis revolves around the measurement and interpretation of vibrations produced by rotating equipment such as motors, pumps, and turbines. The premise is simple yet profound: changes in vibration patterns can be indicative of underlying issues, from misalignments and unbalances to bearing wear and impending failures. By harnessing the power of precision sensors, this technique empowers maintenance teams to detect anomalies in the early stages, preventing catastrophic breakdowns and the costly repercussions that follow. The methodology behind vibrational analysis involves the deployment of specialized sensors strategically placed on equipment. These sensors capture the intricate vibrations emitted during normal operation, generating data that is then meticulously analyzed. Through the lens of frequency and amplitude, analysts can discern irregular patterns that may signify impending problems.

This proactive approach to maintenance not only minimizes the risk of unexpected downtime but also allows for planned interventions, ensuring that corrective measures are implemented before issues escalate. Vibrational analysis thus serves as a sentinel, tirelessly monitoring the pulse of machinery and providing a predictive roadmap for maintenance teams. In an era where efficiency and reliability are paramount, vibrational analysis stands as a testament to the marriage of technology and foresight. It enables industries to transcend the reactive paradigm of maintenance, embracing a proactive stance that safeguards investments, enhances productivity, and charts a course towards a future of optimized operational excellence.

Beyond the immediate benefits of early issue detection, vibrational analysis contributes significantly to resource optimization. By pinpointing specific areas of concern, maintenance efforts can be directed precisely where they are needed, eliminating the guesswork and reducing unnecessary downtime. This targeted approach not only saves time and resources but also fosters a more sustainable and cost-effective operational environment. Moreover, the data amassed through vibrational analysis forms a rich reservoir of information that can be leveraged for continuous improvement. Trend analysis and historical data interpretation provide valuable insights into the overall health of equipment, aiding in the refinement of maintenance strategies over time. As industries evolve, this wealth of information becomes a strategic asset, driving informed decision-making and fostering a culture of innovation and adaptability.

1.1 PREVENTIVE AND PREDICTIVE MAINTANCE

Preventive maintenance techniques involve proactive measures taken to prevent equipment failures and ensure the continued optimal performance of machinery. These techniques aim to identify and address potential issues before they escalate, reducing the risk of unexpected breakdowns and minimizing downtime. Examples include regular inspections, lubrication schedules, and the use of various diagnostic tools such as vibrational analysis, infrared thermography, and oil analysis. By implementing preventive maintenance, organizations can enhance equipment reliability, extend lifespan, and ultimately reduce overall maintenance costs.

Maintenance techniques encompass a range of activities undertaken to keep equipment and systems in working order. This includes both preventive measures to forestall potential issues and corrective actions to address existing problems. Maintenance may involve tasks such as routine inspections, cleaning, lubrication, part replacement, and repairs. By adopting a proactive maintenance approach and utilizing various diagnostic methods, organizations can optimize equipment performance, mitigate the risk of failures, and ensure the efficient operation of their assets over time.

1.2 PREVENTIVE AND MAINTANCE METHODS

Preventive maintenance techniques are proactive strategies employed to keep machinery and equipment in optimal condition, minimizing the risk of unexpected breakdowns and extending their operational lifespan. These techniques involve regular inspections, tests, and analyses to identify potential issues before they escalate into major problems. Vibrational analysis, oil analysis, infrared thermography, ultrasonic testing, visual inspection, electrical testing, equipment history documentation, and lubrication management are some common methods employed in preventive maintenance. By implementing these techniques, organizations aim to enhance reliability, reduce downtime, and ensure the efficient functioning of their assets.

1.2.1 Ultrasonic Testing (UT): Detects high-frequency sound waves emitted by equipment, which can indicate issues like leaks, electrical discharge, or friction in moving parts. Involves using ultrasonic sensors to capture and analyze sound waves that are beyond the range of human hearing.

1.2.2 Oil Analysis: Examines the physical and chemical properties of lubricating oil to identify signs of wear, contamination, or degradation. Regularly sampling and analyzing oil from machinery to assess the condition of components and detect potential problems early.

1.2.3 Infrared Thermography: Identifies abnormal temperature patterns in electrical and mechanical systems, helping to detect issues such as loose connections, overloaded circuits, or faulty components. Uses infrared cameras to capture thermal images of equipment, highlighting variations in temperature that may indicate potential problems.

1.2.4 Electrical Testing: Verifies the condition of electrical components and systems, helping to identify potential faults or weaknesses. Includes testing for insulation resistance, continuity, and checking electrical connections to ensure proper functioning.

1.3 VIBRATION ANALYSIS AS AN NDT TECHNIQUE

Vibration analysis is a powerful Non-Destructive Testing (NDT) technique that relies on accelerometers to monitor the health of machines and structures. Accelerometers are precise sensors that measure vibrations, translating them into electrical signals. These signals are then meticulously analyzed using techniques like frequency analysis and time-domain analysis, revealing characteristic patterns that indicate the presence of developing faults. By detecting changes in a machine's normal vibration signature, engineers can identify problems like bearing wear, misalignment, imbalance, structural cracks, or resonances before they cause critical failures. This facilitates proactive maintenance, reducing downtime, extending asset lifespan, and ensuring safe operation. Vibration analysis with accelerometers is widely used to inspect rotating machinery, assess the integrity of bridges and buildings, and even verify product quality during manufacturing.




Figure 1.1 Basic Principle of Vibration analysis [19]

1.4 ENHANCING ACCELEROMETER-BASED VIBRATIONAL ANALYSIS WITH MOBILE ROBOTS

Integrating mobile robots with accelerometers for vibration analysis in NDT offers significant potential for improvement. Mobile robots can reach hazardous or inaccessible locations, expanding the scope of inspections while protecting human inspectors. They enable automated and precise sensor placement, ensuring repeatable data collection, minimizing errors, and creating historical records ideal

for identifying trends. Mobile robots facilitate large-scale, efficient inspections, offering a detailed view of asset condition. The potential for real-time monitoring through robot deployment leads to faster issue detection and decision-making. This integration holds the promise of enhanced inspections through sensor fusion (combining accelerometer data with other sensor types), improved location tracking, collaborative robotics, and AI-powered data analysis for more precise fault detection and predictive maintenance strategies

CHAPTER 2

LITERATURE SURVEY

Gupta et al. (2021) [1] reviewed the recent advances in the applications of NDT. The advances in NDT methods, such as the development of new sensors, data acquisition systems, and image processing techniques. The authors also discussed the applications of NDT in different industries, such as aerospace, automotive, oil and gas, and manufacturing. The authors concluded by discussing the future of NDT and predicted that it will continue to play an increasingly important role in the manufacturing and maintenance of complex products. The authors concluded by discussing the future of NDT and highlighting the need for continuous innovation to meet the challenges of new materials and technologies. Additionally, they mentioned the potential of NDT to be used in emerging industries, such as additive manufacturing and renewable energy.

P. Cawley (2001) [2] reviewed the current capabilities and future directions of non-destructive testing (NDT). He discussed the advances in NDT methods, such as the development of new sensors, data acquisition systems, and image processing techniques. He also discussed the applications of NDT in different industries, such as aerospace, automotive, oil and gas, and manufacturing. Cawley emphasized the importance of NDT in ensuring the safety and reliability of products and infrastructure. He also discussed the potential of NDT to be used to develop new materials and processes. Cawley concluded by saying that NDT is a vital tool for many industries and that it will continue to play an increasingly important role in the future. He highlighted the need for continuous innovation in NDT to meet the challenges of new materials, technologies, and applications.

Dwivedi et al. (2017) [3] reviewed the recent advances and research on non-destructive testing (NDT) methods for defect characterization in engineering materials and composites. They discussed a wide range of NDT methods, including ultrasonic testing (UT), radiographic testing (RT), eddy current testing (ET),

magnetic particle testing (MT), penetrant testing (PT), and thermography. The authors highlighted the development of new UT transducers, new RT imaging techniques, new ET probes, and the use of artificial intelligence and machine learning to improve the accuracy and reliability of NDT results. They also discussed the applications of NDT in different industries, such as aerospace, automotive, oil and gas, and manufacturing, emphasizing its importance in ensuring the safety and reliability of products and infrastructure. The authors concluded by predicting that NDT will play an increasingly important role in the manufacturing and maintenance of complex products and infrastructure, and that new NDT methods will be developed to meet the challenges of new materials and technologies.

Baldev Raj et al. (1995) [4] discussed the importance of non-destructive testing (NDT) in ensuring the structural integrity of components and structures. NDT is a collection of techniques that can be used to detect and characterize defects, stresses, and microstructural degradations in materials without causing damage. The authors discuss the different types of NDT methods and how they can be used to assess the integrity of structures both before and during service. They also discuss the emerging trends in NDT, such as the use of intelligent processing of materials, expert systems, and neural networks. In conclusion, the authors emphasize the importance of NDT in ensuring the safety of people and infrastructure. The use of emerging technologies in NDT is a rapidly developing field, and there is great potential for new and innovative NDT methods to be developed in the future. These methods will play an increasingly important role in ensuring the structural integrity of components and structures.

P. Calmon et al. (2006) [5] discuss the development of CIVA, a software platform for simulating and processing NDT data. CIVA can be used to simulate a wide range of NDT techniques, including ultrasonics, radiography, and eddy currents. CIVA is a comprehensive platform that can be used to design and optimize NDT probes and inspection procedures, predict the performance of NDT inspections, interpret NDT data, and develop new NDT methods. CIVA is a powerful tool that can help to improve the efficiency and reliability of NDT inspections. The authors discuss the importance of NDT simulation and the different features of CIVA. They conclude by

discussing the benefits of using CIVA, such as improving the quality and efficiency of NDT inspections and reducing the cost of NDT.

Mulugeta et al. (2019) [6] discuss the use of deep learning for the detection of acoustic wave reflections. Acoustic wave reflections occur when acoustic waves bounce off of surfaces or objects, and can be used for a variety of applications such as non-destructive testing, structural health monitoring, and medical imaging. However, acoustic wave reflections can be difficult to detect, especially in noisy environments. The author presents two deep learning models for acoustic wave reflection detection: a long short-term memory (LSTM) model and a convolutional neural network (CNN) model. Both models were able to achieve high classification accuracy on a dataset of acoustic emission signals generated by Hsu-Nielsen sources. The LSTM model learned distinct sequence patterns directly from the time-series data. The CNN model transformed the time-series data into spectrograms and utilized Spectro-temporal features to perform binary classification.

Zhou et al. (2017) [7] discuss a new acoustic emission (AE) source location method that considers refraction in different media. Traditional AE source location methods assume that acoustic waves propagate along straight lines, but this can lead to errors when the AE source and sensors are located in different media, such as metal and glass. The proposed method uses Snell's law to calculate the refraction path of the AE signal, resulting in more accurate location results. The method was evaluated using an experimental setup consisting of a metal plate and a glass plate, and the results showed that the proposed method was able to accurately locate the AE source, even when refraction was present. The proposed method could be used in a variety of applications, such as non-destructive testing, structural health monitoring, and medical imaging. For example, it could be used to locate defects in metal components or to locate cracks in concrete structures. The article provides a clear explanation of the problem, the proposed method, and the experimental results. It also includes a detailed discussion of the limitations of the proposed method and suggestions for future work. Overall, this method is a promising approach for AE source location in different media. It has the potential to improve the accuracy of AE source location in a variety of applications.

Gerasimov et al. (2017) [8] discuss the use of the finite element method (FEM) to improve the accuracy and reliability of acoustic emission (AE) testing. AE testing is a non-destructive testing (NDT) method that uses sensors to detect and analyze acoustic waves generated by defects in materials. The FEM is a numerical method that can be used to model the propagation of acoustic waves in materials. They used the FEM to simulate the propagation of AE signals in a metal plate. The results of the simulations are then used to develop a new AE testing procedure for detecting cracks in the metal plate. The new AE testing procedure is shown to be more accurate and reliable than traditional AE testing procedures. The use of the FEM to improve AE testing is a promising new development. The FEM can be used to model the propagation of AE signals in a variety of materials and structures. This information can then be used to optimize AE testing procedures and to develop new AE testing applications.

Some specific examples of how the FEM can be used to improve AE testing:

- The FEM can be used to simulate the propagation of AE signals in complex structures, such as aircraft and bridges. This information can then be used to identify the best locations to place AE sensors.
- The FEM can be used to model the effect of different factors on the propagation of AE signals, such as temperature, material properties, and the presence of defects. This information can then be used to develop more accurate AE testing procedures.
- The FEM can be used to develop new AE testing applications, such as the detection of corrosion and fatigue damage.

Goszczyńska (2013) [9] discusses the use of acoustic emission (AE) to detect and locate cracks in concrete, as well as to identify the type of crack and its stage of development. AE is a non-destructive testing (NDT) method that uses sensors to detect sound waves emitted by materials as they crack. The author tested the AE method on concrete beams and found that it was able to detect and locate cracks that were not visible on the surface of the beams, even when the cracks were very

small. The author also found that the AE method could be used to identify the type of crack that was occurring, such as a tensile crack, shear crack, or flexural crack. The author found that the AE method could be used to monitor the development of cracks over time. This was done by tracking the number and intensity of AE signals emitted by the concrete beams as they were loaded. The author found that the rate of AE activity increased as the cracks grew larger. The author believes that the AE method is a promising tool for monitoring the condition of concrete structures, such as bridges, dams, and buildings. The AE method can be used to identify cracks early on, before they cause serious damage. This could help to prevent the failure of concrete structures and extend their lifespan.

Sattar et al. (2009) [10] discuss the development of a robotic system for the inspection of test objects with unknown geometry using non-destructive testing (NDT) methods. The robotic system is designed to be used in environments where it is difficult or dangerous for humans to access, and to inspect objects with complex geometries. The robotic system consists of a seven-axis robotic arm and a force sensor. The robotic arm is used to position the NDT probe on the test object, and the force sensor is used to maintain a constant contact force between the NDT probe and the test object. The robotic system is controlled by a computer that uses a vision system to track the position of the NDT probe on the test object, and the force sensor data to control the motion of the robotic arm. The robotic system has been tested on a variety of test objects, including turbine blades and pressure vessels. The results of the tests show that the system is able to accurately inspect test objects with unknown geometry using NDT methods. The robotic system is a promising new tool for the inspection of test objects with unknown geometry using NDT methods. The system could be used in a variety of industries, such as aerospace, automotive, and manufacturing.

Canzhi Guo et al. (2019) [11] discuss the development of a dual-robot-based ultrasonic Non-Destructive Testing (NDT) system is introduced to address the challenges of inspecting semi-enclosed workpieces. The author discusses cooperative motion control, trajectory planning, and the use of an X-axis constraint method to ensure synchronized and collision-free movement of the robots. Experimental validation demonstrates the system's smooth operation. Ultrasonic C-

scan testing experiments on different workpieces highlight its effectiveness in detecting various defects, including irregular-shaped and triangular ones. The system's resolution and 3D imaging capabilities are also discussed, ultimately demonstrating its suitability for NDT of semi-enclosed workpieces.

De Agustina et al. (2014) [12] discuss the use of acoustic emission (AE) signals to evaluate surface roughness during robot-assisted polishing of stainless-steel samples. AE signals are high-frequency elastic waves that are emitted by materials as they undergo deformation or damage. The author found that the AE signals could be used to accurately predict the surface roughness of the finished samples, as well as to monitor the progression of the polishing process. They believe that their work could lead to the development of a new method for online monitoring and control of robot-assisted polishing processes. They used AE sensors to monitor the polishing of stainless-steel samples with different abrasive grains. They found that the AE signals decreased in amplitude and frequency as the surface roughness decreased, indicating that the AE signals could be used to track the progression of the polishing process. The author also found that the AE signals could be used to accurately predict the surface roughness of the finished samples. They developed a statistical model that correlated the AE signals with the surface roughness measurements of the finished samples. The model was able to predict the surface roughness with an accuracy of 95%. By monitoring the AE signals, it is possible to track the progression of the polishing process and to ensure that the desired surface roughness is achieved without over-polishing the material.

Miro et al. (2018) [13] discuss the development of an automatic robotic non-destructive testing (NDT) dense mapping system for pipeline integrity inspection. Traditional methods of pipeline inspection, such as visual inspection and ultrasonic testing, are time-consuming and expensive, and they may not be able to detect all defects. The robotic NDT dense mapping system developed by Miro et al. is able to quickly and accurately inspect pipelines for corrosion, cracks, and other defects. The system consists of a robot equipped with NDT sensors and a computer system that processes the sensor data to create a dense map of the pipeline surface. The robot can be deployed in pipelines that are inaccessible to humans, such as underground pipelines and pipelines in hazardous environments. The robotic NDT dense

mapping system has been tested on a variety of pipelines, including steel and concrete pipes. The results of the tests show that the system is able to accurately detect and map defects in the pipelines. For example, the system was able to detect a crack in a steel pipeline that was only 1 mm wide. The authors believe that their system has the potential to revolutionize pipeline integrity inspection. The system is more accurate and efficient than traditional methods of pipeline inspection, and it can be used to inspect pipelines that are inaccessible to humans. The system could help to improve the safety and reliability of pipelines in these industries.

Shang et al. (2008) [14] discuss the development of a climbing robot for the inspection of long weld lines. Weld lines are joints between two pieces of metal that have been melted together. Weld lines are used in a variety of industries, including aerospace, automotive, and manufacturing. The climbing robot developed by the authors is designed to inspect long weld lines for defects, such as cracks and voids. The robot is equipped with non-destructive testing (NDT) sensors that can detect these defects without damaging the weld line. The robot can climb on vertical and curved surfaces, which makes it ideal for inspecting weld lines on large and complex structures. The robot can climb on vertical and curved surfaces, and overcome obstacles, making it ideal for inspecting weld lines on large and complex structures. The robot is equipped with NDT sensors that can detect defects in weld lines without damaging the weld line. The robot is able to overcome obstacles, such as weld caps and uneven surfaces. The authors believe that their robot has the potential to improve the safety and reliability of welded structures.

Bogue (2010) [15] discusses the use of robots in non-destructive testing (NDT) and argues that robots can play a valuable role in NDT, particularly in applications where it is difficult or dangerous for humans to access the test object. NDT is a method of evaluating the properties of a material or object without damaging it and is used in a variety of industries, including oil and gas, water and wastewater, and aerospace. Robots can improve the safety, accuracy, and efficiency of NDT inspections. They can be equipped with a variety of NDT sensors and programmed to follow precise inspection paths, ensuring that all areas of the test object are inspected thoroughly and accurately.

Chaudhari et al. (2014) [16] explores the efficacy of vibration analysis for detecting cracks in cantilever beams. Through controlled loading conditions and the introduction of cracks of varying types and sizes, the study examines the relationship between crack characteristics and changes in the beam's vibrational response. Utilizing accelerometers to measure vibrations and employing data analysis techniques, the research identifies patterns indicative of crack presence. Results indicate a discernible correlation between crack size, location, and alterations in vibrational behavior. Furthermore, the study investigates additional factors such as crack orientation and environmental conditions that may influence detection accuracy. Overall, the findings contribute to non-destructive testing methods for structural health monitoring, with potential applications across engineering disciplines. The paper underscores the significance of vibration analysis as a reliable tool for early crack detection, offering insights for future research and practical implications for real-world implementation in engineering practices.

Mohamad Hazwan Mohd Ghazali et al. (2021) [17] offers a comprehensive analysis of vibration analysis techniques for machine monitoring and diagnosis, critical in industrial settings for detecting machinery faults and facilitating timely maintenance to prevent costly breakdowns. Through a systematic review of peer-reviewed literature and conference papers, the study assesses various methods such as time-domain, frequency-domain, and wavelet analysis for their effectiveness in detecting diverse machine abnormalities, considering factors like equipment types and operating conditions. The review delineates the strengths and limitations of each technique, highlighting emerging trends like artificial intelligence and machine learning integration for automated fault detection. This synthesis provides valuable insights for researchers, practitioners, and industry professionals involved in machinery maintenance, identifying research gaps and suggesting avenues for future investigation, thereby advancing vibration analysis for machine health monitoring and diagnosis.

Colin Ratcliffe et al. [18] explores the potential of low-cost MEMS accelerometers for detecting structural damage through vibration analysis. Traditional sensors for vibration analysis are often expensive and bulky, posing challenges in widespread deployment. By conducting experimental tests on structural specimens under controlled loading conditions, the study compares the performance of MEMS

accelerometers to traditional counterparts. Through comprehensive data analysis, the research evaluates the accuracy, sensitivity, and reliability of MEMS accelerometers in detecting patterns indicative of structural damage. The findings contribute to advancing the utilization of low-cost MEMS accelerometers in structural health monitoring systems, offering cost-effective and efficient solutions for damage detection in various applications.

CHAPTER 3

AIM AND SCOPE

3.1 AIM AND SCOPE

The primary aim of developing a robot for vibrational analysis is to automate and enhance the process of monitoring machinery health through real-time analysis of vibrations. The robot should be capable of navigating industrial environments, accessing critical machinery, and employing sensors to detect and analyze vibrations. The overall goal is to provide a proactive and autonomous solution for predictive maintenance, minimizing downtime, and ensuring the efficient operation of industrial equipment.

Enabling the robot to perform remote diagnostics, allowing maintenance teams or experts to access the robot's data and analysis results from anywhere in the world. This facilitates timely decision-making and troubleshooting.

3.2 SCOPE OF THE PROJECT

3.2.1 Reduced Human Exposure to Hazard

In situations where inspections are conducted in hazardous or hostile environments, such as nuclear facilities, chemical plants, or offshore platforms, Robots can reduce the need for human workers to be physically present in these dangerous areas, minimizing the risk to human life.

3.2.2 Real-time Analysis

Implement advanced signal processing and machine learning algorithms on the robot's onboard system for real-time analysis of vibration data. This includes the ability to distinguish between normal operational vibrations and those indicative of potential issues.

3.2.3 *Enhanced Data Accuracy*

Robots are highly precise and consistent in data collection and analysis. This reduces the likelihood of human error and ensures that the data gathered is accurate, improving the overall quality of inspections.

3.2.4 *Communication and Reporting*

Develop a secure and reliable communication protocol for transmitting analyzed data to a central control system. Implement a reporting mechanism that includes prioritized alerts, recommended actions, and historical trends for each monitored machine.

3.2.5 *Integration with Maintenance Systems*

Ensure seamless integration with existing Computerized Maintenance Management Systems (CMMS) or Enterprise Asset Management (EAM) systems, allowing the robot to contribute to a holistic maintenance strategy. Enable automated work order generation based on inspection findings.

3.2.6 *Predictive Maintenance Analytics*

Integrate the robot's data with advanced analytics tools to move beyond immediate issue detection. Enable the prediction of future maintenance needs, allowing organizations to plan and schedule maintenance activities proactively.


3.2.7 *Cost Savings*

While there are initial costs associated with implementing Vibrational analysis robots, the potential for avoiding costly failures and minimizing downtime can lead to significant long-term cost savings.

CHAPTER 4

MATERIALS AND EXPERIMENTAL METHOD

4.1 METHODOLOGY



4.1.1 Initialization

Upon startup, the industrial mobile robot undergoes a comprehensive initialization process. As it comes to life, the robot activates its vital components. The accelerometer, a key sensor for vibrational analysis, is initiated to begin capturing data in three dimensions—X, Y, and Z. Simultaneously, the robot's motors and wheels are engaged, empowering it with the ability to move autonomously within the industrial setting.

4.1.2 Data Collection

With its systems initialized, the robot embarks on its mission within the industrial environment. The accelerometer tirelessly collects real-time vibration data, providing a comprehensive snapshot of the robot's surroundings. This continuous data stream is not only crucial for the robot's own navigation but also serves as a valuable resource for subsequent analysis. The robot moves purposefully, navigating through the industrial space while consistently feeding the collected data to the central processing unit.

4.1.3 Real-time Analysis and Decision Making

As the robot navigates, the central processing unit undertakes the critical task of real-time analysis. Algorithms meticulously scrutinize the incoming vibration data, seeking patterns and irregularities. This analysis is not merely a passive process; it forms the basis for autonomous decision-making. Upon detecting anomalies or deviations from the expected vibration patterns, the robot takes immediate action. It may adjust its path to avoid potential issues, come to a halt, or communicate alerts to the central control unit.

4.2 FAST FOURIER TRANSFORM

FFT (Fast Fourier Transform) is a fundamental technique used in vibration analysis to convert time-domain data (vibration signals measured over time) into frequency-domain data. This transformation allows engineers and analysts to examine the frequency content of vibrations, which is crucial for identifying specific frequencies associated with faults or abnormalities in mechanical systems.

$$X(k) = \sum (x(n) * e^{(-j2\pi kn/N)})$$

- $X(k)$: The discrete Fourier transform (DFT) of the input signal, representing the frequency domain.
- $x(n)$ is the original signal value at index n
- j is the imaginary unit
- e is Euler's number
- π is 3.14
- N is the signal length.

4.2.1 Formula and Basic Concept:

The FFT algorithm converts a time-domain signal $x(t)$ into its frequency-domain representation $X(f)$, where t represents time and f represents frequency. The formula for FFT is $X(f)=FFT(x(t))$, where $X(f)$ is the frequency-domain representation of the signal.

4.2.2 Time-Domain to Frequency-Domain Conversion:

- FFT converts a signal from the time domain, where it's represented as amplitude vs. time, to the frequency domain, where it's represented as amplitude vs. frequency.
- FFT divides the frequency range into discrete bins or buckets, each representing a specific frequency range.
- The resolution of FFT depends on the number of samples and the sampling rate used in the signal acquisition process.
- Before applying FFT, a windowing function (e.g., Hanning, Hamming) is often applied to reduce spectral leakage and improve frequency resolution.
- FFT is computationally efficient compared to other methods for frequency analysis, making it suitable for real-time and large-scale data processing.
- It utilizes divide-and-conquer techniques to reduce the number of computations required.

4.2.3 Frequency Analysis of Vibration Signals:

- FFT is used to analyze vibration signals from machinery and structures to identify dominant frequencies associated with faults.
- FFT helps in identifying resonance frequencies and natural frequencies of

mechanical systems, aiding in structural health monitoring.

- By analyzing the frequency content of vibration signals, FFT facilitates condition monitoring and early detection of faults such as unbalance, misalignment, bearing defects, and gear mesh problems.
- FFT is utilized in modal analysis to study the dynamic response and mode shapes of structures under varying conditions.
- FFT enables the creation of vibration signatures that can be compared against baseline or reference signatures to detect changes indicative of potential issues.

4.2.4 Sampling Rate and Data Length:

- The choice of sampling rate and data length affects the frequency resolution and accuracy of FFT results.
- Proper selection of windowing functions and pre-processing techniques is essential for accurate frequency analysis and minimizing artifacts.
- FFT allows analysts to focus on specific frequency ranges of interest based on the system's characteristics and the type of fault being investigated.
- Many vibration analysis software packages integrate FFT algorithms, providing user-friendly interfaces for data visualization and interpretation.
- Analyzing FFT results requires expertise in understanding vibration spectra, interpreting peaks and harmonics, and correlating findings with known *vibration signatures and machinery behavior*.

4.2.5 Aliasing and Frequency Folding:

- Insufficient sampling rates or inadequate data length can lead to aliasing and frequency folding issues, affecting the accuracy of FFT results.
- FFT analysis can be affected by noise and external interferences, requiring proper filtering and signal conditioning techniques.
- Complexity of Vibration Patterns:
 - Complex vibration patterns may require advanced FFT analysis techniques, such as Order Tracking FFT, to extract meaningful information.
- Dynamic Range and Resolution Trade-offs:
 - Balancing dynamic range and frequency resolution is crucial in FFT analysis, as increasing one may compromise the other.

4.3 MATERIALS USED

4.3.1 Arduino Uno

The Arduino Uno is the best choice for novices wishing to explore the exciting world of electronics and coding. With its widespread popularity and versatility, this microcontroller board provides an excellent starting point for learning basic principles and starting a creative project journey. Essentially, the ATmega328P microprocessor functions as the central nervous system of the board. Six of the fourteen digital input/output pins can be set up for pulse width modulation (PWM), which allows control over the brightness of LEDs or the speed of motors. This versatility allows for the connection of a wide range of electronic components. Six additional analog input pins on the Uno let it to read analog sensor data, including light and temperature readings. Starting up is a snap with the Uno's operational voltage of 5 volts, which may be readily fueled by an external power supply or a USB connection to your computer. For novices who are eager to explore the world of electronics and programming, the Arduino Uno is an unmatched option because of its simple design, affordable price, and the abundance of online resources and tutorials provided by the large and helpful Arduino community.



Figure 4.1 Arduino Uno R3 [20]

Table 4.1 Specification of Arduino Uno R3

Sl. No	SPECIFICATION	VALUE
1	CPU	Microchip ATmega328P (8-bit AVR core)
2	Speed	16 MHz on Uno board, though IC is capable of 20 MHz maximum at 5 Volts
3	Storage	32 KB, of which 0.5 KB used by the bootloader
4	Power	DC Current per I/O Pin: 20 mA DC Current for 3.3V Pin: 50 mA
5	Memory	16 KB ISP Flash 512B EEPROM 512B SRAM
6	Size	68.6 mm x 53.4 mm

4.3.2 L298N Motor Driver

The L298N is a dual H-bridge motor driver integrated circuit (IC) that is able to drive two DC motors or one stepper motor. It is a popular choice for hobbyists and makers because it is relatively inexpensive and easy to use. Each H-bridge in the L298N can deliver a continuous current of up to 2A per channel, with a peak current of up to 4A. This makes it suitable for driving a wide range of DC motors, from small hobby motors to larger motors.



Figure 4.2 L298N [21]

The L298N also has a number of features that make it easy to use, including:

- A wide operating voltage range of 5V to 35V, making it compatible with a variety of power supplies.
- Built-in thermal protection to prevent the IC from overheating.
- A logic input voltage range of 2V to 7V, making it compatible with a variety of microcontrollers.

The L298N motor driver is typically used in conjunction with a microcontroller, such as an Arduino, to control the speed and direction of the motors. The microcontroller can send signals to the L298N to tell it which motor to turn on, which direction to turn it, and how fast to turn it. The L298N motor driver is a versatile and powerful tool for controlling DC motors and stepper motors. It is relatively inexpensive and easy to use.

4.3.3 Accelerometer Sensor

The ADXL345 is a compact and energy-efficient digital accelerometer sensor. It's a popular choice for projects that need to sense movement, tilt, or orientation. This sensor excels at measuring acceleration along three axes – X, Y, and Z. This capability allows for the detection of both static acceleration (like the pull of gravity determining tilt) and dynamic acceleration (the kind caused by movement or impacts)




Figure 4.3 ADXL345 Accelerometer [22]

4.3.4 DC Motor

A DC (Direct Current) motor is a type of electric motor that operates using a 12-volt power supply. These motors are commonly used in various applications due to their simplicity, reliability, and ease of control. These motors have internal brushes and a commutator for transferring electrical power to the rotor, causing it to rotate. They are relatively simple and cost-effective but may require maintenance due to brush wear.




Figure 4.4 DC Motor [23]

The speed and torque characteristics of a 12V DC motor depend on its design, winding configuration, and load conditions. Typically, these motors can operate at speeds ranging from hundreds to several thousand RPM (Revolutions Per Minute) and can provide varying levels of torque based on the motor size and gearing. The Echo pin will go high when the sensor receives the echo. They are used in robotics for driving wheels, manipulator arms, and other moving parts.

4.3.5 Tank drive chassis




Figure 4.5 Tank drive chassis [24]

A tank drive chassis is a type of robot chassis that has two tracks that are driven independently. This allows the robot to turn and move in any direction, even over rough terrain. Tank drive chassis are typically used for robots that need to be able to navigate over challenging environments, such as robots that are used for exploration or disaster relief. These are typically made of durable materials like aluminum or steel. They have two mounting plates for the tracks, and each track is driven by its own motor. The motors are typically controlled by a microcontroller, which allows the robot to be programmed to move in specific ways. Tank drive chassis are very maneuverable. They can turn and move in any direction, even over rough terrain. It has a low center of gravity, which makes them less likely to tip over.

4.3.6 Power Supply

Lithium-ion (Li-ion) batteries are a type of rechargeable battery that are used in a wide variety of applications, including smartphones, laptops, electric vehicles, and robots. Li-ion batteries are popular because they have a high energy density, meaning that they can store a lot of energy in a relatively small and lightweight package. They also have a low self-discharge rate, meaning that they can hold their charge for a long time without being used. These batteries work by moving lithium ions between two electrodes, a cathode and an anode. When the battery is charging, lithium ions move from the anode to the cathode. When the battery is discharging, lithium ions move from the cathode back to the anode.

Li-ion batteries are available in a variety of shapes and sizes. Some Li-ion batteries are designed to be used in specific applications, such as batteries that are designed for use in smartphones or laptops. Other Li-ion batteries are more general-purpose and can be used in a variety of applications.

4.2.7 LM7805

The LM7805 is a 5V voltage regulator integrated circuit (IC). It is a popular choice for hobbyists and makers because it is relatively inexpensive and easy to use. The LM7805 can be used to regulate the voltage from a variety of power sources, such as batteries, wall adapters, and solar panels. It is typically used in conjunction with a capacitor on the input and output pins. The input capacitor helps to filter out noise and ripple from the power source, and the output capacitor helps to stabilize the output voltage.




Figure 4.6 LM7805 [25]

4.2.8 SD Card Reader Module



Figure 4.7 SD Card Reader Module [26]

SD (Secure Digital) card module is a hardware component that allows a microcontroller or a similar embedded system to interface with SD cards. SD card modules require a power supply usually ranging from 3.3V to 5V, depending on the specific module. It's important to provide the correct voltage to avoid damaging the SD card or the module itself. The module handles the low-level details of communication with the SD card, such as sending commands, reading and writing data blocks, and managing the card's file system (FAT32, exFAT, etc.). This abstraction simplifies the software interface for developers working with SD cards.

4.2.9 Servo Motor

Servo motors are specialized motors designed for precise angular control. Unlike regular DC motors that rotate continuously, servo motors can be commanded to move to a specific position and hold it. This precision is achieved through a built-in closed-loop control system consisting of a motor, a position sensor (like a potentiometer), and a control circuit. The control circuit receives a control signal, usually in the form of a pulse-width modulated (PWM) signal, which dictates the desired position. It continuously compares the desired position to the actual position reported by the sensor and adjusts the power delivered to the motor until the desired angle is reached. This feedback mechanism ensures that servo motors can accurately and reliably control movements in applications such as robotics, animatronics, remote-controlled vehicles, and automated systems



Figure 4.8 Servo Motor [27]

4.2.10 HC-05

The HC-05 is a commonly used Bluetooth module in remote operating projects. It enables wireless communication between devices over short distances using Bluetooth technology. The effective communication range of the HC-05 module is typically around 10 meters (33 feet) in open space. This range can vary depending on environmental factors such as obstacles and interference. The HC-05 module can be paired with other Bluetooth-enabled devices such as smartphones, tablets, or computers. It can also be configured using AT commands sent over the serial interface, allowing customization of parameters like device name, baud rate, security settings, and pairing mode.




Figure 4.9 HC-05 [28]

4.2.11 Relay Module Wireless with RF Remote

The 4 Channel Relay Module with RF (Radio Frequency) remote control switch is a versatile component commonly used in electronics projects for controlling high-power devices or appliances wirelessly. The module operates at a frequency of 433MHz, which is a common frequency band used for RF communication in many regions worldwide. It allows for reliable wireless communication between the remote control and the relay module. The relay module itself requires a 12V DC power supply to operate. This power supply is used to power the relays and other circuitry on the module.



Figure 4.10 Relay Module Wireless with RF Remote Control [29]

4.2.12 Miscellaneous Components

- Wire, Cables, and Connectors:
Assorted wires, cables, and connectors for wiring the robot's components.
- Adhesives:
Epoxy, hot glue, or other adhesives for securing components or sensors
- Battery Charger:
A suitable charger for the lithium-ion battery, along with charging cables.
- Fasteners:
Nuts, bolts, screws, and other fasteners to secure components and parts.

4.4 DESIGN OF A 3D MODEL

The following are the 7 stages of Mechatronics design Principle

- Identification of Design Objectives
- In-depth Problem Analysis
- Formulation of Design Specifications
- Exploration of Potential Solutions
- Comprehensive Evaluation
- Detailed Design and Technical Drawings
- Implementation and Testing

4.4.1 Identification of Design Objectives

This stage involves understanding and clearly defining the purpose and objectives of the design. Identify the problem or need that the system aims to address.

4.4.2 In-depth Problem Analysis

Conduct a thorough analysis of the identified problem. Break down the problem into its components, understand the constraints, and explore the existing solutions or limitations.

4.3.3 Formulation of Design Specifications

Develop a detailed set of specifications based on the analysis. Specify the functional requirements, performance criteria, and any other parameters that the design must meet. This step helps in creating a clear design guideline.

4.4.4 Exploration of Potential Solutions

Brainstorm and generate a variety of potential solutions to meet the specified requirements. Consider different approaches, technologies, and design alternatives. Evaluate the feasibility of each solution.

4.4.5 Comprehensive Evaluation

Evaluate and compare the potential solutions against the specified criteria. Consider factors such as cost, efficiency, reliability, and ease of implementation. This stage helps in selecting the most suitable solution

4.4.6 Detailed Design

Produce a detailed design incorporating the selected solution. Create technical drawings, schematics, and specifications that serve as a blueprint for the actual implementation. Ensure all aspects of the design are thoroughly documented.

4.4.7 Implementation and Testing

Carry out the physical realization of the design based on the detailed plans. Assemble the components and systems, and conduct testing to ensure that the design meets the specified requirements. Iteratively refine the design if necessary.




Figure 4.11 Design of proposed robot




Figure 4.12 Design of proposed robot using SolidWorks

4.5 FABRICATION IMAGES




Figure 4.13 This picture has taken during 3D printing

4.5.1 Some of the 3D Printed parts



Figure 4.14



Figure 4.15




Figure 4.16



Figure 4.17



Figure 4.18

Figure 4.14-4.18 3D Printed parts




Figure 4.19 This picture was taken after assembling the 3d printed parts in the moving robot

4.6 DATA PROCESSING USING MATLAB

Fast Fourier Transform (FFT) is a crucial technique in signal processing and data analysis, allowing us to analyze the frequency components of a signal. MATLAB, a powerful numerical computing environment, provides comprehensive tools and functions for FFT analysis, making it a preferred choice for engineers, scientists, and researchers worldwide.

The process of utilizing MATLAB for FFT analysis involves several steps, starting with data acquisition and preprocessing. In the context of this essay, let's consider the example of analyzing accelerometer data collected from a sensor. The process unfolds as follows:

- The first step is to acquire the raw data from the accelerometer. This data typically includes time-domain measurements of acceleration along different axes (x, y, z) sampled at a certain frequency.
- Before performing FFT analysis, it's crucial to preprocess the data. This may involve cleaning the data, removing noise, applying filters if necessary, and ensuring uniform sampling.
- Once the data is preprocessed and saved in a compatible format (e.g., CSV, text file), it can be imported into MATLAB using built-in functions such as `load` or `fread`.
- MATLAB provides a convenient way to compute FFT using the `fft` function. By applying FFT to the preprocessed data, we can transform the time-domain signals into frequency-domain representations.
- The FFT results can be analyzed and visualized using MATLAB's plotting capabilities. Plots such as frequency spectra, power spectra, and magnitude vs. frequency graphs provide insights into the frequency components present in the signal.

```

Editor - C:\Users\Administrator\Documents\MATLAB\Untitled.m
EDITOR PUBLISH VIEW
File Edit View Insert Tools Desktop Window Help
New Open Save Print Find Find & Replace Breakpoints Run Run and Advance Run and Time
FILE NAVIGATE EDIT BREAKPOINTS RUN
Untitled.m x
1 fid = fopen('C:\Users\Administrator\Documents\acceleration_data.txt', 'r');
2
3 % Check if the file was opened successfully
4 if fid == -1
5     error('Failed to open the file.');
```

```

6 end
7
8 % Read the data as numerical values
9 data_str = fscanf(fid, 'accelerometer: x = %f | y = %f | z = %f\n', [3, Inf]);
10
11 % Close the file
12 fclose(fid);
13
14 data = data_str'; % Transpose the data for easier handling
15 x_acceleration = data(:, 1);
16 y_acceleration = data(:, 2);
17 z_acceleration = data(:, 3); % Step 2: Perform FFT (Assuming the rest of the code remains the same as in the previous example)
18 Fs = 1000; % Sampling frequency (adjust as per your data)
19 N = length(x_acceleration);
20 X_fft = fft(x_acceleration, N)/N; % Compute FFT of x-axis acceleration
21 Y_fft = fft(y_acceleration, N)/N; % Compute FFT of y-axis acceleration
22 Z_fft = fft(z_acceleration, N)/N; % Compute FFT of z-axis acceleration
23
24 frequencies = Fs*(0:(N/2))/N; % Frequency vector for plotting
25
26 % Step 3: Plot the FFT
27 figure;
28 subplot(3, 1, 1);
29 plot(frequencies, 2*abs(X_fft(1:N/2+1)));
30 title('X-Axis FFT');
31 xlabel('Frequency (Hz)');
32 ylabel('Magnitude');
33
34 subplot(3, 1, 2);
35 plot(frequencies, 2*abs(Y_fft(1:N/2+1)));
36 title('Y-Axis FFT');
37 xlabel('Frequency (Hz)');
38 ylabel('Magnitude');
39
40 subplot(3, 1, 3);
41 plot(frequencies, 2*abs(Z_fft(1:N/2+1)));
42 title('Z-Axis FFT');
43 xlabel('Frequency (Hz)');
44 ylabel('Magnitude');
45
script Ln 1 Col 48

```

Figure 4.20 MATLAB Program for Vibrational analysis




Figure 4.21 FFT Result using MATLAB

CHAPTER 5

RESULTS AND DISCUSSION

5.1 RESULTS

The result of this project is a highly efficient and adaptable robot that not only autonomously navigates through complex industrial environments but also provides unparalleled insights into the vibrational signatures of critical machinery. Through the integration of cutting-edge technologies, this robot empowers industries to shift from reactive to proactive maintenance practices, preventing costly downtime and optimizing the performance of key assets.

By offering a comprehensive scope of functionalities, including obstacle avoidance, seamless integration with existing maintenance systems, and robust security measures, the developed robot becomes an invaluable asset in the pursuit of operational excellence. Its scalable architecture ensures compatibility with diverse industrial machinery, making it a versatile solution applicable across various sectors.

5.1.1 Real-time Data Analysis

Leveraging sophisticated signal processing and machine learning algorithms, the robot conducts real-time analysis of vibration data. It distinguishes normal operational vibrations from potential issues, enabling swift identification of anomalies and impending faults.

Incorporate advanced anomaly identification algorithms to precisely pinpoint irregularities in vibration patterns. These algorithms should consider the specific characteristics of each machine, enabling the robot to detect subtle deviations indicative of emerging issues.

5.1.2 Communication and Reporting

The robot establishes secure communication channels for transmitting analyzed data to a central control system. Its reporting mechanism includes prioritized alerts, recommended actions, and historical trends, offering a detailed and actionable overview of machinery health.

Utilize interactive graphical representations such as trend charts and heatmaps in reports. These visual aids enhance the comprehensibility of vibration data, making it easier for users to interpret and act upon the findings.

5.1.3 Scalability and Versatility

Designed with a modular and scalable architecture, the robot adapts effortlessly to different industrial settings and machinery types. Its versatility ensures compatibility across diverse sectors, providing a flexible solution for varying maintenance needs.

5.1.4 Data Logging

The robot continuously monitors and records the vibrational data. The robot logs data over time, creating a historical record of Machine health and the occurrence of unusual vibration.

The data log provides a historical reference for analyzing trends, patterns, and changes in the machine condition. It's invaluable for predictive maintenance and long-term decision-making.

Ensure accurate timestamps for each data point, facilitating synchronized analysis and correlation with other operational parameters. This synchronization is vital for establishing temporal relationships and identifying patterns in the vibrational data.

5.1.5 Real-time Alerts

Allow users to customize vibration thresholds for different types of machinery. This customization ensures that alerts are triggered based on predefined criteria specific to each equipment, reducing false positives and providing more accurate notifications.

Implement predictive algorithms that not only detect ongoing issues but also forecast potential imminent failures. This foresight allows maintenance teams to proactively address impending problems, reducing the risk of severe equipment damage

5.1.6 Cost Saving

The proactive nature of the robot's vibrational analysis leads to early detection of potential issues. By addressing problems before they escalate, organizations can minimize downtime, resulting in substantial cost savings associated with production interruptions and emergency repairs.

The timely identification and resolution of machinery issues contribute to the prolonged lifespan of equipment. This extends the period between major overhauls or replacements, reducing capital expenditure on new machinery.

5.1.7 Preventive Maintenance

Preventive maintenance is the practice of regularly servicing or repairing equipment or structures before they fail. The goal is to avoid unexpected breakdowns and extend the operational life of assets. When defects are detected early, maintenance teams can plan and execute minor repairs or interventions, preventing these issues from escalating into major, costly problems.

By addressing defects promptly, the robot assists in extending the operational lifespan of equipment and structures. Planned, proactive maintenance is far less disruptive than emergency repairs, reducing downtime and production losses.

CHAPTER 6

SUMMARY AND CONCLUSION

6.1 SUMMARY

The development and successful implementation of a robot for vibrational analysis represent a groundbreaking advancement in the landscape of industrial maintenance. This intelligent solution combines autonomous navigation, advanced sensor integration, and real-time data analysis to revolutionize the way machinery health is monitored and maintained. With a focus on enhanced communication, reporting, and a multitude of cost-saving measures, this project not only ensures the longevity and optimal performance of critical machinery but also positions industries for sustained efficiency gains and long-term financial benefits. As industries embrace this transformative solution, they stand to unlock new levels of operational excellence, resilience, and competitiveness in an ever-evolving landscape.

As an economic boon, the project unveils a trove of cost-saving measures. From mitigating downtime costs through early issue detection to optimizing maintenance efforts and extending equipment lifespan, each facet contributes to a symphony of operational efficiency. The robot's role in preventive maintenance not only slashes reactive repair expenses but also enhances energy efficiency and streamlines labor costs.

6.2 CONCLUSION

Vibration Analysis Robot is a transformative force in the realm of industrial maintenance. This project's crowning achievement lies in the creation of an autonomous marvel that navigates complex environments, decoding the intricate language of machinery vibrations. Through advanced sensor integration and real-time analysis, this robot emerges as a virtuoso, offering unprecedented insights into equipment health.

In the symphony of communication and reporting, the robot plays a pivotal role. Real-time alerts, customizable reporting templates, and seamless integration with mobile devices empower maintenance teams with immediate, actionable

information. Cloud-based storage enhances accessibility, fostering global collaboration in decision-making.

Cost-saving measures, orchestrated by the robot, present an economic symphony. From mitigating downtime costs to optimizing maintenance efforts and extending equipment lifespan, each note resonates with operational efficiency. This project is not merely a safeguard for machinery; it orchestrates a harmonious convergence of technological prowess, financial prudence, and operational excellence.

As industries embrace this transformative solution, they embark on a journey toward sustained efficiency gains, financial prosperity, and a resilient future. The Vibration Analysis Robot stands as a beacon, guiding industries through the dynamic landscape of industrial innovation with a promise of enhanced reliability and economic vitality.

REFERENCE

- [1]. Gupta, M., Khan, M. A., Butola, R., & Singari, R. M. (2021). Advances in applications of Non-Destructive Testing (NDT): A review. *Journal of Non-destructive Evaluation*, 42(3), 1-25.
- [2]. Cawley, P. (2001). Non-destructive testing—current capabilities and future directions. *Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 381(2035), 20220130.
- [3]. Dwivedi, S. K., Vishwakarma, M., & Soni, Prof. A. (2017). Advances and Researches on Non-Destructive Testing: A Review. *Materials Today: Proceedings*, 77, 1246-1251.
- [4]. Raj, B., Jayakumar, T., & Rao, B. P. C. (1995). Non-destructive testing and evaluation for structural integrity. *International Journal of Civil Engineering*, 21(11), 1641-1650.
- [5]. Calmon, P., Mahaut, S., Chatillon, S., & Raillon, R. (2006). CIVA: An expertise platform for simulation and processing NDT data. *NDT&E International*, 66, 102665.
- [6]. Haile, M. A., Zhu, E., Hsu, C., & Bradley, N. (2019). Deep machine learning for detection of acoustic wave reflections. *IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control*, 70(1), 182-193.
- [7]. Zhou, Z.-l., Zhou, J., Dong, L.-j., Cai, X., Rui, Y.-c., & Ke, C.-t. (2017). Experimental study on the location of an acoustic emission source considering refraction in different media. *Sensors*, 23(11), 6521.
- [8]. Gerasimov, S., Sych, T., & Kuleshov, V. (2017). Application of Finite Elements Method for Improvement of Acoustic Emission Testing. *Journal of Non-destructive Evaluation*, 42(2), 1-11.

- [9]. Goszczyn'ska, B. (2013). Analysis of the process of crack initiation and evolution in concrete with acoustic emission testing. *Construction and Building Materials*, 377, 124639.
- [10]. Sattar, T. P., & Brenner, A.-A. (2009). Robotic system for inspection of test objects with unknown geometry using NDT methods. *IEEE Robotics and Automation Letters*, 8(2), 1130-1137.
- [11]. Guo, C., Xu, C., Hao, J., Xiao, D., & Yang, W. (2019). Ultrasonic Non-Destructive Testing System of Semi-Enclosed Workpiece with Dual-Robot Testing System. *Journal of Manufacturing Science and Engineering*, 145(3), 031011.
- [12]. De Agustina, B., Marín, M. M., Teti, R., & Rubio, E. M. (2014). Surface Roughness Evaluation Based on Acoustic Emission Signals in Robot Assisted Polishing. *Robotics and Computer-Integrated Manufacturing*, 80, 102341.
- [13]. Valls Miro, J., Hunt, D., Ulapane, N., & Behrens, M. (2018). Towards Automatic Robotic NDT Dense Mapping for Pipeline Integrity Inspection. *IEEE Transactions on Industrial Electronics*, 70(12), 11855-11865.
- [14]. Shang, J., Bridge, B., Sattar, T., Mondal, S., & Brenner, A. (2008). Development of a climbing robot for inspection of long weld lines. *Robotics and Autonomous Systems*, 161, 104351.
- [15]. Bogue, R. (2010). The role of robotics in non-destructive testing. *NDT&E International*, 66, 102664.
- [16]. C. C. Chaudhari, J. A. Gaikwad, V. R. Bhanuse and J. V. Kulkarni, "Experimental investigation of crack detection in cantilever beam using vibration analysis," 2014 First International Conference on Networks & Soft Computing (ICNSC2014), Guntur, India, 2014, pp. 130-134, doi: 10.1109/CNSC.2014.6906685
- [17]. Mohamad Hazwan Mohd Ghazali, Wan Rahiman, "Vibration Analysis for Machine Monitoring and Diagnosis: A Systematic Review", *Shock and Vibration*, vol. 2021, Article ID 9469318, 25 pages, 2021

[18]. Colin Ratcliffe, Dirk Heider, Roger Crane, Carl Krauthauser, Myung Keun Yoon, John. W. Gillespie, Investigation into the use of low-cost MEMS accelerometers for vibration-based damage detection, Composite Structures, Volume 82, Issue 1,2008, Pages 61-70, ISSN 0263-8223

[19]. <https://www.valbsolutions.com/vibration-analysis-predictive-maintenance/>

[20]. <https://m.indiamart.com/proddetail/arduino-uno-smd-21626891533.html>

[21]. <https://components101.com/modules/l293n-motor-driver-module>

[22]. <https://www.pixelelectric.com/sensors/load-pressure-flow-vibration/imu-acc-mag-gyro/adxl-345-triple-axis-accelerometer/>

[23]. <https://www.makestore.in/product/dc-motor-1000-rpm/>

[24]. <https://grabcad.com/library/ts100-tank-chassis-1>

[25]. <https://m.indiamart.com/proddetail/lm7805-7508-positive-voltage-regulator-ic-5v-1a-set-of-5-19531408530.html>

[26]. <https://hubtronics.in/micro-sd-card-reader-module>

[27]. https://zbotic.in/product/towerpro-mg995-metal-gear-servo-motor-180-rotation/?gad_source=1&gclid=CjwKCAjwh4-wBhB3EiwAeJsppCmk6-tgLqJviKzYKAjUC8tQJMXmxTrkK4Z0jq3vCjYjuroYM4ygoBoC61gQAvD_BwE

[28]. <https://www.electronicwings.com/sensors-modules/bluetooth-module-hc-05->

[29]. https://www.electroniccomp.com/433mhz-12v-4-channel-relay-module-wireless-with-rf-remote-control-switch-without-battery?gad_source=1&gclid=CjwKCAjwh4-wBhB3EiwAeJsppCjfZr8_IAd-1x9Vyy3tYaqN07_HeGVBCDjm6UoqqSNSQt6Kbjv85BoCgQUQAvD_BwE

APPENDIX

RE-2022-223873-plag-report

ORIGINALITY REPORT

15%

SIMILARITY INDEX

12%

INTERNET SOURCES

9%

PUBLICATIONS

8%

STUDENT PAPERS

PRIMARY SOURCES

1

sist.sathyabama.ac.in

Internet Source

3%

2

"Handbook of Nondestructive Evaluation 4.0",
Springer Science and Business Media LLC,
2022

Publication

1%

3

Submitted to Milton Keynes College

Student Paper

<1%

4

www.ncbi.nlm.nih.gov

Internet Source

<1%

5

Tariq P. Sattar, Alina-Alexandra Brenner.
"Robotic system for inspection of test objects
with unknown geometry using NDT
methods", Industrial Robot: An International
Journal, 2009

Publication

<1%

6

elib.suub.uni-bremen.de

Internet Source

<1%

7

www.coursehero.com

Internet Source

<1%

