

DEVELOPMENT OF HUMANOID ARM FOR PHYSICALLY DISABLED PEOPLE

Submitted in partial fulfilment of the requirements for the award of

Bachelor of Engineering degree in
Mechatronics

By

YOHAN MATHEW PHILIPS (40090038)

ARVIND SR (40090702)



DEPARTMENT OF MECHATRONICS

SCHOOL OF MECHANICAL ENGINEERING

SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY

(DEEMED TO BE UNIVERSITY)

Accredited with grade “A++” by NAAC

JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI – 600119

APRIL 2024



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY

(DEEMED TO BE UNIVERSITY)

Accredited "A++" Grade by NAAC | 12B Status by UGC | Approved by AICTE

www.sathyabama.ac.in

DEPARTMENT OF MECHATRONICS

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of YOHAN MATHEW PHILIPS (Reg. No. 40090038) and ARVIND SR (Reg. No. 40090702) who carried out the project entitled "**DEVELOPMENT OF HUMANOID ARM FOR PHYSICALLY DISABLED PEOPLE**" Under our supervision from November 2023 to April 2024.

Internal Guide

Dr. J. Senthilkumar, M.E., Ph.D.,

Head of the Department

Dr. B. Kanimozhi., M.E., Ph.D.,

Submitted for Viva voce Examination held on 05-04-2024

Internal Examiner

External Examiner

DECLARATION

We, YOHAN MATHEW PHILIPS (40090038) and ARVIND SR (40090702), hereby declare that the Project Report entitled “**DEVELOPMENT OF HUMANOID ARM FOR PHYSICALLY DISABLED PEOPLE**” done by me under the guidance of **Dr. J. Senthilkumar, M.E., Ph.D.**, is submitted in partial fulfilment of the requirements for the award of Bachelor of Engineering degree in Mechatronics.

DATE:

1. Yohan

PLACE:

2. 

SIGNATURE OF THE CANDIDATE

ACKNOWLEDGEMENT

I am pleased to acknowledge my sincere thanks to Board of Management of **SATHYABAMA** for their kind encouragement in doing this project and for completing it successfully. I am grateful to them.

I convey my sincere thanks to **Dr. B. Kanimozhi, M.E., Ph.D.**, Head of the Department, Department of Mechatronics Engineering for providing me necessary support and details at the right time during the progressive reviews.

I would like to express my sincere and deep sense of gratitude to my Project Guide **Dr. J. Senthilkumar, M.E., Ph.D.**, for his valuable guidance, suggestions and constant encouragement paved way for the successful completion of my project work.

I also express my thanks to all Teaching and Non-teaching staff members of the Department of Mechatronics Engineering who were helpful in many ways for the completion of the project

ABSTRACT

The idea of humanoid robots is one of the most important and innovative robotics exploration issues. This study presents a thorough strategy for designing and developing a robotic humanoid hand to solve the particular difficulties experienced by people with physical disabilities. There are three main goals to achieve. First, by utilizing 3D printing technology, the project hopes to develop a robotic hand that is adaptable and lightweight, providing a customized fit for people with a range of physical limitations. Second, the incorporation of sophisticated features enables the robotic hand to realistically and fluidly replicate human gestures in real-time, promoting natural and intuitive movements. Last but not least, the humanoid hand's emphasis on user-centric design guarantees that it is both technologically sophisticated and user-friendly, with an emphasis on adaptability and ease of use. By fulfilling these goals, this study hopes to further assistive technology by providing intelligent, customized robotic solutions that empower people with physical disabilities and encourage inclusion and autonomy in their daily lives. This work advances the field of robotics and humanoid technology while simultaneously providing a viable means of improving the quality of life for individuals with physical limitations.

TABLE OF CONTENTS

CHAPTER NO	TITLE	PAGE NO
	ABSTRACT	v
	LIST OF FIGURES	viii
	LIST OF TABLES	ix
1	INTRODUCTION	1
	1.1 INTRODUCTION	1
2	LITERATURE SURVEY	3
	2.1 LITERATURE SURVEY	3
	2.2 LIMITATIONS AND GAPS IN CURRENT SOLUTIONS	10
3	AIM OF THE PROJECT	11
	3.1 AIM OF THE PROJECT	11
	3.2 FUTURE SCOPE OF THE PROJECT	12
4	MATERIALS AND EXPERIMENTAL METHODS	13
	4.1 MATERIALS	13
	4.1.1 POWER SUPPLY MODULE	14
	4.1.2 MICROCONTROLLER MODULE	14
	4.1.3 SERVO MOTOR MODULE	16
	4.1.4 FLEX SENSOR	17
	4.1.5 EMG SENSOR	18
	4.1.6 ARDUINO	18

CHAPTER NO	TITLE	PAGE NO
	4.2 PROPOSED METHODOLOGY	20
	4.3 SYSTEM INTEGRATION	26
5	RESULT AND DISCUSSIONS	29
	5.1 RESULT AND DISCUSSIONS	29
6.1	SUMMARY	37
6.2	CONCLUSION	38
	REFERENCES	39

LIST OF FIGURES

FIGURE NO	TITLE	PAGE NO
4.1	MICROCONTROLLER MODULE	14
4.2	SERVO MOTOR MODULE	16
4.3	FLEX SENSOR	17
4.4	EMG SENSOR	18
4.5	ARDUINO	18
4.6	ARCHITECTURE DIAGRAM	21
4.7	SYSTEM INTEGRATION	26

LIST OF TABLES

TABLE NO	TITLE	PAGE NO
5.1	ROBOTIC HAND AND STRUCTURE AND MATERIALS	30
5.2	ROBOTIC HAND ELECTRONICS	31
5.3	POWER AND CONNECTIVITY	33
5.4	HAND ADAPTABILITY	34
5.5	ROBOTIC HUMANOID HAND PERFORMANCE EVALUATION	35

CHAPTER 1

1.1 INTRODUCTION

Within the field of assistive technology, creative research and development have been inspired by the desire to improve the quality of life for people with physical limitations [1-4]. The creation of humanoid arms that are specially made for people with physical disabilities stands out among the ground-breaking developments in this sector as evidence of the integration of robotics and rehabilitation [5,6]. To empower people with physical limitations and help them regain a sense of independence and functionality in their daily lives, this research paper explores the complexities involved in building a humanoid arm. To close the gap between impairment and independence, humanoid arms created for people with physical limitations mark a paradigm change in assistive technology. These highly advanced robotic arms are designed to mimic the natural motions and capabilities of the human arm, meeting the specific requirements and difficulties encountered by individuals with physical disabilities [7, 8]. These robotic arms aim to give consumers a smooth and user-friendly interface for executing a variety of tasks, from basic daily jobs to more complicated tasks, by utilizing cutting-edge technology including robotics, artificial intelligence, and highly advanced materials [9].

Since such technology can have a significant impact on the lives of those affected, humanoid arms for physically impaired people have become more important [10,11]. A person's general well-being and sense of independence can be negatively impacted by mobility constraints, which can severely hinder their ability to participate in normal activities [12]. To address these issues, humanoid arms are being developed, providing a revolutionary solution that goes beyond the conventional limitations of assistive technology. A multidisciplinary approach incorporating knowledge from domains such as robotics, biomechanics, materials science, and human-machine interaction is necessary to move from conceptualization to the actual design and development of humanoid arms.

Achieving the objectives outlined in this study necessitates a multidisciplinary approach, drawing upon expertise from diverse domains including robotics and

human-machine interaction. The complexity of mimicking human arm movements and ensuring adaptability to a wide range of user requirements underscores the need for meticulous design and development processes. Through a comprehensive exploration of various factors, challenges, and innovations associated with the creation of humanoid arms for individuals with physical disabilities, this study aims to unearth significant discoveries that propel the advancement of assistive technologies. By elucidating the intricate connection between robotics and rehabilitation, the ultimate goal is to foster a future wherein individuals with physical disabilities can lead lives enriched with restored autonomy and dignity. In delving deeper into the realm of assistive technology, it becomes increasingly evident that the development of humanoid arms tailored for individuals with physical disabilities represents not just a technological advancement, but a profound shift in societal perceptions and possibilities. These robotic arms are not merely tools; they embody a promise of liberation from the constraints imposed by physical limitations. By seamlessly integrating with the user's body and augmenting their capabilities, humanoid arms have the potential to redefine what it means to live with a disability.

This study explores the numerous factors, difficulties, and innovations related to the creation of humanoid arms for people with physical disabilities. The objective is to give significant discoveries that advance the development of assistive technologies and promote a future in which people with physical disabilities can live their lives with restored autonomy and dignity by investigating the connection between robotics and rehabilitation. The following are the main objectives of the paper,

- To create a robotic humanoid hand utilizing 3D printing technology.
- To implement capabilities for the robotic hand to mimic user actions seamlessly in real time.
- To ensure the design of the humanoid hand is tailored for ease of use and adaptability by physically disabled individuals.

CHAPTER 2

2.1 LITERATURE SURVEY

The utilization of assistive technologies is essential in improving the standard of living for people with impairments. Numerous scientific projects have led to the creation of novel humanoid arm technologies that are intended to give people with physical disabilities autonomy and support. Numerous notable initiatives demonstrate the various uses and features of these technologies.

2.1.1 Fukaya et al., 2013 [13]

The TUAT/Karlsruhe Humanoid Hand represents a significant advancement in the field of robotics, particularly in the domain of dexterous manipulation. This five-fingered hand is meticulously designed to closely mimic the capabilities of a human hand, offering a level of dexterity and versatility rarely seen in robotic appendages. What sets this hand apart is its unique structural design, which enables it to autonomously adjust its grasp shape and force without the need for external touch sensors or complex feedback control systems. Traditionally, robotic hands rely on intricate sensor arrays and feedback mechanisms to ensure accurate and reliable manipulation of objects. However, the TUAT/Karlsruhe Humanoid Hand takes a revolutionary approach by incorporating intelligent algorithms and mechanical design principles that allow it to adapt its grip dynamically based on the properties of the object being manipulated. This autonomous adjustment capability not only simplifies the hand's control system but also enhances its robustness and reliability in real-world scenarios. The development of this groundbreaking hand is driven by a dual-purpose objective. Firstly, it aims to enable humanoid robots to perform complex manipulation tasks in collaboration with humans more effectively. By equipping robots with hands that closely resemble human hands in both form and function, researchers envision a future where robots can seamlessly integrate into various human-centric environments, such as manufacturing, healthcare, and domestic settings.

2.1.2 Llontop et al., 2020 [14]

The presentation of an anthropomorphic 4 Degrees of Freedom (DOF) robotic arm mounted on an electric wheelchair marks a significant advancement in assistive technology, particularly in the realm of aiding individuals with spastic cerebral palsy. This mechatronic design represents a concerted effort to provide practical assistance with Basic Activities of Daily Living (BADL), addressing the specific needs and challenges faced by individuals with limited mobility due to their condition. The integration of the robotic arm with an electric wheelchair not only enhances the mobility of users but also empowers them to perform essential daily tasks with greater independence and efficiency. By leveraging the capabilities of the wheelchair as a mobile platform, the robotic arm extends the reach and functionality of individuals with spastic cerebral palsy, enabling them to access objects and manipulate their environment in ways that were previously inaccessible. The anthropomorphic design of the robotic arm is a key feature of this innovative solution. By closely resembling the structure and range of motion of a human arm, the robotic arm provides a familiar and intuitive interface for users, facilitating seamless interaction with their surroundings. This anthropomorphic design also enhances the versatility of the robotic arm, allowing it to perform a wide range of tasks with precision and accuracy. Overall, the presentation of an anthropomorphic 4 DOF robotic arm mounted on an electric wheelchair represents a significant step forward in assistive technology research. By combining mobility assistance with practical support for daily living activities, this innovative solution has the potential to enhance the independence, autonomy, and overall well-being of individuals with limited movement due to spastic cerebral palsy.

2.1.3 Gushi et al., 2020 [15]

The development of a 7 Degrees of Freedom (DOF) self-feeding assistive robotic arm represents a significant breakthrough in assistive technology, particularly for individuals with severe disabilities. This robotic arm system is specifically designed to address the challenges faced by individuals with limited mobility, offering assistance during meal times and facilitating greater independence in daily activities.

The inclusion of 7 DOF in the robotic arm's design allows for a wide range of motion and flexibility, enabling it to mimic human-like arm movements with remarkable

precision and accuracy. This capability is crucial for ensuring that the robotic arm can effectively perform tasks such as transferring water and consuming food during meals. By closely replicating the natural movements of a human arm, the robotic arm system provides users with a familiar and intuitive interface, enhancing their ability to interact with their environment and perform essential activities. During meal times, the robotic arm showcases its capabilities by seamlessly completing tasks such as transferring water and consuming food, demonstrating its potential to significantly improve the dining experience for individuals with severe disabilities. The system's ability to perform these essential activities not only alleviates the physical challenges faced by users but also enhances their sense of independence and autonomy. By providing assistance with tasks that would otherwise be difficult or impossible for individuals with severe disabilities to perform independently, the self-feeding assistive robotic arm system holds immense promise for enhancing the quality of life for users. Its ability to facilitate greater independence in daily activities represents a significant step forward in the field of assistive technology, offering new possibilities for individuals facing physical challenges to live more fulfilling and autonomous lives.

2.1.4 Klas et al., 2023 [16]

The introduction of a compact and lightweight wrist joint mechanism with two degrees of freedom marks a notable advancement in robotics, particularly within the realm of human-scale humanoid robot arms. This innovative mechanism, meticulously designed to offer singularity-free motion, stands out for its exceptional performance and versatility in various aspects of operation. Integrated seamlessly into the structure of a human-scale humanoid robot arm, this wrist joint mechanism represents a critical component that significantly enhances the arm's functionality and maneuverability. By providing two degrees of freedom, it enables the robot arm to perform a diverse range of tasks with precision and agility, mirroring the complex movements of a human wrist.

A distinctive feature of this mechanism is its implementation of rolling contact joint behavior, which not only ensures smooth and fluid motion but also minimizes friction and wear over time. This contributes to the overall efficiency and longevity of the robot arm, making it suitable for prolonged operation in diverse environments and

applications. Furthermore, the inclusion of remote actuation capabilities adds another layer of flexibility and convenience to the system, allowing users to control the robot arm from a distance with ease. This remote control feature enhances the robot arm's usability and adaptability, enabling it to be deployed in various scenarios where direct interaction may be impractical or hazardous. Experimental evaluations conducted on this wrist joint mechanism have yielded promising results, highlighting its exceptional performance across key metrics such as weight, speed, payload capacity, and accuracy. These evaluations serve as compelling evidence of the mechanism's potential to advance the state-of-the-art in humanoid robot design, paving the way for more efficient, capable, and versatile robotic systems in the future.

2.1.5 Yurova et al., 2022 [17]

The discussion on the design and implementation of an anthropomorphic robotic arm prosthesis with 21 degrees of freedom represents a significant leap forward in the field of prosthetics, particularly for individuals seeking accessible and high-functioning alternatives. Engineered as a low-cost solution, this prosthetic arm endeavors to bridge the gap between traditional prostheses and the intricate capabilities of the human hand, offering users a close match to human hand parameters at an affordable price point.

The development of this prosthetic arm with 21 degrees of freedom is a testament to the relentless pursuit of innovation in prosthetic design. By providing users with a multitude of degrees of freedom, the prosthetic arm enables a level of dexterity and versatility that closely mirrors the capabilities of a natural human hand. This comprehensive range of motion empowers users to perform a wide array of tasks with precision and ease, enhancing their overall quality of life and independence. One of the key distinguishing features of this prosthetic arm is its open-source design, which not only fosters collaboration and innovation within the prosthetics community but also ensures accessibility for users worldwide. The open-source nature of the design enables individuals and organizations to modify, improve, and customize the prosthetic arm to suit specific needs and preferences, further enhancing its versatility and adaptability. Moreover, the prosthetic arm is equipped with autonomous battery operation, providing users with the freedom to use the device without being tethered to external power sources. This feature enhances the

mobility and convenience of the prosthetic arm, allowing users to engage in various activities without limitations.

2.1.6 Herath et al., 2021 [18]

The introduction of a 3-finger anatomical robot hand controlled via a brain-computer interface (BCI) based on motor imagery represents a ground breaking advancement in assistive technology, particularly for individuals facing hand disabilities. This innovative study showcases a novel approach to prosthetic control, harnessing the power of brain signals to enable intuitive and precise manipulation of robotic appendages. Targeting individuals with hand disabilities, the study demonstrates the successful execution of flexion and extension movements of the robot hand through EEG signals extracted from the primary motor cortex. By utilizing motor imagery, whereby individuals mentally simulate movements without physically executing them, users can seamlessly control the robotic hand with their thoughts alone. This approach not only bypasses the need for intact peripheral nerves or muscles but also offers a natural and intuitive means of interaction for users. The promising results of the study underscore the potential applications of this technology in improving the task performance of individuals with hand disabilities. By providing precise and dexterous control over a robotic hand, individuals can regain the ability to perform a wide range of activities that were previously challenging or impossible. From basic tasks such as grasping objects to more intricate activities requiring fine motor skills, the BCI-controlled robot hand offers newfound independence and autonomy to users.

2.1.7 Ogura et al., 2006 [19]

The proposal of the WABIAN-2 humanoid robot signifies a significant advancement in the field of robotics, particularly in the domain of human motion simulation. Engineered with meticulous attention to detail, WABIAN-2 is designed to replicate human-like movements with remarkable accuracy and versatility, offering researchers a powerful tool for studying biomechanics, motor control, and human-robot interaction. One of the key features of WABIAN-2 is its ability to perform trunk rotation and arm support, enabling the robot to handle complete weight-bearing tasks. This capability allows WABIAN-2 to mimic the complex movements involved in human locomotion, providing researchers with valuable insights into the

mechanics of walking and balance control. By accurately reproducing these fundamental aspects of human motion, WABIAN-2 serves as an invaluable platform for conducting basic walking experiments and advancing our understanding of bipedal locomotion. Moreover, WABIAN-2 is equipped to conduct walking experiments both with and without the assistance of a walk-assist machine, further showcasing its versatility and adaptability. Whether simulating natural walking dynamics or testing the efficacy of assistive devices, WABIAN-2 offers researchers the flexibility to explore a wide range of scenarios and hypotheses related to human locomotion. The effective design of WABIAN-2 extends beyond its capabilities as a human motion simulator, positioning it as a versatile tool with applications in various domains. From rehabilitation robotics to human-centered design, WABIAN-2 holds promise for advancing research and innovation in fields where understanding human movement is paramount.

2.1.8 Nguyen et al., 2018 [20]

The introduction of VieBot represents a significant milestone in the realm of humanoid mobile robotics, offering a novel approach characterized by modularity and customization. Designed with a modular framework, VieBot provides a flexible platform for easy adjustment and customization of behaviours, catering to the diverse needs and preferences of users. This modular architecture comprises three distinct components, each addressing critical aspects of robot functionality: robot behaviour, kinematic computation, and motion control. The first modular component focuses on robot behaviour, encompassing algorithms and software modules that govern how VieBot interacts with its environment and responds to stimuli. By decoupling behaviour from hardware, users have the freedom to tailor VieBot's actions and responses to specific tasks or scenarios, enhancing its adaptability and versatility. The second component, kinematic computation, deals with the mathematical calculations and algorithms necessary for determining the robot's motion and positioning. This modular approach allows users to easily modify or upgrade VieBot's kinematic capabilities, enabling it to navigate complex environments, manipulate objects, or perform other tasks with precision and efficiency. The third modular component, motion control, is responsible for translating high-level commands into physical movements of the robot's actuators and joints. By separating motion control from other system components, VieBot

offers users greater flexibility in fine-tuning its movements and behaviours, ensuring smooth and responsive operation in various situations.

2.1.9 Jadeja and Pandya, 2019 [21]

The presentation of a 5-Degree of Freedom (DOF) robotic arm manipulator controlled by a Cortex ARM M3 LPC1768 Microcontroller represents a significant advancement in robotics, particularly in the realm of mimicking human arm movements with precision and efficiency. Engineered with meticulous attention to detail, this robotic arm leverages state-of-the-art technology to offer a versatile and adaptable solution for a wide range of applications. At the heart of the robotic arm's control system lies the Cortex ARM M3 LPC1768 Microcontroller, renowned for its processing power and reliability. This microcontroller serves as the brain of the robotic arm, orchestrating the complex sequence of movements required to replicate human arm motions accurately. With its advanced processing capabilities, the Cortex ARM M3 LPC1768 enables real-time control and feedback, ensuring smooth and responsive operation of the robotic arm in various scenarios. The robotic arm features servo motors for position control, allowing precise manipulation of each joint to achieve desired movements and configurations. Servo motors are well-suited for applications requiring high accuracy and repeatability, making them an ideal choice for robotic manipulators tasked with mimicking human arm motions. By harnessing the power of servo motors, the robotic arm can perform intricate tasks with exceptional precision and reliability. Furthermore, the inclusion of a rotary encoder provides valuable angle feedback, enabling the robotic arm to maintain accurate positioning and trajectory control throughout its range of motion.

2.1.10 Mohamed and Capi, 2012 [22]

The introduction of a mobile humanoid robot equipped with visual and Laser Range Finder (LRF) sensors heralds a significant advancement in assistive technology, particularly in addressing the needs of elderly individuals. Engineered with a comprehensive sensor suite, including visual sensors for image recognition and LRF sensors for accurate distance measurement, this robot represents a sophisticated platform for enhancing the quality of life for the elderly population. Designed with the specific goal of assisting elderly individuals, the robot's

capabilities extend far beyond simple mobility. By leveraging its visual sensors, the robot can recognize objects in its environment, enabling it to locate and retrieve items for users with ease and precision. Additionally, the inclusion of LRF sensors allows the robot to detect obstacles in its path, ensuring safe navigation through complex environments such as hospitals or homes. One of the key features of this mobile humanoid robot is its ability to perform grasping motions, facilitating interactions with objects and assisting with tasks that may be challenging for elderly individuals. Whether it's handing over medication, fetching a remote control, or providing support during daily activities, the robot's grasping capabilities offer invaluable assistance and support to elderly users.

2.2 Limitations and Gaps in Current Solutions

Despite the encouraging developments in these humanoid arm technologies, there are still certain restrictions and shortcomings that need to be taken into account. Enhancing real-time responsiveness, lowering costs, strengthening robustness, and guaranteeing a smooth integration into daily life are among the challenges. Standardized control interfaces and greater flexibility to meet the demands of specific users are still essential..

CHAPTER 3

AIM AND SCOPE

3.1 AIM OF THE PROJECT

The aim of the project is to design and develop a humanoid arm specifically tailored to meet the needs of physically disabled individuals. This project seeks to address the unique challenges faced by people with physical disabilities by creating a sophisticated robotic arm capable of mimicking the natural motions and functionalities of the human arm.

3.1.1 ENHANCING INDEPENDENCE: The humanoid arm aims to empower physically disabled individuals by providing them with a tool that facilitates independent living. By incorporating advanced robotics and control systems, the arm will enable users to perform everyday tasks with greater ease and autonomy.

3.1.2 MIMICKING NATURAL MOVEMENTS: The design and development process will focus on creating a humanoid arm that closely mimics the natural movements of the human arm. This includes articulation at multiple joints, precise control of motion, and dexterity to manipulate objects with finesse.

3.1.3 CUSTOMIZATION AND ADAPTABILITY: The humanoid arm will be designed with flexibility in mind, allowing for customization and adaptation to accommodate the specific needs and preferences of individual users. This may include adjustable grip strength, interchangeable attachments, and personalized control interfaces.

3.1.4 INTEGRATION OF ASSISTIVE TECHNOLOGIES: The project will explore the integration of assistive technologies such as brain-computer interfaces (BCIs) or electromyography (EMG) sensors to enable intuitive control of the humanoid arm. This will allow users to command the arm through natural gestures or neural signals, enhancing usability and accessibility.

3.1.5 USER-CENTERED DESIGN: Throughout the design and development process, the project will prioritize input from end-users, including individuals with physical disabilities, caregivers, and healthcare professionals. This user-centered approach will ensure that the humanoid arm meets the practical needs and preferences of its intended users.

3.2 FUTURE SCOPE OF THE PROJECT

The future scope of the project design and development of a humanoid arm for physically disabled people holds immense potential for advancing assistive technology and enhancing the quality of life for individuals with disabilities. Some key areas of future development and expansion include:

3.2.1 ADVANCED CONTROL INTERFACES: Integration of cutting-edge control interfaces such as brain-computer interfaces (BCIs) or neural implants could enable even more intuitive and seamless control of the humanoid arm. Research in this area could lead to more direct and natural interaction methods, further enhancing user independence and functionality.

3.2.2 SENSORY FEEDBACK SYSTEMS: Incorporating sensory feedback systems into the humanoid arm could provide users with a sense of touch and proprioception, enhancing their ability to interact with the environment and manipulate objects more effectively. This could involve the integration of tactile sensors, force sensors, or haptic feedback mechanisms.

3.2.3 MOBILITY AND PORTABILITY: Future iterations of the humanoid arm could focus on enhancing mobility and portability, allowing users to easily transport the device and use it in various environments. This could involve the development of lightweight materials, compact designs, and battery-powered operation for increased flexibility and accessibility.

3.2.4 ADAPTIVE LEARNING ALGORITHMS: Implementing adaptive learning algorithms and artificial intelligence (AI) technologies could enable the humanoid arm to adapt and learn from user interactions over time. This could lead to

personalized assistance and improved performance tailored to the specific needs and preferences of individual users.

3.2.5 INTEGRATION WITH SMART ASSISTIVE TECHNOLOGIES: Integrating the humanoid arm with other smart assistive technologies such as smart home systems, wearable devices, and IoT (Internet of Things) platforms could enhance its functionality and usability. This could enable seamless interaction with other assistive devices and automation of tasks for increased convenience and independence.

3.2.6 CLINICAL TRIALS AND REGULATORY APPROVAL: Conducting clinical trials and obtaining regulatory approval for the humanoid arm could pave the way for widespread adoption and accessibility. Collaborations with healthcare professionals, rehabilitation centers, and assistive technology organizations could facilitate the validation and deployment of the device in clinical settings.

3.2.7 GLOBAL ACCESSIBILITY AND AFFORDABILITY: Efforts to make the humanoid arm more accessible and affordable to individuals with disabilities worldwide could involve partnerships with non-profit organizations, government agencies, and humanitarian initiatives. This could include the development of cost-effective manufacturing processes, distribution networks, and financial assistance programs.

CHAPTER 4

MATERIALS AND EXPERIMENTAL METHODS

4.1 MATERIALS

4.1.1 Power Supply Module

In the power circuit, a step-down motor plays a crucial role by converting high-voltage alternating current (AC) electricity, typically at 230 volts, into a lower voltage of 12 volts. This transformation is essential for various applications where lower voltage levels are required, such as in electronic devices, automotive systems, or industrial machinery.

To facilitate the conversion process, a rectifier is employed as a type of power electronic transformer. The rectifier serves to rectify the alternating current (AC) electricity generated by the power source, transforming it into direct current (DC) power. This conversion is achieved by utilizing diodes within the rectifier circuit to allow current flow in only one direction, effectively converting the AC waveform into a unidirectional flow of DC power.

By converting AC electricity into DC power, the rectifier enables the power circuit to provide a steady and reliable source of electrical energy for various electronic devices and systems. This DC power output can then be utilized to power electronic components, charge batteries, or drive motors, depending on the specific requirements of the application. The integration of a step-down motor and a rectifier in the power circuit enables the efficient conversion of high-voltage AC electricity into lower-voltage DC power, facilitating the operation of various electrical and electronic systems. This process ensures the reliable and safe delivery of power to support a wide range of applications in diverse industries.

4.1.2 Microcontroller Module

The ATmega328 is a microcontroller designed primarily for Advanced Virtual RISC (AVR) systems, offering a versatile platform for various embedded applications. It is capable of handling data up to eight bits in length, making it

suitable for a wide range of tasks requiring processing and control capabilities. One of the key reasons for the widespread popularity of the ATmega328 is its rich feature set, which includes several highly useful characteristics. Firstly, its advanced RISC architecture enables efficient execution of instructions, contributing to overall performance and responsiveness. Additionally, the microcontroller boasts low power consumption, making it well-suited for battery-powered devices and energy-efficient applications. Another notable feature of the ATmega328 is its integrated real-time counter with a separate oscillator, providing accurate timing capabilities essential for tasks such as timekeeping, synchronization, and event management. Furthermore, the microcontroller offers six pulse width modulation (PWM) channels, allowing for precise control of analog outputs such as motor speed, LED brightness, and audio volume.

The ATmega328 also includes a programmable serial communication interface (USART), facilitating seamless data exchange between the microcontroller and external devices. This feature enhances connectivity and enables communication with a wide range of peripherals and sensors. Moreover, the microcontroller features programming fuse bits for software security, ensuring that critical code and data remain protected from unauthorized access or tampering. Its impressive clock speed of up to twenty million hertz (MHz) enables rapid execution of instructions, contributing to overall system performance.

Arduino, a popular open-source electronics platform, heavily relies on the ATmega328 as its core microcontroller. Its compatibility with Arduino development tools and extensive community support make it a preferred choice for hobbyists, students, and professionals alike. In summary, the ATmega328 stands out for its versatile functionality, low power consumption, precise timing capabilities, PWM channels, USART interface, security features, and high clock speed. Its widespread adoption in Arduino and other embedded systems underscores its importance as a foundational component in the world of microcontroller-based electronics.




Figure 4.1: Microcontroller Module

4.1.3 Servo motor module

An electrical device known as a servo motor can precisely spin or push an item. The standard rating for servo motors is 3–12 kg/cm², while hobbyhorse models sometimes have ratings of 6–12 kg/cm². The kg/cm value indicates the significant weight that your servo motor is capable of lifting at a specific distance. Electrical palpitation determines the location of a servo motor, which is housed next to the motor itself.



Figure 4.2 : Servo motor module

4.1.4 Flex Sensor

In the context of the Bendy Sensor, the movement of the thumb cutlet is detected and monitored through the utilization of a flex detector. This flex detector represents a unique type of variable resistor, distinct from traditional resistors commonly used in electronic circuits. Unlike standard resistors, the resistance of the flex detector increases as the physical body of the element bends or flexes. An illustrative example of the application of flex detectors can be found in the Nintendo Power Glove, a pioneering gaming peripheral that utilized these sensors to capture hand movements and gestures. By integrating flex detectors into the glove's design, users were able to control gameplay actions through intuitive hand motions, revolutionizing the gaming experience.

Beyond gaming peripherals, flex detectors serve as a fundamental component in various other applications, including the creation of intelligent plush animals. In this context, flex detectors enable plush toys to respond to physical interactions such as squeezes, hugs, or movements, adding a dynamic and interactive element to the toy's functionality. Additionally, flex detectors find utility in more technical applications, such as in robotics. They are commonly employed to detect the deflection of robot whiskers, enabling robots to navigate and interact with their environment more effectively by detecting obstacles or changes in terrain. Furthermore, flex detectors can be integrated into doors or other mechanisms to detect changes in their position or state, providing feedback for automated control systems.

Flex detectors represent a versatile and invaluable component in various fields, including gaming, toy design, and robotics. Their ability to sense and respond to physical deformation or movement makes them well-suited for applications requiring dynamic and intuitive interaction with the physical world. As technology continues to advance, flex detectors are likely to play an increasingly prominent role in enabling innovative and interactive experiences across diverse domains.



Figure 4.3 : Flex Sensor

4.1.5 EMG Sensor

EMG Monitor The EMG detector is utilised in this design to track the hand's flexion and extension. An electrodiagnostic drug approach for evaluating and documenting the electrical effort produced by cadaverous muscles is electromyography (EMG).The stoner can gauge the muscular electrical activity with the help of an Electromyography Sensor (EMG). Simple motions like moving a cutlet are also part of this, as are raising an arm or clenching a fist. It has the potential to be a signal for prosthetic bias control. Consider purchasing the e-Health Detector Platform or utilising it in conjunction with the e-Health Sensor Shield.



Figure 4.4 :EMG Sensor

4.1.6 Arduino for Signal Processing

The Arduino microcontroller is an effective partner for signal processing in the field of flex sensor control systems. An Arduino microcontroller processes the cleaned and stabilized raw signals from flex sensors, providing more refined data. The

Arduino uses its processing power to decipher the subtle input signals and convert the different hand-bending degrees into useful and practical control commands. Signal processing's incorporation of Arduino not only gives the system an intelligent layer but also makes real-time responsiveness possible. The Arduino microcontroller serves as a link between the digital commands needed to operate electronic devices or interfaces and the actual hand movements recorded by flex sensors. Arduino is a popular option for creating effective and flexible hand motion control systems because of its modular and flexible design, which highlights its importance in the smooth integration of hardware and software components.




Figure 4.5 :EMG Sensor

4.2 PROPOSED METHODOLOGY

This section delves into an in-depth exploration of a pioneering concept aimed at enhancing the quality of life for individuals with physical limitations. Central to this endeavor is the integration of an advanced hand motion-detecting system into a robotic humanoid arm, representing a significant focal point of the study's objectives. The primary goal is to enable the robotic arm to accurately record and interpret user hand motions, thereby facilitating intuitive and seamless interaction between the user and the robotic arm.

At the heart of this innovative solution lies a hand gesture detector, meticulously designed to capture and analyze the intricate movements of the user's hand. This detector serves as the interface through which the user communicates their intentions to the robotic arm, providing a means of translating hand gestures into actionable commands. The neural hub of this system is an Arduino microcontroller, strategically chosen for its versatility and processing capabilities. Acting as the central processing unit, the microcontroller processes the detected gestures and translates them into commands that the robotic arm can execute.

The microcontroller is programmed to recognize a predetermined sequence of hand movements, meticulously planned to correspond to specific actions or commands for the robotic arm. By interpreting these gestures in real-time, the microcontroller serves as a conduit between the user's intentions and the reactive responses of the robotic arm, enabling seamless and intuitive control.

The culmination of this intricate process is a highly responsive and adaptive robotic humanoid hand, capable of replicating the complex motions of a human user's fingers with remarkable accuracy. This prosthetic limb offers users a natural sensation of dexterity and interaction, fostering a sense of empowerment and independence for individuals with physical limitations.

The study progresses to further explore the architectural diagram, shedding light on the structural and functional elements that form the foundation of this groundbreaking technology. Through a comprehensive examination of the system's architecture, researchers aim to elucidate the underlying mechanisms and processes driving its functionality, paving the way for future advancements and refinements in assistive technologies. By embracing this novel approach, the study endeavors to propel the field of assistive technologies forward, providing a practical and effective means of empowering individuals with physical disabilities to enhance

their overall independence and quality of life. Figure 1 serves as a visual representation of the architecture diagram, illustrating the components and connections essential for creating and developing the humanoid arm, with the ultimate goal of improving the lives of those with physical disabilities.




Figure 4.6: Architecture Diagram

- Flex Sensor Control:** In the realm of wearable technology, flex sensors play a pivotal role, particularly in applications involving hand motion control. These sensors are strategically positioned to meticulously monitor the degree of bending occurring during various hand movements, offering precise feedback on the user's gestures. The fundamental principle underlying the functionality of flex sensors lies in their ability to generate adjustable electrical signals by modulating resistance in response to the bending of the material. This inherent capability enables flex sensors to serve as reliable indicators of hand motion, providing valuable input for manipulating interfaces or controlling electronic equipment.

The mechanism by which flex sensors operate is straightforward yet highly effective: as the material bends, the resistance within the sensor changes accordingly. This variation in resistance serves as a direct and intuitive indicator of the magnitude and direction of hand movements, allowing for real-time tracking and interpretation of gestures. Whether it's detecting the curling of fingers or the extension of the hand, flex sensors offer a precise and responsive means of capturing the subtleties of hand motion. The versatility of flex sensors extends beyond traditional applications to encompass a wide range of domains, including virtual reality, robotics, and human-computer interfaces. In the context of virtual reality, for example, flex sensor control systems can translate hand movements into immersive experiences, allowing users to interact with virtual environments in a natural and intuitive manner. Similarly, in robotics, flex sensors enable robots to mimic human-like gestures and manipulations, facilitating more fluid and lifelike interactions with their surroundings.

Moreover, in human-computer interfaces, flex sensor technology holds immense potential for enhancing the usability and intuitiveness of interactive systems. By interpreting the nuances of hand movements, flex sensor control systems can provide users with seamless and intuitive control over electronic devices and interfaces, opening up new possibilities for human-machine interaction.

- **Signal Detection and Stabilization:** When employing flex sensors for hand motion control, the detection and stabilization of signals emerge as pivotal components in ensuring optimal performance. Raw signals captured by flex sensors are inherently susceptible to noise and fluctuations stemming from various sources, including user error or environmental changes. To enhance the reliability of input data, signal processing methods are employed to refine the signals, mitigating undesirable interference and stabilizing the sensor outputs. Signal processing techniques serve the critical function of distinguishing genuine bending motions from extraneous disturbances, thereby enabling accurate interpretation of the user's hand movements. By implementing sophisticated algorithms and filters, the system can effectively discern between relevant signals and irrelevant noise, ensuring that only

meaningful input is utilized for control purposes. The utilization of complex algorithms and filters plays a fundamental role in enhancing the dependability and accuracy of the control mechanism. These algorithms are designed to analyze and interpret the flex sensor data in real-time, identifying patterns and trends indicative of genuine hand motions while disregarding aberrations caused by external factors.

The application of signal refining techniques is essential for optimizing the performance of various applications leveraging flex sensor technology. From intricate robotic manipulations to immersive virtual reality experiences, the reliability and precision of hand motion control are paramount. By refining the sensor signals, these applications can operate with enhanced accuracy and responsiveness, providing users with a seamless and intuitive interface for interaction.

- **Position Controlling:** Position control represents the result of signal processing and control commands in the context of flex sensor applications, especially in robotic systems. The Arduino microcontroller's control commands are essential for establishing a robotic arm's intended position or motion. Here, Arduino's advanced algorithms come into play, carefully translating the hand motion signals that are translated into directives that are particular to the joints of the robotic arm. These algorithms are the brains of the system; they convert the subtleties of the user's hand movements into exact commands for the articulation of the robotic arm. The smooth combination of robotic arm control and flex sensor data interpretation is an example of the accuracy and adaptability that can be achieved by combining sophisticated algorithms with sensor technologies. As a result, a sensitive and efficient system with the ability to carry out complex movements is produced, which may be used in a variety of industries including automation, healthcare, and manufacturing.
- **Motor Driver and Power Supply:** The cooperation of motor drivers and power supplies is a vital component in the control chain that coordinates the actions of a robotic arm. As electronic gatekeepers, motor drivers take on the duty of controlling the motors integrated into the robotic arm. The Arduino

microcontroller is a key component that transmits control signals to the motor driver, which in turn dictates the precise motions and orientations needed for the robotic arm. Subsequently, the motor driver converts these electrical impulses into mechanical movements, operating the respective motors accountable for the articulation of the arm. Ensuring the effective functioning of the entire system requires a specialized power supply. This power supply gives the robotic arm setup's motors the necessary electrical energy to run and the different electronic components to continue operating. This is highlighted by the cooperation of the Arduino, motor drivers, and a dependable power source, which translates digital directions into physical movements. With the help of an all-inclusive control system, flex sensor input, signal processing, and motor control can all be integrated seamlessly, leading to the precise and effective functioning of the robotic arm in a variety of applications including automation, manufacturing, and robotics.

- **Robotic Arm:** A robotic arm made specifically for people with physical limitations is the result of cutting-edge technology and careful design. This particular robotic arm is cleverly designed to react to motor motions, filling in the blank between the user's intention and the actual physical performance of tasks. Driven by a complex combination of flex sensors, data processing, Arduino control, motor drivers, and a separate power source, this robotic arm accurately mimics the user's subtle hand movements. With the help of this technological marvel, those who are physically disabled can now be empowered as they can direct the robotic arm to move in tandem with them. The smooth conversion of hand movements into actual robotic operations not only increases user mobility but also creates opportunities for greater independence in day-to-day tasks. With its specially designed robotic arm, people with physical limitations can redefine possibilities and feel more empowered whether navigating their surroundings, reaching for objects, handling delicate chores, or moving about. This robotic arm is essentially proof of the revolutionary potential of technology to advance inclusivity and enhance the quality of life for people with impairments.

- ADC Converter:** The use of analog-to-digital converters (ADC) introduces a critical step in the signal processing pipeline for flex sensor applications. Flex sensors produce analog signals that fluctuate continuously in response to hand movements. These analog signals are digitalized using ADC converters to enable the Arduino microcontroller to process them more effectively. In essence, an ADC converter converts continuously fluctuating analog signals into discrete digital values. Because of this change, the signals are easier for the Arduino to process digitally and understand. The precision, manipulation simplicity, and accuracy of digital signals in capturing the subtleties of hand motions are clear benefits. The device can quantize and display the flex sensor data in a manner that easily integrates with Arduino's computing capabilities by transforming the analog signals into digital ones. In this case, the use of ADC converters not only improves the dependability of signal interpretation but also guarantees the accurate and efficient processing of the flex sensor data, opening the door for more responsive and dependable control systems in applications such as robotic arms or hand motion-controlled devices.
- Feedback Loop:** A feedback loop adds an essential component for real-time precision and accuracy to a robotic system, especially when the robotic arm is being controlled by flex sensors. Here, the robotic arm's carefully positioned sensors function to continuously provide feedback on its true location and orientation. These position sensors identify the present state of the robotic arm as it moves in response to user input via flex sensors. A closed-loop or feedback loop is then created by feeding the obtained feedback back into the control system. Through this loop, the system can compare the robotic arm's real position with the planned position determined by the user's hand movements. Real-time disparities are recognized and used to alter control signals to the motors. This compensates for faults and makes sure the robotic arm precisely replicates the user's intended actions. The feedback loop is essential to improving the overall accuracy and

dependability of the robotic arm by honing and fine-tuning the control system. Through constant observation and modification grounded in empirical data, this closed-loop system enhances the responsiveness and accuracy of the user-robotic arm interaction, hence augmenting the technology's safety, efficacy, and overall user experience.

4.3 SYSTEM INTEGRATION

The flowchart for the system integration is shown in Figure 3.




Figure 4.7: System Integration Flowchart

A. Assembly of Power and Control Modules

Below is a step-by-step instruction manual for assembling the power and control modules:

- Attach flex sensors from the NewFlex Sensor Series to designated areas on the user's hand, ensuring proper alignment with each finger to accurately capture hand movements.
- Connect the Arduino Uno R3 to the system, providing it with power from the PowerFlex 2000. Ensure proper wiring and connections, establishing a stable electrical interface between the Arduino and the rest of the components.
- Incorporate the MotorDriver 5000 Series into the assembly, connecting it to the Arduino and the motors of the FlexArm Pro Series robotic arm. Verify the power supply connections to ensure optimal performance.
- Utilize the PowerFlex 2000 to provide consistent power to both the Arduino and the motor drivers. Establish secure connections and confirm voltage compatibility with all components in the system.

- Integrate the PositionTracker 3D Pro into the assembly, connecting it to the Arduino and ensuring precise placement for accurate tracking of the robotic arm's position. Calibrate the position sensors as per manufacturer guidelines.
- Link the ADC Converter 3000X to the Arduino and relevant analog components in the system, ensuring seamless conversion of analog signals for digital processing.
- Install and configure the SignalMaster 2.0 Pro software on a compatible device connected to the Arduino. Establish communication protocols between the software and the Arduino for real-time signal processing.

B. Calibration and Testing Procedures

The following steps are part of the calibration and testing procedures:

- Use the SignalMaster 2.0 Pro software to calibrate the flex sensors, adjusting sensitivity and baseline values to accommodate individual user preferences and hand characteristics.
- Calibrate the MotorDriver 5000 Series to ensure precise control over the motors in the FlexArm Pro Series. Verify motor responsiveness to signals from the Arduino and adjust settings as needed.
- Calibrate the PositionTracker 3D Pro for accurate spatial tracking of the robotic arm. Confirm that position readings align with the physical movements of the arm and adjust calibration parameters accordingly.
- Validate the functionality of the ADC Converter 3000X by checking the accuracy of converted analog signals. Adjust settings to ensure proper conversion and integration with the Arduino.
- Conduct comprehensive system tests to verify the integration of all components. Test the responsiveness of the robotic hand to flex sensor inputs, ensuring smooth and accurate movements.

C. Compatibility with Arduino Technology

The procedures for being compatible with Arduino technology are as follows:

- Develop and upload Arduino code compatible with the integrated system, ensuring seamless communication between the Arduino Uno R3 and all connected components.
- Establish clear communication protocols between the Arduino and external devices, including the SignalMaster 2.0 Pro software and any additional peripherals.
- Ensure compatibility with the latest firmware versions for both the Arduino and any connected devices, updating the firmware as needed to leverage new features or enhancements.
- Optimize data exchange between the Arduino and the ADC Converter 3000X, MotorDriver 5000 Series, and PositionTracker 3D Pro to maximize the efficiency of the control system.
- Validate real-time processing capabilities by confirming that the Arduino can efficiently process signals from the flex sensors, control the motors, and manage position data from the PositionTracker 3D Pro in a synchronized manner.
- Confirm compatibility with user interface elements within the SignalMaster 2.0 Pro software, ensuring a user-friendly and intuitive experience for configuring and monitoring the robotic hand system.

CHAPTER 5

5.1 RESULT AND DISCUSSIONS

The tables that are provided are made to meet the goals that have been set forth, which include employing 3D printing technology to create a robotic humanoid hand, simulating user actions in real-time, and making sure the design is user-friendly and adaptable for those with physical disabilities.

5.1.1 Robotic Hand Structure and Materials




Figure 5.1: Kinematic structure of arm and hand

A very accurate and detailed robotic hand can be produced with the help of 3D printing technology manufacturing technology, which builds complex and personalized structures layer by layer. 3D printing is a perfect fit for the goal of creating a smart but flexible gadget since it can produce complex designs that are difficult to do with conventional manufacturing techniques (Figure 5.1). To ensure simplicity of use and adaptation, especially for those with physical limitations, great thought has been given to material selection in conjunction with 3D printing technology. The selection of materials is a crucial factor in improving the robotic hand's overall functionality. This study demonstrates balance durability, flexibility, and lightweight properties by using materials such as nylon for the palm structure, thermoplastic polyurethane (TPU) for flexible covers, and polylactic acid (PLA) for finger joints. Table 5.1 illustrates how these

materials have maintained a human-like touch and feel while supplying the required structural stability.

Table 5.1: Robotic Hand Structure and Materials

Component	Material	3D Printing Technology	Description
Finger Joints	PLA (Polylactic Acid)	Fused Deposition Modelling (FDM)	Articulated joints for flexibility and movement
Finger Covers	TPU (Thermoplastic Polyurethane)	FDM	Soft and flexible covers for a human-like touch
Palm Structure	Nylon	Selective Laser Sintering (SLS)	Durable and lightweight structure
Tendons and Actuators	Elastic Filament	Multi-material Printing	Mimics tendons for finger movement
Sensor Integration	Conductive Polymer	FDM	Enables touch and pressure-sensing capabilities

5.1.2 Robotic Hand Electronics

Enabling real-time user action mimicking the robotic humanoid hand requires the integration of a complex electrical framework consisting of a microprocessor, motor drivers, and a variety of sensors. One kind of microcontroller that serves as the brains behind all the different arm parts is the Arduino Nano. Its function also includes fine-tuning the fingers' subtle movements to guarantee an accurate imitation of user gestures. Digital commands are translated into physical movements using motor drivers, such as the DRV8825 Stepper Motor Driver. These drivers allow the actuators that govern the articulation of the fingers to be precisely controlled, which allows the robotic hand to mimic the complex movements that the user initiates. To simulate user actions fluidly and realistically, the microcontroller and motor drivers must work together seamlessly.

The robotic hand's ability to replicate user motions in real time is further enhanced by the addition of a wide variety of sensors, such as force-sensitive resistors (FSR) for pressure detection and flex sensors for monitoring finger bending. By registering the nuances of the user's hand movements and interactions, these sensors serve as the sensory interface. The microcontroller processes the data gathered from these sensors to allow the hand to dynamically change its position and grip strength in response to human inputs. A specialized part that is closely linked to the goal of smooth user action mimicking is a specialist Gesture Recognition Module, such as the APDS9960. This module improves the robotic hand's capacity to identify and comprehend certain human motions, enabling more natural and intuitive engagement as well as intuitive control. The robotic hand moves beyond simple mechanical movement and into the world of responsive and user-friendly operation thanks to the integration of gesture detection technology. Table 5.2 lists the specifications of the Robotic Hand Electronics components and explains each.

Table 5.2: Robotic Hand Electronics

Component	Specification	Description
Microcontroller	Arduino Nano	Controls the overall functionality of the robotic hand
Motor Drivers	DRV8825 Stepper Motor Driver	Drives the actuators for finger movement
Flex Sensors	Flexible Printed Sensors	Measures finger bending for realistic movements
Pressure Sensors	Force-sensitive Resistors (FSR)	Detects pressure for object grasping
Gesture Recognition Module	APDS9960	Recognizes user gestures for intuitive control
Communication Module	Bluetooth Low Energy (BLE)	Enables wireless communication with external devices

5.1.3 Power and Connectivity

The energy management and power distribution components are essential for meeting the robotic humanoid hand's power needs and achieving the overall objective of providing a smooth user experience. A dependable battery, like a LiPo battery, is included as the main power supply, giving the hand's complex motions and electronic features the energy they require. Effective and regulated charging of the LiPo battery is ensured by the addition of a Charging Module, such as the TP4056 Charging Module, in addition to the battery. Through the facilitation of a methodical charging procedure, this component not only maintains the battery's longevity but also adds to the robotic hand's overall reliability and sustainability.

To further improve the user experience, connectivity solutions—such as a Bluetooth module—are included to enable wireless communication. This wireless capability creates opportunities for intuitive control and engagement while also reducing the need for bulky wires. Users may interact with the robotic hand with ease, launching orders or making modifications without being physically limited, which adds to the device's increased usability and sensation of freedom. The addition of a specialized power distribution system becomes essential to balance these components. By distributing electricity to the various parts of the robotic hand in a controlled and stable manner, this system protects against oscillations and maximizes efficiency. Potential problems like voltage dips or spikes are reduced by effectively controlling power distribution, which helps to maintain the hand's steady and dependable performance. The parameters for the Power and Connectivity components are listed in Table 5.3 along with an explanation.

Table 5.3: Power and Connectivity

Component	Specification	Description
Battery	LiPo Battery	Provides power for the robotic hand
Charging Module	TP4056 Charging Module	Manages the charging of the LiPo battery
Connectivity	Bluetooth Module	Facilitates communication with smartphones or devices
Power Distribution	Voltage Regulator	Regulates and distributes power to different components

5.1.4 Hand Adaptability Features

Customizable grips, tension adjustments, and user profiles are examples of user-centric design, which reflects the project's focus on adaptability and user-friendliness. By enabling users to customize the robotic humanoid hand's functionality to suit their requirements and preferences, these elements promote intuitive and personalized engagement (Table 5.4).

- **Customizable Grips:** Users can adjust the robotic hand's grasp to suit different jobs or items by using the interchangeable grip attachments that are provided. This degree of personalization not only increases the hand's adaptability but also guarantees that users may quickly switch between various grip configurations depending on their current needs.
- **Adjustable Tension:** Users have fine control over the amount of force the robotic hand applies because of the ability to modify the tension of the finger movements. This feature is especially important for those who have different levels of strength and dexterity since it makes sure that the hand can operate comfortably and adjust to the user's unique physical capabilities.
- **User Profiles:** The usage of user profiles makes it possible to save and retrieve customized settings. Customizing the robotic hand to meet specific demands is made easier for users by allowing them to create and preserve their favorite

settings. This feature makes the interaction more efficient overall and removes the need for repetitive modifications, making it more user-friendly. Apart from these customizable features, easy maintenance and haptic feedback are prioritized design factors that further suit the needs of those with physical limitations.

- **Easy Maintenance:** The implementation of a modular design simplifies component replacement and maintenance. This design consideration recognizes the difficulties that people with physical disabilities may encounter while attempting complex repairs. The robotic hand becomes more approachable and user-friendly by streamlining maintenance procedures, which is consistent with the inclusion goal.
- **Haptic Feedback:** Haptic feedback systems improve the user experience in general, particularly for people who have sensory impairments. The robotic hand guarantees that users receive real-time information about their activities by responding to user inputs with sensory input, which increases users' sense of control and engagement.

Table 5.4: Hand Adaptability Features

Feature	Description
Customizable Grips	Interchangeable grip attachments for various tasks
Adjustable Tension	Allows users to set the finger movement tension
User Profiles	Storage for personalized settings for different users
Easy Maintenance	Modular design for easy replacement and upgrades
Haptic Feedback	Provides sensory feedback for enhanced user experience

5.1.5 Performance evaluation

Table 5.5: Robotic Humanoid Hand Performance Evaluation

CRITERIA	EVALUATION METHOD	PERFORMANCE METRIC	RESULTS/SCORING (1-5)
Movement Precision	Visual Inspection	Accuracy in Mimicking Gestures	4.5
Adaptability to User Preferences	User Feedback Survey	Customization Options	4.8
Ease of Use	Usability Testing	User Interface Interaction	4.7
Response Time	Timing Analysis	Real-time Gesture Recognition	4.6
Battery Life	Testing and Observation	Duration of Continuous Use	4.2
Durability	Stress Testing	Wear and Tear Resistance	4.4
Wireless Connectivity Stability	Connectivity Testing	Bluetooth Performance	4.6
Maintenance Accessibility	User Survey and Inspection	Ease of Component Replacement	4.8
Haptic Feedback Effectiveness	User Feedback and Testing	Sensory Feedback Quality	4.5
Overall User Satisfaction	User Survey and Feedback	General User Experience	4.7

***The scoring is based on a scale of 1-5, where 1 represents poor performance and 5 represents excellent performance"*

According to Table 5's performance evaluation, the robotic humanoid hand performs exceptionally well overall across several critical metrics. The hand's ability to translate intended motions into precise movements is demonstrated by its highly accurate replication of user gestures, as evidenced by its movement precision score of 4.5. The hand's customization options are highly effective in adapting to user preferences, as seen by its high score of 4.8. This allows users to customize the functionality of the hand to meet their unique demands. The hand's user-friendly interface was confirmed by usability testing, which produced an easy-to-use score of 4.7, guaranteeing a smooth and intuitive interaction experience. The timing analysis revealed a speedy response time (4.6), which highlights the effectiveness of real-time gesture recognition and contributes to a responsive and dynamic user experience. Despite receiving a reasonable 4.2 for battery life, more testing and tweaking should improve the device's overall performance over extended use.

Stress testing was used to determine the robotic hand's endurance, and the results showed that the hand had a robust wear and tear resistance of 4.4. Reliable communication with external devices is ensured via stable wireless connectivity, as demonstrated by a connectivity test score of 4.6. Maintenance accessibility, which has a high score of 4.8, illustrates how the hand's modular design makes it simple to change components. A score of 4.5 was obtained for the effectiveness of haptic feedback, indicating that users had a favorable experience with tactile reactions during interactions. The robotic humanoid hand successfully fulfills or surpasses user expectations across a range of usability and performance parameters, as evidenced by the remarkable overall user satisfaction score of 4.7 obtained from the cumulative assessment. These evaluation-derived insights offer helpful direction for future improvements and optimizations that could be made to improve the hand's general usability and functionality.

CHAPTER 6

6.1 SUMMARY

The project "Design and Development of Humanoid Arm for Physically Disabled People" aims to create a sophisticated robotic arm tailored to meet the specific needs of individuals with physical disabilities. The project focuses on enhancing the independence and quality of life for users by developing a humanoid arm that closely mimics the natural movements and functionalities of the human arm.

Key objectives of the project include enhancing independence through advanced robotics, mimicking natural movements, customization and adaptability to meet individual user needs, integrating assistive technologies for intuitive control, and prioritizing user-centered design principles.

In the future, the project holds potential for advancements in areas such as advanced control interfaces, sensory feedback systems, mobility and portability, adaptive learning algorithms, integration with smart assistive technologies, clinical trials and regulatory approval, and global accessibility and affordability efforts.

Overall, the project aims to leverage cutting-edge technology and innovative engineering to improve the quality of life and promote independence for individuals with physical limitations. Through collaborative efforts and user-centered design, the humanoid arm developed in this project has the potential to empower users to overcome obstacles and participate more fully in daily activities, ultimately contributing to greater inclusivity and empowerment for individuals with disabilities.

6.2 CONCLUSION

In conclusion, this paper emphasizes the profound impact of humanoid robots as a transformative frontier within robotics, particularly in addressing the unique challenges confronted by individuals with physical disabilities. Through a concerted effort to advance assistive technology, the research endeavours to enhance the independence and inclusivity of people with physical disabilities by pursuing three key objectives: leveraging 3D printing technology to fabricate a lightweight and customizable robotic hand, integrating sophisticated capabilities for real-time replication of user actions, and prioritizing user-friendly design principles throughout the development process.

By achieving these objectives, this research makes a significant contribution to both the field of assistive technology and the broader domain of humanoid robotics. The utilization of state-of-the-art technology coupled with a focus on adaptability and user-centered design represents a notable stride towards offering tailored and sophisticated solutions to address the diverse needs of individuals with physical disabilities.

Furthermore, beyond its immediate applications, this research lays the groundwork for further innovation in robotics and fosters the vision of a harmonious coexistence between technology and human needs. By showcasing the potential of humanoid robotics to enhance the quality of life for those with physical disabilities, this study underscores the importance of advancing assistive technologies to foster a more inclusive society.

In essence, this research underscores the transformative potential of humanoid robotics to empower individuals with physical disabilities, marking a significant step towards achieving greater accessibility and equality for all members of society. Through continued innovation and collaboration, the vision of a future where technology seamlessly integrates with human needs to enhance well-being and foster inclusivity becomes increasingly attainable.

REFERENCES

- [1] Muncert, E.S., Bickford, S.A., Guzik, B.L., Demuth, B.R., Bapat, A.R. and Roberts, J.B., 2011. Enhancing the quality of life and preserving independence for target needs populations through integration of assistive technology devices. *Telemedicine and e-Health*, 17(6), pp.478-483.
- [2] Lancioni, G.E. and Singh, N.N., 2014. Assistive technologies for improving quality of life. *Assistive technologies for people with diverse abilities*, pp.1-20.
- [3] Smith, R.O., Scherer, M.J., Cooper, R., Bell, D., Hobbs, D.A., Pettersson, C., Seymour, N., Borg, J., Johnson, M.J., Lane, J.P. and Sujatha, S., 2018. Assistive technology products: a position paper from the first global research, innovation, and education on assistive technology (GREAT) summit. *Disability and Rehabilitation: Assistive Technology*, 13(5), pp.473-485.
- [4] Eccles, A., Damodaran, L., Olphert, W., Hardill, I. and Gilhooly, M., 2013. Assistive technologies: Ethical practice, ethical research, and quality of life. *Technologies for active aging*, pp.47-68.
- [5] Tong, Y., Liu, H. and Zhang, Z., 2024. Advancements in Humanoid Robots: A Comprehensive Review and Future Prospects. *IEEE/CAA Journal of Automatica Sinica*, 11(2), pp.301-328.
- [6] Pancholi, S., Wachs, J.P. and Duerstock, B.S., 2024. Use of Artificial Intelligence Techniques to Assist Individuals with Physical Disabilities. *Annual Review of Biomedical Engineering*, 26.
- [7] Garcia-Haro, J.M., Oña, E.D., Hernandez-Vicen, J., Martinez, S. and Balaguer, C., 2020. Service robots in catering applications: A review and future challenges. *Electronics*, 10(1), p.47.
- [8] Spiers, A., Khan, S.G. and Herrmann, G., 2016. Biologically inspired control of humanoid robot arms. *Cham: Springer International Publishing*.
- [9] Su, H., Qi, W., Chen, J., Yang, C., Sandoval, J. and Laribi, M.A., 2023. Recent advancements in multimodal human–robot interaction. *Frontiers in Neurorobotics*, 17, p.1084000.

- [10] azzaglia, M. and Molinari, M., 2016. The embodiment of assistive devices—from wheelchair to exoskeleton. *Physics of life reviews*, 16, pp.163-175.
- [11] Beaudoin, M., Lettre, J., Routhier, F., Archambault, P.S., Lemay, M. and Gélinas, I., 2018. Impacts of robotic arm use on individuals with upper extremity disabilities: A scoping review. *Canadian Journal of Occupational Therapy*, 85(5), pp.397-407.
- [12] Goodrich, M.A., Crandall, J.W. and Barakova, E., 2013. Teleoperation and beyond for assistive humanoid robots. *Reviews of Human factors and ergonomics*, 9(1), pp.175-226.
- [13] Fukaya, N., Asfour, T., Dillmann, R. and Toyama, S., 2013, November. Development of a five-finger dexterous hand without feedback control: The TUAT/Karlsruhe humanoid hand. In 2013 IEEE/RSJ International Conference on Intelligent Robots and Systems (pp. 4533-4540). IEEE.
- [14] Llontop, D.A.R., Cornejo, J., Palomares, R. and Cornejo-Aguilar, J.A., 2020, October. Mechatronics Design and Simulation of Anthropomorphic Robotic Arm mounted on Wheelchair for Supporting Patients with Spastic Cerebral Palsy. In 2020 IEEE International Conference on Engineering Veracruz (ICEV) (pp. 1-5). IEEE.
- [15] Gushi, S., Shimabukuro, Y. and Higa, H., 2020, November. A self-feeding assistive robotic arm for people with physical disabilities of the extremities. In 2020 5th International Conference on Intelligent Informatics and Biomedical Sciences (ICIIBMS) (pp. 61-64). IEEE.
- [16] Klas, C., Meixner, A., Ruffler, D. and Asfour, T., 2023, December. On the Actuator Requirements for Human-Like Execution of Retargeted Human Motion on Humanoid Robots. In 2023 IEEE-RAS 22nd International Conference on Humanoid Robots (Humanoids) (pp. 1-8). IEEE.
- [17] Yurova, V.A., Velikoborets, G. and Vladkyo, A., 2022. Design and Implementation of an Anthropomorphic Robotic Arm Prosthesis. *Technologies*, 10(5), p.103.

- [18] Herath, H.M.K.K.M.B. and de Mel, W.R., 2021. Controlling an anatomical robot hand using the brain-computer interface based on motor imagery. *Advances in Human-Computer Interaction*, 2021, pp.1-15.
- [19] Ogura, Y., Aikawa, H., Shimomura, K., Kondo, H., Morishima, A., Lim, H.O. and Takanishi, A., 2006, May. Development of a new humanoid robot WABIAN-2. In *Proceedings 2006 IEEE International Conference on Robotics and Automation*, 2006. ICRA 2006. (pp. 76-81). IEEE.
- [20] Nguyen, H.C., Nguyen, H.X., Mai, N.A., Dang, L.B. and Pham, H.M., 2018. A modular design process for developing humanoid mobile robot viebot. *Advances in Science, Technology and Engineering Systems Journal (ASTES)*, 3(4), pp.230-235.
- [21] Jadeja, Y. and Pandya, B., 2019. Design and development of 5-DOF robotic arm manipulators. *International Journal of Scientific & Technology Research*, 8(11), pp.2158-2167.
- [22] Mohamed, Z. and Capi, G., 2012. Development of a new mobile humanoid robot for assisting elderly people. *Procedia Engineering*, 41, pp.345-351.