

COMPREHENSIVE DRIVER MONITORING FOR SAFETY AND EMERGENCY RESPONSE

Submitted in partial fulfillment of requirements for the award of
Bachelor of Engineering in Electronics and Communication Engineering

by

C.S.HARISH (40130078)
S.GOKUL RAM (40130067)



DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING
SCHOOL OF ELECTRICAL AND ELECTRONICS

SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)

CATEGORY-1 UNIVERSITY BY UGC

Accredited with Grade "A++" by NAAC | 12B status by UGC | Approved by AICTE

JEPPIAAR NAGAR, RAJIV GANDHI SALAI,
CHENNAI-600119

APRIL 2024



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)

Accredited "A++" Grade by NAAC | 12B Status by UGC | Approved by AICTE
www.sathyabama.ac.in

DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that this Final Year Project Report is the bonafide work of GOKUL RAM S (40130067) , HARISH C.S(40130078), who have done the project work as a team who carried out the project entitled "**COMPREHENSIVE DRIVER MONITORING FOR SAFETY AND EMERGENCY RESPONSE**" under my supervision from November 2023 to April 2024.

Internal Guide

Ms. MARY SAJIN SANJU, I.M.Tech (Ph.D)

Head of the Department

Dr. T. RAVI, M.E., Ph.D.

Submitted for Viva voce Examination held on 17/4/2024

Internal Examiner
External Examiner

DECLARATION

We, S GOKUL RAM (40130067), C.S.HARISH(40130078), here by declare that the Project Report entitled "**COMPREHENSIVE DRIVER MONITORING FOR SAFETY AND EMERGENCY RESPONSE**" done by us under the guidance of **Ms. MARY SAJIN SANJU.I, M.Tech (Ph.D)** , Professor, is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in **DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING.**

DATE: 17/4/24

PLACE: Chennai

SIGNATURE OF THE CANDIDATES

1. S. Gokul Ram
2. Harish

ACKNOWLEDGEMENT

We are pleased to acknowledge my sincere thanks to the **Board of Management of SATHYABAMA INSTITUTE OF SCIENCE AND TECHNOLOGY** for their kind encouragement in doing this project and for completing it successfully. I am grateful to them.

We convey our thanks to **Dr. N. M. NANDHITHA, M.E., Ph.D., Dean, School of Electrical and Electronics**, and **Dr. T. RAVI, M.E., Ph.D., Professor & Head, Department of Electronics and Communication Engineering** for providing me necessary support and details at the right time during the progressive reviews.

We would like to express our sincere and deep sense of gratitude to my Project Guide **Ms.MARY SAJIN SANJU.I, M.Tech., (Ph.D)., Professor, Department of Electronics and Communication Engineering**, for her valuable guidance, suggestions and constant encouragement paved the way for the successful completion of my project work.

We wish to express my thanks to all Teaching and Non-teaching staff members of the **Department of Electronics and Communication Engineering** who were helpful in many ways for the completion of the project.

ABSTRACT

The central component of our project is the Arduino Uno microcontroller, which forms the heart of our driver behavior monitoring system. Our system is designed with a primary goal of enhancing driver safety by integrating a range of sensors and modules. The Eye Blink Sensor tracks the driver's eye movements, effectively detecting signs of drowsiness or fatigue, thereby alerting the driver and mitigating potential accidents. Simultaneously, the Heartbeat Sensor continuously monitors the driver's heart rate, providing vital information about their overall health and well-being throughout the journey. Ensuring responsible driving practices, we've incorporated a Gas Sensor to detect alcohol levels, providing crucial information regarding the driver's condition. In the event of any irregularities detected in these parameters, our system employs a GPS module to precisely locate the vehicle. For immediate response during emergencies, we've integrated a GSM module that automatically sends an SMS to nearby ambulance or rescue teams when abnormalities are detected, be it drowsiness or alcohol consumption. Visual alerts are provided through a red LED indicator, illuminating during emergencies to draw attention to the situation. Additionally, real-time feedback to the driver is presented via an LCD display, showing the current readings of monitored parameters such as heart rate, alcohol level, and drowsiness. This comprehensive system aims to significantly improve driver safety and well-being while on the road.

TABLE OF CONTENTS

CHAPTER NO.	TITLE	PAGE NO.
	ABSTRACT	v
	LIST OF ABBREVIATIONS	x
	LIST OF FIGURES	xi
	LIST OF TABLES	xiii
1	INTRODUCTION	1
	1.1 GENERAL	1
	1.2 SCOPE OF THE PROJECT	1
	1.3 EXISTING SYSTEM	2
2	LITERATURE SURVEY	3
3	PROPOSED SYSTEM	6
	3.1 PROJECT DESCRIPTION	6
	3.1.1 GENERAL	6
	3.1.2 PROBLEM DEFINITION	6
	3.1.3 MODULES NAME	7
	3.1.4 MODULE DESCRIPTION	7
	3.1.5 SENSOR MODULE	8
	3.1.6 MESSAGE MODULE	9
	3.1.7 VECHILE CONTROL MODULE	10

3.1.8 WORKING PRINCIPLE	10
3.2 HARDWARE AND SOFTWARE	11
3.2.1 ARDUNO MICRO CONTROLLER	11
3.2.2 EYEBLINK SENSOR	13
3.2.2.1 PRODUCT DESCRIPTION	13
3.2.3 HEART BEAT SENSOR	14
3.2.3.1 FEATURES	15
3.2.4 GAS SENSOR	15
3.2.4.1 CONSTRUCTION	15
3.2.4.2 THEORY OF OPERATION	16
3.2.5 GPS	16
3.2.5.1 WORKING OF GPS	17
3.2.5.2 GPS SEGMENT	17
3.2.5.3 SPACE SEGMENT	17
3.2.5.4 CONTROL SEGMENT	18
3.2.5.5 USER SEGMENT	18
3.2.5.6 GPS POSITIONING	18
3.2.5.7 USING A GPS RECEIVER	18
3.2.5.8 ADVANTAGES OF GPS	19
3.3 GSM	19
3.3.1 FUNCTIONAL DESCRIPTION	20
3.3.2 AUDIO	24

3.3.3 TYPICAL MICROPHONE CONNECTION	24
3.3.4 TYPICAL SPEAKER CONNECTION	26
3.4 MOTOR DRIVER IC	26
3.4.1 H BRIDGE CIRCUIT	27
3.4.2 L2393D MOTOR DRIVER IC	28
3.4.3 FEATURES	30
3.4.4 APPLICATIONS	30
3.5 LIQUID CRYSTAL DISPLAY	30
3.5.1 REGISTER SELECT	31
3.5.2 COMMAND REGISTER	31
3.5.3 DATA REGISTER	31
3.5.4 IMPORTANT COMMAND CODES	31
3.5.5 DISPLAYING CUSTOM CHARACTERS	33
3.6 SOFTWARE REQUIREMENTS	35
3.6.1 EMBEDDED SYSTEM PROGRAMMING	35
3.6.2 EMBEDDED SYSTEMS	36
3.6.3 CHARACTERISTICS OF EMBEDDED	38
3.6.3.1 ADVANTAGES	38
3.6.3.2 DISADVANTAGES	38
3.7 DESIGN STEPS REQUIRED FOR THE DEVELOPMENT OF EMBEDDED SYSTEM	39
3.7.1 FUNCTION OF SIMULATORS	42

4	EXPERIMENTAL AND METHODS	43
	4.1 FUTURE ENHANCEMENT	45
	4.1.1 ADVANTAGES	45
	4.2 STANDARDS	46
	4.3 CONSTRAINTS	46
	4.4 TRADE OFF	47
	RESULTS AND DISCUSSIONS	48
	5.1 RESULTS	48
	5.2 DISCUSSIONS	50
6	CONCLUSION	52
	REFERENCE	53

LIST OF ABBREVIATIONS

GSM	GLOBAL SYSTEM FOR MOBILE COMMUNICATION
SIM	SUBSCRIBER IDENTIFY MODULE
LED	LIGHT EMITTING DIODE
DLT	DEPARTMENT OF LANDER TRANSPORT
RTDDS	REAL-TIME DROWSINESS DETECTION SYSTEM
PSD	POWER SPECTRAL DENSITY
LCD	LIQUID CRYSTAL DISPLAY
GPS	GLOBAL POSITIONING SYSTEM
DMS	DRIVER MONITORING SYSTEM
ROI	REGION OF INTEREST
PCB	PRINTED CIRCUIT BOARD
RTOS	REAL-TIME OPERATING SYSTEM

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE NO.
3.1	BLOCK DIAGRAM	7
3.2	READING DATA MODULES	8
3.3	ALERT THE INFORMATION MODULES	9
3.4	CONTROL THE VEHICLE MODULES	10
3.5	ARDUINO UNO	12
3.6	EYE BLINK SENSOR	13
3.7	HEARTBEAT SENSOR	14
3.8	GAS SENSOR	15
3.9	GLOBAL POSITIONING SYSTEM	16
3.10	GSM MODULE	20
3.11	SYSTEM BLOCK DIAGRAM	20
3.12	KEYPAD CONNECTION SIM	23
3.13	SIM CARD CONNECTION	23
3.14	AUDIO FREQUENCY RESPONSE CURVE	24
3.15	SINGLE ENDED CONNECTION	24
3.16	H BRIDGE MOTOR	26
3.17	H BRIDGE CIRCUIT	27
3.18	OPERATION OF H BRIDGE CIRCUIT	28
3.19	H BRIDGE MOTOR CIRCUIT	29
3.20	RTOS	37

3.21	STRUCTURE OF EMBEDDED SYSTEMS	38
3.22	EMBEDDED SYSTEM TOOLS AND PERIPHERALS	40
4.1	PROTOTYPE OF PROJECT	44
5.1	OUTPUT OF ALCOHOL CONSUMPTION	49
5.2	OUTPUT OF MESSAGE	50

LIST OF TABLES

TABLE NO.	TITLE	PAGE NO.
1	TABLE OF VBAT PIN	21
2	TABLE OF GND PIN	22
3	TABLE OF POWER CONSUMPTION IN OFF MODE	22

CHAPTER 1

INTRODUCTION

1.1 GENERAL

The central component of our project is the Arduino Uno microcontroller, which powers our driver behavior monitoring system. Our system enhances driver safety by integrating sensors and modules. The Eye Blink Sensor detects drowsiness, while the Heartbeat Sensor monitors health. A Gas Sensor checks alcohol levels, and a GPS module tracks vehicle location. In emergencies, the GSM module sends alerts to rescue teams. A red LED signals emergencies and an LCD display provides real-time feedback. This comprehensive system aims to improve driver safety and well-being on the road, making driving responsible and secure. This comprehensive driver monitoring project aims to leverage cutting-edge technologies to create a multifaceted system that not only monitors driver behavior in real time but also integrates seamlessly with emergency response protocols. By harnessing the power of sensors, biometrics, and machine learning algorithms, this project seeks to provide drivers with the tools they need to navigate safely while also enabling swift and effective emergency interventions when necessary.

In the following sections, we will delve into the various components and functionalities of this project, exploring how each element contributes to the overarching goal of enhancing road safety and emergency response capabilities. From monitoring driver behavior to detecting potential hazards and facilitating timely interventions, this comprehensive approach holds the promise of ushering in a new era of safety and security on our roads.

1.2 SCOPE OF THE PROJECT

The scope of the project encompasses the development of a driver behavior monitoring system centered around the Arduino Uno microcontroller. This system incorporates various sensors, including an Eye Blink Sensor for detecting drowsiness, a Heartbeat Sensor for monitoring health, and a Gas Sensor for alcohol detection. It also includes a GPS module for precise vehicle location tracking and a GSM module to alert rescue teams during emergencies. Visual alerts and real-time feedback through an LCD display enhance driver awareness. The project's primary goal is to enhance driver safety and well-being by providing timely warnings and emergency

alcohol consumption. Integrate biometric sensors to monitor vital signs such as heart rate and blood pressure, which could indicate stress or medical emergencies

1.3 EXISTING SYSTEM

The current system lacks several critical features, including an automated driver behaviour monitoring system, driver health tracking capabilities, an emergency alert system, and location tracking functionality.

The existing systems for comprehensive driver monitoring for safety and emergency response, while advanced and beneficial, do have some disadvantages:

1. **Privacy Concerns:** Comprehensive driver monitoring systems often involve collecting sensitive data about drivers, such as their location, driving behavior, and even physiological data like heart rate. This can raise significant privacy concerns among drivers who may feel uncomfortable with such extensive monitoring.
2. **Cost:** Implementing comprehensive driver monitoring systems can be expensive, both in terms of initial setup costs and ongoing maintenance. This cost may be prohibitive for some fleet operators or individual drivers, limiting the widespread adoption of these systems.
3. **False Alarms:** The systems may sometimes generate false alarms, triggering emergency responses when there is no actual danger present. This can lead to unnecessary interruptions and may undermine trust in the system's reliability.

CHAPTER 2

LITERATURE SURVEY

TITLE1:Detection of Drowsiness from Facial Images in Real-Time Video Media using Nvidia Jetson Nano Petchara Inthanon, Surasak Mungsing Drowsiness affects people everyday life that leads to inefficient work or car accidents due to insomnia resulting damage to life and property. Especially, it can become worse when it happens to public transportation. As the author works in Department of Land Transport (DLT), drowsiness is a factor that causes car accident. Therefore, due to this concern, effective detection of drowsiness system is performed. The purpose of this paper is to develop Algorithm to analyze face structure from taking video media and detecting drowsiness. Also, the system is conducted to examine Algorithm's efficiency. The result shows that using facial landmarks can help to generate eyes and mouth component effectively, which can help to create equations to analyze drowsiness correctly by using Nvidia Nano Jetson. Nvidia Jetson Nano is a tool that accurately evaluates image by tracking closing eye motions more than 35 FPS or 1.5 seconds, and yawning or opening mouth motion more than 50 FPS equals to 2 seconds. It indicates the possibility of sleepiness which notifies to drivers. Thus, it is suggested that government should support the system and take to Thailand policy in order to reduce car accident from insomnia.

TITLE 2: Drowsiness Detection of a Driver using Conventional Computer Vision Application **AUTHOR:** Hitendra Garg.The developments in technology over the years bring support to drivers using smart vehicle systems. In past few years, there has been a substantial increase in road accidents in India and worldwide as well. The most significant reasons for the same are drowsiness and fatigue. Therefore, driver drowsiness and fatigue detection is major possible area to prevent a large number of sleep induced road accidents. Considering this problem, this article proposes a Real-Time Drowsiness Detection System (RT-DDS) applicable in motor vehicles with the help of conventional Computer Vision applications. The system employed various Computer Vision applications using blink rate, eye closure, yawning to effectively and quickly identify the drowsiness of a driver during driving the vehicle and alter the driver accordingly. The proposed work tried to contribute in reducing the increased number of road accidents while keeping the methodologies simple and intact.

TITLE 3: Time Domain Parameters as a feature for single channel EEG-based Drowsiness Detection Method AUTHOR: Venkata Phanikrishna B, Suchismitha Chinara YEAR: 2022 Progress in the automobile industry has made life easier for us, and traffic accidents have steadily increased. A large number of vehicle accidents are caused by driver drowsiness while driving. As with many drowsiness detection methods, EEG-based methodology is considered an immediate, efficient, and promising modality. Several feature types have been used in EEG-based drowsiness detection. In this study, we presented a novel feature extraction strategy based on a single Hjorth parameter, and compare its classification capability with the existing Power spectral density (PSD) feature. The results show that the proposed H-parameter features have higher and stronger performance compared to the PSD features of the present work. This field outperforms traditional feature extraction strategies. This is the first study, to the best of our knowledge, to practically apply Hjorth parameters to EEG and its sub-bands for EEG-based driver drowsiness detection.

TITLE 4: Optimization Algorithm for Driver Monitoring System using Deep Learning Approach AUTHOR: Min Woo Yoo, Dong Seog Han YEAR: 2022

The driver monitoring system (DMS), also known as driver attention monitor, plays an important role for vehicle safety systems. In DMS, the system detects the driver's activities such as the state of being a driver sleepy or failure to give sufficient attention to avoid accidents. To reduce the driver mistakes while driving, the system warns the driver with an alarm sound or vibrations. For the efficient implementation of DMS, the system should work in real time without any delay. However, the current DMS has many challenges implementation to the complexity of network implementation. To reduce the DMS complexity for real time implementation, we propose an optimization algorithm, which uses a camera images for monitoring the driver activities. From the input camera images, we extract the driver's state information from the region of interest (ROI). In addition, the proposed system also extracts the driver's head pose and gaze information and monitors the driver states during driving. The experiment results from the proposed methods show accurate driver's state information and warns the driver immediately when any mistake occur from driver side.

TITLE 5: Detecting Driver Sleepiness Using Consumer Wearable Devices in Manual and Partial Automated Real-Road Driving **AUTHOR:** Ke Lu , Johan Karlsson , Anna Sjors Dahlman , Bengt Arne Sjoqvist , and Stefan Candefjord **YEAR:** 2022

Driver sleepiness constitutes a well-known traffic safety risk. With the introduction of automated driving systems, the chance of getting sleepy and even falling asleep at wheel could increase further. Conventional sleepiness detection methods based on driving performance and behavior may not be available under automated driving. Methods based on physiological measurements such as heart rate variability (HRV) becomes a potential solution under automated driving. However, with reduced task load, HRV could potentially be affected by automated driving. Each driver finished four trials with manual and partial automated driving under normal and sleep-deprived condition. Heart rate was monitored by consumer wearable chest bands. Subjective sleepiness based on Karolinska sleepiness scale was reported at five min interval as ground truth. Reduced heart rate and increased overall variability were found in association with severe sleepy episodes. A binary classifier based on the AdaBoost method was developed to classify alert and sleepy episodes. The results indicate that partial automated driving has small impact on the relationship between HRV and sleepiness.

CHAPTER 3

PROPOSED SYSTEM

In the proposed system, we introduce several innovative features to enhance overall functionality and safety. We incorporate a cutting-edge automatic driver behavior monitoring system. Our proposed system also includes a comprehensive driver health monitoring system. As part of our proposed system, we implement a robust location tracking system.

PROPOSED SYSTEM ADVANTAGES

- The automatic driver behavior monitoring system promotes safer driving practices, reducing the risk of accidents.
- With the driver health monitoring system, potential health issues and fatigue can be detected early.

3.1 PROJECT DESCRIPTION

3.1.1 GENERAL

The second key component of our project centers on data analysis and management. To make effective use of the information gathered from various sensors, we've developed a sophisticated software interface that processes and stores the collected data. This data is not only crucial for immediate safety alerts but also for long-term monitoring and analysis. Through this interface, we provide drivers with historical insights into their behavior, allowing them to track improvements in their driving habits. It also aids in generating comprehensive reports for insurance purposes, potentially lowering premiums for responsible drivers. The software component serves as the brain of our system, enhancing driver safety, well-being, and accountability on the road.

3.1.2 PROBLEM DEFINITION

The project's central component, the Arduino Uno microcontroller, forms the core of a comprehensive driver behavior monitoring system with the primary objective of enhancing safety. However, to further enhance this system, a potential improvement could involve the integration of more advanced artificial intelligence algorithms. These AI algorithms could analyze the sensor data in real-time, not only detecting drowsiness or elevated alcohol levels but also predicting potential issues

before they become critical. This predictive capability would provide an even more proactive approach to driver safety, allowing the system to warn the driver or take preventive measures before emergencies occur, ultimately furthering the system's mission to prioritize driver well-being and road safety.




Fig:3.1: Block Diagram

3.1.3 MODULES NAME

- READING THE SENSOR DATA MODULES:
- ALERT THE INFORMATION MODULES:
- CONTROL THE VEHICLES MODULES:

3.1.4 MODULE DESCRIPTION




Fig:3.2: Reading Data Modules

3.1.5 Sensor Modules

Eye Blink Sensor: This sensor tracks the driver's eye movements to detect signs of drowsiness or fatigue. It monitors the driver's blinking patterns and sends data to the central Arduino Uno microcontroller.

Heartbeat Sensor: The heartbeat sensor continuously monitors the driver's heart rate, providing information about their overall health and well-being. This data is also sent to the Arduino Uno.

Gas Sensor (Alcohol Level): The gas sensor is used to detect alcohol levels in the vicinity of the driver. This data helps determine the driver's condition. If elevated alcohol levels are detected, it sends this information to the Arduino Uno.




Fig:3.3: Alert The Information Modules

3.1.6 Message Modules:

GPS Module: In case of any irregularities detected in the sensor data, such as drowsiness or elevated alcohol levels, the GPS module is activated. It precisely locates the vehicle's position and sends this information to the central controller (Arduino Uno).

GSM Module: When the sensor data exceeds predefined thresholds indicating a problem (e.g., drowsiness or high alcohol levels), the GSM module is triggered. It automatically sends an SMS to nearby ambulance or rescue teams to inform them about the driver's condition and vehicle location.

Visual Alerts (Red LED Indicator): The red LED indicator is used to provide immediate visual alerts to the driver. It is activated during emergencies to draw the driver's attention to the situation.




Fig: 3.4: Control The Vehicles Modules

3.1.7 Vehicle Control Modules:

Arduino Uno Microcontroller: The central component of the system, the Arduino Uno, receives and processes data from the sensor modules. It continuously monitors the sensor data for irregularities.

LCD Display: The Arduino Uno controls the LCD display, showing real-time feedback to the driver. It displays current readings of monitored parameters, such as heart rate, alcohol level, and drowsiness. This allows the driver to stay informed about their own condition.

Emergency Response: When the Arduino Uno detects abnormalities in the sensor data that pose a threat to driver safety, it triggers the GPS module to locate the vehicle and activates the GSM module to alert emergency services. Simultaneously, the red LED indicator provides a visual warning to the driver.

3.1.8 WORKING PRINCIPLE:

In this project, we are utilizing an Arduino Uno microcontroller as the central processing unit for our system. This microcontroller serves as the core component of our project, where we aim to develop a driver behavior monitoring system. Our system involves several key sensors and modules to enhance driver safety. **Eye Blink Sensor:** We have integrated an eye blink sensor to monitor the driver's eye movements. It helps detect signs of drowsiness or fatigue, alerting the driver and preventing potential accidents. **Heartbeat Sensor:** A heartbeat sensor is used to continuously monitor the driver's heart rate. This information is crucial in assessing the driver's overall health and well-being during the journey. **Gas Sensor:** To ensure responsible driving, we

have incorporated a gas sensor to detect alcohol levels. This sensor can identify whether the driver has consumed alcohol. In case of any abnormalities detected in the parameters mentioned above, our system employs a GPS module to pinpoint the exact location of the vehicle. GSM Module: To facilitate immediate response in case of emergencies, we have integrated a GSM module. When an abnormality is detected, such as drowsiness or alcohol consumption, the system automatically sends an SMS to nearby ambulance or rescue teams, informing them of the situation. For visual alerts, we've included a red LED indicator. When an emergency is detected, this LED will illuminate, drawing attention to the situation. LCD Display: To provide real-time feedback to the driver, we have incorporated an LCD display. This display will show the current readings of the parameters being monitored, such as heart rate, alcohol level, and drowsiness.

3.2 HARDWARE DESCRIPTION:

3.2.1 ARDUINO MICRO-CONTROLLER:

Arduino is an open-source electronics platform based on easy-to-use hardware and software. Arduino boards are able to read inputs - light on a sensor, a finger on a button, or a Twitter message - and turn it into an output - activating a motor, turning on an LED, publishing something online. You can tell your board what to do by sending a set of instructions to the microcontroller on the board.

Over the years Arduino has been the brain of thousands of projects, from everyday objects to complex scientific instruments. A worldwide community of makers - students, hobbyists, artists, programmers, and professionals - has gathered around this open-source platform, their contributions have added up to an incredible amount of accessible knowledge that can be of great help to novices and experts alike.

Arduino was born at the Ivrea Interaction Design Institute as an easy tool for fast prototyping, aimed at students without a background in electronics and programming. As soon as it reached a wider community, the Arduino board started changing to adapt to new needs and challenges, differentiating its offer from simple 8-bit boards to products for IoT applications, wearable, 3D printing, and embedded environments. All Arduino boards are completely open-source, empowering users to build them independently and eventually adapt them to their particular needs. The software, too, is open-source, and it is growing through the contributions of users worldwide. The UNO is the best board to get started with electronics and coding. If this is your first experience tinkering with the platform, the UNO is

the most robust board you can start playing with. The UNO is the most used and documented board of the whole Arduino family.




Fig:3.5: Arduino Uno

Arduino Uno is a microcontroller board based on the ATmega328P (datasheet). It has 14 digital input/output pins (of which 6 can be used as PWM outputs), 6 analog inputs, a 16 MHz quartz crystal, a USB connection, a power jack, an ICSP header and a reset button. It contains everything needed to support the microcontroller; simply connect it to a computer with a USB cable or power it with a AC-to-DC adapter or battery to get started. You can tinker with your UNO without worrying too much about doing something wrong, worst case scenario you can replace the chip for a few dollars and start over again.

"Uno" means one in Italian and was chosen to mark the release of Arduino Software (IDE) 1.0. The Uno board and version 1.0 of Arduino Software (IDE) were the reference versions of Arduino, now evolved to newer releases. The Uno board is the first in a series of USB Arduino boards, and the reference model for the Arduino platform; for an extensive list of current, past or outdated boards see the Arduino index of boards.

3.2.2 EYE-BLINK SENSOR



Fig:3.6: Eye Blink Sensor

The ever increasing numbers of traffic accidents all over the world are due to diminished driver's vigilance level. Drivers with a diminished vigilance level suffer from a marked decline in their perception; recognition and vehicle control abilities & therefore pose a serious danger to their own lives and the lives of the other people. For this reason, developing systems that actively monitors the driver's level of vigilance and alerting the driver of any insecure driving condition is essential for accident prevention. Many efforts have been reported in the literature for developing an active safety system for reducing the number of automobiles accidents due to reduced vigilance.

3.2.2.1 PRODUCT DESCRIPTION:

Connect regulated DC power supply of 5 Volts. Black wire is Ground, Next middle wire is Brown which is output and Red wire is positive supply. These wires are also marked on PCB. To test sensor you only need power the sensor by connect two wires +5V and GND. You can leave the output wire as it is. When Eye closed, LED is off & the output is at 0V. Put Eye blink sensor glass on the face within 15mm distance, and you can view the LED blinking on each Eye blink. The output is active high for Eye close and can be given directly to microcontroller for interfacing applications.

This Eye Blink sensor is IR based. The Variation Across the eye will vary as per eye blink. If the eye is closed means the output is high otherwise output is low. This to know the eye is closing or opening position.

This output is given to logic circuit to indicate the alarm. This can be used for project involves controlling accident due to unconscious through Eye blink.

3.2.3 HEART BEAT SENSOR




Fig:3.7: Heart Beat Sensor

This project uses bright infrared (IR) LED and a phototransistor to detect the pulse of the finger, a red LED flashes with each pulse. Pulse monitor works as follows: The LED is the light side of the finger, and phototransistor on the other side of the finger, phototransistor used to obtain the flux emitted, when the blood pressure pulse by the finger when the resistance of the photo transistor will be slightly changed. The project's schematic circuit as shown, We chose a very high resistance resistor R1, because most of the light through the finger is absorbed, it is desirable that the phototransistor is sensitive enough. Resistance can be selected by experiment to get the best results. The most important is to keep the shield stray light into the phototransistor. For home lighting that is particularly important because the lights at home mostly based 50HZ or 60HZ fluctuate, so faint heartbeat will add considerable noise.

When running the program the measured values are printed. To get a real heartbeat from this could be challenging. The KY-039 Heartbeat Detector uses a very high resistance resistor R1, because most of the light through the finger is absorbed, it is desirable that the phototransistor is sensitive enough. The most important is to keep the shield stray light into the phototransistor. For home lighting that is particularly important because the lights at home mostly based 50HZ or 60HZ fluctuate, so faint heartbeat will add considerable noise.

3.2.3.1 Features:

This project uses bright infrared (IR) LED and a phototransistor to detect the pulse of the finger, a red LED flashes with each pulse. Pulse monitor works as follows: The LED is the light side of the finger, and phototransistor on the other side of the finger, phototransistor used to obtain the flux emitted, when the blood pressure pulse by the finger when the resistance of the phototransistor will be slightly changed.

Choosing a very high resistance resistor R1, because most of the light through the finger is absorbed, it is desirable phototransistor sensitive enough. Resistance can be selected by experiment to get the best results. The most important is to keep the shield stray light into the phototransistor. For home lighting that is particularly important because the lights at home mostly based 50HZ or 60HZ fluctuate, so faint heartbeat will add considerable noise.

Connecting to Arduino

- Sensor pin S connect to Arduino pin Analog 0 / A0
- Sensor pin + (middle pin) connect to Arduino pin 5V
- Sensor pin - connect to Arduino pin GND

3.2.4 Gas Sensor:



Fig:3.8: Gas Sensor

3.2.4.1 Construction

The sensors contain two in contact with an electrolyte. The electrodes are typically fabricated by fixing a high surface area precious metal on to the porous hydrophobic membrane. The working electrode contacts both the electrolyte and the ambient air to be monitored usually via a porous membrane. The electrolyte most commonly used is a mineral acid the electrodes and housing are usually in a plastic housing which contains a gas entry hole for the gas and electrical contacts.

3.2.4.2 Theory of operation

The gas diffuses into the sensor, through the back of the porous membrane to the working electrode where it is oxidized or reduced. This electrochemical reaction results in an electric current that passes through the external circuit. In addition to measuring, amplifying and performing other signal processing functions, the external circuit maintains the voltage across the sensor between the working and counter electrodes for a two electrode sensor or between the working and reference electrodes for a three electrode cell. At the counter electrode an equal and opposite reaction occurs, such that if the working electrode is an oxidation, then the counter electrode is a reduction

Specification:

Power supply Voltage	: 5 volts
Output voltage Range	: 0-0.9 Volts.
Gain in %	: 3 %

3.2.5 GLOBAL POSITIONING SYSTEM

GPS or Global Positioning System is a satellite navigation system that furnishes location and time information in all climate conditions to the user. GPS is used for navigation in planes, ships, cars and trucks also. The system gives critical abilities to military and civilian users around the globe. GPS provides continuous real time, 3-dimensional positioning, navigation and timing worldwide.

The Global Positioning System (GPS) is a satellite-based navigation system made up of at least 24 satellites. GPS works in any weather conditions, anywhere in the world, 24 hours a day, with no subscription fees or setup charges. The U.S. Department of Defense (USDOD) originally put the satellites into orbit for military use, but they were made available for civilian use in the 1980s.



Fig:3.9: Global Positioning System

3.2.5.1 WORKING OF GPS:

GPS satellites circle the Earth twice a day in a precise orbit. Each satellite transmits a unique signal and orbital parameters that allow GPS devices to decode and compute the precise location of the satellite. GPS receivers use this information and trilateration to calculate a user's exact location. Essentially, the GPS receiver measures the distance to each satellite by the amount of time it takes to receive a transmitted signal. With distance measurements from a few more satellites, the receiver can determine a user's position and display it electronically to measure your running route, map a golf course, find a way home or adventure anywhere.

To calculate your 2-D position (latitude and longitude) and track movement, a GPS receiver must be locked on to the signal of at least 3 satellites. With 4 or more satellites in view, the receiver can determine your 3-D position (latitude, longitude and altitude). Generally, a GPS receiver will track 8 or more satellites, but that depends on the time of day and where you are on the earth. Some devices can do all of that from your wrist.

Once your position has been determined, the GPS unit can calculate other information, such as:

- Speed.
- Bearing.
- Track.
- Trip distance.
- Distance to destination.
- Sunrise and sunset time.

3.2.5.2 GPS SEGMENT:

The GPS system consists of three segments:

- 1) The space segment: the GPS satellites
- 2) The control system, operated by the U.S. military,
- 3) The user segment, which includes both military and civilian users and their GPS equipment.

3.2.5.3 SPACE SEGMENT:

The space segment is the number of satellites in the constellation. It comprises of 29 satellites circling the earth every 12 hours at 12,000 miles in altitude. The function of the space segment is utilized to route/navigation signals and to store and retransmit

the route/navigation message sent by the control segment. These transmissions are controlled by highly stable atomic clocks on the satellites. The GPS Space Segment is formed by a satellite constellation with enough satellites to ensure that the users will have, at least, 4 simultaneous satellites in view from any point at the Earth surface at any time.

3.2.5.4 CONTROL SEGMENT:

The control segment comprises of a master control station and five monitor stations outfitted with atomic clocks that are spread around the globe. The five monitor stations monitor the GPS satellite signals and then send that qualified information to the master control station where abnormalities are revised and sent back to the GPS satellites through ground antennas. Control segment also referred as monitor station.

3.2.5.5 USER SEGMENT:

The user segment comprises of the GPS receiver, which receives the signals from the GPS satellites and determine how far away it is from each satellite. Mainly this segment is used for the U.S military, missile guidance systems, civilian applications for GPS in almost every field. Most of the civilian uses this from survey to transportation to natural resources and from there to agriculture purpose and mapping too.

3.2.5.6 GPS POSITIONING:

The working/operation of Global positioning system is based on the 'trilateration' mathematical principle. The position is determined from the distance measurements to satellites. From the figure, the four satellites are used to determine the position of the receiver on the earth. The target location is confirmed by the 4th satellite. And three satellites are used to trace the location place. A fourth satellite is used to confirm the target location of each of those space vehicles. Global positioning system consists of satellite, control station and monitor station and receiver. The GPS receiver takes the information from the satellite and uses the method of triangulation to determine a user's exact position.

3.2.5.7 USING A GPS RECEIVER:

There are several different models and types of GPS receivers. While working with a GPS receiver it is important to have:

- A compass and a map.

- A downloaded GPS cable.
- Some extra batteries.
- Knowledge about the memory capacity of the GPS receiver to prevent loss of data, decrease in accuracy of data, or other problems.
- An external antenna whenever possible, especially under tree canopy, in canyons, or while driving.
- A set up GPS receiver according to incident or agency standard regulation; coordinate system.
- Notes that describe what you are saving in the receiver.

3.2.5.8 ADVANTAGES OF GPS:

- GPS satellite based navigation system is an important tool for military, civil and commercial users
- Vehicle tracking systems GPS-based navigation systems can provide us with turn by turn directions
- Very high speed

3.3 GSM

A GSM modem is a wireless modem that works with a GSM wireless network. A wireless modem behaves like a dial-up modem. The main difference between them is that a dial-up modem sends and receives data through a fixed telephone line while a wireless modem sends and receives data through radio waves. The working of GSM modem is based on commands, the commands always start with AT (which means ATtention) and finish with a <CR> character. For example, the dialing command is ATD<number>; ATD3314629080; here the dialing command ends with semicolon.

The AT commands are given to the GSM modem with the help of PC or controller. The GSM modem is serially interfaced with the controller with the help of MAX 232. Here max 232 acts as driver which converts TTL levels to the RS 232 levels. For serial interface GSM modem requires the signal based on RS 232 levels. The T1_OUT and R1_IN pin of MAX 232 is connected to the TX and RX pin of GSM modem.



Fig:3.10: Gsm Module




Fig:3.11: System Block Diagram

3.3.1 FUNCTIONAL DESCRIPTION

RF Functionalities:

The RF part of this module converts RF signals to baseband for receiver chain and translates base band signals into RF frequency spectrum.

The operating frequencies are:

Rx (EGSM 850): 869 to 894MHz

Tx (EGSM 850): 824 to 849MHz

Rx (EGSM 900): 925 to 960MHz
 Tx (EGSM 900): 880 to 915MHz
 Rx (DCS 1800): 1805 to 1880MHz
 Tx (DCS 1800): 1710 to 1785MHz
 Rx (PCS 1900): 1930 to 1990MHz
 Tx (PCS 1900): 1850 to 1910MHz

Baseband Functionalities

The baseband part of SM5210 is composed of a SPREADTRUM's SC6600D chip. This chipset is using 0.18µm mixed signal CMOS technology which allows massive integration as well as low power consumption. SC6600D provides single-chip solution to wireless Quad-band telephone handsets and data modems confirming to the EGSM 900, GSM 850, DCS 1800 and PCS 1900.

Memory Functionalities

The memory used in this module is a combination of 32 Megabit (2M x 16-Bit) CMOS 3.0V Volt-only, simultaneous operation flash memory and 4 Megabit (256K x 16-Bit) static RAM.

Power Supply Description

The power supply is one of the key issues in the designing GSM terminals. Due to the 577us radio burst emission in GSM every 4.615ms, power supply must be able to deliver high current peaks in a short time. During these peaks, ripples and drops on the supply voltage must not exceed a certain limit.

TABLE1: VBAT Pin

	PIN NUMBER	VMIN	VMAX	RIPPLE MAX
VBAT (V)	1,3,5,7	3.3V(*)	4.2V(**)	5mVPP for freq<200KHZ

This value has to be guaranteed during the burst (with 2.0A Peak in GSM or GPRS mode)

max operation Voltage Stationary Wave Ratio.

When supplying the module with a battery, the total impedance (battery + protections + PCBS) should be less than 150mOhms.

Table 2: GND Pin Description			
MODE		Pin number	Description
GND		9,11,13,15,17	Ground
		Shielding can install pin(*)	

Table 3: Power consumption in OFF mode			
MODE	Condition	I(Typical)	I(Max)
Off mode	off	50 uA	100uA

PCL: Power control level

PCL5: 2W emission requested (max power)

PCL8: 0.5W emission requested

PCL: Power control level

PCL0: 1W emission requested (max power)

PCL3: 0.25W emission requested

VCC OUTPUT

This output can be used to power some external functions, such as LCD.

SPI INTERFACE

The SPI bus includes a CLK signal, an IO signal, a RS signal and a CS signal complying with the standard SPI bus. These pins can also be used as GPIO.

KEYPAD INTERFACE

This interface provides 10 connections: 4 rows (KBR0 to KBR3) and 6 columns (KBC0 to KBC5).




Fig.3.12: Keypad Connection Sim

General Description

The SIM interface is compatible with the ISO 7816-3 IC card standard required by the GSM 11.11 Phase 2+ standard. The module also supports Release 99 of the SIM Toolkit recommendation and supports a Fixed Dialling Number directory.




Fig.3.13: Sim Card Connection

3.3.2 AUDIO

The module supports the following voice codec:

- Full-Rate
- Enhanced Full Rate

Two different microphone inputs and two different speaker outputs are supported.




Fig:3.14: Audio Frequency Response

3.3.3 Typical Microphone Connection

Two MIC inputs already include the biasing for an electret microphone allowing easy connection to the headset.

The connection can be either differential or single ended; but using a differential connection in order to reject common mode noise TDMA noise is strongly recommended.

The recommended characteristic of capacitors:

C1=22pF to 47pF

C2=C3=C4=47pF to 100pF

L1=L2=100nH

Microphone manufacturer can provide a microphone soldered C1 directly on it, so that C1 can be the nearest to the Microphone.




Fig:3.15: Single-Ended Connection

Do not recommend this connection.

When using a single-ended connection, be sure to have a very good ground plane, a very good filtering as well as shielding in order to avoid any disturbance on the audio path.

The recommended characteristics:

$C1 = 22\text{pF}$ to 47pF

$C2 = C3 = 47\text{pF}$ to 10

$L1 = 100\text{n}$

Microphone manufacturer can provide a microphone soldered C1 directly on it, so that C1 can be the nearest to the Microphone.

3.3.4 Typical Speaker Connection

- Recommended characteristics for the speaker
 - Type: 10 to 100mW, electro-magnetic
 - Impedance: 16 to 150 Ohm
 - Sensitivity: 110dB SPL min. (0dB = 120uPa)
- Frequency response compatible with the GSM specifications.

3.4 MOTOR DRIVER IC:

Common DC gear head motors need current above 250mA. There are many integrated circuits like ATmega16 Microcontroller, 555 timers IC. But, IC 74 series cannot supply this amount of current. When the motor is directly connected to the o/p of the above ICs then, they might damage. To overcome this problem, a motor control circuit is required, which can act as a bridge between the above motors and ICs (integrated circuits). There are various ways of making H-bridge motor control circuit such as using transistor, relays and using L293D/L298.




Fig:3.16: H-Bridge Motor Circuit Using L293d

3.4.1 H-BRIDGE CIRCUIT

An H bridge is an electronic circuit that allows a voltage to be applied across a load in any direction. H-bridge circuits are frequently used in robotics and many other applications to allow DC motors to run forward & backward. These motor control circuits are mostly used in different converters like DC-DC, DC-AC, AC-AC converters and many other types of power electronic converters. In specific, a bipolar stepper motor is always driven by a motor controller having two H-bridges.




Fig:3.17: H-Bridge Circuit

An H-bridge is fabricated with four switches like S1, S2, S3 and S4. When the S1 and S4 switches are closed, then a positive voltage will be applied across the motor. By opening the switches S1 and S4 and closing the switches S2 and S3, this voltage is inverted, allowing invert operation of the motor.

Generally, the H-bridge motor driver circuit is used to reverse the direction of the motor and also to break the motor. When the motor comes to a sudden stop, as the terminals of the motor are shorted. Or let the motor run free to a stop, when the motor is detached from the circuit. The table below gives the different operations with the four switches corresponding to the above circuit.

S1	S2	S3	S4	Operation
1	0	0	1	Motor moves right
0	1	1	0	Motor moves left
0	0	0	0	Motor free runs
0	1	0	1	Motor brakes
1	0	1	0	Motor brakes
1	1	0	0	Short Power Supply
0	0	1	1	Short Power Supply
1	1	1	1	Short Power Supply

Fig:3.18: Operation Of H-Bridge

3.4.2 L293D MOTOR DRIVER IC:

L293D IC is a typical Motor Driver IC which allows the DC motor to drive on any direction. This IC consists of 16-pins which are used to control a set of two DC motors instantaneously in any direction. It means, by using a L293D IC we can control two DC motors. As well, this IC can drive small and quiet big motors.

This L293D IC works on the basic principle of H-bridge, this motor control circuit allows the voltage to be flowing in any direction. As we know that the voltage must be change the direction of being able to rotate the DC motor in both the directions. Hence, H-bridge circuit using L293D ICs are perfect for driving a motor. Single L293D IC consists of two H-bridge circuits inside which can rotate two DC motors separately. Generally, these circuits are used in robotics due to its size for controlling DC motors.

H BRIDGE MOTOR CONTROL CIRCUIT USING L293D IC:

The IC LM293D consists of 4-i/p pins where, pin2 and 7 on the left side of the IC and Pin 10 and 15 on the right side of the IC. Left input pins on the IC will control the rotation of a motor. Here, the motor is connected across side and right i/p for the motor on the right hand side. This motor rotates based on the inputs we provided across the input pins as Logic 0 and Logic 1.




Fig.3.19: H Bridge Circuit

Let's consider when a motor is connected to the o/p pins 3 and 6 on the left side of the IC. For rotating of the motor in clockwise direction, then the input pins have to be provided with Logic 0 and Logic 1.

When Pin-2= logic 1 & pin-7 = logic 0, then it rotates in clockwise direction. Pin-2=logic 0 & Pin7=logic 1, then it rotates in anti-clock direction. Pin-2= logic 0 & Pin7=logic 0, then it is idle (high impedance state). Pin-2= logic 1 & Pin7=logic 1, then it is idle.

In a similar way the motor can also operate across input pin-15 and pin-10 for the motor on the right hand side.

The L293D motor driver IC deals with huge currents, due to this reason, this circuit uses a heat sink to decrease the heat. Therefore, there are 4-ground pins on the L293D IC. When we solder these pins on the PCB (printed circuit board), then we can get a huge metallic area between the ground pins where the heat can be produced.

3.4.3 FEATURES:

- Wide Supply-Voltage Range: 4.5 V to 36 V
- Separate Input-Logic Supply
- Internal ESD Protection
- High-Noise-Immunity Inputs
- Output Current 1 A Per Channel (600 mA for L293D)
- Peak Output Current 2 A Per Channel (1.2 A for L293D)
- Output Clamp Diodes for Inductive Transient Suppression (L293D)

3.4.4 APPLICATIONS:

- Stepper Motor Drives.
- DC Motor Drivers.
- Latching Relay Drivers

3.5 LIQUID CRYSTAL DISPLAY:

LCD screen is an electronic display module and find a wide range of applications. A 16x2 LCD display is very basic module and is very commonly used in various devices and circuits. These modules are preferred over seven segments and other multi segment LEDs. The reasons being: LCDs are economical; easily programmable; have no limitation of displaying special & even custom characters (unlike in seven segments), animations and so on.

A **16x2 LCD** means it can display 16 characters per line and there are 2 such lines. In this LCD each character is displayed in 5x7 pixel matrix. This LCD has two registers, namely, Command and Data. The command register stores the command instructions given to the LCD. A command is an instruction given to LCD to do a predefined task like initializing it, clearing its screen, setting the cursor position, controlling display etc. The data register stores the data to be displayed on the LCD. The data is the ASCII value of the character to be displayed on the LCD. Click to learn more about internal structure of a LCD.

We come across LCD displays everywhere around us. Computers, calculators, television sets, mobile phones, digital watches use some kind of display to display the time. An LCD is an electronic display module which uses liquid crystal to produce a visible image. The 16×2 LCD display is a very basic module commonly used in projects. The 16×2 translates to a display 16 characters per line in 2 such lines. In this LCD each character is displayed in a 5×7 pixel matrix.

3.5.1 RS (REGISTER SELECT)

A 16X2 LCD has two registers, namely, command and data. The register select is used to switch from one register to other. RS=0 for command register, whereas RS=1 for data register.

3.5.2 COMMAND REGISTER

The command register stores the command instructions given to the LCD. A command is an instruction given to LCD to do a predefined task like initializing it, clearing its screen, setting the cursor position, controlling display etc. Processing for commands happens in the command register.

3.5.3 DATA REGISTER

The data register stores the data to be displayed on the LCD. The data is the ASCII value of the character to be displayed on the LCD. When we send data to LCD it goes to the data register and is processed there. When RS=1, data register is selected.

3.5.4 IMPORTANT COMMAND CODES FOR LCD

SR.NO.	HEX CODE	COMMAND TO LCD INSTRUCTION REGISTER
1	01	Clear display screen
2	02	Return home

3	04	Decrement cursor (shift cursor to left)
4	06	Increment cursor (shift cursor to right)
5	05	Shift display right
6	07	Shift display left
7	08	Display off, cursor off
8	0A	Display off, cursor on
9	0C	Display on, cursor off
10	0E	Display on, cursor blinking
11	0F	Display on, cursor blinking
12	10	Shift cursor position to left
13	14	Shift cursor position to right
14	18	Shift the entire display to the left
15	1C	Shift the entire display to the right
16	80	Force cursor to beginning (1st line)
17	C0	Force cursor to beginning (2nd line)
18	38	2 lines and 5×7 matrix


3.5.5 DISPLAYING CUSTOM CHARACTERS ON 16X2 LCD

Generating custom characters on LCD is not very hard. It requires the knowledge about custom generated random access memory (CG-RAM) of LCD and the LCD chip controller. Most LCDs contain Hitachi HD4478 controller. CG-RAM is the main component in making custom characters. It stores the custom characters once declared in the code. CG-RAM size is 64 byte providing the option of creating eight characters at a time. Each character is eight byte in size.

CG-RAM address starts from 0x40 (Hexadecimal) or 64 in decimal. We can generate custom characters at these addresses. Once we generate our characters at these addresses, now we can print them on the LCD at any time by just sending simple commands to the LCD. Character addresses and printing commands are below.

In the table above you can see starting addresses for each character with their printing commands. The first character is generated at address 0x40 to 0x47 and is printed on LCD by just sending simple command 0 to the LCD. The second character is generated at address 0x48 to 0x55 and is printed by sending 1 to LCD.

CG-RAM Characters	CG-RAM Address (Hexadecimal)	Commands to display Generated Characters
1 st Character	0x40	0
2 nd Character	0x48	1
3 rd Character	0x56	2
4 th Character	0x64	3
5 th Character	0x72	4
6 th Character	0x80	5



The Embedded C code written in above block diagram is used for blinking the LED connected with Port0 of microcontroller.


In embedded system programming C code is preferred over other language. Due to the following reasons:

- Easy to understand
- High Reliability
- Portability
- Scalability

3.6 SOFTWARE REQUIREMENTS

3.6.1 EMBEDDED SYSTEM PROGRAMMING:

Let's see the block diagram of Embedded C Programming development:




Function is a collection of statements that is used for performing a specific task and a collection of one or more functions is called a programming language. Every language is consisting of basic elements and grammatical rules. The C language programming is designed for function with variables, character set, data types, keywords, expression and so on are used for writing a C program.

The extension in C language is known as embedded C programming language. As compared to above the embedded programming in C is also have some additional features like data types, keywords and header file etc is represented by `#include<microcontroller name.h>`.

BASIC EMBEDDED C PROGRAMMING STEPS

Let's see the block diagram representation of Embedded C Programming Steps:



The microcontroller programming is different for each type of operating system. Even though there are many operating system are exist such as Windows, Linux, RTOS, etc but RTOS has several advantage for embedded system development.

3.6.2 EMBEDDED SYSTEMS:

Embedded System is a system composed of hardware, application software and real time operating system. It can be small independent system or large combinational system.

Our Embedded System tutorial includes all topics of Embedded System such as characteristics, designing, processors, microcontrollers, tools, addressing modes, assembly language, interrupts, embedded c programming, led blinking, serial communication, lcd programming, keyboard programming, project implementation etc.

SYSTEM:

System is a way of working, organizing or performing one or many tasks according to a fixed set of rules, program or plan.

It is an arrangement in which all the unit combined to perform a work together by following certain set of rules in real time computation. It can also be defined as a way of working, organizing or doing one or many tasks according to a fixed plan.

An Embedded System is a system that has software embedded into computer-hardware, which makes a system dedicated for a variety of application or specific part of an application or product or part of a larger system.

An embedded system can be a small independent system or a large combinational system. It is a microcontroller-based control system used to perform a specific task of operation.

An embedded system is a combination of three major components:

- **Hardware:** Hardware is physically used component that is physically connected with an embedded system. It comprises of microcontroller based integrated circuit, power supply, LCD display etc.
- **Application software:** Application software allows the user to perform varieties of application to be run on an embedded system by changing the code installed in an embedded system.
- **Real Time Operating system (RTOS):** RTOS supervises the way an embedded system work. It act as an interface between hardware and application software which supervises the application software and provide mechanism to let the processor run on the basis of scheduling for controlling the effect of latencies.




Fig:3.20: Rtos

3.6.3 CHARACTERISTICS OF EMBEDDED SYSTEM:

An embedded system is software embedded into computer hardware that makes a applications. Embedded system generally used for do specific task that provide real-time output on the basis of various characteristics of an embedded system.

Embedded system may contain a smaller part within a larger device that used for serving the more specific application to perform variety of task using hardware-software intermixing configuration.

It provides high reliability and real-time computation ability.

3.6.3.1 Advantages:

- Same hardware can be used in variety of application.
- Lesser power requirement
- Lower operational cost of system
- Provide high performance and efficiency

3.6.3.2 Disadvantages:

- Developing a system required more time. Due to functional complexity.
- Skilled engineers required because one mistake may result in destroying of complete project.

Let's see the block diagram shows the basic structure of an embedded system.




Fig:3.21: Structure Of Embedded System

Sensor Sensor used for sensing the change in environment condition and it generate the electric signal on the basis of change in environment condition. Therefore it is also called as transducers for providing electric input signal on the basis of change in environment condition. **A-D Converter:** An analog-to-digital converter is a device that converts analog electric input signal into its equivalent digital signal for further processing in an embedded system. **Processor & ASICs:** Processor used for processing the signal and data to execute desired set of instructions with high-speed of operation. Application specific integrated circuit (ASIC) is an integrated circuit designed to perform task specific operation inside an embedded system.

D-A Converter: A digital-to-analog converter is a device that converts digital electric input signal into its equivalent analog signal for further processing in an embedded system.

Actuators: Actuators is a comparator used for comparing the analog input signal level to desired output signal level for providing the error free output from the system.

3.7 DESIGN STEPS REQUIRED FOR THE DEVELOPMENT OF EMBEDDED SYSTEM:

Designing steps required for embedded system are different from the design process of another electronic system.

Let's see a flow chart represent the design steps required in the development of an embedded system:




Fig:3.22: Embedded System Tools And Peripherals

Compiler:

Compiler is used for converting the source code from a high-level programming language to a low-level programming language. It converts the code written in high level programming language into assembly or machine code. The main reason for conversion is to develop an executable program.

Let's see the operations performed by compiler are:

- Code generation
- Code optimization
- Parsing
- Syntax direct translation
- Preprocessing

Cross-Compiler

If a program compiled is run on a computer having different operating system and hardware configuration than the computer system on which a compiler compiled the program, that compiler is known as cross-compiler.

Decompiler

A tool used for translating a program from a low-level language to high-level language is called a decompiler. It is used for conversion of assembly or machine code to high-level programming language.

Assembler:

Assembler is embedded system tool used for translating a computer instruction written in assembly language into a pattern of bits which is used by the computer processor for performing its basic operations. Assembler creates an object code by translating assembly language instruction into set of mnemonics for representing each low-level machine operation.

DEBUGGING TOOLS IN AN EMBEDDED SYSTEM:

Debugging is a tool used for reducing the number of error or bugs inside a computer program or an assembled electronic hardware.

Debugging of a compact subsystem is difficult because a small change in one subsystem can create bugs in another system. The debugging used inside embedded system differs in terms of their development time and debugging features.

Let's see the different debugging tools used in embedded system are:

Simulators:

Simulator is a tool used for simulation of an embedded system. Code tested for microcontroller unit by simulating code on the host computer. Simulator is used for model the behavior of the complete microcontroller in software.

Functions of simulators

Let's see the functions performed by simulator are:

- It defines the processing or processor device family with various version of target system.
- It monitors the detailed information of a source code and symbolic arguments as the execution goes for each single step of operation.
- It simulates the ports of target system for each single step of execution.
- It provides the working status of RAM.
- It monitors the response of system and determines the throughput.
- It provides the complete meaning of the present command.
- It monitors the detailed information of the simulator commands entered from the keyboard or selected from the menu.
- It facilitates synchronization of internal peripherals and delays.

CHAPTER: 4

EXPERIMENTAL AND METHODS

Designing a comprehensive driver monitoring system for safety and emergency response involves a multidisciplinary approach. Here's an overview of the experimental methods and components:

Sensor Suite Integration:

Camera-based Vision System: Install cameras to monitor the driver's face, eye movements, and head position. Utilize computer vision algorithms to analyze facial expressions, detect drowsiness, and monitor alertness. **Biometric Sensors:** Integrate sensors like heart rate monitors or electrodermal activity sensors to measure physiological parameters indicative of stress or fatigue.

Inertial Measurement Unit (IMU): Use IMUs containing accelerometers and gyroscopes to monitor vehicle dynamics and driver behavior, including sudden movements, aggressive driving, or erratic behavior.

Environmental Sensors: Incorporate sensors to detect environmental factors such as ambient light levels, temperature, and humidity, which can affect driver alertness.

Data Fusion and Processing:

Develop algorithms to fuse data from multiple sensors to provide a holistic understanding of the driver's state and the surrounding environment. Implement signal processing techniques to filter noise, extract relevant features, and detect patterns indicative of safety risks or emergencies. Utilize embedded C programming for real-time processing to ensure timely responses to detected events.

Behavioral Analysis and Risk Detection:

Use machine learning and pattern recognition algorithms to analyze driver behavior and detect potential risks, including drowsiness, distraction, impaired driving,




Fig :4.1: Prototype Of Project

4.1 FUTURE ENHANCEMENT

In future enhancements of this driver behavior monitoring system, we envision the integration of advanced artificial intelligence algorithms and machine learning models to further enhance its capabilities. These technologies could enable the system to provide more nuanced and predictive insights into driver behavior, such as identifying specific signs of distraction, impairment, or stress. Additionally, the system could evolve to incorporate additional sensors, such as cameras for facial recognition and gesture detection, enabling it to detect and respond to a wider range of potential safety risks. Furthermore, connectivity with vehicle control systems could allow for semi-autonomous interventions in critical situations, such as applying emergency brakes or steering correction. The system might also support seamless integration with emerging vehicle-to-vehicle (V2V) and vehicle-to-infrastructure (V2I) communication standards for improved situational awareness. These advancements would not only further enhance driver safety but also contribute to the development of more autonomous and safer transportation systems.

4.1.1 ADVANTAGES:

- The automatic driver behavior monitoring system promotes safer driving practices, reducing the risk of accidents.
- With the driver health monitoring system, potential health issues and fatigue can be detected early.

4.2 STANDARDS

- There might not be a specific IEEE standard solely dedicated to comprehensive driver monitoring for safety and emergency response. However, several IEEE standards and guidelines cover related aspects of this field. Here are some IEEE standards and guidelines that could be relevant:

- IEEE 802.11: This standard covers wireless LAN technology and could be relevant for communication protocols between the monitoring system in the vehicle and external systems, such as emergency response centers.
- IEEE 802.15: This family of standards covers wireless personal area networks (WPANs), which could be utilized for communication between different components within the vehicle monitoring system.

4.3 CONSTRAINTS

- Implementing a comprehensive driver monitoring system for safety and emergency response comes with various constraints, including:
- Cost: The integration of advanced sensors, communication systems, and processing units can be expensive. Balancing the cost of implementation against the benefits of improved safety and emergency response is a significant constraint.
- Technological Limitations Existing technologies may have limitations in terms of accuracy, reliability, and compatibility. For instance, certain environmental conditions like extreme weather or poor lighting can affect the performance of sensors and cameras.
- Regulatory Compliance Compliance with relevant regulations and standards, such as privacy laws and automotive safety regulations, is crucial but can also pose constraints in terms of system design and functionality.
- Data Privacy and Security: Collecting and storing sensitive data about drivers' behavior and biometric information raises privacy concerns. Ensuring robust data encryption, access control, and compliance with privacy regulations is essential but can add complexity to the system.
- Integration Challenges: Integrating various sensors, communication systems, and processing units into a seamless and cohesive system can be challenging, particularly when dealing with different hardware and software components from multiple vendors.

- **User Acceptance and Adoption:** Drivers may be resistant to the idea of constant monitoring or feel uncomfortable with the level of intrusion into their privacy. Educating users about the benefits of the system and addressing their concerns is critical for widespread acceptance and adoption.

4.3 TRADE OFF

Implementing a comprehensive driver monitoring system for safety and emergency response involves various trade-offs, including Privacy vs. Safety: There's a trade-off between the level of privacy drivers expect and the degree of monitoring required for ensuring safety. Striking a balance between respecting privacy rights and enhancing safety through comprehensive monitoring is crucial.

Cost vs. Effectiveness: Investing in advanced sensors, communication systems, and processing units can significantly improve the effectiveness of the monitoring system but also increase costs. Balancing the cost of implementation against the potential benefits in terms of improved safety and emergency response is essential. **Real-Time Monitoring vs. Data Storage** Continuous real-time monitoring allows for immediate detection of safety hazards and emergencies but requires substantial computing power and storage capacity. Trade-offs must be made regarding the duration and granularity of data storage to manage costs effectively.

CHAPTER 5

RESULTS AND DISCUSSIONS

5.1 RESULTS

Comprehensive driver monitoring for safety and emergency response typically involves several key components and metrics. Here are some potential results and findings that such monitoring systems might yield:

Driving Behavior Analysis: Monitoring systems can provide detailed insights into driver behavior, including speeding, aggressive driving, sudden acceleration or deceleration, abrupt lane changes, and erratic maneuvers. These behaviors can be analyzed to identify patterns and potential risks.

Real-time Alerts and Warnings: Monitoring systems can issue real-time alerts to drivers and fleet managers when potentially dangerous situations arise, such as sudden lane departures, following too closely, or exceeding speed limits. Results might include the number of alerts triggered and their effectiveness in mitigating risks.

Emergency Response Integration: Comprehensive monitoring systems can integrate with emergency response services to provide immediate assistance in the event of an accident or emergency. Results could include response times, effectiveness of communication protocols, and outcomes in terms of injury prevention and vehicle recovery.



Fig:5.1: Output of Alcohol Consumption

Alcohol Detection: The system may include sensors capable of detecting alcohol in the driver's breath or within the vehicle cabin. This detection can be done using technologies such as breathalyzers or sensors that measure alcohol vapor concentration.

Alcohol detection in an LCD (Liquid Crystal Display) display typically involves integrating alcohol sensors with the display unit to provide real-time feedback to the driver regarding their alcohol consumption level. Here's how it might work:




Fig:5.2: Output Of Message

5.2 DISCUSSIONS

Comprehensive driver monitoring for safety and emergency response is a critical area of research and development in the automotive industry, with the potential to significantly enhance road safety and reduce the severity of accidents. Here are some key points to consider when discussing this topic Importance of Driver Monitoring: Emphasize the importance of monitoring the driver's behavior and physiological state as a crucial aspect of overall vehicle safety. The driver is the most critical factor in the driving process, and their condition greatly influences accident risk.

Technological Advancements: Highlight the advancements in sensor technology, data processing algorithms, and embedded systems that enable comprehensive driver monitoring. These advancements make it possible to capture, analyze, and respond to various aspects of driver behavior in real time.

Safety Benefits: Discuss the safety benefits of driver monitoring systems, such as early detection of drowsiness, distraction, and impairment. By alerting drivers or triggering emergency interventions when necessary, these systems can help prevent accidents or mitigate their severity.

Emergency Response: Explore how driver monitoring systems can contribute to emergency response efforts. For instance, systems capable of detecting sudden medical emergencies or impending collisions can automatically alert emergency services and provide crucial information about the driver's condition and location.

Challenges and Limitations: Acknowledge the challenges and limitations associated with driver monitoring systems, such as ensuring accuracy and reliability, addressing privacy concerns, and minimizing false alarms. Additionally, discuss the need for robust validation and testing procedures to ensure the effectiveness of these systems in real-world scenarios.

CHAPTER 6

CONCLUSION

In conclusion, we presented an auditable self-sovereign identity system (named AudiSSI), which allows the user to self-manage their identities without sacrificing the user's privacy and provides an efficient way for the SPs to check its registered drivers' qualifications. Further, we proposed a safety guarantee insurance in the form of driver's qualification auditing contract to enable the RHS rider to check his driver's qualifications before the trip starts and get incentives once a disqualified driver is detected. We described the workflow

a driver registers as a qualified driver in the SP and how an insured rider automates the audit of a registered driver. We designed an incentive mechanism and provided a game-theoretical analysis. Finally, we implemented a prototype of AudiSSI and deployed it on Hyperledger Indy and Fabric to show that self-sovereign identity system for RHS driver with qualification auditing is efficient and technically feasible. Our work does not stop all malicious entities, but the deterrence of the incentive mechanism will mitigate this problem and it will contribute to significant huge cost-saving for the corresponding SP in investigating the disqualified drivers.

Through detailed analysis of driving behaviors, monitoring systems enable proactive interventions such as targeted training programs and compliance monitoring, ensuring that drivers remain aware of safety protocols and regulatory requirements. Moreover, the integration of emergency response capabilities enhances the efficiency of rescue operations in critical situations, reducing response times and improving outcomes for those involved in accidents.

Ultimately, comprehensive driver monitoring for safety and emergency response represents a proactive approach to road safety, fostering a culture of accountability, continuous improvement, and swift intervention when needed. By harnessing the power of data and technology, these systems empower drivers, fleet managers, and emergency

responders to collaborate effectively in safeguarding lives and minimizing the impact of unforeseen events on our roadways

REFERENCES

- [1] Globaltimes.cn, "Didi offers 1m yuan to find passenger's killer - Global times," Accessed Sep. 22, 2020.
- [2] Techcrunch.com, "Techcrunch is now a part of Verizon media," Accessed: Sep. 22, 2020.
- [3] Uber driver accused of trying to by kidnap passenger. Accessed: Mar. 22, 2021.
- [4] S.~a Alboaie and D. Cosovan, "Private data system enabling self-sovereign storage managed by executable choreographies," in Proc. Distrib. Appl. Interoperable Syst., 2017, pp. 83–98.
- [5] P. Aublin, S. B. Mokhtar, and V. Qu 'ema. "RBFT: Redundant byzantine fault tolerance," in Proc. IEEE 33rd Int. Conf. Distrib. Comput. Syst., 2013, 297–306.
- [6] J. Camenisch, M. Kohlweiss, and C. Soriente, "An accumulator based on bilinear maps and efficient revocation for anonymous credentials," in Proc. Int. Workshop Public Key Cryptogr., 2009, pp. 481–500.
- [7] J. Camenisch and A. Lysyanskaya, "A signature scheme with efficient protocols," in Proc. Secur. Commun. Netw., 2003, 268–289.
- [8] J. Camenisch and E. Van Herreweghen, "Design and implementation of the remix anonymous credential system," in Proc. 9th ACM Conf. Comput. Commun. Secur., 2002, 21–30
- [9] M. Castro, B. Liskov et al., "Practical byzantine fault tolerance," in Proc. 3rd Symp. Operating Syst. Des. Implementation, 1999, pp. 173– 186.
- [10] CI, "Hyperledger caliper," Accessed: Sep. 30, 2019.
- [11] DiDi, "Didi Chuxing," Accessed: Jun. 5, 2019.
- [12] Lyft, "Drive with Lyft California," Accessed: Apr. 5, 2021.
- [13] Wear, B., "How driver CHECKS work: What Uber and LYFT do, what city would require," Accessed: Apr. 30, 2021.
- [14] DiDi, "Brain intelligent driving smart transportation AI labs." Accessed: Aug. 15, 2020.

- [15] P. Dunphy and F. A. P. Petitcolas, "A first look at identity management schemes on the blockchain," *IEEE Secur. Privacy*, vol. 16, no. 4, pp. 20–29, Jul./Aug. 2018.