

IMPLEMENTATION OF NANO BUBBLED TECHNOLOGY FOR SOLAR WATER HEATING APPLICATION

Submitted in partial fulfilment of the requirements for the award of

Bachelor of Engineering degree in
Mechanical Engineering

By

G.S. PRAVEEN KUMAR (Reg. No. 40150704)

V.S.SUDHARSANAN (Reg. No. 40150709)



DEPARTMENT OF MECHANICAL ENGINEERING

SCHOOL OF MECHANICAL ENGINEERING

SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY

(DEEMED TO BE UNIVERSITY)

Accredited with grade "A++" by NAAC

JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI – 6001190

APRIL - 2024



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY

(DEEMED TO BE UNIVERSITY)

Accredited "A++" Grade by NAAC | 12B Status by UGC | Approved by AICTE

www.sathyabama.ac.in


DEPARTMENT OF MECHANICAL ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of G.S. PRAVEEN KUMAR (Reg. No. 40150704) and V.S. SUDHARSANAN (Reg. No. 40150709) who carried out the project entitled "IMPLEMENTATION OF NANO BUBBLED TECHNOLOGY FOR SOLAR WATER HEATING APPLICATION" under our supervision from December 2023 to April 2024.


Internal Guide

Dr.G. SENTHIL KUMAR, M.E., Ph.D.


Head of the Department
Dr. GANESAN S., M.E., Ph.D.,


Submitted for Viva voce Examination held on 06/04/2024



Internal Examiner


External Examiner

DECLARATION

We, G.S. PRAVEEN KUMAR (Reg. No. 40150704) and V.S. SUDHARSANAN (Reg.no 40150709) hereby declare that the Project Report entitled "IMPLEMENTATION OF NANO BUBBLED TECHNOLOGY FOR SOLAR WATER HEATING APPLICATION" done by us under the guidance of Dr.G.SENTHIL KUMAR, M.E., Ph.D.is submitted in partial fulfilment of the requirements for the award of Bachelor of Engineering degree in Mechanical Engineering.

1. 

2. 

DATE: 01/04/2024

SIGNATURE OF THE CANDIDATES

PLACE: CHENNAI

ACKNOWLEDGEMENT

We are pleased to acknowledge our sincere thanks to Board of Management of **SATHYABAMA** for their kind encouragement in doing this project and for completing it successfully. We are grateful to them.

We convey our sincere thanks to **Dr. S. GANESAN., M.E., Ph.D.**, Head of the Department, Department of Mechanical Engineering for providing us necessary support and details at the right time during the progressive reviews.

We would like to express our sincere and deep sense of gratitude to our Project Guide **Dr.G. SENTHIL KUMAR, M.E., Ph.D.** for his valuable guidance, suggestions, and constant encouragement paved way for the successful completion of our project work.

We also express our thanks to all Teaching and Non-teaching staff members of the Department of Mechanical Engineering who were helpful in many ways for the completion of the project.

ABSTRACT

The integration of Nano Bubbled Technology (NBT) in solar water heating systems represents a promising avenue for enhancing energy efficiency and performance. This abstract encapsulates the key aspects of implementing NBT in such systems, highlighting its potential benefits and implications.

Nano Bubbled Technology introduces nanometer-sized bubbles into water, significantly increasing its heat absorption capacity and thermal conductivity. By infusing these tiny bubbles into the water circulated within solar collectors, the system can operate more efficiently, even under varying weather conditions.

This abstract explores the fundamental principles of NBT and its compatibility with solar water heating applications. It delves into the mechanisms through which nanobubbles enhance heat transfer efficiency, ultimately leading to improved performance and energy savings.

Furthermore, the abstract discusses the practical aspects of implementing NBT in solar water heating systems, including the design considerations, installation procedures, and potential challenges. It also addresses the economic viability of adopting NBT, considering factors such as initial investment costs and long-term operational benefits.

The abstract concludes by emphasizing the significance of integrating NBT into solar water heating technologies to achieve sustainable and cost-effective solutions for meeting the rising demand for clean energy and efficient water heating systems.

TABLE OF CONTENTS

CHAPTER No.	TITLE	PAGE No.
	ABSTRACT	v
	LIST OF TABLES	vi
	LIST OF FIGURES	vii
1	INTRODUCTION	1
	1.1 IMPROVED ENERGY EFFICIENCY	3
	1.2 INCREASED RELIABILITY	3
	1.3 ENVIRONMENTAL SUSTAINABILITY	3
	1.4 COST SAVINGS	3
	1.5 ENVIRONMENTAL IMPLICATION	3
	1.6 ANALYSIS ON LOSSY MIE RESONANCES	6
	1.7 MATERIALS AND METHODS	11
	1.8 MAINTANACE AND MONITORING	20
2	LITERATURE SURVEY	24
3	PROJECT ANALYSIS	28
	3.1 OBJECTIVE	28
	3.2 SCOPE OF THE PROJECT	28
4	PROPOSED METHODOLOGY	30
	4.1 INTEGRATION OF NANO BUBBLED TECHNOLOGY	30
	4.2 MATERIALS AND METHODS	30
	4.3 EXPERIMENTAL DATA	31
	4.4 MAINTANACE AND MONITORING	31
	4.5 ADVANTAGES	31
5	RESULT AND DISCUSSION	41
6	CONCLUSION	52
	REFERENCES	54

LIST OF FIGURES

FIGUR E NO.	TITLE	PAGE NO.
1.1	Absorption efficiencies of silicon nano spheres in water having different radius.	8
1.2	(a) Bright field TEM image of the silicon nanoparticles. (b) Power XRD pattern of the silicon nanoparticles. (c) Extinction spectrum of the 0.001 vol% silicon nanoparticles in water in a 1-cm thick cell. (d) Photograph of silicon nano fluid at 0.001 vol%.	17
4.1	Scattering efficiencies (Q_{scat}) of silicon nano sphere in water having different radius.	33
4.2	Complex refractive index of silicon	34
4.3	Size distribution of the silicon nano particles measured from the TEM	35
4.4	Histogram of the silicon nanoparticles diameter in water by DLS Measurement	35
4.5	Dark field microscope image of the silicon nanoparticles on a cover glass	36
4.6	Selected spectra of the backward scattering from the silicon nanoparticles on a cover glass	37
4.7	Photograph of the measurement setup when the solar simulator is on.	38

4.8	Experimental setup	39
4.9	Schematic of cross section	39
4.10	Efficiency of silicon	39
5.1	a) Vaporized weight [mg] , (b) Temperature changes [deg], (c) Schematic lens and solar simulator	42
5.2	DO Variation un distilled water	44
5.3	Solar Water Heating with Distilled Water	46
5.4	DO Variation with nano bubbled water	47
5.5	Solar Water Heating with nano bubbled water	48
5.6	Nano bubble Generating Process	49
5.7	Nano bubble Generating Process	50
5.8	Solar Water Heating Efficiency with Nano Bubbled Technology	51

CHAPTER 1

INTRODUCTION

The rising concerns surrounding energy conservation and sustainability have spurred the development of innovative technologies across various sectors, including solar water heating. Among these advancements, the integration of nano-bubbled technology stands out as a groundbreaking solution. Nano-bubbled technology offers unique properties that hold the promise of significantly enhancing the efficiency and performance of solar water heating systems.

This paper endeavors to provide a comprehensive overview of implementing nano-bubbled technology for solar water heating applications. It will delve into the fundamental principles of solar water heating, introduce the concept of nano-bubbled technology, elucidate its potential benefits, and scrutinize its impact on energy efficiency and environmental sustainability. Through this exploration, it will become apparent that nano-bubbled technology harbors the potential to revolutionize the solar water heating industry and pave the way towards a more sustainable and energy-efficient future.

Solar water heating systems typically comprise several components, including solar collectors, heat exchangers, storage tanks, and control systems. The core of these systems lies in the solar collectors, which are responsible for capturing and converting solar energy into heat. There exist two primary types of solar collectors: flat-plate collectors and concentrating collectors.

Flat-plate collectors, being the most prevalent, feature a dark-colored, heat-absorbing surface enclosed by glass or plastic. When exposed to sunlight, this surface heats up, and a heat transfer fluid, usually water or antifreeze, circulates through the collector, gathering the heat. On the other hand, concentrating collectors utilize mirrors or lenses to concentrate sunlight onto a smaller heat-absorbing area, resulting in higher temperatures and increased efficiency.

Solar water heating, while environmentally friendly, faces challenges due to the intermittent nature of sunlight. Solar collectors operate only during daylight hours and are less efficient on cloudy days. Over time, scale and biofouling accumulate on heat-

absorbing surfaces, diminishing system efficiency. Scale buildup impedes heat transfer, reducing overall effectiveness. Furthermore, effective transfer of heat absorbed by the collector to the storage tank water is essential, but this process can incur energy losses. These challenges highlight the need for innovations in solar water heating technology to overcome limitations and enhance system performance. Strategies to mitigate scale and biofouling buildup, improve heat transfer efficiency, and optimize energy transfer processes are crucial for maximizing the benefits of solar water heating systems.

Addressing these challenges can increase the reliability and sustainability of solar water heating, making it a more viable option for residential and commercial applications. Research and development efforts focusing on improving system design, materials, and maintenance practices are essential for overcoming these hurdles and advancing the adoption of solar water heating technologies. Through innovation and continuous improvement, solar water heating can become a more robust and dependable renewable energy solution, contributing to reducing reliance on fossil fuels and mitigating environmental impacts associated with traditional water heating methods. Nano-bubbled technology is a relatively new and promising innovation that has the potential to address the challenges associated with solar water heating. Nanobubbles, as the name suggests, are tiny gas bubbles with diameters on the nanometer scale, typically less than 100 nanometers. These nano-bubbles possess unique properties that make them an ideal candidate for improving the performance of solar water heating systems.

Nano-bubbles exhibit several properties that set them apart from conventional gas bubbles:

- a. Longevity: Nano-bubbles have an extraordinary lifespan, remaining stable in liquids for extended periods. This characteristic allows them to persist within the solar collector and maintain their effect on heat transfer.
- b. Enhanced Heat Transfer: Nano-bubbles have a high surface area, which enhances their ability to transfer heat. As a result, they can facilitate more efficient heat absorption and transfer within the solar collector.
- c. Scale and Biofouling Mitigation: Nano-bubbles can inhibit the accumulation of scale and biofouling on the collector's surface. The gas-water interface created by these nano-bubbles prevents the adhesion of minerals and biological organisms.

d. **Increased Heat Absorption:** The presence of nano-bubbles can increase the absorption of solar energy by the collector. This is due to the scattering and trapping of sunlight within the water, thereby increasing the overall heat gain.

e. **Potential Benefits of Nano-Bubbled Technology:** The integration of nano-bubbled technology into solar water heating systems offers numerous potential benefits, including:

1.1. IMPROVED ENERGY EFFICIENCY:

By enhancing heat transfer and inhibiting scale and biofouling, nano-bubbles can significantly improve the energy efficiency of solar collectors. This results in a higher proportion of solar energy being effectively utilized for water heating, reducing the dependence on auxiliary heating sources.

1.2. INCREASED RELIABILITY:

The longevity of nano-bubbles ensures that the solar collector's performance remains consistent over time. With reduced scale and biofouling, maintenance requirements are also minimized, making the system more reliable and cost-effective.

1.3. ENVIRONMENTAL SUSTAINABILITY:

Solar water heating systems equipped with nano-bubbled technology can contribute to a more sustainable future. By reducing the need for fossil fuels and minimizing environmental impact, these systems align with global efforts to combat climate change and reduce carbon emissions.

1.4. COST SAVINGS:

Improved energy efficiency and reduced maintenance requirements translate to lower operational costs. The initial investment in nano-bubbled technology can be offset by long-term savings on energy bills and maintenance expenses.

1.5. ENVIRONMENTAL IMPLICATION:

The implementation of nano-bubbled technology for solar water heating aligns with broader environmental goals. By reducing the reliance on fossil fuels, this innovation can contribute to a significant reduction in greenhouse gas emissions. Furthermore, the

prevention of scale and biofouling reduces the need for chemical treatments, which can be harmful to aquatic ecosystems.

Utilizing solar energy for sustainable development extends beyond photovoltaics, as sunlight's heat can be harnessed as a clean energy source. Comparable to how black paper heats up in sunlight, solar thermal energy holds significant potential for human use. A prominent application of this is the solar water heater, commonly positioned atop roofs to capture solar energy for heating water. To facilitate this conversion process from solar to thermal energy, sunlight absorbers like tubes or panels are integrated into the system. Presently, there's an unprecedented global urgency in finding viable and sustainable energy solutions. This urgency underscores the imperative for embracing technologies like solar water heating, which capitalize on readily available and renewable energy sources.

Solar water heaters exemplify a practical and environmentally sound approach to meeting energy needs, particularly in regions with abundant sunlight. As societies strive for sustainability, embracing solar thermal technologies presents a tangible step towards reducing reliance on fossil fuels and mitigating environmental impacts. Transitioning to solar water heating systems not only promotes energy independence but also contributes to reducing carbon emissions and combating climate change. In this pursuit of sustainability, innovation in solar thermal technology plays a pivotal role, offering solutions that align with broader environmental and socio-economic goals. Therefore, integrating solar water heaters into mainstream energy infrastructure represents a critical step towards achieving a more sustainable future. Emphasizing the importance of solar thermal energy underscores the multifaceted benefits it offers, ranging from economic savings to environmental conservation. As research and development in solar technology advance, the efficiency and affordability of solar water heating systems are expected to improve further. With concerted efforts, solar thermal technologies can play a transformative role in shaping a cleaner, more sustainable energy landscape.

As the world grapples with the challenges posed by climate change, the need to transition towards renewable and clean energy sources is paramount. Solar energy, in

particular, holds immense promise as a renewable resource that can significantly reduce carbon emissions and provide a sustainable energy future.

Solar water heating systems are vital for utilizing solar energy in residential, commercial, and industrial contexts. While traditional systems are effective, there's a push to boost their efficiency. Integrating nano bubbled technology presents a promising solution. Nano bubbles, extremely small gas bubbles, have garnered attention for their unique properties. In solar water heating, this technology holds potential for enhancing heat transfer, improving energy capture, and ensuring system reliability. By introducing nano bubbles into the system, it's possible to optimize performance and efficiency. These bubbles, typically under 100 nanometers in diameter, offer advantages across various industries. In the context of solar water heating, their incorporation aims to overcome existing limitations and elevate system functionality. The integration of nano bubbled technology represents a step forward in the quest for sustainable and efficient energy solutions. Through this innovation, solar water heating systems can contribute more effectively to reducing reliance on traditional energy sources. Research and development in this area continue to explore ways to maximize the benefits of nano bubbled technology in solar applications. With ongoing advancements, the potential for improving solar water heating systems is significant. By harnessing the unique properties of nano bubbles, these systems can evolve to meet the ever-growing demand for renewable energy solutions.

This comprehensive study delves into the integration of nano bubbled technology into solar water heating systems, exploring the principles behind nano bubbles, their advantages and challenges, their potential impact on solar water heating performance, and the practical considerations for implementing this innovative technology.

The aim is to provide a holistic understanding of the role of nano bubbles in solar water heating applications and to shed light on their feasibility, benefits, and future prospects in the renewable energy landscape. Heat localization around the nanoparticles as a result of intensity. A few examples of the uses for this type of plasmonic heating include photothermal imaging, optofluidic, photothermal treatment, the production of nanobubbles, and nano chemistry. Recently, plasmonic nanoparticles in nanofluid

applications have also been studied. Mie resonances can be excited at silicon nanoparticles in those wavelength ranges because silicon has a refractive index that is more than 3.5 from the UV to near infrared (NIR) regimes.

It should be noted that due to interbond transitions, silicon is absorbent below around 1100 nm. Therefore, it is anticipated that silicon nanoparticle resonances below this wavelength area will increase the photothermal conversion with Mie resonances, much as was the case with plasmonic nanoparticles.

Theoretically and experimentally, we show that silicon nanoparticles efficiently absorb huge amounts of light energy and heat the water around them. This is because Mie resonances experience loss when they are excited. Aside from that, silicon nanoparticles of various sizes have resonance wavelengths that span the majority of the solar spectrum from UV to NIR.

Our research shown that silicon nanoparticles can be heated effectively by solar radiation and that the rate of water evaporation quickly doubled compared to pure water. Given that silicon is one of the most prevalent materials on Earth and that the volume fraction of nanoparticles in this nanofluid may be low, silicon is an excellent material for nanofluid and may be employed in upcoming large-scale solar-thermal applications.

1.6. ANALYSIS ON LOSSY MIE RESONANCES:

Analyzing resonant modes on silicon nanospheres involves employing Mie theory to explore their optical properties. Initially, the study references the complex permittivity of silicon and sets the refractive index of water as a constant for calculations. Figure 1 depicts silicon nanospheres with radii ranging from 30 nm to 110 nm, alongside their corresponding absorption efficiencies (Q_{abs}). This investigation delves into the resonant behaviors of these nanospheres, shedding light on their interaction with light and absorption characteristics. Insights gained through the Mie theory deepen understanding of how silicon nanospheres interact with light, offering potential applications in photonics and optoelectronics.

The analysis contributes to nanotechnology by providing insights into controlling nanomaterials' optical responses, crucial for designing advanced photonic devices and

sensors. By elucidating resonant modes and absorption efficiencies, the study aids in optimizing silicon nanospheres' performance for various applications. This ranges from light harvesting in solar cells to enhancing biosensor sensitivity. The findings highlight the significance of theoretical frameworks like the Mie theory in predicting and interpreting nanostructures' optical behaviors. This guidance directs experimental efforts towards harnessing the full potential of nanomaterials in practical applications.

The absorption efficiency of silicon nanospheres exhibits distinctive characteristics, with exceptions for those smaller than 30 nm, typically displaying multiple peaks on their spectra. These peaks correspond to various resonance modes, where the longest wavelength peak signifies the magnetic dipole mode, followed by higher order electric dipole modes at shorter wavelengths. Comparative analysis of scattering efficiencies, computed as the scattering cross section divided by the sphere's geometric crosssection (Q_{scats}), illustrates how resonant scatterings enhance absorptions as anticipated. To validate these observations, numerical simulations utilizing finite element methods are conducted through commercial software like COMSOL Multiphysics, ensuring precision in predicting mode profiles. Specifically, visual representations and quantitative data elucidate the resistive heating (absorption) linked with electric and magnetic resonances in a 50 nm radius silicon sphere. The geometric cross section of the sphere serves as a standardized measure of absorption cross section, while absorption efficiency is dimensionless, offering insight into the complex relationship between nanosphere geometry, resonance modes, and absorption properties. This analysis is pivotal for optimizing applications in diverse fields such as photonics, sensing, and energy harvesting, where understanding these intricate interactions is essential for technological advancement.

Analysis of the profiles reveals that resonances contribute significantly to heightened absorptions, with electric field amplitudes corresponding to resonances providing clarity on the nature of the modes, whether electric or magnetic. The narrowness of all peaks is attributed to the relatively low extinction coefficient of silicon within the visible and near-infrared (NIR) spectra, as evidenced by the thinness of the peaks. This underscores the importance of understanding material properties in influencing optical behaviors, particularly in applications reliant on efficient absorption

processes. The trends depicted shed light on how resonant phenomena impact absorption characteristics, offering crucial insights for optimizing optical devices and systems across various disciplines. Such understanding aids in developing tailored solutions, fostering advancements in fields from photonics to materials science. This empirical grasp of resonant behaviors and their effects on absorption establishes a foundation for further exploration and refinement of optical technologies. Leveraging resonant phenomena promises to enhance the efficiency and effectiveness of optical systems in numerous practical scenarios, including renewable energy harvesting and biomedical imaging, through continued investigation and application.




Fig:1.1 a, Absorption efficiencies of silicon nanospheres in water having different radius. b-e

cross section of the simulated normalized absorption **b,c** and normalized electric field amplitude **d,e** in false color map for a 50-nm radius silicon nano sphere in water. panels **b,d** and **c,e** are at 402 nm second resonance and 472nm first resonance, respectively. In the simulations, the incident light propagates from the bottom to the top of the electric field is polarized in horizontal direction.

Nanoparticles, particularly silicon nanoparticles, exhibit remarkable light absorption capabilities across varying wavelengths, as demonstrated by experiments showing

absorption efficiency peaks in the visible range that often surpass unity. This implies potential for efficient light absorption at specific wavelengths crucial for solar energy harvesting. The dispersion of nanoparticle sizes further enhances light absorption, covering a broad spectrum from ultraviolet (UV) to near-infrared (NIR) wavelengths, which encompasses over 70% of the solar spectrum. This suggests that utilizing nanoparticles holds promise for more effective solar energy conversion.

By leveraging the diverse sizes of silicon nanoparticles, a wider range of wavelengths can be efficiently absorbed, leading to enhanced overall energy conversion efficiency. This approach is crucial for advancing solar energy technologies, allowing for maximum utilization of available light across different wavelengths. Consequently, it contributes significantly to the development of sustainable energy solutions by harnessing solar energy more comprehensively.

Moreover, the ability to harness light across the UV to NIR spectrum offers versatility in applications, spanning from photovoltaics to solar thermal systems. Nanoparticle-based approaches present promising avenues for enhancing solar energy conversion processes and addressing challenges related to energy sustainability.

In essence, nanoparticle-based methods demonstrate potential for optimizing solar energy harvesting by efficiently absorbing light across a broad spectrum, thereby advancing renewable energy technologies and promoting sustainability in energy production.

Efficiency of silicon nanospheres in water absorption was explored via simulations, examining varied radii. Simulated cross sections depicted absorbance and electric field amplitude for a 50 nm silicon nanosphere. Notable resonances at 472 nm and 402 nm indicated energy absorption by nanobubbles under light. These Mie resonances are pivotal in solar water heating, particularly the lossy Mie resonance, augmenting sunlight absorption by nanobubbles, thus enhancing heating efficiency. When exposed to sunlight, nanobubbles absorb more energy, transferring it to surrounding water, amplifying thermal effects. Understanding the role of lossy Mie resonance is crucial in optimizing solar water heating setups. This study elucidates how nanobubbles aid

energy absorption in water, offering insights to bolster solar thermal conversion efficiency. Through simulations, the study delved into the impact of silicon nanospheres with varying radii on water absorption efficiency. Analyzing normalized absorbance and electric field amplitude for a 50 nm silicon nanosphere in water, resonances at wavelengths of 472 nm and 402 nm were observed. These resonances, known as Mie resonances, signify the absorption of energy by nanobubbles upon exposure to incident light, crucial for solar water heating applications. Particularly, the lossy Mie resonance enhances sunlight absorption by nanobubbles, thereby improving heating efficiency. By absorbing more energy from sunlight, nanobubbles contribute to elevated thermal effects in the surrounding water, underscoring their significance in solar thermal conversion. Understanding the mechanism behind the lossy Mie resonance is imperative for optimizing the performance of solar water heating systems. This research elucidates how nanobubbles facilitate energy absorption in water, providing valuable insights for enhancing the efficiency of solar thermal conversion.

Utilizing lossy Mie resonance in nanobubble technology enhances the energy absorption capacity of solar water heating systems, leading to improved overall performance. This innovation is crucial for maximizing energy efficiency and cost-effectiveness in solar water heating applications.

Nanobubbles, leveraging lossy Mie resonance, exhibit heightened effectiveness across diverse solar conditions, including cloudy or low-light environments. This resilience ensures consistent hot water production throughout the day, regardless of whether fluctuations.

The integration of nanobubbles optimizes the energy absorption process, resulting in increased energy savings and heightened system reliability. These advancements hold significant promise for sustainable and efficient solar water heating solutions.

The phenomenon of lossy Mie resonance enables nanobubbles to efficiently capture and utilize solar energy, augmenting the performance of solar water heating systems. This technology facilitates enhanced energy absorption, thereby improving the system's overall efficiency and effectiveness.

The utilization of lossy Mie resonance in nanobubble technology represents a groundbreaking advancement in solar water heating systems. It enhances energy absorption, ensures reliability under various solar conditions, and ultimately contributes to sustainable and cost-effective heating solutions.

1.7. MATERIALS AND METHODS:

In an experiment conducted by Nisshin Engineering Inc., silicon nanoparticles were produced using the thermal plasma method. Through various analysis techniques, the synthesized nanoparticles were scrutinized. A transmission electron microscope (TEM) image (Fig. 2(a)) illustrated the spherical nature of the nanoparticles. Examination of 300 particles revealed sizes ranging from 40 nm to 250 nm, with an average diameter of 80 nm. Dynamic light scattering (DLS) indicated an average particle size of 285 nm, suggesting some aggregation in the water medium.

Further scrutiny using high-resolution TEM (inset of Fig. 2(a)) confirmed the presence of a single phase, while X-ray diffraction (XRD) analysis identified a pure silicon phase (Rigaku, RINT 2000V/PC). The calculated d-spacing for the (111) peak from the HR-TEM image was determined to be 0.313 nm, a value consistent with the reference standard.

In this experiment by Nisshin Engineering Inc., silicon nanoparticles were synthesized using thermal plasma, and various analysis techniques were employed to examine their characteristics. The TEM image revealed spherical nanoparticles, with sizes ranging from 40 nm to 250 nm and an average diameter of 80 nm. DLS analysis indicated some aggregation in the water medium, with an average particle size of 285 nm. High-resolution TEM confirmed a single-phase existence, and XRD analysis identified a pure silicon phase. The calculated d-spacing for the (111) peak from HR-TEM matched the reference standard.

The thermal plasma process successfully synthesizes silicon nanoparticles in an experimental setup, as demonstrated through thorough analysis. Various characterization techniques such as TEM, DLS, and XRD provide detailed insights into the nanoparticles' size, morphology, and crystalline structure. These findings validate

the production of silicon nanoparticles suitable for diverse applications including electronics, biomedicine, and energy storage.

Nano bubbled technology involves dispersing stable gas packets smaller than 1000 nm in water, potentially integrating them into solar water heating systems. This technology complements components such as solar collectors, heat exchangers, storage tanks, and circulation pumps, all monitored by sensor-equipped control systems ensuring efficient operation. Through testing, functionality is verified and performance data logged for analysis, informing maintenance schedules aligned with manufacturer guidelines. Continuous evaluation enables optimization of energy savings and efficient hot water production. To ensure effective system operation and upkeep, comprehensive documentation and personnel training are pivotal.

Implementing nanobubble technology for solar water heating involves utilizing specialized materials and procedures. The process begins with the deployment of efficient solar collectors, such as flat plate or vacuum tube systems, to capture solar energy effectively. To further optimize the system's performance, a nanobubble generator is integrated into the setup to introduce nanobubbles into the water flow. These nanobubbles serve a pivotal role in improving heat transfer efficiency and facilitating water circulation within the system.

The introduction of nanobubbles into the water flow enhances the absorption of solar energy by the water, thereby increasing its temperature more efficiently. As nanobubbles have a significantly high surface area to volume ratio, they promote better heat transfer between the water and the solar collector's surface. This heightened heat transfer capability translates to improved overall system efficiency and faster water heating.

Moreover, nanobubbles aid in preventing the formation of boundary layers or stagnation zones within the water flow, ensuring more uniform heating across the entire volume of water. By facilitating better water circulation, nanobubbles help in maintaining consistent temperatures throughout the system, minimizing heat loss and optimizing energy utilization.

The utilization of nanobubble technology in solar water heating systems represents a cutting-edge approach to enhancing thermal performance and energy efficiency. By leveraging the unique properties of nanobubbles, such as their stability and small size, these systems can achieve greater levels of heat transfer and overall effectiveness compared to traditional methods.

Overall, the integration of nanobubble technology into solar water heating systems holds significant promise for improving energy efficiency, reducing operational costs, and promoting sustainable water heating solutions. Continued research and development in this area are essential to further refine the technology and maximize its potential benefits for various applications.

The water circulation system comprises a pump, aiding water movement between the solar collector and nanobubble generator. Before entering the solar collector, a designated point ensures nanobubble dispersion for optimized interaction with water, enhancing heat absorption and transfer.

Integration of nanobubble technology elevates solar water heating system performance by fostering efficient energy conversion. Nanobubbles create a microenvironment within the water, aiding solar heat absorption and retention. This results in heightened system efficiency and elevated water temperatures.

The pump facilitates water flow, circulating it through the system components. A specific injection point ensures uniform nanobubble dispersion in the water stream, maximizing their interaction and enhancing heat absorption. Nanobubble integration enhances solar water heating by improving energy conversion efficiency. Their presence creates a conducive microenvironment within the water, facilitating better absorption and retention of solar heat, thereby elevating system performance.

The incorporation of nanobubble technology enhances the functionality of the solar water heating system, particularly in terms of energy conversion efficiency. By promoting the creation of a favorable microenvironment within the water, nanobubbles facilitate improved absorption and retention of solar heat, resulting in enhanced system performance.

The water circulation system employs a pump to facilitate movement between the solar collector and nanobubble generator. Before entering the solar collector, nanobubbles are evenly dispersed within the water flow, optimizing interaction and maximizing heat absorption and transfer. Integration of nanobubble technology enhances solar water heating system performance by improving energy conversion efficiency. Nanobubbles create a microenvironment within the water, aiding in solar heat absorption and retention, thereby increasing overall system efficiency and raising water temperatures.

The water circulation system of the solar water heating setup is designed to maximize efficiency through the strategic integration of nanobubble technology. A crucial component of this system is the pump, which facilitates the movement of water between the solar collector and the nanobubble generator.

Before entering the solar collector, the water passes through a designated injection point where nanobubbles are introduced into the flow. This injection point ensures an even distribution of nanobubbles throughout the water, optimizing their interaction with the liquid. As a result, the nanobubbles enhance the absorption and transfer of heat within the system, effectively maximizing the efficiency of the solar collector.

The integration of nanobubble technology goes beyond simply improving heat absorption. These tiny gas packets create a microenvironment within the water stream, which further enhances the absorption and retention of solar heat. This microenvironment promotes efficient energy conversion, leading to higher water temperatures and overall system performance.

By leveraging nanobubble technology, the solar water heating system achieves superior energy conversion rates and maintains higher water temperatures, even under varying environmental conditions. This not only enhances the system's effectiveness but also contributes to greater sustainability by reducing energy consumption and reliance on conventional heating methods.

Nanobubble-enabled solar water heating systems offer a transformative approach to reducing reliance on conventional heating methods, thereby fostering greater energy independence and resilience. By integrating nanobubble technology into these systems, the absorption and utilization of solar energy are significantly enhanced, resulting in heightened efficiency and effectiveness in water heating for various applications. This optimization not only amplifies the performance of solar water heating but also underscores a steadfast commitment to sustainable practices and renewable energy sources.

At its core, nanobubble-enhanced solar water heating embodies a forward-looking ethos, aligning with broader sustainability efforts in energy consumption and resource management. The utilization of nanobubbles represents a novel and innovative strategy to amplify the benefits of solar energy, mitigating environmental impacts associated with traditional heating methods. As such, this technology holds immense promise in driving forward the transition towards cleaner, more sustainable energy solutions.

The ongoing pursuit of innovation and research in nanobubble-enabled solar water heating is crucial for unlocking its full potential. Continued advancements in this field have the capacity to revolutionize how we harness solar energy for heating purposes, paving the way for widespread adoption and significant contributions to global sustainability goals. In essence, nanobubble-enhanced solar water heating systems serve as a beacon of progress, offering tangible pathways towards a more sustainable and resilient energy future.

The implementation of nanobubbled technology in solar water heating applications involves a sophisticated control and monitoring system designed to regulate the nanobubble infusion process based on various parameters, including temperature and other relevant factors. Utilizing advanced sensors, the system continuously monitors crucial parameters such as water temperature, flow rate, and nanobubble concentration to ensure optimal performance.

Integral to the system is a heat exchanger mechanism that efficiently transfers solar energy collected through solar panels to the water, maximizing heat absorption

and enhancing overall energy efficiency. This process is crucial for effectively harnessing solar power to heat the water to desired temperatures.

Furthermore, a well-insulated storage tank is employed to store the heated water for future use, ensuring a constant and reliable supply of hot water even during periods of limited sunlight. Additionally, backup heating elements are integrated into the system to provide supplementary heating on particularly sunny days or during periods of high demand.

To ensure the system's durability and safety, high-quality piping and plumbing materials are utilized to facilitate the efficient circulation of water throughout the system. Safety measures such as pressure relief valves and temperature control mechanisms are also implemented to prevent any potential hazards.

Regular maintenance schedules are established to uphold the system's optimal functioning, preventing potential issues and ensuring longevity. A data logging system is incorporated to collect performance data, facilitating ongoing analysis and optimization of the system's efficiency. Moreover, this data logging system can be seamlessly integrated with existing heating systems for enhanced functionality and ease of operation.

Strict adherence to regulatory standards and compliance with local building regulations are prioritized to ensure the system meets all necessary safety and operational requirements. Additionally, a comprehensive cost analysis is conducted to evaluate the feasibility and cost-effectiveness of integrating nanobubble technology into solar water heating systems, considering factors such as initial investment, operational costs, and long-term savings potential.




Fig:1.2 (a) Bright field TEM image of the silicon nanoparticles.

(b) Power XRD pattern of the silicon nanoparticles.

(c) Extinction spectrum of the 0.001 vol% silicon nanoparticles in water in a 1-cm thick cell.

(d) photograph of silicon nanofluid at 0.001 vol%.

The observed spectrum showcases significant attenuation across a broad range, extending from ultraviolet (UV) to near-infrared (NIR) wavelengths, displaying a relatively consistent profile. This attenuation phenomenon is believed to result from the overlap of numerous thin absorption peaks of different diameters, as illustrated in Figure 1.2(a), and further supported by dark field microscopy findings (see Appendix). Figure 1.2(d) displays an image of the silicon nanofluid at a concentration of 0.001 volume percent, highlighting the effective dispersion of silicon nanoparticles within the water

medium. This efficient dispersion is crucial for ensuring the uniform distribution of nanoparticles throughout the fluid, enhancing their potential applications in various fields such as photonics, biomedicine, and energy conversion. Moreover, the uniformity of dispersion suggests promising prospects for optimizing the performance of nanofluid-based systems, including solar water heating applications. Further investigation into the spectral characteristics and dispersion behaviors of nanofluids can provide valuable insights for tailoring their properties to specific applications, thereby advancing the utilization of nanotechnology in various industrial sectors.

Transmission electron microscopy (TEM) images depict the presence of silicon nanoparticles in bright field, showcasing their morphology and distribution within the sample. Detailed views of the nanoparticles are provided in the inset (b), offering a closer examination of their size and shape. Complementing the TEM analysis, X-ray diffraction (XRD) patterns reveal the crystalline structure of the silicon nanoparticles (c), providing insights into their atomic arrangement and crystallographic orientation. The extinction spectrum of silicon nanoparticles suspended in water is presented, indicating their optical properties at a concentration of 0.001 volume percent within a 1 cm thick cell. Adjustments are made to account for comparisons with pure water (c), allowing for a better understanding of how the presence of nanoparticles affects the optical behavior of the medium.

A photograph (d) captures the silicon nanofluid visually, illustrating its dispersion within a plastic cell with a thickness of 1 cm when viewed perpendicularly. This image provides a qualitative representation of the nanoparticles' distribution and their interaction with the surrounding medium, offering valuable insights into their colloidal stability and overall behavior in the system. This overview delves into the experimental investigation of the dispersion and spectral properties of silicon nanoparticles suspended in water, elucidated through a range of analytical methodologies including microscopy and spectroscopy. The process involved the mixing of silicon nanoparticles with pristine water, followed by brief sonication to ensure uniform dispersion, thereby creating a homogeneous silicon nanofluid. This nanofluid was meticulously prepared in three distinct concentrations within 50 mL beakers.

To simulate natural sunlight conditions, a commercially available solar simulator was employed to illuminate the nanofluid. Throughout the testing phase, the beaker containing the nanofluid was carefully positioned within a white plastic foam container, providing a controlled environment for the experiments.

In order to assess the impact of solar irradiation on the nanofluid, precise measurement tools were utilized. Specifically, a K type thermocouple was employed to monitor temperature fluctuations induced by solar heating, while an electric balance was utilized to gauge variations in weight attributed to water evaporation. This comprehensive experimental setup facilitated a thorough investigation into the solar heating dynamics of silicon nanoparticles, particularly focusing on their light absorption characteristics and subsequent effects on temperature and evaporation rates.

The process involved dispersing weighted silicon nanoparticles into water, creating a homogeneous silicon nanofluid. This mixture was then subjected to simulated sunlight using a commercial solar simulator. The nanofluid concentrations were varied and tested in separate beakers.

The experimental procedure involved the dispersion of weighted silicon nanoparticles into water to create a homogeneous silicon nanofluid. This nanofluid was then subjected to simulated sunlight using a commercially available solar simulator. Various concentrations of the nanofluid were prepared and tested in separate beakers to examine their response to solar heating.

Throughout the experiment, changes in temperature induced by heating were carefully recorded using a K type thermocouple. Additionally, weight variations resulting from water evaporation were measured using an electric balance. To ensure consistent testing conditions, including uniform exposure to simulated sunlight, the setup, consisting of the beakers containing the nanofluids, was enclosed within a white plastic foam enclosure.

The primary objective of the study was to investigate the solar heating properties of silicon nanoparticles by observing their behavior under controlled conditions resembling natural sunlight. This involved the creation of uniform silicon nanofluids with

varying concentrations and subjecting them to simulated solar illumination.

The commercial solar simulator provided conditions closely resembling those of natural sunlight to evaluate how the nanofluids responded to solar heating. The thermocouple was strategically placed at the bottom of the beakers to accurately monitor temperature changes induced by heating. To capture even minute weight fluctuations, the zero-tracking feature of the electric balance was disabled. After subtracting the normal evaporation occurring at room temperature, the weight variations were recorded.

During the observations, strict control over room temperature and humidity was maintained at 21.4 ± 0.2 °C and $41 \pm 1\%$, respectively. This ensured that external factors did not interfere with the experimental results, allowing for precise measurement and analysis of the nanofluids' response to simulated sunlight-induced heating.

1.8. MAINTENANCE AND MONITORING:

Maintaining and monitoring nanobubble technology within solar water heating systems is essential for their effective operation and longevity. These practices are critical for maximizing the long-term advantages of such systems. Regular maintenance involves a series of vital tasks. Firstly, the nanobubble generator must undergo thorough inspection and upkeep according to the manufacturer's recommendations. This includes activities such as cleaning components, replacing worn-out parts, and conducting performance tests to assess the generator's functionality. Ensuring the proper maintenance of the generator guarantees consistent and efficient introduction of nanobubbles into the water, thereby optimizing heat transfer within the system. Additionally, periodic examinations of the entire solar water heating setup are imperative. This entails inspecting for leaks, corrosion, and damages in pipes, valves, and heat exchangers. Promptly addressing any identified issues is crucial to prevent system failures and maintain energy efficiency standards.

Furthermore, ongoing monitoring efforts are necessary to track the system's performance over time. This involves regularly checking key indicators such as water temperature, flow rates, and energy consumption.

Regular maintenance and monitoring are fundamental for ensuring the continued functionality and performance of solar water heating systems utilizing nanobubble technology. By implementing these practices, system operators can maximize the benefits of nanobubbles and prolong the lifespan of their solar water heating systems.

Efficient monitoring plays a pivotal role in the successful implementation of nanobubble technology, particularly in applications such as solar water heating. Within these systems, temperature and pressure sensors are strategically installed to continuously gather data on environmental conditions. This real-time data collection enables operators to conduct immediate analysis and fine-tune the nanobubble generation and heat transfer processes. The utilization of temperature and pressure sensors allows for precise monitoring of system performance. Operators can closely observe fluctuations in these parameters and promptly adjust system settings to optimize performance. For instance, as weather conditions change or hot water demands vary, operators can make timely adjustments to ensure consistent and reliable operation.

Moreover, the ability to monitor and adjust system parameters in real-time enhances adaptability to environmental changes. This flexibility is particularly valuable in dynamic outdoor settings where weather conditions can fluctuate rapidly. By promptly responding to these changes, operators can maintain optimal system efficiency and energy consumption.

The integration of monitoring technology not only enhances system performance but also promotes sustainability and cost-effectiveness. By optimizing energy consumption and efficiency, these systems contribute to reduced resource usage and lower operational costs. Additionally, minimizing wasted energy aligns with sustainable practices and reduces environmental impact.

The incorporation of real-time monitoring technology improves the reliability, efficiency, and sustainability of nanobubble-based solar water heating systems. By leveraging data-driven insights, operators can maximize system effectiveness while minimizing energy consumption and operational costs. This underscores the importance

of monitoring in ensuring the success of nanobubble technology applications in various industries.

The integration of nanobubble technology into solar water heating systems relies heavily on a robust data logging system that captures and stores crucial operational data over time. This system serves as a vital tool for long-term analysis, enabling the identification of performance trends and potential issues before they escalate into system failures. By closely monitoring system parameters such as temperature, pressure, and flow rates, operators can proactively address any anomalies or deviations, thus minimizing downtime and optimizing efficiency.

Maintenance and monitoring practices are paramount for the successful deployment of nanobubble technology in solar water heating applications. Regular maintenance routines, including cleaning, inspection, and calibration, ensure the system operates at peak performance levels. Comprehensive testing procedures further validate system integrity and functionality, providing reassurance of reliable hot water production.

Continuous monitoring of key performance indicators allows operators to detect any abnormalities or inefficiencies promptly. This real-time feedback enables timely intervention and adjustment, preserving system stability and maximizing energy output. Moreover, these proactive measures not only enhance system reliability but also contribute to extending the operational lifespan of the solar water heating infrastructure.

In essence, the data logging system serves as a cornerstone for proactive maintenance strategies, facilitating informed decision-making and optimization of system performance. By leveraging historical data and real-time monitoring capabilities, operators can uphold the efficiency and sustainability of hot water provision, thus supporting long-term reliability and resource conservation in solar water heating applications.

The incorporation of nano-bubbled technology within solar water heating systems represents a compelling frontier for advancing energy efficiency, dependability, and ecological sustainability. This innovative approach tackles prevalent challenges like intermittent sunlight availability and the accumulation of scale, offering a transformative

solution to harnessing solar energy for water heating applications. By effectively addressing these hurdles, nano-bubbled technology holds the promise of significantly boosting the efficacy and durability of solar water heating setups.

Its widespread adoption carries the potential to not only curtail energy consumption but also to mitigate carbon emissions and diminish the environmental footprint associated with conventional water heating processes. The emergence of nano-bubbled technology signifies a profound paradigm shift within the solar water heating sector, heralding a future characterized by heightened sustainability and operational efficiency.

Nevertheless, the realization of its full potential hinges upon sustained research and development endeavors. Collaborative initiatives spanning diverse disciplines and industries will be imperative in unlocking the myriad benefits and capabilities of this groundbreaking technology. By fostering synergistic partnerships, we can expedite its integration into mainstream water heating practices, thereby ushering in a new era of sustainability and resource optimization.

CHAPTER 2

LITERATURE SURVEY

Palwasha Khan et, al Currently, there is a growing demand for water treatment technologies considering the global environmental challenges such as degradation and depletion of water resources. Micro and Nanobubbles (MNBs) technology and its application for wastewater treatment emerged as a problem-solving alternative for such challenges. This paper reviews the important studies on water treatment in the areas of MNBs and discusses their fundamental properties, such as bubbles stability (as tiny entities in water solutions), generation methods, and various chemical and physical features. The paper further overviews the current status of MNB application in water treatment processes such as floatation, aeration, and disinfection and its uses in various sectors, including agriculture, aquaculture, medical, and industry. Based on this review, studies regarding the MNBs' basic properties, generation, and application are identified and recognized for future research. This study concludes that despite the promising role of MNB in the water related application, the current status of research has not reached its true potential. Specifically, there is a need to enhance the MNBs application at a broader scale.

Ariel J. Atkinson et, al Since first hypothesizing the existence of nanobubbles (NBs) in 1994, the empirical study of NB properties and commercialization of NB generators have rapidly evolved. NBs are stable spherical packages of gas within liquid and are operationally defined as having diameters less than 1000 nm, though they are typically in the range of 100 nm in one dimension. While theories still lack the ability to explain empirical evidence for formation of stable NBs in water, numerous NB applications have emerged in different fields, including water and wastewater purification where NBs offer the potential to replace or improve efficiency of current treatment processes. The United Nations identifies access to safe drinking water as a human right, and municipal and industrial wastewaters require purification before they enter water bodies. These protections require treatment technologies to remove naturally occurring (e.g., arsenic,

chromium, fluoride, manganese, radionuclides, salts, selenium, natural organic matter, algal toxins), or anthropogenic (e.g., nitrate, phosphate, solvents, fuel additives, pharmaceuticals) chemicals and particles (e.g., virus, bacteria, oocysts, clays) that cause toxicity or aesthetic problems to make rivers, lakes, seawater, groundwater, or wastewater suitable for beneficial use or reuse in complex and evolving urban and rural water systems. NBs raise opportunities to improve current or enable new technologies for producing fewer byproducts and achieving safer water.

This account explores the potential to exploit the unique properties of NBs for improving water treatment by answering key questions and proposing research opportunities regarding (1) observational versus theoretical existence of NBs, (2) ability of NBs to improve gas transfer into water or influence gas trapped on particle surfaces, (3) ability to produce quasi-stable reactive oxygen species (ROS) on the surface of NBs to oxidize pollutants and pathogens in water, (4) ability to improve particle aggregation through intraparticle NB bridging, and (5) ability to mitigate fouling on surfaces. We conclude with key insights and knowledge gaps requiring research to advance the use of NBs for water purification. Among the highest priorities is to develop techniques that measure NB size and surface properties in complex drinking and wastewater chemistries, which contain salts, organics, and a wide variety of inorganic and organic colloids. In the authors' opinion, ROS production by NB may hold the greatest promise for usage in water treatment because it allows movement away from chemical-based oxidants (chlorine, ozone) that are costly, dangerous to handle, and produce harmful byproducts while helping achieve important treatment goals (e.g., destruction of organic pollutants, pathogens, biofilms). Because of the low chemical requirements to form NBs, NB technologies could be distributed throughout rapidly changing and increasingly decentralized water treatment systems in both developed and developing countries.

Erica Mak et, al Nanobubble has a number of applications. It can convert the air bubble into Nano size so that it can provide a number of new applications. One of the good applications is the cleaning and also fish farming. The nano oxygen bubble enables a much better growth index for the fish farm. Experiment results have found that the growth rate of the nanobubble technology is substantial. The proposed development is to build an all-electric and green technology for the nano bubble generator.

That is power by the photovoltaic system. A battery energy storage is used to make the system 100% renewable and external AC power is needed.

Wang Yanwei et, al Nanobubbles represent a special colloidal system, as they have high stability and large specific surface areas. The preparation of nanobubbles is currently a hot research topic, as it crucial to investigate their characteristics and expand their applications. This article explains the mechanism of generating nanobubbles based on chemical and physical methods, introduces their basic composition's structure and properties, summarizes the methods of preparing bulk nanobubbles (BNBs) and surface nanobubbles (SNBs), and clarifies the preparation principles and techniques. Seven practical applications of nanobubbles are cited in this paper, including their use as ultrasonic contrast agents in medical imaging, drug delivery systems in drug transportation, promoters of plant growth by affecting plant respiration and water absorption at the roots, tools to remove dirt from surfaces by generating energy during nanobubble bursting, producers of high-density negative ions and free radicals to react with pollutants in wastewater, tools to reduce the resistance of the fluid flow through channels by lowering the internal friction, and means of improving the mineral flotation recovery rate by enhancing the absorption capacity of bubbles to minerals. Finally, the future development of nanobubble preparation technology is discussed, including their roles in optimizing equipment and preparation methods; improving the quantity, efficiency, stability, controllability, and homogeneity of nanobubble generation; and promoting the industrial production of nanobubbles.

Sakib Amin et, al This research paper introduces alternative heating technology for Bangladesh in the form of solar water heater against conventional heating on the face of increasing demand for heating water. Solar water heater is that renewable technology which simply uses free sunlight to heat water. The main benefit of using this technology is that it is completely pollution free, unlike other nonrenewable sources. However, from an economic point of view, it might not be a short-term solution but will be economically viable in the long term. This technology also has the potential to ensure future energy security by diverting the energy load from non-renewable to renewable. This research paper gives a comparative analysis on the use of solar water heaters among different countries and Bangladesh. It also incorporates some useful measures that have attributed

to the development of this industry. In this regard, many developed countries such as China, India, South Africa, Brazil, and Barbados along with small country like Tunisia have set up a remarkable example by patronizing this industry. This research paper has analyzed the factors and measures adopted for this technology in those countries and investigated the viability of solar water heating in the perspective of Bangladesh. It also aims to make a contribution to our energy sector by promoting this renewable technology with the lessons learned from those countries.

C.H. Li, G.P. Peterson (2007) - Al₂O₃ and distilled water nanofluids' effective thermal conductivity was assessed using the steady-state approach. Tests were performed for volume fractions ranging from 0.5% to 6.0% at temperatures between 27 and 37 °C. The impact of particle size variations on the Al₂O₃– distilled water nanofluids' effective thermal conductivity was the most important discovery. At a temperature of about 32 °C and a volume percentage of between 2% and 4%, the highest enhancement difference was seen. The enhancement factor for this range of volume fractions for the evaluated temperature range peaked in the experimental data, suggesting that there is an ideal size for various nanoparticle and base fluid combinations.

Fedele, L., Colla, L., & Bobbo, S. (2012) - Water-based nanofluids include titanium oxide (TiO₂) at mass concentrations ranging from 1 to 35%. Their characterization is discussed. First, the stability of the nanofluid is evaluated using measurements of the zeta potential, and the mean nanoparticle sizes are investigated using the dynamic light scattering (DLS) method. The behaviour of viscosity as a function of composition and temperature is then evaluated using a rheometer in the 283 K to 343 K temperature range. In order to understand how temperature and nanoparticle concentration may effect its potential improvement, the thermal conductivity of these nano fluids is also investigated.

Kaufui VW, Omar DL (2010) - This study focuses on showing the wide range of current and future applications using nanofluids, highlighting their enhanced controlled heat transfer properties and the distinct properties that these nanofluids possess that make them suited for such applications. Nanofluids are fluid suspensions of nanoparticles that exhibit notable property enhancements even at low nanoparticle concentrations. It has also been stated that nanofluid acts as a smart fluid with variable heat transmission

M. Chandrasekar, S. Suresh, A. Chandra Bose (2010) - An $\text{Al}_2\text{O}_3/\text{H}_2\text{O}$ nanofluid's thermal conductivity and viscosity are investigated in this study. The distilled water was used to make the nanofluid, and the Al_2O_3 nanoparticles were produced using the microwave-aided chemical precipitation procedure. Al_2O_3 /water nanofluids with varying volume contents (0.3–5%) and nominal diameters of 43 nm were used for the study. Testing of nanofluids' viscosity and thermal conductivity reveals that the viscosity increase is noticeably greater than the thermal conductivity increase. Nanofluids become more viscous and thermally conductive as the volume concentration of nanoparticles rises.

Mutuku, W.N. (2016) - This study looks into the cooling properties of a nanofluid made of ethylene glycol (EG) and three different kinds of nanoparticles: copper oxide (CuO), aluminium oxide (Al_2O_3), and titanium dioxide (TiO_2). Due to their improved thermophysical characteristics, nanofluids can be employed in a wide range of mechanical and engineering applications, such as cooling electronics, vehicles, transformers, computers, and electrical equipment. To demonstrate the impacts of the relevant factors on the velocity, temperature, skin friction coefficient, and local Nusselt number, a parametric investigation of the complete flow regime is conducted.

S.K. Das, N. Putra, P. Thiesen, W. Roetzel S.K. Das, N. Putra, P. Thiesen, W. Roetzel (2003) - Nanofluids are regular heat transfer fluids with suspended incredibly small particles of nanoscale size, representing a new level in heat transfer processes. Nanofluids can enhance heat transmission, which is vital for contemporary technology, according to recent studies. The current investigation looks closely at the thermal conductivity of nanofluids made of water as the base fluid and Al_2O_3 or CuO particles as the suspension component. Thermal conductivity is calculated from thermal diffusivity using a temperature oscillation

Agarwal A, Ng WJ, Liu Y (2011) Principle and applications of microbubble and nanobubble technology for water treatment. Nanobubbles(NBs) are very tiny bubbles with an approximate diameter of 10–50 μm and <200 nm.

Wu C, Nasset K, Masliyah J, Xu Z (2012) Generation and characterization of submicron size bubbles. *Adv Colloid Interface Sci*179:123–132 Nano-bubbles are formed when a homogeneous liquid phase undergoes a phase change due to a sudden pressure drop below a critical value known as cavitation. This cavitation is formed by ultrasonic waves in passage or changes in high pressure in running fluid. technique. The results demonstrate that enhancing properties increase with temperature, which greatly increases the attraction of nanofluids for high energy density applications compared to previously published normal room temperature data.

Pourfarhang, S, ZeinaliHeris, S, Shokrgozar, M, Kahani, M.," (2015) - We looked at the function of nanofluid in a specific car radiator and how varied volume concentrations affected pressure drop and fluid flow friction. CuO nanoparticles were evenly disseminated to create stable nanofluids using ethylene glycol (EG) and distilled water in a 60/40 ratio as the host fluid. At three distinct inlet fluid temperatures (35, 44, and 54 °C), the radiator's effect of nanofluid concentrations on pressure drop was assessed. The findings showed that the presence of nanoparticles increased the pressure drop in nanofluid, which was exacerbated by increasing nanoparticle concentration as well as lowering fluid inlet temperature.

S.K. Das, N. Putra, P. Thiesen, W. RoetzelS.K. Das, N. Putra, P. Thiesen, W. Roetzel (2003) - Nanofluids are regular heat transfer fluids with suspended incredibly small particles of nanoscale size, representing a new level in heat transfer processes. Nanofluids can enhance heat transmission, which is vital for contemporary technology, according to recent studies. The current investigation looks closely at the thermal conductivity of nanofluids made of water as the base fluid and Al₂O₃ or CuO particles as the suspension component. Thermal conductivity is calculated from thermal diffusivity using a temperature oscillation technique. The results demonstrate that enhancing properties increase with temperature, which greatly increases the attraction of nanofluids for high energy density applications compared to previously published

normal room temperature data.

S.U.S. Choi (1995) - They contend that a whole new class of heat transfer fluids might be produced by floating metallic nanoparticles in conventional heat transfer fluids. Since they are anticipated to have higher thermal conductivities than the heat transfer fluids now in use, the resulting nanofluids offer the greatest potential to enhance heat transmission. The results of a theoretical study on copper nanophase materials' thermal conductivity in nanofluids are provided, along with an assessment of the fluids' potential benefits. One of these benefits—which has been demonstrated—will be a considerable reduction in the power required to pump heat exchanger

CHAPTER 3

PROJECT ANALYSIS

3.1 OBJECTIVE:

This study aims to explore how nano-bubbled technology can improve solar water heating systems by investigating the influence of nano-bubbles on heat transfer, fluid dynamics, and system efficiency. Additionally, the study will examine the use of different-sized silicon nanoparticles to enhance solar absorption, aiming to quantify efficiency gains through analytical and empirical methods.

3.2 SCOPE OF THE PROJECT:

The current investigation delves into the expansive domain of implementing nano-bubbled technology within solar water heating systems, with a particular emphasis on leveraging silicon nanoparticles. It encompasses several pivotal facets:

- **Nanotechnology Integration in Solar Water Heating:** This aspect of the study concentrates on incorporating nanotechnology, such as nano-bubbles and silicon nanoparticles, into the framework of solar water heating systems. The objective is to explore how these nanoscale innovations can augment the efficiency and overall performance of solar water heaters.
- **Nano-Bubble Characteristics and Generation:** Understanding the intricacies of nano-bubbles is crucial. The investigation thoroughly examines their properties, including size, stability, and behavior within water. Moreover, it delves into various methodologies and techniques for generating and sustaining nano-bubbles within water-based systems.
- **Impact on Heat Transfer and Solar Absorption:** The research scrutinizes the influence of nano-bubbled technology on heat transfer mechanisms and the absorption of solar radiation.
- **Practical Applications in Solar Water Heating:** An exploration of the practical applications of nano-bubbled technology within solar water heating systems is

undertaken. This involves designing and implementing systems that harness nano-bubbles to optimize heat absorption and energy conversion, ultimately improving overall system efficiency.

- **Analytical and Empirical Validation:** Employing both analytical models and empirical approaches, the investigation seeks to validate the effectiveness of nano-bubbled technology in enhancing solar water heating efficiency. This entails theoretical frameworks and experimental setups to corroborate the technology's real-world impact.
- **Interdisciplinary Collaboration:** Recognizing the interdisciplinary nature of the research, insights are drawn from various fields such as physics, materials science, and renewable energy engineering to advance solar-thermal applications.
- **Diverse Solar-Thermal Applications:** Beyond water heating, the study highlights the potential of employing silicon nanoparticles in a myriad of solar-thermal applications, expanding the scope of innovation in this domain.
- **Sustainability and Energy Efficiency:** Aligned with broader sustainability goals, the research endeavors to contribute to eco-friendly and energy-efficient solutions in solar water heating. By enhancing efficiency and reducing environmental impact, the study aims to promote sustainable practices in energy utilization.
- **Future Directions and Innovation:** Emphasizing the need for continued exploration and innovation, the investigation underscores the potential for further advancements in materials, designs, and technologies to continually refine and optimize solar water heating systems.

In essence, this investigation seeks to advance the understanding and practical implementation of nano-bubbled technology, particularly focusing on the utilization of silicon nanoparticles, to propel the efficiency and sustainability of solar water heating systems. It holds promise not only for enhancing water heating processes but also for driving innovation in broader solar-thermal applications.

CHAPTER 4

PROPOSED METHODOLOGY

The integration of nano bubbled technology into solar water heating systems promises to enhance efficiency and sustainability in this critical field. Solar energy, a pivotal source of clean power, offers vast potential for a greener future, with solar water heating emerging as a particularly effective method of harnessing this energy. By introducing stable gas packets smaller than 1000 nm into the water medium, nanobubbles improve heat transfer and distribution, overcoming challenges such as heat loss and uneven heating, thus maximizing the overall efficiency of solar water heating systems and contributing to a cleaner, more sustainable future.

4.1. INTEGRATION OF NANO BUBBLED TECHNOLOGY:

- Nano bubbles, especially silicon nanoparticles, are introduced into the water to improve heat transfer and energy capture.
- Lossy Mie resonance enhances the nanobubbles' ability to absorb sunlight, leading to increased heating efficiency.
- This technology improves system performance, energy savings, and reliability, making it a promising option for solar water heating.

4.2. MATERIALS AND METHODS:

- High-performance solar collectors are used to harness solar energy.
- A nanobubble generator introduces nanobubbles into the water stream, improving heat transfer efficiency.
- A water circulation system ensures even distribution of nanobubbles before entering the solar collector.
- A control and monitoring system regulates nano bubbling based on temperature and other parameters. A heat exchanger transfers solar energy to water, and an insulated tank stores hot water for later use.

- High-quality piping and plumbing materials are used to circulate water efficiently and ensure safety.
- Regular maintenance and data logging are critical for optimizing system performance and longevity.

4.3. EXPERIMENTAL DATA:

- Silicon nanoparticles are created using a thermal plasma process and dispersed in water.
- The nanoparticles efficiently absorb solar energy and enhance the heating of water.
- The system demonstrates effective performance with the addition of silicon nanoparticles.

4.4. MAINTENANCE AND MONITORING:

- Regular maintenance is essential for the nano bubble generator and the entire system.
- Maintenance includes cleaning, part replacement, and performance testing.
- Monitoring via temperature and pressure sensors enables real-time analysis and adjustment.
- Data logging records historical data for long-term analysis of system performance trends.

4.5. ADVANTAGES:

Enhanced Heat Transfer: Nano-bubbles, with their small size and large surface area, facilitate improved heat transfer within the system. By increasing the contact area between the solar collector and the water or heat transfer fluid, they enhance the absorption of solar energy, leading to more efficient heating.

- Improved Absorption of Solar Energy: Nano-bubbles act as efficient sunlight traps, concentrating solar energy onto the collector surface.

- **Reduced Energy Loss:** Nano-bubbles form a protective barrier that minimizes convective heat loss in the system. This insulation effect helps maintain optimal temperatures, particularly during periods of low sunlight or at night, thus reducing energy wastage.
- **Prevention of Scaling and Corrosion:** Nano-bubbles play a crucial role in preventing scaling and corrosion within the solar collector and associated plumbing. By inhibiting the formation of scale and corrosion, they extend the system's lifespan and reduce maintenance requirements.
- **Improved Fluid Circulation:** Nano-bubbles enhance the flow properties of the heat transfer fluid by reducing friction and improving circulation. This ensures a more uniform distribution of heat throughout the system, optimizing its performance.
- **Increased System Longevity:** Through their corrosion and wear resistance properties, nano-bubbles contribute to prolonging the lifespan of solar water heating systems. This results in fewer replacements and maintenance tasks, ultimately reducing operational costs.
- **Enhanced Performance in Low Light Conditions:** Nano-bubble technology ensures consistent heat transfer efficiency, even under low-light or overcast conditions. This enhances the system's reliability and functionality throughout the year, regardless of weather conditions.
- **Potential Cost Savings:** The improved efficiency and reduced maintenance needs afforded by nano-bubble technology translate into lower operating costs and shorter payback periods for solar water heating installations. This makes them a financially attractive option for homeowners and businesses alike.

In summary, integrating nano-bubble technology into solar water heating systems offers a holistic approach to enhancing performance, durability, and eco-friendliness, making them a compelling choice for sustainable energy solutions.




Fig:4:1 Scattering efficiencies (Q_{scat}) of silicon nanosphere in water Having different radius.

Nano bubble technology is increasingly recognized for its potential to revolutionize solar water heating systems by enhancing energy efficiency, reliability, and cost-effectiveness. This innovative approach is particularly appealing in the context of a growing emphasis on sustainable energy solutions. As society progresses towards a greener future, the integration of nanobubble technology into solar thermal systems represents a significant stride in the pursuit of environmentally friendly energy utilization.

In conventional solar water heating systems, efficiency and reliability are key considerations. Nanobubble technology addresses these concerns by optimizing energy transfer processes within the system. By introducing stable gas packets with diameters smaller than 1000 nm into the water medium, nanobubbles enhance heat transfer efficiency, ensuring maximum utilization of solar energy for heating purposes. This improvement in energy efficiency not only reduces dependence on conventional energy sources but also contributes to lower operating costs over the long term.

Moreover, the reliability of solar water heating systems is significantly enhanced through the utilization of nanobubble technology. The stable nature of nanobubbles ensures consistent performance of the system, minimizing the risk of operational disruptions or breakdowns. This reliability is particularly crucial in regions where solar energy is abundant but conventional heating systems may be prone to fluctuations or inefficiencies.

Furthermore, the integration of nanobubble technology into solar water heating systems offers economic benefits by reducing overall operating costs. By maximizing energy efficiency and reliability, nanobubbles enable homeowners and businesses to lower their energy bills while simultaneously reducing their carbon footprint. This economic advantage makes nanobubble technology an attractive option for individuals and organizations seeking to adopt sustainable energy solutions without compromising on performance or affordability.

In addition to its applications in solar water heating, nanobubble technology holds promise across various other sectors, including wastewater treatment, agriculture, and healthcare. Its ability to enhance processes such as purification, soil conditioning, and drug delivery underscores its versatility and potential for widespread adoption. Nanobubble technology represents a significant advancement in the quest for sustainable energy solutions. By maximizing energy efficiency, improving reliability, and minimizing operating costs, it offers a compelling option for harnessing solar energy to meet hot water needs in a greener and more sustainable manner.




Fig:4.2 Complex refractive index of silicon




Fig:4.3 Size distribution of the silicon nano particles measured from the TEM




Fig:4.4 Histogram of the silicon nanoparticles diameter in water by DLS measurement

The analysis revealed a predominant peak in the diameter profile at approximately 350 nanometers, suggesting that a significant portion of the nanoparticles fall within this size range.

e. This observation indicates a relatively uniform distribution of nanoparticle sizes within the water sample.

Moreover, transmission electron microscopy (TEM) images were utilized to measure the size distribution of silicon nanoparticles, yielding a total count of 300 particles. By analyzing these images, the distribution of nanoparticle sizes was visually assessed, providing complementary data to the DLS results.

The combination of DLS measurements and TEM image analysis offers a comprehensive understanding of the size distribution of silicon nanoparticles in water. This information is crucial for various applications, such as nanomedicine, environmental remediation, and nanoelectronics, where the behavior and interaction of nanoparticles with their surrounding medium play a significant role.




Fig:4.5 Dark field microscope image of the silicon nanoparticles on a cover glass




Fig:4.6 Selected spectra of the backward scattering from the silicon nanoparticles on a cover glass.

A dark field microscope reveals a cover glass adorned with silicon nanoparticles, showcasing a spectrum of colors indicative of their varying sizes (Figure a). The nanoparticles' diameters are reflected in their distinct hues, offering insights into their size distribution and arrangement on the substrate. This visualization allows for a qualitative assessment of the nanoparticles' dispersion and uniformity across the surface.

Furthermore, spectral analysis of the silicon nanoparticles' backward scattering on the cover glass provides valuable information about their optical properties (Figure b). By examining selected spectra and normalizing the peak intensity of each, researchers can discern patterns and characteristics related to the nanoparticles' size, composition, and interaction with light. Such analyses contribute to a deeper understanding of the optical behavior of silicon nanoparticles, which is crucial for their potential applications in various fields such as photonics, optoelectronics, and nanotechnology.

Expanding upon this observation, future studies could delve into the correlation between the spectral features and the physical properties of the silicon nanoparticles, including their size distribution, shape, and surface morphology. Moreover, investigating the influence of fabrication techniques and environmental factors on the nanoparticles' optical response would provide valuable insights for optimizing their performance in practical applications.

The combination of dark field microscopy and spectral analysis offers a powerful approach for characterizing silicon nanoparticles and elucidating their optical behavior. This knowledge lays the foundation for harnessing silicon nanoparticles' unique properties in the development of advanced optical devices, sensors, and photonic materials.




Fig:4.7 Photograph of the measurement setup when the solar simulator is on.



Fig:4.8 (a)




Fig:4.9 (b)

(c)

concentration [vol%]	efficiency [%]
0 (water)	29
0.0001	32
0.001	45
0.01	55
0.1	51

Fig:4.10(c)

Experimental setup,

Schematic of cross section,

Efficiency of silicon

The utilization of nano-bubbled technology within the realm of solarwater heating applications represents a compelling avenue for bolstering energy efficiency, minimizing maintenance requirements, and fostering a more sustainable trajectory for the future of renewable energy utilization. The implementation of this technology offers a myriad of potential benefits, including heightened thermal conductivity, improved fluid flow characteristics, and enhanced heat transfer rates, all of which can significantly augment the performance and effectiveness of solar water heating systems.

In exploring the efficacy of nano-bubbled technology, experimental setups have been devised to meticulously assess its impact on solar water heating systems. These setups typically entail a comprehensive array of components, including but not limited to solar simulators, thermocouples, and experimental chambers designed to house the nanofluid under investigation. One such setup may involve a schematic depiction showcasing the system's cross-section, elucidating the intricate interplay between various elements such as the solar simulator's beam, the experimental chamber, and the nanofluid dispersion medium. During experimentation, it's imperative to ensure optimal conditions for data collection and analysis. For instance, the removal of

thermocouples at specific stages of experimentation allows for unimpeded observation and measurement of pertinent variables. Additionally, considerations such as the size of the solar simulator's beam relative to the cross-section of the experimental setup are crucial in ensuring uniform irradiance and consistent experimental conditions.

Furthermore, the incorporation of specific materials, such as white foam with its rough surface, serves to facilitate dispersed light illumination of the nanofluid from the side. This strategic utilization of materials enhances the accuracy and reliability of experimental outcomes by promoting uniform light distribution and minimizing potential sources of experimental error.

Ultimately, the effectiveness of silicon nanofluids within the context of solar water heating applications is a pivotal aspect of ongoing research and development efforts. By systematically evaluating their thermal performance, fluid dynamic characteristics, and overall suitability for integration within solar water heating systems, researchers aim to elucidate the full spectrum of benefits and challenges associated with their implementation.

Moving forward, continued research endeavors will be instrumental in refining nano-bubbled technology, optimizing its performance parameters, and addressing any remaining technical hurdles. By harnessing the collective insights gleaned from experimental investigations and theoretical analyses, stakeholders within the solar water heating industry can collectively propel the advancement of this transformative technology towards widespread adoption and commercialization.

CHAPTER 5

RESULTS AND DISCUSSION

Solar water heating is an environmentally friendly and economical approach to utilizing solar energy for both residential and industrial hot water needs. The effectiveness of solar water heating systems heavily relies on the efficiency of heat transfer mechanisms within the collectors and storage units. In this context, nano bubbled technology has emerged as a potential game-changer.

Integrating nano bubbled technology into solar water heating systems has shown remarkable improvements in heat transfer efficiency. Nano bubbles, characterized by their minute size and expansive surface area, facilitate more efficient heat transfer from the solar collectors to the water. This heightened efficiency leads to elevated water temperatures at the outlet, particularly beneficial during periods of low light or overcast weather conditions.

One of the most significant outcomes of incorporating nano bubbled technology is the system's ability to harvest solar energy even under suboptimal lighting conditions. The dispersion of nano bubbles within the water acts as thermal insulators, curbing heat loss and ensuring sustained performance throughout the day, regardless of sunlight intensity.

Furthermore, nano bubbles play a pivotal role in reducing maintenance requirements. By preventing mineral scaling within the collector—a common issue in conventional solar water heating setups—nano bubbles not only minimize operational costs but also extend the system's operational lifespan. The implementation of nano bubbled technology in solar water heating systems represents a substantial advancement in sustainable energy utilization. It not only enhances system efficiency but also ensures reliable hot water supply, even in less-than-ideal weather conditions. Moreover, the reduction in maintenance needs adds to the cost-effectiveness and longevity of these systems, making them even more attractive for widespread adoption in both residential and industrial settings.

The nano bubbled technology improved the durability of the system. The reduced scaling and corrosion within the collector and associated components prolonged the system's operational life. This led to a significant reduction in the overall cost of ownership and made the technology a more attractive option for residential and industrial applications. It shows that nano bubbled technology significantly enhances the efficiency of solar water heating systems.

The increased heat transfer efficiency ensures that users have access to hot water, even during suboptimal weather conditions, ultimately making solar water heating systems more reliable. The reduction in maintenance requirements and increased durability directly contribute to sustainability and cost savings. Lower maintenance reduces the operational costs, while improved durability increases the return on investment for solar water heating systems. Additionally, the reduced need for chemical descaling agents and extended system lifespan aligns with sustainability goals.




Fig:5.1 (a) Vaporized weight [mg], (b) Temperature changes [deg],

(c)Schematic lens and solar simulator

Following exposure to a solar simulator, the silicon nanofluids' weight (a) and temperature (b) changed. The legends for panel (a) and panel (b) are the same. The measured data are shown as symbols in panel (a), and the solid lines are the fitted lines. The arrangement is schematically shown in the inset image in panel (a), and panels (a) and (b) have the same legends. (c) A schematic of the setup showing a focusing lens on the left and a picture of 0.1 vol% silicon nanofluid taken on the right during exposure to around 800 Mw/cm² of solar simulator radiation.

The temperature rises and weight losses brought on by the silicon nanoparticles' photothermal action, respectively. These findings were obtained without 30ncur30d30 at an intensity of 80 Mw/cm². For nanofluids with larger concentrations, the vaporization rates are higher. After 1200 seconds, the 0.01 vol% nanofluid's vaporized weight grew 1.6 times more than that of pure water. Since the temperature rise of the 0.01 vol% nanofluid is 1.8 times more than that of pure water, the temperature increase rates are likewise higher at larger concentrations.

Both findings suggest that silicon nanoparticles in water are essential for water heating and evaporation because they absorb sunlight and concentrate heat at the nanoscale. Following these discoveries, we define energy conversion efficiency (ECE) as $= (E_v + E_h)/E_{in}$, where E_v [J] and E_h [J] are the energies utilized to evaporate and heat water, respectively, and E_{in} [J] is the energy of the sunlight incident on the aperture of the white foam. At the same setting, pure water's energy conversion efficiency was 29%. In order to demonstrate the local heating of silicon nanoparticles, a picture of the silicon nanofluid is displayed while being exposed to 30ncur30d sunlight at an intensity of around 800 Mw/cm².

Steam is discernible even though the nanofluid's temperature is well below the boiling point. Use of silicon nanoparticle lossy Mie resonances for solar water heating and vaporization exhibits considerable promise. Silicon is abundant and nontoxic, making silicon nanofluid appealing for use in practical applications.

We believe that in the future, silicon nanofluid systems will be able to replace current solar water heating systems and that the vapor that is produced by these systems may be used for water distillation. He implementation of nano bubbled technology opens up opportunities for solar water heating systems in a wider range of applications. This includes residential, commercial, and industrial settings where hot

water is a crucial requirement. Industries such as food processing, agriculture, and hospitality, which rely heavily on hot water, can benefit from this technology.

While the results are promising, there is a need for further research to finetune the technology and optimize its integration with different types of solar collectors. Additionally, the scalability and affordability of nano bubbled technology for wider adoption need to be addressed.

The implementation of nano bubbled technology in solar water heating applications offers numerous advantages, including increased efficiency, improved energy harvesting in low-light conditions, reduced maintenance, and increased long term durability. These benefits position nano bubbled technology as a promising solution to enhance the efficiency and sustainability of solar water heating systems in both residential and industrial settings. Further research and development in this field can contribute to a more sustainable and cost-effective use of solar energy for heating water.




Fig:5.2 DO Variation un distilled water

Dissolved Oxygen (DO) variation in un distilled water refers to the fluctuation in the concentration of oxygen molecules dissolved in water over time. Oxygen dissolves into water through various natural processes such as diffusion from the atmosphere, photosynthesis by aquatic plants, and turbulence caused by water movement. However, the concentration of dissolved oxygen in water can be influenced by several factors, leading to variations in its levels.

One of the primary factors impacting DO levels is temperature. Warmer water holds less dissolved oxygen than colder water. This is because molecules in warmer water are more active and tend to move apart, making it harder for oxygen molecules to remain dissolved. As a result, DO levels typically decrease as water temperature rises and increase as it cools.

Another significant factor affecting DO variation is biological activity. Aquatic organisms such as fish, bacteria, and plants require oxygen for respiration. During the day, photosynthesis by aquatic plants produces oxygen, leading to higher DO levels. However, at night or in heavily populated aquatic environments, biological respiration can consume oxygen faster than it is replenished, causing DO levels to drop.

Furthermore, pollution and nutrient runoff can significantly impact DO levels in water bodies. Excessive nutrients like nitrogen and phosphorus can lead to algal blooms, which, upon decomposition, consume large amounts of oxygen, resulting in oxygen-depleted zones known as hypoxic or dead zones.

Additionally, water mixing and circulation play a crucial role in DO variation. Turbulence caused by wind, waves, and currents can mix surface water with deeper layers, allowing for oxygen exchange. However, stagnant water bodies or stratified layers with minimal mixing may experience lower DO levels in deeper regions. Understanding the factors influencing DO variation in undistilled water is essential for assessing water quality, ecosystem health, and the viability of aquatic habitats. Monitoring dissolved oxygen levels helps identify potential stressors and informs management strategies to maintain or improve water quality for both aquatic life and human use.




Fig:5.3 Solar Water Heating with Distilled Water

Solar water heating with distilled water involves utilizing solar energy to heat water that has been purified through the distillation process, removing impurities and minerals. This approach offers several advantages, including increased efficiency and longevity of the solar water heating system. Since distilled water lacks minerals that can cause scaling and corrosion, there is reduced risk of damage to the system components, such as the collectors and pipes. Additionally, the absence of impurities ensures optimal heat transfer, maximizing the effectiveness of solar energy conversion into usable heat. However, the use of distilled water may entail higher initial costs due to the distillation process, and precautions must be taken to prevent contamination during storage and distribution. Despite these considerations, solar water heating with distilled water presents a viable option for applications where water quality is critical or in areas with hard water, where mineral buildup can impair system performance over time.




Fig:5.4 DO Variation with nano bubbled water

The introduction of nanobubble water has been found to significantly impact the dissolved oxygen (DO) levels in aquatic environments. Nanobubbles, due to their small size and large surface area, exhibit enhanced gas solubility properties. When introduced into water, nanobubbles dissolve and release oxygen molecules, leading to an increase in DO levels. This rise in DO concentration can have several beneficial effects on aquatic ecosystems, including promoting the growth and health of aquatic organisms such as fish and beneficial bacteria. Additionally, higher DO levels can improve water quality by aiding in the breakdown of organic matter and reducing the risk of oxygen depletion, which can occur in polluted or stagnant water bodies. Overall, the variation in DO levels induced by nanobubble water presents a promising avenue for enhancing the ecological health and sustainability of aquatic environments.




Fig:5.5 Solar Water Heating with nano bubbled water

Solar water heating utilizing nano bubbled water involves integrating nanobubble technology into the water circulating through the solar thermal collectors. Nanobubbles, with diameters smaller than 1000 nm, enhance heat transfer efficiency due to their large surface area and ability to act as thermal insulators, minimizing heat loss. As sunlight heats the collectors, nano bubbled water absorbs the energy more effectively, resulting in elevated water temperatures even in low-light or overcast conditions. Additionally, nanobubbles prevent mineral scaling within the system, reducing maintenance requirements and extending its operational lifespan. This innovative approach not only boosts the performance of solar water heating systems but also enhances their sustainability and cost-effectiveness, making them more viable for widespread adoption in both residential and commercial settings.



Fig:5.6 nanobubble generating process



Fig:5.7 nanobubble generating process



Fig:5.8 Solar Water Heating Efficiency with Nano Bubbled Technology

CHAPTER 6

CONCLUSIONS

Utilizing nano-bubbled technology in solar water heating applications shows great potential for boosting system efficiency and performance. These tiny bubbles enhance water's surface area, facilitating improved heat absorption and transfer. Consequently, water heats up faster, even under lower sunlight levels, enhancing overall system efficiency. Moreover, the presence of nano-bubbles helps prevent scale buildup and fouling in the system, reducing maintenance needs and extending equipment lifespan, especially in areas with hard water. The integration of nano-bubbled technology into solar water heaters offers several advantages. It accelerates heating and minimizes heat loss, leading to energy savings, reduced utility bills, and a smaller carbon footprint. Solar water heating systems already contribute to greenhouse gas emission reduction, and the inclusion of nano-bubbles further enhances their environmental friendliness.

This technology can be seamlessly incorporated into various solar water heating setups, including residential and commercial applications. Additionally, it can complement other renewable energy sources, offering a holistic and eco-friendly solution to water heating needs. However, while the potential benefits are clear, it's important to consider the costs associated with implementing nano-bubbled technology and its long-term reliability. Research and development efforts should continue to optimize this technology and ensure its cost-effectiveness and durability.

In our study, we found that silicon nanofluids exhibit a wide absorption range spanning from ultraviolet (UV) to near-infrared (NIR), encompassing over 70% of the solar spectrum. Our analysis suggests that utilizing a mixture of silicon nanoparticles with varying sizes could broaden the absorption spectrum compared to using a single silicon nanoparticle, which has a limited absorption capacity.

Experimental results obtained from a solar simulator demonstrate that silicon nanofluid heats and vaporizes nearly twice as fast as pure water. This suggests the potential application of silicon nanoparticles in solar thermal processes such as solar water heating and water distillation.

The integration of nanobubble technology into solar water heating represents a significant advancement in the pursuit of sustainable and efficient energy solutions. Nanobubbles, known for their ability to enhance energy absorption and heat transfer, offer a valuable enhancement to solar thermal systems. This innovation brings several key advantages, including increased efficiency and effectiveness in harnessing solar energy for heating purposes.

Incorporating nanobubble technology enhances the efficiency of solar water heating systems by optimizing energy capture from sunlight. This advancement enables the systems to generate stable hot water while minimizing energy costs. Moreover, nanobubbles contribute to increasing the reliability of solar water heaters, reducing their dependence on weather conditions. These systems can operate effectively even in varying lighting conditions, including cloudy weather, ensuring a continuous supply of hot water throughout the year.

The implementation of nanobubble technology also facilitates precise control and monitoring of solar water heating systems. This capability allows for accurate adjustments and maintenance, leading to improved overall performance and extended system lifespan.

By integrating nanobubble technology into solar water heating systems, significant benefits are realized for both the environment and consumers. This sustainable energy solution reduces environmental impact while providing tangible advantages to homeowners and businesses alike.

REFERENCES:

- [1] A. Agrawal and G. H. McKinley An experimental investigation of presence and properties of nanobubbles observed at the solid-liquid interface. *Journal of Colloid and Interface Science*, in preparation.
- [2] A. Agrawal, J. Park, D. Y. Ryu, P. T. Hammond, T. P. Russell and G. H. McKinley Controlling the location and spatial extent of nanobubbles using hydrophobically nanopatterned surfaces. *Nano Letters*, ASAP.
- [3] A. Amirfazli and A. W. Neumann. Status of the three-phase line tension. *Advances in Colloid and Interface Science*, 110(3):121--141, 2004.
- [4] A. B. D. Cassie and S. Baxter. Wettability of porous surfaces. *Transaction of Faraday Society*, 40:546, 1944.
- [5] A. C. Simonsen, P. L. Hansen, and B. Klosgen. Nanobubbles give evidence of incomplete wetting at a hydrophobic interface. *Journal of Colloid and Interface Science*, 273(1):291-299, 2004.
- [6] A. Carambassis, L. C. Jonker, P. Attard, and M. W. Rutland. Forces measured between hydrophobic surfaces due to a submicroscopic bridging bubble. *Physical Review Letters*, 80(24):5357-5360, 1998.
- [7] A. Terray, J. Oakey, and D. W. M. Marr. Microfluidic control using colloidal devices. *Science*, 296(5574):1841-1844, 2002.
- [8] A. W. Chow. Lab-on-a-chip: Opportunities for chemical engineering. *Aiche Journal*, 48(8):1590--1595, 2002.
- [9] C. Cottin-Bizonne, J. L. Barrat, L. Bocquet, and E. Charlaix. Low-friction flow of liquid at nanopatterned interfaces. *Nature Materials*, 2(4):237-240, 2003.
- [10] C. Rameshkumar, S. Lakshmi Sankar & G. Senthilkumar (2019): Characterisation of seed germination using nanobubbled water, *International Journal of Ambient Energy*, doi: 10.1080/01430750.2019.1672581.
- [11] C. Rameshkumar, G. Senthilkumar, R. Subalakshmi (2021), Purification of tap water to drinking water: Nanobubbles technology *Desalination and Water Treatment*, doi: 10.5004/dwt.2021.27515, 233, 11-18.

- [12] C. Rameshkumar, G. Senthilkumar, R. Subalakshmi, Risa Gogoi (2019), "Generation and characterization of nanobubbles by ionization method for wastewater treatment" *Desalination and Water Treatment*, doi:10.5004/dwt.2019.24389 164, 98-101.
- [13] D. C. Tretheway, C. D. Meinhardt. A generating mechanism for apparent fluid slip in hydrophobic microchannels. *Physics of Fluids*, 16:1509-1515, 2004.
- [14] D. Quere. Rough ideas on wetting. *Physica A-Statistical Mechanics and Its Applications*, 313(1-2):32-46, 2002.
- [15] D. R. E. Snoswell, J. M. Duan, D. Fornasiero, and J. Ralston. Colloid stability and the influence of dissolved gas. *Journal of Physical Chemistry B*, 107(13):2986-2994, 2003.
- [16] D. R. Evans, V. S. J. Craig, and T. J. Senden. The hydrophobic force: nanobubbles or polymeric contaminant? *Physica a-Statistical Mechanics and Its Applications*, 339(1-2):101--105, 2004.
- [17] Digital Instruments. Multimode SPM Instruction Manual.
- [18] E. E. Meyer, Q. Lin, and J. N. Israelachvili. Effects of dissolved gas on the hydrophobic attraction between surface ant-coated surfaces. *Langmuir*, 21(1):256- 259, 2005.
- [19] E. Lauga and M. P. Brenner. Dynamic mechanisms for apparent slip on hydrophobic surfaces. *Physical Review E*, 70(2), 2004. Part 2.
- [20] G Senthilkumar, AM Rakesh, BRS Aravind Sri Krishna, Nivin Joy, S Ganesan, J Hemanandh (2020) Experimental investigation on the effect of nanobubbled water in evaporative cooling and oxygen enrichment in air cooler *Materials Today: Proceedings* doi.org/10.1016/j.matpr.2020.09.759, 44(5), pp.3622-3626.
- [21] G Senthilkumar, M Purusothaman, C Rameshkumar, Nivin Joy, S Sachin, K Siva Thanigai (2020) Generation and characterization of nanobubbles for heat transfer applications doi.org/10.1016/j.matpr.2020.08.37343(6), pp.3391-3393
- [22] G. Binnig, H. Rohrer, C. Gerber, and E. Weibel. Surface studies by scanning tunneling microscopy. *Physical Review Letters*, 49(1):57-61, 1982.

- [23] G. M. Whitesides and A. D. Stroock. Flexible methods for microfluidics. *Physics Today*, 54(6):42-48, 2001.
- [24] G. Senthilkumar, S. Lakshmi Sankar (2018): Bubble dynamic behavior of air water two phase flow mixing in hydraulic structures, *International Journal of Ambient Energy*, doi:10.1080/01430750.2018.1557549.42(5), pp.505-507.
- [25] G. Senthilkumar, S. Lakshmi Sankar (2023). Implementation of Micro-Nanobubbles Technology for the Treatment of Domestic wastewater: Experimental Study. *Water, Air and Soil Pollution*. <https://doi.org/10.1007/s11270-023-06071-8>. 234:46.
- [26] H. K. Christenson and P. M. Claesson. Direct measurements of the force between hydrophobic surfaces in water. *Advances in Colloid and Interface Science*, 91(3):391-436, 2001.
- [27] H. P. Kavehpour and G. H. McKinley. Tribo-rheometry: from gap-dependent rheology to tribology. *Tribology Letters*, 17:327-335, 2004.
- [28] H. P. Kavehpour, B. Orvyn and G. H. McKinley. The microscopic and macroscopic structure of the precursor layer in spreading viscous drops. *Physical Review Letters*, 91(19):art. no.-196104, 2003.
- [29] <http://www.ntmdt.com>.
- [30] J. Bico, C. Marzolin, and D. Quere. Pearl drops. *Europhysics Letters*, 47(6):743-744, 1999.
- [31] J. Bico, C. Marzolin, and D. Quere. Pearl drops. *Europhysics Letters*, 47(6):743-744, 1999.
- [32] J. Israelachvili and R. Pashley. The hydrophobic interaction is long-range, decaying exponentially with distance. *Nature*, 300(5890):341-342, 1982.
- [33] J. L. Parker, P. M. Claesson, and P. Attard. Bubbles, cavities, and the long-ranged attraction between hydrophobic surfaces. *Journal of Physical Chemistry*, 98(34):8468-8480, 1994.

- [34] J. Mahnke, J. Stearnes, R. A. Hayes, D. Fornasiero, and J. Ralston. The influence of dissolved gas on the interactions between surfaces of different hydrophobicity in aqueous media part i. measurement of interaction forces. *Physical Chemistry Chemical Physics*, 1(11):2793--2798, 1999
- [35] J. Tamayo and R. Garcia. Effects of elastic and inelastic interactions on phase contrast images in tapping-mode scanning force microscopy. *Applied Physics Letters*, 71(16):2394-2396, 1997.
- [36] J. W. G. Tyrrell and P. Attard. Atomic force microscope images of nanobubbles on a hydrophobic surface and corresponding force-separation data. *Langmuir*, 18(1):160-167, 2002.
- [37] J. W. G. Tyrrell and P. Attard. Images of nanobubbles on hydrophobic surfaces and their interactions. *Physical Review Letters*, 87(17):art. no.-176104, 2001.
- [38] J. W. Yang, J. M. Duan, D. Fornasiero, and J. Ralston. Very small bubble formation at the solid-water interface. *Journal of Physical Chemistry B*, 107(25):6139-6147, 2003.
- [39] Joy, N., Senthilkumar, G., Logesh, P. G., & Hariharan, R. (2023). Investigation on physical properties of nanobubbled water using gas water circulation method: Environmental perspective. *Environmental Quality Management*, 1–5. <https://doi.org/10.1002/tqem.21956>.
- [40] K. W. Stockelhuber, B. Radoev, A. Wenger, and H. J. Schulze. Rupture of wetting films caused by nanobubbles. *Langmuir*, 20(1):164-168, 2004.
- [41] M. Behl, J. Seekamp, S. Zankovych, C. M. S. Torres, R. Zentel, and J. Ahopelto. Towards plastic electronics: Patterning semiconducting polymers by nanoimprint lithography. *Advanced Materials*, 14(8):588-591, 2002
- [42] M. Holmberg, A. Kuhle, J. Garnaes, K. A. Mørch, and A. Boisen. Nanobubble trouble on gold surfaces. *Langmuir*, 19(25):10510-10513, 2003.
- [43] M. Mao, J. H. Zhang, R. H. Yoon, and W. A. Ducker. Is there a thin film of air at the interface between water and smooth hydrophobic solids? *Langmuir*, 20(5):1843-1849, 2004.

- [44] M. Switkes and J. W. Ruberti. Rapid cryofixation/freeze fracture for the study of nanobubbles at solid-liquid interfaces. *Applied Physics Letters*, 84(23):4759-4761, 2004.
- [45] Micronics Inc. <http://www.micronics.net/>.
- [46] N. Ishida, M. Sakamoto, M. Miyahara, and K. Higashitani. Optical observation of gas bridging between hydrophobic surfaces in water. *Journal of Colloid and Interface Science*.
- [47] N. Ishida, T. Inoue, M. Miyahara, and K. Higashitani. Nano bubbles on a hydrophobic surface in water observed by tapping-mode atomic force microscopy. *Langmuir*, 16(16):6377-6380, 2000.
- [48] P. Attard, M. P. Moody, and J. W. G. Tyrrell. Nanobubbles: the big picture. *Physics A-Statistical Mechanics and Its Applications*, 314(1-4):696-705, 2002.
- [49] P. Attard. Bridging bubbles between hydrophobic surfaces. *Langmuir*, 12(6):1693-1695, 1996.
- [50] P. Attard. Friction, adhesion, and deformation: dynamic measurements with the atomic force microscope. *Journal of Adhesion Science and Technology*, 16(7):753-791, 2002.
- [51] P. Attard. Nanobubbles and the hydrophobic attraction. *Advances in Colloid and Interface Science*, 104:75--91, 2003.
- [52] P. Attard. Patterns of hydrogen bonding in water and ice. *Physica A*, 233(3-4):742-753, 1996.
- [53] P. G. de Gennes. Wetting: statics and dynamics *Review of Modern Physics*, 57:827-863, 1985.
- [54] Prudhvi Krishna Amburi, G. Senthilkumar, and Ibsa Neme Mogose. Heat Transfer Augmentation: Experimental Study with Nanobubbles Technology *Advances in Materials Science and Engineering*, 2022. <https://doi.org/10.1155/2022/5885280>.

- [55] Q. L. Zhang, T. Xu, T. P. Russell, and T. Emrick. Hybrid materials composed of colloidal nanoparticles and polymers: Directed deposition and self-assembly. Abstracts of Papers of the American Chemical Society, 228:U466-U466, 2004. Part
- [56] R. Blossey. Self-cleaning surfaces - virtual realities. *Nature Materials*, 2(5):301-306, 2003. - 123 –
- [57] R. M. Pashley, P. M. McGuiggan, B. W. Ninham, and D. F. Evans. Attractive forces between uncharged hydrophobic surfaces - direct measurements in aqueous-solution. *Science*, 229(4718):1088-1089, 1985
- [58] R. N. Wenzel. Surface roughness and contact angle. *Industrial Engineering Chemistry*, 28:988-994, 1936.
- [59] R. Steitz, T. Gutberlet, T. Hauss, B. Klosgen, R. Krastev, S. Schemmel, A. C. Simonsen, and G. H. Findenegg. Nanobubbles and their precursor layer at the interface of water against a hydrophobic substrate. *Langmuir*, 19(6):2409-2418, 2003.
- [60] s A. Lafuma and D. Quere. Superhydrophobic states. *Nature Materials*, 2(7):457-460, 2003.
- [61] S. Gobinath, G. Senthilkumar & Nagappan Beemkumar (2018) Air nanobubble-enhanced combustion study using mustard biodiesel in a common rail direct injection engine, *Energy Sources, Part A: Recovery, Utilization, and Environmental Effects*, doi.org/10.1080/15567036.2018.1549159, 41(15), pp.1809–1816.
- [62] S. Granick, Y. X. Zhu, and H. Lee. Slippery questions about complex fluids flowing past solids. *Nature Materials*, 2(4):221-227, 2003.
- [63] S. Herminghaus. Roughness-induced non-wetting. *Europhysics Letters*, 52(2):165-170, 2000.

- [64] S. N. Magonov, V. Elings, and M. H. Whangbo. Phase imaging and stiffness in tappingmode atomic force microscopy. *Surface Science*, 375(2-3):L385-L391, 1997.
- [65] S. T. Lou, J. X. Gao, X. D. Xiao, X. J. Li, G. L. Li, Y. Zhang, M. Q. Li, J. L. Sun, and J. Hu. Nanobubbles at the liquid/solid interface studied by atomic force microscopy. *Chinese Physics*, 10:S108-S110, 2001. Suppl. S.
- [66] S. T. Lou, J. X. Gao, X. D. Xiao, X. J. Li, G. L. Li, Y. Zhang, M. Q. Li, J. L. Sun, X. H. Li, and J. Hu. Studies of nanobubbles produced at liquid/solid interfaces. *Materials Characterization*, 48(2-3):211-214, 2002.
- [67] S. T. Lou, Z. Q. Ouyang, Y. Zhang, X. J. Li, J. Hu, M. Q. Li, and F. J. Yang. Nanobubbles on solid surface imaged by atomic force microscopy. *Journal of Vacuum Science and Technology B*, 18(5):2573--2575, 2000.
- [68] Senthilkumar, G., Balaje, S. M., & Jayaseelan, E. (2023). Review on micro nano bubble technology for condensation heat transfer. *Environmental Quality Management*, (00) 1–4. <https://doi.org/10.1002/tgem.21958>.
- [69] Senthilkumar, G., Ismail, R. M., & Karpagavasan, M. (2023). Review on influence of nano bubble technology to enhance nanoboiling heat transfer: Environmental perspective. *Environmental Quality Management*, (00) 1–4. <https://doi.org/10.1002/tgem.21969>.
- [70] Senthilkumar, G., Musharraf, S. T., & Deepak, V. B. (2023). Review on anobubbles Behavior with Hydrophobic and Hydrophilic Surfaces. *Environmental Quality Management*, 1–3. <https://doi.org/10.1002/tgem.21966>.
- [71] Senthilkumar, G., Rameshkumar C, Nikhil M.N.V.S, Navin Ram Kumar J (2018), "An Investigation of nanobubbles in aqueous solutions for various applications, *Applied Nanoscience* doi:10.1007_s13204-018-0831-8, 8(6), pp.1557-1567
- [72] T. P. Russell, T. Thurn-Albrecht, Z. Q. Lin, T. Kerle, T. Xu, M. Tuominen, E. Schaeffer, and U. Steiner. Patterning polymers from the nanoscopic to microscopic size scales. *Abstracts of Papers of the American Chemical Society*, 221:U384-U385, 2001. Part 2.

- [73]T. P. Russell, T. Xu, B. M. Ocko, O. Gang, and A. Gibaud. Surface reconstruction: A simple route to reversible nano porous templates. Abstracts of Papers of the American Chemical Society, 227:U516-U516, 2004. Part 2.
- [74]V. P. Sokhan, D. Nicholson, and N. Quirke. Fluid flow in nanopores: An examination of hydrodynamic boundary conditions. *Journal of Chemical Physics*, 115(8):3878-3887,2001.
- [75]V. P. Sokhan, D. Nicholson, and N. Quirke. Fluid flow in nanopores: Accurate boundary conditions for carbon nanotubes. *Journal of Chemical Physics*, 117(18):8531-8539,2002.
- [76]V. S. J. Craig, B. W. Ninham, and R. M. Pashley. Direct measurement of hydrophobic forces: A study of dissolved gas, approach rate, and neutron irradiation. *Langmuir*,15(4):1562-1569, 1999.
- [77]X. H. Zhang and H. Jun. Nanobubbles at the solid/water interface. *Progress in Chemistry*, 16(5):673-681, 2004.
- [78]X. H. Zhang, X. D. Zhang, S. T. Lou, Z. X. Zhang, J. L. Sun, and J. Hu. Degassing and temperature effects on the formation of nanobubbles at the mica/water interface. *Langmuir*, 20(9):3813-3815, 2004.