

AI-POWERED AUTOMATED WHEELCHAIR BASED ON LANE DETECTION WITH GESTURE, VOICE AND FACE RECOGNITION

Submitted in partial fulfillment of the requirements for the award of Bachelor of
Technology degree in Biomedical Engineering

By

SETHURAMAN.K(40240031)

ABIRAJ.B(40240002)



**DEPARTMENT OF BIOMEDICAL ENGINEERING
SCHOOL OF BIO AND CHEMICAL ENGINEERING**

SATHYABAMA

**INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)**

Accredited with Grade "A++" by NAAC

JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI

APRIL - 2024



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY

[DEEMED TO BE UNIVERSITY]

Accredited "A++" Grade by NAAC | 12B Status by UGC | Approved by AICTE

www.sathyabama.ac.in

DEPARTMENT OF BIOMEDICAL ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of **ABIRAJ.B(40240002)**, **SETHURAMAN.K(40240031)** who have done the project work as a team and carried out the project entitled **AI-POWERED AUTOMATED WHEELCHAIR BASED ON LANE DETECTION WITH GESTURE, VOICE AND FACE RECOGNITION** under our supervision from November 2023 to April 2024

Dr. J. BETHANNEY JANNEY, M.E., Ph.D.,

Guide and Supervisor

Dr. T. SUDHAKAR, M.Sc., Ph.D.,

Head of the Department

Head of the Department
Department of Biomedical Engineering
Sathyabama Institute of Science & Technology
(Deemed to be University)
Category I University by UGC
Jeppiaar Nagar, Rajiv Gandhi Salai,
Chennai - 600 119

Submitted for Viva voce Examination held on 05/04/24

Internal Examiner


External Examiner


DECLARATION

We, **SETHURAMAN.K(40240031)**, **ABIRAJ. B (40240002)** hereby declare that the Project Report entitled **AI-POWERED AUTOMATED WHEELCHAIR BASEDON LANE DETECTION WITH GESTURE, VOICE AND FACE RECOGNITION** done by us under the guidance of **Dr. J. Bethanne Janney, M.E., Ph.D., Department of Biomedical Engineering at SATHYABAMA INSTITUTE OF SCIENCE AND TECHNOLOGY** is submitted in partial fulfillment of the requirements for the award of Bachelor of Technology degree in Biomedical Engineering.

DATE: 05/04/24

PLACE: CHENNAI


1) ABIRAJ B


2) SETHURAMAN K

SIGNATURE OF THE CANDIDATES

ACKNOWLEDGEMENT

We are pleased to acknowledge our sincere thanks to the Board of Management of Sathyabama Institute of Science and Technology for their encouragement in doing this project and for completing it successfully. We are grateful to them.

We convey my thanks to **Dr. T. SUDHAKAR, M.Sc., Ph.D.**, Head of the Department, Department of Biomedical Engineering for providing me with the necessary support during the progressive reviews.

We would like to express our sincere and deep sense of gratitude to my Project Guide **Dr. J. Bethanne Janney, M.E., Ph.D.** for her valuable guidance, suggestions, and constant encouragement that paved the way for the successful completion of my project work.

We wish to express our thanks to all Teaching and Non-teaching staff members of the Department of Biomedical Engineering who were helpful in many ways for the completion of the project.

We would like to express our thanks to our parents for their unwavering support to us during these years.

ABSTRACT

The Empower Wheel Chair stands as a beacon of innovation in assistive mobility, seamlessly merging cutting-edge technology with user-centric design. Through groundbreaking features like facial recognition, gesture control, voice commands, lane detection, and Gaze Control, it transcends conventional aids, granting unprecedented independence. By integrating seamlessly into users' lives, it fosters autonomy and enhances overall well-being. Safety features such as lane detection ensure real-time awareness of surroundings, while Gaze Control facilitates effective communication for non-verbal individuals, promoting social engagement. Moreover, health-tracking capabilities empower users to monitor and manage their physical well-being proactively. More than just a mobility aid, the Empower Wheel Chair embodies inclusivity and freedom, reshaping the landscape of accessibility for individuals with mobility impairments. By embracing innovation and prioritizing user needs, it heralds a new era of independence and connection, empowering users to navigate their world with confidence and dignity.

Keywords—Wheelchair, Lane Detection, Computer vision, Voice Recognition, Hand tracking, Face Tracking

TABLE OF CONTENTS

CHAPTER NO.	TITLE	PAGE NO.
	ABSTRACT	i
	TABLE OF CONTENTS	ii
	LIST OF FIGURES	iv
	LIST OF ABBREVIATIONS	v
1	INTRODUCTION	1
2	LITERATURE SURVEY	2
3	AIM AND SCOPE	4
	AIM	4
	SCOPE	4
4	MATERIALS AND METHODS	5
	4.1 MATERIALS USED	5
	4.1.1 RASPBERRY PI	5
	4.1.2 L298 MOTOR MODULE	6
	4.1.3 DC MOTOR	6
	4.1.4 PI CAM	7
	4.2 SOFTWARES USED	8
	4.2.1 RASPBIAN	8
	4.2.2 PYTHON	8
	4.2.3 VISUAL STUDIO CODE	8
	4.3 ALGORITHM USED	8
	4.3.1 LANE DETECTION	8
	4.3.2 GAZE DETECTION	9
	4.3.3 FACE TRACKING	9
	4.3.4 SPEECH RECOGNITION	9
	4.3.5 HAND GESTURE RECOGNITION	10
	4.3.6 OPENCV	10
	4.3.7 ANOMALY DETECTION	10
	4.3.8 ZONE ANALYSIS	10
	4.3.9 RASPBIAN OS	10

5	RESULTS AND DISCUSSION , PERFORMANCE ANALYSIS	11
	5.1 RESULTS AND DISCUSSION	11
	5.1.1 USER INTERFACE	11
	5.1.2 LANE DETECTION	11
	5.1.3 FACE TRACKING	12
	5.1.4 HAND DETECTION	13
	5.1.5 GAZE DETECTION AND AAC	14
	5.1.6 VOICE RECOGNITION AND PURCHASE AUTOMATION	15
	5.1.7 AR NAVIGATION	16
	5.1.8 ALERT SYSTEM	18
	5.1.9 HARDWARE RESULTS	19
	5.2 PERFORMANCE ANALYSIS	20
	5.2.1 GAZE RECOGNITION	20
6	SUMMARY AND CONCLUSION	23
	6.1 SUMMARY	23
	6.2 CONCLUSION	24
	FUTURE WORKS	25
	REFERENCES	26

LIST OF FIGURES

FIGURE NUMBER	FIGURE NAME	PAGE NUMBER
4.1	RASPBERRY PI	5
4.2	L298 MOTOR MODULE	5
4.3	DC MOTOR 6V	6
4.4	PI CAM	7
4.5	BLOCK DIAGRAM	7
5.1	USER INTERFACE RESULT	11
5.2	LANE DETECTION RESULT	12
5.3	FACE TRACKING RESULT	13
5.4	HAND DETECTION RESULT	13
5.5	GAZE CONTROL OUTPUT	14
5.6	AAC OUTPUT	15
5.7	VOICE RECOGNITION	15
5.8	OCR RECOGNITION OF BILL	15
5.9	PURCHASE AUTOMATION RESULT	16
5.10	3D MODEL OF HOME	16
5.11	AR NAVIGATION APPLICATION	17
5.12	ZONE ANALYSIS RESULT	18
5.13	ANOMALY DETECTION RESULT	18
5.14	HARDWARE RESULT	19
5.15	RESNET	20
5.16	EFFICIENT NET	21
5.17	TENSORFLOW	22
5.18	PYTORCH	22

LIST OF ABBREVIATIONS

ABBREVIATIONS	DESCRIPTION
AAC	AUGMENTATIVE ALTERNATIVE COMMUNICATION
OS	OPERATING SYSTEM
HSV	HUE SATURATION VALUE
OCR	OPTICAL CHARACTER RECOGNITION
RANSAC	RANDOM SAMPLE CONSENSUS
AR	AUGMENTED REALITY
CNN	CONVOLUTIONAL NEURAL NETWORK
RESNET	RESIDUAL NETWORK
CV	COMPUTER VISION

CHAPTER 1

INTRODUCTION

In an ever-changing world driven by technological advancements, the core values of inclusivity and accessibility take on paramount importance. One of the key domains where these values are of utmost significance is in addressing the mobility challenges faced by individuals with physical disabilities. Our groundbreaking project, the Wheelchair, emerges as a beacon of innovation, aimed at revolutionizing the landscape of mobility solutions for a diverse range of mobility impairments. For millions across the globe, mobility is not a mundane task; it's a symbol of freedom and autonomy. However, mobility limitations encompass not only the act of moving but also challenges related to communication, healthcare access, environmental interaction, and social participation.

The Wheelchair is envisioned as a profound departure from the conventional wheelchair, representing a leap into the future of mobility, communication, and healthcare support. It's not just a mode of transportation; it's an intelligent, multifaceted device meticulously designed to enhance the lives of those with mobility impairments. This project redefines the traditional concept of a wheelchair by infusing it with cutting-edge technology, enabling a new era of independence, communication, and overall well-being. The Wheelchair transcends traditional boundaries, offering features such as facial and gesture recognition, voice command functionality, real-time health monitoring, obstacle detection, and seamless online medication management. These elements converge to empower users, enabling them to confidently navigate the world and express their needs effectively. This project exemplifies how advanced technology can pave the way for a more inclusive and equitable future, especially for those grappling with mobility challenges. It's not just a mobility solution; it's a holistic approach to addressing mobility, communication, and healthcare needs. The Wheelchair signifies a transformative step forward and reflects our unwavering commitment to emancipating individuals from the constraints of limited mobility, while ushering in a new era of empowerment.

CHAPTER 2

LITERATURE SURVEY

Long Yang Ma et.al (2021) presented a novel multi-lane detection method based on the constraints of lane information proposed in this paper. The proposed method consists of ego-lane detection, side lane detection, and post-processing and mainly uses the RANSAC algorithm.

Sundeepp Siddula et.al (2022) described an implementation of an eye blink sensor wheelchair that compels the lives of physically challenged people unruffled. This type of wheelchair has many improved facilities compared to the other wheelchairs.

Manas Kumar Rath et.al (2022) developed a novel lane detection method based on Deep learning using CNN and the proposed method consists of Edge Detection, Canny Algorithm, Hough Transform, Lane line detection, and Feature Extraction.

K. Suresh et al (2022) proposed Smart Lane Detection Using OpenCV And Image Processing and EBFM is used for detecting the lanes on the road. The EBFM incorporates the outcomes acquired from two stages to identify multi-lanes. In the main stage, multipath location detection is performed by utilizing EW-CSA.

Rajeshree Khande et.al (2022) proposed a Smart Voice and GestureControlled Wheel Chair and the successful implementation of this research work will encourage the disabled population to use a smart wheelchair, which can be controlled by using gestures and voice commands.

Heltin Genitha C et.al (2022) in their developed system has two primary components. Firstly, in the initial image processing step, it identifies white lane lines in grayscale and yellow lane lines in the HSV color space. These two sets of information are then combined to enhance the accuracy of recognizing yellow lane lines. Secondly, in contrast to the conventional Hough transform method, the

system detects curved lane lines by employing a unique combination of inverse perspective transformation and sliding window polynomial fitting. This approach significantly enhances the precision in recognizing and tracking curved lane lines.

Nusrat Farheen et.al (2022) in their work suggests using easily accessible, commercially available components to build a vision-based navigation system. These components include the Kinect camera system, a single-board computer like the Raspberry Pi 4, and an Edge TPU co-processor. The system also relies on open-source software tools such as OpenCV, python-freeness, and TensorFlow. This hardware concept is paired with a pre-trained Convolutional Neural Network (CNN), enabling the system to recognize obstacles and consequently avoid them while the autonomous vehicle is in operation.

Salna Joy et.al (2022) in their framework route identification model effectively showcase a reliable method for creating Advanced Driver Assistance Systems (ADAS) and Driving Systems. In the next step, the output from this system will be incorporated into another algorithm responsible for controlling speed and vehicle orientation (tilt or title).

Raoging Rui et.al (2023) in their implemented technique involves processing the image into two color spaces: grayscale for white lane lines and HSV (Hue, Saturation, and Value) for yellow lane lines. By doing so, the system can accurately identify and isolate both white and yellow lane lines. This is a clever approach because white and yellow lane lines can be best distinguished in these specific color spaces. The information from these two-color spaces is then merged to improve the overall accuracy of detecting yellow lane lines, enhancing the system's ability to recognize lane markings accurately.

Ninad Khertkar et.al (2023) constructed a system that employs an Android application to capture user gestures as input. These gestures are then transmitted to a Raspberry Pi for additional processing. The Raspberry Pi interprets these gestures and carries out specific actions associated with each gesture.

CHAPTER 3

AIM AND SCOPE

3.1 AIM

The primary aim of the Revolutionary Wheelchair project is to transform the mobility and healthcare management experience for individuals with disabilities. We aim to create a smart, user-centric wheelchair that leverages cutting-edge technologies to provide enhanced independence, health support, and overall well-being for users. The core objective is to make a significant and positive impact on the lives of people with mobility challenges.

3.2 SCOPE

- **Mobility Enhancement:** The smart wheelchair will feature autonomous navigation, obstacle detection, and adaptive movement capabilities to provide users with improved mobility and safety.
- **Healthcare Integration:** Users will be able to manage their healthcare needs by order-ing medications and scheduling doctor appointments directly through the wheelchair, simplifying healthcare routines.
- **Customization:** The wheelchair will be highly customizable to cater to individual user requirements and specific mobility and healthcare needs.
- **Intelligent Interaction:** Artificial intelligence and voice recognition technologies will enable users to control the wheelchair and access its features through voice commands, ensuring a user-friendly experience.
- **Inclusivity:** The project emphasizes inclusivity by involving users with diverse disabilities in the design and development process to ensure the wheelchair addresses their unique needs.
- **Scalability:** The project's design allows for future enhancements and expansions to keep the wheelchair up-to-date and relevant.
- **Ethical Considerations:** Ethical guidelines will be established to protect user privacy and ensure responsible technology use.
- **Affordability and Accessibility:** The project aims to make the smart wheelchair accessible and affordable to a wide range of users, prioritizing cost-effectiveness.

CHAPTER – 4

MATERIALS AND METHODS

4.1 MATERIALS USED

4.1.1 *Raspberry Pi*



Fig.4.1 Raspberry Pi

- The Raspberry Pi is a versatile, small, and affordable single-board computer that can play a significant role in the Wheelchair project.

Application

- Central Processing Unit
- Sensor Interfaces
- Real-time Data Processing
- Communication Hub
- User Interface
- AI and Machine Learning
- Remote Updates
- IoT Connectivity
- Voice Processing

4.1.2 L298 Motor Module




Fig.4.2 L298 Motor Module

This L298N Motor Driver Module is a high-power motor driver module for driving DC and Stepper Motors. This module consists of an L298 motor driver IC and a 78M05 5V regulator. L298N Module can control up to 4 DC motors, or 2 DC motors with directional and speed control.

4.1.3 DC Motor



Fig.4.3 DC Motor

A 6V DC motor can be used in a wide range of applications, especially those that require low to moderate power for mechanical motion.

4.1.4 Pi Cam




Fig.4.4 Pi Cam

The Pi Cam typically refers to a camera module designed for use with Raspberry Pi single-board computers. The official camera module for Raspberry Pi is simply called the Raspberry Pi Camera or Raspberry Pi Camera Module.




Fig.4.5 Block Diagram

4.2 SOFTWARES USED

4.2.1 Raspbian

Raspberry Pi OS is developed specifically for the Raspberry Pi hardware, which includes various models with different configurations. This means it's optimized to run efficiently on the ARM-based processors used in Raspberry Pi boards, making the most of the limited resources available. This optimization results in a responsive and stable operating system for a wide range of applications.

4.2.2 Python

Python is known for its simplicity and readability, making it an excellent choice for beginners and experienced developers alike. Its extensive ecosystem, active community, and broad range of applications make it a powerful and versatile language for various programming tasks.

4.2.3 Visual Studio Code

Visual Studio Code, often referred to as VS Code, is a free and open-source code editor developed by Microsoft. It's optimized for building and debugging modern web and cloud applications. It's lightweight but powerful, and runs on your desktop with support for Windows, macOS, and Linux.

4.3 ALGORITHMS USED

4.3.1 Lane Detection

Algorithms process camera images, identify lane markings, and calculate the vehicle or wheelchair's position within the lane. This information is crucial for autonomous navigation and ensuring safe and accurate movement within a lane. However, robust lane detection can be challenging in diverse lighting and road conditions, requiring advanced computer vision techniques and algorithms for reliable performance.

4.3.2 Gaze Detection

Gaze Detection: The algorithm calculates the user's gaze based on the position of the pupils within each eye frame. By analyzing the relative positions of the pupils, it determines the direction of the user's gaze, such as left, right, up, or down. The gaze control algorithm in our project utilizes advanced computer vision techniques to enable users to control the wheelchair through eye movements.

4.3.3 Face Tracking

Face tracking --PID (peripheral integral deviation) Control: Once the face is detected, a PID control system is employed to maintain the face at a specific position within the frame. This position corresponds to the desired direction of wheelchair movement. The PID controller continuously adjusts the wheelchair's orientation to keep the face within the specified range.

4.3.4 Speech Recognition

Speech recognition: Natural language processing techniques may be applied to understand and interpret more complex user instructions. This allows for more conversational and flexible interactions with the wheelchair system. voice recognition algorithm facilitates hands-free control of the wheelchair and interactions with the system through spoken commands. It converts spoken language into actionable instructions, enhancing accessibility and user convenience. Advanced features like NLP and continuous learning contribute to a more user-centric experience.

4.3.5. Hand Gesture Recognition

Hand gesture recognition: Landmark Localization(the hand is detected, and the algorithm localizes specific landmarks on the hand, such as fingertips and joints. These landmarks provide crucial information about the hand's position and orientation.

4.3.6 Open CV

OpenCV, which stands for Open-Source Computer Vision Library, is an open-source computer vision and machine learning software library. It's designed to provide a comprehensive infrastructure for computer vision applications and is widely used for a variety of tasks, including image and video analysis. OpenCV is used in a wide range of applications, including robotics, autonomous vehicles, medical image analysis, augmented reality, surveillance, and more.

4.3.7 Anomaly Detection

Implement anomaly detection algorithms to identify irregularities in the patient's behavior that may indicate distress or discomfort. Deviations from established behavior patterns can trigger alerts, providing timely assistance when needed.

4.3.8 Zone Analysis (Alert System)

Implementing a robust alert system utilizing openCV for zone analysis involves leveraging camera technology to identify danger zones in a specified map. By applying computer vision through OpenCV, the system can detect predefined danger areas using image processing techniques. Once these zones are identified, an alert system is activated to ensure prompt responses to potential risks. This integration allows for real-time monitoring of designated regions through the camera, enabling a proactive approach to user safety. The openCV-driven solution enhances the alert system's accuracy and responsiveness, providing an effective tool for detecting and addressing potential dangers within the specified zones.

4.3.9 Raspbian Os

Raspbian is an operating system (OS) designed specifically for the Raspberry Pi, a small, affordable, single-board computer developed by the Raspberry Pi Foundation. Raspbian is based on the Debian Linux distribution and optimized for the ARM architecture, which is the architecture used by Raspberry Pi's processors.

CHAPTER – 5

RESULTS AND DISCUSSION

5.1 RESULTS AND DISCUSSION

5.1.1 User Interface

The Python-based user interface (UI) Fig 5.1 provides seamless control over advanced computer vision functionalities, including face tracking, lane detection, and hand tracking. Utilizing libraries like OpenCV, the UI allows users to dynamically select and toggle between these features, empowering them with intuitive control. This UI not only enhances accessibility but also fosters user engagement and understanding, ensuring a smooth and efficient experience in leveraging these powerful computer vision capabilities.




Fig.5.1 User Interface Result

5.1.2 Lane Detection

Lane detection Fig 5.2 plays a crucial role in our project, facilitating autonomous navigation and control of the wheelchair. Utilizing computer vision algorithms, it identifies and tracks lanes on the ground, akin to systems in autonomous vehicles. This technology ensures safe and accurate wheelchair movement, particularly in indoor and outdoor settings. By capturing real-time video feeds from onboard cameras, the wheelchair sees its surroundings. Computer vision algorithms then process this data, detecting lane

features like road markings or tile patterns. This information guides the wheelchair's control system, enabling it to adjust its path autonomously and maintain its course. Our system's adaptability to various environments and lighting conditions, through techniques like adaptive thresholding and feature extraction, enhances accuracy and robustness. Continuously updating lane information in real time ensures dynamic navigation support. In summary, lane detection empowers the wheelchair with autonomous navigation, enhancing user independence and overall experience in diverse environments.




Fig.5.2 Lane Detection Result

5.1.3 Face Tracking

Face tracking Fig 5.3, a core aspect of our project, enables seamless communication with users and ensures safe navigation. Utilizing advanced computer vision, the wheelchair detects and tracks facial movements and expressions in real time. This involves capturing live video of the user's face and precise recognition of facial features. The system continuously monitors facial position to adjust seating or headrests for user comfort and safety. Additionally, intuitive head gestures influence navigation. Safety protocols engage if the user's face is obscured, halting or activating obstacle avoidance. Combining facial landmark detection, geometric calculations, and PID control methods ensures robust performance, even in challenging conditions.




Fig.5.3 Face Tracking Result

5.1.4 Hand Detection

Hand recognition Fig 5.4 is pivotal in revolutionizing wheelchair interaction. Real-time monitoring of hand motions offers users precise control. Initially, the system detects and tracks the hand using advanced computer vision. Landmarks like fingertips guide accurate tracking for effective response. Recognized gestures, such as clenched fists for stop or open palms for move forward, empower intuitive control. Translating gestures into commands enables functions like turning and speed adjustment. Despite challenges like lighting variations, algorithm refinements ensure consistent performance. Hand recognition not only simplifies wheelchair operation but also enhances inclusivity and user-centricity, redefining accessibility standards.




Fig.5.4 Hand Detection Result

5.1.5 GAZE DETECTION AND AAC

Gaze control Fig 5.5 is pivotal in our project, enabling intuitive interaction with the wheelchair through eye movements. The process involves real-time monitoring and interpretation of user eye behavior, starting with detection and extraction of the eye region. Computer vision algorithms precisely locate and track the eyes, including gaze direction and blinking patterns. Users steer the wheelchair by looking in their desired direction, enhancing accessibility for those with limited hand or voice use. Gaze control also triggers commands, such as adjusting settings or issuing voice commands. Challenges include lighting variations and individual eye behavior, addressed through robust algorithms and calibration. Gaze control revolutionizes wheelchair interaction, empowering precise, hands-free navigation and communication for individuals with mobility impairments.

Augmentative and Alternative Communication (AAC) Fig 5.6 is an integral aspect of our project, alongside gaze control, enhancing interaction with the wheelchair for individuals with mobility impairments. AAC functionalities provide users with versatile means of communication and control beyond traditional methods.




Fig.5.5 Gaze Detection Output

In addition to voice recognition, our project incorporates Fig 5.8 and 5.9 Selenium automation for medicine and doctor appointment booking user interfaces (UIs), enriching the user experience and streamlining access to essential healthcare services.

Selenium automation enables seamless navigation and interaction with medicine and appointment booking UIs by automating repetitive tasks and complex workflows. Users can utilize voice commands to initiate these processes, triggering Selenium automation scripts to perform actions such as browsing medicine catalogs, selecting preferred medications, and scheduling doctor appointments.




Fig.5.9 Purchase Automation Result

5.1.7 AR NAVIGATION




Fig.5.10 3d Model Of Home Using Blender

The integration of Blender for 3D house modeling Fig 5.10 and Unity for AR navigation Fig 5.11, offers users a compelling and immersive experience in exploring architectural spaces. In Unity, an AR navigation scene is set up, utilizing AR Foundation or Vuforia to enable augmented reality functionalities. Wayfinding logic guides users through the environment, with virtual waypoints or arrows placed using AR anchors or markers. A user interface provides route information and interactivity for seamless navigation. Meanwhile, Blender is employed to meticulously craft a 3D model of the house, encompassing detailed architectural elements such as walls, floors, doors, and windows. Texturing and lighting techniques in Blender enhance realism, ensuring a visually stunning representation of the house. The finished 3D model is then imported into Unity and seamlessly integrated with the AR environment. Users can interact with the 3D house model, exploring rooms, opening doors, and inspecting interior details. Additional information overlays provide context, while AR navigation seamlessly guides users to specific locations within the house. This combination of Unity and Blender creates a captivating and informative experience, allowing users to navigate and explore architectural spaces with unprecedented realism and interactivity.




Fig.5.11 Ar Navigation Application

5.1.8 ALERT SYSTEM




Fig.5.12 Zone Analysis Result

Zone analysis Fig 5.12 utilizes cameras to divide an area into distinct regions, detecting movement within each zone and triggering alarms upon detection. Employing computer vision techniques like OpenCV, cameras capture live feeds, segmented into predefined regions for analysis. Algorithms monitor each zone for motion, distinguishing between human movement and environmental changes. When movement is detected, an alarm system is activated, alerting authorities or security personnel. This approach enhances surveillance efficiency, enabling targeted responses to potential threats while minimizing false alarms. By leveraging zone analysis, organizations bolster security measures, safeguarding assets and ensuring prompt intervention in critical situations.




Fig.5.13 Anomaly Detection Result

An alert system Fig 5.13 integrated into a wheelchair utilizes anomaly detection via CVZone or OpenCV for real-time risk assessment. Utilizing onboard cameras, these computer vision libraries detect anomalies like obstacles or sudden changes in terrain. Upon anomaly detection, the system triggers alerts such as audible warnings, visual cues, or emergency braking. CVZone and OpenCV's features enable precise anomaly recognition, ensuring swift responses to potential hazards. By continuously monitoring the wheelchair's surroundings, this system enhances user safety and provides caregivers with peace of mind.

5.1.9 Hardware Results




Fig.5.14 Hardware Result

The hardware setup Fig 5.22 for the prototype wheelchair incorporates a Raspberry Pi, a camera (such as the PiCam), and a rechargeable 3.6V battery. Additionally, a power bank is included to ensure sustained operation. This configuration enables the wheelchair to perform various functions seamlessly, including face tracking, hand tracking, and other controls. The Raspberry Pi serves as the central processing unit, running the necessary software for facial and hand tracking using libraries like OpenCV. The camera captures real-time video feed, allowing the wheelchair to detect and track faces and hands accurately. The rechargeable 3.6V battery powers the Raspberry Pi, camera, and other components, providing mobility and flexibility without relying on a constant external power source. The power bank serves as a backup power supply, ensuring uninterrupted operation during extended usage or in case of battery depletion.

This hardware configuration provides a streamlined and effective solution for integrating advanced features into the wheelchair prototype, significantly improving user interaction and mobility. The Raspberry Pi serves as the brain of the system, orchestrating various functionalities seamlessly. Its compact size and low power consumption make it an ideal choice for embedded applications, ensuring efficient utilization of resources.

5.2 PERFORMANCE ANALYSIS

5.2.1 Gaze Recognition

Gaze recognition employing ResNet Fig 5.15, a Residual Neural Network architecture, utilizes deep learning to precisely estimate a person's gaze direction. In this approach, a ResNet model is trained on a substantial dataset of annotated eye images, learning to extract relevant features indicative of gaze direction, such as pupil position and eye shape. The ResNet's distinctive feature, residual connections, aids in training very deep networks effectively by alleviating the vanishing gradient problem. During training, the model adjusts its parameters to minimize the disparity between predicted and ground truth gaze directions. Once trained, the ResNet can accurately predict gaze direction from input eye images. This technology finds applications in various fields, including human-computer Interaction, driver monitoring systems, and assistive technologies. By harnessing the power of deep learning, gaze recognition using ResNet enhances the naturalness and intuitiveness of human-machine interactions, paving the way for more seamless and responsive systems.




Fig.5.15 Resnet

Gaze recognition using EfficientNet Fig 5.16, a highly efficient convolutional neural network architecture, leverages deep learning to accurately determine the direction of a person's gaze. EfficientNet is renowned for its superior performance and computational efficiency compared to traditional convolutional neural networks. In this approach, the EfficientNet model is trained on a sizable dataset of annotated eye images, learning to extract meaningful features indicative of gaze direction, such as pupil position and eye orientation. The model's efficient architecture allows it to process large amounts of data with minimal computational resources, making it suitable for real-time applications. During training, the EfficientNet model adjusts its parameters to minimize the difference between predicted gaze directions and ground truth labels. Once trained, the model can accurately predict the direction of a person's gaze from input eye images. Gaze recognition using EfficientNet finds applications in diverse fields, including human-computer interaction, driver monitoring systems, and assistive technologies.




Fig.5.16 Efficient Net

Gaze recognition using TensorFlow Fig 5.17 involves training neural network models to estimate gaze direction accurately. TensorFlow, a versatile machine learning framework, supports the development and training of convolutional neural networks (CNNs) on large datasets of annotated eye images. These models learn to extract features indicative of gaze direction, like pupil position, from input images. During training, TensorFlow optimizes model parameters to minimize differences between predicted and ground truth gaze directions. Once trained, the TensorFlow model accurately predicts gaze direction from new input images. This technology finds applications in human-computer interaction, driver monitoring, and assistive tech. Leveraging TensorFlow's capabilities enhances gaze estimation accuracy and efficiency, facilitating natural and intuitive interactions between humans and machines.




Fig.5.17 Tensorflow

Gaze recognition using PyTorch Fig 5.18 involves training neural network models to accurately estimate the direction of a person's gaze. PyTorch, a popular deep learning framework, provides a flexible and efficient platform for building and training convolutional neural networks (CNNs) or other deep learning architectures on large datasets of annotated eye images. In this approach, PyTorch is used to develop and train models that learn to extract features from input eye images, such as the position of the pupil and eye landmarks, which are indicative of gaze direction. During training, PyTorch optimizes the model's parameters to minimize the difference between predicted gaze directions and ground truth labels. Once trained, the PyTorch model can accurately predict the direction of a person's gaze from new input images. Gaze recognition using PyTorch has applications in various fields, including human-computer interaction, driver monitoring systems, and assistive technologies. By leveraging PyTorch's capabilities, this technology enhances the accuracy and efficiency of gaze estimation, enabling natural and intuitive interactions between humans and machines




Fig.5.18 Pytorch

CHAPTER – 6

SUMMARY AND CONCLUSION

6.1 SUMMARY

The project's primary objective is to create an advanced alert system specifically designed to enhance the safety and well-being of wheelchair users. To achieve this, the system utilizes OpenCV, a powerful computer vision library, to conduct zone Analysis within a designated map. This involves deploying cameras equipped with OpenCV to monitor predefined danger zones, such as areas with potential obstacles or hazards. Through sophisticated image processing algorithms, OpenCV identifies and delineates these danger zones in real time, providing precise spatial information crucial for ensuring user safety. Once these zones are detected, the system triggers an alert mechanism designed to promptly notify users or caregivers of any impending risks.

Furthermore, the integration of behavior analysis adds an extra layer of sophistication to the system. By leveraging OpenCV's capabilities in recognizing facial expressions and movements, the system can analyze the behavior of wheelchair users in response to their surroundings. This enables the system to adapt its alert strategies based on individual user patterns, providing a personalized and tailored approach to safety. In essence, the project combines cutting-edge technology with innovative algorithms to create a proactive and responsive alert system. By seamlessly integrating zone analysis with behavior recognition, the system aims to provide wheelchair users with a heightened sense of security and autonomy, ultimately improving their quality of life and fostering greater independence.

6.2 CONCLUSION

In conclusion, our report highlights the significant strides made in the field of assistive technology through the development of a cutting-edge wheelchair system tailored for individuals with mobility impairments. By integrating advanced technologies such as hand gesture recognition, voice control, lane detection, and gaze control, we have created a user-centric solution that prioritizes accessibility, functionality, and independence. Throughout the project, we encountered and addressed various challenges, including mitigating issues related to varying lighting conditions and fine-tuning algorithms for optimal performance. However, our unwavering dedication to research, development, and user feedback has enabled us to overcome these hurdles and deliver a transformative wheelchair system.

Moving forward, our focus remains on refining existing features, exploring new assistive capabilities, and ensuring the adaptability of our system to individual user needs. We are committed to continual innovation and improvement, with the ultimate goal of enhancing the lives of individuals with mobility impairments and making our advanced wheelchair system widely accessible.

6.3 FUTURE WORKS

While the Revolutionary Wheelchair represents a significant advancement in mobility assistance technology, there are several avenues for future development and enhancement. One promising direction is the integration of augmented reality (AR) navigation capabilities, which would provide users with real-time visual guidance and information about their surroundings. By overlaying digital information onto the physical environment, AR navigation can further enhance the user's spatial awareness and autonomy. Additionally, incorporating real-time AI accessibility features could further augment the wheelchair's capabilities. By leveraging AI algorithms, the wheelchair could dynamically adapt to changing environments and user needs, providing personalized assistance and support in various scenarios. For example, real-time object recognition and scene understanding could help the wheelchair navigate crowded spaces more effectively and anticipate potential obstacles or hazards.

Furthermore, the project could explore opportunities to enhance connectivity and interoperability with other smart devices and assistive technologies. By seamlessly integrating with smart home systems, wearable devices, and communication platforms, the wheelchair could offer a more comprehensive and interconnected user experience, enabling users to interact with their environment more intuitively and efficiently.

REFERENCES

1. D. Liang, Y. C. Guo, S. K. Zhang, "Lane detection: A survey with new results," *Journal of Computer Science and Technology*, vol. 35, no. 3, pp. 493–505, May 2020.
2. G. Zhang, H. Zhu, Y. Li, and H. Leung, "A novel adaptive Kalman filter for robust state estimation with outliers," *IEEE Transactions on Control Systems Technology*, vol. 29, no. 1, pp. 123-136, DOI: 10.1109/TCST.2020.2987102, Jan. 2021.
3. Gurghian, T. Koduri, S. V. Bailur, "DeepLanes: End-To-End Lane Position Estimation Using Deep Neural Networks," *IEEE Conference on Computer Vision & Pattern Recognition Workshops*, 2016.
4. H. Lin, Y. Chen, X. Chen, "Lane Detection Using Deep Learning with Feature Fusion and Temporal Modeling," *IEEE Access*, vol. 9, pp. 68494-68505, 2021.
5. H. Yoo, U. Yang, K. Sohn, "Gradient-Enhancing Conversion for illumination Robust Lane Detection," *IEEE Transactions on Intelligent Transportation Systems*, vol. 14, no 3, pp. 1083-1094, September 2013.
6. H. Zhu, G. Zhang, Y. Li, and H. Leung, "A novel robust Kalman filter with unknown non-stationary heavy-tailed noise," *Automatica*, vol. 127, 2021. DOI: 10.1016/j.automatica, 2021.
7. H. Zhu, G. Zhang, Y. Li, and H. Leung, "An adaptive Kalman filter within accurate noise covariances in the presence of outliers," *IEEE Transactions on Automatic Control*, 2021.
8. H. Zhang, J. Zhang, Z. Wang, "Lane Detection Based on Machine Learning Algorithms and Fusion Strategy," *IEEE Transactions on Intelligent Vehicles*, vol. 8, no. 4, pp. 572-581, 2023.
9. H. Zhang, Y. Wang, L. Zhang, "Lane Detection Based on Deep Learning and Image Enhancement Techniques," *IEEE Access*, vol. 9, pp. 3315-3324, 2021.
10. J. H. Yoo, S. W. Lee, S. K. Park, "A robust lane detection method based on vanishing point estimation using the relevance of line segments," *IEEE Transactions on Intelligent Transportation Systems*, vol. 18, no. 12, pp. 3254-3266, March 2017.

11. Kumar, V. Singh, R. S. Tomar, "Fuzzy Logic-Based Lane Detection and Tracking in Challenging Conditions," IEEE Access, vol. 9, pp. 43818-43828, 2021.
12. Kumar, V. Singh, R. S. Tomar, "Lane Detection and Tracking Using Sensor Fusion and Deep Learning," IEEE Transactions on Intelligent Transportation Systems, vol. 22, no. 4, pp. 2383-2392, 2021.
13. Liu, C. Wu, Z. Zhang, "A Lane Detection Method Based on Adaptive Threshold and Deep Learning," IEEE Access, vol. 9, pp. 50558-50567, 2021.
14. M. Aly, "Robust Lane detection using feature-based methods," Journal of Autonomous Vehicles, vol. 5, no. 2, pp. 87-98. DOI: 10.1016/j.jav.2023.02.001, Jun. 2023.
15. M. Marzougui, A. Alasiry, J. A. Kortli Yand Baili, "Lane Tracking Method Based on Progressive Probabilistic Hough Transform," IEEE Access, vol. 8, pp. 84893-84905, May 2020.
16. Manas Kumar Rath, Prasanta Kumar Swain, Shobhan Banerjee, "An Optimised Deep Learning Approach of Lane Detection in Complex Indian Environment", IEEE DOI: 10.1109/ICIDEA53933.2022.9970079, 2022.
17. Ninad Kheratkar, "Gesture Controlled Home Automation using CNN", IEEE Xplore Part Number: CFP20K74-ART; ISBN: 978-1-7281-4876-2, July 2023.
18. N. K. K. Jayawardana, S. P. Mudiyansele, K. C. Perera, "Lane Boundary Detection Using Machine Learning Techniques," International Conference on Advances in Computing, Communication, and Automation, 2020.
19. Rahjeshree Khande, Sheetal Rajapurkar, "Smart Voice and Gesture Controlled Wheel Chair", IEEE Xplore Part Number: CFP22J32-ART; ISBN: 978-1-6654-8328-5, 2022.
20. S. Zhao, L. Wang, X. Wang, "Real-Time Lane Detection Using Deep Learning and Semantic Segmentation," Sensors, vol. 21, no. 7, 2021.
21. S. Zhang, Y. Li, H. Zhu, and H. Leung, "A novel robust Kalman filter with unknown non-stationary heavy-tailed noise," Automatica, vol. 127, 2021. DOI: 10.1016/j.automatica, 2021.
22. Sundeep Siddhula, Mallika, M. Srujan, "Advance Eye Blink Sensor Controller Based Wheelchair", IEEE DOI: 10.1109/ICA- CITE53722.2022.9823704, 2021.

23. Suresh. K, Samjeevi Gandhi. A, Sowmya. M, Dakshina. R, "Smart Lane Detection Using Open CV And Image Processing", IEEE DOI:10.1109/ICPECTS56089.2022.10047442, 2022.
24. T. Koduri, A. Gurghian, S. V. Bailur, "DeepLaneNet: Deep learning approach for lane detection in urban environments," IEEE Intelligent Transportation Systems Magazine, vol. 15, no. 2, pp. 77-87, DOI: 10.1109/MITS.2024.3689012, Apr. 2024.
25. U. Yang, H. Yoo, K. Sohn, "Adaptive Lane detection using convolutional neural networks," IEEE Transactions on Intelligent Vehicles, vol. 7, no. 3, pp. 415-426, DOI: 10.1109/TIV.2022.3146189, Sep. 2022.
26. Y. C. Guo, D. Liang, S. K. Zhang, "Recent advancements in lane detection techniques: A comprehensive review," Transportation Research Part C: Emerging Technologies, vol. 123, pp. 102893,. DOI: 10.1016/j.trc.2021.102893, Apr. 2021.
27. Y. Wang, J. Li, Z. Zhang, "Lane Detection in Challenging Conditions Using Convolutional Neural Networks," IEEE Transactions on Vehicular Technology, vol. 70, no. 1, pp. 120-131, 2021.
28. Y. Li, G. Zhang, H. Zhu, and H. Leung, "An adaptive Kalman filter within accurate noise covariances in the presence of outliers," IEEE Transactions on Automatic Control, 2021.
29. Y. Zhang, W. Wang, X. Sun, "Lane Detection Based on Deep Learning and Ensemble Methods," IEEE Access, vol. 9, pp. 68277-68286, 2021.
30. Z. Liu, X. Li, Y. Li, "Lane Detection in Urban Traffic Scenes using Multi Region Convolutional Neural Networks," IEEE Access, vol. 9, pp. 39850-39859, 2021.