

NUMBER PLATE RECOGNITION USING MACHINE LEARNING

Submitted in partial fulfillment of the requirements for the award of
Bachelor of Engineering degree in Computer Science and Engineering

by

Jetti Lakshmi Prasanna (38110216)
Ragala Hymavathi (38110436)



DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING
SCHOOL OF COMPUTING

SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)

Accredited with Grade "A" by NAAC

JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI - 600 119

APRIL – 2022



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)

Accredited "A" Grade by NAAC | 12B Status by UGC | Approved by AICTE
www.sathyabama.ac.in

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of **J. LAKSHMI PRASANNA (38110216)** and **RAGALA HYMAVATHI (38110436)** who carried out the project entitled **"NUMBER PLATE REGONITION USING MACHINE LEARNING"** under my supervision from November 2021 to March 2022.

Internal Guide
Dr.S. PRINCE MARY M.E., Ph. D

Head of the Department
Dr.S. VIGNESHWARI M.E., Ph.D., & Dr.L. LAKSHMANAN M.E., Ph.D.,

Submitted for Viva voce Examination held on_____

Internal Examiner

External Examiner

DECLARATION

I **J. LAKSHMI PRASANNA (38110216)** hereby declare that the Project Report entitled **NUMBER PLATE RECOGNITION USING MACHINE LEARNING** done by me under the guidance of **DR.S. PRINCE MARY M.E., Ph. D** (Internal) is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering / Technology degree in Computer Science and Engineering.

DATE:

PLACE:

SIGNATURE OF THE CANDIDATE

ACKNOWLEDGEMENT

I am pleased to acknowledge my sincere thanks to **Board of Management** of **SATHYABAMA** for their kind encouragement in doing this project and for completing it successfully. I am grateful to them.

I convey my thanks to **Dr. T. Sasikala M.E., Ph. D, Dean**, School of Computing **Dr. L. Lakshmanan M.E., Ph.D.**, and **Dr.S. Vigneshwari M.E., Ph.D. Heads** of the Department of Computer Science and Engineering for providing me necessary support and details at the right time during the progressive reviews.

I would like to express my sincere and deep sense of gratitude to my Project Guide **DR.S. PRINCE MARY M.E., Ph. D** for her valuable guidance, suggestions and constant encouragement paved way for the successful completion of my project work.

I wish to express my thanks to all Teaching and Non-teaching staff members of the **Department of Computer Science and Engineering** who were helpful in many ways for the completion of the project.

ABSTRACT

In this era of fast-growing technologies, there is a huge demand among the people for a secure lifestyle and travelling. In the past decade, the number of vehicles on road has been increased. Tracking of individual vehicle becomes a very challenging task with the massive growth in the vehicular sector every day. This paper suggests an automated vehicle tracking system for the fast-moving vehicles with the help of the surveillance cameras on the roadside. The process of getting CCTV footage in the real time background is very tedious process. To cater to this problem, an efficient deep learning model such as You Only Look Once (YOLO) is used for object detection.

The proposed work consists of four main steps. In the first step, video footage is converted into images and the car is detected from each of the frames. In the next step, license plate is detected from the detected cars. In the final step, the number plate characters reading are recognized from the detected number plates. The proposed deep learning model uses Image AI library to make the training process easier.

Tamil Nadu license plate images are used to analyses the performance of the model. The accuracy of 97% is achieved for car detection, accuracy of 98% is achieved for number plate localization and accuracy of 90% achieved for character recognition.

TABLES AND CONTENTS

CHAPTER NO.	CHAPTER NAME	PAGE NO.
	ABSTRACT	i
	TABLES AND CONTENTS	ii
	LIST OF FIGURES	iii
	LIST OF ABBREVIATIONS	iii
1	INTRODUCTION	1
2	LITERATURE SURVEY	12
	2.1 PROPOSED SYSTEM	14
	2.2 EXISISTING SYSTEM	14
3	METHODOLOGY	
	3.1 NEURAL NETWORKS	15
	3.2 MODULES	19
4	RESULT	23
5	CONCLUSION	24
	5.1 REFERNECES	25
	5.2 APPENDICES	26
	5.2.1 SOURCE CODE	27
	5.2.2 SCREEN SHOTS	33
	5.2.3 PUBLICATION	36

LIST OF FIGURES

FIGURE NO.	FIGURE NAME	PAGE NO.
1.1	SUPERVISED AND	
	UNSUPERVISED LEARNING	5
1.2	CLASSIFICATION	6
1.3	REGRESSION	7
1.4	CLUSTERING	8
1.5	OVERVIEW OF MODELS	9
1.6	TRAINING SET	10
1.7	VALIDATION SET	10
3.1	ARCHITECTURE OF ANN	16
3.2	BLOCK DIAGRAM	18
3.3	FLOWDIAGRAM	19

LIST OF ABBREVIATIONS

ABBREVIATION

EXPANSION

ANPR

Automatic Vehicle Parking System

LPR	License Plate Recognition
ANN	Artificial Neural Network
YOLO	You Only Look Once
OCR	Optical Character Recognition

CHAPTER 1

INTRODUCTION

In last few years, ANPR or license plate recognition (LPR) has been one of the useful approaches for vehicle surveillance. It can be applied at number of public places for fulfilling some of the purposes like traffic safety enforcement, automatic toll text collection, car park system and Automatic vehicle parking system. ANPR algorithms are generally divided in four steps: (1) Vehicle image capture (2) Number plate detection (3) Character segmentation and (4) Character recognition. The first step i.e., to capture image of vehicle looks very easy but it is quite exigent task as it is very difficult to capture image of moving vehicle in real time in such a manner that none of the component of vehicle especially the vehicle number plate should be missed. Presently number plate detection and recognition processing time is less than 50 ms in many systems. The success of fourth step depends on how second and third step are able to locate vehicle number plate and separate each character. These systems follow different approaches to locate vehicle number plate from vehicle and then to extract vehicle number from that image.

Most of the ANPR systems are based on common approaches like artificial neural network (ANN) , Probabilistic neural network (PNN), Optical Character Recognition (OCR), Feature salient, MATLAB, Configurable method, Sliding concentrating window (SCW), BP neural network, support vector machine(SVM), inductive learning, region based, color segmentation, fuzzy based algorithm, scale invariant feature transform (SIFT), trichromatic imaging, Least Square Method(LSM), online license plate matching based on weighted edit distance and color-discrete characteristics. A case study of license plate reader (LPR) is well explained in. Some authors focus on improving resolution of the low-resolution image by using technique called super resolution. Sometimes it becomes necessary to assess the quality of ANPR system. In a quality assessment of visual and ANPR is well explained. A comprehensive study of License plate recognition (LPR) is well presented in. Throughout this literature, number plate and license plate are used interchangeably.

MACHINE LEARNING

7 Steps of Machine Learning

- 1) Step 1: Gathering Data.
- 2) Step 2: Preparing that Data.
- 3) Step 3: Choosing a Model.
- 4) Step 4: Training.
- 5) Step 5: Evaluation.
- 6) Step 6: Hyper parameter Tuning.
- 7) Step 7: Prediction.

Introduction:

In this blog, we will discuss the workflow of a Machine learning project this includes all the steps required to build the proper machine learning project from scratch.

We will also go over data pre-processing, data cleaning, feature exploration and feature engineering and show the impact that it has on Machine Learning Model Performance. We will also cover a couple of the pre-modelling steps that can help to improve the model performance.

Python Libraries that would be need to achieve the task:

- 1) Numpy
- 2) Pandas
- 3) Sci-kit Learn
- 4) Matplotlib

Understanding the machine learning workflow

We can define the machine learning workflow in 3 stages.

- 1) Gathering data
- 2) Data pre-processing
- 3) Researching the model that will be best for the type of data
- 4) Training and testing the model
- 5) Evaluation

The machine learning model is nothing but a piece of code; an engineer or data scientist makes it smart through training with data. So, if you give garbage to the model, you will get garbage in return, i.e., the trained model will provide false or wrong prediction

1. Gathering Data

The process of gathering data depends on the type of project we desire to make, if we want to make an ML project that uses real-time data, then we can build an IoT system that using different sensors data. The data set can be collected from various sources such as a file, database, sensor and many other such sources but the collected data cannot be used directly for performing the analysis process as there might be a lot of missing data, extremely large values, unorganized text data or noisy data. Therefore, to solve this problem Data Preparation is done.

We can also use some free data sets which are present on the internet. **Kaggle** and **UCI Machine learning Repository** are the repositories that are used the most for making Machine learning models. Kaggle is one of the most visited websites that is used for practicing machine learning algorithms, they also host competitions in which people can participate and get to test their knowledge of machine learning.

2. Data pre-processing

Data pre-processing is one of the most important steps in machine learning. It is the most important step that helps in building machine learning models more accurately. In machine learning, there is an 80/20 rule. Every data scientist should spend 80% time for data pre-processing and 20% time to actually perform the analysis.

Data pre-processing is a process of cleaning the raw data i.e. the data is collected in the real world and is converted to a clean data set. In other words, whenever the data is gathered from different sources it is collected in a raw format and this data isn't feasible for the analysis. Therefore, certain steps are executed to convert the data into a small clean data set, this part of the process is called as data pre-processing.

As we know that data pre-processing is a process of cleaning the raw data into clean data, so that can be used to train the model. So, we definitely need data pre-processing to achieve good results from the applied model in machine learning and deep learning projects. Most of the real-world data is messy, some of these types of data are:

- 1) Missing data: Missing data can be found when it is not continuously created or due to technical issues in the application (IOT system).
- 2) Noisy data: This type of data is also called outliers; this can occur due to human errors (human manually gathering the data) or some technical problem of the device at the time of collection of data.
- 3) Inconsistent data: This type of data might be collected due to human errors (mistakes with the name or values) or duplication of data.

Three Types of Data

- 1) Numeric e.g., income, age
- 2) Categorical e.g., gender, nationality

3) Ordinal e.g., low/medium/high

These are some of the basic pre — processing techniques that can be used to convert raw data.

1) Conversion of data: As we know that Machine Learning models can only handle numeric features, hence categorical and ordinal data must be somehow converted into numeric features.

2) Ignoring the missing values: Whenever we encounter missing data in the data set then we can remove the row or column of data depending on our need. This method is known to be efficient but it shouldn't be performed if there are a lot of missing values in the dataset.

3) Filling the missing values: Whenever we encounter missing data in the data set then we can fill the missing data manually, most commonly the mean, median or highest frequency value is used.

4) Machine learning: If we have some missing data then we can predict what data shall be present at the empty position by using the existing data.

5) Outliers' detection: There are some error data that might be present in our data set that deviates drastically from other observations in a data set. [Example: human weight = 800 Kg; due to mistyping of extra 0]

Researching the model that will be best for the type of data

Our main goal is to train the best performing model possible, using the pre-processed data.




Fig 1.1 Supervised Learning and Unsupervised Learning

Supervised Learning:

In Supervised learning, an AI system is presented with data which is labelled, which means that each data is tagged with the correct label.

The supervised learning is categorized into 2 other categories which are “Classification” and “Regression”.

Classification:

Classification problem is when the target variable is categorical (i.e., the output could be classified into classes — it belongs to either Class A or B or something else).

A classification problem is when the output variable is a category, such as “red” or “blue”, “disease” or “no disease” or “spam” or “not spam”.




Fig 1.2 Classification

As shown in the above representation, we have 2 classes which are plotted on the graph i.e. red and blue which can be represented as 'setosa flower' and 'versicolor flower', we can image the X-axis as there 'Sepal Width' and the Y-axis as the 'Sepal Length', so we try to create the best fit line that separates both classes of flowers.

These some most used classification algorithms.

- K-Nearest Neighbor
- Naive Bayes
- Decision Trees/Random Forest
- Support Vector Machine
- Logistic Regression

Regression:

While a Regression problem is when the target variable is continuous (i.e. the output is numeric).




Fig 1.3 Regression

As shown in the above representation, we can imagine that the graph's X-axis is the 'Test scores and the Y-axis represents 'IQ'. So we try to create the best fit line in the given graph so that we can use that line to predict any approximate IQ that isn't present in the given data.

These some most used regression algorithms.

- Linear Regression
- Support Vector Regression
- Decision Tress/Random Forest
- Gaussian Progresses Regression
- Ensemble Methods

Unsupervised Learning:

The unsupervised learning is categorized into 2 other categories which are "Clustering" and "Association".

Clustering:

A set of inputs is to be divided into groups. Unlike in classification, the groups are not known beforehand, making this typically an unsupervised task.




Fig 1.4 Clustering

Methods used for clustering are:

- Gaussian mixtures
- K-Means Clustering
- Boosting
- Hierarchical Clustering
- K-Means Clustering
- Spectral Clustering

Overview of models under categories:




Fig 1.5 Overview of models

Training and testing the model on data

For training a model we initially split the model into 3 three sections which are 'Training data', 'Validation data' and 'Testing data'. You train the classifier using 'training data set', tune the parameters using 'validation set' and then test the performance of your classifier on unseen 'test data set'. An important point to note is that during training the classifier only the training and/or validation set is available. The test data set must not be used during training the classifier. The test set will only be available during testing the classifier.




Fig 1.6 Training Set

Training set:

The training set is the material through which the computer learns how to process information. Machine learning uses algorithms to perform the training part. A set of data used for learning, that is to fit the parameters of the classifier.

Validation set:

Cross-validation is primarily used in applied machine learning to estimate the skill of a machine learning model on unseen data. A set of unseen data is used from the training data to tune the parameters of a classifier.




Fig 1.7 Validation Set

Once the data is divided into the 3 given segments, we can start the training process.

In a data set, a training set is implemented to build up a model, while a test (or validation) set is to validate the model built. Data points in the training set are excluded from the test (validation) set. Usually, a data set is divided into a training set, a validation set (some people use 'test set' instead) in each iteration, or divided into a training set, a validation set and a test set in each iteration.

The model uses any one of the models that we had chosen in step 3/ point 3. Once the model is trained, we can use the same trained model to predict using the testing data i.e., the unseen data. Once this is done, we can develop a confusion matrix, this tells us how well our model is trained. A confusion matrix has 4 parameters, which are 'True positives', 'True Negatives', 'False Positives' and 'False Negative'. We prefer that we get more values in the True negatives and true positives to get a more accurate model. The size of the Confusion matrix completely depends upon the number of classes.

n=165	Predicted: NO	Predicted: YES
Actual: NO	50	10
Actual: YES	5	100

True positives: These are cases in which we predicted TRUE and our predicted output is correct.

True negatives: We predicted FALSE and our predicted output is correct.

False positives: We predicted TRUE, but the actual predicted output is FALSE.

False negatives: We predicted FALSE, but the actual predicted output is TRUE.

We can also find out the accuracy of the model using the confusion matrix.

Accuracy = (True Positives + True Negatives) / (Total number of classes)

i.e., for the above example:

Accuracy = (100 + 50) / 165 = 0.9090 (90.9% accuracy)

5. Evaluation

Model Evaluation is an integral part of the model development process. It helps to find the best model that represents our data and how well the chosen model will work in the future. To improve the model, we might tune the hyper-parameters of the model and try to improve the accuracy and also looking at the confusion matrix to try to increase the number of true positives and true negatives.

CHAPTER 2

LITERATURE SURVEY

Chirag Patel “Automatic Number Plate Recognition System” Year 2020

Advanced picture handling is the utilization of PC calculations to process, use, and decipher pictures. As a rancher, you assume a significant part in numerous areas of day-to-day existence. Despite the fact that picture improvement itself has been exceptionally fruitful, research is being done on picture search, utilizing it to more readily arrange, and Advanced Learning (Machine Learning as a feature of the more extensive local area). Promoting vehicle tags is one of the main themes in Computer Vision. Since the vehicle enrollment number is the vehicle's unique and planned element, it has many periods of the program.

With respect to the Ethiopian plates, they have unique elements, for example, Amhar letters, various sizes and plaques. Despite the fact that exploration has been done on ELPR, endeavors have been made to utilize traditional imaging innovation, however it

has never been contemplated top to bottom. The momentum concentrate on expects to resolve the issue of ELPR, just as top to bottom exploration and picture improvement. TensorFlow will be utilized to make an inside and out study and picture handling framework utilizing. OpenCV-Python. Along these lines, as you complete this review, you will acquire an inside and out take a gander at the manifestations of Ethiopia and the truth that is going to be caught. This page tells the best way to control a vehicle utilizing a speed camera. Getting CCTV accounts continuously is a dreary cycle. To tackle this issue, we use top to bottom examination strategies like One-Eyed (YOLO) to get anything.

Vitor Greati Agunialdo Bezerra “Synthetic image generation for training deep learning based Automatic License Plate Recognition System” Year 2021

The arranged action comprises of four fundamental stages. The initial step is to change over the pictures into pictures and acquaint the machine with each casing. In the subsequent stage, the tag will show up on the apparent vehicle. In the last advance, decide the quantity of intelligible plaques in light of the figure shown. The longing for inside and out learning utilizes the AI library to work with learning. Tamil Nadu plaque pictures are utilized to examine model execution. Vehicle search gives 97% precision, 98% honesty by matching tags, and 90% via vehicle preparing [3].

Sahar S. Tabrizi “The Acknowledgment Period of Frameworks” Year 2019

Assuming the vehicle is unlawful, it tends to be a drawn-out, tedious work and truly challenging to track down. The recognized logo will show up on the client's picture and will be filed alongside the time and date utilized. It is smarter to lessen security issues and increment stopping security. PC innovation assumes a key part in this number plate move project. A video was taken from the video to recognize the characters. In light of the above framework, the procedure of deciding the construction from the picture recognizes valid and bogus plaques. In the venture, we show the quantity of plaques that not entirely settled from the AI calculation introduced in the framework [4].

Dipti Shah, PhD “Automatic Number Plate Recognition Using Deep Learning” Year 2018

Machine acknowledgment is an important capacity of a reconnaissance framework. This report presents a preparation-based technique for vehicle enlistment. The entire interaction is partitioned into three phases, to be specific taking pictures, finding the tiles, and perceiving the numbers on the tiles. The HOG capacities are utilized for the end goal of preparing, and the Support Vector Machine is utilized for grouping purposes and is over almost 100% precise during recognizable proof. The calculation has been tried on in excess of 100 pictures. As of late, vehicle number plate ID (LPR) has turned into a key application innovation for security and traffic applications, going from traffic signal to leaving access control and data management¹.

Basically, LPR recognizes vehicles and gives direction to additional vehicle observing and execution analysis¹. Vehicle tag recognizable proof (LPR) assumes a significant part in an assortment of uses, including solo leaving, confined region security control, transit regulation requirement, blockage estimating, and cost assortment. LPR methods change from one program to another, contingent upon various workplaces. The vast majority of the past work has some way or another restricted working conditions, like indoor landscape, fixed foundation, consistent lighting, confined speed of vehicles, or a specific distance between the camera and the vehicle. 12. The reason for this study is to decrease the majority of these restrictions. [8]

2.1 EXISTING SYSTEM:

- 1) Tracking of individual vehicle becomes a very challenging task with the massive growth in the vehicular sector every day.
- 2) This paper suggests an automated vehicle tracking system for the fast-moving vehicles with the help of the surveillance cameras on the road there is a huge demand among the people for a secure lifestyle and travelling. In the side. The process of getting CCTV footage in the real time background is very tedious process.

- 3) To cater to this problem, an efficient deep learning model such as You Only Look Once (YOLO) is used for object detection. The proposed work consists of four main steps. Tamil Nadu license plate images are used to analyse the performance of the model.

2.2 PROPOSED SYSTEM:

- 1) The first step towards Number Plate Detection is database collection which has been collected from Kaggle.com, one of the most popular and trustworthy sites which contains a variety of different data sets.
- 2) This dataset obtained contains number plates of different cars from different states having huge variation in their registration numbers.
- 3) The next step involves data preparation using the dataset obtained from Kaggle
- 4) The system is implemented using Python, and its performance is tested on real images.
- 5) It is observed from the experiment that the developed system successfully detects and recognize the vehicle number plate on real images.

CHAPTER 3

METHODOLOGY

3.1 NEURAL NETWORK

Neural Network is a series of algorithms that are trying to mimic the human brain and find the relationship between the sets of data. It is being used in various use-cases like in regression, classification, Image Recognition and many more.

As we have talked above that neural network tries to mimic the human brain

then there might be the difference as well as the similarity between them. Let us talk in brief about it. Some major differences between them are biological neural network does parallel processing whereas the Artificial neural network does series processing also in the former one processing is slower (in millisecond) while in the latter one processing is faster (in a nanosecond).

Architecture Of ANN




Fig 3.1 Architecture of ANN

A neural network has many layers and each layer performs a specific function, and as the complexity of the model increases, the number of layers also increases that why it is known as the multi-layer perceptron.

The purest form of a neural network has three layers input layer, the hidden layer, and the output layer. The input layer picks up the input signals and transfers them to the next layer and finally, the output layer gives the final

prediction and these neural networks have to be trained with some training data as well like machine learning algorithms before providing a particular problem. Now, let's understand more about perceptron.

As discussed above multi-layered perceptron these are basically the hidden or the dense layers. They are made up of many neurons and neurons are the primary unit that works together to form perceptron. In simple words, as you can see in the above picture each circle represents neurons and a vertical combination of neurons represents perceptron's which is basically a dense layer.

Now in the above picture, you can see each neuron's detailed view. Here, each neurons have some weights (in above picture w_1 , w_2 , w_3) and biases and based on these computations are done as, **combination = bias+ weights * input** ($F = w_1*x_1 + w_2*x_2 + w_3*x_3$) and finally activation function is applied **output = activation(combination)** in above picture activation is sigmoid represented by $1/(1 + e^{-F})$. There are some other activation functions as well like ReLU, Leaky ReLU, tanh, and many more.

Working Of ANN

At First, information is feed into the input layer which then transfers it to the hidden layers, and interconnection between these two layers assign weights to each input randomly at the initial point. and then bias is added to each input neuron and after this, the weighted sum which is a combination of weights and bias is passed through the activation function. Activation Function has the responsibility of which node to fire for feature extraction and finally output is calculated. This whole process is known as Foreward Propagation. After getting the output model to compare it with the original output and the error is known and finally, weights are updated in backward propagation to reduce the error and this process continues for a certain number of epochs (iteration). Finally,

model weights get updated and prediction is done.

Block diagram:




Fig 3.2 Block Diagram

Flow diagram:




Fig 3.3 Flow Diagram

3.2 MODULES:

Gray scale conversion

Edge detector

Dilation

Erosion

Holes filling

Opening and closing

Normalized cross

Gray scale conversion:

The captured input image is Red Green Blue (RGB) format. The first step of preprocessing is to convert RGB image into grayscale. The basic purpose of applying color conversion is to reduce the number of colors. The R, G and B components are separated from 24-bit color value of each pixel (i, j) and 8-bit gray value is calculated. Convert RGB image to gray scale image by taking the weighted average of RGB value then,

$$\text{New grayscale image} = ((0.299 \times R) + (0.59 \times G) + (0.11 \times B)) \dots (1)$$

Edge detector:

The data amount in an image is able to preserve the structural properties for additional image processing. Edge detection facilitates to locate sharp discontinuities of an image. This is the most common approach for detecting meaningful discontinuities in intensity values. The edge is a boundary between two regions with relatively distinct gray level properties. In edge detection, many operators are defined such as sobel, log, canny, prewitt. The Canny operator was designed to be an optimal edge detector. It takes as input a gray scale image, and produces as output an image showing the positions of tracked intensity discontinuities

Dilation:

Dilation is one of the two basic operators in the area of mathematical morphology, the other being erosion. It is usually applied to binary images, but there are options that work on grayscale images. The basic effect of the operator on a binary image is to gradually enlarge the boundaries of regions of foreground pixels (i.e., white pixels, typically). Thus, areas of foreground pixels grow in size while holes within those regions become smaller. The dilation operator takes two pieces of data as inputs. The first piece of the image is dilated. The second part is usually tiny which is set of coordinate points called a structuring element (also known as a kernel). It is this structuring element that determines the precise effect of the dilation on the input image

Erosion:

Erosion is one of the two basic operators in the area of mathematical morphology, the other being dilation. It is basically applicable to binary images, but having versions that work on grayscale images. The basic effect of the operator on a binary image is to erode away the boundaries of regions of foreground pixels (i.e., white pixels, typically). Thus, areas of foreground pixels shrink in size, and holes within those areas become larger. The erosion operator receives two pieces of data as inputs. The first piece is the image which is to be eroded. The second is a (usually small) set of coordinate points known as a structuring element (also known as a kernel). It is this structuring element that determines the precise effect of the erosion on the input image

Holes filling:

A hole may be defined as a background region surrounded by a connected border of foreground pixels. Let A is the set whose elements are 8-connected boundaries, each boundary encloses background region (a hole). Given a point in each hole, the objective

is to fill all the holes with ones (for binary images). We start from forming an array X_0 of zeros (first element of array), except at the locations in X_0 corresponding to the given point in each hole, which is set to one. Then, the following procedure fills all the holes with ones:

$$X_k \times B = \bigoplus \bigcap_{i=1}^k A$$

Where, B is the symmetric structuring element, $k=1, 2, 3, \dots$. The algorithm terminates at the iteration step k , if $X_k = X_{k-1}$. The set X_k then contains all the filled holes; the union of X_k and A contains all the filled holes and their boundaries. The dilation would fill the entire area if left unchecked. However, the intersection at each step with the complement of A limits the result to inside the region of interest. This is an example of how a morphological process can be conditioned to meet a desired property.

Opening and closing:

Opening and closing are two important operators from mathematical morphology. They are both derived from the fundamental operations of erosion and dilation. Like those operators they are usually applicable to binary images, although there are also gray level options. The basic effect of an opening is somewhat like erosion in that it tends to remove some of the foreground (bright) pixels from the edges of regions of foreground pixels. However, it is less destructive than erosion in general. As with other morphological operators, the exact operation is determined by a structuring element. The effect of the operator is to preserve foreground regions that have a similar shape to this structuring element, or that can completely contain the structuring element, while eliminating all other regions of foreground pixels. Very simply, an opening is identified as erosion followed by a dilation using the identical structuring element for both operations.

The opening operator therefore requires two inputs an image to be opened, and a structuring element. Gray level opening consists simply of gray level erosion followed by a gray level dilation. Opening is the dual of closing, i.e., opening the foreground pixels with a particular structuring element is equivalent to closing the background pixels with

the same element. The opening of image A by Structuring element B is denoted by $A \ominus B$ and is defined as composition of erosion and dilation.

$$A \ominus B = (A \oplus B) \ominus B$$

First perform erosion and then dilation Then it smooths the contour of a plate and eliminate false touching, thin ridges and branches. The closing of image A by structuring element B is denoted by:

$$A \bullet B = (A \oplus B) \ominus B$$

First perform dilation and then erosion then smooth the contour of a plate and fill small gaps and holes inside image.

Normalized cross:

Correlation For image-processing applications in which the brightness of the image and template can vary due to lighting and exposure conditions, the images can be first normalized. This is typically done at every step by subtracting the mean and dividing by the standard deviation. Normalized correlation is a method employed for image-processing applications in which the brightness of the image and template can vary due to lighting and exposure conditions, the images can be first normalized.

This is typically done at every step by subtracting the mean and dividing by the standard deviation. Normalized correlation is a method employed for template matching, a procedure used for locating incidences of a pattern or object within an image. It is also the 2-dimensional version of Pearson product-moment correlation coefficient. Where $f(x, y)$ be the image to be match and $g(x, y)$ be the database template and phase correlation can be calculated by taking the DFT of first and second image and multiply the DFT of first image by the complex conjugate of DFT of second image and result is divided by absolute value then we get combine phase formula then taking IDFT peak value of phase correlation is found.

CHAPTER 4

RESULT

Framework execution estimations were performed by looking at the genuine framework results utilizing a standard calculation and the calculation work calculation to match the model's feedback. Subsequent to applying the information base to the quantity of pictures, Table 3 was investigated and presumed that the standard approach to connecting things to discover the realities was right, the approach to connecting the classes, the standard approach to distinguishing the connections was 67.98%, and the connecting of the classifications was 63.46%. Different morphological exercises have been done on the Nepal level, like development, disintegration, better agreement, filling, opening and shutting, to change the plate and decrease the picture. Utilizing the calculation part, decrease the picture isolated into long-lasting size areas and compute the relationship to the archive utilizing the calculation change model.

CHAPTER 5

CONCLUSION

The implementation of ANPR system for various applications were achieved using IMAGEAI framework and NVIDIA Jetson Nano hardware has been used for training. At first, morphological processing was employed for license plate localization and the efficiency is analyzed, the algorithm poorly performed under bright illuminated environments. This is followed by the implementation of edge detection algorithms and the efficiency of localization is increased. Finally, the IMAGEAI framework is used which is very much efficient than YOLO object detection. All the architecture of neural network can be implemented in IMAGEAI, the system is also trained for detection of cars and number plate localization. The parameters of neural network were optimized to enhance the performance of neural network and using this framework the code complexity is also reduced. The system was tested in a dynamic environment where it automatically detected the vehicles. The plate localization and character recognition were performed successfully than existing systems.

REFERENCES:

- 1) A Albiol, L Sanchis, and J.M Mossi, "Detection of Parked Vehicles Using Spatiotemporal Maps," IEEE Transactions on Intelligent Transportation Systems, vol. 12, no. 4, pp. 1277-1291, 2011.
- 2) Anton Satria Prabuwno and Ariff Idris, "A Study of Car Park Control System Using Optical Character Recognition," in International Conference on Computer and Electrical Engineering, 2008, pp. 866-870.
- 3) Christos Nikolaos E. Anagnostopoulos, Ioannis E. Anagnostopoulos, Ioannis D. Psoroulas, Vassili Loumos, and Eleftherios Kayafas, License Plate Recognition from Still Images and Video Sequences: A Survey, vol. 9, no. 3, pp. 377-391, 2008.
- 4) Christos Nikolaos E. Anagnostopoulos, Ioannis E. Anagnostopoulos, Vassili Loumos, and Eleftherios Kayafas, "A License Plate-Recognition Algorithm for Intelligent Transportation System Applications," pp. 377- 392, 2006.
- 5) Fink O (2008) Vulnerability Identification.
- 6) Kim KK, Kim KI, Kim JB, Kim HJ (2000) Learning Based Approach for License Plate Recognition, Neural Networks for Signal Processing. IEEE Signal Processing Society Workshop 2: 614-623.
- 7) Massoud MA, Sabee M, Gergais M, Bakhit R (2013) Automated NEW LICENSE Plate Recognition in Egypt. Alexandria Engineering Journal 52: 319-326.

- 8) You-Shyang Chen and Ching-Hsue Cheng, "A Delphi- based rough sets fusion model for extracting payment rules of vehicle license tax in the government sector," Expert Systems with Applications, vol. 37, no. 3, pp. 2161- 2174, 2010.
- 9) Zhao B, Liu Y, Xia SW (2000) Support Vector Machine and Its Application in Handwritten Numeral Recognition. Proceeding's 15th International Conference on Pattern Recognition 2: 720-723.
- 10)Zheng, He, Wu, Hintz (2005) Character Recognition of Car Number Plates. International Conference on Computer Vision 1: 33-39.
- 11)Zheng Y, Li H, Doermann DS (2004) Machine Printed Text and Handwriting Identification in Noisy Document Images. IEEE Transactions on Pattern Analysis and Machine Intelligence 26: 337-353.

APPENDICES

1) Source Code:

```
import numpy as np
import cv2
from copy import deepcopy
from PIL import Image
import pytesseract as tess
import numpy as np
import smtplib
import imutils
import sys
import pytesseract
import pandas as pd
import time
def preprocess(img):
    cv2.imshow("Input",img)
    imgBlurred = cv2.GaussianBlur(img, (5,5), 0)
    gray = cv2.cvtColor(imgBlurred, cv2.COLOR_BGR2GRAY)

    sobelx = cv2.Sobel(gray, cv2.CV_8U,1,0, ksize=3)
    cv2.imshow("Sobel", sobelx)
    #cv2.waitKey(0)
```

```

    ret2, threshold_img = cv2.threshold(sobelx,0,255,
cv2.THRESH_BINARY+cv2.THRESH_OTSU)
    cv2.imshow("Threshold", threshold_img)
    #cv2.waitKey(0)
    return threshold_img

def cleanPlate(plate):
    print ("CLEANING PLATE. . .")
    gray = cv2.cvtColor(plate, cv2.COLOR_BGR2GRAY)
    #kernel = cv2.getStructuringElement(cv2.MORPH_CROSS, (3, 3))
    #thresh= cv2.dilate(gray, kernel, iterations=1)

    _, thresh = cv2.threshold(gray, 150, 255, cv2.THRESH_BINARY)
    contours, hierarchy = cv2.findContours(thresh. Copy (), cv2.RETR_EXTERNAL,
cv2.CHAIN_APPROX_NONE)

    if contours:
        areas = [cv2.contourArea(c) for c in contours]
        max_index = np. argmax(areas)

        max_cnt = contours[max_index]
        max_cntArea = areas[max_index]
        x, y, w, h = cv2.boundingRect(max_cnt)

        if not ratioCheck (max_cntArea, w, h):
            return plate, None

        cleaned_final = thresh[y:y+h, x:x+w]
        cv2.imshow("Function Test",cleaned_final)
        return cleaned_final, [x,y,w,h]

    else:
        return plate,None

def extract_contours(threshold_img):
    element = cv2.getStructuringElement(shape=cv2.MORPH_RECT, ksize=(17, 3))
    morph_img_threshold = threshold_img.copy()
    cv2.morphologyEx(src=threshold_img, op=cv2.MORPH_CLOSE,
kernel=element, dst=morph_img_threshold)

```

```

cv2.imshow("Morphed",morph_img_threshold)
cv2.waitKey(0)

contours, hierarchy=
cv2.findContours(morph_img_threshold,mode=cv2.RETR_EXTERNAL,method=cv2.CHAIN_APPROX_NONE)
return contours

def ratioCheck(area, width, height):
    ratio = float(width) / float(height)
    if ratio < 1:
        ratio = 1 / ratio

    aspect = 4.7272
    min = 15*aspect*15 # minimum area
    max = 125*aspect*125 # maximum area

    rmin = 3
    rmax = 6

    if (area < min or area > max) or (ratio < rmin or ratio > rmax):
        return False
    return True

def isMaxWhite(plate):
    avg = np.mean(plate)
    if(avg>=115):
        return True
    else:
        return False

def validateRotationAndRatio(rect):
    (x, y), (width, height), rect_angle = rect

    if(width>height):
        angle = -rect_angle
    else:
        angle = 90 + rect_angle

```

```

if angle>15:
    return False

if height == 0 or width == 0:
    return False

area = height*width
if not ratioCheck(area,width,height):
    return False
else:
    return True

def cleanAndRead(img,contours):
    #count=0
    print(len(contours))
    for i, cnt in enumerate(contours):
        min_rect = cv2.minAreaRect(cnt)
        print(min_rect)

        if validateRotationAndRatio(min_rect):

            x, y, w,h = cv2.boundingRect(cnt)
            plate_img = img [y:y+h, x:x+w]
            print ('-----')
            print(plate_img)

            if(isMaxWhite(plate_img)):
                #count+=1
                clean_plate, rect = cleanPlate(plate_img)
                print ('-----')
                print(rect)

                if rect:
                    x1, y1, w1, h1 = rect
                    x, y, w, h = x+x1, y+y1, w1, h1
                    cv2.imshow("Cleaned Plate", clean_plate)
                    cv2.waitKey(0)

```

```

plate_im = Image.fromarray(clean_plate)
text = tess. image_to_string (plate_im, lang='eng')
print ("Detected Text: ", text)
if ("PGeMN112" in text):
    # creates SMTP session
    s = smtplib.SMTP('smtp.gmail.com', 587)
    # start TLS for security
    s.starttls()
    # Authentication
    s.login ("info.acdtest@gmail.com",
"Dob11011993")

    # message to be sent
    message = "Detected "+text
    # sending the mail
    s.sendmail("info.acdtest@gmail.com",
"s.sowmisathiya2012@gmail.com", message)
    # terminating the session
    s. quit ()

img = cv2.rectangle(img,(x,y),(x+w,y+h),(0,255,0),2)
cv2.imshow("Detected Plate",img)
cv2.waitKey(0)

#print "No. of final cont: ", count

if __name__ == '__main__':
    print ("DETECTING PLATE . . .")

    img = cv2.imread("testData/Cars4.png")
    #img = cv2.imread("car.jpeg")

    threshold_img = preprocess(img)
    contours = extract_contours(threshold_img)
    pytesseract.pytesseract.tesseract_cmd = 'C:\Program
Files\Tesseract-OCR\tesseract.exe'
    #image = cv2.imread('car.jpeg')

    image = imutils.resize(img, width=500)

```

```

cv2.imshow("Original Image", image)

gray = cv2.cvtColor(image, cv2.COLOR_BGR2GRAY)
cv2.imshow("1 - Grayscale Conversion", gray)

gray = cv2.bilateralFilter(gray, 11, 17, 17)
cv2.imshow("2 - Bilateral Filter", gray)

edged = cv2.Canny(gray, 170, 200)
cv2.imshow("4 - Canny Edges", edged)

(cnts, _) = cv2.findContours(edged.copy(), cv2.RETR_LIST,
cv2.CHAIN_APPROX_SIMPLE)
cnts = sorted(cnts, key=cv2.contourArea, reverse=True)[:30]
NumberPlateCnt = None

count = 0
for c in cnts:
    peri = cv2.arcLength(c, True)
    approx = cv2.approxPolyDP(c, 0.02 * peri, True)
    if len(approx) == 4:
        NumberPlateCnt = approx
        break

# Masking the part other than the number plate
mask = np.zeros(gray.shape, np.uint8)
new_image = cv2.drawContours(mask, [NumberPlateCnt], 0, 255, -1)
new_image = cv2.bitwise_and(image, image, mask=mask)
cv2.namedWindow("Final_image", cv2.WINDOW_NORMAL)
cv2.imshow("Final_image", new_image)

# Configuration for tesseract
config = ('-l eng --oem 1 --psm 3')

# Run tesseract OCR on image
text = pytesseract.image_to_string(new_image, config=config)

# Data is stored in CSV file
raw_data = {'date': [time.asctime(time.localtime(time.time()))],

```

```

        'v_number': [text]}

df = pd.DataFrame(raw_data, columns=['date', 'v_number'])
df.to_csv('data.csv')

# Print recognized text



print(text)
if("WOR SIGK" in text):
    print(text+"Mail send-----")
    s = smtplib.SMTP('smtp.gmail.com', 587)
    # start TLS for security
    s.starttls()
    # Authentication
    s.login("lrvehiclealert@gmail.com", "alert@123")
    # message to be sent
    message = "Traffic E-Challan Ap2952896089800688 for Rs.1000/- for
vehicle " + text
    # sending the mail
    s.sendmail("lrvehiclealert@gmail.com", "hanushajetti1999@gmail.com",
message)
    # terminating the session
    s.quit()


cv2.waitKey(0)
cleanAndRead(img, contours)


if len(contours)!=0:
    print( len(contours)) #Test
    cv2.drawContours(img, contours, -1, (0,255,0), 1)
    cv2.imshow("Contours",img)
    cv2.waitKey(0)


```

2) Screen Shoots:









3) Publication:

ABSTARCT:

Signage is an advanced picture handling innovation that utilizes a tag to distinguish a vehicle. The objective is to make a superior vehicle ID framework utilizing a vehicle enrollment number. The framework can be carried out locally to screen the security of seriously confined regions, like military zones and encompassing regions. The Legislature, the Supreme Court, and so on ... Change the dim vehicle tag This data can be utilized to track down the proprietor of the vehicle, where to enlist, address, etc. The framework is carried out

utilizing Python, and its presentation is tried on a genuine guide. Studies have shown that the 006Cly framework functions admirably and perceives vehicle enlistment numbers for genuine photographs.

Keywords- *Number Plate Recognition, Machine Learning, ANN, License plate detection*

INTRODUCTION

As of late, the license plate recognition (LPR) has become one of the main vehicle controls. It very well may be utilized in

numerous public spots to accomplish specific capacities like street wellbeing, programmed charge assortment, leaving framework, and vehicle leaving. The ANPR calculation is for the most part isolated into four classes: (1) Vehicle show (2) Display of show plates (3) Design area, (4) Characteristics. As you can find in Figure 1, the initial phase in snapping a picture of a vehicle appears to be straightforward, however it is extremely challenging in light of the fact that it is extremely challenging to snap a picture of a vehicle moving continuously. Vehicle enrollment numbers, particularly vehicle enlistment numbers, should be taken out. As of now, most frameworks have under 50 ms to recognize and handle the plates. The accomplishment of the fourth step relies upon how the second and third steps can get the vehicle number and the distinction between each letter. These frameworks utilize various strategies to observe the vehicle number and afterward remove the vehicle number from the picture.

Numerous ANPR frameworks utilize conventional techniques like organization associations, rapid organization, optical sign acknowledgment, highlights, MATLAB, tradable strategies, sliding between Windows, and BP organizations. . , upholds vector machine (SVM), discrete activities, area based, shading allotment, fluffy calculation, invariance transformation, trichromatic pictures, early technique, weight change distance, vehicle number - division of resources. The quantity of vehicles is obvious. A few scholars center around further developing

low-goal pictures utilizing super-goal procedures. Some of the time, it is important to survey the nature of the ANPR framework. This plainly clarifies the positive appraisal by ANPR. A top to bottom investigation of vehicle number is displayed here. In this book, the vehicle number is a similar vehicle number.

LITERATURE REVIEW

Advanced picture handling is the utilization of PC calculations to process, use, and decipher pictures. As a rancher, you assume a significant part in numerous areas of day to day existence. Despite the fact that picture improvement itself has been exceptionally fruitful, research is being done on picture search, utilizing it to more readily arrange, and Advanced Learning (Machine Learning as a feature of the more extensive local area). Promoting vehicle tags is one of the main themes in Computer Vision. Since the vehicle enrollment number is the vehicle's unique and planned element, it has many periods of the program. With respect to the Ethiopian plates, they have unique elements, for example, Amhar letters, various sizes and plaques. Despite the fact that exploration has been done on ELPR, endeavors have been made to utilize traditional imaging innovation, however it has never been contemplated top to bottom. The momentum concentrate on expects to resolve the issue of ELPR, just as top to bottom exploration and picture improvement. TensorFlow will be utilized to make an inside and out study and

picture handling framework utilizing OpenCV-Python. Along these lines, as you complete this review, you will acquire an inside and out take a gander at the manifestations of Ethiopia and the truth that is going to be caught. This page tells the best way to control a vehicle utilizing a speed camera. Getting CCTV accounts continuously is a dreary cycle. To tackle this issue, we use top to bottom examination strategies like One-Eyed (YOLO) to get anything.

The arranged action comprises of four fundamental stages. The initial step is to change over the pictures into pictures and acquaint the machine with each casing. In the subsequent stage, the tag will show up on the apparent vehicle. In the last advance, decide the quantity of intelligible plaques in light of the figure shown. The longing for inside and out learning utilizes the AI library to work with learning. Tamil Nadu plaque pictures are utilized to examine model execution. Vehicle search gives 97% precision, 98% honesty by matching tags, and 90% via vehicle preparing [3].

Assuming the vehicle is unlawful, it tends to be a drawn-out, tedious work and truly challenging to track down. The recognized logo will show up on the client's picture and will be filed alongside the time and date utilized. It is smarter to lessen security issues and increment stopping security. PC innovation assumes a key part in this number plate move project. A video was taken from the video to recognize the characters. In light of the above framework, the procedure of deciding the

construction from the picture recognizes valid and bogus plaques. In the venture, we show the quantity of plaques that not entirely settled from the AI calculation introduced in the framework [4].

Machine acknowledgment is an important capacity of a reconnaissance framework. This report presents a preparation-based technique for vehicle enlistment. The entire interaction is partitioned into three phases, to be specific taking pictures, finding the tiles, and perceiving the numbers on the tiles. The HOG capacities are utilized for the end goal of preparing, and the Support Vector Machine is utilized for grouping purposes and is over almost 100% precise during recognizable proof. The calculation has been tried on in excess of 100 pictures. As of late, vehicle number plate ID (LPR) has turned into a key application innovation for security and traffic applications, going from traffic signal to leaving access control and data management¹. Basically, LPR recognizes vehicles and gives direction to additional vehicle observing and execution analysis¹. Vehicle tag recognizable proof (LPR) assumes a significant part in an assortment of uses, including solo leaving, confined region security control, transit regulation requirement, blockage estimating, and cost assortment. LPR methods change from one program to another, contingent upon various workplaces. The vast majority of the past work has some way or another restricted working conditions, like indoor landscape, fixed foundation, consistent lighting, confined speed of vehicles, or a specific distance between the camera and the vehicle. ¹². The reason for this study is

to decrease the majority of these restrictions. [8].

EXISTING SYSTEM:

The vehicle business is developing massively each day, making it truly challenging to control vehicles. There is a colossal interest for a more secure way of life and the travel industry among the populace, which offers a mechanized framework to screen high velocity vehicles with the assistance of reconnaissance cameras out and about. As an afterthought. Getting CCTV film on a constant foundation is an exceptionally monotonous cycle. To tackle this issue, you utilize a successful top to bottom preparation model, for example, a one-time look (YOLO), to identify objects. The proposed work comprises of four primary stages.

PROBLEM STATEMENT:


Over the most recent couple of many years, the quantity of current street networks at the nearby, city, and public levels has expanded. This required viable traffic light and the executives. The objective of this undertaking is to make a model that can perceive and recognize vehicle numbers from their pictures. Extra examination is as yet required because of various attributes, for example, the tag framework, shading, image language, style, and size of the tag. The primary reason for the proposed framework is to comprehend the Convolutional Neural Network and use it in number acknowledgment frameworks. Utilizing cctv isn't successful for checking. Utilizing

a calculation is a sluggish cycle. Taking pictures isn't clear the drawing system is somewhat flawed


PROPOSED SYTEM:

The initial phase in deciding the number is to gather a data set from Kaggle.com, one of the most famous and entrusted locales with an assortment of data. In this data set, the enrollment number incorporates different vehicle numbers from various states. The subsequent stage is to set up the information utilizing the informational collection from Kaggle. The framework is carried out utilizing Python, and its presentation is tried, in actuality. Studies have shown that a high-level framework can precisely decide the quantity of a vehicle in genuine photographs.

Block diagram:



Flow diagram:



METHODOLOGY

Gray scale conversion

The changing shade of the inherent texture is installed in the green picture. The initial phase in pre-handling is to change the dark RGB picture. The principle motivation behind utilizing shading change is to decrease the quantity of tones. Think about the pieces of R, G, and B from the 24-bit tone (I, j) of every pixel and ascertain the worth of the 8-cycle tree [9]. Presently take the weighted normal of the RGB worth and convert the RGB picture to the diminished picture, New dim picture = $((0.299 \times R) + (0.59 \times G) + (0.11 \times B)) \dots$ (1)

Edge detector

The Image Size Tool can hold the right picture handling mode. Distinguishing the sides that assistance to recognize sharp impediments. It is a generally expected method for distinguishing genuine boundaries to energy. The limit is between the two zones contrasted with the different dim elements. Distinguish the sides of the multiplier, for example, sobel, log, shrewd, prewitt, from there, the sky is the limit. The Canny client is intended to be the best sensor on the lookout. Shading catches the picture as info and emanates the picture demonstrating where the energy is going.

Dilation

Development is one of the two most significant capacities as far as morphology, and the other is deterioration. It is generally utilized for two pictures, yet there are possibilities for working with pictures of garments. The principle impact of parallel is to steadily expand the front pixel limits (for instance, white pixels) areas. Consequently, as the interior pixel expands, the quantity of openings around there diminishes. Extension of exercises takes up two pieces of the income stream. The initial segment of the picture is wide. The subsequent part is a little area comprising of a progression of purported useful components (additionally called beginnings). It is the build that decides the genuine impact of growing the info card. Extend f to the picture f for the build given by fs, the develop s are situated at the beginning (x, y), and the worth of the new not entirely set in stone fair and square:

1 assuming s is fg $(x, y) = \{\dots \dots$

..... (2)
 0 at the end of the day

Erosion

Deterioration is one of the two most significant elements of science and the other is development. It is for the most part a double picture, however there is a variant that deals with surfaces. The primary impact of double is to eliminate the lines of the inward pixel (for instance, white pixels) locales. Therefore, the front of the front pixel shrivels and the openings in those parts become bigger. The worth-based client gets two data and enters it. The initial segment is an image of dress and crying. The second is a mix of (typically little) blends of alleged productive components (otherwise called centers). It is the structure material that decides the impact of wearing on the section card

Holes filling

An opening can be characterized as the region around a line that associates a pixel limit. Accept that every limit around the back (opening) is a bunch of 8 limit components. The intention is to fill every one of the openings together, considering the places of each opening (in the two pictures). We start to make a variety of X0 from the zero put on one (the main thing to clarify), with the exception of the situation in X0 comparative with a given point in each opening. Presently the accompanying method fills every one of the openings: $X_k B = \bigoplus \bigcap (k-1) A \dots \dots \dots$

..... SetXk currently all containing openings; The intersection of Xk and A contains openings loaded up with their limits. The expansion fills the caution when uncontrolled. Be that as it may, consolidating each progression and finishing the limits makes an appealing district. This is an outline of how to design the morphological cycle to match the ideal qualities.

Opening and closing

Open and close Open and close are two significant numerical things. Both are gotten from the essential elements of mileage. In spite of the fact that there is a clothing classification, the equivalent is valid for the ones regularly utilized in the two pictures. The fundamental impact of the opening is that disintegration will in general eliminate a portion of the internal (white) parts from the side of the inward pixel zone. Notwithstanding, it is for the most part not any more unsafe than disintegration. Like other morphologists, its actual not set in stone by its underlying properties. The client impact can be to keep an area with a similar design or to contain every one of the primary components, while eliminating all the front pixel zones, opening the accompanying additions, and extending involving a comparative construction for the two capacities. Along these lines, the initial client is needed to open two info pictures with primary components. The kickoff of the piece of clothing layer comprises just of the wear layer and afterward the piece

of clothing layer. Opening is a two-way lock, which includes opening the front pixels with unique underlying components comparable to locking the back pixels with a similar thing. The launch of type An is portrayed by AoB and is characterized as a part of wear and extension [15,16]. $AoB = (A \ominus B) \oplus B \dots \dots \dots$, tiny particles, branches. Shutting Figure An in B: $A \bullet B = (A \oplus B) \ominus B \dots \dots \dots$

Normalized cross

It is generally Cross-Link Image Processing, and the picture first gets back to typical on the grounds that the light and style of the picture fluctuate contingent upon the lighting and brightening. This is typically done at each progression of the ordinary dissemination and division process. Ordinary Correlation with Emp Method Light and example might shift contingent upon the lighting and enlightenment. This is generally done at each progression of the typical conveyance and division process. Typical correspondence is a technique used to find protests that address models, activities, and objects. Another two-way Pearson item time relationship coefficient [1]. If $f(n1, n2)$ is the comparing figure in $g(n1, n2)$, the essential and capacity capacities can be determined by taking the DFT of the first and second pictures and afterward duplicating the DFT of the main picture by the complex form. In the wake of isolating the DFT and arrangements of the second consider along with outright qualities, we match the period of the recipe and afterward arrive at the pinnacle of the capacity worth to get the IDFT.

Algorithms

Step 1: Take a photograph of the camera.
Step 2: Change the picture shipped off the dim line.

Step 3: Use the Sobel Identification Method.

Step 4: Control the boundary until the shore is apparent.

Step 4: Do the extension work. Stage 5: Fill the opening in the image.

Step 6: Perform depreciation exercises.
Step 7: Use a channel.


Step 8: Number of letters and numbers.
Step 9: Calculate the communication top for the store

Artificial Neural Network

A muscle network is an AI calculation in light of human standards. ... It works like a human cerebrum handling data. The ANN incorporates a number that joins the handling units that cooperate in information handling. They additionally give commonsense arrangements. Neural organizations are a gathering of calculations that give essential correspondence in the field of data that takes after the human mind. The neural organization assists with changing the information so the organization can give better outcomes without changing the result plan.

ANN is a kind of PC program that can "instruct" connections in the media. On the off chance that ANN is "prepared", it tends to be utilized to uncover the result of new data, other mind boggling or befuddling

techniques. ANNs are a significant instrument in AI. This is a framework that takes in and initiates the mind's cerebrum and imitates the manner in which we learn.



Working of ANN

The primary portrayal enters the passage and moves to the secret area, and the blend of the two classifications disseminates the load to the top situation for every section. then, at that point, the predisposition is added to each info neuron, and afterward a weighty and one-sided total is gone through the weighty errand. The usefulness of the capacity on the open hub is to download the capacity, and afterward the shading is yield. This entire cycle is called progress. When the result is caught, contrasted with the first result, the blunder is accounted for, and afterward changed by changing the load to lessen the mistake, an interaction that takes a specific measure of time (causes). Then, at that point, the model weight is changed and anticipated.

CONCLUSION

The ANPR framework for different exercises was carried out utilizing the IMAGEAI structure, and NVIDIA Jetson Nano gear was utilized in the preparation. At first, the morphology was utilized to recognize the machine numbers, the presentation was dissected, and the calculation performed inadequately in high light. From that point onward, the edge discovery calculation is carried out and the nearby movement increments. At last, YOLO utilizes the IMAGEAI work which

is more helpful than understanding. Everything store organizations can be executed in IMAGEAI, and the framework is prepared to know vehicles and to know numbers. Working on the presentation of the organization, the organization norms of the gear have been carried out and troublesome code has been diminished utilizing this level. The framework was tried earth and the machines were quickly distinguished. Associating portions of a Slab should be associated with a segment line and should be associated with a segment line

RESULTS

Framework execution estimations were performed by looking at the genuine framework results utilizing a standard calculation and the calculation work calculation to match the model's feedback. Subsequent to applying the information base to the quantity of pictures, Table 3 was investigated and presumed that the standard approach to connecting things to discover the realities was right, the approach to connecting the classes, the standard approach to distinguishing the

connections was 67.98%, and the connecting of the classifications was 63.46%. Different morphological exercises have been done on the Nepal level, like development, disintegration, better agreement, filling, opening and shutting, to change the plate and decrease the picture. Utilizing the calculation part, decrease the picture isolated into long-lasting size areas and compute the relationship to the archive utilizing the calculation change model.

REFERENCE PAPERS:

1. Anton Satria Prabuwono and Ariff Idris, "A Study of Car Park Control System Using Optical Character Recognition ," in International Conference on Computer and Electrical Engineering, 2008, pp. 866-870.
2. A Albiol, L Sanchis, and J.M Mossi, "Detection of Parked Vehicles Using Spatiotemporal Maps," IEEE Transactions on Intelligent Transportation Systems, vol. 12, no. 4, pp. 1277-1291, 2011.
3. Christos Nikolaos E. Anagnostopoulos, Ioannis E. Anagnostopoulos, Ioannis D. Psoroulas, Vassili Loumos, and Eleftherios Kayafas, License Plate Recognition From Still Images and Video Sequences: A Survey, vol. 9, no. 3, pp. 377-391, 2008.
4. Christos Nikolaos E. Anagnostopoulos, Ioannis E. Anagnostopoulos, Vassili Loumos, and Eleftherios Kayafas, "A License Plate-Recognition Algorithm for

Intelligent Transportation System Applications," pp. 377- 392, 2006.

5. Massoud MA, Sabee M, Gergais M, Bakhit R (2013) Automated NEW LICENSEPLATE Recognition in Egypt. Alexandria Engineering Journal 52: 319-326.
6. Fink O (2008) Vulnerability Identification.
7. Zheng, He, Wu, Hintz (2005) Character Recognition of Car Number Plates. International Conference on Computer Vision 1: 33-39.
8. Kim KK, Kim KI, Kim JB, Kim HJ (2000) Learning Based Approach for License Plate Recognition, Neural Networks for Signal Processing. IEEE Signal Processing Society Workshop 2: 614-623.

Bibliography



Master Jetti Lakshmi Prasanna graduating from the beloved university Sathyabama Institute of Science and Technology in the stream of Computer Science and Engineering has excelled in this stream. Her research interest is Machine Learning, Neural Network and Web Development.



Master Ragala

Hymavathi graduating from the beloved university Sathyabama Institute of Science and Technology in the stream of Computer Science and Engineering has excelled in this stream. Her research interest is Machine Learning, Neural Network and Cyber Security.



Dr.S. Prince Mary M.E.,

Ph. D, Assistant professor in the Department of Computer Science and Engineering at Sathyabama Institute of Science and Technology in Chennai. Her area of specialization is Database Management Systems, Data Mining, Machine Learning, and Data Analytics. She has authored in various reputed conferences and in international journals.