

PROFESSIONAL TRAINING REPORT
at
Sathyabama Institute of Science and Technology
(Deemed to be University)

Submitted in partial fulfillment of the requirements for the award of
Bachelor of Engineering in Computer Science And Engineering

By

Galla Thrinadh
(REG. NO. 38110149)

C.S. Geethik Reddy
(REG.NO. 38110160)



**DEPARTMENT OF COMPUTER SCIENCE AND
ENGINEERING**

SCHOOL OF COMPUTING

SATHYABAMA INSTITUTE OF SCIENCE AND TECHNOLOGY

**JEPPIAAR NAGAR, RAJIV GANDHI SALAI,
CHENNAI – 600119, TAMILNADU**



SATHYABAMA
INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)

Accredited with Grade “A” by NAAC

(Established under Section 3 of UGC Act, 1956)

JEPPIAAR NAGAR, RAJIV GANDHI SALAI

CHENNAI– 600119

www.sathyabama.ac.in



DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of **THRINADH. G (Reg. No: 38110149) GEETHIK REDDY. C. S (Reg. No: 38110160)** who carried out the project entitled “**Adaptive Transmission Of Sensitive Information In Online Social Networks**” under my supervision from June 2021 to November 2021.

Internal Guide

MS. R. Yogitha, M.E.,

Ph.D.,

Head of the Department

Dr. L. Lakshmanan, M.E., Ph.D.,

Dr. S. VIGNESHWARI, M.E., PH.D.,

Submitted for Viva voce Examination held on _____

Internal Examiner

External Examiner

DECLARATION

I, **THRINADH.G (REG.NO: 38110149)**, **GEETHIK REDDY (REG.NO: 38110160)** hereby declare that the project report entitled **Adaptive Transmission Of Sensitive Information In Online Social Networks** done by me under the guidance of **MS. R. YOGITHA** is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering Degree in Computer Science and Engineering.

DATE: 01-03-2022

PLACE: CHENNAI

SIGNATURE OF THE CANDIDATE

ACKNOWLEDGEMENT

I am pleased to acknowledge my sincere thanks to **Board of Management** of **SATHYABAMA** for their kind encouragement in doing this project and for completing it successfully. I am grateful to them.

I convey my thanks to **Dr. T. Sasikala M.E., Ph.D, Dean**, School of Computing, **Dr. S. Vigneshwari M.E., Ph.D.,** and **Dr. L. Lakshmanan M.E., Ph.D., Head of the Department of Information Technology** for providing me necessary support and details at the right time during the progressive reviews.

I would like to express my sincere and deep sense of gratitude to my Project Guide **MS. R. YOGITHA M.E., Ph.D.,** for her valuable guidance, suggestions and constant encouragement paved way for the successful completion of my project work.

I wish to express my thanks to all Teaching and Non-teaching staff members of the **Department of Computer Science And Engineering** who were helpful in many ways for the completion of the project.

ABSTRACT

The cascading of sensitive information such as private contents and rumors is a severe issue in online social networks. One approach for limiting the cascading of sensitive information is constraining the diffusion among social network users. However, the diffusion constraining measures limit the diffusion of non-sensitive information diffusion as well, resulting in the bad user experiences. To tackle this issue, in this paper, we study the problem of how to minimize the sensitive information diffusion while preserve the diffusion of non-sensitive information, and formulate it as a constrained minimization problem where we characterize the intention of preserving non-sensitive information diffusion as the constraint. We study the problem of interest over the fully-known network with known diffusion abilities of all users and the semi-known network where diffusion abilities of partial users remain unknown in advance. By modeling the sensitive information diffusion size as the reward of a bandit, we utilize the bandit framework to jointly design the solutions with polynomial complexity in the both scenarios. Moreover, the unknown diffusion abilities over the semi-known network induce it difficult to quantify the information diffusion size in algorithm design. For this issue, we propose to learn the unknown diffusion abilities from the diffusion process in real time and then adaptively conduct the diffusion constraining measures based on the learned diffusion abilities, relying on the bandit framework. Extensive experiments on real and synthetic datasets demonstrate that our solutions can effectively constrain the sensitive information diffusion, and enjoy a 40%less diffusion loss of non-sensitive information comparing with four baseline algorithms.

Table of Contents

ACKNOWLEDGEMENT	i
DECLARATION	ii
ABSTRACT	iii
Chapter -1	1
1. Introduction	1
1.2 Existing System	2
1.3 Proposed System	3
Chapter -2	4
2. Literature Survey	4
Chapter -3	7
3. Analysis	7
3.1 Feasibility Study	8
3.2 Performance Requirements	9
3.2.1 Hardware Requirements	13
3.2.2 Software Requirements	14
Chapter -4	15
4. Design	15
4.1 Class Diagram	15
Chapter -5	17
5. Methodology	17
Chapter -6	22
6. Implementataion	22
6.1 Introduction	22
6.2 Sample Code	54
Chapter -7	55
7. Testing	55

7.1 UnitTesting	55
7.2 Integration Testing	56
7.3 Functional Test	56
7.4 System Test	57
Chapter -8	58
8. Results and Discussion	58
Chapter -9	61
9. Conclusion	61
Chapter -10	62
10. Refference	62
Chapter-11	66
11. Appendix	66
Chapter -12	73
12. Excussion Process	73

List of Figures

S. No.	Figure No.	Figure Name	Page No.
01	4.1.1	Class Diagram	16

List Of Screens

S. No.	Figure No.	Screen Name	Page No.
01	11.1	Home Page	66
02	11.2	View All Images	66
03	11.3	User Image	67
04	11.4	Image Server	68
05	11.5	User Transaction	69
06	11.6	View Distance Of Images	70
07	11.7	Upload Image Details	71

Chapter - 1

INTRODUCTION

The prevalence of online social networks such as Facebook, Twitter and Wechat facilitates the information diffusion among users, and thus enables the efficient promotion of positive information's, e.g., products, news, innovations [1]- [8]. Although such efficient diffusion can easily lead to large- scale diffusion called information cascading, the unconstrained cascading behavior could meanwhile cause the sensitive information to be incautiously diffused over the network [9]- [20]. Here the sensitive information refers to any kind of information that needs to be prohibited from cascading such as rumors, personal contents, and trade secrets. The cascading of such sensitive information may cause the risk of leaking users' privacies or arising panics among publics [9] - [20]. With this concern, several social network medias (e.g., Facebook, Twitter) have claimed authorities to block accounts of users and delete some posts or tweets when they violate relevant rules about privacies or securities [9] [21] [22]. Thus network managers are able to take measures to prohibit the cascading of sensitive information.

The existing attempts that share the closest correlation with prohibiting sensitive information diffusion belong to the rumor influence minimization [9]- [20], whose current strategies can mainly be classified into two aspects. The first is diffusing the truths over network to counteract rumors [12]- [14]. However, diffusing truths is only suitable for constraining the rumors, while is not suitable for constraining the diffusion of the other kinds of sensitive information's, including personal information's, trade secrets, and etc. The second is temporarily blocking a number of users with high diffusion abilities [9] [10] [15] [16] or blocking a number of social links among users [17]- [20] in hope of minimizing the diffusion of a rumor. Although such strategy is effective for preventing rumors about some significant events like earthquakes, terrorist attacks and political elections, it is unrealistic for network managers to adopt this strategy on constraining the diffusion of sensitive information's with various contents that widely exist in our daily lives. If network managers take such measure, it is required to block a much larger size of users or links. Then two critical problems arise. Firstly, blocking too many users or social links will degrade user experiences and may arouse complaints for the right violation. Secondly, blocking users or social links for restraining rumors also brings the loss of the diffusion of positive information's, say information loss, which is not beneficial to the viral marketers that utilize information cascading to promote products.

EXISTING SYSTEM

The existing attempts that share the closest correlation with prohibiting sensitive information diffusion belong to the rumor influence minimization, whose current strategies can mainly be classified into two aspects.

- The first is diffusing the truths over network to counteract rumors. However, diffusing truths is only suitable for constraining the rumors, while is not suitable for constraining the diffusion of the other kinds of sensitive informations, including personal informations, trade secrets, and etc.
- The second is temporarily blocking a number of users with high diffusion abilities or blocking a number of social links among users in hope of minimizing the diffusion of a rumor.

PROPOSED SYSTEM

- To tackle the above challenges, we utilize the constrained combinatorial multi-arm bandit framework to jointly design our solutions over the fully- known and semi-known networks, where we take the diffusion size of sensitive informations as the reward of a bandit and model the probability variations as the arms in bandit.
- With this mapping, we determine the probability variations through a constrained arms picking process with the aim of minimizing the obtained rewards.
- Through incorporating the constraint of diffusion probability variations into the construction of the arms of bandit, we relax the problem of interest into an unconstrained minimization problem when determining the diffusion probability variations based on the arms.

Introduction

- This enables us to determine the probability variations via social 1. <https://www.douban.com/> links with high efficiency.
- Furthermore, for coping with the unknown diffusion abilities over the semi-known network, we propose to iteratively learn the unknown diffusion abilities through learning the reward distributions of the arms based on the rewards obtained from previously picked arms, and then determine the diffusion probability variations based on the learned reward distributions of arms.

LITERATURE SURVEY

Regarding the limitations of existing solutions, in this paper, we take the first look into limiting the cascading of sensitive informations while preserving the diffusion of non-sensitive ones to lower the information loss. Considering the randomness of the users accepting informations diffused from their social neighbors, we adopt the widely used random diffusion model that each user diffuses information to his social neighbor successfully with a diffusion probability via the social link between them. Then our technical objective is adjusting the diffusion probabilities via social links to minimize the diffusion size of sensitive informations, under the constraint of keeping the value of the sum of diffusion probabilities via all social links. Corresponding to the reality, we consider a case where some advertisements in viral marketing and some rumors simultaneously diffuse over an online social network. In this case, decreasing diffusion probabilities models the measures such as deleting partial posts or fanpages reposted by users [25] [26], while the measures for increasing diffusion probabilities include sticking and adding pushes or deliveries of the posts reposted by given users

[16] [27]. Then, if network managers decrease the diffusion probability from a user holding rumors, the advertisements diffused from the user will inevitably be constrained as well. Thus, for lowering the diffusion loss of the advertisements and preserving the global diffusion ability of the whole network on diffusing non-sensitive informations, a natural approach is increasing the diffusion probabilities from one or more other users which hold the advertisements. We study the problem of interest on both fully-known and semi-known networks which are the two main scenarios considered in current studies on information diffusion [1]- [16]. Over the fully-known network, we assume network managers know the diffusion abilities of all users. The examples for the fully-known network lie on the social networks for enterprises (e.g., Skype) or special interest groups (SIGs) (e.g., Douban¹). As the full topology of a local social network, which consists of the staff of a same enterprise or the members in a same SIG, is available to network managers, it is feasible to quantify the diffusion abilities of all users. On the contrast, the semi-known network here refers to the case that diffusion abilities of partial users remain unknown in advance. For example, the data of Facebook was reported to be utilized to influence the 2016 election in the US, which then led to a severe trust

crisis for Facebook. Thus, due to the privacy concern and potential side effect, even for network managers, it is difficult to obtain the full topology of some global large scale social networks like Facebook, Wechat. Unless the full network topology is known, we cannot evaluate the diffusion abilities of all users.

Over the fully-known network, although we can determine the diffusion probability variations via social links through solving a constrained minimization problem, the huge size of social links in current large scale networks leads to the high complexity of the problem. Moreover, the unknown diffusion abilities of partial users over the semi-known network induce it infeasible to directly solve the constrained minimization problem for minimizing the diffusion size of sensitive informations. To tackle the above challenges, we utilize the constrained combinatorial multi-arm bandit framework to jointly design our solutions over the fully-known and semi-known networks, where we take the diffusion size of sensitive informations as the reward of a bandit and model the probability variations as the arms in bandit. With this mapping, we determine the probability variations through a constrained arms picking process with the aim of minimizing the obtained rewards.

Through incorporating the constraint of diffusion probability variations into the construction of the arms of bandit, we relax the problem of interest into an unconstrained minimization problem when determining the diffusion probability variations based on the arms. This enables us to determine the probability variations via social links with high efficiency. Furthermore, for coping with the unknown diffusion abilities over the semi-known network, we propose to iteratively learn the unknown diffusion abilities through learning the reward distributions of the arms based on the rewards obtained from previously picked arms, and then determine the diffusion probability variations based on the learned reward distributions of arms.

Our main contributions are summarized as follows: (1) We take the first look into minimizing the diffusion size of sensitive informations while preserving the diffusion of non-sensitive ones. We formulate the problem of interest into a constrained minimization problem where we characterize the intention of preserving non-sensitive information diffusions as the constraint. (2) We propose an efficient bandit based framework to jointly explore the solutions over the fully-known and semiknown networks within polynomial running time. Moreover, we design the distributed implementation scheme of our solutions for the further improvement of time efficiency. (3) We

further extend our bandit based solution into a “learning- determining” manner for addressing the challenge of unknown diffusion abilities in semi-known networks. We theoretically prove that the regret bound of our solution is sub-linear to the diffusion time, indicating that the probability variations returned by our solution approximates to the optimal one with the increase of diffusion time. (4) We perform extensive experiments on both real and synthetic social network datasets. The results demonstrate that the proposed algorithms can effectively constrain the diffusion of sensitive informations, and more importantly, enjoy a superiority over four baselines in terms of 40% less information diffusion loss.

3.1 INTRODUCTION:

A Software Requirements Specification (SRS) – a requirements specification for a software system – is a complete description of the behavior of a system to be developed. It includes a set of use cases that describe all the interactions the users will have with the software. In addition to use cases, the SRS also contains non-functional requirements. Non-functional requirements are requirements which impose constraints on the design or implementation (such as performance engineering requirements, quality standards, or design constraints).

System requirements specification: A structured collection of information that embodies the requirements of a system. A business analyst, sometimes titled system analyst, is responsible for analyzing the business needs of their clients and stakeholders to help identify business problems and propose solutions. Projects are subject to three sorts of requirements:

- **Business requirements** describe in business terms what must be delivered or accomplished to provide value.
- **Product requirements** describe properties of a system or product (which could be one of Several ways to accomplish a set of business requirements.)
- **Process requirements** describe activities performed by the developing organization. For instance, process requirements could specify specific methodologies that must be followed, and constraints that the organization must obey.

3.2 FEASIBILITY STUDY:

The feasibility of the project is analyzed in this phase and business proposal is put forth with a very general plan for the project and some cost estimates. During system analysis the feasibility study of the proposed system is to be carried out. This is to ensure that the proposed system is not a burden to the company. For feasibility analysis, some understanding of the major requirements for the system is essential.

Three key considerations involved in the feasibility analysis are

- ECONOMICAL FEASIBILITY
- TECHNICAL FEASIBILITY
- SOCIAL FEASIBILITY

3.2.1 Economical Feasibility:

This study is carried out to check the economic impact that the system will have on the organization. The amount of fund that the company can pour into the research and development of the system is limited. The expenditures must be justified. Thus the developed system as well within the budget and this was achieved because most of the technologies used are freely available. Only the customized products had to be purchased.

3.2.2 Technical Feasibility:

This study is carried out to check the technical feasibility, that is, the technical requirements of the system. Any system developed must not have a high demand on the available technical resources. This will lead to high demands on the available technical resources. This will lead to high demands being placed on the client. The developed system must have a modest requirement as only minimal or null changes are required for implementing this system.

3.2.3 Social Feasibility:

The aspect of study is to check the level of acceptance of the system by the user. This includes the process of training the user to use the system efficiently. The user must not feel threatened by the system, instead must accept it as a necessity. The level of acceptance by the users solely depends on the methods that are employed to educate the user about the system and to make him familiar with it. His level of confidence must be raised so that he is also able to make some constructive criticism, which is welcomed, as he is the final user of the system.

3.3 PERFORMANCE REQUIREMENTS (SDLC):

Structured project management techniques (such as an SDLC) enhance management's control over projects by dividing complex tasks into manageable sections. A software life cycle model is either a descriptive or prescriptive characterization of how software is or should be developed.

But

none of the SDLC models discuss the key issues like Change management, Incident management and Release management processes within the SDLC process, but, it is addressed in the overall project management. In the proposed hypothetical model, the concept of user-developer interaction in the conventional SDLC model has been converted into a three dimensional model which comprises of the user, owner and the developer. In the proposed hypothetical model, the concept of user-developer interaction in the conventional SDLC model has been converted into a three dimensional model which comprises of the user, owner and the developer. The one size fits all approach to applying SDLC methodologies is no longer appropriate. We have made an attempt to address the above-mentioned defects by using a new hypothetical model for SDLC described elsewhere. The drawback of addressing these management processes under the overall project management is missing of key technical issues pertaining to software development process that is, these issues are talked in the project management at the surface level but not at the ground level.

WHAT IS SDLC?

A software cycle deals with various parts and phases from planning to testing and deploying software. All these activities are carried out in different ways, as per the needs. Each way is known as a Software Development Lifecycle Model (SDLC). A software life cycle model is either a descriptive or prescriptive characterization of how software is or should be developed. A descriptive model describes the history of how a particular software system was developed. Descriptive models may be used as the basis for understanding and improving software development processes or for building empirically grounded prescriptive models.

SDLC models

- **The Linear model (Waterfall)** - Separate and distinct phases of specification and development. - All activities in linear fashion. - Next phase starts only when first one is complete.
- **Evolutionary development** - Specification and development are interleaved (Spiral, incremental, prototype based, Rapid Application development) Incremental Model (Waterfall in iteration), RAD (Rapid Application Development) - Focus is on developing quality product in less time.

Spiral Model - We start from smaller module and keeps on building it like a spiral. It is also called Component based development.

- **Formal systems development** - A mathematical system model is formally transformed to an implementation.
- **Agile Methods** - Inducing flexibility into development.
- **Reuse-based development** - The system is assembled from existing components.

The General Model

Software life cycle models describe phases of the software cycle and the order in which those phases are executed. There are tons of models, and many companies adopt their own, but all have very similar patterns. Each phase produces deliverables required by the next phase in the life cycle. Requirements are translated into design. Code is produced during implementation that is driven by the design. Testing verifies the deliverable of the implementation phase against requirements.

SDLC Methodology:

Spiral Model

The spiral model is similar to the incremental model, with more emphases placed on risk analysis. The spiral model has four phases: Planning, Risk Analysis, Engineering and Evaluation. The baseline spiral, starting in the planning phase, requirements is gathered and risk is assessed. Each subsequent spirals builds on the baseline spiral. Requirements are gathered during the planning phase. In the risk analysis phase, a process is undertaken to identify risk and alternate solutions. A prototype is produced at the end of therisk analysis phase. Software is produced in the engineering phase, along with testing atthe end of the phase. The evaluation phase allows the customer to evaluate the output of the project to date before the project continues to the next spiral. In the spiral model, the angular component represents progress, and the radius of the spiral represents cost. Spiral Life Cycle Model.


This document plays a vital role in the development of life cycle (SDLC) as it describes the complete requirement of the system. It means for use by developers and will be the basic during t

testing phase. Any changes made to the requirements in the future will have to go through formal change approval process.

SPIRAL MODEL was defined by Barry Boehm in his 1988 article, “A spiral Model of Software Development and Enhancement. This model was not the first model to discuss iterative development, but it was the first model to explain why the iteration models.

The steps for Spiral Model can be generalized as follows:

- The new system requirements are defined in as much details as possible. This usually involves interviewing a number of users representing all the external or internal users and other aspects of the existing system.
- A preliminary design is created for the new system.
- A first prototype of the new system is constructed from the preliminary design. This is usually a scaled-down system, and represents an approximation of the characteristics of the final product.
- A second prototype is evolved by a fourfold procedure:
 - Evaluating the first prototype in terms of its strengths, weakness, and risks.
 - Defining the requirements of the second prototype.
 - Planning an designing the second prototype.
 - Constructing and testing the second prototype.



Fig

3.3.1

Spiral

Model

Advantages

1. High amount of risk analysis
2. Good for large and mission-critical projects.
3. Software is produced early in the software life cycle

Disadvantages

1. Does not work well for smaller projects.
2. It is not suitable for low risk projects. It is very costly model

3.4 SOFTWARE REQUIREMENTS& HARDWARE REQUIREMENTS:

HARDWARE REQUIREMENTS

- System : Pentium IV 2.4 GHz.
- Hard Disk : 40 GB.
- Floppy Drive : 1.44 Mb.
- Monitor : 15 VGA Colour.
- Mouse : Logitech.
- Ram : 512 Mb.

SOFTWARE REQUIREMENTS

- Operating system : - Windows XP.
- Coding Language : J2EE
- Data Base : MYSQL

Research Roadmap on Information Diffusion is given below.




Fig 4.1 Roadmap

4.1 CLASS DIAGRAM:

A Unified Modeling Language (UML) class diagram is a sort of static structure diagram for software engineering which describes the structure of a system by showing system classes , attributes , operations (or methods) and class relationships. This defines which class contains knowledge.




fig 4.1.1 Class diagram

5.METHODOLOGY

NETWORK MODEL:

We model the online social network as a directed graph $G = (V, E)$, where each node in V ($|V| = n$) represents a user in the network and each directed edge in E ($|E| = m$) represents a social link between a pair of users. We say the node v is a neighbor of node u if there is an edge in E with the source node being u and the destination node being v . Each node is classified as either a sensitive node or a non-sensitive one. In correspondence to social networks, sensitive nodes refer to the individuals who hold sensitive informations (e.g., rumors or private informations of users). Moreover, each edge $i \in E$ has a weight w_i representing the probability that the source it connects can successfully diffuse information to the destination node via it. That is, we assume that the diffusion results via each edge are independent, and the diffusion result via an edge i follows the Bernoulli distribution $B(w_i)$. We assume that the weight on each edge follows a uniform distribution of $U(0, w_{\max})$ ($w_{\max} \in (0, 1)$). As mentioned earlier, we study the adaptive diffusion of sensitive informations over both fully-known and semi known networks. In the sequel, we respectively present the definitions of the two scenarios. Specifically, in our setting, the semi-known network consists of the informed nodes and the uninformed nodes, and the nodes in the fully-known network are all informed.

DIFFUSION MODEL:

Over both the fully-known and semi-known networks, the sensitive informations can only be diffused from the sensitive nodes. We assume there are T time rounds. A non-sensitive node will turn to sensitive once it receives sensitive informations, and from then on until the end of the T rounds, as long as the sensitive informations it holds are not out of date, it will have chance to diffuse sensitive informations to its neighbors. The t -th round refers to the time from time stamp t to $t + 1$. We use V_t to denote the set of the sensitive nodes at time stamp t . We denote the edges whose source nodes are in sensitive as the target edges.

We study the problem of adaptively adjusting diffusion probabilities via edges at the beginning of each round, for taking measures in real time to minimize the sensitive information diffusion. For this end, we define the duration of each round as the time for two-hop diffusion. That is, the informations diffuse two hops during a round. In particular, during each round, the source node of an edge i , say S_i , first diffuses informations I_i to the destination node D_i successfully with probability w_i , and D_i then diffuses the received informations to its neighbors.

Moreover, in the first hop in each round, we define each sensitive source node having a single chance to diffuse sensitive informations to each of its neighbors. If a node receives sensitive informations during the first hop, it further has one chance to diffuse the received sensitive informations to its own neighbors in the second hop. Notably, we define that each sensitive node has the chance to diffuse sensitive informations to their neighbors in each round as long as the sensitive informations it holds are not out of date. Our insight for such definition comes from the real behavior that users of social medias are probably to repeatedly review the Moments or Tweets, which are posted by their friends several days or even several months ago. At the same time, the diffusion of non-sensitive informations also occurs in the network, and is in a same manner with the diffusion of sensitive informations. A node will simultaneously hold and diffuse non-sensitive and sensitive informations, if the node receives the both kinds of informations during diffusion.

ADAPTIVE DIFFUSION IN FULLY-KNOWN NETWORKS:

In the fully-known network, the problem of interest in Eqn. (1) is a classical Linear Programming (LP) problem. However, the classical solutions (e.g., Simplex Algorithm [30], Ellipsoid Algorithm

[31] and Karmarkar Algorithm [32]) for the LP problem cannot be efficiently applied to problem (1) in adaptive diffusion, due to the high dimension of the variable vector. . For the issue of the high complexity of classical solutions, we seek the solution for the adaptive diffusion based on the bandit framework. In particular, we model the probability variation vector in each round as the arm of a bandit, and model the diffusion size of sensitive information as the reward obtained from the bandit after picking such arm. By this, we explore the efficient solution for the adaptive diffusion through exploring efficient arm picking algorithm under the objective of minimizing obtained rewards. In addition, we adopt the bandit framework here also under the consideration that the bandit model will enable us to deal with the partial unknown diffusion abilities in the semi-

known network. That is, we utilize the bandit framework to jointly design the solutions in both the fully-known and semi-known networks.

$$\sum_{t=1}^T \vec{D}^t \cdot (\vec{\beta}_0^t + \Delta \vec{\beta}^t) \quad (1)$$

INTRODUCTION OF THE BANDIT FRAMEWORK:

We seek the solutions for the adaptive diffusion problem by mapping it into a Constrained Combinatorial MultiArm Bandit (CCMAB) framework, which is a variation of the Multi-Arm Bandit (MAB) for coping with the combinatorial optimization problem in online manner. In the general formation of the MAB, there are multiple independent arms that provide stochastic rewards with certain distributions. The objective of the MAB-based optimizing problems is, through sequentially picking an arm in each round based on the reward distributions of arms, maximizing the sum of the rewards obtained from all picked arms. Furthermore, the major feature of the CCMAB framework that we adopt in this paper lies on the dependencies between arms, different from the independences in general MAB model. In each round, for maximizing the obtained rewards, the CCMAB picks a super-arm which consists of a set of base-arms under given constraints. Such feature enables the CCMAB to be adopted in the online combinatorial optimization problems.

Algorithm in Fully-known Network:

Based on the above mappings, the aim of our algorithm for Adaptive Diffusion in Fully-known Network, named ADFN, is selecting a combination of base-arms with the minimum sum of mean rewards. We present the pseudo code of ADFN in Algorithm 1, where we use the combination to denote the set of the selected base-arms. In ADFN, we iteratively select the base-arm v with the minimum mean reward. Then, if the base-arm v is not conflicted with all the base-arms in the current combination and has negative mean reward, we add it into the combination. Furthermore, the super-arm in each round is determined by the sum of the probability variation vectors represented by the base-arms in the combination. Now, we present the complexity of the algorithm ADFN. In each round, ADFN needs to traverse all the base-arms for obtaining a valid

combination with the minimum reward, and costs a complexity. Thus, ADFN costs a polynomial time complexity in terms of the network size, when determining the super-arm in each round. Moreover, since the size of base-arms and the complexity of ADFN is the twice order of network size, we then propose the distributed implementation scheme of ADFN for the further improvement of time efficiency. The complexity of ADFN is mainly on the traverse of the base-arms. By this, we propose to distributedly implement ADFN by storing the base-arms in a distributed manner, and then conduct ADFN over the distributedly stored basearms. The idea of the distributed implementation is presented as follows. For distributedly implementing ADFN, we chop the base-arms into blocks and traverse the blocks in a parallel manner by multitasking. Technically, we store the base-arms into N storage units. For each given base-arm, we store the IDs of all the other base-arms that can be validly combined with it along with its ID. We call the main procedures in ADFN as master, and the distributed storage units as slaves. Each slave keeps a local lookup table recording the mean reward of each local base-arm. With such distributed storage units, ADFN is then distributedly implemented as below. In each round, every slave first selects a valid local combination with the minimum reward from all the local base-arms, and returns the local combination to the master. The master then emerges all the base-arms in the N local combinations from slaves into the ActionPool. Upon generating the ActionPool, the master determines the value as

Algorithm 1.

Algorithm 1: ADFN in the t -th diffusion round

Input: All the base-arms in the t -th round
Output: Variation Probability vector $\vec{\Delta\beta}^t$
ActionPool $\leftarrow$ All the base-arms, *combination* $\leftarrow \emptyset$;
while *ActionPool* $\neq \emptyset$ **do**
 $v = \text{MIN}(\text{ActionPool})$;
 /* MIN(S) returns the item with the
 smallest reward in set S . */;
 if $\vec{D}^t \cdot \vec{\beta}_v > 0$ **then**
 | End While;
 end
 ActionPool $\leftarrow$ *ActionPool* $\setminus \{v\}$;
 if *VALID*(*combination*, v) **then**
 | *combination* $\leftarrow$ *combination* $\cup \{v\}$;
 end
end
for $\vec{\beta}_i \in \text{combination}$ **do**
 | $\vec{\Delta\beta}^t = \vec{\Delta\beta}^t + \vec{\beta}_i$;
end
return $\vec{\Delta\beta}^t$

6.1 INTRODUCTION:

Java is omnipresent from laptops to data centers, gaming consoles to science supercomputers. Java is a language for programming designed specifically for use in the distributed internet environment. The C++ programming language has been built to look and sound, but it is easier to use than C++. The object-focused programming paradigm is introduced.

Java is ideal for developing full applications that can be built on a single device or spread through servers and network clients. It can also be used as part of a web page to create a little module or applet for application (a quick, small application). Applets allow users to communicate with the page's web page.

Why Java is so important?

Java was founded in California, under the leadership of Sun Microsystems, a company founded in 1982 by Andreas Bechtolsheim, Vinod Khosla, and Scot McNeally, not unlike so many of the innovations that affect our daily lives to date. This being said, technologically experienced types prefer to look to the future rather than in the past, so you do not really want a history lesson if you are curious about the modern world of coding or wonder how important Java was to the technological world. You most probably pursue the current applicability of a technology which has continually developed to keep up with the times.

Java has been developed to be a rival, class, object-oriented programming language as well as a computing platform, launched by Sun Microsystems in 1995. Unless you have java installed, a large number of websites and applications do not work. Java's refusal is like denying you access to a technical infrastructure. Java's performance, protection and reliability are highly valued and advertised.

Where is Java Being Used?

Java has been the native and seasoned programmers' choice for many years. Java is one of the core applications:

- **Creating Android Applications** – Although there are a wide range of JVM and packaging methods to distribute Android devices, Java is simply the code written. Even the new

Implementation

- Kotlin programming language from Android device creators is inspired by Java. Apps for the Android platform are mainly used by Google's Android API.
- **Designing Web Applications** – Java is another popular use for web applications design. Besides private organizations like Google, government agencies, health agencies, education institutions and even departments of defense rely on Java for important web applications.
- **Scientific Applications** – In addition, Java is used to realize science applications. It is superior to C++, which is often used in the same way, as it flaunts better high-quality tools for competition as well as being free, portable and maintainable.
- **Software Tools** - The software industry is largely based on Java. This has been used by both commercial and open-source projects. Eclipse, IDEA IntelliJ, and IDE Net Beans are some of the very best Java IDEs for developing applications.

Why Programming in Java?

This is the fundamental strength of the Java system and why many developers system it. Java is simple to write and easy to operate. You can run Java almost anywhere, if you write Java once. Java can be used to create full applications that can be run on a single device or distributed over the network servers and clients.

You can also use it to create mobile apps easily or to operate on desktop applications using various operating systems and servers, including Linux and Windows.

When a developer knows how to install JDK, it will be easy to define PATH and understand how CLASSPATH functions.

With Java, you can do a lot and find libraries that do almost everything. Java is better than the default AWT (Abstract Window Toolkits) and Swing libraries with GUI (Graphical User Interface).

You are also able to connect to the JDBC (Java Server Connectivity) databases.

The technology community therefore demonstrates that the language and its platform are solid. If there is no community to support, support and share their knowledge, a programming language would not survive. The community continues to expand and inspire with the tens of millions of developers who use and work on Java programming.

ion Why is Java so popular with modern programmers of development tools?

The solution lies primarily in Java's traditionally rigorous testing, updating and distribution consistency. A dedicated group of developers, architects and enthusiasts from Java was tested, refined, extended and demonstrated. Although Java has been developing over the years, despite almost two decades of origins.

Java seeks to build compact, high-power applications for the broadest possible ranges of computer platforms, allowing both general usability and user interaction as fundamental principles. Businesses can deliver more services and improve end-user efficiency, connectivity and collaboration through heterogeneous applications – and significantly reduce the costs of ownership of businesses and customer applications.

Java has become extremely useful to developers by enabling them to:

- (1) Write and run applications on almost every other application on a computer.
- (2) Build web browser-controlled software programs and web access services accessible.
- (3) Build online forums, shops, surveys, and HTML forms processing server-side applications and more.
- (4) To build highly customizable applications or services, combine apps or services using the Java language.
- (5) Write powerful and efficient applications for mobile, remote, micro, wifi, sensor, gate, consumer goods and virtually any other electro device. Write down powerful and efficient applications.

Thread:

Basically, a thread is a program's way of execution. Most projects composed today run as a solitary thread, causing issues when numerous occasions or activities need to happen simultaneously. Suppose, for instance, a program isn't equipped for drawing pictures while understanding keystrokes. The program must concentrate on the console input coming up short on the capacity to deal with more than each occasion in turn. The perfect answer for this issue is the consistent execution of at least two areas of a program simultaneously.

Creating

threads:

Implementation

Java's makers have benevolently planned two different ways of making threads: actualizing an interface and broadening a class. Expanding a class is the manner in which Java acquires techniques and factors from a parent class. For this situation, one can just broaden or acquire from a solitary parent class. This constraint inside Java can be overwhelmed by executing interfaces, which is the most well-known approach to make threads. (Note that the demonstration of acquiring simply permits the class to be run as a thread. It is dependent upon the class to begin() execution, and so forth.)

Interfaces give an approach to software engineers to lay the foundation of a class. They are utilized to structure the necessities for a lot of classes to actualize. The interface sets everything up, and the class or classes that execute the interface accomplish all the work. The distinctive arrangements of classes that actualize the interface need to adhere to similar guidelines.

Java Applets:

An applet is a program written in the Java programming language that can be remembered for a HTML page, much similarly a picture is remembered for a page. At the point when you utilize a Java innovation empowered program to see a page that contains an applet, the applet's code is moved to your framework and executed by the program's Java Virtual Machine (JVM). For data and models on the most proficient method to incorporate an applet in a HTML page, allude to this depiction of the <APPLET> tag. An applet is an extraordinary sort of Java program that a program empowered with Java innovation can download from the web and run. An applet is ordinarily implanted inside a site page and runs with regards to the program. An applet must be a subclass of the java.applet.Applet class, which gives the standard interface between the applet and the program condition.

A Java applet can have any or the entirety of the accompanying focal points

- ☐ It is easy to make it work away at Linux, Windows and Mac OS for example to make it cross platform.
- ☐ A similar applet can work away "by any stretch of the imagination" introduced forms of Java simultaneously, instead of simply the most recent module form as it were. Be that as it may, if an applet requires a later form of the JRE the customer will be compelled to hold up during the huge download.
- ☐ It is upheld by most internet browsers.

Implementation

- ❑ It will reserve in most internet browsers, so will rush to stack when coming back to a site page yet may stall out in the reserve and have issues when new forms come out.
- ❑ It can have full access to the machine it is running on if the client concurs.
- ❑ It can improve with use: after a first applet is run, the JVM is as of now running also, begins rapidly, profiting ordinary clients of Java yet the JVM should restart each time the program begins new.
- ❑ It can run at a speed that is similar to (yet by and large more slow than) other gathered dialects, for example, C++, yet ordinarily quicker than JavaScript.
- ❑ It can move the work from the worker to the customer, making a web arrangement more adaptable with the quantity of clients/customers.

Features of Java:

(1) Great Performance

The efficiency of the Java compiler is achieved. Java code is compiled by bytecode and then compiled with the Java compiler. Please feed it to the Java virtual machine (JVM) before converting the JVM to the level code of your machine.

(2) Inspired by C and C++

C and C++ are long-lasting languages and are the predecessors of modern languages such as Java and Python. Java is somewhat similar to C and C++, but it has no features like pointers or multiple inherits. It is also beneficial in studying Java to grasp C and C++.

(3) Multi-Threaded

Multithreading functions come directly in the language of Java. This ensures that highly interactive and responsive apps can be created with many concurrent operation threads.

(4) Platform Independence

WORA (Writing once, running everywhere) is a philosophy of Java. The Java code is compiled into a byte code format called JVM (Java virtual machine). Java code is to be used in the JVM format. A Java code can be executed in any machine running a JVM.

(5) Truly

Object

Oriented

Implementation

Built on C++, which focuses half on objects, Java expands its versatility to a completely object-oriented language for programming. Some of the key features of a puritan oriented object are:

- (i) Abstraction
- (ii) Encapsulation
- (iii) Inheritance
- (iv) Polymorphism

(6) Robust

In order to build very stable applications, Java directs programmers to follow essential programming habits. Like C and C++, Java uses an automated waste collection feature improved memory management model.

(7) Secure

In the language and runtime frameworks, safety features are implemented. This involves checking runtime and static compile time style checks. It is an awful job to enter a Java app from outside with these features.

(8) Simple

Facility to read and write makes any language easy. This refers to Java because its syntax terminology is less vague. Anyone can start Java right away with an understanding of the fundamental programming principles.

The following figure illustrates features of java




Fig: 6.1.1 Features of Java

Other Benefits of Java

Besides the above features, here are some other great options for choosing Java over other languages:

- (i) A huge selection of libraries open access.
- (ii) Oracle-backed, with technology companies including Google with IBM high-level funding.
- (iii) Public participation of broad and mature.
- (iv) Many frames for fast building reliable applications, readily available.
- (v) A multitude of IDEs and tools are available to simplify Java development.

JAVA AWT

AWT is a Java Class toolkit that allows a programmer to build graphics and graphical user interface components. It is a member of Sun Microsystems' JFC (Java Foundation Classes). Java's AWT API consists primarily of an extensive collection of classes and methodologies needed to simplify the creation and management of the GUI. It has been developed to include a common set of tools to build application interfaces.

The fact that AWT relies on the framework is an important aspect of the project. This ensures that the AWT applications use the authentic software of the platforms. This method helps to preserve each platform's look and feel. But as it all comes with a tag, this strategy has a big downside. If carried out on different platforms, it would be different on each platform because of platform dependence. This hinders an application's accuracy and aesthetic.

Features of AWT in Java

- (1) AWT is a collection of components for the user interface
- (2) It is based on a robust model of event management
- (3) It offers tools such as shape, color, and fonts for graphics and imaging
- (4) AWT also provides layout managers to help make the windows more versatile
- (5) Data transmission classes are also a part of AWT, which helps with the native clipboard platform

- (6) Supports a broad range of libraries needed to create graphics for gambling, banking, education and more.

AWT UI Aspects:

Any UI consists of 3 entities:

- (i) **UI elements:** this involves the key visual elements that the user can see and communicate with the program. In Java, AWT offers an extensive list of common elements.
- (ii) **Layouts:** It determines how UI components are arranged on the screen and gives the GUI the finishing touch.
- (iii) **Behavior:** This determines what activities will take place if a user communicates with IPs.

Hierarchy Of AWT:

The component is the super class of all GUI controls, you can find in the below diagram . It is an abstract class encapsulating all the attributes of a visual component and a graphic imagery entity. The look and feel of the current interface is primarily a component class case.




Fig 6.1.2 Hierarchy of AWT

Components and containers:

All components are known as components such as buttons , text fields, scroll-bars, etc. For each part in AWT we have classes as shown above. We must attach it to a container if we want it to be put on a computer. A container is like a display where components such as buttons, texts, check boxes and more are placed. Simply placed the layout of components is contained and reviewed. A container itself (seen in the diagram above) is a part, which allows us to add a container to the container.

Types of containers:

As above, a container is a location where components such as text area, button or checkbox are added. AWT comprises four container types: Window, Frame, Dialog and Table. Frame and Dialog are subclasses of the window class, as seen in the hierarchical diagram above.

Window: The Window class instance has no cap and no heading

Dialog: The border and title of the dialog class. Absent an related Frame class instance, a dialog class instance can not exist.

Panels: No title bar, menu bar, or boundary found in the screen. The components are a standardized package. A panel class instance provides a container for adding components.

Frame: Frame includes heading, border and menu bars. Frame: It may contain several components, such as buttons, scrollbars, text fields, etc. This container is most widely used during the production of an AWT application.

Why AWT is platform dependent?

Java Abstract Window Toolkit calls native framework i.e. subroutine mechanism for components such as text box, checkbox, button etc. to build components. For instance, an AWT Interface with a button will have a different look and feel on various platforms such as Windows, Mac OS, and Unix, etc. as the platforms look and feel various for their own native buttons and then the AWT would directly call up its native subsystem that will produce a button. Simply put, the AWT-built application looks more like a Windows application, but the same software looks like a Mac application if you run on the Mac Operating System.

Best

Java

Compilers:

Implementation

A Java compiler compiles or runs Java code on the Java platform. Java class file is the most common type of Java compiler, and machinery for the hardware or operating system emits native code. A key role in a compilation is played by hardware or operating system. Various operating systems have various specifications which are used to compile various codes across different platforms. In JSR 199, there was a specification on how to define Java compilers.

The virtual Java machine (JVM) loads the class file and either converts it into byte code or just in time with the Java programming language compilation techniques. Compilers like BlueJ are available and the basic feature of a compiler is to translate user code to machine code, then run it with various functions and the sense of programming.

Some of the compilers in Java used to run code are

(i) Codiva

Codiva.io is the best Java compiler that is commonly used in Java language interface coding and programming. Codiva best benefits by automatically compiling the code when it is typed by the user, handling compiler errors and displaying them in the editor. After typing is complete, we see the final results of the compilation that appear in the compiler's editor. There is also a good provision for automated completion. Those two features save a lot of time during the compilation processing of a basic or complex piece of code. Codiva has more than one files and packages that can be activated. Files whose names can be customized can also be given. Codiva runs on mobile devices very well too. Codiva supports Java, C or C++ only, some of the drawbacks. Codiva supports Java 9, but does not support Java 9 modules and neither do Java modules support any of the other online compilers. It is also very clear that Java 9 modules are not supported.

(ii) JDoodle

JDoodle is a widely used Java-code on the Java platform online compiler. Almost 70 languages are supported. JDoodle only allows one file, but no filename is needed. You will find these by searching the name of your file. It provides excellent terminal support for programs that deal with the live code one by one. Period of the programs is 10 seconds. Android Studio uses Java for Android software and Jdoodle is among the few compilers that are used in it. If you know multiple languages and know how to switch between languages, it would be a perfect option. JDoodle's annoyance is present. Some of the

Implementation

downsides is that after it's written or drafted, the code is assembled. The consumer then will find the error message, go to the line of the error and make appropriate modifications. It's really difficult for people who used Codiva before to treat JDoodle first. Furthermore, JDoodle 's drawback is that it supports just one script. Packages can not be taught as the encapsulation method. JDoodle has a number of drawbacks. JDoodle is popular due to its many uses despite its inconvenience.

(iii)RexTester

Rextester started as a standard expression testing tool. It was later built into an online gui. C # users can use it very well and can be used for over 30 languages, including Java. There is a difference among many editor widgets in Rextester. It has one of the strongest support in the Java programming language for live collaboration. You can share the URL and start typing with ease. There was no glitch so far and many users could edit it simultaneously. Netbeans are also a large-scale forum for Rextester. Only one file is allowed, and Rextester will follow the file's class name. The class should also not be released. Java uses BlueJ or Eclipse framework to execute Java code in desktop programming. The time and performance of the compilation depends on the hardware or operating system configuration we use.

Testing Frameworks for Java:

A collection of principles or guidelines are specified in a structure that we should follow in order to consistently achieve the necessary results. There are various ways to test JAVA / J2EE apps and server elements and test frameworks are supported.

Many are designed for a unit or functional testing, while other parts like display, logic, and validation are used in specific Java. The benefit of using testing frames is that the speed of the testing increases and the reliability and the exactness of the entire process is preserved. This not only reduces risks but also decreases research maintenance costs.

The List of Testing frameworks for Java are:

(i) JUnit:

JUnit is the Java Open Source Test Unit Platform. Unit Testing is used to evaluate a small amount of code in a direction, feature or process. Developers who follow the test method first need to write and execute the test unit before any code. All checks will be conducted and passed until the code is completed. If there is a code added, all test scenarios must be updated and everything must be done properly. Thanks to faster coding, improved output quality and speed for production.

(ii) Jasmine:

This is a frame-testing machine designed specifically for the Java script. Jasmine-friendly testers like Screw Unit, JSSpect and JSpeci rotate fast because of its good relation between them. Jasmine is particularly useful in behavior-driven development methodologies. Jasmine is best known for developing AngularJS applications.

(iii) JBehave:

The method of testing offers a straightforward overview of acceptance testing for company users. JBehave is another Java application system, used primarily for Application Java development by Selenium WebDriver. The main objective behind JBehave 's launch is to help newcomers to quickly learn about BDD. It is a design theory that extends the test process of an application.

(iv) Serenity:

This is an open source repository for conduct-driven research. This system enables you to write well-structured and retained specifications for acceptance. It extends the features of **JUnit and WebDriver**. It used to be referred to as thucydides. This was nothing but the question of expression, which is the principal reason for changing the name. However, the ancient name may be used when referring.

(iv) Selenium:

Selenium is an automated free (open source) software kit for various browsers and platforms on the Internet. Selenium is very similar to HP Quick Test Pro (QTP now UFT) for the automation of web-based software. We name Selenium Trials when research is performed

Implementation

using the selenium method. Selenium is not a tool, but a software package that meets the specific testing criteria of a client.

Because Selenium has an open source, it does not require licensing costs, and thus, the principal benefit over other research methods. This supports platform-independent operating systems such as Windows, Mac or Linux. In order to manage test cases and report creation we can integrate Selenium with tools such as JUnit, TestNG and others such as Maven, Docker and Jenkins for continuous testing. This can be combined with other Java applications. You can use browsers like Safari, Mozilla, Google, etc to complete test results.

(v) TestNG:

It is an application software system inspired by Java. TestNG in research is even easier. The Term NG in TestNG reflects the next generation. This system seeks to enhance the efficiency of integration. During test results, you can produce an HTML chart. The research is much simpler by allowing the database tests and front-end tests within the system.

(vi) QUnit:

The most that JQuery testing method is probably QUnit because it is simple and easy to understand. There's no jquery requirement but all jQuery 1.x browsers are supported, including IE, Chrome , Firefox, Opera and Safar.

(vii) Cucumber

Cucumber is yet another strong Java test environment. This is distinct from the other framework due to its design capabilities. Cucumber incorporates all the specifications and documents to create a final report. Concurrently, the final report is automatically checked and the specifications are revised.

(viii) Mocha :

Mocha is a test system for JavaScript running on the Node.js packed with different functions. This makes research asynchronous. Mocha tests run serially and require versatile and precise reporting when exceptions to the appropriate test cases are mapped.

(ix) REST Assured:

REST Assured simplifies the testing and validation of REST APIs and is focused on testing techniques in ruby, groovy, etc. In java it is very complex to validate and check REST services.

Implementation

This question is overcome by REST Assured, and REST services can be checked and reviewed easily with this system. REST Library HTTP is provided by Assured.

(viii) Mockito:

This is a research application for open-source Java. It is widely used for unit testing Java. There is no need to build mock objects, but the benefit of using this java system is, it generates it automatically. It uses annotations to construct a copy. It is used to write developmental type tests using syntactic sugar. Syntactic Sugar is a syntax in the programming languages that makes the programs easy to read and understand.

Java monitoring Tool:

The java surveillance tool is described as a monitoring tool that monitors the performance in java-programmed applications. The tool can also track server performance. Since Java is the most common language for programming and applications are built mostly in Java, a tool to track the performance of Java applications is often needed. Once every program is launched the CPU and the memory are used and resources used during application execution are also used.

The monitoring tool is used to detect bugs and errors in the software while the program is in the development process. The application's output is evaluated as the program goes through the QA process. Numerous java monitoring tools are available to evaluate java applications' performance. Eclipse Floor, Netbeans Profiler, VisualVM, Scouter and many more are examples of java monitoring tools.

The following section explains the Top 7 java monitoring tools:

Implementation

SolarWinds AppOptics:

This kind of java monitoring tool is used for measuring application output and also for tracking application. The tool is also used to personalize and preconfigure warnings on dashboards. The SolarWinds AppOptics tool can be used for a detailed review of the output of the app. The other advantage of the tool is that it helps to change the application's performance and lets developers understand full java infrastructure. Process speed, active threads, java heap use, response time and other performance parameters are available to developers. The tool has an interactive interface which allows the user to thoroughly analyze application performance and analyze web applications in java.

1. SolarWinds Loggly:

For log management, this form of java surveillance tool is used to increase application speed. A server is a cloud-based service which also improves the application's logging module. The developers can analyze logs from a separate web application with this tool and also show network logs on the GUI platform. Even all network logs can be visualized conveniently in one dashboard. When java programs create logs, the logging function can be centralized.

2. Eclipse memory analyzer:

The eclipse memory analyser is the most popular method for controlling the java-based device for the study of the memories. Within this method, the application's java heap is continuously monitored. When a java application is developed, the objects are stored in heap. It contains objects. The fluctuation can be found in heap use while the program is running. And there is no space for more artifacts when the heap size is depleted. This method allows the memory usage to be analyzed and also enables developers to test the memory of the Java program. If there are so many items in the java program, heap dumps can be easily analyzed. This method allows the object size to be measured and the function of a collector to be tracked.

3. Lightstep:

Implementation

The Lightstep is a web tracking tool that helps to monitor web applications' performance and is also useful for IT teams to assess the application 's performance. To the developers, manual monitoring of network packets, protocol recognition and IP address monitoring is a very hectic job. The Lightstep provides developers with the perfect alternative because the tool automatically tracks web application results. The tool's other feature is that it can be combined easily with any program in java.

4. EJ Technologies JProfiler:

Not only is the work for developers when writing the program code. You will also have to describe the application's output calculation, memory usage and other program execution information. And Jprofiler is the ideal solution for this reason. The JProfiler tool is used primarily to calculate the JVM application standard. During the device, the output flash gaps can be calculated and memory leaks in the java framework can también be found. The tools include the UI in which the developer can display the objects generated in Java and obtain complete object descriptions.

5. Pingdom Server Monitor:

The Pingdom Server Monitor tool is a JMX monitoring application that facilitates log management and java analysis. The tool is able to provide information on JVM 's safety and also tells you about JVM. Using the JMX console, information on MBeans is open. This method helps the java code to be versatile. The user can control the application's heap memory usage and also the application's non-heap field. With the tool, developers can understand the java problems linked to the app they have created.6)Eclipse MATh The Eclipse is a type of memory measurement instrument which is used to evaluate the java heap of the application. The Memory Analyzer Tool The storage leaks can be easily identified by using the MAT tool and helps to maximize storage resources. The objects that are the source of the old GC can easily be found in this method and help gather discarded items for waste.

Best Java IDE:

Java is a very popular language used almost across the world – Mobile devices, gaming consoles and even supercomputers. The product is known for its simplicity and incredible portability. Today's article explores the 10 best Java IDEs of all time. In the integrated programming environment, the Java IDE stands for IDE. An IDE is an independent application, which allows you not only to edit and compile your code, but also supports resources management, allowing you to use advanced delivery and release control functionality in your project.

IDE means integrated development climate. integrated development environment. This is a request that promotes application development. In general, an IDE is a graphical user interface based on a GUI. It aims to help a developer with the setting and all the appropriate instruments in the construction of mobile apps. The selection of an ideal IDE is based on variables like language support, OS requirements and expenses, etc.

Advantages of Java IDE

You save a lot of time with the JAVA IDE system. These advantages include:

- (1) The traditional approach is to be linked to a community of programmers simply by operating in the same development environment.
- (2) Standards will be further implemented if an IDE offers preset templates or if the application libraries are shared amongst teams who work on the same project.
- (3) The IDE's goal is to make the development process absolutely simpler and more quickly. A variety of tools and functions help you manage resources, prevent mistakes and provide shortcuts.
- (4) Most IDEs have documents that either automate the designer's comments or comment on different fields.

The list of Best JAVA IDE

Eclipse is a free distributed IDE for web-development companies with an open-source cross-platform. In 1998, IBM Software Group created an IDE which could penetrate deeply and be a pioneer in competing IDE rooms. This led to the creation of Eclipse as one of the finest Java IDEs for web development. It's a Java IDE, one of the best Android IDEs. The popular embedded development environment is available in both desktop and cloud versions. The version of Cloud

Implementation

is Eclipse Che that helps programmers to build web browser-based applications. When written mainly in Java, Eclipse is a case in point of successful Java applic

Features of Eclipse IDE

The version of Java 8.0 and 9.0 can be accessed with Eclipse

IDE.Helps refactor code, update validation timely, compile increments, interferences, and make suggestions.

Smart code completion and fast fixes.

Eclipse provides excellent efficiency and usability. Eclipse also supports a mac os / Linux / Windows operating system.

A PDE for Java programmers wanting to develop unique Eclipse function.

1. IntelliJ:

Perhaps one of the best Java Ides is IntelliJ IDEA. It is available with 2 different versions, Apache 2 licensed group and an Ultimate (commercial) exclusive version paid for. IntelliJ IDEA provides features such as language re-factoring and data flow evaluation to enable developers to deepen their knowledge of Java 's code as the open source IDE and JVM (Java Virtual Machine) IDEA and Android's development. It supports Javas, Colin, Groovies, and Scalas SBTs, Git, SVN, Mercurials, and TFS. The last edition is aimed at improving the website and business in addition to the other version control system.

Features of IntelliJ

- (1) The open source IDE is easy to install and can be used on various platforms.*
- (2) It's a well-known IDE in the field of mobile development and appliance.*
- (3) The Java development team of the third party can also extend it for plug-ins at a later date.*
- (4) The Java editor helps programmers to syntactically and sémantically highlight Java's code to construct personalizated software applications.*
- (5) The tools of NetBeans also help developers rework and write bug-free code.*

1. JDeveloper:

Oracle's freeware IDE is JDeveloper. The software provides application characteristics Java, XML, SQL, PL / SQL, HTML , JavaScript, BPEL or PHP. The development process from design , coding, debugging, optimization and deployment is completed by JDeveloper. The development process from design , coding, debugging, optimization and deployment is completed by JDeveloper.

Features of JDeveloper

- (1) It simplifies the development of Java applications that deal with every stage of the application life cycle.*

Implementation

- (2) It mainly offers an integrated software system with a variety of features and different visual development tools.*
- (3) This Oracle J developer should be used in the Oracle Application Development Framework (Oracle ADF) in order to promote further development of the program.*
- (4) HTML, JavaScript, PHP, SQL and XML apps are also provided by JDeveloper in addition to Java.*
- (5) Provides a full development life cycle, including coding, design , testing, optimization, profiling and delivery.*

2. MyEclipse:

MyEclipse helps establish an simple and dynamic boundary and develop a clear backdrop. In today's business, it has an extremely critical combination. It was designed and operated by a well-known corporation, Genuitec, a founding partner of The Eclipse Foundation. MyEclipse offers leading industry apps for a range of platforms including Windows , Linux and Mac.

Features of MyEclipse

- (1) Resource with advanced JavaScript functions for Ajax & Web 2.0.*
- (2) The maven configuration is provided in MyEclipse.*
- (3) Specialized recording instruments.*
- (4) The market pioneer in Java persistence software and many more.*

3. DrJava:

DrJava is another lightweight Java IDE, particularly for beginners of Java. Effective establishment and management of the JavaPLT Team is at Rice University. To advanced users it also has good characteristics. DrJava can be downloaded free of charge. While it's not as good for Java development as other big names, DrJava has an unregulated gui.

Features

of

DrJava

Implementation

- (1) Dr. Java calls for the console to test Java code and to interactively view the database performance.*
- (2) This allows programmers to coordinate and locate functions or replace them.*
- (3) It provides advanced programmers with automatic indentation, brace matching, color statement and syntax.*
- (4) In comparison to other Java IDEs, DrJava is continuous on different platforms. It is equipped with the Sun Microsystems swing toolkit.*
- (5) DrJava can also be applied via a plugin with Eclipse.*

4. JGRASP:

One of the finest lightweight IDEs in Java is JGRASP. It does not include an embedded debuggers and a workbench for Java developers to effectively produce a complexity graphic profile and UM Layer graphics.

Features of JGRASP

- (1) It helps to simplify the visualization of information and improve the overall comprehension of any program.*
- (2) Java IDE is a lightweight framework capable of static source code frame display as well as visualizations of the data structure during execution.*
- (3) Acts as a helpful source code editor for other languages as well. The free IDE can be programmed to work with most commercial compilers for various programming languages.*
- (4) JGRASP is able to produce CSDs in other programming languages while applying Java.*

5. JCreator:

Implementation

This has the same interface as Visual Studio in Windows. JCreator is a Xinox Java IDE program. Xinox Software said, since Jcreator is fully programmed to Java (except for the first (.1) version based on Java) it is faster than competing Java IDEs. JCreator is only available on the Windows operating system. All LE and Pro versions of JCreator however function well on Linux (using Wine). No Linux updates are scheduled for immediate release, but fresh sections are built for cross-compatibility. In addition, certain functions including code completion, and other free IDEs, are missing in the free LE version.

Features of JCreator

- (1) In three different formats, the Lite edition, the Pro Edition and the Live-Pro Edition are available.
- (2) The Lite version, Pro Version and Life-Style Edition are available in three different versions.
- (3) While JCreator is entirely developed in C++, other big Java IDEs do exist. In addition, JRE is not necessary for executing Java code. This is why JCreator is more popular than other traditional Java-based IDEs in the developer community.

Java Compilers:

The programming language compilers are Java Compilers. Every programming language has its own collection of programs to execute the return code in that language. No magic occurs behind the code in a particular language.

There's something that someone writes to translate the code written in a civilized language that a machine understands. The same goes with java as well. Java by humans is easy to comprehend. This should be translated to machine language when you write programs in java. Machine language is nothing other than 0's and 1, and Java has its own set of compilers to translate this code into byte code. We only knew a few compilers in general. So you can only learn one compiler called Java, when you're new to Java. Compilers allow us to communicate with other platforms. On any platform such as Windows , Linux, MAC, etc. we could run our program in Java. Which compiler is to be used is not limited. Nonetheless, we will know for the time being the availability of different compilers. Let's now see what it means exactly.

Implementation

Compilers are a comprehensible bridge between the language of humans and computers. The Java compiler operates with the .java file or with the source code. Each class in the .java file is then translated into its corresponding .class file. This .class file can be used in any program. Java is therefore a language focused on platforms. Note that it converts the code to machine language when compiling our Java file with the Javac command. This code is referred to as bytecode. Now is the time to try out various worlds open to us at present.

Types of Java Compilers

1. Javac

It has been introduced by Martin Odersky at Oracle's Sun Microsystems. To run a java program, this javac compiler has to be installed with any IDE. Javac is in the Java language itself. For Windows, UNIX, and other OS, this compiler is necessary.

2. Edison Design Group

This is an organization that compiles the EDG. It's carried out by J. Stephen "Steve" in 1988. Stephen "Steve." They write preprocessing and parsing compilers primarily. This is also available on Windows, UNIX and Oss, but this is not available on any IDE.

3. GCJ

GCJ reflects Java's GNU Compiler. This is a free Java Program Language compiler. This compiler compiles the computer comprehensible source code. It can also compile bytecode-based JARs. This compiler is only available for UNIX rather than for other operating systems like Windows. You can also compile C, C++, Fortran, Pascal and other languages in this compiler.

Implementation

4. ECJ

It is an Eclipse Java compiler which is supplied with Eclipse IDE which is available on Windows, UNIX etc. operating systems. Nevertheless, the other part of the code can be checked whether it works well or not with this compiler, if a certain part of the code has a compile-time error. It is not the case for javac, since before compilation, you must correct all errors. Eclipse compiler makes an execution exception if the java source code has some compile-time error. This compiler can also be running in the IDE context and also accelerates compile compared to javac.

5. Jikes

This is an OSI open source java compiler written in C++ by Dave Shields and Philippe Charles on IBM. This is a high-performance compiler used in large projects and much faster than Sun's compiler for compiling small projects. Jikes was released for Linux in 1998. The problem with Jikes compilers is that Java 5 and above is not allowed because IBM does not update it on the same version. The JDK 1.3 and below versions work best with this compiler.

6. Power J

This compiler has been published at SAP's Sybase. For Windows and IDEs, this is also available.

7. JIT

It is a compiler that is just in time and is used to improve Java application performance. Defaults are allowed for this compiler. If any method in java is called, it becomes active. JIT compiles in machine code the byte code for

that process. It is a Java Runtime Environment component that increases performance in time.

8. Client-Side Compilers

The compiler on the client side is C1 and is enabled by the `-Client` in the commandline option for JVM initialization. This is used by customer-side systems that have very few resources and decreases applications' startup time.

9. Server Side Java Compilers

Implementation

This is used for server-side applications such as server-side business applications. The compiler on the client side is not adequate for server-side applications. The compiler on the server side is C2, and the compiler is disabled via the commandline startup JVM server option. For the program with a server side-compiler, sophisticated algorithms and techniques may be used.

Java tools:

Java is a programming language oriented towards objects used by the developer for applications , websites, and others. It depends on platform, i.e. it can be run on any platform system, no limitations are imposed. An application written in Java language can run on any platform with a portable function of java. Multiple Java tools that developers use to create the application are available.

Below are some of Java Tools

(1) Java Development Kit

JDK is a Java Applets and a writing tool. The Java Development Kit includes the Java, Java API runtime framework. The tools for designing, debugging and monitoring Java applications are included. Nearly all new and seasoned programmers can be started quickly. The JDK provides a JVM and a variety of other tools for the development of the Java program.

Features of JDK

- (a) There is a string in switch language.
- (b) There is an underlining between digits liberals in numerical literals.
- (c) To handle a few exceptions, provide support in one capture block.
- (d) There is an automatic form of infusion in generic object instantiation.

(2) NetBeans

NetBeans is an open-source java platform for creating Cloud, Mobile and Desktop applications. For the official Java 8 IDE, NetBeans IDE is well recognized.

Features Of NetBeans

- (a) Supports all new technology in the java area.

Implementation

- (b) It offers vocabulary, related phrases, lists, terms, and predictive suggestions in order to avoid incorrect vocabulary or coding.
- (c) This can be mounted on any Java-supporting computer.
- (d) The programming languages of NetBeans IDE include Java, JavaScript , Python, HTML, groovy, c , c++, PHP.
- (e) It effectively handles all files and directories so that everyone can quickly understand the project structure.
- (f) It provides a GUI interface to render programming simple, simply drag and drop objects to generate code.
- (g) It provides software in order to detect and correct errors.

(3) IntelliJ IDEA

IntelliJ IDEA is a multifunctional IDE focused on Java development. It facilitates the development of cloud, mobile and hybrid applications. IntelliJ Idea is named 'the most intelligent Java IDE.'

Feature of IntelliJ IDEA

- (a) Code is evaluated for any project database and language.
- (b) In this sense, it lists the most suitable symbols.
- (c) Search for double flying code pieces.
- (d) Consumers with static methods or constants will easily use it.

(4) Spark

Spark is a popular Java-based software web application platform. It enables developers to create internet applications without writing boilerplate code. The Spark runs separately and in the cloud on Hadoop, Apache Mesos, Cubans. There may be various sources of data. Spark offers more than 80 operators which simplify the construction of parallel applications.

Features of Spark

- (a) Spark has many languages to support.
- (b) It includes interactive / declarational query tools, streaming knowledge, machine learning.
- (c) The culture is healthy, incremental and increasing.

Implementation

- (d) Not only does Spark work independently, it can work on Hadoop as well.
- (e) For RAM Server sparks the information is saved, which enables fast access and in effect speeds research.

(5) Eclipse

Eclipse is an integrated open-source Java-free platform for development. Eclipse provides much needed code, refactor and syntax tests. It offers new features, various tool models, java test techniques and growth frameworks. It also offers a range of Java apps called Java Development Tools Project (JDT), software to build different Java applications.

Features of Eclipse

- (a) JUnit is fast and seamless to incorporate
- (b) Provide complete written information
- (c) You can also customize it quickly. In conjunction with Ctrlflow, automated error reporting system.
- (d) For example , it allows developers to combine C / C++ and PHP IDE language support.

(6) Gradle

Gradle is a project automation Java tool. It builds on the features of Apache Ant and Apache Maven.

Features of Gradle

- (a) Effective representation of dependency with the Java library plugin reduces the class path compilation volume.
- (b) Gradle Wrapper can be used on unassembled computers Gradle.
- (c) The smart course avoids the need to construct when the binary interface of a library has never changed.

(7) Java Decompiler

Java Decompiler is a free-to-use Java tool which rebuilds a source code from CLASS Java. To accurately render Java source code, you can decompile java applets, JAR and ZIP files. To view predefined Java class data including HashMap, HashSet, ArrayList, etc, you can use the java decompiler.

Features of Java Decompiler

- (a) The drag and drop tools of the javaDeCompiler support.
- (b) The color code is shown in Java, decompiler source code.
- (c) This works with virtually compatible with every java version.

(8) JUnit

JUnit is a java programming testing tool. It's a source that is proprietary and not free.

Features of JUnit

- (a) The test script becomes simple with this tool writing and running
- (b) The database is filled with a specific data set.
- (c) It offers annotations to easily classify various types of test methods and run test cases.
- (d) It enables quicker coding, thus increasing quality and speed.
- (e) It is used to prepare different inputs and objects.

(9) Apache JMeter

Apache JMeter™ is Java entirely open-source software, first developed for operational behavior monitoring and performance measurement by Stefano Mazzocchi of Apache Software Foundation. The Web Application or FTP application was originally used by JMeter. JMeter is also being used to practical monitoring, cloud database monitoring, and so on.

Features of Apache JMeter

- (a) JMeter allows loading and output checking of various server types.
- (b) This tool stores the XML test plans and users can use a text editor to build the test plan.
- (c) The tool is also used for automated and practical testing of software.
- (d) Extensibility and configuration of data processing and visualization plugins.
- (e) Functions for knowledge manipulation research can include dynamic feedback.

(10) Groovy

Groovy is a popular Java application object-focused language. Groovy 's primary objective is to increase developers' development speed. It works with JVM i.e. Java Computer

Interactive.

Features of Groovy

- (a) This automatically stresses syntax and error such as NetBeans to avoid programming errors.
- (b) It can fit into java or any libraries of third parties
- (c) Groovy supports AST processing
- (d) Static and dynamic typing is allowed.
- (e) It generates getters and settings automatically.

(11) Oracle JDeveloper

Oracle JDeveloper is a Java integrated programming environment for open-source software. This helps a user to use the Java platform to build reliable services.

Features of Oracle JDeveloper

- (a) JDeveloper provides the drag-and - drop options and simply drag-and - drop to IDE, so there is no need to type code manually.
- (b) Used for web and mobile applications creation.
- (c) It supports database administration.

(12) JRat

The Java Runtime Analysis Toolkit for Java is an open-source Java platform performance profiler that is low overhead, simple to implement and still tests quality.

To display and analyze this information, use the JRat Desktop, a swing application

Features of JRat

- (a) We can easily transfer the file to another device from one location.
- (b) JRat allows remote control.
- (c) JRat funds websites for redirection.
- (d) JRat permits the modification of device files.
- (e) Enables users to access their systems.
- (f) Screenshots allow the manager to document issues on the customer's screen.

(13) Mockito

Implementation

Mockito is an open source and test tool for Java Mocking. Mockito is a well-known open source Java mocking container. It lets developers write tidy, well-designed and closely related code. The checks are easy to read and yield smooth check errors.

Features of Mockito

- (a) It is simpler to use the Mockito tool than any other tool.
- (b) This offers an easy-to-read syntax. The boilerplate code also offers some required annotations
- (c) It can be used to write syntactic sugar conduct production checks.

(14) Clover

Clover is a Unit Check Java tool that generates reports on application coverage. You should close the code with Clover which can be the toughest and ensure that your check is based on the answer. It is supported as a plug-in in Ant, Eclipse and Maven. It can also be used to gather knowledge about integration test coverage. All of this is supplied by new functionality and enhancements constantly modified and published.

Features of Clover

- (a) It is a free-to-use opensource tool in java.
- (b) Really simple to use because of the fly byte code
- (c) Inline feedback allows the reporting of claims to be visually emphasized
- (d) Research optimization renders it painless before check-in to run the test suite

(15) Encache

An open source cache is a standard, performance-enhancing cache that downloads the data base and enables scalability. It is the most widely used Java cache because it is versatile, tested, extensive and incorporated in other popular frameworks and libraries. Ehcache range from in-process caching to hybrid deployments with terabyte caches.

Features of Encache

- (a) We need Java 8 + in order to use Ehcache
- (b) Ehcache API is really basic and that makes it easy to use.
- (c) Can be up to 100 caches scalable
- (d) Requires Spring Caching and Hibernat integration with Javax cache boxes
- (e) Ehcache is committed as lightly as possible to preserve its applications

(16) VisualVM

VisualVM is a visual tool used on the command-line to combine JDK resources. It offers lightweight profiling capabilities. This can be used for both production and creation.

Features of VisualVM

- (a) It shows local and remote Java processes.
- (b) Quality and mechanism of memory control
- (c) Leistungs and memory use profile
- (d) Basic Java process data can be read.

(17) FindBugs

The Java open-source Java bytecode is tested for possible bugs. FindBugs is a static review. It helps the developer at a beginning of growth to reach all forms of error.

Features of FindBugs

- (a) It can recognize patterns of bugs accurately.

This supports the Guava library and addresses a range of specific forms of violence.

6.2 SAMPLE CODE:

```
import
java.io.FileNotFoundException;
import java.io.PrintWriter;
import
java.util.*;
public class
Users {
    private static int[] users = new int[2315];
    public Users(String inputFile) throws FileNotFoundException {
        users = getUsers(inputFile);
    }
    public static int[] getUsers(String inputFile) throws FileNotFoundException {
        File userFile = new File(inputFile);
        Scanner in = new Scanner(userFile);
        for(int i = 0; i<2315; ++i) {
            users[i] = in.nextInt();
        }
        Arrays.sort(users);
        return users;
    }
}
```

```

public static boolean checkUser(int userID) throws FileNotFoundException {
    boolean found = false;
    int low = 0;
    int position = 0;
    int high = users.length - 1;
    while (low <= high && !found)
        { position = (low +
          high) / 2;
          if (users[position] ==
              userID) found =
                true;
              else if (users[position] < userID)
                low = position + 1;
              else high = position - 1;
            }
    if (found)
        return true;
        Else
            return false;
    }
}

```

7.1 UNIT TESTING:

Unit testing is typically conducted as part of the software life cycle 's combined code and unit test process while coding and unit testing is not unusual to be done as two separate stages. ***Test strategy and approach:***

Field testing will be performed manually and functional tests will be written in detail.

Check goals

- All field entries need to work correctly.
- Pages have to be allowed from the connection found.
- Don't miss the entry screen, notifications and answers.

Attributes to check

- Make sure submissions are of the right format
- Don't authorize duplicate entries
- All links will take the user to the page in question.

7.2 INTEGRATION TESTING:

Software integration testing is the gradual integration testing on a single platform of two or more compatible software components to create errors triggered by device defects. The purpose of the integration check is to verify whether components or software applications communicate without error, e.g. components in a software system or-one step up-software applications at the company level.

Test Results: All of the above test cases passed successfully. No defects found.

7.3 ACCEPTANCE TESTING:

User Acceptance Testing is a critical phase of any project and requires substantial end user involvement. This also ensures the framework meets the practical demands.

Test Results: All of the above test cases passed successfully. No defects found.

7.4 FUNCTIONAL TEST:

Functional tests provide systematic demonstrations that functions tested are available as specified by the business and technical requirements, system documentation, and user manuals.

Functional testing is centered on the following items:

Valid Input : identified classes of valid input must be accepted.

Invalid Input : identified classes of invalid input must be

rejected. Functions : identified functions must be exercised.

Output : identified classes of application outputs must be
exercised. Systems/Procedures : interfacing systems or
procedures must be invoked.

Organization and preparation of functional tests is focused on requirements, key functions, or special test cases. In addition, systematic coverage pertaining to identify Business process flows; data fields, predefined processes, and successive processes must be considered for testing. Before functional testing is complete, additional tests are identified and the effective value of current tests is determined.

7.5 SYSTEM TEST:

System testing ensures that the entire integrated software system meets requirements. It tests a configuration to ensure known and predictable results. An example of system testing is the configuration oriented system integration test. System testing is based on process descriptions and flows, emphasizing pre-driven process links and integration points.

WHITE BOX TESTING:

White Box Testing is a testing in which in which the software tester has knowledge of the inner workings, structure and language of the software, or at least its purpose. It is purpose. It is used to test areas that cannot be reached from a black box level.

BLACK BOX TESTING:

Black Box Testing is testing the software without any knowledge of the inner workings, structure or language of the module being tested. Black box tests, as most other kinds of tests, must be written from a definitive source document, such as specification or requirements document, such as specification or requirements document. It is a testing in which the software under test is treated, as a black box .you cannot “see” into it. The test provides inputs and responds to outputs without considering how the software works.

ALPHATESTING:

Combination of three testing methods (unit, integration and system testing) forms the alpha testing. Alpha testing is conducted by the development team and quality assurance team. The following things in the application are tested during the alphatesting:

- ☐ SpellingMistakes
- ☐ BrokenLinks
- ☐ CloudyDirections
- ☐ Measuring the loading time in the minimum system specifications for optimization.

BETATESTING:

Once the alpha testing is completed successfully, the product development team moves onto beta testing. In beta testing, a prerelease version of the software isprovided to sample user base over the internet. These early users will use the software and provide a timely feedback about the software working. Following steps are performed in thistesting:

- ☐ Installation of the software by the users and feedback submission to the development team at regularintervals.
- ☐ Noting down the visual errors, generating crashreports.
- ☐ Once the feedback is received, development team fixes the issues and once all the known bugs are fixed, a final version is released to theusers.
- ☐ The nature of the software determines the consumer satisfaction. So, as more and more issues are fixed, nature of the product is increased which results in higher consumersatisfaction.

RESULTS AND DISCUSSION

In this section, we evaluate the performance of the proposed solutions for the adaptive diffusion problem from the following four aspects, i.e., information diffusion loss, regret, cascading scale of sensitive informations, and the time efficiency of distributed implementation. (1) The information diffusion loss quantifies the loss of non-sensitive information diffusion when constraining sensitive information diffusion. The lower information diffusion loss means better user experience in reality. (2) We compare the reward obtained from ADSN with that of CUCB to justify the effectiveness of ADSN on minimizing the overall reward. (3) We present the cascading scale of sensitive information over time to show that our solution can effectively constrain the diffusion of sensitive information. (4) We report the running time of ADFN and ADSN as the original procedures and the distributed implementation schemes.

Datasets. Our experiments are over the datasets of three real social networks and three synthetic networks², whose basic descriptions and statistics are summarized as follows

- **Twitter:** This dataset consists of partial users and social links in Twitter, and includes 81,306 nodes and 1,768,149 edges.
- **Livejournal:** Livejournal is an online community with almost 10 million members. This datasets contains 4,847,571 nodes and 68,993,773 edges.
- **Pokec:** Pokec is the most popular online social network in Slovakia. This dataset contains a network with 1,632,803 nodes and 30,622,564 edges.
- **B.A. graph** (short for Barabasi Albert graph) [39]: A synthetic graph that forms as newly added nodes preferentially attaching to existing nodes with higher degrees. The B.A. graph well captures the power law degree distribution in real social networks. Each graph has two parameters: n (total number of nodes), p (number of edges that each new node connects with existing nodes). We generate three networks as the B.A. model with the parameters respectively being ($n = 1,000$, $p = 3$), ($n = 5,000$, $p = 4$) and ($n = 10,000$, $p = 5$).

Settings. We set the original diffusion probability via each social link as 5×10^{-3} . In the experiments over semiknown networks, we set the diffusion abilities of half of the users as

unknown. We initially set the diffusion abilities of uninformed nodes as the average of the diffusion abilities of all the informed nodes, and set the initial mean rewards of base-arms built upon uninformed node based on such initial diffusion abilities. All the algorithms over a computer with Ubuntu 16.04 LTS, 40 cores 2.30 GHz and 128 GB memory.

Information Diffusion Loss

As illustrated earlier, we aim at constraining the diffusion of sensitive information while lowering the diffusion loss of non-sensitive information, for the aim of preserving the global diffusion ability of the whole network on diffusing non-sensitive information. In experiments, for quantifying the diffusion loss of non-sensitive information, we run the diffusion process with and without sensitive information constraining measures respectively. We compare the info-loss of ADFN on fully-known network and ADSN on semi-known network with the following four baselines:

(1) **DRIMUX [9]**: As an online rumor blocking algorithm, DRIMUX periodically blocks a given fraction α of the most influential users to constrain rumor diffusion. For user experience, DRIMUX sets a threshold of the blocking time of each user. Referring to the settings in [9], when conducting DRIMUX, we set the fraction of blocked users in each round as $\alpha = 10^{-4}, 5 \times 10^{-4}, 10^{-3}$. Also, we set the threshold of blocking time of each user as 100 rounds.

(2) **TIBS [15]**: For minimizing the diffusion of rumors, TIBS proposes to block a given number K of the most influential users during the diffusion. Then, when conducting TIBS, we set $K = 10, 25, 50$ according to [15].

(3) **RIPOSTE [16]**: Typically, RIPOSTE forwards an item with a probability larger than a given amount if a user likes the item, and with a probability smaller than the given amount otherwise. In our scenario, we implement RIPOSTE by randomly decreasing or increasing the diffusion probabilities via some edges by a constant value.

(4) **Monotone [27]**: This strategy constrains the rumor diffusion through decreasing the diffusion probabilities with time. We fit this strategy into our scenario also by decreasing the diffusion probabilities via edges with time. Before we conduct the diffusion constraining algorithms, over each network, we start the diffusion of sensitive information from the node with the highest out-degree and start the diffusion of non-sensitive information from a randomly chosen node both for 50 rounds. Then, the users which receive sensitive information during the

In this paper, we study the problem of constraining the diffusion of sensitive information in social networks while preserving the diffusion of non-sensitive information. We model the diffusion constraining measures as the variations of diffusion probabilities via social links, and model the problem of interest as adaptively determining the probability variations through a constrained minimization problem in multiple rounds. We utilize the CCMAB framework to jointly design our solutions in the fully-known and semi known networks. Over the fully-known network, we propose the CCMAB based algorithm ADFN to efficiently determine the probability variations via social links. Over the semi-known network, for tackling the challenge of unknown diffusion abilities of partial users, we propose the algorithm ADSN to iteratively learn the unknown diffusion abilities and determine the probability variations based on the learned diffusion abilities in each round. The analysis of regret bound and extensive experiments have been conducted to justify the superiority of our solutions. In addition, in the current work, we define the constraint of maintaining the sum of diffusion probabilities via edges in the objective problem, for the aim of preserving the global diffusion ability of the whole network on diffusing nonsensitive informations. In the future work, we will explore other relevant solutions such as simultaneously minimizing the sensitive information diffusion and maximizing the nonsensitive information diffusion.

Chapter – 10 Referen ces

- [1] Y. Li, J. Fan, Y. Wang, and K. L. Tan, “Influence maximization on social graphs: A survey”, in IEEE Transactions on Knowledge and Data Engineering (TKDE), vol. 30, no. 10, pp. 1852- 1872, 2018.
- [2] L. Sun, W. Huang, P. S. Yu, and W. Chen, “ Multi-round influence maximization”, in Proc. ACM SIGKDD, 2018.
- [3] Q. Shi, C. Wang, J. Chen, Y. Feng, and C. Chen, “Post and repost: A holistic view of budgeted influence maximization”, in Neurocomputing, vol. 338, pp. 92-100, 2019.
- [4] X. Wu, L. Fu, Y. Yao, X. Fu, X. Wang, and G. Chen, “GLP: a novel framework for group - level location promotion in Geo-social networks”, in IEEE/ACM Transactions on Networking (TON), vol. 26, no. 6, pp. 1-14, 2018.
- [5] Y. Lin, W. Chen, and J. C. Lui, “Boosting information spread: An algorithmic approach”, in Proc. IEEE ICDE, 2017.
- [6] Y. Zhang, and B. A Prakash, “Data-aware vaccine allocation over large networks”, in ACM Transactions on Knowledge Discovery from Data (TKDD), vol. 10, no. 2, article 20, 2015.
- [7] Q. Shi, C. Wang, J. Chen, Y. Feng, and C. Chen, “Location driven influence maximization: Online spread via offline deployment”, in Knowledge-Based Systems, vol. 166, pp. 30-41, 2019.
- [8] H. T. Nguyen, T. P. Nguyen, T. N. Vu, and T. N. Dinh, “Outward influence and cascade size estimation in billion-scale networks, in Proc. ACM SIGMETRICS, 2017.
- [9] B. Wang, G. Chen, L. Fu, L. Song, and X. Wang, “Drimux: Dynamic rumor influence minimization with user experience in social networks”, in IEEE Transactions on Knowledge and Data Engineering (TKDE), vol. 29, no. 10, pp. 2168-2181, 2017.
- [10] Q. Shi, C. Wang, D. Ye, J. Chen, Y. Feng, and C. Chen, “Adaptive Influence Blocking: Minimizing the Negative Spread by Observation-based Policies”, in Proc. IEEE ICDE, 2019.


- [11] S. Wen, J. Jiang, Y. Xiang, S. Yu, W. Zhou, and W. Jia, “To shut them up or to clarify: Restraining the spread of rumors in online social networks”, in *IEEE Transactions on Parallel and Distributed Systems*, vol. 25, no. 12, pp. 3306–3316, 2014.
- [12] X. He, G. Song, W. Chen, and Q. Jiang, “Influence blocking maximization in social networks under the competitive linear threshold model”, in *Proc. SIAM SDM*, 2012.
- [13] W. Chen, A. Collins, R. Cummings, T. Ke, Z. Liu, D. Rincon, X. Sun, Y. Wang, W. Wei, and Y. Yuan, “Influence Maximization in Social Networks When Negative Opinions May Emerge and Propagate”, in *Proc. SIAM SDM*, 2011.
- [14] C. Budak, D. Agrawal, and A. El Abbadi, “Limiting the spread of misinformation in social networks”, in *Proc. ACM WWW*, 2011.
- [15] C. Song, W. Hsu, and M. L. Lee, “Temporal influence blocking: minimizing the effect of misinformation in social networks”, in *Proc. IEEE ICDE*, 2017.
- [16] G. Giakkoupis, R. Guerraoui, A. Jegou, A.M. Kermarrec, and N. Mittal, “Privacy-conscious information diffusion in social networks”, in *International Symposium on Distributed Computing*, pp. 480–496, Springer, 2015.
- [17] Q. Yao, C. Zhou, L. Xiang, Y. Cao, and L. Guo, “Minimizing the negative influence by blocking links in social networks”, in *International conference on trustworthy computing and services*, pp. 65–73, 2014.
- [18] H. Tong, B. A. Prakash, T. Eliassi-Rad, M. Faloutsos, and C. Faloutsos, “Gelling, and melting, large graphs by edge manipulation”, in *Proc. ACM CIKM*, 2012.
- [19] M. Kimura, K. Saito, and H. Motoda, “Minimizing the Spread of Contamination by Blocking Links in a Network”, in *Proc. AAI*, 2008.
- [20] E. B. Khalil, B. Dilkina, and L. Song, “Scalable diffusion-aware optimization of network topology”, in *Proc. ACM SIGKDD*, 2014.
- [21] M. M. Kircher, “A woman named Isis claims shes been blocked from signing into Facebook”, <https://www.businessinsider.com/woman-named-isis-blocked-facebook-2015-11>, 2015.
- [22] S. Fiegerman, “Facebook, google, twitter accused of enabling isis”, <https://money.cnn.com/2016/12/20/technology/twitter-facebook-google-lawsuit-isis/index.html>, 2016.
- [23] D. Kempe, J. Kleinberg and E. Tardos, “Maximizing the spread of influence through a social network”, in *Proc. ACM SIGKDD*, pp. 137–146, 2003.

- [24] S. Feng, G. Cong, A. Khan, X. Li, Y. Liu, and Y. M. Chee, “Inf2vec: Latent Representation Model for Social Influence Embedding”, in Proc. IEEE ICDE, 2018.
- [25] A. Guille and H. Hacid, “A predictive model for the temporal dynamics of information diffusion in online social networks”, in Proc. ACM WWW, 2012.
- [26] Y. Yang, J. Tang, C.W. Leung, Y. Sun, Q. Chen, J. Li and Q. Yang, “RAIN: Social Role-Aware Information Diffusion”, in Proc. AAAI, 2015.
- [27] X. Xu, X. Chen, “Modeling time-sensitive information diffusion in online social networks”, in Computer Communications Workshops (INFOCOM WKSHPS), pp. 408–413, IEEE, 2015.
- [28] A.L. Barabasi and R. Albert, “Emergence of scaling in random networks”, in Science, vol. 286, no. 5439, pp. 509–512, 1999.
- [29] J. Iribarren and E. Moro, “Impact of human activity patterns on the dynamics of information diffusion”, in Physical review letters, vol. 103, no. 3, pp. 038702, APS, 2009.
- [30] V. Klee and G.J. Minty, “How good is the simplex algorithm”, in WASHINGTON UNIV SEATTLE DEPT OF MATHEMATICS, 1970.
- [31] L. G. Khachiyan, “A polynomial Algorithm in Linear Programming”, in Soviet Mathematics Doklady, vol. 20, no. 1, pp. 191–194, 1979.
- [32] N. Karmarkar, “A new polynomial-time algorithm for linear programming”, in Proc. ACM symposium on Theory of computing, pp. 302-311, ACM, 1984.
- [33] Y. Gai, B. Krishnamachari, and R. Jain, “Combinatorial network optimization with unknown variables: Multi-armed bandits with linear rewards and individual observations”, in IEEE/ACM Trans. on Networking (TON), vol. 20, pp. 1466–1478, 2012.
- [34] W. Chen, Y. Wang, and Y. Yuan, “Combinatorial multi-armed bandit: General framework and applications”, in Proc. ACM ICML, pp. 151–159, 2013.
- [35] P. Auer, N. Cesa-Bianchi, and P. Fischer, “Finite-time analysis of the multiarmed bandit problem”, in Machine learning, vol. 47, pp. 235–256, Springer, 2002.
- [36] P. Auer, “Using confidence bounds for exploitation-exploration trade-offs”, in Journal of Machine Learning Research, vol. 3, pp. 397-422, 2002
- [37] T. L. Lai, and H. Robbins, “Asymptotically efficient adaptive allocation rules”, in Advances in applied mathematics, vol. 6, no. 1, pp. 422, 1985.
- [38] S. Wang, and L. Huang, “Multi-armed Bandits with Compensation”, in Proc. NeurIPS, 2018.

- [39] Barabási-Albert model, [https://en.wikipedia.org/wiki/Barabási-Albert model](https://en.wikipedia.org/wiki/Barabási-Albert_model), Wikipedia, 2018.
- [40] S. Lei, S. Maniu, L. Mo, R. Cheng and P. Senellart, “Online influence maximization”, in Proc. ACM SIGKDD, 2015.
- [41] M. Karsai, M. Kivela, R. K. Pan, K. Kaski, J. Kertész, A. Barabási and J. Saramaki, “Small but slow world: How network topology and burstiness slow down spreading”, in Physical Review E, vol. 83, no. 2, pp. 025102, APS, 2011.
- [42] S. Myers, C. Zhu and J. Leskovec, “Information diffusion and external influence in networks”, in Proc. ACM SIGKDD, 2012.
- [43] S. Mannor and O. Shamir, “From bandits to experts: On the value of side-observations”, in Proc. NeurIPS, 2011.
- [44] X. Wu, L. Fu, J. Meng, and X. Wang, “Evolving Influence Maximization”, in arXiv preprint arXiv:1804.00802, 2018.
- [45] Z. Wen, B. Kveton, M. Valko, and S. Vaswani, “Online influence maximization under independent cascade model with

Chapter - 11

Appendix :



View Diffusion of Tweet Sensitive x

localhost:9090/Adaptive%20Diffusion%20Of%20Sensitive%20Information%20In%20Online%20Social%20Networks/A_View_Tweet_Sensitive_Information.jsp

Home User **Admin Server**

Adaptive Diffusion Of Sensitive Information In Online Social Networks



View All Diffusion of Tweet Sensitive Information Details...

ID	Tweet Name	User Name	Tweet Desc Details	Date and Time
0	Pendrive	omkar	sandesk pen drive is external storage device and is manufactured by sandesk which is for slum people	16/10/2020 13:31:46

[Back](#)

Server Menu
[Home](#)
[Logout](#)

View_All_Negative_Information x

localhost:9090/Adaptive%20Diffusion%20Of%20Sensitive%20Information%20In%20Online%20Social%20Networks/A_View_All_Negative_Information.jsp

Home User **Admin Server**

Adaptive Diffusion Of Sensitive Information In Online Social Networks




View All Negative Information...

ID	Tweet Name	User Name	ReTweet Details	Date and Time
3	Hp_Tab	rakesh	it is bad tab.	16/10/2020 13:19:03

[Back](#)

Server Menu
[Home](#)
[Logout](#)



Welcome to Registration Form

User Name (required)

Password (required)

Email Address (required)

Mobile Number (required)

Date of Birth (required)

Select Gender (required) --Select--

Address

Enter Pincode (required)

Select Network (required) --Select--

Select Profile Picture (required) No file chosen

Back

Server Menu

Home


Logout

Sidebar Menu

Home

Tweet Server

User



Server Main... x User Friend Request... x +

localhost:9090/Adaptive%20Diffusion%20Of%20Sensitive%20Information%20In%20Online%20Social%20Networks/U_FriendReq.jsp

Adaptive Diffusion Of Sensitive Information In Online Social Networks



All Friend Requests:



Name	Majeeth
Status	Accepted

Back

Sidebar Menu

- Home
- LogOut

Server Main... x User Add Tweets... x +

localhost:9090/Adaptive%20Diffusion%20Of%20Sensitive%20Information%20In%20Online%20Social%20Networks/U_AddTweets.jsp

Adaptive Diffusion Of Sensitive Information In Online Social Networks



Adding Tweet Details...



Tweet Name (required)	BMW
Select Tweet image (required)	Choose File BMW.jpg
Description	BMW is a costly car and not manufactured for

Create Tweet & Publish

Back

Sidebar Menu

- Home
- LogOut



Chapter-12

Execution Process

Backend process:

- ☐ Connect to MySQL database.
- ☐ Go to start → run → SQLyog → ok
- ☐ It will be connected to MySQL database.
- ☐ Create a new user for your project.
- ☐ Sql>create user username identified by password ; → enter
- ☐ Sql>grant dba to username ; → enter
- ☐ Sql>type password ; → enter
- ☐ Sql>select * from tab ; → enter
- ☐ No rows are selected because it is the new user of our project.
- ☐ Then minimize SQLyog.
- ☐ Click on the project code, next click → databases, click → databases.sql.
- ☐ Right click → databases.sql and click → edit on notepad++.
- ☐ The tables will be imported and automatically the imp.exe command prompt closes.
- ☐ Again go to SQLyog.
- ☐ Sql>select * from tab;
- ☐ Tables will be displayed.

Frontend:

Using Net beans

1.Project

Deployment

2.Connectivity

3.Run to execute

1.Project Deployment:

Execution Process

Click on NetBeans IDE ☐ file ☐ import ☐ existing projects into workspace ☐ copy code path
☐ click finish.

2. Connectivity

- ☐ Start NetBeans IDE.
- ☐ In the IDE, choose File > New Project.
- ☐ in the Name and Location page of the wizard,
- ☐ In the Project Name field, type
- ☐ Leave the Use Dedicated Folder for Storing Libraries checkbox unselected.
- ☐ In the Create Main Class field,

You have left the Create Main Class checkbox selected in the New Project wizard, the IDE has created a skeleton main class

- ☐ Save the change by choosing File > Save.

3. Run to execute:

To click Run as ☐ Run on the project

Using Tomcat

Go to project open it -> source code/code -> code for tomcat -> copy the code and paste in web-apps (open tomcat -> web apps) -> code -> web root -> WEB-INF -> config -> system. Properties -> open it Change duser, dpass as you created for the project.

url=jdbc: oracle: thin: @localhost:1521: xe

In URL we have hostname, port number, service name to change this names and number.

Go to oracle where it is installed -> open it and search for tnsnames.ora -> save.

Start Tomcat server then go web browser type URL as

http://localhost:8081

Select Tomcat manager -> enter

Select your project.