

POWER GENERATION THROUGH REGENERATIVE BREAKING SYSTEM

Submitted in partial fulfillment of the requirements for the award of

Bachelor of Engineering degree in
Mechanical Engineering

Kakustham Pavan suri (38150077)

Putta Sri Venkata Durgesh (38150085)



DEPARTMENT OF MECHANICAL ENGINEERING

SCHOOL OF MECHANICAL ENGINEERING

SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY

(DEEMED TO BE UNIVERSITY)

Accredited with Grade "A" by NAAC

JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI - 600119

MAY 2022



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)

Accredited "A" Grade by NAAC | 12B Status by UGC | Approved by AICTE

www.sathyabama.ac.in

DEPARTMENT OF MECHANICAL ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of **KAKUSTHAM PAVAN SURI (Reg no-38150077)** and **PUTTA SRI VENKATA DURGESH (Reg no-38150085)** who have done the Project entitled "POWER GENERATION THROUGH REGENERATIVE BRAKING SYSTEM" under my supervision from September 2021 to April 2022

Internal Guide

Mr. S. Lakshmi Sankar, M.E., (Ph.D)

Head of the Department

Dr. G. Arunkumar, M.E., Ph.D.,


Submitted for Viva voce Examination held on _____

Internal Examiner

External Examiner

DECLARATION

I, Kakustham pavan suri (Regno-38150077), hereby declare that the Project Report titled "POWER GENERATION THROUGH REGENERATIVE BRAKING SYSTEM," which I completed under the supervision of Dr.S.Lakshmi sankar, is submitted in partial fulfilment of the requirements for the award of a Bachelor of Engineering degree in Mechanical Engineering.

A photograph of a handwritten signature in blue ink on a light-colored surface. The signature reads "K. Pavan Suri" and is underlined.


DATE: 20.04.2022

PLACE: CHENNAI

SIGNATURE OF THE CANDIDATE

DECLARATION

I, Putta sri venkata durgesh (Regno-38150085), hereby declare that the Project Report titled "POWER GENERATION THROUGH REGENERATIVE BRAKING SYSTEM," completed under the supervision of Dr.S.Lakshmi sankar, is submitted in partial fulfilment of the requirements for the award of a Bachelor of Engineering degree in Mechanical Engineering.

A rectangular box containing a handwritten signature in blue ink that reads "P.S.V. Durgesh".

DATE:

PLACE:

SIGNATURE OF THE CANDIDATE

ACKNOWLEDGEMENT

We would like to express our gratitude to the Board of Directors of SATHYABAMA for their support and encouragement during this project, which we are happy to report was successfully completed. They have our deepest gratitude.

Dr. S. PRAKASH, M.E., Ph.D., the Dean of the School of Mechanical Engineering and the Head of the Department **Dr. G. Arunkumar, M.E., Ph.D.**, of Mechanical Engineering at the Dept. of Mechanical Engineering, provided us with the necessary support and information at the right time during the progressing reviews, and we are grateful to them for their efforts.

This project has been possible with the invaluable advice, recommendations, and ongoing support provided by our Project Guide **Mr. S. Lakshmi Sankar M.E., (Ph.D.)**

Please accept our sincere gratitude to all Mechanical Engineering faculty and non-faculty members who contributed to the successful completion of this project.

Abstract

There is a need for particular technology to recover energy that is often squandered in today's world because of the energy crisis and the resulting resource depletion. To put it another way, the regenerative braking system is one of those useful advancements for automobiles on the whole. The Kinetic Energy (K.E.) of a vehicle or object is converted into a structure that may either be used immediately or stored for future use. Regenerative braking is an energy recovery technology. It is possible to recover part of the vehicle's K.E. that is lost during the braking process by using the regenerative brake system in automobiles. Alternatively, the vehicle's K.E. is stored or returned to its original layout. During a battery or bank of capacitors, this energy is occasionally put away for use sometime in the future . Energy likewise can be put away with the help of a pivoting flywheel which is one among the premier economical and viable strategy for putting away and recovering power. The current development gives energy-putting away regenerative stopping mechanism by sending the flywheel force as a force having a tendency to go against the forward revolution of a wheel on applying the brakes.

The exceptional slowing down mechanism is specifically stood firm on in footing by a rider-controlled grip instrument, to gather energy more than a few slowing down occasions. Using regenerative braking, electric vehicles use the engine as a generator, and the product is sent to an electrical load. Slowing down has an influence, and power is recovered by transferring energy to the heap.

TABLE OF CONTENTS

	Page no
Bonafide certificate	I
Declaration	II
Acknowledgement	III
Abstract	IV
Table of Contents	V
List of Tables	V-VI
List of Figures	VII
CHAPTER 1: INTRODUCTION	1-4
1.1 Introduction	1
1.2 Working Principle	1
1.3 Types of Regenerative Braking System	2
1.4 Problem statement	3
1.5 Applications	4
1.6 Advantages	4
1.7 Disadvantages	4
1.8 Future Scope	4
CHAPTER 2: LITERATURE REVIEW	5-10
2.1 History	
CHAPTER 3: METHODOLOGY	11-24
3.1 Fabrication	11
3.2 List of Materials	13
3.3 Equipments used	20

CHAPTER 4: RESULTS AND DISCUSSION	25-26
4.1 Result	25
4.2 Tabulation	25
4.3 Discussion	26
CHAPTER 5: CONCLUSION AND RECOMMENDATIONS	27-28
5.1 Conclusion	27
5.2 Reecommendations	27
REFERENCES	
LIST OF TABLES	
Table 3.2 List of Materials	13
Table 4.2 Result Table	25
LIST OF FIGURES	
Fig 1.2 Regenerative braking mechanism	2
Fig 2.1 Flybrid	5
Fig 2.2 Flywheel	6
Fig 3.1.1 Design Front view	11
Fig 3.1.2 Design Side view	11
Fig 3.1.3 Design Top view	11
Fig 3.2.1 Shaft	14
Fig 3.2.2 Bearing	14
Fig 3.2.3 bicycle wheel	15
Fig 3.2.4 Sewing machine motor	15
Fig 3.2.5 Pulley	16
Fig 3.2.6 Multimeter	16
Fig 3.2.7 pulley rope	17
Fig 3.2.8 Brake wheel	17
Fig 3.2.9 Brake spindle	18
Fig 3.2.10 Electric wire	18
Fig 3.2.11 Brushed D.C. Motor	19

Fig 3.3.1 Cutting saw	20
Fig 3.3.2 Table saw	21
Fig 3.3.3 Drilling machine	22

CHAPTER 1

1.1 Introduction


The recent focus of advanced car research has shifted from increasing productivity and lowering exhaust gas emissions to addressing the current lack of reliable optional energy sources. A significant amount of active energy is lost during the frequent slowing and steady driving at low speeds on allotted city courses for business cars, for example, which results in a greater fuel consumption and GHG release than other on-street vehicles. Several efforts have been made to improve automobiles in the future. EGR and DPF after treatment is perhaps the best strategy to manage vehicle yield, outstandingly for NOx and residue. 'Mechanical mix' Although this method may reduce GHG emissions, the low-temperature igniting of this invention causes an increase in the amount of fuel used. It's impossible to solve the energy crisis by sacrificing the efficiency of a motor in exchange for less pollution. In order to meet the goal of reducing GHG emissions, a significant reduction in business cars is needed.

Advances in advanced automotive research have focused on increasing productivity and reducing emissions since there are no solid alternative energy sources available at this time. Businesses, such as refuse trucks and conveyance vehicles that constantly slow down and operate at low speeds on allotted municipal courses, consume more fuel and emit more Green House Emission Gas (GHG) than other on-road vehicles, bringing about more prominent fuel utilization and GHG emanations. A few endeavors have been made to further develop autos later on. EGR and DPF after treatment are a popular mechanical combination for settling vehicle discharge, especially for NOx and residue. EGR and DPF are two of the most used diesel particulate filters. The low temperature burning of this invention causes an increase in fuel punishment, hence this technology will not reduce GHG emissions. It's not possible to solve the energy crisis by sacrificing motor skills in exchange for reduced toxins. The usage of commercial vehicles must be reduced significantly if we are to achieve our overall goal of reducing GHG emissions.

It has been shown that the front pivot of commercial vehicles loses between 50 and 80 percent of their braking energy and that this misfortune changes with time. That's why only around 20 to 30 percent of the regeneration energy potential has been measured.

1.2 Working Principle

Regenerative slowing down is a slowing down method that utilizes the motor's mechanical energy by changing over it into electrical energy, which is then stored in the vehicle's battery. Hypothetically, the regenerative slowing mechanism may use a similar standard to an alternator to power the battery by changing over a significant portion of its motor energy.



Regenerative braking mechanism

Regenerative braking uses the car's electric engine to slow the vehicle down when the driver presses the brake pedal, and the electric engine works backwards to do so. The motor functions as a generator and recharges the batteries while going backwards. It was still operating at full speed while the motor was moving ahead and drawing energy from the battery. Because it uses less gasoline and emits less pollutants thanks to regenerative braking, electric vehicles are more environmentally friendly. These kinds of brakes are most suited to urban driving environments, where stop-and-go traffic is common.

1.3 Types of Regenerative Braking System

This system uses springs, flywheels, electromagnetic, and hydraulic processes to convert energy. A Regenerative Braking System with a cross-over electromagnetic-flywheel has just evolved. As a result, the shifting efficiency and applications for every kind of Regenerative Braking System are different. Each type makes use of an alternative energy change or capacity method.

1.3.1 Electromagnetic

1.3.2 Flywheel

1.3.3 Electromagnetic flywheel

1.3.4 Spring

1.3.5 Hydraulic

1.3.1 Electromagnetic

In an electromagnetic framework, the vehicle's drive shaft is connected to an electric generator that utilizes an attractive field to confine the turn of the drive shaft, easing back the vehicle and making power. By virtue of electric and hybrid vehicles, the power created is delivered off the batteries, giving them charge. In inward ignition vehicles, the power can be used to control the vehicles equipment or delivered off a battery that may hence be utilized to help the vehicle's power yield. This technique is presently being utilized in a few Le Mans Prototype hustling vehicles.

1.3.2 Flywheel

Flywheel Regenerative Braking System utilises a transmission and gearbox to revolve a flywheel connected to the drive shaft for braking purposes. The spinning flywheel may then exert force on the vehicle's drive shaft, providing it with a source of power.

1.3.3 Electromagnetic flywheel

The electro flywheel regenerative brake is a half and half of electromagnetic and flywheel Regenerative Braking Systems. The electromagnetic structure is shown the fundamental standards of the power period, however the energy is put away in a flywheel instead of batteries. The flywheel might be considered a mechanical battery that stores and deliveries electrical energy. Electric flywheel Regenerative Braking System is a more financially savvy power limit method since flywheel batteries have a more extended life expectancy than lithium-molecule batteries.

1.3.4 Spring

Vehicles driven by humans, such as bicycles and wheelchairs, usually use a regenerative system that uses stacked springs. Human-controlled vehicles, like bikes and wheelchairs, frequently utilize a spring-stacked regenerative stopping mechanism. During slowing down, a loop or spring is twisted around a cone to store energy as versatile potential in a spring regenerative stopping mechanism. Driving up a hill or across an ugly environment may be made easier with the return of the potential.

1.3.5 Hydraulic

An electric motor generates power that is then utilised to compress fluid in the Hydraulic Regenerative Braking System. It is fairly uncommon for people to choose nitrogen gas as their working liquid. As 6 compressed liquid does not disperse energy after some time, water-controlled Regenerative Braking Systems offer the longest energy stockpiling limit of any structure being used today. Compacting gas by means of a siphon, then again, is an awkward activity that seriously restricts the regenerative stopping mechanism's power.

1.4. Problem statement

Automobile manufacturers have a significant challenge in this century's quest to decrease vehicle fuel consumption and emissions owing to dwindling fuel supplies and an accompanying worsening of the world's air pollution crisis. Ozone, carbon monoxide, and other air pollutants present in metropolitan areas are all attributed to conventional ICE automobiles by the United States Environmental Protection Agency (EPA). According to one research, the brake uses between 20 and 25 percent of the energy available. The appearance of the Regenerative Braking System is viewed as an answer for these four challenges since it recuperates lost energy and returns it to the matrix in another structure. Regenerative Braking System has a significant and positive impact, but it also has its own set of challenges to overcome; one of the most major concerns is the battery that should be used in this kind of vehicle.

1.4 Applications

- Kinetic energy re-use system.
- It is also used in electric lift engines and crane lifting engines.

- Electric and half-hybrid automobiles, electric rail route vehicles, electric motorcycles, and so on all use this technology.
- A transport architecture that moves material from one workstation to the next and finishes at a predetermined distance after an authorised stretch might benefit from this technology.

1.5 Advantages

- Better Performance.
- Eliminates contamination connected with supply generation.
- Depending on the machine cycles, vehicle plan, computerised control plan, and productivity of the individual section of the machine, the fuel use may be reduced.
- Decreased mileage of Engines.
- Cutting down on the cost of replacement brake linings, the cost of labour for the establishment and personal machine time. • Diminished Brake Wear
- Diminished emanations Cuts down on contamination connected with power age, motor decoupling diminishes the absolute number of transformations and accordingly motor emanations.
- Smaller accessories - decreasing the size of the fuel tank and hence the vehicle's weight.

1.6 Disadvantages

The regenerative brakes have a little margin of safety when it comes to stopping a car, thus a high number of vehicles that use them also have rubbing brakes functioning nearby. This is one reason why regenerative brakes don't safeguard all of the slowing down energy.

- Excessive expenses for parts, plan, and establishment.
- As opposed to dynamic brakes, regenerative brakes are expected to match the power given by the data supply (DC and AC supplies), and this is done interestingly with the guide of progression of power gadgets.
- Regenerative slowing mechanism wellbeing is compromised when the batteries it are completely energized to store the recovered energy. In the event of an excessive charge, the battery's voltage would exceed an acceptable threshold of safety.
- Depending on the complexity of the strategy, more care may be required.

1.7 Future Scope

However, future turns of events, like ultra-capacitors, flywheels, and pressure-driven frameworks, may have much higher power limits, increasing the likelihood of relying significantly more intensely on regenerative slowing down components, even at high velocities and high stops, with the possibility to decrease or even wipe out the grinding stopping mechanism.

CHAPTER 2

LITERATURE REVIEW

2.1 History

1. The Flybird was the first of these devices to be unveiled. After accounting for internal losses, the system has a total energy capacity of 400 kJ and a mass of 24 kg. For a total of 6.67 seconds, a power increase of 60 kW (80.4 HP, 81.6 PS) may be applied. The flywheel has a diameter of 240 mm, weighs 5.0 kg, and rotates at 64,500 revolutions per minute (rpm). Its maximum torque is 18 Nm (13.3 ft lbs). The system has a 13-liter capacity.



2.1 Flybrid

Formula one

FIA approved the usage of KERS' 81 hp (60 kilowatts; 82 ponies) in the 2009 Formula One season's regulations, as a sign of Formula One's support for environmentally conscious solutions. A flywheel-based device was first tested in 2008, and it may be used to store mechanical or electrical energy, depending on the user's preference (as a battery or super capacitor).



2.2flywheel

- 2 Tests of the KERS system in 2008 resulted in two minor mishaps. When Red Bull Racing tested their KERS batteries for the first time in July, the most important thing occurred: it broke down and caused a fire alarm that prompted the group's production line being cleared [3].
- 3 A BMW Sauber mechanic was electrocuted during a test at the Jerez track after he came into touch with Christian Klien's KERS-equipped car, which had just been out of the shop for seven days.
4. Ferrai, Renault, BMW, and McLaren were the first four teams to use KERS in 2009, and they all did so sooner or later all through the season. Renault and BMW quit using the innovation all through the season. Vodafone McLaren Lewis Hamilton's triumph at the Hungarian Grand Prix on July 26 was whenever a Mercedes first group had dominated a F1 race utilizing a KERS-prepared suspension. The group's second KERS-prepared vehicle came in fifth spot. ' Hamilton's colleague Heikki Kovalainen qualified second and completed second in the following race, becoming Hamilton the primary driver to acquire the post position with a KERS vehicle. 5 This was the first time a front row of all KERS engines was used. Kimi Räikkönen won in the Belgian Grand Prix on August 30, 2009, utilizing a KERS-prepared Ferrari. Second-put Giancarlo

Fisichella said that "Truly, I was faster than Kimi... He took me in light of KERS at the beginning" since it was whenever KERS first had straightforwardly added to the race triumph.

CARMAKERS

- Honda is one of three automakers that have experimented with KERS frameworks so far. Peugeot Sport divulged the Peugeot 908 HY during the 2008 1,000 km of Silverstone, a cross breed electric adaptation of the diesel 908 with KERS.
- Peugeot intended to race the vehicle in the 2009 Le Mans Series season, notwithstanding the way that it was not ready to score title focuses. The Hybrid Air power train from Peugeot is similarly compressed air regenerative slowing down.
- Vodafone McLaren Mercedes started testing 13 of its KERS in September 2008 at the Jerez test circuit in anticipation of the 2009 F1 season, in spite of the way that it was not yet known whether they may be working an electrical or mechanical system at that point.
- By 2010, Freescale Semiconductor will work with McLaren Electronic Systems to additionally foster KERS for McLaren's Formula One vehicles. This was first reported in November 2008. The two players accepted this cooperation would work on McLaren's KERS framework and assist the framework with separating down to street vehicle innovation.
- While competing in the 24 Long Periods of Tokachi event in July 2007, Toyota used a super capacitor to help it recover from the loss.
- Regenerative slowing down has been utilized by BMW on their E90 3 Series and in late forms like the F255 Series under the Efficient Dynamics screen.
- Blue Motion regenerative slowing down advances are found in the MK7 Golf and MK7 Golf Estate/Wagon models, as well as other VW bunch brands including SEAT, Skoda, and Audi.

Auto part makers

- 3 As part of Bosch Motorsport Service, a KERS is being developed for use in motorsport. A lithium-particle battery with a variable limit or a flywheel, a four-to eight-kilogram electric

motor (with a most extreme power level of 60 kW or 80 hp), and the KERS controller for power and battery the board are all included in these power storage frameworks for crossover and motor capabilities. Electric half-breed systems from Bosch are also available for light-duty and corporate use.

4 Motorcycles

In the 2008 Valencian Grand Prix season-ending 125cc Valencian Grand Prix, KTM hustle manager Harald Bartol discovered that the manufacturing facility rushed with a secret dynamic energy recovery framework (KERS). Due to the fact that this was against the rules, they were unable to carry it out going forward.

5 Use in civilian transport

Cars

Numerous electric cars from the early days of the AMC Amitron concept vehicle have regenerative brakes. Regenerative stopping mechanisms can't completely imitate customary brake work for drivers, however there are proceeding with progressions.

The adjustments used to decide when energy will be recovered and while contact slowing down is utilized to dial back the vehicle influences the manner in which the driver feels the braking activity.

Car examples:

- Audi e-tron
- Ford Fusion Hybrid
- Hyundai Kona Electric
- Nissan Leaf
- Tesla Model
- Toyota Prius

Bicycles

Non-electric bicycles may also benefit from regenerative braking. With the assistance of understudies from the University of Michigan, the EPA assisted with fostering the Hydraulic Regenerative Brake Launch Assist (RBLA). Electric motorcycles with direct-drive centre point engines can easily get you there.

Objectives

- To shorten the time it takes to brake by employing regenerative brakes and producing power by using kinetic energy to generate electricity.
- To be able to rapidly and effectively regulate the speed and stop a vehicle without sticking.

CHAPTER 3


METHODOLOGY

3.FABRICATION


3.1 DESIGN


Only the fundamental braking system will suffice, and a regenerative braking mechanism may not be enough on its own. This is because of the restrictions on energy dissipation that come with operating at such high voltages. Plan limitations may prevent the frameworks from working at those levels. Because of basic degree of security associated with the framework, dependability becomes begging to be proven wrong and it requires a frictional slowing mechanism to coincide with electrical regenerative braking mechanism. This frames a half and half slowing mechanism, and that implies:

1. Very much like hybrid drive frameworks, there can be many plan arrangements and control techniques.
2. The design and management of the structure should ensure that the vehicle's braking performance is optimal while also catching, if necessary, however much energy as could reasonably be expected.



11





3.2 List of Materials

S.NO	NAME OF PARTS	DESCRIPTION	QUANTITY
1.	Solid shaft	14mm DIA	0.62m
2.	Bearing	Internal DIA 14mm	2 pieces
3.	Bicycle wheel	Internal DIA 14mm	1 piece
4.	Sewing Machine Motor	6500 r.p.m	1 piece
5.	Pulley	Internal DIA 14mm	1 piece
6.	Multimeter		
7.	Pulley rope	V-BELT	600mm length
8.	Brake wheel		
9.	Brake spindle		1 piece
10.	Electric Wires	Copper wire	6m
11.	Brushed D.C Motor	Brushed D.C 12v	1piece

3.2.1 Solid shaft

This mild steel solid shaft served as the foundation for the wheel and brake spindle. It was necessary to mount the wheel to the shaft. In order to link one of the shafts to the electric engine, a pulley and rope were utilized.

Movement is communicated from the engine to the pulley, and afterward from the pulley to the wheel's shaft, as soon as it is started by the engine.



3.2.1 Shaft


3.2.2 Bearing

A course is a gadget having an enemy of rubbing bearing in it, which permits any strong shaft to turn while the external ring stays still. The inner diameter of the bearing employed in the project is 14 mm. It is implanted in the bearing, which is used for the development of rotation in the shaft.



3.2.3 Bicycle wheel

Vehicle wheels are represented by the bicycle wheels used in this illustration. To demonstrate the movement and application of brakes in a typical car, it is utilised in this way. The pulley and the motor are linked by a belt to the bicycle wheel, which is then turned by the motor.



3.2.4 Sewing Machine Motor

An AC 220V Sewing Machine Motor may reach a maximum speed of 6500 RPM. Towards the end of the motor, there is a little pulley where the belt is attached. The motor's acceleration mechanism may be utilised to raise and decrease the motor's speed as needed.




3.2.5 Pulley

The motor's rotatory action is transferred to the shaft through the pulley. The internal diameter of the pulley utilised is 14 mm. The belt serves as the link between the pulleys.



3.2.6 Multimeter

A **multimeter** is an equipment used for measuring current, voltage, and resistance, as well as for troubleshooting household appliances and electrical components of vehicles.



3.2.7 Pulley rope

The power from the motor is transferred to the shaft by means of a pulley rope.



3.2.8 Brake wheel

The shaft's progress may be halted by applying pressure to the braking wheel. The internal diameter of the braking wheel, which is 14 mm, is attached to the shaft. Polyvinyl Chloride is the material used to construct the brake rotors (PVC).



3.2.9. Brake spindle

The motor's tip is used to drive a gear in the braking spindle. Shaft development is dialed back once the stuff on the slowing down axle and one more stuff on the brake wheel network appropriately.




3.2.10 Electric Wires

The internal wire is made with copper and it is secured. They are used to move the power from the motor to the multimeter.



3.2.11. Brushed D.C Motor

As a Dynamo, this engine is put to good use. Small braking wheel is attached to motor tip and gear meshes with the brake wheel causes the spindle to move. Electrical energy is converted from dynamic energy by the pivoting axle's motor and electro-attractive force. The motor's voltage limit is 12 volts.



3.3 Equipments used in Fabrication

CUTTING SAW

A saw is a device that has a sharp edge, wire, or chain with a toothed edge that is solid and sturdy. It is used to cut various materials, such as wood, metal, and stone, on a regular basis. The material is sliced by pressing the toothed edge against it and pushing it aggressively forward and backward or continually forward.



Table saw

A table saw, otherwise called a seat saw, is a carpentry device with a round saw state of the art fixed on an arbor and controlled by an electric engine, either straightforwardly, through a belt, or by means of cog wheels and stuff trains. Through the most elevated place of the table, the sharp edge helps the material, which is usually wood, to be cut.



Drilling

Penetrating is a metal evacuation technique wherein a bore is utilized to make or grow a roundabout opening in strong materials. Utilizing a bore is a rotating cutting strategy. The piece is turned at speeds going from hundreds to thousands of cycles each moment while being constrained against the work piece. While the front line is constrained against the workpiece, it removes chips at the drill opening's edge.





PROCEDURE

- ✚ At first for the frame work we used a plywood with thickness of 18mm and cut it using a table saw with length of 760mm and breadth of 580mm.
- ✚ For holding the bearings we cut the wood to two rectangular pieces drilled holes with DIA 20mm and fixed the bearing in that drilled holes.
- ✚ For placing the rectangular bars we removed certain amount of wood material to the depth of 20mm.
- ✚ As we place the rectangular wooden bars at its position with a distance in between of 420mm.
- ✚ The shaft of DIA 14mm is placed in between the bearings .
- ✚ The shaft consists of a wheel,pully and brake wheel.
- ✚ The DIA of wheel is 120mm and internal DIA of 14mm, DIA of the pully is 40mm and internal DIA of 14mm,the brake wheel DIA is 60mm and internal DIA of 14mm as of shaft.
- ✚ Then we placed the sewing motor at a distance of 120mm from the shaft.
- ✚ A speed regulator is connected to the sewing motor to adjust speed levels.
- ✚ For connecting the motor and shaft using a belt, which helps to transmit motor energy to rotate the shaft.
- ✚ The brake wheel is attached to the tip of the dynamo which is attached to a brake spindle .which helps in generating energy as well as stop the vehicle.
- ✚ The output of the dynamo is connected to the multimeter using copper wire.
- ✚ The output can be seen in multimeter which displays the certain value of energy generated during braking. The value increases depending on speed of the vehicle.

Precautions used during Fabrication

- Apron is worn
- Gloves are used
- Face shield
- Proper coolant is supplied during the Drilling process.

Final Fabrication



CHAPTER 4

RESULTS AND DISCUSSION

4.1 Results

After the successful testing, the model is run and the data acquired under different loading conditions are recorded and tabulated.

4.2 Result table

S.NO	RPM	VOLTAGE OUTPUT
1.	500	2.3V
2.	1300	3.1V
3.	1700	4.2V
4.	2100	5.2V

As per the outcomes table, the effectiveness of regenerative stopping mechanisms utilizing D.C. engines ascends as the rakish speed of the engine increments. This is because the recovered energy increases with the speed of the vehicle, making the system more efficient. The engine is less proficient at lower speeds, in this manner the misfortunes are bigger, yet at higher velocities, the misfortunes are generally mechanical, for example, contact and air drag.

4.3 Discussion

As the markets for hybrid, electric, and conventionally driven cars with high efficiency and low emissions expand, so too does the rate of development of regenerative braking systems. Battery-electric vehicles (BEVs) now face two major hurdles in the market: their high cost (especially for the battery packs) and their restricted range. Cost reduction, increased vehicle range, and compliance with more stringent safety and emissions regulations will be major future hurdles for system development. Advanced systems that not only stop the car but also collect braking energy will need to have the brake regulation applied to them. This will be necessary.

Summary: present, "original" regenerative braking methods don't give a second thought to safety. The tests did on one such structure, fitted to a mutt vehicle, raised no security issues. An important factor in determining the strength of a regenerative stopping mechanism may be the capacity of a battery or other energy storage device/framework, that is all there is to its capacity to rapidly change over the dynamic energy of the vehicle into its put away structure.

Essential mechanical designing theory proposes for current frameworks, which can work at exceptionally low power levels ($< 30\text{KW}$, say), the regenerative slowing down part is likely going to be very little, particularly at high speeds. Such frameworks in this way need a significant extra wellspring of slowing down force for medium-high deceleration prevents from such velocities, for example a regular frictionbraking framework.

CHAPTER 5

CONCLUSION AND RECOMMENDATIONS

5.1 Conclusion

Using a regenerative braking system, which is what the cars have, allows the driver to save energy when braking. When the car is slowing down, the battery charge is lost. The regenerative braking system attempts to recover part of that charge. Contact brakes disseminate the heat generated from the converted energy. Generator rotors pivot using this energy to convert mechanical energy from the wheels into precious battery charge. It is impossible to use the regenerative slowing down framework as a major stopping mechanism for a vehicle since it is unable to bring the vehicle to a complete stop.

Increasing the wheel speed (rpm) increases the voltage generated, and vice versa. This has been shown experimentally. D.C. engines are used instead of stepper or servo engines as a regenerative engine since other researchers have used these types of engines. For example, the voltage generated by the gear-operated DC engine is much greater than that of the two other engines.

Accordingly, in any event, somewhere around 11% of the battery's energy might be recuperated utilizing the regenerative stopping mechanism, which would somehow or another be spent to warm rubbing brakes. Therefore, the distance between two charging prerequisites might be expanded by 10 to 15 percent by utilizing regenerative slowing down in the middle of them.

5.2 Recommendations

A few complications may arise if this framework is extended to the present fleet of operational cars, since this is entirely dependent on an experimental test rig. Anti-Lock Braking System should be used to implement this framework since regenerative braking mechanisms do not offer quick braking.

If you're going to use an Anti-Lock Braking System, you'll need a different form of Braking framework, such as Regenerative Braking.

It's necessary to make a few adjustments to the driving style in order to include regenerative braking into a vehicle's architecture. This requires some investment becoming acclimated to, however studies have shown that drivers answer decidedly and attempt to amplify the energy they can recover and hereby broaden their reach.

Carrying out this framework in the current working vehicle will increase the mass of the vehicle so, that consumes extra space. So this component should be considered before plan of the vehicle so that this component could be survived.

the utilization of regenerative slowing down is immovably associated with eco-driving. If eco-it are applied to drive techniques by countless drivers, this could effectively affect traffic stream.

REFERENCES

- [1] Zhang, J., Lu, X., Xue, J., and Li, B. (2008). Regenerative braking mechanism for series hybrid electric city transport. *World Electric Vehicle Journal*, 2(4), 363-369
- [2] Nian, X., Peng, F., & Zhang, H. (2014). Regenerative braking system of electric vehicle driven by brushless DC motor. *IEEE Transactions on Industrial Electronics*, 61(10), 5798-5808
- [3] Boldea, I., Tutelea, L. N., Parsa, L., & Dorrell, D. (2014). Automotive electric propulsion systems with reduced or no permanent magnets: An overview. *IEEE Transactions on Industrial Electronics*, 61(10), 5696- 5711
- [4] Tang, X., Yang, W., Hu, X., & Zhang, D. (2017). A novel simplified model for torsional vibration analysis of a series-parallel hybrid electric vehicle. *Mechanical Systems and Signal Processing*, 85, 329-338.
- [5] Rahman, K. M., Fahimi, B., Suresh, G., Rajarathnam, A. V., & Ehsani, M. (2000). Advantages of switched reluctance motor applications to EV and HEV: Design and control issues. *IEEE transactions on industry applications*, 36(1), 111-121.
- [6]
- [7]
- [8]
- [9]
- [10]
- [11]
- [12]
- [13]
- [14]
- [15]
- [16]
- [17] Sayed Nashit, Sufiyan Adhikari, Shaikh Farhan, Srivastava Avinash and Amruta Gambhire, 'Design, Fabrication and Testing of Regenerative Braking Test Rig for BLDC Motor', 2016.
- [18] Tushar L. Patil, Rohit S. Yadav, Abhishek D. Mandhare, Mahesh Saggam, Ankul Pratap, 'Performance Improvement of Regenerative braking system', *International*
- [19] C. Jagadeesh Vikram, D. Mohan Kumar, Dr. P. Naveen Chandra, 'Fabrication of Regenerative Braking System', *International Journal of Pure and Applied Mathematics Volume 119*, (2018).
- [20] A. Eswaran, S Ajith, V Karthikeyan, P Kavin, S Loganandh, 'Design and Fabrication of Regenerative Braking System', *International Journal of Advance Research and Innovative Ideas in Education-Vol-4 Issue-3* (2018).
- [21] Ketan Warake, Dr. S. R. Bhahulikar, Dr. N. V. Satpute, 'Design & Development of Regenerative Braking System at Rear Axle', *International Journal of Advanced Mechanical Engineering. Volume 8, Number 2* (2018).
- [22] Siddharth K Sheladia, Karan K Patel, Vraj D Savalia, Rutvik G Savaliya, 'A Review on Regenerative Braking

Methodology in Electric Vehicle', International Journal of Creative Research Thoughts, Volume 6, Issue 1 (2018).

[23]

[24] Ehsani Mehrdad, Gao Yimin, Emadi Ali, Modern Electric, Hybrid Electric and Fuel Cell Vehicles, CRC Press, 2010.

[25] Gao, Dr. Yimin, "Regenerative Braking," Encyclopedia of Sustainability Science and Technology, 2012.