

EFFECT OF ISO-BUTANOL ADDITION TO DIESEL FUEL ON PERFORMANCE AND EMISSIONS OF A DI DIESEL ENGINE WITH EXHAUST GAS RECIRCULATION

Submitted in partial fulfillment of the requirements for the award of
**Bachelor of Engineering Degree in
Mechanical Engineering**

BY

NAVEEN KUMAR (38150070)

VINITH K (38150125)



**DEPARTMENT OF MECHANICAL ENGINEERING
SCHOOL OF MECHANICAL ENGINEERING**

SATHYABAMA

**INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)**

**Accredited with Grade "A" by NAAC | 12B Status by UGC |
Approved by AICTE JEPPIAR NAGAR, RAJIV GANDHI SALAI,
CHENNAI – 600119**

May - 2022



SATHYABAMA

**INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)**

Accredited with Grade "A" by NAAC | 12B Status by UGC | Approved by AICTE
Jeppiaar Nagar, Rajiv Gandhi Salai, Chennai – 600 119
www.sathyabama.ac.in



DEPARTMENT OF MECHANICAL ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that this project report is the bonafide work of **NAVEEN KUMAR (38150070)** , **VINITH K (38150125)** who carried out the project entitled **"EFFECT OF ISO-BUTANOL ADDITION TO DIESEL FUEL ON PERFORMANCE AND EMISSIONS OF A DI DIESEL ENGINE WITH EXHAUST GAS RE-CIRCULATION"** under our supervision from November 2021 to May 2022.

Internal Guide

Dr. S.P. VENKATESAN, M.E., Ph.D.,

Head of Department

Dr. G. ARUNKUMAR, M.E., Ph.D.,

Submitted for Viva voce Examination held on _____

Internal Examiner

External Examiner

DECLARATION

We, **NAVEEN KUMAR (38150070)** and **VINITH K (38150125)** hereby declare that the Project Report entitled “**EFFECT OF ISO-BUTANOL ADDITION TO DIESEL FUEL ON PERFORMANCE AND EMISSIONS OF A DI DIESEL ENGINE WITH EXHAUST GAS RE-CIRCULATION**” done by us under the guidance of **Dr. S.P. VENKATESAN, M.E., Ph.D.**, is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in Mechanical Engineering.

DATE:

PLACE: CHENNAI

SIGNATURE OF THE CANDIDATE

ACKNOWLEDGEMENT

I am pleased to acknowledge my sincere thanks to Board of Management of **SATHYABAMA** for their kind encouragement in doing this project and for completing it successfully. I am grateful to them.

I convey my thanks to **Dr. S. PRAKASH, M.E., Ph.D.**, Dean, School of Mechanical Engineering and **Dr. G. ARUNKUMAR, M.E., Ph.D.**, Head of the Department, Dept. of Mechanical Engineering for providing the necessary support and details at the right time during the progressive reviews.

I would like to express my sincere and deep sense of gratitude to my guide **Dr. S.P. VENKATESAN, M.E., Ph.D.**, for his valuable guidance, suggestion and constant encouragement paved way for the successful completion of my project work.

I would like to express my thanks all Teaching and Non-Teaching staff members of the Department of Mechanical Engineering who were helpful in many ways for the completion of the project.

ABSTRACT

Iso-butanol is a second generation biofuel that can possibly further develop energy security and moderate hurtful toxins in responding engines. The current review researches the impact of iso-butanol expansion to diesel fuel on execution and emanations of a solitary chamber direct-infusion diesel motor with fumes gas distribution (EGR). For this goal, four iso-butanol/diesel mixes containing 10%, 20%, 30% and 40% were ready by volume premise and tried in the engine under three EGR rates: 10 to 30% (at augmentations of 10%) with the mix of two infusion timings: 23° and 21° wrench point (CA) before top flawlessly focused (bTDC). Exploratory outcomes showed that the blend of 30% EGR rate, 40% iso-butanol expansion (ISB40) and impeded infusion timing by 2° CA bTDC all the while decreased NO_x discharges from 1284 to 749ppm and smoke obscurity from 20.7 to 1.9% with a slight drop in execution. It was found that higher iso-butanol/diesel mixes require higher EGR levels to achieve ideal degrees of smoke and NO_x outflows. Both hydrocarbon (HC) and carbon-monoxide (CO) discharges introduced a rising pattern at raising EGR rates. At impeded infusion timing, ISB40 mix introduced diminished HC outflows, expanded CO emanations with slight drop in execution contrasted with its infusion at unique timing. . The point of this study is to explore the reasonableness of isobutanol-diesel fuel mixes as another option fuel for the diesel motor, and tentatively decide their impacts on the engine execution and exhaust discharges, in particular brake power, brake explicit fuel utilization (BSFC), brake warm effectiveness (BTE) and emanations of CO, HC and NO_x. For this reason, four distinct isobutanol-diesel fuel mixes containing 5, 10, 15 and 20% isobutanol were ready in volume premise and tried in a normally suctioned four stroke direct infusion diesel motor at full - load conditions at the paces somewhere

in the range of 1200 and 2800 rpm with time periods rpm. The outcomes acquired with the mixes were contrasted with those with the diesel fuel as benchmark. The test results demonstrate that the brakes power marginally diminishes with the mixes containing up to 10% isobutanol, while it altogether diminishes with the mixes containing 15 and 20% isobutanol. There is an expansion in the BSFC in relative to the isobutanol content in the mixes. In spite of the fact that diesel fuel yields the most noteworthy BTE, the mix containing 10% isobutanol brings about a slight improvement in BTE at high engine paces. The outcomes likewise uncover that, contrasted with diesel fuel, CO and NO_x emanations decline with the utilization of the mixes, while HC outflows increment impressively.

TABLE OF CONTENTS

CHAPTER NO	TITLE	PAGE NO
	ABSTRACT	v
	LIST OF TABLES	ix
	LIST OF FIGURES	x
	LIST OF ABBREVIATION	xi
1	INTRODUCTION	1
	1.1 IC ENGINES	1
	1.2 BIO-DIESEL ON IC ENGINE	3
	1.3 OUTLINE OF THE PROJECT	5
2	LITERATURE SURVEY	6
3	AIM AND SCOPE OF THE PRESENT INVESTIGATION	10
	3.1 AIM	10
	3.2 SCOPE	10
	3.3 PROBLEM STATEMENT	11
4	MATERIALS AND METHODS USED	12
	4.1 STUDY OF ADDITIVES AND EMISSION	12
	4.1.1 ISO-Butanol	12
	4.1.2 Emission Overview	14
	4.2 PREPARATION OF BLENDS AND THEIR PROPERTIES	15
	4.2.1 ISB 20	15
	4.2.2 ISB 30	15
	4.2.3 ISB 40	16
	4.3 ENGINE CHARACTERISTICS	16
	4.3.1 Test Procedure	18
	4.3.2 EGR Setup	19

CHAPTER NO	TITLE	PAGE NO
	4.3.3 Engine Testing Software	20
	4.3.4 Gas Analyses	20
5	ANALYSIS OF PERFOEMANCE AND EMISSION	21
5.1	EFFECT OF BLEND ON PERFORMANCE	21
5.1.1	Brake Thermal Efficiency	22
5.1.2	Specific Fuel Consumption	24
5.2	EFFECT OF BLEND ON EMISSION	25
5.2.1	Nitrogen Oxide Emission	25
5.2.2	Carbon Monoxide Emission	27
5.2.3	Hydro Carbon Emission	28
5.2.4	Smoke Capacity	30
6	RESULTS AND CONCLUSIONS	33
6.1	RESULTS AND CONCLUSIONS	33
	REFERENCE	36
	APPENDIX	40

LIST OF TABLES

TABLE NO.	TITLE	PAGE NO.
4.1	Fuel Properties	13
4.2	Properties of Blend (ISB 20)	15
4.3	Properties of Blend (ISB 30)	15
4.4	Properties of Blend (ISB 40)	16
4.5	Engine Specification	17

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE NO.
3.1	AVRA Iso butanol	11
4.1	Fuel Blends	14
4.2	VCR Engine	18
4.3	Schematic of the Experimental Set up	19
4.4	Gas Analysis	20
5.1	Engine Drive	21
5.2	Emission Graph - BTE VS BP	23
5.3	Emission Graph - FC VS BP	24
5.4	Emission Sensing System	25
5.5	Emission Graph - Nox VS BP	27
5.6	Emission Graph - CO VS BP	28
5.7	Emission Graph - HC VS BP	30
5.8	Emission Graph - SMOKE (%) VS BP	32

LIST OF ABBREVIATIONS

BE	-	Biodiesel-Ethanol
BSFC	-	Break Specific Fuel Consumption
bTDC	-	Before Top Dead Centre
BTE	-	Break Thermal Efficiency
CA	-	Crank Angle
CI	-	Compression Ignition
CO	-	Carbon-Monoxide
CO ₂	-	Carbon Dioxide
EGR	-	Exhaust Gas Recirculation
HC	-	Hydro Carbon
HRR	-	Hotness Discharge Rate
IARC	-	International Office for Research on Disease
IC	-	Inside Combustion
ISB40	-	Iso-butanol Addition
NO _x	-	Nitrogen Oxides
PCPs	-	Pinnacle Chamber Pressures
PHRRs	-	Pinnacle Heat Discharge Rates
PM	-	Particulate Matter
SCA	-	Shower Cone Point
SI	-	Flash Start
SMD	-	Sauter Mean Measurement
STP	-	Splash Tip Infiltration
SVD	-	Size-Volume Circulation
VCR	-	Variable Compression Ratio
WHSC	-	World Harmonized Steady-State Cycle

CHAPTER 1

INTRODUCTION

1.1 IC ENGINES

IC engine is a hotness motor where the burning of the air-fuel combination happens inside the ignition chamber that produces high temperature and high gas pressure. This gas pressure pushes the cylinder over a distance and changes the compound energy into nuclear power which is utilized for playing out the mechanical work. The size and plan of the motor changes as indicated by the application and the prerequisites. A few examination bunches are attempting to build the productivity of IC motors, since it is utilized in the greater part of the applications. Practically speaking, every one of the motors are undermined by their properties like proficiency, weight, exhaust, commotion, heat, power. In the event that the proficiency of the motor is high, it will give better mileage and consequently decrease fuel utilization and working expense. Among the flash start (SI) and Compression Ignition (CI) motors, the CI motor assumes an indispensable part since 80%-90% of use of IC motors is utilized with CI motors. These motors are the significant supporters of natural contamination and a danger to life on the planet. The motors transmit NO, CO, HC, carbon dioxide (CO₂), smoke, and particulate matter, which may either straightforwardly or by implication influence the climate and living medium. Uncompromising and long stretch transportation industry are faced with difficulties on air quality (contamination outflows) and an Earth-wide temperature boost (ozone depleting substances). One of the arrangements is to consolidate progressed burning ideas with low-carbon elective powers to accomplish the objective of a perfect and proficient motor. This work mostly centers around the chance of applying liquor fills (ethanol and butanol) in low-temperature burning ideas. Trial examinations are performed on a substantial motor arrangement to analyze the burning and discharge qualities of liquor powers when worked in various

ignition ideas. All the more critically, the work accentuates the practicality of liquor fuel applications with the base adjustments to the actual motor. The initial segment of the review centers around the fuel combinations with high liquor mix proportions. The liquor fuel mixes are straightforwardly infused into the chamber to accomplish to some degree premixed burning (PPC). A twofold immediate infusion (DI) procedure is proposed to expand the working burden limit. The outcomes show that the pilot/primary procedure can successfully lessen pressure rise rate contrasted with single DI and principle/post DI methodologies at high burden. It additionally accomplishes lower NO_x outflows and higher efficiencies than delta warming and channel supporting at low burden. With this particular infusion procedure, both ethanol and butanol fuel mixes can be worked from low to high load. Contrast and regular diesel burning, residue/NO_x tradeoff is alleviated however with expanded HC/CO emanations for both ethanol and n-butanol mixes. Albeit a lower burning proficiency is noticed, the n-butanol fuel mix accomplishes gross showed productivity (GIE) above half from low to medium-high burden.

Different researchers and specialists added to the advancement of gas powered motors. In 1791, John Barber fostered the gas turbine. In 1794 Thomas Mead protected a gas motor. Likewise in 1794, Robert Street licensed a gas powered motor, which was additionally quick to utilize fluid fuel, and constructed a motor around that time. In 1798, John Stevens constructed the main American gas powered motor. In 1807, French designers Nicéphore Niépce (who proceeded to imagine photography) and Claude Niépce ran a model gas powered motor, utilizing controlled dust blasts, the *Pyréolophore*, which was conceded a patent by Napoleon Bonaparte. This motor controlled a boat on the Saône stream, France.[7][8] around the same time, Swiss designer François Isaac de Rivaz developed a hydrogen-based gas powered motor and fueled the motor by electric flash. In 1808, De Rivaz fitted his development to a crude working vehicle - "the world's first inner burning controlled automobile".[9] In 1823, Samuel Brown licensed the main gas powered motor to be applied economically.

1.2 BIO-DIESEL ON IC ENGINE

Biodiesel is an inexhaustible, nontoxic, eco-accommodating and manageable elective fuel for pressure start motors. Regardless of having some application issues, biodiesel, as of late, being thought of as one of the most encouraging elective powers in gas powered motor. It has been demonstrated that the poisons in the vehicular emanations essentially affect the biological frameworks and on the soundness of individuals. Hence there is a rising interest on fixing the discharge principles of engine vehicles, as well as a consistently expanding need for creating method for lessening outflows from in help engine vehicles. Biofuel, like liquor and biodiesel, could part of the way supplant oil fuel, lessen harmful outflows and all the more significantly limit the life-cycle emanation of CO. In the current paper, prior examinations have been gathered and dissected. The point of the current review is to assess the practicality of biodiesel in cars, with exceptional accentuation on emanation angles. Barely any perspectives on sturdiness and execution are additionally included. Assessment is done on both regular and CRDI motors, however writing on the last option are not many and deficient when contrasted with the previous. Biodiesel use, when contrasted with diesel as a fuel, in traditional diesel motors with almost no alteration prompts the significant decrease in particulate matter (PM), hydro carbon (HC) and carbon monoxide (CO) outflows. This is joined by a light power misfortune, expansion in fuel utilization and an expansion in nitrogen oxide (NO_x) emanation. Biodiesel is a promising elective fuel for diesel motors, yet its high consistency and low unpredictability have limits in diminishing emanations. As a sustainable elective fuel with a high oxygen content, ethanol mixed with biodiesel can diminish kinematic consistency and further develop fuel dissipation. In this review, the impacts of the ethanol expansion proportion on the shower, ignition, and outflow exhibitions of a diesel motor fuelled with biodiesel were examined. The shower attributes were estimated utilizing a high velocity camera and Malvern laser examination, while the ignition and emanation exhibitions were tried on a turbocharged normal rail direct infusion (CRDI) diesel motor. The outcomes show that adding ethanol to biodiesel extends the shower cone point (SCA) and abbreviates splash tip infiltration (STP). Also, the bends of the size-volume circulation (SVD) of the atomized fuel drops advance toward a more modest breadth, and the Sauter mean measurement (SMD) of the biodiesel-ethanol (BE)

mixes slowly diminishes with expanding ethanol extent. At low loads, the fuel infusion procedure is multi-infusion, and the pinnacle chamber pressures (PCPs) of BE mixes are 0.77-1.96% higher than that of diesel at various ethanol mixing proportions. In any case, the pinnacle heat discharge rates (PHRRs) of BE mixes are 9.3-11.5% higher than that of diesel attributable to a quicker ignition rate, longer primary infusion span, and more hydroxyl extremists created in the pilot-infusion stage. At medium-high loads, the infusion methodology changes to single infusion, the PCPs of BE mixes are generally identical to that of diesel, and the PHRRs of BE mixes for various ethanol mixing proportions are 9.76-11.91% lower than that of diesel. This is a direct result of the lower dispersion ignition proportion, lower heat worth, and change of infusion term comparing to the variety in fuel properties. Also, the aftereffects of the pinnacle pressure rise rate and the cyclic variety demonstrate that the higher ethanol expansion proportion builds the burning commotion and diminishes the ignition security. Concerning fumes discharges, contrasted and biodiesel, with expanding ethanol mixing proportion, the residue outflows for various BE mixes decline by 11.28-47.23%, the NO_x emanations increment by 2.68-7.04%, and the HC emanations increment by 9.99-21.47%. Considering the motor exhibition extensively, a 20% ethanol mixing proportion in biodiesel is suggested. Lately, n-butanol created from squander or lignocellulosic materials has turned into an appealing and reasonable efficient power energy hotspot for diesel motors on the grounds that has an unmistakable potential for the fractional replacement of fossil-based diesel fuel. This review expects to dissect the impacts of various n-butanol/diesel fuel mixes on the presentation and fumes outflows of an Euro V substantial diesel motor following the World Harmonized Steady-State Cycle (WHSC), as well as the impact of every mode on the test found the middle value of results. The mixes assessed here were mixes of customary diesel fuel with 5%, 10% and 20% (by volume) n-butanol. Customary diesel fuel was utilized as a kind of perspective fuel to look at the exhibition and discharge qualities of the different n-butanol mixes. The primary discoveries show that 10% butanol could be considered as an appropriate extent for mixing n-butanol/customary diesel attributable to its positive presentation and decrease in particulate discharges, without huge changes in the vaporous outflows of NO_x. Mode-by-mode relative examination results show further developed motor execution with the utilization of n-butanol in many modes, paying little mind to speed or load conditions. CO discharges in everyday increment,

in spite of the joining of n-butanol diminishes CO emanations under high-burden and low-speed conditions. THC discharges increment with n-butanol, being more basic under cool beginning circumstances. The impact of n-butanol on NOX emanations doesn't have a reasonable pattern, however it is seen that NO2 discharges decline in all modes with the utilization of n-butanol mixes, mostly in low burden modes.

1.3 OUTLINE OF THE PROJECT

It was found that higher iso-butanol/diesel blends require higher EGR levels to attain optimum levels of smoke and NOx emissions. Both hydrocarbon (HC) and carbon-monoxide (CO) emissions presented an increasing trend at escalating EGR rates. At retarded injection timing, ISB40 blend presented decreased HC emissions, increased CO performance compared to its injection at original timing.

CHAPTER 2

LITERATURE REVIEW

As of late, examinations on higher chain alcohols like butanol and pentanol have accumulated interest among the researchers.⁶⁻⁸ These alcohols have more prominent possibilities as mixing parts with diesel fuel inferable from their higher energy thickness, higher cetane number, better mix dependability, and less hygroscopic nature when contrasted with lower alcohols like methanol and ethanol. Iso-butanol is a normally happening 4-carbon liquor that can be gotten by fermentation of natural yield material like corn and sugarcane that has caught energy from sun and put away it in the type of synthetic energy. Iso-butanol can likewise be supportive of reduced by anaerobic maturation of cellulose,¹¹ bio-union of hereditarily designed microorganisms like *Escherichia coli*, cyanobacteria, *Saccharomyces cerevisiae*¹²⁻¹⁴ and by direct electro-microbial conversion of carbon dioxide¹⁵ absent a lot of dependence on food crops. Further, restrictive biochemical way ways are being created by biofuel makers for enormous scope business creation of iso-butanol in request to diminish the significant expenses involved.^{16,17} There are not many examinations that contemplated the utilization of iso-butanol in diesel motors. Al-Hasan et al.¹⁸ concentrated on the exhibition of four iso-butanol/diesel mixes (10%, 20%, 30%, and 40%) in a solitary chamber diesel motor at various motor rates. Their results showed that BTE diminished and brake explicit fuel utilization (BSFC) expanded with iso-butanol expansion when contrasted with diesel fuel. Karabektaset al.⁶ concentrated on the impacts of utilizing four iso-butanol/diesel mixes (5%, 10%, 15%, and 20%) in a naturally-suctioned, single-chamber diesel motor on performance and discharges at various speed announced a lessening in brake power and an expansion in BSFC. They observed that NO_x and CO outflows have decreased with expansion in iso-butanol content while there was an expansion in HC emanations. There was no data on sediment discharges in this review. Ozsezan et al.⁸ researched the impacts of three iso-

butanol/diesel mixes (5%, 10%, and 15%) in a super charged six-chamber diesel motor and have shown comparative outcomes as to NO_x, HC, and CO outflows as in Karabektas and Hosoz.⁶ In addition, they revealed that smoke outflows diminished with expanding iso-butanol portion in the mixes. Gusset al.¹⁹ concentrated on the singular impacts of EGR furthermore, infusion timing in a six-chamber direct infusion diesel motor filled with iso-butanol and n-butanol diesel mixes upto 30% extent at light/medium loads. They presumed that the mix of a low EGR and suitable hindered infusion timing is essential for low smoke and NO_x discharges while keeping a satisfactory efficiency. There was no data on HC emanations in their review. As of late, Zheng et al. ²⁰ concentrated on the impacts of four butanol isomers mixes in diesel (20% and 40%) on execution and outflows in a solitary chamber diesel motor under EGR rates upto 65%. They viewed that as iso-butanol has the longest start deferral and favorable to reduced most minimal smoke emanations contrasted with other isomers. The review presumed that controlled emanations are not altogether impacted by the expansion of butanol isomers. Iso-butanol is picked in this study since it presents higher pinnacle pressures and higher premixed heat discharge rates than n-butanol.¹⁹ It likewise gives longer start delay than n-butanol which is needed for compelling premixing of air-fuel blend before combustion and it delivers least smoke emanations among all butanol isomers.²¹ as of late, iso-butanol is progressively preferred by the business since n-butanol creation innovation is crippled by high energy cost because of low groupings of n-butanol delivered and critical volumes of water handled, indeed, even with new Clostridia strains.²² Another benefit is that current ethanol establishes that utilization corn, sugarcane furthermore, cellulose as feedstock can be reused to favorable to reduce iso-butanol by altering the biocatalyst as shown by Gevo.²³ The goal of the current review is to examine:

(i) the impacts of utilizing three iso-butanol/diesel mixes (10%, 20%, and 30%) on execution and outflows of a normally suctioned single-chamber diesel motor at its whole burden range; (ii) the impacts of applying EGR paces of upto 30% on execution and emissions of the test motor filled with the over three iso-butanol/diesel mixes at its whole burden range; (iii) the joined impacts of EGR paces of upto 30% furthermore, impeded infusion timing by 2-CA bTDC on per-formance and outflows of the test motor filled with the most noteworthy iso-butanol/diesel mix

(ISB40) at high motor burdens. lower cetane number, calorific worth and instability [Choi and Jiang, 2015]. The upsides of bio-diesels as diesel fuel are the negligible sulfur and sweet-smelling content, and the higher blaze point, lubricity and cetane number. Their burdens incorporate the higher thickness (however much lower than the vegetable oils one), the higher pour point, the lower calorific worth and instability, the hygroscopic inclination, and the lower oxidation strength [Choi et. al., 2015]. Attributable to the above impediments specialists are currently focusing on liquor based energizes. Liquor energizes can be utilized as oxygenated fuel added substances with fossil-based powers for diesel motors as a clean elective fuel source to decrease the ozone harming substance outflows, sustainable power use in different regions [Karabektas and Hosoz, 2009]. Liquor powers, for example, ethanol, methanol and butanol can be utilized as oxygenated fuel added substances in fossil-based powers for diesel motors as elective fuel sources [Siwale et al. 2013]. Liquor diesel fuel mixes in diesel motors expand start postpone time of the burning system and this period relies upon the sort of liquor mixed and turns out to be longer as the substance of the liquor in the mixes is expanded [Hajba et al. 2011]. cetane fuel makes a motor run as expected and unobtrusively as in light of the fact that higher cetane fills have more limited start delay contrasted with lower cetane energizes (limiting of start postpone results in less unburned fuel in the chamber and less extreme thump) [Tingbo et al. 2012]. The glimmer point of butanol is very high (30°C) contrasted with ethanol (13-14°C) making it a more secure fuel to use than ethanol. Along these lines considering the better characteristics of butanol over ethanol, butanol would be desirable over ethanol for mixing with customary diesel and that's only the tip of the iceberg so than methanol.

The inordinate interest for non-renewable energy sources has caused extreme ecological effects, for example, GHG-related impacts and inescapable contamination. Right off the bat, it is fundamental to recognize the principle issues emerging from petroleum derivative creation and utilization, which will empower the pursuit and execution of innovative, supportable, and prudent choices to relieve the recent concern. With the cutting edge innovative advances in this particular region, the utilization of biofuels has extended, given their high capability of creation from assorted classes of biomass. Delivering biodiesel from microalgae oil explicitly, as an approach to acquiring spotless and environmentally friendly power, can assume

a critical part in this unique situation, and the interaction is of exorbitant interest to the energy area. Biodiesels are delivered through combinations of ethyl esters or unsaturated fat methyl esters, which are created by the amalgamation of oil with liquor within the sight of the catalyst liquor lipase. There are clear difficulties connected to the new advancements utilized to get biofuels from microalgae, and there likewise are solid possibilities to these methodologies, since they are very energy-productive and harmless to the ecosystem. Along these lines being, the current survey depicts the primary viewpoints related with biodiesel creation from microalgae, featuring the basics of the strategy, the immobilization processes followed, the utilization of solvents to advance response media, bioreactor frameworks, as well as the presentation streamlining of microalgae biodiesel-based motors, while thinking about significant monetary and ecological perspectives. Future patterns in the biofuel logical exploration and industry are likewise included, targeting encouraging conversations on the improvement of other critical advances in the utilization of microalgae lipase and oil innovation for biodiesel creation.

CHAPTER 3

AIM AND SCOPE OF THE PRESENT INVESTIGATION

3.1 AIM

The main objective of the project Effect of ISO--butanol addition to diesel fuel on performance and emissions of a DI diesel engine with exhaust gas re-circulation.

3.2 SCOPE

Diesel motors are widely utilized inside combustion (IC) motors in auto, transportation, modern power-train, rural gear, power age, and rock solid applications attributable to their high fuel-transformation effectiveness, high forceability, dependability, toughness, and cost adequacy. In any case, diesel motor outflows have destructive consequences for both human wellbeing and environment. They contain particulate matter (PM) that can cause cardio-respiratory wellbeing problems.¹ Further, diesel motor fumes has been named carcino-genic to people in view of adequate proof that its openness is related with an expanded gamble of lung disease by the International office for research on disease (IARC), which is a region of the planet Health Organization. ² NO_x (nitrogen oxides) present in diesel exhaust is a main source for brown haze, ground level ozone, furthermore, corrosive rain. ³⁻⁵ Besides diesel fuel is gotten from quickly draining unrefined petroleum saves which makes concerns of energy frailty. Change in unrefined petroleum costs influences the economies of nations that don't have their own oil holds and are intensely reliant on oil imports. Such worldwide worries of natural corruption and energy frailty are driving the research local area to find reasonable inexhaustible change local fills for use in IC motors. Replacement of even a negligible portion of non-renewable energy source with sustainable biofuel will emphatically affect both the economy and environment. Among the option

sustainable fills like biogas, bio-alcohol, and bio-diesel, bio-alcohol appears to be the most alluring. Biogas is principally methane what's more, carbon dioxide (powerful ozone harming substances) whose spillage could be dangerous to the climate. The capacity of biogas for over a day's stockpile is by and large unrealistic and ought to be fundamentally utilized "as and where" it is delivered.

3.3 PROBLEM STATEMENT

Be that as it may, the utilization of alcohols in pressure ignition motors presents specific troubles due to their low cetane number, high inactive hotness of vaporization, furthermore, long start delay.⁶ Further the less calorific esteem, unfortunate miscibility with diesel and poor lubricating properties limits their utilization in diesel engines. ⁷ The properties of certain alcohols are recorded in Table 1. A few methods like liquor fumigation, double injection, liquor diesel mixes, and liquor diesel emulsions have been utilized to manage the above-said limits of alcohols as a diesel motor fuel.⁸ From wellbeing viewpoint, alcohols have low glimmer point (FP) what's more, are named Class I fluids ($FP < 37.8 - C$) alongside gas by the National Fire Protection Affiliation (NFPA) in the United States. Diesel is delegated Class II fluid ($FP > 37.8 - C$). Expansion of alcohols to diesel brings down its FP and thus could push it under Class 1 fluids which would require a similar foundation as gas for capacity and taking care of. Then again, there are a few positive parts of alcohols that can be advantageous to be utilized in diesel motors. Alcohols being oxygenated fills with a hydroxyl bunch increment the accessibility of oxygen during burning and decrease smoke outflows in diesel motors particularly at high motor loads.⁹ There are likewise no genuine effects in NO_x discharges with alcohols due to their higher inert fieriness of vaporization and lower energy content when contrasted with diesel oil.¹⁰



Fig: 3.1 AVRA Iso-Butanol

CHAPTER 4

MATERIALS AND METHODS USED

4.1 STUDY OF ADDITIVE AND EMISSION

4.1.1 *ISO-Butanol*

Iso-butanol guaranteed to an immaculateness of almost 100% (logical grade) was obtained from AVRA combination for this study. Super low sulfur diesel fuel was obtained from Indian oil enterprise, Chennai. Four test energizes, ISB10, ISB20, ISB30, and ISB40 were ready by blending iso-butanol at a mixing proportion of 10/90, 20/80, 30/70, and 40/60 by volume premise with diesel separately. The test energizes were tried for their solubility and no stage partition was seen after 48 h for every one of the mixes. By the by to guarantee homogeneity, all mixes were blended well utilizing an electric blender not long prior to powering during trial and error. It tends to be construed from Table 1 that higher mixes of iso butanol will have lower thickness, lower cetane number, lower calorific worth and higher oxygen content than diesel fuel. The standard infusion timing of the test motor is 23- CA bTDC. Diesel fuel infused at the motor's standard infusion timing structures the allude ence fuel for this review and is alluded to as "Diesel" all through the conversations. Every one of the mixes infused at the motor's standard planning were alluded to as ISB10, ISB20, ISB30, and ISB40. Later the infusion timing is hindered by 2- CA by changing the thickness of the development shim situated in the association between the motor and fuel siphon. The test fuel ISB40 infused at this hindered timing of 21-CA bTDC is assigned as "ISB40 Ret". Test motor and offices. Tests were acted in a normally suctioned. Residue outflows by and large lessening with an increment of butanol mixing proportion. The impact of the butanol mix proportion on NO_x is vague and relies upon the particular motor and working circumstances [50]. Butanol can impact the chamber temperature in two neutralizing ways (the high idle hotness of vaporization de-wrinkles the chamber temperature

while more premixed burning prompts quick hotness discharge and higher ignition temperature). They found that iso-butanol/diesel mixes introduced longest start delay and created most reduced smoke discharges when contrasted with different isomers. Rajesh et al. [2,28] revealed that the blend of EGR rates up to 30%, iso-butanol expansion of up to 40% and hindered infusion timing by 2°CA bTDC can all the while lessen NO_x and smoke outflows.

Table 4.1 Fuel Properties

Properties	Diesel	Methanol	Ethanol	n-butanol	Iso-butanol
Molecular formula	C ₁₂ H ₂₆ – C ₁₄ H ₃₀	CH ₃ OH	C ₂ H ₅ OH	C ₄ H ₉ OH	C ₄ H ₉ OH
Cetane number	52	2	11	<15	<15
Low heating value (MJ/kg)	43.356	20.08	26.83	33.80	33.64
Latent heat of vaporization (kJ/kg)	250-290	1162.64	918.42	626	684
Kinematic viscosity at 40 C (mm ² /s)	3.522	0.58	1.13	2.67	2.63
Oxygen (wt%)	0	49.93	34.73	21.62	21.62
C/H ratio	6.8	2.98	4.0	4.8	4.8
Density (kg/m ³)	840	791.3	789.4	810	802
Flash point (C)	70	11	14	28	27.8
Boiling point (C)	227	65	79	117.7	107.9
Self-ignition temperature (C)	254	385	363	343	415.6



Fig: 4.1 Fuel Blends

4.1.2 Emission Overview

As currently referenced significant exhaust emanations are

- (I) unburnt hydrocarbons, (HC)
- (ii) oxides of carbon, (CO and CO₂),
- (iii) oxides of nitrogen, (NO and NO₂)
- (iv) oxides of sulfur, (SO₂ and SO₃)
- (v) particulates
- (vi) sediment and smoke.

The initial four are normal to both SI and CI motors and the last two are primarily from CI motors. The primary non-exhaust emanation is the unburn hydrocarbons from gas tank and crankcase blowby. Figure 15.1 shows the variety of HC, CO and NO_x emanations as an element of proportionality proportion for a SI motor. It is plainly seen that every one of the three outflows are a solid capacity of proportionality proportion. As can be seen from the Fig.4.1 that a rich blend doesn't have sufficient oxygen to respond with all the carbon and hydrogen, and both HC

and CO emanations increment. For $\phi < 0.8$, HC outflows likewise increment because of unfortunate ignition and fizzle. The age of nitrogen oxide emanations is a component of the burning attitude, most elevated close to stoichiometric circumstances when temperatures are at the pinnacle esteem. Greatest NO_x emanations happen at somewhat lean conditions, where the burning temperature is high and there is an abundance of oxygen to respond with the nitrogen.

4.2 PREPARATION OF BLENDS AND THEIR PROPERTIES

Made the blends was done at international research Centre Sathyabama Institute of Science and Technology Chennai

4.2.1 ISB 20

Table 4.2 Properties of Blend (ISB 20)

S.No	Parameters	Results
1	Density	0.797 g/cc
2	Kinematic Viscosity @ 40°C	0.58 cSt
3	Flash point by PMCC method	46 °C
4	Fire point by PMCC method	57 °C
5	Calorific value	8179.34 Cal/g

4.2.2 ISB 30

Table 4.3 Properties of Blend (ISB 30)

S.No	Parameters	Results
1	Density	0.798 g/cc
2	Kinematic Viscosity @ 40°C	0.58 cSt
3	Flash point by PMCC method	46 °C
4	Fire point by PMCC method	55 °C
5	Calorific value	7663.9 Cal/g

4.2.3 ISB40

Table 4.4 Properties of Blend (ISB 40)

S.No	Parameters	Results
1	Density	0.790 g/cc
2	Kinematic Viscosity @ 40°C	0.59 cSt
3	Flash point by PMCC method	46 °C
4	Fire point by PMCC method	57 °C
5	Calorific value	7688.44 Cal/g

4.3 ENGINE CHARACTERISTICS

The arrangement comprises of single chamber, four stroke, VCR (Variable Compression Ratio) Electric turn over Diesel motor associated with vortex current sort dynamometer for stacking. The pressure proportion can be changed without halting the motor and without changing the ignition chamber math by uniquely planned shifting chamber block plan. Arrangement is given with vital instruments for ignition pressure what's more, wrench point estimations. These signs are interacted to PC through motor marker for P θ PV outlines. Arrangement is likewise made for connecting wind stream, fuel stream, temperatures and burden estimation. The set up has independent board box comprising of air box, two gas tanks for mix test, manometer, fuel estimating unit, transmitters for air and fuel stream estimations, process pointer and motor marker. Rotameters are accommodated cooling water and calorimeter water stream estimation. The arrangement empowers investigation of VCR motor execution with EGR for brake power, showed power, frictional power, BMEP, IMEP, brake warm effectiveness, shown warm proficiency, Mechanical productivity, volumetric effectiveness, explicit fuel utilization, A/F proportion and hotness balance. Lab view based Engine Performance Analysis programming bundle "Engines off" is accommodated on line execution assessment.

Table 4.5 Engine Specification

Product	VCR Engine test setup 1 cylinder, 4 stroke, Diesel with EGR (Comp.)
Product code	234
Engine	Make Kirloskar, Type 1 cyl., 4 stroke Diesel, water cooled, power 3.5kW at 1500rpm, stroke 110mm, bore 87.5mm. 661cc, CR17.5, Modified to VCR engine CR 12 to 18. With electric start arrangement, battery and charger
Dynamometer	Type eddy current, water cooled,
Propeller shaft	With universal joints
Air box	M S fabricated with orifice meter and manometer
Fuel tank	Capacity 15 lit with glass fuel metering column
Calorimeter	Type Pipe in pipe
EGR	Water cooled, SS, Range 0-15%
Piezo sensor	Range 5000 PSI, with low noise cable
Crank angle sensor	Resolution 1 Deg, Speed 5500 RPM with TDC pulse.
Data acquisition device	NI USB-6210, 16-bit, 250kS/s.
Piezo powering unit	Model AX-409.
Temperature sensor	Type RTD, PT100 and Thermocouple, Type K
Temperature transmitter	RTD PT100, Range 0–100°C, 3 Nos; Thermocouple, Range 0-1200 °C, 2 Nos
Load indicator	Digital, Range 0-50 Kg, Supply 230VAC
Load sensor	Load cell, type strain gauge, range 0-50 Kg
Fuel flow transmitter	DP transmitter, Range 0-500 mm WC
Air flow transmitter	Pressure transmitter, Range (-) 250 mm WC
Software	“EngineSoft” Engine performance analysis software
Rotameter	Engine cooling 40-400 LPH; Calorimeter 25-250 LPH
Pump	Type Monoblock
Overall dimensions	W 2000 x D 2500 x H 1500 mm
Optional	Computerized Diesel injection pressure measurement with injection variation 0-25 deg BTDC



Fig: 4.2. VCR Engine

4.3.1 Test Procedure

All tests were done under consistent state conditions with no changes to the test motor. The temperature of the greasing up oil was kept up with between 85 -C and 90 -C. Tests were conveyed out at steady surrounding temperature to work on the unwavering quality of the accounts. The motor was permitted to run for 10 min for adjustment previously the readings were recorded. Motor tests were conveyed out at a steady speed of 1500 r/min for the whole load range. The infusion pressure is kept steady (21MPa) in this review. The motor was first run at its standard infusion timing with diesel fuel which structures the reference fuel for this review. The pattern information was recorded. Then the motor was powered with the mixes ISB10, ISB20, ISB30, and ISB40 at its standard injection timing. The EGR rates were continuously expanded close by utilizing the EGR control valve. Afterward, the infusion timing was impeded by 2- CA bTDC and again the test fuel ISB40 was run. Every single test was rehashed multiple times to guarantee repeatability. The motor was generally permitted to run for quite a while prior to refueling for it to consume the fuel that stayed in the fuel framework during the past preliminary.




Fig: 4.3 Schematic of the experimental setup

4.3.2 EGR Setup

In this review, an outer cooled-EGR framework was utilized. Cooled EGR decreases the admission charge gum based paintture and brings down the top in-chamber temperatures that favor NO_x arrangement. Cooling likewise expands the thickness of re-coursed gases empowering a more prominent favorable to piece of EGR to be utilized. In this manner, a small portion of fumes gas is shipped off the EGR cooler before it is redirected into the admission complex for blending in with the approaching air. EGR cooler is a hotness exchanger in which cooling water is kept up with at a steady temperature to retain heat from the approaching exhaust gas. It must be noticed that temperature of the exhaust gas re-flowed is kept lower than the motor fumes furthermore, hotter than the admission air charge. In this C.EGR rate is constrained by an EGR valve. An opening is utilized to gauge the stream pace of the fumes gas. A blending chamber guarantees sufficient blending of incoming air and once again circled fumes gas before it get senlisted into the ignition chamber. EGR amount was resolved utilizing the connection $EGR \% = \frac{CO_2 \text{ consumption} - CO_2 \text{ exhaust}}{100}$ The amount of CO₂ in the exhaust was estimated by the MRU gas analyzer. This is finished by changing the EGR control

valve to fluctuate the stream pace of the exhaust until the amount of CO₂ in the admission comes to the ideal worth. Comparable strategy was utilized by Bhaskar et al. 24 to decide EGR rates in a comparable motor

4.3.3 Engine Testing Software

EngineSoft is Labview based programming bundle created by Pinnacle Innovations Pvt. Ltd. for motor execution observing framework. EngineSoft can serve a large portion of the motor testing application needs counting observing, revealing, information passage, information logging. The product assesses power, efficiencies, fuel utilization and hotness discharge. It is configurable according to motor set up. Different diagrams are acquired at different working condition. While on line testing of the motor in RUN mode fundamental signs are checked, put away and introduced in diagram. Put away information record is gotten to see the information graphical and even designs. The outcomes and charts can be printed. The information in dominate arrangement can be utilized for additional investigation.

4.3.4 Gas Analyses



Fig: 4.4. Gas Analysis

CHAPTER 5

ANALYSIS OF PERFORMANCE AND EMISSION

Motor tests were done at four consistent burdens with brake mean compelling tensions (bmep) of 0.0, 1.3, 2.6, 4, and 5.3 bar and at the greatest force speed of 1500 r/min. The test aftereffects of different motor burning, execution, and discharge boundaries are examined independently as sub-areas.



Fig: 5.1. Engine Drive

5.1 EFFECT OF BLENDS AND PERFORMANCE

The in-chamber tension and hotness discharge rate (HRR) profiles for iso-butanol/diesel mix (ISB40) at contrastent conditions are displayed in examination with gauge diesel activity in Figures 2 and 3, respectively. In this review, start delay is determined as the contrastence between fuel infusion timing and the circumstance at which 5% mass part of fuel is scorched. It very well may be seen

from Figure 2 that start is deferred by the expansion of iso-butanol to diesel. This is because of the lower cetane of iso-butanol than diesel. One of the significant impacts of EGR is to drag out the start delay²⁶ and henceforth more deferral is acknowledged by ISB40 at EGR 30%. The start gets additionally postponed at impeded infusion timing. Figure 2 likewise shows that ISB40 mixes give high top in-chamber pressures than diesel. The more premixed fuel-air combination because of long start defers builds the pinnacle upsides of chamber pressure. Premixed ignition staging for the most part relies upon the time accessible for air-fuel blending before start. The top HRR happens at a wrench point that is moved to a later stage. Longer start delays advance fuel-air blending went with higher premixed combustion fractions.²⁰ However, the blend of EGR furthermore, impeded infusion timing brought about lower top pressures and somewhat lower top HRR than diesel. This different way of behaving with this blend was additionally detailed by Gu et al.¹⁹ with iso-butanol/diesel mixes. It tends to be seen that at hindered timing, ISB40 shows a drop in pressure. This is on the grounds that impeding the fuel infusion causes late burning what's more, thusly, pressure rises just when the chamber volume grows quickly away from the TDC and brings about diminished compelling strain to take care of business. In every one of the sub-segment that follows, the variations of a specific motor boundary with deference to various burden conditions for all iso-butanol mixes are talked about. Then, at that point, the varieties of a specific motor boundary at various burden conditions under expanding EGR rates are talked about. For this reason, one mix (ISB30) was chosen for conversation on the grounds that different mixes additionally introduced comparative variety patterns under EGR conditions. At last the varieties of a specific motor boundary are talked about under expanding EGR rates joined with the impacts of impeding the infusion timing at a high motor burden (bmep $\frac{1}{4}$ 5.3 bar) and afterward contrasted and pattern diesel activity.

5.1.1 Brake Thermal Efficiency

Variations of BTE at various burden conditions for slick diesel fuel and different rates of isobutanol also, its mixes with diesel fuel. It very well may be seen that BTE increments with motor burden however diminishes somewhat from 75% to 100 percent loads. This slight drop could be because of the great greasing up oil

temperature and low abundance air proportion at high motor loads that fall apart the oil and combustion.²⁷ It should be visible that iso-butanol mixes have lesser BTE than diesel. Expanding iso-butanol content in the mix caused a drop in BTE because of the less energy content of iso- butanol when contrasted with diesel fuel. Figure 6(b) shows the varieties of BTE as a component of burden at different EGR rates for ISB30 mix. There is a drop in execution with expanding EGR rates due to the weakening of the burning system by the presence of idle gases in the chamber. Figure 7 shows the varieties of BTE at different EGR rates for various iso-butanol mixes at bmep $\frac{1}{4}$ 5.3 bar. It very well may be seen that BTE diminishes at expanding EGR rates for all iso-butanol/diesel mixes with the drop being most extreme for ISB40 mix. Expansion in EGR thwarts the typical burning supportive of cess and diminishes the consuming rate. The higher CO furthermore, HC outflows due to expanded EGR rates too represents ignition misfortunes and diminished performance of iso-butanol mixes with diesel. It tends to be seen that at hindered timing, ISB40 shows slight drop in execution. This is on the grounds that impeding the infusion of fuel causes late burning and, there-front, pressure rises just when the chamber volume grows quickly away from the TDC and results in diminished powerful strain to take care of business




Fig: 5.2. Emission Graph - BTE VS BP

5.1.2 Specific Fuel Consumption

Explicit fuel utilization is how much fuel consumed by a vehicle for every unit of force yield. A vehicle's particular fuel utilization is pretty much autonomous from its nitrogen oxide discharges per kilometer. The particular fuel utilization of a motor is the pace of fuel consumed to create a unit of pushed. Varieties of exhaust temperature at various burden conditions for slick diesel fuel and the different rates of iso-butanol and its mixes with diesel fuel. Exhaust temperature diminishes with expanding iso-butanol content in the mix. Low energy content of iso-butanol causes less burning temperature and ISB40 having the least energy content among all the mixes creates least exhaust temperatures by any stretch of the imagination motor burdens. The higher inert hotness of vaporization of iso-butanol/diesel mixes likewise lessens the fumes temperature. Figure 5.3 shows the varieties of exhaust temperature at various burdens and EGR rates for ISB30 mix. It tends to be seen that the exhaust temperature somewhat diminishes with expansion in EGR rates for all mixes because of decrease in top burning temperature. The higher inert of fume ization of iso-butanol/diesel likewise gives a cooling impact during burning and henceforth brings about lower exhaust temperatures.




Fig: 5.3. Emission Graph - FC VS BP

5.2 EFFECT OF BLENDS ON EMISSION



Fig: 5.4. Emission Sensing System

5.2.1 Nitrogen Oxide Emission

Nox emanations Figure 5.4 shows the varieties of Nox emanations at various burden conditions for perfect diesel fuel and different rates of iso-butanol mixes with diesel fuel. It very well may be seen that Nox outflows diminishes with expanding iso-butanol content in the mixes. This is because of the motor running in general more slender and the temperature bringing down impact of iso-butanol (because of its lower calorific worth and higher hotness of dissipation) having a prevailing impact against the contradicting impact of the lower cetane number of iso-

butanol which can prompt higher temperatures during the premixed ignition phase.⁸ This equilibrium relies upon the particular motor and its working conditions.²⁹ Figure 10(b) shows the variations of Nox discharges at various burdens and EGR rates for ISB30 mix. It tends to be seen that Nox discharges for ISB30 mix decline with expanding EGR rates. Presenting EGR diminishes the fire temperature and oxygen fixation inside the burning chamber. The idle gases present in EGR ingest the hotness delivered during ignition also, decreases the pinnacle temperatures that works with the development of Nox. Nox discharges decrease from 1284 ppm to 876 ppm at full burden condition as a aftereffect of 30% EGR rates. Figure 11 shows the varieties of Nox discharges at expanding EGR rates for different iso-butanol mixes at bmep $\frac{1}{4}$ 5.3 bar. True to form, Nox discharge diminishes for all test powers because of lower ignition temperature and longer start delay because of expanding EGR rates.²⁶ At 30% EGR rate, Nox discharge is diminished to 37%, 36%, 32%, and 31% by ISB10, ISB20, ISB30, and ISB40 mixes regardively when contrasted with standard diesel activity without EGR. Further decreases in Nox discharges could be acknowledged by hindering the infusion timing which creates further setback for start. For example, ISB40 infused at hindered timing decreases Nox emissions by upto 42% when contrasted with benchmark diesel activity. It can likewise be seen that at expanding EGR rates, Nox emanation slowly increments with increasing iso-butanol content among the four mixes. Expansion of iso-butanol in diesel brings down its cetane number which brings about a more extended start delay. This postpone makes more fuel get infused into the chamber. Whenever this high amount fuel gets combusted during the premixed burning stage, it results in expanded chamber temperatures. This advances the development of Nox. Comparable Nox conduct at high motor burdens was additionally detailed with this liquor prior.




Fig: 5.5 Emission Graph - Nox VS BP

5.2.2 Carbon Monoxide Emissions

Varieties of CO outflows at various burden conditions for slick diesel fuel and the different rates of iso-butanol and its mixes with diesel fuel. CO discharges diminishes with expanding motor burden because of expansion in chamber temperature at higher burdens. CO outflows are by and large low for all isobutanol mixes when contrasted with base- line diesel fuel attributable to the improvement of fuel air blending by the expanded oxygen content of the mixes. Subsequently blending of more iso-butanol in diesel causes leaning impact on the mixes because of the lower stoichiometric air/fuel proportion of iso-butanol which brings down CO emissions.⁶ Figure 5.5 shows the varieties of CO outflows as a component of burden at different EGR rates for ISB30 mix. Presentation of EGR diminishes the oxygen fixation in the chamber and debilitates the burning cycle bringing about expanded CO emissions with expansion in EGR rates. Figure 18 shows the varieties of CO emanations at different EGR rates for various iso butanol mixes at bmep $\frac{1}{4}$ 5.3 bar. CO outflows pursues comparative direction like HC outflows. As a general

rule, CO outflow increments with expanding EGR rates for all mixes. The exceptionally oxygenated states of higher mixes of iso-butanol (ISB30 and ISB40) have predominant impact over the diminished oxygen fixation brought about by EGR and henceforth there is slight decrease in CO emanations when contrasted with lower mixes. At hindered infusion timing, ISB40 shows slight expansion in CO discharges which might be because of diminished oxidation process as a aftereffect of poor premixed ignition stage.




Fig: 5.6. Emission Graph - CO VS BP

5.2.3 Hydro Carbon Emissions

HC emanations at various burden conditions for slick diesel fuel and the different rates of iso-butanol and its mixes with diesel fuel. HC outflows are by and large high for all iso-butanol mixes when contrasted with standard diesel fuel. The fact that HC discharge additionally makes it seen increments with expanding isobutanol content in the mixes. The lower cetane number of iso-butanol debases

the self-start qualities of the mixes and advances extinguishing impact in the leaner blend zone of the cylinder.⁶ The higher fieriness of vanishing of iso-butanol additionally causes more slow evaporation and more unfortunate fuel-air blending which results in fragmented burning. Along these lines, expanded isobutanol content in the mixes came about in expanded HC outflows. One more justification for expansion in HC outflows can be credited to the lower thickness and thickness of iso-butanol/diesel fuel mixes, which causes the development of little estimated fuel drops. These beads reach to the nearer segment of the cylinder dividers and lead to extinguishing impact because of more slender combination and furthermore bring about additional unburned fuel. At higher burdens, there is a decline in HC discharges for all mixes because of further developed oxidation due to higher in-chamber gas temperatures. Figure 5.6 shows the varieties of HC discharges as a capacity of burden at different EGR rates for ISB30 mix. HC discharge increments with expanding EGR rates due to the crumbling of ignition process as a consequence of expanded inactive gas fixation inside the chamber. HC emanations increments by upto 62% under high motor burdens at 30% EGR rate for ISB30 mix. Figure 5.7 shows the varieties of HC outflows at different EGR rates for various iso-butanol mixes at high motor heap of bmep $\frac{1}{4}$ 5.3 bar. As talked about earlier, HC discharge increments with expanding EGR rates for all iso-butanol/diesel mixes. It very well may be noticed that HC discharges of ISB40 infused at impeded timing shows decrease in HC discharges at all EGR rates. This might be because of the diminished fire extinguishing thickness.³³ Also HC emanations are brought down since hindered infusion timing might permit some time for better blending of fuel and air.




Fig: 5.7 Emission Graph - HC VS BP

5.2.4 Smoke Capacity

Varieties of smoke haziness at various burden conditions for flawless diesel fuel and different rates of iso-butanol mixes with diesel fuel. It tends to be seen that smoke capacity diminishes with expanding iso-butanol content in the mixes. This is ascribed to the oxygenated nature of alcohols. The accessibility of fuel-borne oxygen in iso-butanol (21.62 by wt%) helps the burning process by upgrading the fuel-air blending process especially even in fuel-rich zones and brings down the possibilities of ash cores arrangement during dissemination burning period.^{27,30} Figure 12(b) shows the varieties of smoke obscurity at various burdens and EGR rates for ISB30 mix. It tends to be noticed that smoke darkness for a specific mix increments with expanding EGR rates. High EGR rates decline the oxygen focus. What's more, increment the neighborhood comparability proportion causing fragmented burning and advancing sediment formation. Because of high EGR, chamber temperature additionally gets diminished and smoke development is

advanced varieties of smoke darkness at expanding EGR rates for different iso-butanol mix at bmep $\frac{1}{4}$ 5.3 bar. It very well may be seen that smoke haziness scarcely increments upto 20% EGR rate and later which it has expanded quickly for all mixes. Studies have shown that residue discharges increments quickly with EGR increase once the EGR rate surpasses a particular value. 20,32 An ash knock exists in a particular EGR range where the residue outflows are delicate to variety in EGR rates causing an extraordinary trouble in controlling the ignition process. Comparable perceptions were too made with various mixes of n-butanol isomers with diesel, where a residue knock happened at around 30% EGR rate. 20,26 Equally from Figure 5.8 it can be seen that smoke darkness stayed low for higher iso-butanol mixes under heightening EGR conditions. This can be because of predominant impact of expanded oxygen division and lower in general equivalence proportion because of adding iso-butanol to diesel over the impacts of EGR. Comparative situation was too announced with n-butanol/diesel mixes under high EGR rates. Figure 5.9 shows the connection between NO_x discharges and smoke haziness for all test powers at bmep $\frac{1}{4}$ 5.3 bar. The fact that both NO_x and smoke makes it seen emanations can be at the same time diminished by the combination of iso-butanol expansion (upto 40%), EGR (somewhere in the range of 25% and 30%) and hindered infusion timing. Figure 14(a) shows that NO_x discharges can be cut down further by impeding the infusion timing without sharp expansion in smoke murkiness. When contrasted with benchmark diesel activity, 40% iso-butanol expansion lessens NO_x discharges from 1284 to 1244 ppm and smoke obscurity from 20.7% to 0.8%. At 30% EGR rates, 40% iso-butanol expansion decreases NO_x outflows from 1284 to 886 ppm and smoke obscurity from 20.7% to 1.6%. The mix of 30% EGR application, 40% iso-butanol expansion also, impeded infusion timing by 2-CA bTDC decreases NO_x discharges from 1284 to 749 ppm and smoke opacity from 20.7% to 1.9% Figure 5.9 shows the compromise bend between NO_x discharges and smoke haziness of iso-butanol mixes for different EGR rates at high motor burden. Since the units of smoke and NO_x discharges were unique, their qualities were standardized to aspect less numbers to address the compromise better in a similar chart. The place where the bends of smoke and NO_x emanation of a specific mix meet, compares to the degree of EGR past which the compromise shows up for that specific mix. It tends to be seen from Figure 5.9 that for ISB10 mix, the compromise the shows up at EGR levels underneath 25% while for ISB30

mix it shows up at a level somewhat higher than 25%. Consequently, it very well may be presumed that higher iso-butanol/diesel mixes present better EGR tolerance while keeping up with synchronous decrease of NO_x and smoke outflows. This can be ascribed to the profoundly oxygenated state of ISB30 mix (compared to bring down mixes) that overwhelms the weakening impact brought about by EGR. It tends to be gathered from Figure 14(b) that 20% EGR can be viewed as ideal for iso-butanol/diesel mixes to accomplish a more commonsense compromise among NO_x and smoke outflows.




Fig: 5.8. Emission Graph – SMOKE (%) VS BP

CHAPTER 6

RESULTS AND CONCLUSIONS

6.1 RESULTS AND CONCLUSIONS

In this review, the impact of iso-butanol expansion upto 40% in diesel fuel on execution and emanations of a single chamber direct-infusion diesel motor under fumes gas distribution for the whole burden range was examined and contrasted and standard diesel activity. The consolidated impact of EGR and hindered infusion timing on execution and discharges of the same motor energized with high iso-butanol content (ISB40) was likewise learned at high motor burdens. The following ends were drawn in light of the test results.

1. Iso-butanol can be blended in with diesel upto to 40% with next to no stage division and can be utilized in the current direct-infusion diesel motor infra- structure without requiring any changes.
2. NO_x discharges diminished with expanding iso-butanol content in the mixes for the whole burden spectrum of the motor. Because of 30% EGR rates, it was observed that NO_x emanations descended from 1284 ppm to 876 ppm at high motor burdens for ISB40 when contrasted with pattern diesel operation. Further decreases of upto 11% can be accomplished when the infusion timing was impeded by 2-CA bTDC for ISB40.
3. Smoke murkiness diminishes with expanding iso-butanol content in the mixes for the whole burden range of the motor due to oxygenated conditions of the mixes. Under EGR conditions, it was observed that smoke murkiness scarcely increments upto 20% EGR rate and past which it expanded definitely for all mixes.

4. NO_x emanations can be brought somewhere near hindering the infusion timing without sharp expansion in smoke obscurity. When contrasted with standard diesel activity, at high burden conditions (bmep $\frac{1}{4}$ 5.3 bar) it was viewed that as: (i) Iso-butanol expansion (ISB40) at the same time decreased NO_x outflows from 1284 to 1244 ppm and smoke opacity from 20.7% to 0.8%. (ii) Iso-butanol expansion (ISB40) under EGR paces of upto 30% simultaneously diminished NO_x emanations from 1284 to 886 ppm and smoke murkiness from 20.7% to 1.6%. (iii) The blend of EGR paces of upto 30%, iso-butanol expansion of upto 40% (ISB40) and impeded infusion timing by 2- CA bTDC all the while decreased NO_x outflows from 1284 to 749 ppm and smoke darkness from 20.7% to 1.9%.
5. 20% EGR is viewed as ideal for isobutanol/diesel mixes for concurrent decrease of smoke and NO_x discharges. Additionally, higher iso-butanol/diesel mixes present better EGR tolerance while keeping up with concurrent decrease of NO_x and smoke discharges
6. HC discharges were viewed as high for all iso-butanol mixes when contrasted with standard diesel fuel for the whole burden range of the motor. HC emanations showed expanding pattern with expanding iso-butanol content in the mixes. At expanding EGR rates, they introduced a rising pattern. Be that as it may, they showed slight decrease at hindered infusion timing for ISB40 mix when contrasted with its infusion at the first planning of the motor.
7. CO discharges diminished with expanding motor load. They are for the most part low for all iso-butanol mixes when contrasted with benchmark diesel fuel. Presentation of EGR brought about expanded CO emanations with expansion in EGR rates. At hindered infusion timing, ISB40 showed slight expansion in CO discharges.

8. Expanding iso-butanol content in the mix caused a drop in BTE because of the less energy content of iso-butanol when contrasted with diesel fuel. At impeded infusion timing, ISB40 showed a slight drop in execution when contrasted with its injection at the first infusion timing. Along these lines, iso-butanol can successfully substitute diesel fuel by upto 40% and can accomplish synchronous decreases of NO_x and smoke emanations with a slight drop in execution.

REFERENCES

- [1] Al-Hasan, M.I., and Al-Momany, M., "The effect of isobutanol-diesel blends on engine performance", *Transport*, Vol. 23, 2008, pp. 306–310.
- [2] Alriksson, M., Rente, T., and Denbratt, I., "Low soot, low NO_x in a heavy duty diesel engine using high levels of EGR", SAE Technical Paper, 2005-01-3836, 2005.
- [3] Benbrahim Tallaa, L., Baan, R.A., Grosse, Y., et al. "Carcinogenicity of diesel-engine and gasoline-engine exhausts and some nitroarenes", *Lancet Oncol.*, Vol. 13, 2012, pp. 663–664.
- [4] Bhaskar, K., Nagarajan, G. and Sampath, S., "Optimization of FOME (fish oil methyl esters) blend and EGR (exhaust gas recirculation) for simultaneous control of NO_x and particulate matter emissions in diesel engines", *Energy*, Vol. 62, 2013, pp. 224–234.
- [5] Campos-Fernandez, J., Arnal, J.M., and Gomez, J., et al. "A comparison of performance of higher alcohols/ diesel fuel blends in a diesel engine", *Appl Energy* Vol. 95, 2012, pp. 267–275.
- [6] Chen, Z., Wu, Z., and Liu, J., et al., "Combustion and emissions characteristics of high n-butanol/diesel ratio blend in a heavy-duty diesel engine and EGR impact", *Energy Convers Manage*, Vol. 78, 2014, pp. 787–795.
- [7] Chock, D.P., Dunker, A.M., Kumar, S., et al. "Effect of nitrogen oxides (NO_x) emission rates on smog formation in the California South Coast Air Basin", *Environ Sci Technol.*, Vol.15, 1981, pp. 933–939.
- [8] Corkwell, K.C., Jackson, M.M. and Daly, D.T., "Review of exhaust emissions of compression ignition engines operating on E diesel fuel blends", SAE Technical Paper Series, 2003-01-3283, 2003.
- [9] De Caro, P.S., Mouloungui, Z., Vaitilingom, G., and Berge, J. C., "Interest of combining an additive with diesel– ethanol blends for use in diesel engines", *Fuel*, Vol. 80(4), 2001, pp. 565–74. doi:10.1016/S0016-2361(00)00117-4.
- [10] Desai, S.H., Rabinovitch-Deere, C.A., and Fan, Z., et al., "Isobutanol production from cellobionic acid in *Escherichia coli*", *Microb Cell Fact.*, Vol. 14, 2015, p. 52.

- [11] Dog˘ an O., “The influence of n-butanol/diesel fuel blends utilization on a small diesel engine performance and emissions”, *Fuel*, Vol. 90, 2011, pp. 2467–2472.
- [12] Formighieri, C., “Cyanobacteria as a platform for direct photosynthesis-to-fuel conversion”, *Springer Briefs in Environmental Science*, 2015, pp.31–38.
- [13] Gevo resumes commercial production of isobutanol at its Luverne plant. *Focus Catalysts*, Vol. 8, 2013, p. 2.
- [14] Gevo to make bio-isobutanol in Malaysia. *Focus Catalysts*, Vol. 8, 2012, p. 3.
- [15] Giles, L.V., Carlsten, C. and Koehle MS. “The effect of preexercise diesel exhaust exposure on cycling performance and cardio-respiratory variables”. *Inhal Toxicol* Vol. 24, 2012, pp. 783–789.
- [16] Gu, X., Li, G., and Jiang, X., et al. “Experimental study on the performance of and emissions from a low-speed light duty diesel engine fueled with n-butanol–diesel and isobutanol–diesel blends”, *Proc IMechE, Part D: J Automobile Engineering*, Vol. 227, 2013, pp. 261–271.
- [17] He, C., Ge, Y. S., Han, X. K. and Lu, X. M., “Combustion characteristics of direct injection diesel engine fueled with biodiesel”, *Chinese Internal Combustion Engine Engineering*, Vol. 28, 2007, pp. 7–15.
- [18] He, C., Ge, Y., Ma, C., Tan, J., Liu, Z., Wang, C., and Ding, Y., “Emission characteristics of a heavy-duty diesel engine at simulated high altitudes”, *Science of the Total Environment*, Vol. 409(17), 2011, pp. 3138–43, doi:10.1016/j.scitotenv.2011.01.029.
- [19] He, C., Ge, Y., Tan, J., You, K., Han, X., and Wang, J., “Characteristics of polycyclic aromatic hydrocarbons emissions of diesel engine fueled with biodiesel and diesel”, *Fuel*, Vol. 89(8), 2010, pp. 2040–46, doi:10.1016/j.fuel.2010.03.014.
- [20] He, C., Ge, Y., Tan, J., You, K., Han, X., Wang, J., and Shah, A.N., “Comparison of carbonyl compounds emissions from diesel engine fueled with biodiesel and diesel”, *Atmospheric Environment*, Vol. 43(24), 2009, pp. 3657–61. doi:10.1016/j.atmosenv.2009.04.007.
- [21] Higashide, W., Li, Y., and Yang, Y., “Metabolic engineering of *Clostridium cellulolyticum* for production of isobutanol from cellulose”, *Appl Environ Microbiol.*, Vol. 77, 2011, pp. 2727–2733.
- [22] Hulwan, D.B., and Joshi, S.V., “Performance, emission and combustion characteristic of a multicylinder DI diesel engine running on diesel–ethanol–biodiesel blends of high ethanol content”, *Applied Energy*, Vol. 88(12), 2011, pp. 5042–55. doi:10.1016/j.apenergy.2011.07.008.

- [23] Imran, A., Varman, M., Masjuki, H.H., et al., "Review on alcohol fumigation on diesel engine: A viable alternative dual fuel technology for satisfactory engine performance and reduction of environment concerning emission", *Renew Sustain Energy Rev.*, Vol. 26, 2013, pp. 739–751.
- [24] Innes, W.B. "Effect of nitrogen oxide emissions on ozone levels in metropolitan regions", *Environ Sci Technol.*, Vol. 15, 1981, pp. 904–912.
- [25] Jha, S.K., Fernando, S., Columbus, E., and Willcutt, H., "A comparative study of exhaust emissions using diesel-biodiesel-ethanol blends in new and used engines", *Transactions of the ASABE*, Vol. 52(2), 2009, pp. 375–81. doi:10.13031/ 2013.26821.
- [26] Karabektas, M., and Hosoz, M., "Performance and emission characteristics of a diesel engine using iso-butanol - diesel fuel blends", *Renew Energy*, Vol. 34, 2009, pp. 1554–1559.
- [27] Kolodziej, R., and Scheib, J., Bio-isobutanol: The next generation biofuel. www.hydrocarbonprocessing.com/Article/3081332/Bio-isobutanol-The-next-generation-biofuel.html (accessed 16 September 2015).
- [28] Kwanchareon, P., Luengnaruemitchai, A., and Jai-In, S., "Solubility of a diesel–biodiesel–ethanol blend, its fuel properties, and its emission characteristics from diesel engine", *Fuel*, Vol. 86 (7–8), 2007, pp. 1053–61. doi:10.1016/j.fuel.2006.09.034.
- [29] Lapuerta, M., Garcí'a-Contreras, R., and Campos-Fernández, J., et al. "Stability, lubricity, viscosity, and cold-flow properties of alcohol–diesel blends", *Energy Fuels* Vol. 24, 2012, pp. 4497–4502.
- [30] Lee, C. S., Park, S. W., and Kwon, S. I., "An experimental study on the atomization and combustion characteristics of biodiesel-blended fuels", *Energy & Fuels*, Vol. 19(5), 2005, pp. 2201–08. doi:10.1021/ef050026h.
- [31] Lee, W. J., Liu, Y. C., Mwangi, F. K., Chen, W. H., Lin, S. L., Fukushima, Y., and Wang, L. C., "Assessment of energy performance and air pollutant emissions in a diesel engine generator fueled with water-containing ethanol–biodiesel–diesel blend of fuels", *Energy*, Vol. 36(9), 2011, pp. 5591–99, doi:10.1016/j.energy.2011.07.012.
- [32] Lei, J. L., Bi, Y. H., and Shen, L. Z., "Performance and emission characteristics of diesel engine fueled with ethanol-diesel blends in different altitude regions", *Journal of Biomedicine and Biotechnology*, 2011, pp.1–10, doi:10.1155/ 2011/417421.
- [33] Lei, J. L., Shen, L. Z., Bi, Y. H. and Chen, H., "A novel emulsifier for ethanol-diesel blends and its effect on performance and emissions of diesel engine", *Fuel*, Vol. 93, 2012, pp. 305–11. doi:10.1016/j.fuel.2011.06.013.

- [34] Li, H., Opgenorth, P.H., and Wernick, D.G., et al. "Integrate delectromicrobial conversion of CO₂ to higher alcohols", *Science*, Vol. 335, 2012, pp. 1596–1596.
- [35] Merchant, S.S., Zanoelo, E.F., Speth, R.L., et al., "Combustion and pyrolysis of iso-butanol: Experimental and chemical kinetic modeling study", *Combust Flame*, Vol. 160, 2013, pp. 1907–1929.
- [36] Moffat, R.J., "Using uncertainty analysis in the planning of an experiment", *J Fluids Eng.*, Vol. 107, 1985, pp. 173–178.
- [37] Noguchi, N., Terao, H., and Sakata, C., "Performance improvement by control of flow rates and diesel injection timing on dual-fuel engine with ethanol", *Bioresource Technology*, Vol. 56(1), 1996, pp. 35–39, doi:10.1016/0960-8524(95)00174-3.
- [38] Ofuonye, E., Kutin, K. and Stuart, D.T., "Engineering *Saccharomyces cerevisiae* fermentative pathways for the production of isobutanol", *Biofuels*, Vol. 4, 2013, pp. 185–201.
- [39] Ozsezen, A.N., Turkcan, A., and Sayin, C., et al., "Comparison of performance and combustion parameters in a heavy duty diesel engine fueled with iso-butanol/diesel fuel blends", *Energy, Explor Exploit.*, Vol. 29, 2011, pp. 525–541.
- [40] Pan, L., Zhang, Y., and Tian, Z., et al., "Experimental and kinetic study on ignition delay times of iso-butanol", *Energy Fuels*, Vol. 28, 2014, pp. 2160–2169.
- [41] Rakopoulos, D.C., Rakopoulos, C.D., Giakoumis, E.G., et al., "Effects of butanol–diesel fuel blends on the performance and emissions of a high-speed DI diesel engine", *Energy Convers Manage*, Vol. 51, 2010, pp. 1989–1997.
- [42] Wamankar, A.K., and Murugan, S., "Effect of injection timing on a DI diesel engine fuelled with a synthetic fuel blend", *J Energy Inst*, DOI: 10.1016/j.joei.2014. 11.003.
- [43] Wei, L., Cheung, C.S. and Huang, Z., "Effect of n-pentanol addition on the combustion, performance and emission characteristics of a direct-injection diesel engine", *Energy*, Vol. 70, 2014, pp. 172–180.
- [44] Zheng, Z., Li, C., and Liu, H., et al., "Experimental study on diesel conventional and low temperature combustion by fueling four isomers of butanol", *Fuel*, Vol. 141, 2015, pp. 109–119.
- [45] Zhu, R., Wang, X., and Miao, H., et al., "Effect of dimethoxymethane and exhaust gas recirculation on combustion and emission characteristics of a direct injection diesel engine", *Fuel*, Vol. 90, 2011, pp. 1731–1737.

APPENDICIES

ISB10	10% Iso-butanolp90% diesel by volume injected at standard injection timing
ISB20	20% Iso-butanolp80% diesel by volume injected at standard injection timing
ISB30	30% Iso-butanolp70% diesel by volume injected at standard injection timing
ISB40	40% Iso-butanolp60% diesel by volume injected at standard injection timing
ISB40 Ret	40% Iso-butanolp60% diesel by volume injected at retarded injection timing
Ret	retarded injection timing (21 CA bTDC)