

PROFESSIONAL TRAINING REPORT
at
Sathyabama Institute of Science and
Technology (Deemed to be University)

Submitted in partial fulfillment of the requirements for the
award of B.Tech (Bachelor in Technology) Bachelor of
Engineering Degree in Information Technology

By

AMIRNENI KRISHNA TEJA
REG. NO. 39120008



DEPARTMENT OF INFORMATION TECHNOLOGY

SCHOOL OF COMPUTING

SATHYABAMA INSTITUTE OF SCIENCE AND
TECHNOLOGY

JEPPIAAR NAGAR, RAJIV GANDHI SALAI,
CHENNAI – 600119, TAMILNADU

NOVEMBER 2021



SATHYABAMA
INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)
Accredited with Grade “A” by NAAC
(Established under Section 3 of UGC Act, 1956)
JEPPIAAR NAGAR, RAJIV GANDHI SALAI
CHENNAI– 600119
www.sathyabama.ac.in



DEPARTMENT OF INFORMATION TECHNOLOGY

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of **Amirneni Krishna Teja(Reg. No: 39120008)** who carried out the project entitled “**South German Creditbased on machine learning**” under my supervision from June 2021 to November2021.

Internal Guide

Dr.V.Nirmalrani

HEAD OF THE DEPARTMENT

Dr. R. SUBHASHINI M.E., Ph.D.,

Submitted for Viva voce Examination held on _____

InternalExaminer

ExternalExaminer

DECLARATION

I, **Amirneni Krishna Teja** hereby declare that the project report entitled "**South German Creditbased on machine learning**" done by me under the guidance of **Dr.V.Nirmalrani**, is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering Degree in Information technology.

DATE:

PLACE:

SIGNATURE OF THECANDIDATE

ACKNOWLEDGEMENT

I am pleased to acknowledge my sincere thanks to **Board of Management of SATHYABAMA** for their kind encouragement in doing this project and for completing it successfully. I am grateful to them.

I convey my thanks to **Dr.T.SasikalaM.E.,Ph.D,Dean,SchoolofComputing, Dr.R.Subhashini,M.E.,Ph.D Head of the Department of Computer Science and Engineering** for providing me necessary support and details at the right time during the progressive reviews.

I would like to express my sincere and deep sense of gratitude to my Project Guide **Dr.V.Nirmalrani**, for her valuable guidance, suggestions and constant encouragement paved way for the successful completion of my project work.

I wish to express my thanks to all Teaching and Non-teaching staff members of the **Department of Computer Science and Engineering** who were helpful in many ways for the completion of the project.

TRAINING CERTIFICATE



Abstract

It is a dare to the bank to give the loan to someone because, it is based on the persons the applicant's demographic and socio-economic profiles.

When a bank receives a loan application, based on the applicant's profile the bank has to make a decision regarding whether to go ahead with the loan approval or not. Two types of risks are associated with the bank's decision:

- If the applicant is a good credit risk, i.e. is likely to repay the loan, then not approving the loan to the person results in a loss of business to the bank
- If the applicant is a bad credit risk, i.e. is not likely to repay the loan, then approving the loan to the person results in a financial loss to the bank

It may be assumed that the second risk is a greater risk, as the bank (or any other institution lending the money to a untrustworthy party) had a higher chance of not being paid back the borrowed amount.

Soits on the part of the bank or other lending authority to evaluate the risks associated with lending money to a customer.

This study aims at addressing this problem by using the applicant's demographic and socio-economic profiles to assess the risk of lending loan to the customer.

In business terms, we try to minimize the risk and maximize of profit for the bank. To minimize loss from the bank's perspective, the bank needs a decision rule regarding who to give approval of the loan and who not to. An applicant's demographic and socio-economic profiles are considered by loan managers before a decision is taken regarding his/her loan application.

TABLE OF CONTENTS

CHAPTERNO.	TITLE	PAGENO.
	ABSTRACT	6
	LIST OF FIGURES	10
1	INTRODUCTION	11
	1.1 SOUTH GERMAN CREDIT	11
	1.2 ESTIMATION DATASET INFORMATION	12
	1.3 COMMON MACHINE LEARNING ALGORITHMS AND GOALS	13
2	AIM AND SCOPE OF THE PRESENT INVESTIGATION	19
	2.1 AIM	19
	2.2 SCOPE	19
	2.3 ATTRIBUTE INFORMATION	20
	2.4 MISSING ATTRIBUTES	21
	2.5 DISTRIBUTION OF ATTRIBUTE NO 21	21
	2.6 DATA PREPARATION	22

3	EXPERIMENTAL OR MATERIALS AND METHODS, ALGORITHMS USED	25
	3.1 TYPES OF CLASSIFICATION ALGORITHMS USED	25
	3.2 DECISION TREE ALGORITHM	25
	3.3 IMPORTED LIBRARIES	25
	3.5 IMPLEMENTATION OF DECISION TREE	30
4	RESULTS AND DISCUSSION, PERFORMANCE ANALYSIS	31
	4.1 TRAINING AND ACCURACY (MODEL ANALYSIS)	31
5	SUMMARY AND CONCLUSIONS	34
	5.1 SUMMARY AND CONCLUSIONS	34
	REFERENCES	34
	APPENDIX SCREENSHOTS AND OUTPUTS	36
	SOURCE CODE	47

LIST OF FIGURES

FIGURE NO.	FIGURE NAME	PAGE NO.
1	1.2	12
2	1.3.1	13
3	1.3.2	14
4	1.3.3	14
5	1.3.4	16
6	1.3.5	17
7	1.3.6	17
8	1.3.7	18
9	2.6.2	23
10	3.3.1	26
11	3.3.5	27
12	3.3.6	28
13	3.3.7	29
14	3.3.8	29
15	3.4.3	30
16	4.1.1	31
17	4.1.2	32

CHAPTER-1:INTRODUCTION

1.1 SOUTH GERMAN CREDIT

This Dataset is only for the bank for the loan. When a bank receives a loan application, based on the applicant's profile the bank has to make a decision regarding whether to go ahead with the loan approval or not. Two types of risks are associated with the bank's decision

- If the applicant is a good credit risk, i.e. is likely to repay the loan .If the applicant is a bad credit risk, i.e. is not likely to repay the loan
- This study aims at addressing this classification problem by using the the applicant's demographic and socio-economic profiles of **south german credit data** to examine the risk of lending loan to the customer.

we try to minimize the risk and maximize of profit for the bank. To minimize loss from the bank's perspective, the

bank needs a decision rule regarding who to give approval of the loan

1.2 ESTIMATING DATASET INFORMATION

- The given dataset contains 800 rows and 22 columns. The first 21 columns are features, the last column contains the classification label of '0's and '1'.

Dataset is given below (Fig.1.2)

Id	laufkont	laufzeit	moral	verw	hoehe	sparkont	beszeit	rate	fanges	buerge	wohnzeit	verm	alter	weilkred	wohn	bishkred	beruf	pers	telef	gastarb	kredit
1	0	1	18	4	2	1049	1	2	4	2	1	4	2	21	3	1	1	3	2	1	1
2	1	1	9	4	0	2799	1	3	2	3	1	2	1	36	3	1	2	3	1	1	2
3	2	12	2	9	841	2	4	2	2	1	4	1	23	3	1	1	2	2	1	2	1
4	3	1	12	4	0	2122	1	3	3	3	1	2	1	39	3	1	2	2	1	1	1
5	5	1	10	4	0	2241	1	2	1	3	1	3	1	48	3	1	2	2	1	1	1
6	6	1	8	4	0	3398	1	4	1	3	1	4	1	39	3	2	2	2	1	1	1
7	7	1	6	4	0	1361	1	2	2	3	1	4	1	40	3	2	1	2	1	1	1
8	8	4	18	4	3	1098	1	1	4	2	1	4	3	65	3	2	2	1	2	1	2
9	9	2	24	2	3	3758	3	1	1	2	1	4	4	23	3	1	1	1	2	1	2
10	10	1	11	4	0	3905	1	3	2	3	1	2	1	36	3	1	2	3	1	1	2
11	11	1	30	4	1	6187	2	4	1	4	1	4	3	24	3	1	2	3	2	1	2
12	12	1	6	4	3	1957	1	4	1	2	1	4	3	31	3	2	1	3	2	1	2
13	13	2	48	3	10	7582	2	1	2	3	1	4	4	31	3	2	1	4	2	2	2
14	15	1	6	2	3	2647	3	3	2	3	1	3	1	44	3	1	1	3	1	1	2
15	16	1	11	4	0	3939	1	3	1	3	1	2	1	40	3	2	2	2	1	1	2
16	17	2	18	2	3	3213	3	2	1	4	1	3	1	25	3	1	1	3	2	1	2
17	18	4	11	4	0	7228	1	3	1	3	1	4	2	39	3	2	2	2	1	1	2
18	19	2	12	4	0	3124	1	2	1	3	1	3	1	49	1	2	2	2	1	1	2
19	20	3	12	4	4	1424	1	4	4	3	1	3	2	26	3	2	1	3	2	1	2
20	21	1	6	4	0	4716	5	2	1	3	1	3	1	44	3	2	2	2	1	1	2
21	22	2	11	3	3	4771	1	4	2	3	1	4	2	51	3	2	1	3	2	1	2
22	23	1	12	2	2	652	1	5	4	2	1	4	2	24	3	1	1	3	2	1	2
23	24	8	15	2	0	3556	5	3	3	3	1	2	4	29	3	2	1	3	2	1	2
24	25	3	42	4	1	4796	1	5	4	3	1	4	4	56	3	3	1	3	2	1	2
25	26	3	30	4	3	3017	1	5	4	3	1	4	2	47	3	2	1	3	2	1	2
26	27	31	4	36	4	3535	1	4	4	3	1	4	3	37	3	2	2	3	2	2	2
27	28	33	4	24	2	1376	3	4	4	2	1	1	3	28	3	2	1	3	2	1	2

Fig 1.2 - excel sheet of the given south german credit dataset

1.3 COMMON MACHINE LEARNING ALGORITHMS AND GOALS

Then the The variety of machine learning algorithms are classified into three categories as follows –

Supervised learning algorithms model the relationship between features (independent variables) and a label (target) from given set of observations. Then the model is used to predict the label of new observations using the features. Depending on the characteristics of the target variable i.e., it can be either be classification(discrete variable) or regression (continuous variable) the task is further engaged.

Unsupervised learning finds the structures in unlabeled data.

Reinforcement learning works on action-reward principle. An agent learned to reach the goal by continuously calculating the rewards that it gained from the actions




Fig 1.3.1 - types of machine learning along with the field of use

ALGORITHMS

1. Linear Regression is a supervised learning algorithm and tries to be a bridge between a continuous target variable and one or more independent variables by fitting a linear equation to the data. For choosing this algorithm, there needs to be a linear relation between independent and target variable. As scatter plot shows the positive correlation between an independent variable(x-axis) and dependent variable (y-axis).




Fig 1.3.2 - Linear regression scatter plot

This would try to put regression line to represent relations. Common technique is ordinary-least squares (OLS). As a result, we could get a regression line as

a outcome by minimizing sum square of distance between data points and regression line.




Fig 1.3.3- Linear regression scatter plot with regression line

2. Naïve Bayes is a supervised learning algorithm used for classification problems, also called as Naïve Bayes Classifier. It assumes that features are independent of each other and there is no correlation between features. As assumption of features being uncorrelated is the reason for the name “naïve”.

Equaton:

$$p(A|B) = \frac{p(A) \cdot p(B|A)}{p(B)} \quad (\text{Bayes' Theorem})$$

$p(A|B)$: Probability of event A given event B has already occurred

$p(B|A)$: Probability of event B given event A has already occurred

$p(A)$: Probability of event A

$p(B)$: Probability of event B

3. Logistic Regression is a supervised learning algorithm which is mostly used for binary classification problems. Even when regression contradicts with classification, here the spot is for logistic that refers to logistic function which

does the classification task. It is simple but effective classification algorithms most commonly used for binary classification problems. Logistic function also known as sigmoid function.

Equation:

$$\text{Sigmoid Function: } y = \frac{1}{1 + e^{-x}}$$

Logistic regression takes linear equation as input and uses sigmoid function and logs odds to perform a binary problem. As result s shape graph will be the output




Fig 1.3.4 - Logistic regression with probability output in s shape

4. Decision Trees build upon continuously to partition the data. The aim of decision tree is to increase the predictiveness as much as possible at each stage so that the model keeps gaining information about the dataset.

Randomly splitting will not give us valuable insight into dataset. The purity of

node is inversely proportional to distribution of different classes in that node. Overfitting model would be too specific model and not be generalize well. Though it achieves high accuracy with training set but poorly on new. The depth of the tree is controlled by max_depth parameter for decision tree algorithm in scikit-learn. Is also suitable to work on a mixture of feature data types.

Example




Fig 1.3.5 - Example for decision tree

5. Random Forest is an ensemble of many decision trees. They are built using a method called bagging where decision trees are used as parallel estimators. When used in classification problem, the result will be based on majority of vote received from each decision tree.




Fig 1.3.6 - Random forest outlier

6. K-means Clustering is a way to group of set of data points in a way that similar data points are together. Thus, they look for dissimilarities or similarities among data points. It is an unsupervised learning so there is no label associated with data points. They try to find the underlying structures of the data. Clustering is not Classification.




Fig 1.3.7 -scatter plot on K- means clustering

CHAPTER-2: AIM AND SCOPE OF PRESENT INVESTIGATION

2.1 AIM:

To predict the Credit Risk in the given South German credit Data set using features from the given Data set

2.2 SCOPE:

In our daily life , all banks are Thinking the only thing about the loan.

Means, for giving loan to the person is it good to give or bad based on their demographic and socio-economic profiles.

In the given data set ,

1. Data set characteristics are Multivariate
2. Attribute characteristics are interger,real
3. Associated task – Classification
4. no.of instances – 800
5. no.of attributes – 22 (one attribute is not usefull)

Then, it will be 21 Attributes

2.3 ATTRIBUTES INFORMATION :

1. Id = Id of individual entries, for evaluation
2. laufkont = status
 - 1 : no checking account
 - 2 : ... < 0 DM
 - 3 : $0 \leq \dots < 200$ DM
 - 4 : ... ≥ 200 DM / salary for at least 1 year
3. laufzeit = duration
4. moral = credit_history
 - 0 : delay in paying off in the past
 - 1 : critical account/other credits elsewhere
 - 2 : no credits taken/all credits paid back duly
 - 3 : existing credits paid back duly till now
 - 4 : all credits at this bank paid back duly
5. verw = purpose
 - 0 : others
 - 1 : car (new)
 - 2 : car (used)
 - 3 : furniture/equipment
 - 4 : radio/television
 - 5 : domestic appliances
 - 6 : repairs
 - 7 : education
 - 8 : vacation
 - 9 : retraining
 - 10 : business
6. hoehe = amount
7. sparkont = savings
 - 1 : unknown/no savings account
 - 2 : ... < 100 DM
 - 3 : $100 \leq \dots < 500$ DM
 - 4 : $500 \leq \dots < 1000$ DM
 - 5 : ... ≥ 1000 DM
8. beszeit = employment_duration
 - 1 : unemployed
 - 2 : < 1 yr
 - 3 : $1 \leq \dots < 4$ yrs
 - 4 : $4 \leq \dots < 7$ yrs
 - 5 : ≥ 7 yrs
9. rate = installment_rate
 - 1 : ≥ 35
 - 2 : $25 \leq \dots < 35$
 - 3 : $20 \leq \dots < 25$
 - 4 : < 20
10. famges = personal_status_sex
 - 1 : male : divorced/separated
 - 2 : female : non-single or male : single
 - 3 : male : married/widowed
 - 4 : female : single
11. buerge = other_debtors
 - 1 : none
 - 2 : co-applicant
 - 3 : guarantor
12. wohnzeit = present_residence
 - 1 : < 1 yr
 - 2 : $1 \leq \dots < 4$ yrs
 - 3 : $4 \leq \dots < 7$ yrs
 - 4 : ≥ 7 yrs
13. verm = property
 - 1 : unknown / no property
 - 2 : car or other
 - 3 : building soc. savings agr./life insurance
 - 4 : real estate
14. alter = age
15. weatkred = other_installment_plans
 - 1 : bank
 - 2 : stores
 - 3 : none
16. wohn = housing
 - 1 : for free
 - 2 : rent
 - 3 : own

17. bishkred = number_credits1 : 1
2 : 2-3 3 : 4-5 4 : >= 6
18. beruf = job
1 : unemployed/unskilled - non-resident
2 : unskilled - resident
3 : skilled employee/official
4 : manager/self-empl./highly qualif. employee
19. pers = people_liable
1 : 3 or more 2 : 0 to 2
20. telef = telephone
1 : no
2 : yes (under customer name)
21. gastarb = foreign_worker1 : yes 2 : no
22. kredit (target column) = credit_risk0 : bad 1 : good

2.4 MISSING ATTRIBUTES :(denoted by "null")

Data columns (total 21 columns):

#	Column	Non-Null Count	Dtype
---	-----	-----	-----
0	status	800 non-null	int64
1	duration	800 non-null	int64
2	credit_history	800 non-null	int64
3	purpose	800 non-null	int64
4	amount	800 non-null	int64
5	savings	800 non-null	int64
6	employment_duration	800 non-null	int64
7	installment_rate	800 non-null	int64
8	personal_status_sex	800 non-null	int64
9	other_debtors	800 non-null	int64
10	present_residence	800 non-null	int64
11	property	800 non-null	int64
12	age	800 non-null	int64
13	other_installment_plans	800 non-null	int64
14	housing	800 non-null	int64
15	number_credits	800 non-null	int64
16	job	800 non-null	int64
17	people_liable	800 non-null	int64
18	telephone	800 non-null	int64
19	foreign_worker	800 non-null	int64
20	credit_risk	800 non-null	int64

dtypes: int64(21)

memory usage: 131.4 KB

Therefore there is no null values in the data set

2.5 DISTRIBUTION OF ATTRIBUTE NUMBER 21 :credit Risk

```
Good 1    600  
Bad  0    200  
Name: credit_risk, dtype: int64
```

2.6 DATA PREPARATION

In this project as a backbone tool python is used to carry out machine learning concepts. With the help of a software called Anaconda Navigator, a jupyter notebook is launched where it is already installed along with the navigator. jupyter notebook is an open-source web application that allows to create and share documents and has live code and also visualization.

After importing the required libraries the dataset will be read in the note book with help of data frame (two-dimensional labeled data structure with columns of potentially different types) and read_csv(desired file type).

Reading Dataset :

```
sgc=pd.read_csv(r"F:\machine learning by  
cognibot\my project techphanthons\SGC.csv")
```

The Dataset which is provided by them is in the language in German and we again modified it into the English(u.k)

The dataset provided cannot always be a fully valued set, in that case we need to prepare the data in such a way the machine understands what is the value that has been entered.

The Updated Dataset

In [6]:

```
sgc.columns=columns
sgc.head()
```

Out[6]:

	status	duration	credit_history	purpose	amount	savings	employment_duration	installment_rate	personal_status_sex	other_debtors	...	property	age	other_installment_plans	housing	number_credits	job	people_liable	tele
0	1	18	4	2	1049	1	2	4	2	1	...	2	21	3	1	1	3	2	
1	1	9	4	0	2799	1	3	2	3	1	...	1	36	3	1	2	3	1	
2	2	12	2	9	841	2	4	2	2	1	...	1	23	3	1	1	2	2	
3	1	12	4	0	2122	1	3	3	3	1	...	1	39	3	1	2	2	1	
4	1	10	4	0	2241	1	2	1	3	1	...	1	48	3	1	2	2	1	

5 rows × 21 columns

Fig 2.6.2 –Updated Dataset and Modified Dataset

Check the values for null using isnull() function.

```
status          0
duration        0
credit_history  0
purpose         0
amount          0
savings         0
employment_duration  0
installment_rate  0
personal_status_sex  0
other_debtors   0
present_residence  0
property        0
age            0
other_installment_plans  0
housing        0
number_credits  0
job            0
people_liable   0
telephone       0
foreign_worker  0
credit_risk     0
dtype: int64
```

The dataset is now ready for creating a machine learning model.

CHAPTER-3:EXPERIMENTAL OR MATERIAL AND METHODS, ALGORITHMS USED

The given data set is in the form of Classification algorithm.so,we used classification types to predict the accuracy.

3.1 Types of classification algorithms used:

Decision Tree

3.2Decision tree Algorithm:

- Decision Tree is a Supervised learning technique that can be used for both classification and Regression problems, but mostly it is preferred for solving Classification problems.
- It is a tree-structured classifier, where internal nodes represent the features of a dataset, branches represent the decision rules and each leaf node represents the outcome.
- In a Decision tree, there are two nodes, which are the Decision Node and Leaf Node
- It is a graphical representation for getting all the possible solutions to a problem/decision based on given conditions.

3.3 IMPORTED LIBRARIES

Libraries are collections of prewritten code that users can use to optimize tasks. In project as python is used for implementation tool, it has the most libraries as compared to other programming languages. More than of 60% machine learning developers use and goes for python as it is easy to learn. As python has comparatively large collection of libraries let's Ilook at the libraries that came in handy for mammographic dataset.




Fig 3.3.1- various python libraries for Machine Learning

LIBRARIES USED:

1. Pandas is a widely-used data analysis and manipulation library for python. It provides a lot of functions and methods that expedite the data analysis and preprocessing steps. IT also provides fast, flexible and expressive data structures working with relational or labeled or both easy and intuitive. Considered as fundamental high-level building block in performing practical, real-world data analysis in python. Has powerful tools like DataFrame and

Series for analyzing.

2. Numpy stands for Numerical Python, is a library consisting of multidimensional array objects and a collection of countless of routines for processing those arrays. Using this mathematical and logical operations on arrays can be performed. The difference in using Numpy from pandas is, it works on numerical data whereas pandas on tabular data.

3. sklearn stands for Scikit-learn, a machine learning library. It is imported for various classification, regression and clustering algorithms including k-means, random forest, support vector machines, gradient boosting and DBSCAN. It is designed using libraries Numpy and Scipy.

From the sklearn library and from the tree inside the library

DecisionTreeClassifier. It is a class capable of performing multi-class classifier on a dataset. When compared with other classifiers, DecisionTreeClassifier takes input as two arrays: an array X, sparse or dense, of shape(n_samples, n_features) holding training samples and an array Y of integer values, shape (n_samples), holding class labels for training sample.

From sklearn another one called model_selection for training and testing the model imports train_test_split. It is a method setting a blueprint to analyze data and the using it to measure new data. Selecting a proper model allows to generate accurate results while making prediction. For proceeding, we need to train the model by using a specific dataset and test the model against another dataset.

By default, `sklearntrain_test_split` will make random partitions for two subsets. We can also specify a random state for the operation. First, we need to split the dataset and then allocate the size for train and test. For this mammographic dataset we need train size as 80% (0.80) and test size as 20% (0.20) with the random state of 100.

4. Seaborn is a library built on top of matplotlib. It used for data visualization and exploratory data analysis. They work easily with dataframes and pandas library. The graphs created can also be customized easily. It provides default styles and color palettes to make statistical plots more attractive. Also closely integrated to the data structures from pandas




Fig 3.3.5- Example implementation of Seaborn library

6. Matplotlib.pyplot is a state-based interface to matplotlib. It provides a MATLAB-like way of plotting. It make changes to figures.





Fig 3.3.6- Hist plot

7. plotly:

The Plotly library is an interactive open-source library. Plotly makes data visualization and understanding simple and easy.

Fig 3.3.7 -plotly plot

Credit Risk



```
In [1]: import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
import plotly
import plotly.express as px
import plotly.graph_objects as go
import plotly.offline as pyo
from plotly.offline import init_notebook_mode, plot, iplot
import plotly.figure_factory as ff

from sklearn.metrics import accuracy_score
from sklearn.metrics import classification_report
from sklearn.metrics import confusion_matrix
from sklearn.model_selection import train_test_split
from sklearn.tree import DecisionTreeClassifier
```

Fig 3.3.8- Imported libraries in jupyter notebook

3.4 Implementation of Decision Tree :

1. Import the packages and classes you need.
2. Provide data to work with and eventually do appropriate transformations.
3. Create a regressor model and fit it with existing data.
4. Check the results of model fitting to know whether the model is satisfactory.

5. Apply the model for predictions.

Fitting the values into Decision Tree Classifier

```
In [32]: DT = DecisionTreeClassifier()  
DT.fit(x_train, y_train)  
y_pred = DT.predict(x_test)
```

Fig3.4.3 Testing and Training data

CHAPTER-4

RESULTS AND PERFORMANCE ANALYSIS

4.1 TRAINING AND ACCURACY (MODEL ANALYSIS)

Confusion matrix is to evaluate the accuracy of a classification. This visual metric plots the number of predictions made for each class for each possible class in a table, with each row corresponding to the actual labels and each column corresponding to a prediction. It is beneficial for detecting which actual classes are being detected the most, and what predicted classes are being misclassified as (Bhardwaj and Tiwari, 2015; Liu et al., 2009). To further highlight the misclassifications and compare predictions with other classifiers, the confusion

matrices are normalized to show a percentage rather than a count.

The resulted confusion matrix has 45 incorrect prediction i.e., $(25 + 20 = 45)$.

From the matrix of y_test and y_pred with the help of metrics library the incorrect prediction is the outcome

		PREDICTIVE VALUES	
		POSITIVE (1)	NEGATIVE (0)
ACTUAL VALUES	POSITIVE (1)	TP	FN
	NEGATIVE (0)	FP	TN

Fig 4.1.1- outlier of confusion matrix

For the given dataset:

Confusion matrix

```
cm=confusion_matrix(y_test,y_pred)
print('confusion matrix is\n',cm)
```

```
confusion matrix is
[[21 25]
 [24 90]]
```

Accuracy is an evaluation metric would be misleading as it would not be representative of how well the classifier fitted the data. Additionally, in breast cancer detection, detecting FPs and FNs is primordial to avoid interpreting malignant as

benign and vice versa, an interpretation which could harm the patient and eventually lead to their death.

$$\text{Accuracy} = \frac{TP + TN}{P + N}$$

For instance, if a dumb classifier that always classifies an image as “normal” is created, it would achieve 64.28% accuracy on the mini-MIAS dataset despite never picking up abnormal cases. Therefore, a mixture of additional metrics should be used to assess how well the model learns the mammograms data and generalize to unseen cases

Precision

corresponds to the number of correct positive predictions showing the model's ability to avoid labelling negative instances as positive.

$$\text{Precision} = \frac{TP}{TP + FP}$$

Recall

is the number of positive instances that are correctly predicted showing how well the model can find all positive instances.

$$\text{Recall} = \frac{TP}{TP + FN}$$

F1 Score

The F1 Score is the $2 * ((\text{precision} * \text{recall}) / (\text{precision} + \text{recall}))$. It is also called the F Score or the F Measure. Put another way, the F1 score conveys the balance between the precision and the recall.

```

*****
Accuracy  69.375
*****
*****
*****
precision    recall  f1-score   support

     0         0.47         0.50         0.48         46
     1         0.79         0.77         0.78        114

 accuracy          0.69         160
  macro avg         0.63         0.64         0.63         160
weighted avg         0.70         0.69         0.70         160
*****

```

FIGURE 4.1.2 ACCURACY, PRECISION, F1-SCORE, RECALL

CHAPTER-5

5.1 SUMMARY AND CONCLUSIONS

- We have modelled the South German Credit Data set using Decision Tree with the *accuracy* 69.375
- In this Project the credit risk is mainly based on the status of the account, Amount, credit history, purpose, age, gender, installment rate and the remaining rows are showing less impact on the project.
- In the future we can add more categories, plotting more graphs and make it more user friendly and improves its quality. I and my team members are interested in studying


these methods and implement in another Machine learning Algorithms .

REFERENCES

- [1] UCI Machine Learning Repository: Ionosphere Data Set
<https://drive.google.com/file/d/1LmZKbq3TPG5KkTGArsoHvhXpAvNb7u4J/view?usp=sharing>
- [2] For Learning Python Language
<https://www.learnpython.org/>
- [3] Scipy Lectures Notes
<http://scipy-lectures.org/downloads/ScipyLectures-simple.pdf>
- [4] Git Hub
<https://github.com/dabeaz-course/practical-python/blob/master/Notes/Contents.md>
- [5] Numpy
<https://numpy.org/doc/stable/user/quickstart.html>


WORKING ENVIRONMENT

ANACONDA NAVIGATOR is desktop GUI used to launch applications and also manage packages in one place. Outlook



CODING ENVIRONMENT

Jupyter notebook from the anaconda navigator is launched along with all the preinstalled packages for python.



A.Screenshots and Outputs

IRCTC Next G... x 39120101 Sai... x 39120101 Sai... x 39120101 Sai... x b tech full for... x MLPT Final Ph... x UCI Machine... x Team Tech Ph... x plotly in pyth... x

C:/Users/SRAVA/Downloads/Team%20Tech%20Phanthons%20(1).html

SOUTH GERMAN CREDIT RISK ANALYSIS

Variable name: status
Content: status of the debtor's checking account with the bank

Variable name: duration
Content: credit duration in months (quantitative)

Variable name: credit_history
Content: history of compliance with previous or concurrent credit contracts (categorical)

Variable name: purpose
Content: purpose for which the credit is needed (categorical)

Variable name: amount
Content: credit amount in DM (quantitative; result of monotonic transformation; actual data and type of transformation unknown)

Variable name: savings
Content: debtor's savings (categorical)

Variable name: employment_duration
Content: duration of debtor's employment with current employer (ordinal; discretized quantitative)

Variable name: installment_rate
Content: credit installments as a percentage of debtor's disposable income (ordinal; discretized quantitative)

Variable name: personal_status_sex
Content: combined information on sex and marital status; categorical; sex cannot be recovered from the variable, because male singles and female non-singles are coded with the same code (2); female widows cannot be easily classified, because the code table does not list them in any of the female categories

Variable name: age
Content: age in years (quantitative)

Variable name: other_installment_plans
Content: installment plans from providers other than the credit-giving bank (categorical)

Variable name: housing
Content: type of housing the debtor lives in (categorical)

Variable name: number_credits
Content: number of credits including the current one the debtor has (or had) at this bank (ordinal, discretized quantitative); contrary to Fahrmeir and Hamerle (1984) statement, the original data values are not available.

Variable name: job
Content: quality of debtor's job (ordinal)

Variable name: people_liable
Content: number of persons who financially depend on the debtor (i.e., are entitled to maintenance) (binary, discretized quantitative)

Variable name: telephone
Content: Is there a telephone landline registered on the debtor's name? (binary; remember that the data are from the 1970s)

Variable name: foreign_worker
Content: Is the debtor a foreign worker? (binary)

Variable name: credit_risk
Content: Has the credit contract been complied with (good) or not (bad) ? (binary)

```
In [1]: import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
import plotly
```

IRCTC Next G... 39120101 Sai... 39120101 Sai... 39120101 Sai... b tech full for... MLPT Final Ph... UCI Machine... Team Tech Ph... plotly in pyth...

C:\Users\SRAVA\Downloads\Team%20Tech%20Phanthons%20(1).html

```

In [1]: import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
import plotly
import plotly.express as px
import plotly.graph_objects as go
import plotly.offline as pyo
from plotly.offline import init_notebook_mode, plot, iplot
import plotly.figure_factory as ff

from sklearn.metrics import accuracy_score
from sklearn.metrics import classification_report
from sklearn.metrics import confusion_matrix
from sklearn.model_selection import train_test_split
from sklearn.tree import DecisionTreeClassifier

```

```

In [2]: sgcdp.read_csv(r"F:\machine learning by cognibot\my project tech phanthons\SGC.csv")

```

```

In [3]: sgc.head()

```

```

Out[3]:
   Id  laufkont  laufzeit  moral  verw  hoehe  sparkont  beszeit  rate  fanges  ...  verm  alter  weitekred  wohn  bishkired  beruf  pers  telef  gastarb  kredit
0  0         1         18         4         2    1049         1         2         4         2  ...         2    21         3         1         1         3         2         1         2         1
1  1         1         9         4         0    2799         1         3         2         3  ...         1    36         3         1         2         3         1         1         2         1
2  2         2        12         2         9     841         2         4         2         2  ...         1    23         3         1         1         2         2         1         2         1
3  3         1        12         4         0    2122         1         3         3         3  ...         1    39         3         1         2         2         1         1         1         1
4  5         1        10         4         0    2241         1         2         1         3  ...         1    48         3         1         2         2         1         1         1         1

5 rows x 22 columns

```

```

In [4]: sgc=sgc.drop('Id',axis=1) #Here,i am just dropped the column "Id" because, it is not usefull

```

```

In [5]: columns =['status','duration','credit_history','purpose','amount','savings','employment_duration','installment_rate',
               'personal_status_sex','other_debtors','present_residence','property','age','other_installment_plans','housing',
               'number_credits','job','people_liable','telephone','foreign_worker','credit_risk']
#here i just changed the column names from german to english for understand

```

The Updated Dataset

```

In [6]: sgc.columns=columns
sgc.head()

```

```

Out[6]:
   status  duration  credit_history  purpose  amount  savings  employment_duration  installment_rate  personal_status_sex  other_debtors  ...  property  age  other_installment_plans  housing  number_credits  job  people_liable  tele
0      1         18         4         2     1049         1         2         4         2         1  ...         2    21         3         1         1         3         2         1
1      1         9         4         0     2799         1         3         2         3         1  ...         1    36         3         1         2         3         1         1
2      2         12         2         9     841         2         4         2         2         1  ...         1    23         3         1         1         2         2         1
3      1         12         4         0     2122         1         3         3         3         1  ...         1    39         3         1         2         2         1         1
4      1         10         4         0     2241         1         2         1         3         1  ...         1    48         3         1         2         2         1         1

5 rows x 21 columns

```

```

In [7]: sgc.info()



```


```

<class 'pandas.core.frame.DataFrame'>
RangeIndex: 800 entries, 0 to 799
Data columns (total 21 columns):
 #   Column                Non-Null Count  Dtype
---  -
 0   status                800 non-null   int64
 1   duration              800 non-null   int64
 2   credit_history         800 non-null   int64
 3   purpose               800 non-null   int64
 4   amount               800 non-null   int64
 5   savings               800 non-null   int64
 6   employment_duration    800 non-null   int64
 7   installment_rate       800 non-null   int64
 8   personal_status_sex    800 non-null   int64
 9   other_debtors          800 non-null   int64
10   present_residence      800 non-null   int64
11   property               800 non-null   int64
12   age                   800 non-null   int64
13   other_installment_plans 800 non-null   int64


```


100% 22°C Polluted... ENG 22:48








Amount with credit_risk









IRCTC Next G... 39120101 Sai... 39120101 Sai... 39120101 Sai... b tech full for... MLPT Final Ph... UCI Machine... Team Tech Ph... plotly in pyth...

C:\Users\SRAVA\Downloads\Team%20Tech%20Phantons%20(1).html

```

1 34
Name: foreign_worker, dtype: int64

In [24]: fsgc.groupby(['job', 'foreign_worker'])['credit_risk'].mean().sort_values(ascending=False).reset_index()
round(f)

#here for job 1 : 'unemployed/unskilled - non-resident',
#2 : 'unskilled-resident', 3 : 'skilled employee/official', 4 : 'manager/self-employed/highly qualified employee'

Out[24]:
   job  foreign_worker  credit_risk
0    1                1          1.0
1    2                1          1.0
2    3                1          1.0
3    2                2          1.0
4    3                2          1.0
5    4                2          1.0
6    1                2          1.0
7    4                1          0.0

```

Installment Rate, Job, Employment Duration with Credit Risk

```


In [25]: hsgc.groupby(['installment_rate', 'job', 'employment_duration'])['credit_risk'].value_counts()
h


#here, installment rate for 1 : '35 or more', 2 : '25 to 35', 3 : '20 to 25', 4 : 'less than 20'
# employment duration 1 : 'unemployed', 2 : 'less than 1 year', 3 : '1 to 4 yrs', 4 : '4 to 7 yrs', 5 : '7 yrs or more'

Out[25]:
installment_rate  job  employment_duration  credit_risk
1                1    1                    1             4
                1    2                    1             2
                3    1                    1             1
                2    2                    1            10
                2    2                    0             2
                2    2                    0             0

```

100% 22°C Polluted... ENG 22:49







Finally

```
In [27]: trace = go.Pie(labels=['good','bad'], values = sg['credit_risk'].value_counts(),
                    textfont=dict(size=15), opacity = 0.8,
                    marker=dict(colors=['lightskyblue', 'gold'],
                                linedict(colors='000000', width=1.5)))

layout = dict(title = 'Credit Risk')

fig = dict(data = [trace], layout=layout)
iplot(fig)
```


Credit Risk



Correlation

```
In [28]: z=sgc.corr()
z
```

	status	duration	credit_history	purpose	amount	savings	employment_duration	installment_rate	personal_status_sex	other_debtors	property	age	other_installment_plans	housing	number_credits
status	1.000000	-0.061875	0.200746	0.048367	-0.046179	0.194128	0.124235	0.011159	0.037605	-0.149470	-0.025172	0.057873	0.075229	0.010417	
duration	-0.061875	1.000000	-0.104558	0.123985	0.633837	0.060331	0.040891	0.067341	0.017962	-0.033319	0.313027	-0.021195	-0.048868	0.180119	
credit_history	0.200746	-0.104558	1.000000	-0.084822	-0.062988	0.035090	0.128223	0.030229	0.028785	-0.031270	-0.038588	0.179632	0.194204	0.054755	
purpose	0.048367	0.123985	-0.084822	1.000000	0.059389	-0.017706	0.036595	0.043147	-0.019936	-0.006199	0.010090	0.015053	-0.099491	0.037090	
amount	-0.046179	0.633837	-0.062988	0.059389	1.000000	0.068256	-0.042872	-0.275210	-0.011889	-0.026118	0.317258	0.020706	-0.035665	0.150883	
savings	0.194128	0.060331	0.035090	-0.017706	0.068256	1.000000	0.136748	0.019063	0.007841	-0.115848	0.019604	0.073814	0.022783	-0.013802	
employment_duration	0.124235	0.040891	0.128223	0.036595	-0.042872	0.136748	1.000000	0.139715	0.092085	-0.016063	0.091126	0.243963	-0.014281	0.098030	
installment_rate	0.011159	0.067341	0.030229	0.043147	-0.275210	0.019063	0.139715	1.000000	0.122127	0.003414	0.064126	0.067389	-0.003730	0.095744	
personal_status_sex	0.037605	0.017962	0.028785	-0.019936	-0.011889	0.007841	0.092085	0.122127	1.000000	0.026368	-0.002655	0.010548	-0.044485	0.096432	
other_debtors	-0.149470	-0.033319	-0.031270	-0.006199	-0.026118	-0.115848	-0.016063	0.003414	0.026368	1.000000	-0.149506	-0.036346	-0.031670	-0.056457	
present_residence	-0.050166	0.031589	0.092603	0.031865	0.025308	0.080951	0.238146	0.057500	-0.046932	-0.016545	0.144737	0.270707	0.002125	0.012454	
property	-0.025172	0.313027	-0.038588	0.010090	0.317258	0.019604	0.091126	0.064126	-0.002655	-0.149506	1.000000	0.087131	-0.136345	0.353851	
age	0.057873	-0.021195	0.179632	0.015053	0.020706	0.073814	0.243963	0.067389	0.010548	-0.036346	0.087131	1.000000	-0.031647	0.309279	
other_installment_plans	0.075229	-0.048868	0.194204	-0.099491	-0.035665	0.022783	-0.014281	-0.003730	-0.044485	-0.031670	-0.136345	-0.031647	1.000000	-0.101504	
housing	0.010417	0.180119	0.054755	0.037090	0.150883	-0.013802	0.098030	0.095744	0.096432	-0.056457	0.353851	0.309279	-0.101504	1.000000	
number_credits	0.078500	-0.048292	0.450637	0.051137	-0.039061	-0.051418	0.112053	0.033783	0.045938	-0.023929	-0.001736	0.174650	-0.022205	0.055591	
job	0.045783	0.211473	0.010358	-0.006346	0.271071	-0.000767	0.108581	0.113897	0.014435	-0.046642	0.291816	-0.027636	0.024630	0.108978	
people_liable	0.017806	0.034983	-0.018131	0.037829	-0.030990	-0.022125	-0.127112	0.097828	-0.142611	-0.001280	-0.020057	-0.143718	0.066010	-0.106718	
telephone	0.069530	0.170775	0.053842	0.074890	0.285864	0.093448	0.091812	0.018358	0.024519	-0.085703	0.217852	0.155646	-0.017744	0.081088	
foreign_worker	0.034981	0.142461	-0.001099	0.117252	0.028530	-0.019944	0.042701	0.105954	-0.085654	-0.145788	0.146795	-0.010294	-0.018295	0.094082	
credit_risk	0.338864	-0.188310	0.229800	-0.023707	-0.137515	0.161292	0.113270	-0.080210	0.043531	0.010696	-0.126377	0.093694	0.108955	0.001369	



Model Building

```
In [30]: x=sgc.drop('credit_risk',axis=1)
y=sgc['credit_risk']
```

Train Test split

```
In [31]: x_train, x_test, y_train, y_test = train_test_split(x, y, test_size=0.2, random_state=1)
print("x_train",x_train.shape)
print("x_test",x_test.shape)

x_train (640, 20)
x_test (160, 20)
```

Fitting the values into Decision Tree Classifier

```
In [32]: DT = DecisionTreeClassifier()
DT.fit(x_train, y_train)
y_pred = DT.predict(x_test)
```

Accuracy

```
In [33]: print("Accuracy ",accuracy_score(y_test,y_pred)*100)

Accuracy 69.375
```

Confusion matrix

```
In [34]: cm=confusion_matrix(y_test,y_pred)
print('confusion matrix is\n',cm)

confusion matrix is
```

IRCTC Next G... x 39120101 Sa... x 39120101 Sa... x 39120101 Sa... x b tech full fo... x MLPT Final Ph... x UCI Machine... x Team Tech Ph... x plotly in pyth... x

C:\Users\SRAYA\Downloads\Team%20Tech%20Phantons%20(1).html

```
x_train (640, 20)
x_test (160, 20)
```

Fitting the values into Decision Tree Classifier

```
In [32]: DT = DecisionTreeClassifier()
DT.fit(x_train, y_train)
y_pred = DT.predict(x_test)
```

Accuracy

```
In [33]: print("Accuracy ", accuracy_score(y_test, y_pred)*100)
```

Accuracy 69.375

Confusion matrix

```
In [34]: cm=confusion_matrix(y_test,y_pred)
print('confusion matrix is\n',cm)
```

confusion matrix is
[[21 25]
[24 90]]

Classification Report (Precision and Recall)

```
In [35]: print(classification_report(y_test,y_pred))
```

	precision	recall	f1-score	support
0	0.47	0.46	0.46	46
1	0.78	0.79	0.79	114
accuracy			0.69	160
macro avg	0.62	0.62	0.62	160
weighted avg	0.69	0.69	0.69	160

In []:

100% 22°C Polluted... ENG 22:49

SOURCE CODE :

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
import plotly
import plotly.express as px
import plotly.graph_objects as go
import plotly.offline as pyo
from plotly.offline import init_notebook_mode, plot, iplot
import plotly.figure_factory as ff
```

```
from sklearn.metrics import accuracy_score
from sklearn.metrics import classification_report
from sklearn.metrics import confusion_matrix
from sklearn.model_selection import train_test_split
from sklearn.tree import DecisionTreeClassifier
sgc = pd.read_csv(r"F:\machine learning by cognibot\my project tech
phantons\SGC.csv")
```

In [3]:

```
sgc.head()
sgc = sgc.drop('Id', axis=1) #Here, i am just dropped the column "Id"
because, it is not usefull
```

In [5]:

```
columns
=['status', 'duration', 'credit_history', 'purpose', 'amount', 'savings', 'empl
oyment_duration', 'installment_rate',

'personal_status_sex', 'other_debtors', 'present_residence', 'property', '
age', 'other_installment_plans', 'housing',

'number_credits', 'job', 'people_liable', 'telephone', 'foreign_worker', 'cre
dit_risk']
#here i just changed the column names from german to english for
understand
sgc.columns = columns
sgc.head()
sgc.info()
```

```

sgc.isnull().sum()
sgc.describe().transpose()
sns.heatmap(sgc.isnull(),cmap='viridis')
plt.title('Sample Heat Map')
sgc['credit_risk'].value_counts()
sns.countplot(x='credit_risk',data=sgc) #here 0 is good and 1 is bad
plt.title('Credit Risk \n "0" is Bad && "1" is Good')
#here, some numerical coloums in the dataset which is
duration,amount,age
n=['duration','amount','age']
sgc[n].describe()
plt.figure(figsize=(13,7))
plt.hist(sgc['amount'],bins=30);
plt.title('amount\n')
plt.figure(figsize=(13,7))
plt.hist(sgc[sgc['credit_risk']==0]['amount'])
plt.title('Bad to credit')
plt.figure(figsize=(13,7))
plt.hist(sgc[sgc['credit_risk']==1]['amount'])
plt.title('Good to credit')
plt.figure(figsize=(10,10))
sns.countplot(x=sgc['credit_risk'],hue=sgc['purpose'])
plt.title('Purpose for Credit \n')
d=sgc.groupby(['purpose','credit_history'])['credit_risk'].mean().sort_
values(ascending=False).reset_index()
round(d)
plt.figure(figsize=(20,7))
sns.barplot(x='purpose',y='credit_risk',hue='credit_history',data=d)
plt.title(" Purpose && Credit history bar plot")
e=sgc.groupby(['personal_status_sex','installment_rate'])['credit_ris
k'].mean().sort_values(ascending=False).reset_index()
round(e)
plt.figure(figsize=(20,8))
sgc.groupby(['personal_status_sex','installment_rate'])['credit_risk'].
value_counts().sort_values(ascending=False).plot(kind='bar')
sgc['foreign_worker'].value_counts() #here 1=yes ,2=no
f=sgc.groupby(['job','foreign_worker'])['credit_risk'].mean().sort_valu
es(ascending=False).reset_index()
round(f)

```

```

#here for job 1 : 'unemployed/unskilled - non-resident',
#2 : 'unskilled-resident',3 : 'skilled employee/official',4 :
'manager/self-employed/highly qualified employee'
h=sgc.groupby(['installment_rate','job','employment_duration'])['credit_risk'].value_counts()
h

```

```

#here, installment rate for 1 : '35 or more', 2 : '25 to 35', 3 : '20 to 25', 4 : 'less than 20'
# employment duration 1 : 'unemployed',2 : 'less than 1 year', 3 : '1 to 4 yrs', 4 : '4 to 7 yrs', 5 : '7 yrs or more'
plt.figure(figsize=(25,10))
sns.pairplot(data=sgc,
              vars = ['installment_rate','job','employment_duration'],
              kind="scatter",
              diag_kind="kde",
              hue='credit_risk',
              height=2,
              aspect=1.1,
              palette="muted"
              )
plt.suptitle("Pair plot on Installment Rate , Job , Employment Duration", y=1.02)
plt.show()
trace =go.Pie(labels = ['good','bad'], values
=sgc['credit_risk'].value_counts(),
textfont=dict(size=15), opacity = 0.8,
              marker=dict(colors=['lightskyblue', 'gold'],
                          line=dict(color='#000000', width=1.5)))

layout =dict(title = 'Credit Risk')

fig =dict(data = [trace], layout=layout)
iplot(fig)

```

Correlation

```
z=sgc.corr()
```

```
z
```

Heatmap

```
plt.figure(figsize=(25,10))
```

```
sns.heatmap(z,annot=True,cmap='rainbow')
```

Model Building

```
x=sgc.drop('credit_risk',axis=1)
```

```
y=sgc['credit_risk']
```

```
x_train,x_test,y_train,y_test=train_test_split(x,y,test_size=0.2,random_state=1)
```

```
print("x_train",x_train.shape)
```

```
print("x_test",x_test.shape)
```

```
DT =DecisionTreeClassifier()
```

```
DT.fit(x_train, y_train)
```

```
y_pred=DT.predict(x_test)
```

```
print("Accuracy ",accuracy_score(y_test,y_pred)*100)
```

```
cm=confusion_matrix(y_test,y_pred)
```

```
print('confusion matrix is\n',cm)
```

```
print(classification_report(y_test,y_pred))
```

--THE END--