

SMART CROP PROTECTION FROM ANIMALS USING RASPBERRY PI

Submitted in partial fulfillment of the requirements for the award of
Bachelor of Engineering degree in
Electronics and Communication Engineering

By

T.HARI PREETHAM REDDY (37130154)
K.VISHNU VARDHAN (37130175)



DEPARTMENT OF ELECTRONICS AND COMMUNICATION
ENGINEERING

SCHOOL OF ELECTRICAL AND ELECTRONICS

SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)

Accredited with Grade "A" by NAAC
JEPPIAAR NAGAR, RAJIV GANDHI SALAI,
CHENNAI - 600 119

APRIL - 2021



SATHYABAMA
INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)
Accredited with Grade "A" by NAAC
JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI - 600 119
www.sathyabama.ac.in



**DEPARTMENT OF ELECTRONICS AND
COMMUNICATIONENGINEERING**

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of **T HARI PREETHAM** (Reg. No. 37130154) and **K VISHNU VARDHAN** (Reg. No. 37130175) who carried out the project entitled "**SMART CROP PROTECTION USING RASPBERRY PI**" under our supervision from December 2020 to March 2021.

Internal Guide
(Dr. S. BARANI)

Dr. T. RAVI, M.E., Ph.D.,
Head of the Department

Submitted for Viva voce Examination held on _____

Name:

Signature:

Internal Examiner

External Examiner

DECLARATION

We **T HARI PREETHAM** (Reg.No.37130154) and **K VISHNU VARDHAN** (Reg.No.37130175) hereby declare that the Project Report entitled **“SMART CROP PROTECTION USING RASPBERRY PI”** done by us under the guidance of **Dr. S. BARANI** at Sathyabama Institute of Science and Technology, **Chennai-600119** is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in Electronics and Communication Engineering.

1.

2.

DATE: 15.04.2021

PLACE: Chennai

SIGNATURE OF THE CANDIDATES

ACKNOWLEDGEMENT

We are pleased to acknowledge our sincere thanks to Board of Management of **SATHYABAMA** for their kind encouragement in doing this project and for completing it successfully. We are grateful to them.

We convey our thanks to **Dr. N. M. Nandhita, Dean, School of Electrical and Electronics Engineering** and **Dr. T. RAVI, Head of the Department, Dept. of Electrical and Electronics Engineering** for providing us necessary support and details at the right time during the progressive reviews.

We would also like to express our sincere and deep sense of gratitude to our internal guide **Dr. S. Barani** for her valuable guidance and suggestions during the progressive reviews for our project.

Table of Contents

S.No	Title	Page.No.
	Abstract	1
1.	Introduction	2
2.	Literature Survey	3
3.	IOT	5
3.1	Background	5
3.2	Definition	7
3.3	Vision	7
3.4	Objectives	7
4.	Embedded Systems	8
4.1	Example of Embedded System	9
4.2	History of Embedded System	9
4.3	Characteristics of an Embedded System	10
4.4	Important Terminologies used in embedded system	11
4.5	Architecture of embedded system	12
4.6	Types of embedded system	13
4.7	Differences between Microprocessor and microcontroller	15
4.8	Application of embedded system	15
4.9	Advantages of embedded system	17
5.	Methodology	19
5.1	Existing system	19
5.2	Proposed system	19
5.3	Hardware requirements	20
6.	Hardware Device	21
6.1	Raspberry Pi3model	21
6.2	Importance of raspberry pi3	23
6.3	Architectural overview	24
6.4	Performances	24
6.5	GPIO pin descriptions for raspberry pi	25
6.6	System console or unix console	29

6.7	USB Camera	33
6.8	Buzzer	38
7.	Software installation	40
7.1	Requirements for software installations	40
7.2	Set up raspberry pi with os	41
7.3	Operating System	42
7.4	Hook up with raspberry pi	46
7.5	Configure raspberry pi	47
7.6	Python	48
8	Results/Conclusions	50
	References	52

	List of Figures	
4.3	Characteristics of embedded system	10
4.5	Architecture of embedded system	12
4.6	Types of embedded systems	13
5.2	Block diagram	20
6.1	Raspberry pi3 board	22
6.5	GPIO pin diagram for raspberry pi3	26
6.6.1	SDHC Card	31
6.6.2	SD Card pin specification	31
6.7.1	USB Camera	33
6.7.2	Camera focus top view	36
6.8	Buzzer	39
7.2	Selection of ultra sd card	41
7.3	Image file selection	42
7.4	Raspberry pi connections	46
7.5	Raspberry pi configuration	47

ABSTRACT

Observation assumes a significant part in numerous fields be it at home, medical clinics, schools, public spots, farmlands and so on It assists us with checking a specific territory and forestall robbery and furthermore gives confirmation of proof. On account of farmlands or agrarian grounds reconnaissance is vital to keep unapproved individuals from accessing the region just as to shield the region from animals. Different strategies point just at observation which is primarily for human interlopers, however we will in general fail to remember that the fundamental foes of such ranchers are the animals which obliterate the yields. This prompts helpless yield of harvests and critical monetary misfortune to the proprietors of the farmland. This issue is articulated to the point that occasionally the ranchers choose to leave the zones infertile because of such continuous animal assaults. This framework assists us with warding off such wild animals from the farmlands just as gives observation usefulness.

CHAPTER-1

INTRODUCTION

Lately wild animals are exceptional test for the ranchers all through the world, Animals like wild pigs, elephant, tiger and monkeys and so on influence genuine harm to crops by animals running over the field and stomping on absurd. It makes the monetary issue the ranchers. To defeat this difficult we give an answer in this paper. This venture is utilized to ensure the farmland by utilizing raspberry pi.

In late many years, the work of many cultivating networks in the nation has gone under danger from the assaults of wild creatures on crops. Known about homeless animals regularly enter to fields and annihilate the harvests which bring about loss of yields for ranchers. The right now accessible situation utilize an alternate kind of techniques like utilizing boisterous commotions, disturbing conditions and egg splash units to keep the creatures from entering or annihilating the yield field. In certain frameworks, the animals are just identified utilizing PIR sensors and notice is shipped off the ranchers. These frameworks are not dependable with various sorts of creatures. In this proposed work, we are presenting an IOT based framework which is straightforward, solid and cost proficient to beat the issue looked by the ranchers. Each creature or gathering of creatures is having a particular scope of hearing frequencies. A specific scope of frequencies between the conference range is aggravating for creatures. The scope of aggravating recurrence of various creatures is determined to the framework. A recurrence generator is utilized to create the sounds with the ideal recurrence. The IOT framework can identify the creatures by utilizing TensorFlow picture preparing and caution them by transmitting a ultrasonic sound which has a place with their perceptible recurrence range. The essential thought is each creature have a feeling of obscure danger. In this proposed IOT framework, we utilize such frequencies to frighten.

CHAPTER-2

LITERATURE SURVEY

A few strategies have been proposed for keeping creatures from entering and obliterating the yield fields. The greater part of the framework utilizes noisy commotion and caution conditions. Some framework utilizes egg shower units and smoke to forestall creatures. Yet, over every one of these advances, creating the ultrasound frequencies of creatures which is disturbing for them is dependable and effective. These frequencies are diverse for all creatures. We made a model of the framework which produces Ultrasound frequencies and shows the most ideal outcome.

Jayprakash D Sonone, Dattatray A. Patil, and Kantilal P. Rane, "irritating and hearing recurrence distinguishing proof and age to keep away from creatures mishap", proposed a technique which shields the creatures from vehicle mishaps. The framework utilizes a PIR sensor with an ARM7 processor and sound recurrence generator to flee the creatures. The PIR sensor recognizes whether there are creatures out and about. The movement is perceived by the ARM7 processor and comparing ultrasonic signs are produced utilizing a sound enhancer. The sound intensifier is utilized to enhance the recurrence and this Ultrasound is delivered through a sound bell .

P. A. V. Deshpande, "Design and execution of a canny security framework for ranch insurance from wild animals", presented another framework in which the farmland is shielded from animals through pervasive wired organization gadgets. In this framework, the creatures are followed when they connect with the fence. fencing wire is utilized as the sensor for identifying the creatures. a speaker circuit is additionally utilized since the opposition of the wire is high. in the event that any adjustment in fencing wire is identified, it will be intensified and given to the ADC of the miniature regulator. Because of the change, a SMS is shipped off the ranchers utilizing the GSM module.

D. K. Sheela Sobana Rani, M. R. Lavanya, and M. Gayathri, proposed "An automatic repelling system to reduce human elephants conflicts using sensor" In this system, piezoelectric vibrating sensors are used to detect the elephants. There are three layers in the system in which the first and second layers are deployed with piezoelectric vibrating sensors. By sensing the voltage created by the sensor it detects whether it is an elephant or not. An Arduino microcontroller is used as the processing unit for the sensors. When the elephant crosses the first and second layers of the system, the piezoelectric sensor placed in the third layer will detect the elephant and smoke valve placed in this system will be activated which emits heavy smoke around that area. The smell created will runaway the animals from the area.

P. Divya, P. Ushakiran, and P. Praveen M, "Iot-based wild creature interruption identification framework",

presented a framework which screens the yield documented constantly. The framework is utilized to distinguish creatures also, offer notice to ranchers. The framework utilizes PIR sensors to distinguish creatures. Arduino microcontroller is utilized as the preparing unit of the framework. at the point when the creatures are identified the camera is enacted and the picture is sent for handling and distinguishing the sort of creature. When the wild creature is recognized then the subsequent anti-agents framework Is applied. The anti-agents framework can be of Sound Buzzer or Bright light producer. The framework will likewise inform the ranchers by sending SMS utilizing GSM module.

S. R.Chourey, P. A.Amale, and N. B.Bhawarkar,"IoT based remote sensor network for anticipation of yields from wild creatures", proposed a framework which utilizes remote sensor networks (WSN) and Internet of things (IOT) to keep the creatures from entering the harvest fields. Raspberry Pi is utilized as the primary preparing unit of the framework. The WSN is set in the homestead field and this comprise of one expert hub sensor. The proposed framework examinations the information for at least two groups having 8-10 hubs. The webcam is utilized to catch the picture of wild creatures that are identified. By utilizing the GSM module when the animals are identified, a SMS is shipped off the ranchers. Speaker is likewise used to create commotion.

CHAPTER-3

INTERNET OF THINGS(IoT)

3.1 BACKGROUND

The advanced space has seen significant changes over the most recent few years and according to industry specialists would keep on developing itself. The furthest down the line participant to the computerized space is the Internet of Things (IoT). IoT can likewise be characterized as interaction for programming, telecom and electronic equipment industry and vows to offer enormous freedoms for some businesses.

With the appearance of the Internet of Things (IoT), took care of by sensors soon to number in the trillions, working with savvy frameworks in the billions, and including a great many applications, the Internet of Things will drive new buyer and business conduct that will request progressively insightful industry arrangements, which, thusly, will drive trillions of dollars in a promising circumstance for IT industry and surprisingly more for the organizations that exploit the IoT. The quantity of Internet-associated gadgets (12.5 billion) outperformed the quantity of people (7 billion) in the world in 2011, and by 2020, Internet-associated gadgets are required to number between 26 billion and 50 billion worldwide. The Indian Government's arrangement of creating 100 brilliant urban communities in the country, for which Rs. 7,060 crores has been dispensed in the current financial plan could prompt an enormous and fast extension of IoT in the country. Likewise, the dispatch of the Digital India Program of the Government, which targets changing India into advanced engaged society and information economy will give the necessary force to improvement of the IoT business in the country.

The different activities proposed to be taken under the Smart City idea and the Digital India Program to arrangement Digital Infrastructure in the nation would help support the IoT business. IoT will be basic in making these urban areas more brilliant.

A portion of the vital parts of a shrewd city will be:

- Smart stopping
- Intelligent transport framework.

- Tele-care.
- Woman Safety Smart networks.
- Smart metropolitan lighting.
- Waste the board.
- Smart city upkeep.
- Digital-signage.
- Water Management

In addition to other things, IoT can help computerize answers for issues looked by different enterprises like horticulture, wellbeing administrations, energy, security, catastrophe the executives and so on through distantly associated gadgets. IoT offers roads for telecom administrators and framework integrators to altogether support their incomes and this has brought about their taking lead in selection of IoT applications and administrations being offered by the innovation. Aside from direct IoT applications, the IT business additionally has a chance to offer types of assistance, investigation and applications identified with IoT.

Web of Things includes three particular stages:

1. the sensors which gather information (counting recognizable proof and tending to the sensor/gadget),
2. an application which gathers and investigates this information for additional combination and,
3. Decision making and the transmission of information to the dynamic worker.

Scientific motors and Big information might be utilized for the dynamic interaction. A few nations like US, South Korea, China among others, have taken lead in their readiness for exploiting for IoT. The vital partners in the Internet of things activities would be the residents, the public authority and the business. Interest and coordinated effort of every one of the partner at a fitting stage is fundamental. At this crossroads, we require arrangements for advancement of IoT and choice of e fundamental spaces and afterward underline on building

answers for what Data will Service the Citizens . Web of Things ought to obviously plan with a basic objective of Value Up and Cost Down models. With industry coordinated effort, encounters from worldwide discussions, learnings from different nations who are pioneers in IoT, dynamic cooperation of worldwide accomplices will assist us with inciting development driven methodology. Key to achievement of Internet of Things would be in building open stages for usability and ease, building versatile models and utilizing residents as sensors. Information should be transparently gathered and divided among cross capacities to bring out greatest advantages. Support of new businesses at 4 this stage will help us devise some innovative methods/ concepts which could be cornerstones for the upcoming overall smart concept.

.

3.2 DEFINITION

IoT is a seamless connected network of embedded objects devices, in which M2M communication happens without any human involvement is possible using standard communication protocols. Phones and PCs are not part of IoT.

3.3 VISION

"To create associated and shrewd IoT based framework for our nation's Economy, Society, Environment and worldwide requirements. "

3.4 OBJECTIVES

1. To make an IoT industry in India of USD 15 billion by 2020. This will likewise prompt expansion in the associated gadgets from around 200 million to over 2.7 billion by 2020. According to Gartner Report the complete income produced from IoT industry would be USD 300 billion and the associated gadgets would be 27 billion by 2020 worldwide. It has been expected that India would have a portion of 5-6% of worldwide IoT industry
2. To embrace limit improvement (Human and Technology) for IoT explicit ranges of abilities for homegrown and global business sectors.
3. To attempt Research and advancement for all the helping advances.
4. To create IoT items explicit to Indian necessities in the areas of farming, wellbeing, water quality, cataclysmic events, transportation, security, car, production network the board, keen urban communities, Automated metering and observing of utilities, squander the executives, Oil and Gas) and so forth

CHAPTER-4

EMBEDDED SYSTEMS

What is a System

A framework is a game plan where all its segment work as indicated by the particular characterized rules. It is a strategy for getting sorted out, working, or performing at least one errands as per a fixed arrangement

What is an Embedded System

Installed System is a mix of program and equipment which is either fixed in capacity or programmable. An inserted framework can be either a free framework, or it very well may be a piece of an enormous framework. It is generally intended for a particular capacity or capacities inside a bigger framework. For instance, an alarm is a typical illustration of an implanted framework which can detect just smoke.

4.1EXAMPLES OF EMBEDDED SYSTEMS

Laser Printer

Laser Printers are one of the instances of Embedded Systems which uses inserted frameworks to oversee different part of the printing. Aside from playing out the primary errand of printing, it needs to take client inputs, oversee correspondence with the PC framework, to deal with issues, and sense papers left on the plate, and so on

Here, the principle errand of the chip is to comprehend the content and control the printing head so that it releases ink where it is required.

To play out this, it needs to disentangle the various documents given to it and comprehend the textual style and designs. It will devour generous CPU time to deal with the information just as it needs to take client inputs, control engines, and so forth.

4.2 History of Embedded system

Important milestones from the history of embedded system:

- In 1960, embedded framework was first utilized for creating Apollo Guidance System by Charles Stark Draper at MIT.
- In 1965, Automatics, built up the D-17B, the PC utilized in the Minuteman rocket direction framework.
- In 1968, the previously implanted framework for a vehicle was delivered.
- Texas Instruments built up the first microcontroller in 1971.
- In 1987, the originally implanted OS, VxWorks, was delivered by Wind River.

- Microsoft's Windows inserted CE in 1996.
- By the last part of the 1990s, the originally inserted Linux framework showed up.
- The inserted market reach \$140 billion out of 2013.
- Analysts are projecting an Embedded market bigger than \$40 billion by 2030.

4.3 Characteristics of an Embedded System



Fig.4.3.characteristics of embedded system

- Requires constant execution
- It ought to have high accessibility and unwavering quality.
- Developed around a continuous working framework
- Usually, have simple and a diskless activity, ROM boot
- Designed for one explicit errand
- It should be associated with peripherals to interface information and yield gadgets.
- Offers high dependability and strength
- Needed insignificant UI
- Limited memory, ease, less force utilizations
- It needn't bother with any optional memory in PC.

4.4 Important terminologies used in embedded system

Reliability

This proportion of the endurance likelihood of the framework when the capacity is basic during the run time.

Fault-Tolerance

Adaptation to non-critical failure is the ability of a PC framework to get by within the sight of flaws.

Real-Time

Implanted framework should meet different planning and different limitations. They are forced on it by the continuous common conduct of the outer world.

For instance, an air force division which monitors approaching rocket assaults should absolutely ascertain and design their counter-assault because of hard constant cutoff time. Else, it'll get annihilated.

Flexibility

It's structure frameworks with worked in troubleshooting openings which permits far off support.

For instance, you are building a space apparatus which will arrive on another grower to gather different kinds of information and send gathered detail back to us. On the off chance that this rocket went crazy and lost the control, we ought to have the option to make some significant demonstrative. Thus, adaptability is imperative while planning an installed framework.

Portability

Convenience is a proportion of the simplicity of utilizing similar inserted programming in different conditions. It requires summed up deliberations between the application program rationale itself and the low-level framework interfaces.

What is Microcontroller

A microcontroller is a solitary chip VLSI unit which is likewise called microcomputer. It contains all the memory and I/O interfaces required, while a universally useful microchip needs extra chips to offered by these vital capacities. Microcontrollers are generally utilized in implanted frameworks for ongoing control applications.

What is a Microprocessor

A microchip is a solitary chip semiconductor gadget. Its CPU contains a program counter, an ALU a stack pointer, working register, a clock timing circuit. It additionally incorporates ROM and RAM, memory decoder, and numerous sequential and equal ports.

4.5 Architecture of the Embedded System

Below is basic architecture of the Embedded System:




Fig.4.5.Architecture of embedded system

1) Sensor:

Sensor helps you to measures the actual amount and converts it to an electrical sign. It additionally stores the deliberate amount to the memory. This sign can be prepared by a spectator or by any electronic instrument like A2D converter.

Memory:

Memory is used to store information. Embedded System majorly contains two memory cells

1) Volatile 2) Non volatile memory.

Processor & ASICs:

This processes the data to measure the output and store in the memory.

D-A Converter:

D-A converter (A digital-to-analog converter) helps you to convert the digital data fed by the processor to analog data.

Actuator:

An actuator allows you to compare the output given by the D-A converter to the original output stored in it and stores the original output in the memory.

Types of Embedded System

Three types of Embedded Systems are:

Small Scale
Medium Scale
Sophisticated




Fig.4.6.Types of embedded system

4.6.1 Small Scale Embedded Systems:

This implanted framework can be planned with a solitary 8 or 16-cycle microcontroller. It tends to be worked with the assistance of a battery. For growing limited scope implanted framework, an editorial manager, constructing agent, (IDE), and cross constructing agent are the most imperative programming instruments.

4.6.2 Medium Scale Embedded Systems:

These sorts of implanted frameworks are planned utilizing 16 or 32-digit microcontrollers. These frameworks offer both equipment and programming intricacies. C, C++, Java, and source code designing apparatus, and so forth are utilized to build up this sort of implanted framework.

4.6.3 Sophisticated Embedded Systems

This sort of inserted frameworks have bunches of equipment and programming intricacies. You may require IPS, ASIPS, PLAs, design processor, or versatile processors. For the improvement of this framework, you need equipment and programming co-plan and parts which needs to consolidate in the last framework.

4.8 Application of Embedded Systems

Following are an important application of Embedded system:

Robotic science:

- Ground Vehicles
- Drones
- Underwater Vehicles
- Industrial Robots

Medical

- Dialysis Machine
- Infusion Pumps
- Cardiac Monitor
- Prosthetic Device

Automotive

- Engine Control
- Ignition System
- Brake System

Networking

- Router
- Hubs
- Gateways
- Electronics Instruments

Home Devices:

- TVs
- Digital Alarm
- Air Conditioner
- DVD Video Player
- Cameras

Automobiles

- Fuel Injection
- Lighting System
- Door Locks

- Air Bags
- Windows
- Parking Assistant System

Industrial Control

- Control System
- Missiles
- Shuttles

Advantages of Embedded System

- It can cover a wide assortment of conditions
- Less liable to reprise blunders
- Embedded System improved on equipment which, which decreases costs in general.
- Offers an upgraded execution
- The implanted framework is helpful for large scale manufacturing.
- The implanted framework is profoundly dependable.
- It has not many interconnections.
- The implanted framework is little in size.
- It has a quick activity.
- Offers improved item quality.
- It enhances the utilization of framework assets.
- It has a low force activity.

Disadvantages of Embedded System

- Embedded systems do a very specific task, so it cannot do different things.
- Embedded systems offer very limited resources.
- It doesn't offer any technological advancement.
- It is hard to backup of embedded files.

CHAPTER -5

METHODOLOGY

5.1 EXISTING SYSTEM:

A few strategies have been proposed for keeping creatures from entering and annihilating the harvest fields. The greater part of the framework utilizes uproarious clamor and alert conditions. Some framework utilizes egg shower units and smoke to forestall animals. Traditional electrified barrier has been useful as a gatekeeper of harvests. Nonetheless, that framework has a few issues, for example, it can't inform the voltage which at times drops. Moreover, the proprietors of the fence need to check the voltage however they can't know it without going there .

5.2 PROPOSED SYSTEM:

The primary point of our task is to shield the harvests from harm brought about by creature just as redirect the creature with no harm. Animal location framework is intended to recognize the presence of creature and offer an admonition. In this undertaking we utilized PIR sensors to recognize the development of the creature and convey message to the regulator .PIR sensors are sent nearby to identify any movement and henceforth turns ON a camera when development is distinguished, along these lines giving real time observing. It includes robotization of specific techniques used to keep the wild animals from entering the farmlands and annihilating the crops, by making sound utilizing buzzer. If movement of animal distinguished, a message will be shipped off the rancher and furthermore a live video connect is shipped off approved individual by means of email. All the sensors and parts are interfaced to the Raspberry pi board. Subsequently we think of such an item that can be helpful for ranchers, it forestalls the deficiency of harvests.




Fig.5.2.BLOCK DIAGRAM:

HARDWARE REQUIREMENTS:

- RASPBERRY PI
- USB CAMERA
- PIR MOTION SENSOR
- POWER SUPPLY
- MONITOR
- BUZZER

CHAPTER – 6

HARDWARE DESCRIPTION

6.1 RASPBERRY PI 3 MODEL B

The Raspberry Pi is a list card-sized single-board PC created in the UK by the Raspberry Pi Foundation with the expectation of advancing the instructing of fundamental software engineering in schools.

- The Raspberry Pi 3 conveys multiple times the preparing limit of Raspberry Pi 1 model.
- This second era Raspberry Pi has an updated Broadcom BCM2837 processor, which is an incredible ARM Cortex-A53 based 64 bit quad-center processor that runs at 1.2GHz. The board likewise includes an expansion in memory ability to 1Gbyte.

The Raspberry Pi has a Broadcom BCM2836 framework on a chip which incorporates a 900 MHz 32-digit quad-center ARM Cortex-A7, Video Core IV GPU, and was initially dispatched with 256 megabytes of RAM, later overhauled .




Fig 6.1 Raspberry Pi-3 Board

- It does exclude an underlying hard plate or strong state drive, yet it utilizes a SD card for booting and persevering stockpiling, with the Model B+ utilizing a Micro SD as demonstrated in figure 2.1.
- The Foundation gives Debian and Arch Linux ARM circulations for download.
- Tools are accessible for Python as the primary programming language, with help for BBC BASIC (by means of the RISC OS picture or the Brandy Basic clone for Linux), C, Java and Perl.

6.2 IMPORTANCE OF RASPBERRY PI 3

SPECIFICATIONS:

- Chip Broadcom BCM2837 SoC
- Core architecture: Quad-core ARM Cortex-A53
- 1.2GHz 32/64-bit quad-core ARM Cortex-A53
- GPU Dual Core Video Core IV® Multimedia Co-Processor
- Provides Open GL ES 2.0, hardware-accelerated Open VG, and 1080p30 H.264
- high-profile decode Capable of 1Gpixel/s, 1.5Gtexel/s or 24GFLOPs with texture filtering and DMA infrastructure
- Memory 1 GB LPDDR2 RAM at 900 MHz
- Operating System Boots from Micro SD card, running a version of the Linux operating system
- Dimensions 85 x 56 x 17mm
- Power Micro USB socket 5V, 2A
- Operating system-Linux, Fedora, RISC OS, Free BSD, Net BSD
- Power 2.5w, CPU-ARM116JZF-S.

CONNECTORS

- Ethernet 10/100 Base T Ethernet attachment.
- Video Output HDMI.
- Composite RCA (PAL and NTSC).
- Audio Output 3.5mm jack, HDMI.
- USB 4 x USB 2.0 Connector.
- GPIO Connector 40-pin 2.54 mm (100 mil) development header: 2x20 strip.
- Providing 40 GPIO sticks just as +3.3 V, +5 V and GND supply lines.
- Camera Connector 15-pin MIPI Camera Serial Interface (CSI-2).
- JTAG Not populated.

APPLICATIONS

- Living room PC.
- A mini Web browser.
- Arcade Pi.
- Robotics.
- Firefox OS on Pi.
- Bit Torrent Server.
- Weather Station.
- Home automation.
- Raspberry Pi Cluster.

6.3 ARCHITECTURAL OVERVIEW

The Raspberry Pi depends on the Broadcom BCM2837 framework on a chip SOC), which incorporates a 64-bit quad-core ARM Cortex-A53, 1.2GHz processor.

Video Core IV GPU, and was initially sent with 512 megabytes of RAM, later updated (Model B and Model B+) to 1GB. The framework has Secure Digital (SD) or Micro SD (Model B+) attachments for boot media and tenacious capacity.

The Raspberry Pi 3 conveys multiple times the preparing limit of past models. This second era Raspberry Pi has an updated Broadcom BCM2837 processor, which is an incredible ARM Cortex-A53 based quad-center processor that runs at 1.2GHz.

The board additionally includes an expansion in memory ability to 1Gbyte.

6.4 PERFORMANCES

The Raspberry Pi 3, with a quad-center Cortex-A53 processor, is portrayed as multiple times the exhibition of a Raspberry Pi 1. This was recommended to be profoundly reliant upon task stringing and guidance set use.

Benchmarks showed the Raspberry Pi 3 to be around 80% quicker than the Raspberry Pi 2 in parallelized undertakings.

6.5 GPIO PIN DESCRIPTIONS FOR RASPBERRY PI

Notwithstanding the natural USB, Ethernet and HDMI ports, the R-Pi offers lower-level interfaces expected to associate all the more straightforwardly with chips and subsystem modules.

These GPIO (broadly useful I/O) signals on the 2x13 header pins incorporate SPI, I²C, and sequential UART, 3V3 and 5V force. These interfaces are not "attachment and play" and expect care to stay away from miswriting.

The pins utilize a 3V3 rationale level and are not open minded toward 5V levels, for example, you may discover on a 5V fueled Arduino. CSI (camera sequential interface) can be utilized to associate the 5 MP camera accessible.

Not yet programming empowered is the flex link connectors with DSI (show sequential interface) and a sequential connection inside the HDMI connector called CEC.




Fig 6.5.1 GPIO Pin Diagram of Raspberry Pi-3

GPIO functions:

Universally useful information/yield (GPIO) is a nonexclusive pin on a coordinated circuit whose conduct, including whether it is an info or yield pin, can be constrained by the client at run time. GPIO pins have no unique reason characterized, and go unused as a matter of course.

The thought is that occasionally the framework integrator constructing a full framework that utilizes the chip may think that its valuable to have a small bunch of extra computerized control lines, and having these accessible from the chip can stay away from the exertion of masterminding extra hardware to give them.

GPIOs are used in:

- ☐ Devices with pin shortage: incorporated circuits like framework on-a-chip, implanted and custom equipment, and programmable rationale gadgets (for instance, FPGAs).
- ☐ Multifunction chips: power chiefs, sound codes, and video cards.
- ☐ Embedded applications (for instance, Arduino, Beagle Bone, PSoC packs and Raspberry Pi) utilize GPIO for perusing from different natural sensors (IR, video, temperature, 3-hub direction, and speed increase), and for composing yield to DC engines (by means of PWM), sound, LCD presentations, or LEDs for status.

GPIO capabilities may include:

- ☐ GPIO pins can be arranged to be information or yield
- ☐ GPIO pins can be empowered/crippled
- ☐ Input esteems are clear (ordinarily high=1, low=0)
- ☐ Output esteems are writable/comprehensible
- ☐ Input esteems can frequently be utilized as IRQs (normally for wakeup occasions)

GPIO peripherals fluctuate broadly. Now and again, they are exceptionally basic, a gathering of pins that can be exchanged collectively to one or the other information or yield.

Raspberry Pi Power Supply

To make the B+ more reliable and reduce the current, the power supply is completely modified.





Fig 6.5.2 Raspberry Pi 3 Power Supply

6.6 SYSTEM CONSOLE OR LINUX CONSOLE

The framework reassure, PC support, root comfort, administrator's comfort, or essentially comfort is the content section and show gadget for framework organization messages, especially those from the BIOS or boot loader, the bit, from the init framework and from the framework lumberjack.

It is an actual gadget comprising of a console and a screen, and generally is a book terminal, however may likewise be a graphical terminal. Framework supports are summed up to work stations, which are disconnected separately by virtual consoles and terminal emulators.

Today correspondence with framework comforts is by and large done uniquely, through the standard streams (stdio, stdout, and stderr), yet there might be framework explicit interfaces, for instance those utilized by the framework part.

6.7 SDHC (Secure Digital High Capacity Card)

Secure Digital (SD) is a nonvolatile memory card utilized broadly in convenient gadgets, like cell phones, advanced cameras, GPS route gadgets, handheld consoles, and tablet PCs.

The Secure Digital standard was presented in August 1999 as a developmental improvement over Multi Media Cards (MMC).

The Secure Digital standard is kept up by the SD Association (SDA). SD advances have been carried out in excess of 400 brands across many item classifications and in excess of 8,000 models.

The Secure Digital organization incorporates four card families accessible in three diverse structure factors. The four families are the first Standard-Capacity (SDSC),

6.8 Buzzer

A bell or beeper is a flagging gadget, generally electronic, ordinarily utilized in cars, domestic devices like a microwave, or game shows.

It most normally comprises of various switches or sensors associated with a control unit that decides whether and which catch was pushed.

A current time has slipped by, and typically enlightens a light on the suitable catch or control board, and sounds an admonition as a constant or irregular humming or signaling sound.

At first this gadget depended on an electromechanical framework which was indistinguishable from an electric ringer without the metal going. Frequently these units were moored to a divider or roof and utilized the roof or divider as a sounding board.

Another execution with some AC-associated gadgets was to carry out a circuit to make the AC current into a commotion sufficiently boisterous to drive an amplifier and attach this circuit to a modest 8-ohm speaker.

These days, it is more well known to utilize a ceramic based piezoelectric sounder like a Son ready which makes a piercing tone. Normally these were snared to "driver" circuits which fluctuated the pitch of the sound or beat the sound on and off.

A current time has passed, and as a rule enlightens a light on the suitable catch or control board, and sounds an admonition as a persistent or discontinuous humming or signaling sound.

At first this gadget depended on an electromechanical framework which was indistinguishable from an electric chime without the metal going. Regularly these units were moored to a divider or roof and utilized the roof or divider as a sounding board.

. In game shows it is otherwise called a "lockout framework," since when one individual signs ("hums in"), all others are bolted out from flagging. A few game shows have enormous ringer catches which are distinguished as "uncloggers".

"Signal" comes from the scratching commotion that ringers made when they were electromechanical



Fig: 6.8 Buzzer

CHAPTER - 7

7.1 SOFTWARE INSTALLATION

REQUIREMENTS FOR SOFTWARE INSTALLATION

The Raspberry Pi may be a computer all on its own, but you'll still need a lot of other things to make it work:

- ☐ A Raspberry Pi model B
- ☐ An HDMI-or composite video-able TV or screen: A HDMI-able screen since it offers better goal and inherent sound. You can utilize simple on the off chance that you need, in any case.
- ☐ An HDMI or composite video link: You'll need this link to interface Raspberry Pi to TV or screen.
- ☐ A 4GB Class 4 SD card (or better) and a card peruser: Most SD cards will work, however some aren't viable and will consequently cause issues.
- ☐ A USB console and mouse: Any standard USB console or mouse will do. Remote (non-Bluetooth) peripherals worked for me, yet I needed to unplug them and attachment them back in after the Raspberry Pi booted.
- ☐ An Ethernet link: Any standard Ethernet link will do. We need this to interface with network and the web, in any case, so we can forget about this thing whenever wanted.
- ☐ A great quality, miniature USB power supply that can give in any event 700mA at 5V: Most present day Smartphone chargers supply 700mA at 5V, however not all do. In the event that it offers at any rate that amount power, presumably great to go.

SET UP RASPBERRY PI WITH A BASIC OPERATING SYSTEM



Fig 7.2 Selection of Ultra SD Card ForOs Installation

7.3.OPERATING SYSTEM




Fig 7.3 Image File Selection

- ☐ Download the most recent variant of Raspbian and unfasten the .img record inside. (It's practically 500MB so it might take a short time to download.)
- ☐ Download RPi-sd card developer (make certain to pick the proper variant for introduced adaptation of OS X) and unfasten the application.
- ☐ Insert SD card into Mac utilizing a card peruser.
- ☐ Open RPi- sd card manufacturer. You'll promptly be approached to pick a Raspbian picture. Pick the .img document you downloaded before.
- ☐ It will ask SD card is associated. Since we embedded it before, it is, so feel free to click Continue. It will introduce SD card alternatives.
- ☐ If you just have one embedded, you will not see whatever else in the rundown and it'll be checked. If not, simply check just the card you need to utilize and click OK.
- ☐ Enter your executive secret word and snap OK.
- ☐ You'll be inquired as to whether the SD card was launched out. This should occur, as the application needs to un amount it so it can play out an immediate duplicate.

☐ Double-watch that your SD card is not, at this point accessible in the Finder. Try not to eliminate it from your USB port. At the point when you're certain, click Continue.

- RPi-sd card developer wraps up setting up your SD card, securely launch it and supplement it into your Raspberry Pi unit.
- RPi-sd card developer isn't an application to such an extent as it's an Automator activity that acts like one. A few group have detailed issues utilizing it, so in the event that you run into issues simply open up the Terminal application (Hard Drive → Applications → Utilities → Terminal) and adhere to the directions for Linux.
- The Raspberry Pi is a truly fit minicomputer that is adequately little to fit in your pocket (despite the fact that you'd likely never keep it there).
- You can amount to two USB gadgets (which, as a rule, will be a mouse and console) and interface it to the web through wired Ethernet. The Raspberry Pi is amazing and reasonable, permitting you to make a home media focus, web radio, or even your own VPN worker for next to nothing.
- That said, a little arrangement and a ton of different parts are needed to get it ready for action. In this post we'll investigate how to get a Raspberry Pi set up so you can begin utilizing it for an assortment of purposes.
- Open RPi-sd card developer. You'll promptly be approached to pick a Raspbian picture. Pick the .img document you downloaded before.
- It will ask SD card is associated. Since we embedded it before, it is, so feel free to click Continue. It will introduce SD card choices.
- If you just have one embedded, you will not see whatever else in the rundown and it'll be checked. If not, simply check just the card you need to utilize and click OK.
- Enter your head secret word and snap OK.

RASPBERRY PI OS INSTALLATION:

Raspberry Pi OS is the suggested working framework for ordinary use on a Raspberry Pi.

Raspberry Pi OS is a free working framework dependent on Debian, advanced for the Raspberry Pi equipment. Raspberry Pi OS accompanies more than 35,000 bundles: precompiled programming packaged in a decent configuration for simple establishment on your Raspberry Pi.

Raspberry Pi OS is a local area project under dynamic turn of events, with an accentuation on improving the solidness and execution of whatever number Debian bundles as could reasonably be expected.

Introducing working framework pictures

This asset discloses how to introduce a Raspberry Pi working framework picture on a SD card. You will require another PC with a SD card peruser to introduce the picture.

Before you start, remember to check the SD card prerequisites.

Utilizing Raspberry Pi Imager

Raspberry Pi have built up a graphical SD card composing device that deals with Mac OS, Ubuntu

18.04 and Windows, and is the least demanding alternative for most clients as it will download the picture and introduce it naturally to the SD card.

- Download the most recent rendition of Raspberry Pi Imager and introduce it.
- If you need to utilize Raspberry Pi Imager on the Raspberry Pi itself, you can introduce it from a terminal utilizing `sudo well-suited introduce rpi-imager`.
- Connect a SD card peruser with the SD card inside.
- Open Raspberry Pi Imager and pick the necessary OS from the rundown introduced.
- Choose the SD card you wish to compose your picture to.
- Review your choices and snap 'WRITE' to start composing information to the SD card.

Boot your new OS

You would now be able to embed the SD card into the Raspberry Pi and force it up.

For the authority Raspberry Pi OS, on the off chance that you need to physically sign in, the default client name is pi, with secret key raspberry. Recall the default console design is set to UK.

Arranging Raspberry Pi OS:

`raspi-config`

This page portrays the support based `raspi-config` application. On the off chance that you are utilizing the Raspberry Pi work area, you can utilize the graphical Raspberry Pi Configuration application from

the Preferences menu to arrange your Raspberry Pi.

`raspi-config` is the Raspberry Pi arrangement instrument initially composed by Alex Bradbury. It targets Raspberry Pi **OS**.

sudo raspi-config

The sudo is required because you will be changing files that you do not own as the pi user. You should see a blue screen with options in a grey box:

Note that the menu shown may differ slightly. It has the following top level options available:

Raspberry Pi Software Configuration Tool (rasp pi-config) | 1 System Options Configure system settings
Display Options Configure display settings

Interface Options Configure connections to peripherals4 Performance Options Configure performance settings

5 Localisation Options Configure language and regional settings6 Advanced Options Configure advanced settings

Update this tool to the latest version

About raspi-config Information about this configuration tool

<Select> <Finish>

Moving around the menu

Go through the and down bolt keys to move the featured determination between the alternatives accessible. Squeezing the correct bolt key will leap out of the Options menu and take you to the <Select> and <Finish> catches. Squeezing left will return you to the choices. Then again, you can utilize the Tab key to switch between these.

Note that in considerable arrangements of alternative qualities (like the rundown of timezone urban areas), you can likewise type a letter to jump to that part of the rundown. For instance, entering L will skip you to Lisbon, only two alternatives from London, to save you looking over entirely through the letter set.

7.4 HOOK UP RASPBERRY PI




Fig 7.4 Raspberry Pi Connections

Interfacing everything to Raspberry Pi is really simple. Start by associating the HDMI link from the unit to your TV (or screen). In case you're utilizing the simple composite video connection all things considered, associate it to your TV (or screen) and plug in a bunch of speakers to the 3.5mm sound jack.

On the off chance that you need your Raspberry Pi to interface with your organization and additionally the web, utilize an Ethernet link to associate it to your switch. In the event that you've set up a PC previously, this should all appear to be recognizable.

At long last, you need to interface Raspberry Pi with a miniature USB power connector. As referenced before, you need a connector that can give at any rate 700mA at 5V. Luckily, you likely as of now have one.

Numerous Smartphone and tablet chargers use miniature USB and give 700mA at 5V (or more). You can discover by perusing the little content on the fitting and searching for the yield segment.

7.5 CONFIGURE RASPBERRY PI



Fig 7.5.RASPBERRY PI CONFIGURATION

When Raspberry Pi boots interestingly you'll have to design a couple of things. You'll know it's prepared for you when you see a Raspi-config window with a huge rundown of settings. You can meddle with the others in the event that you feel so slanted.

Be that as it may, the lone thing you truly need to do is extend the record framework so you can go through all the space on your SD card. To do as such, follow these means:

1. Select extend rootfs (the subsequent choice) and press enter.
2. Confirm that you need to extend the record framework and let Raspbian do its thing.
3. When you're gotten back to the setup list, go right to the base and select the Finish choice.
4. It'll inquire as to whether you need to reboot. Pick yes.

Your Raspberry Pi will reboot and take a little longer this time since it needs to extend the record framework. Following an about brief you'll be approached to sign in.

Once you've logged in, you've got yourself a working Raspberry Pi.

PYTHON:

Python is an open source programming language that was made to be not difficult to-peruse and incredible. A Dutch software engineer named Guido van Rossum made Python in 1991. He named it after the network show Monty Python's Flying Circus. Numerous Python models and instructional exercises incorporate jokes from the show.

Python is a deciphered language. Deciphered dialects don't should be arranged to run. A program called a mediator runs Python code on practically any sort of PC. This implies that a developer can change the code and rapidly see the outcomes. This likewise implies Python is more slow than a gathered language like C, since it isn't running machine code straightforwardly.

Python is a decent programming language for novices. It is a significant level language, which implies a developer can zero in on what to do rather than how to do it. Composing programs in Python takes less time than in some different dialects.

Python drew motivation from other programming dialects like C, C++, Java, Perl, and Lisp.

Python has an exceptionally simple to-understand language structure. A portion of Python's grammar comes from C, since that is the language that Python was written in. However, Python utilizes whitespace to delimit code: spaces or tabs are utilized to put together code into gatherings. This is not the same as C. In C, there is a semicolon toward the finish of each line and wavy supports ({}) are utilized to bunch code. Utilizing whitespace to delimit code makes Python an exceptionally simple to-understand language.

Python use

Python is utilized by countless developers and is utilized in numerous spots. Now and then just Python code is utilized for a program, however more often than not it is utilized to do basic positions while another programming language is utilized to accomplish more muddled assignments.

Its standard library is comprised of numerous capacities that accompany Python when it is introduced. On the Internet there are numerous different libraries accessible that make it feasible for the Python language to accomplish more things. These libraries make it an amazing language; it can do various things.

Some things that Python is often used for are:

- Web development
- Scientific programming
- Desktop GUIs
- Network programming
- Game programming

CHAPTER-8

RESULTS

The destruction of crops by wild animals is one of the major problem faced by farmers. This project has the solution to prevent the animals from entering the crop . Hence we have designed an IoT based system which is cost efficient and requires less energy. Such a system will help the farmers to protect the fields and also save them from financial losses .In the future, this system can be designed more efficiently by using solar powered cameras and sound buzzers, which is cost-efficient and can be used without a wired connection.



REFERENCES

- Jayprakash D Sonone, Dattatray A. Patil, and Kantilal P. Rane, "Irritating and hearing frequency identification and generation to avoid animals accident," in International Journal of Innovative Research in Science, Engineering and Technology, July 2014, pp. 1–11.
- P. A. V. Deshpande, "Design and implementation of an intelligent security system for farm protection from wild animals," in International Journal of Science and Research (IJSR), Feb 2016, pp. 1–4.
- D. K. Sheela Sobana Rani, M. R. Lavanya, and M. Gayathri, "An automatic repelling system to reduce human elephants conflicts using sensors," in 2017 International Journal for Research in Applied Science Engineering Technology (IJRASET), May 2017, pp. 1–5.
- P. Divya, P. Usha kiran, and P. Praveen M, "Iot-based wild animal intrusion detection system," in International Journal on Recent and Innovation Trends in Computing and Communication, July 2018, pp. 1–3.
- S. R. Chourey, P. A. Amale, and N. B. Bhawarkar, "Iot based wireless sensor network for prevention of crops from wild animals," in International Journal of Electronics, Communication Soft Computing Science and Engineering, 2017, pp. 1–4.
- Pooja G and Mohmad Umair Bagali, "A smart farmland using raspberry pi crop vandalization prevention intrusion detection system," in IJARIE, 2016, pp. 1–7.
- [https://www.wolfib.com/Image Recognition-Intro-Part-1/](https://www.wolfib.com/Image%20Recognition-Intro-Part-1/), "How to build a simple imagerecognition system with tensorflow."
- K. Jambroi, B. Ivanevi, and A. Stimac, "The influence of ultrasound on animal irritation," 05 2019.
- <https://www.newscientist.com/article/dn12746-elephants-buzz-off-atthe-sound-of-bees/>, "Elephants buzz off at the sound of bees."
- P. K. Binu, R. A. Krishnan, and A. P. Kumar, "An efficient indoor location tracking and navigationsystem using simple magnetic map matching," in 2016 IEEE International Conference on Computational Intelligence and Computing Research (ICCIC), Dec 2016, pp. 1–7.
- S. Emrick, "Design and development of an iot based smart irrigation and fertilization system for chilli farming," 03 2018.

P. K. Binu, V. Akhil, and V. Mohan, "Smart and secure iot based child behaviour and health monitoring system using hadoop," in 2017 International Conference on Advances in Computing, Communications and Informatics (ICACCI), Sep. 2017, pp. 418–423.

P. Rekha, V. P. Rangan, M. V. Ramesh, and K. V. Nibi, "High yield groundnut agronomy: An iotbased precision farming framework," in 2017 IEEE Global Humanitarian Technology Conference (GHTC), Oct 2017, pp. 1–5.

Report

ORIGINALITY REPORT

11 %
SIMILARITY INDEX

0 %
INTERNET SOURCES

0 %
PUBLICATIONS

11 %
STUDENT PAPERS

PRIMARY SOURCES



Submitted to BITS, Pilani-Dubai
Student Paper

11 %

Exclude quotes On
Exclude bibliography On

Exclude matches < 10%