

ENHANCING OF FARMING PRODUCTIVITY WITH PROGRAMMABLE OBJECT INTERFACES

Submitted in partial fulfillment of the requirements for the award
of Bachelor of Engineering Degree in Electronics and
Communication Engineering

by

K. SUBBARAO (37130207)
K. SRI RAM (37130206)



SATHYABAMA

**INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)**

Accredited with Grade "A" by NAAC

JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI - 600 119

APRIL 2021



SATHYABAMA

**INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)**



Accredited with Grade “A” by NAAC

JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI 600119

www.sathyabama.ac.in

DEPARTMENT OF ELECTRONICS AND

COMMUNICATION ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of **K. SUBBARAO (37130207)** and **K. SRI RAM (37130206)** who carried out the project entitled “ENHANCING OF FRAMING PRODUCTIVITY WITH PROGRAMMABLE OBJECT INTERFACES” under our supervision from October 2020 to March 2021.

Internal Guide

Dr. S. Lakshmi M.E., Ph.D.

Department of ECE

Head of the Department

Dr. T. RAVI, M.E., Ph.D.

Submitted for Viva voce examination held on _____

Internal Examiner

External Examiner

DECLARATION

We, **K. SUBBARAO (37130207)** and **K. SRI RAM (37130206)** hereby declare that the Project Report entitled “**ENHANCING OF FARMING PRODUCTIVITY WITH PROGRAMMABLE OBJECT INTERFACES**” done by us under the guidance of **Dr. S. LAKSHMI M.E., Ph.D.** submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in Electronics and Communication Engineering.

1)

2)

DATE:

PLACE:

SIGNATURE OF THE CANDIDATES

ACKNOWLEDGEMENT

We are pleased to acknowledge our sincere thanks to Board of Management of **SATHYABAMA** for their kind encouragement in doing this project and for completing it successfully. We are grateful to them.

We convey our thanks to **Dr. N. M. NANDHITHA, M.E., Ph.D. Dean, School of Electrical and Electronics Engineering** and **Dr. T. RAVI, M.E., Ph.D. Head of the Department, Department of Electronics and Communication Engineering** for providing us necessary support and details at the right time during the progressive reviews.

We would like to express our sincere and deep sense of gratitude to our Project Guide **Dr. S. LAKSHMI M.E., Ph.D. Department of Electronics and Communication Engineering** for his valuable guidance, suggestions and constant encouragement paved way for the successful completion of the project work.

We wish to express our thanks to all teaching and Non-teaching staff members of the **Department of Electronics and Communication Engineering** who were helpful in many ways for the completion of the project.

We express our gratitude to our parents for their constant encouragement and support for the completion of the project.

TABLE OF CONTENTS

CHAPTER NO	TITLE	PAGE NO
	TABLE OF CONTENTS	V
	ABSTRACT	VII
	LIST OF FIGURES	VIII
	LIST OF ABBREVIATIONS	X
1.	INTRODUCTION	1
	1.1 IOT (INTERNET OF THINGS)	1
	1.2 IOT IN AGRICULTURE FOR SMART FRAMING	2
	1.3 RECENT TRENDS AND FUTURE	4
	1.4 ORGIN OF IDEA	5
2.	LITERATURE SURVERY	6
	2.1 LITERATURE SURVEY	6
	2.2 PROBLEMS FROM SURVEY	8
	2.3 OBJECTIVES	8
3.	EXISTING SYSTEM	9
	3.1 INTRODUCTION	9
	3.2 OBJECTIVES OF EXISTING SYSTEM	10

4.	PROPOSED SYSTEM	11
	4.1 PROPOSED METHODOLOGIES	11
	4.2 AREA OF PROJECT WORK AND SERVER	11
	4.3 DATA REFINEMENT ALGORITHM	12
	4.4 OVERVIEW	12
	4.5 COMPONENTS AND FUNCTIONING	13
	4.6 THINGSPEAK SERVER/CLOUD	38
5.	RESULT AND DISCUSSION	41
	5.1 DATA PROCESSED IN SERVER	41
	5.2 IDEAL VIEW	41
	5.3 OUTPUT ANALYSIS	43
6.	CONCLUSION AND FUTURE WORKS	45
	6.1 CONCLUSION	45
	6.2 FUTURE SCOPE	45
	REFERENCES	46

ABSTRACT

Agriculture is the common source of living for the people in India. It is backbone for the Indian economy. Agriculture using smart farming system, which uses Programmable Object Interfaces using IOT technology. It provide information about nature of farming fields and also take action depending on the farmer input. The created framework is fit for observing temperature, dampness, soil dampness level utilizing Arduino UNO and a few sensors associated with it, and warning as SMS will shipped off farmers telephone with Wi-Fi about natural state of of the field and the separate application is developed, for further requirements and is data is pushed to the server. Using Thing Speak server, the farmer can control the field through with various methods. This framework is a lot of supportive for ranchers they need to routinely siphon water and check the situation with each yield. From anywhere in the world, farmers can know the values of humidity, temperature and soil moisture and if the water is on through the server present in their smartphones. Smart irrigation system is useful for the ICT (Information and Communication Technology) in great manner like Agriculture extension and advisory service and can promote environmentally sustainable farming practices. Food safety is the first priority for every human being the ICT takes responsible in making it more effective.

The Thingspeak is the IoT examination stage administration that permits the client to total, imagine and investigate live information streams in the cloud by utilizing the Wi-Fi module. It provides the instant visualizations of data processed and pushed back with new data processed. Thingspeak in common known as Data Aggregation and analytics. Sufficient water check for the crop known by Soil moisture sensor. To be fact and technically speaking it improves the framing techniques and productivity. Finally using this method it increases the quantity and quality of Agriculture Products with reduction in work efficiency and daily wages.

LIST OF FIGURES

FIGURE NO	TITLE	PAGE NO
1.1	SMART FARMING	2
3.1	EXISTING SYSTEM BLOCK DIAGRAM	9
4.1	BLOCK DIAGRAM OF SMART FARMING	13
4.2	ARDUINO UNO PINOUT GUIDE	15
4.3	ARDUINO UNO	15
4.4	TECHNICAL SPECIFICATONS	16
4.5	ARDUINO CONNECTIONS ON CIRCUIT BOARD	18
4.6	TEMPERATURE SENSOR	19
4.7	LM35 ON CIRCUIT BOARD	20
4.8	HUMIDITY SENSOR	21
4.9	DHT11 ON CIRCUIT BOARD	21
4.10	LDR-LM393	22
4.11	LDR ON CIRCUIT BOARD	23
4.12	SOIL MOISTURE SENSOR	24
4.13	SOIL SENSOR ON CIRCUIT BOARD	24
4.14	WI-FI MODULE PINOUT	25
4.15	WIFI MODULE ON CIRCUIT BOARD	27
4.16	GSM MODULE	29

4.17	SIM800L ON CIRCUIT BOARD	30
4.18	GSM ARCHITECTURE	31
4.19	RELAY	34
4.20	WATER PUMP	35
4.21	WATER PUMP ON CIRCUIT BOARD	36
4.22	POWER SUPPLY	37
4.23	POWER SUPPLY ON CIRCUIT	
	BOARD.	38
4.24	THINKSPEAK	40
5.1	DEMONSTRATION	41
5.2	IDEAL VIEW WITH WATER	42
5.3	IDEAL VIEW WITHOUT WATER	42
5.4	TEMPERATURE CHART	43
5.5	HUMIDITY CHART	43
5.6	LDR CHART	44
5.7	SOIL CHART	44

LIST OF ABBREVIATIONS

IOT	INTERNET OF THINGS
DRA	DATA REFINEMENT ALGORITHM
LDR	LIGHT DEPENDENT RESISTOR
ICT	INFORMATION AND COMMUNICATION TECHNOLOGY
TTL	TRANSISTOR-TRANSISTOR LOGIC
ICSP	IN-CIRCUIT SERIAL PROGRAMMING
IDE	INTEGRATED DEVELOPMENT ENVIRONMENT
FDR	FREQUENCY DOMAIN REFLECTOMETRY
TDT	TIME DOMAIN TRANSMISSION
AMPS	ADVANCED MOBILE PHONE SERVICE
PDC	PERSONAL DIGITAL CELLULAR
CDMA	CODE DIVISION MULTIPLE ACCESS
GSM	GLOBAL SYSTEM FOR MOBILE COMMUNICATION
MMS	MULTIMEDIA MESSAGING SERVICES
AUC	AUTHENTICATION CENTRE
LCC	LOGICAL CONTROL CHANNEL
BSC	BASE STATION CONTROLLER
HLR	HOME LOCATION REGISTOR
VLR	VISITOR LOCATION REGISTOR

CHAPTER-1

INTRODUCTION

1.1 IOT (INTERNET OF THINGS)

In today's technology IoT had a good impact of making the things smarter and better. Technically speaking to the Technology that we live in, have multi-functioning in every aspects. No matter what is product is making the things smarter and better functioning setting the trend in present livelihood.

In the present innovation of IoT had a decent effect of making the things more astute and better. The IoT in today's world makes the things smarter and better options for the user in predictive manner. It is key role for the development of various technologies used to date. The web based automated smart data analysis, self-balancing projects in electronics were been modified using the IoT technology with smart emerging ways of data and managing it in efficient manner. The IoT technology also used in healthcare, agriculture fields were to manage the things in smart ways of arranging and predicting in advance. A delineation of the technology never predicted and not in analyzing ways of the modern methods used will ensure the daily basis of work with needed parameters. The different capacities in from exploring the technology IoT is the advanced solution for the future analysis. The data been stored and managed in various forms as user implements the code in own ways of developed things. IoT presents a typical stage for the entirety of the gadgets. An illustration of a straightforward IoT, an apparatus now accessible in certain houses sensor and might choose when people consume positive rooms and control levels of warming, lighting installations and various abilities in the house in this way. By expanding the Internet from "An organization of interconnected PCs to a local area of interconnected things" (Commission of the European People group 2009), the IoT will incorporate a monstrous and complex organization of devices.

1.2 IOT IN AGRICULTURE FOR SMART FRAMING

Smart Farming is the latest technique and best use in horticulture in developing food in a maintainable manner. It will enhance the productivity in efficient manner maintaining the risk of pressures in stable. As shown in figure 1.1 the Smart Farming significantly relies upon IoT accordingly disposing of the need for actual work of ranchers and cultivators and along these lines expanding the efficiency in each conceivable way.

Environment assumes a basic part for cultivating. Furthermore, having ill-advised information about environment vigorously disintegrates the amount and nature of the yield creation. IoT arrangements empower you to know the constant climate conditions. Sensors put inside and outside of the horticulture fields for data processing.



Fig: 1.1: Smart Framing

The traditional data set framework needs more stockpiling for the information gathered from the IoT sensors. Cloud based information stockpiling and a start to finish IoT Platform assumes a significant part in the keen horticulture framework. These frameworks assessed to assume a significant part to such an extent that better exercises performed. In the IoT world, sensors are the essential wellspring of gathering information for an enormous scope. The information examined and changed to important data utilizing examination devices. The information investigation helps in the examination of climate

conditions, domesticated animals conditions, and yield conditions. The information gathered use the mechanical developments and along these lines settling on better choices. With the assistance of the IoT gadgets, you can know the constant status of the yields by catching the information from sensors. Utilizing prescient investigation, you can get an understanding to settle on better choices identified with reaping. The pattern investigation encourages the ranchers to know impending climate conditions and reaping of harvests. IoT in the Agriculture Industry has assisted the ranchers with keeping up the nature of yields and richness of the land, in this manner improving the item volume and

The Advantages of Smart Framing

The Advantages of Smart Framing: Optimized crop treatment like exact planting, watering, pesticide application and assembling clearly impacts creation rates. Environment assumptions and soil soggy sensors think about water use exactly when and where required. Ranchers can picture creation levels, soil dampness, daylight power and more continuously and distantly speed up will help in settling on choice. Mechanizing measures in planting, treatment and reaping can lessen asset utilization, human blunder and generally cost. Dissecting creation quality and results in relationship to treatment can instruct ranchers to change cycles to build nature of the item. Precisely following creation rates by field over the long haul takes into consideration definite anticipating of future harvest yield and estimation of a ranch. Sensors and machines can used to identify propagation and wellbeing occasions prior in creatures. Geo fencing area following can likewise improve animals checking and the board. All protection endeavors, for example, water use and expanded creation per land unit straightforwardly influence the natural impression emphatically. Neighborhood and business ranchers can screen various fields in different areas all throughout the planet from a web association. Choices can be made continuously and from anyplace. Cultivating gear can checked and kept up as per creation rates, work adequacy and disappointment expectation.

1.3 RECENT TRENDS AND FUTURE

With the recent agriculture trends dependent on agriculture, Internet of Things has brought huge benefits like efficient use of water, optimization of inputs and many more. What made difference were the huge benefits and which has become a revolutionized agriculture in the recent days. Making the field with in the user control and can add the advanced techniques to the field. The fate of patterns making the farming field into Smart Framing utilizing IoT. It is based Smart Farming improves the whole Agriculture framework by observing the field progressively. With the assistance of sensors and interconnectivity, the Internet of Things in Agriculture has saved the hour of the ranchers as well as diminished the lavish utilization of assets like Water and Electricity. It keeps various factors like humidity, temperature, soil etc. under check real-time observation.

The following were the future trends of IoT in Smart Framing

- Global Connectivity through any devices of analyzing the data processed.
- Minimum Human efforts in daily basis.
- Faster Access in the growth of the plants.
- Time Efficiency is more reliable.
- Efficient Communication like ICT used.

As well known the climatic conditions in India is Adverse and therefore having the data of the field helps the farmer to predict and analysis of the efficient crop growth depending on the season vary. IoT for Agriculture for Remote Monitoring data and the field results to benefits in agriculture. Livestock management and monitoring are the future of IoT in agriculture in India, where as Climate monitoring and greenhouse farming predicted. It results to the challenging tasks to Agriculture Sector.

Additionally, IoT necessities for computerization, interoperability, and establishment are simple. Besides, ton of scientists take thoughtfulness regarding the significance of the utilization of IoT in their examinations even with showing up certain difficulties like gathering information and security. Simultaneously the usage uses of IoT to reality it accompanied the success through improved harvest yield utilizing information measurements and overseeing of meteorological ranch stations.

1.4 ORIGIN OF IDEA

Our term is to ensure and encourage the Smart Farming techniques in efficient manner for making the agriculture more quality and quantity crops. The data processed in the server will help the farmers to analyze and predict the seasonal crop accordingly. The recent articles and novels of Smart Framing enhances the agriculture role in productive manner. The drawbacks of the existing found and done in efficient sensing of the sensors and data will be push back into the server effectively. Enhancing of framing productivity with programmable object interfaces will be a great novel to the Agriculture Sector.

CHAPTER-2

LITERATURE SURVEY

2.1 LITERATURE SURVEY

A reasonable number of works have found in the Literature Survey. There were very few using the techniques in the predictive manner. Although the proposed method is effectively used and it can be modified further. Our Survey helps us to find the errors and the way of overcoming it with smart algorithms and techniques.

Ahmed. N and Hussain. I, (2018), as they will probably control the way toward planning and executing Smart cultivating checking frameworks, in this paper we propose a nonexclusive reference engineering model, contemplating additionally a vital non-utilitarian necessity, the energy utilization limitation. Also, they introduce and examine the advances that fuse the four layers of the design model that are the Sensor Layer, the Network Layer, the Service Layer and the Application Layer.

Anusha. A and Sivanageswar Rao. G (2019), Measures taken for Atmosphere changes and precipitation has been capricious preposterous decade. Due to this in continuous time, climate smart methodologies called as smart agriculture embraced by various Indian farmers. Insightful cultivating is a robotized and facilitated information development completed with the IOT (Internet of Things). IOT is developing rapidly and by and large associated in each far off condition. In this paper, sensor development and distant frameworks blend of IOT advancement has been thought of and reviewed reliant on the genuine condition of rustic structure. A combined strategy with web and far off trades, Remote Monitoring System (RMS) is proposed.

Brun-Laguna. K and Diedrichs A. L, (2016) their objective of the PEACH project is to foresee ice occasions by dissecting estimations from sensors sent around a plantation. This demo gives an outline of the total arrangement we intended for Low-power remote organization and the back-end framework. The low-power remote organization is made completely out of business off-the-rack gadgets. We build up a strategy for conveying the organization and present the open-source apparatuses to help with the sending, and to screen the organization.

Chavan. C. H and Karande. P. V, (2014) as the conventional way to deal with measure these elements in a horticultural climate implied people physically taking estimations and checking them at different occasions. This paper examines a distant checking framework utilizing Zig honey bee. These hubs send information remotely to a focal worker, which gathers the information, stores it and will permit it to be dissected at that point showed depending on the situation and furthermore be shipped off the customer versatile.

Jaishetty. S. A and Patil. R, (2016) their view is Indian ranchers have received manual perception based strategy has brought about either inordinate utilization of pesticides or under utilization of watering or numerous issues which brings about less effective and less gainful harvests. We propose a novel IoT based answer for horticulture field observing and water system control. The framework interfaces actual detecting gadgets with the cloud and associates the water system control instrument with the cloud.

Karan kansara, and Babu Madhav (2015), measures followed were the conventional farmland water system procedures require manual intercession. With the mechanized innovation with water system, human intercession can limited. At whatever point there is an adjustment in temperature and mugginess of the environmental factors these sensors detects the adjustment in temperature and stickiness and gives an interfere with sign to the miniature regulator.

Katyara. S and Chowdhry. B. S and Kumar. W (2017), their exploration entitles the possibility of execution of remote sensor networks as far off terminal units (RTUs) and neighborhood control for administrative control and information procurement applications. These RTUs measure different elements including area and air moistness, kind of field and its temperature. The premise of this data, the measure of water required at various kinds of fields can provided and lot of water can be put something aside for other business applications.

2.2 PROBLEMS FROM SURVEY

Many were using the wireless technology in efficient manner, knowing the data within server is a challenging task. The algorithms and techniques used form various sources and missing the major things in productive framing like tracking, alert system, auto pumping water to the field. The field with sensors sensing the data in huge manner were will be stored in the server and push back to ensure that new data to be entered. The many techniques used here were like Zig bee technology and RF Technology, these were useful in the small analysis of the field, where as these can be produced limited areas only. The adoption techniques and power-less auto sensing methods and various fields of knowing the data. Most of the work done on the smart irrigation of sensing data but not storing of data in efficient manner. By using the LCD and knowing the data within specified area or Limited bandwidth. The sensors used were similar to that of existing and, data will pushed back to the server in our proposed method. The Problems in the survey helps to analyze the problems that they had done and helped us to overcome problems with that of existing methods. Many techniques and algorithms used but efficient as our proposed algorithm were, it helps the farmers for analyzing the seasonal crop growth and sustainably used.

2.3 OBJECTIVES

The objectives of this project firstly, using the IOT technology in day-to-day makes the life better and smarter. The Smart irrigation system in the agriculture fields will enhance the framing productivity in great manner. The data collected through the Thing speak server will help the farmers for predicting and analysis of farming with smart data pushed into the server. The very well needed and managing for the field is water in monitoring the field helps the farmers for automatic water pumping system in Agriculture fields.

- Field monitoring.
- Water management.
- Data processed and stored, Data will pushed back to the server.

CHAPTER-3

EXISTING SYSTEM

3.1 INTRODUCTION

Used the IOT for efficiency growth and quality crop, were as it has the better alerting system. Modern way of making use of SMS and Wi-Fi enabled module. Advanced solution for monitoring the soil. Webpage used for analyzing the data in the field. The proper way of tracking the filed with pH sensors. The data enhanced and predicted but not pushed back into the server. The field monitoring done based on weather conditioning. Cell phone with blynk utilized as Interface. In the framework rancher need not make the water stream into fields physically, however the framework consequently does that proficiently. The conventional techniques rehearsed by individuals may bring about colossal wastage of water.




Fig: 3.1. Existing system block diagram.

The Existing system is very clear that the data been shown in the LCD as shown in figure 3.1 the block diagram enhances the LCD setup for data entry. The data sensed by the sensors commonly entered to the Arduino converts the analog data to digital format. The Relay is similar to that of the proposed system clearly the data

processed in the proposed system will pushed back to the server to enter the new data readily to the server.

3.2 OBJECTIVES OF EXISTING SYSTEM

The after effect of preparing then passed to the dynamic and activity conjuring framework that decides a mechanized activity to be included. The versatile application created in android assists with checking the field from any place through utilization of web. The Internet options for the data not been processed to the server. The data entered in the server will help the user of farmers to predict the data and used for analysis. The objective of the existing system is Agriculture uses 85% of available fresh water resources worldwide. As the demand on water consumption is increasing, there is an urgent need to create strategies for sustainable use of water. As the world is trending into modern technologies. It is necessary to trend up in agriculture also. Latest technologies such as Internet of Things and Cloud in combination with Wireless Sensor Networks can lead to agricultural modernization. IoT can benefit from virtually unlimited capabilities and resources of cloud. Cloud can offer a powerful answer for IoT administration the board. IoT is an environment of associated actual gadgets that are available through the Internet. It consists of objects, sensor devices, communication infrastructure, computational and processing units. The objects have certain unique features and are uniquely identifiable and accessible to the Internet. These actual items are furnished with Radio Frequency Identification (RFID) labels. The sensors convey the data over the Internet to the cloud worker is a computational and preparing unit

The Objectives of the Existing System were as follows:

- Using IOT for Efficiency growth and quality crop.
- Modern way of using SMS and LCD for showing the data.
- Quality assessment for the crop.
- Advanced solution for monitoring soil.
- Webpage used for notification.

CHAPTER-4

PROPOSED SYSTEM

4.1 PROPOSED METHODOLOGIES

- Our proposed project will encounter the problems with of existing system limitations.
- Sufficient water to the field with the help of Relay.
- Adding the feature to the data processed to push back the data to the server.
- GSM provides the instant messages to the framers in case of any insufficient measures obtained.
- Reduction in the work efficiency and daily wages.
- Helpful for ICT (Information and communication Technology).

4.2 AREA OF PROJECT WORK AND SERVER

Agriculture in “Internet of Things” is modern method of implementing in today’s day-to-day life. Agriculture is predominant thing in India, where it is a backbone of Indian economy. The trends in this world today is to make the things to work smarter and better. The Internet of Things, or IoT, alludes to any arrangement of actual gadgets that get and move information over remote organization networks with restricted human mediation. It upholds the correspondence between devices, furthermore comprehensively known as (M2M) machine-to-machine correspondence. Along these lines, the actual gadgets can remain associated and thus the absolute straightforwardness is accessible with lesser failures and more noteworthy quality. This aide in Automation and control and prompts work quicker and precise. The information is the kind of source were every human needed in the world, the source attached to the IoT encourages the information in large amount in smarter ways. The IoT helps in monitoring this is the obvious advantage of IoT in monitoring. The time saved because of IoT cloud be quite large. The money invested on IoT is less and affordable. It enhances the automation in daily tasks leads to better monitoring of devices. The smart life is nothing but Better quality of life, everyone in world

were enhancing it. IoT used in Home Automation, Industrial Automation, Health monitoring, environment and Framing. IoT makes everyday objects “smart” by enabling them to transmit data and automate tasks. The IoT agricultural applications are making it possible for ranchers and farmers to collect meaningful data. Huge landowners and little ranchers should comprehend the capability of the IoT market for horticulture by introducing brilliant advancements to expand intensity and manageability in their creations. With the populace developing quickly, the interest can be effectively executed, just as little ranchers, carry out agrarian IoT arrangements in a prosperous way. Keen Farming is an arising idea that alludes to overseeing ranches utilizing present-day Information and Communication Technologies to expand the amount and nature of items while streamlining the human work required.

4.3 DATA REFINEMENT ALGORITHM

Data refinement algorithm is the process using a labeled set of input data and known responses to the data (output). The clusters combined and results the output in predicted manner. The data refines and be readily to that of next data entered.

4.4 OVERVIEW

Enhancing of framing productivity with programmable object interfaces. As shown in figure 4.1, The ThingSpeak is an IoT investigation stage administration that permits you to total, break down and envision the live information streams in the cloud. It resembles the local area where any client on the planet and open and check the examination of the outcomes acquired. It is cloud platform where you can send sensor data to the cloud. The user also can analyze and visualize your data with MATLAB or other software, including making the own applications. The ThingSpeak is widely used and it is available as a free service for non-commercial small projects (<3 million messages/year or ~8,200 messages/day). One unit also provides the ability to create a fixed number of channels on ThingSpeak. The farming productivity of the project consists of Arduino UNO, temperature sensor, LDR, Humidity, Soil moisture sensor, Power supply, GSM, Relay, Water Pump, Wi-Fi module, Server or cloud.




Fig: 4.1: Block Diagram of Smart Farming System.

ICT (INFORMATION AND COMMUNICATION TECHNOLOGY)

ICT fuses electronic innovations and strategies used to oversee data and information, including data dealing with apparatuses used to create, store, process, disseminate and trade data. The data processed in the server is useful for predictions and useful for analyzing the fields. The roles that it can enhance were as follows

- Agriculture Extension for field sources & Advisory service for latest methods.
- Promote environmentally sustainable farming practices and maintain hygiene.
- Disaster Management in different seasons.
- Enhanced market access within limits.
- Food safety and traceability one of the major priority.
- Financial Inclusion and Risk Management the result in managing profit and loss.
- Capacity building, empowerment in storing.
- Regulatory and policy with various methods.

4.5 COMPONENTS AND FUNCTIONING

The components used for doing this project were Arduino UNO, Temperature Sensor, Humidity Sensor, LDR, Soil moisture Sensor, Wi-Fi module, GSM Module, Relay (Water Pump), Power Supply.

ARDUINO UNO

Arduino is a PC equipment and programming organization, undertaking, and client local area that plans and makes microcontroller units for building computerized gadgets and intuitive items that can detect and control objects in the actual world. The task's items dispersed as open-source equipment and programming, which authorized under the GNU Lesser General Public License (LGPL) or the GNU General Public License (GPL), allowing the production of Arduino sheets and programming appropriation by anybody. Arduino sheets are accessible industrially in preassembled structure, or as DIY packs.

Arduino board designs use a variety of microprocessors and controllers. The sheets are outfitted with sets of cutting edge and straightforward information/yield (I/O) sticks that may be interfaced to various expansion sheets (shields) and various circuits.

The sheets feature successive correspondences interfaces, including Universal Serial Bus (USB) on specific models, which moreover used for stacking programs from PCs. The microcontrollers are routinely adjusted using a vernacular of features from the programming tongues C and C++

Hardware of Arduino:

Arduino is open-source equipment. As demonstrated in figure 4.2 the pinout of Arduino, The equipment reference plans were under a Creative Commons Attribution-Share-Alike 2.5 permit and are accessible on the Arduino site. Design and creation records for certain adaptations of the equipment are additionally accessible.

The source code for the IDE delivered under the GNU General Public License, rendition. By the by, an authority Bill of Materials of Arduino sheets has never been delivered by Arduino.




Fig: 4.2: Arduino Pinout Guide

An Arduino board comprises of an Atmel 8-, 16-or 32-digit AVR microcontroller (ATmega8, ATmega168, ATmega328, ATmega1280, ATmega2560), yet other creators' microcontrollers have been utilized since 2015. The sheets utilize single-line pins or female headers that work with associations for programming and joining into different circuits, as demonstrated in sort 4.3 the zoom out photograph of pins in Arduino were as per the following. Fig: 4.3:




Fig: 4.3: Arduino UNO

Arduino UNO The Arduino board uncovered the greater part of the microcontroller's I/O pins for use by different circuits. The Diecimila, Duemilanove, and current Uno] give 14 computerized I/O pins, six of which can deliver beat width regulated signs, six simple data sources, which can utilized as six advanced I/O pins. A few variations utilize various processors, of changing similarity. The Arduino project gives the Arduino facilitated improvement environment (IDE), which cross-stage application written in the programming language Java. It began from the IDE for the lingos Processing and Wiring. It likewise contains a message region, a book comfort, a toolbar with catches for regular capacities and a chain of command of activity menus. As demonstrated in figure 4.4 the specialized particulars of Arduino.

Microcontroller	ATmega328P
Operating Voltage	5V
Input Voltage (recommended)	7-12V
Input Voltage (limit)	6-20V
Digital I/O Pins	14 (of which 6 provide PWM output)
PWM Digital I/O Pins	6
Analog Input Pins	6
DC Current per I/O Pin	20 mA
DC Current for 3.3V Pin	50 mA
Flash Memory	32 KB (ATmega328P) of which 0.5 KB used by bootloader
SRAM	2 KB (ATmega328P)
EEPROM	1 KB (ATmega328P)
Clock Speed	16 MHz
LED_BUILTIN	13
Length	68.6 mm
Width	53.4 mm
Weight	25 g

Fig: 4.4: Technical Specifications.

The Arduino IDE upholds the dialects C and C++ utilizing uncommon standards of code organizing. The Arduino IDE supplies a product library from the Wiring project, which gives numerous basic info and yield systems.

Client composed code just requires two essential capacities, for beginning the sketch and the primary program circle, that are accumulated and connected with a program stub principle() into an executable cyclic leader program with the GNU toolchain, likewise included with the IDE circulation. Fig: 4.4: Technical Specifications. Programming The

Arduino/Genuino Uno can be customized with the (Arduino Software (IDE)). Select "Arduino/Genuino Uno" from the Tools > Board menu (as indicated by the microcontroller on your board). For subtleties, see the reference and instructional exercises. The ATmega16U2 (or 8U2 in the rev1 and rev2 sheets) firmware source code is available in the Arduino store. The ATmega16U2/8U2 is stacked with a DFU bootloader, which can be initiated by: On Rev1 sheets: interfacing the weld jumper on the rear of the board (close to the guide of Italy) and afterward reseating the 8U2. On Rev2 or later sheets: there is a resistor that pulls the 8U2/16U2 HWB line to ground, making it simpler to place into DFU mode. As demonstrated in figure 4.5 were the associations of the Arduino made for this task. Fig: 4.5 Arduino Connections on circuit board.

Memory The ATmega328 has 32 KB (with 0.5 KB involved by the bootloader). It likewise has 2 KB of SRAM and 1 KB of EEPROM (which can be perused and composed with the EEPROM library). Obviously they measure from ground to 5 volts, anyway it is possible to change the upper completion of their compass using the AREF pin and the straightforward reference () work. There are a couple of various pins on the board: AREF, Reference voltage for the simple sources of info. Utilized with simple reference (). Reset. Bring this line LOW to reset the microcontroller. Commonly used to add a reset catch to safeguards block the one on the board. Correspondence Arduino/Genuino Uno has various offices for speaking with a PC, another Arduino/Genuino board, or other microcontrollers. The ATmega328 gives UART TTL (5V) sequential correspondence, which is accessible on advanced pins 0 (RX) and 1 (TX). An ATmega16U2 on the board channels this consecutive correspondence over USB and appears as a virtual com port to programming on the PC. The 16U2 firmware uses the standard USB COM drivers, and no external driver is required. Regardless, on Windows, record is required. The Arduino Software (IDE) consolidates a persistent screen, which grants direct printed data to send and from the board. The RX and TX LEDs on the board will streak when data sent through the USB-to-consecutive chip and USB relationship with the PC (yet not for successive correspondence on pins 0 and 1). A Software Serial library licenses successive correspondence on any of the Uno's automated pins. The ATmega328 moreover maintains I2C (TWI) and SPI correspondence. The Arduino Software (IDE) incorporates a Wire library to work on

utilization of the I2C transport; see the documentation for subtleties. For SPI correspondence, utilize the SPI library.

As shown in figure 4.5 were the connections of the Arduino made for this project.



Fig: 4.5 Arduino Connections on circuit board.

It incorporates a code editorial manager with highlights, for example, text reordering, looking and supplanting text, programmed indenting, support coordinating, and language structure featuring, and gives straightforward a single tick systems to accumulate and transfer projects to an Arduino board. It likewise contains a message territory, a book comfort, a toolbar with catches for regular capacities and a progressive system of activity menus. The force pins are as per the following: V-in. The data voltage to the Arduino/Genuino board when it is using an external power source (as opposed to 5 volts from the USB affiliation or other oversaw power source). You can supply voltage through this pin, or, if giving voltage through the power jack, access it through this pin. 5V. This pin yields an oversaw 5V from the regulator on the board. The board can be given force either from the DC power jack (7 - 12V), the USB connector (5V), or the VIN pin of the board (7-12V). Giving voltage through the 5V or 3.3V pins avoids the regulator, and can hurt your board. 3V3. A 3.3 volt supply created by the on-board regulator. Most prominent current draw is 50 mA. GND. Ground pins. IOREF. This pin on the Arduino/Genuino board outfits the voltage reference with which the microcontroller works. An appropriately

One of the hardware stream control lines (DTR) of the ATmega8U2/16U2 is related with the reset line of the ATmega328 through 100 nanofarad capacitor. At the point when this line is stated (taken low), the reset line drops adequately long to reset the chip. The Arduino Software (IDE) utilizes this ability to permit you to transfer code by just squeezing the transfer button in the interface toolbar. This implies that the bootloader can have a more limited break, as the bringing down of DTR can be Well-organized with the beginning of the transfer

The temperature sensor utilized here is LM35. The LM35 is an incorporated circuit sensor that can be utilized to quantify temperature with an electrical yield corresponding to the temperature (in $^{\circ}\text{C}$). As demonstrated in figure 4.6 is the temperature sensor.



- 19

figure 4.6 is the temperature sensor. The LM35 - An Integrated Circuit Temperature Sensor Use of LM35s To Measure Temperature You can quantify temperature more precisely than a utilizing a thermistor The sensor hardware is fixed and not expose to oxidation, and so forth The LM35 produces a higher yield voltage than thermocouples and may not need that the yield voltage intensified. Working of LM35 It has a yield voltage that is corresponding to the Celsius temperature. The scale factor is $.01\text{V}/^\circ\text{C}$ The LM35 doesn't need any outer alignment or managing and keeps a precision of $\pm 0.4^\circ\text{C}$ at room temperature and $\pm 0.8^\circ\text{C}$ over a scope of 0°C to $+100^\circ\text{C}$.

- Another significant quality of the LM35DZ is that it draws just 60 miniature amps from its stock and has a low self-warming ability. The sensor self-warming causes under 0.1 C temperature ascend in still air. Utilize A LM35 (Electrical Connections) Here is a usually utilized circuit. For associations allude to the image above As demonstrated in figure 4.7 is the association of how temperature is associated with the circuit board. Fig: 4.7: LM35 on Circuit Board Use An LM35 (Electrical Connections)
- Here is a commonly used circuit. For connections refer to the picture above

As shown in figure 4.7 is the connection of how temperature is connected to the circuit board.




Fig: 4.7: LM35 on Circuit Board.

One wire in the photograph goes to the force supply. Both the resistor and the dark wire go to ground. The yield voltage estimated from the center pin to ground. To ascertain the Celsius perusing from the simple worth, we utilize the accompanying recipe to figure the

temperature in Celsius: Val = is the worth ship off the PC by the sequential port. Temp C= is the determined temperature esteem (in Celsius).

$$tempC = \frac{5.0 * val * 100}{1024}$$

- Val = is the worth ship off the PC by the sequential port. Temp C= is the determined temperature esteem (in Celsius). 5 is the reference we are utilizing 1024 is the goal of the 10 cycle inside ADC.

HUMIDITY SENSOR

The Humidity sensor used here is DTH11 as shown in figure 4.8 is Humidity sensor chips away at the guideline of relative moistness and gives the yield as voltage. This simple voltage gives the data about the rate relative stickiness present in the climate.




Fig: 4.8 Humidity Sensor

A miniature sensor consisting of a RH sensitive material deposited on a ceramic substrate. The AC resistance (impedance) of the sensor decreases as relative humidity increases

As shown in figure 4.9 the DHT11 wired on a circuit board.




Fig: 4.9 DHT11 on Circuit Board.

The general mugginess characterized as simple yield of sensor associated with ADC to get its comparing advanced worth. For alignment of advanced qualities, the reference voltage of ADC is set to 1.5 volts. The advanced qualities got at port of microcontroller. These digital values used to calculate percentage relative humidity of environment. The calculated data sent to the server by Wi-Fi module to display the percentage relative humidity.

- High sensitivity and reliability in a small package.
- Fast response time.
- High resistance to chemicals and contaminants.
- 5mm pitch terminations.

LDR (Light Dependent Resistor)

The LDR used here is LM393. As shown in figure 4.10, used for observing the Light Intensity of the field. A Light-Dependent Resistor, called an LDR, Photo resistor, photoconductor, or photocell, is a variable resistor whose value decreases with increasing incident light intensity.




Fig: 4.10 LDR- LM393

A LDR is made of a high-obstruction semiconductor. In the occasion that light falling on the device is of adequately high repeat, photons devoured by the semiconductor give bound electrons enough energy to bob into the conduction band.

The subsequent free electron (entire accomplice) lead power, in this way bringing down obstruction. As shown in figure 4.11 LM393 wired on a circuit board.




Fig: 4.11 LDR on Circuit Board.

When in darkness its resistance is very large and as more and more light falls on it its resistance becomes smaller and smaller.

SOIL MOISTURE SENSOR

Soil moisture sensor as shown in figure 4.12 were sensors measure the volumetric water content in soil. Since the direct gravimetric estimation of free soil dampness requires eliminating, drying, and weighing of an example, soil dampness sensors measure the volumetric water content by implication by utilizing some other property of the dirt, like electrical block, dielectric consistent, or correspondence with neutrons, as a middle person for the soggiiness content.

Fig: 4.12 Soil dampness Sensor The connection between the deliberate property and soil dampness must aligned and may differ contingent upon ecological factors, for example, soil type, temperature, or electric conductivity.




Fig: 4.12: Soil moisture Sensor

- Reflected microwave radiation influenced by the dirt dampness and utilized for distant detecting in hydrology and horticulture. Convenient test instruments can utilized by ranchers or landscapers. Soil dampness sensors ordinarily allude to sensors that gauge volumetric water content. Another class of sensors measure another property of dampness in soils called water potential. These sensors as referred to as soil water potential sensors and include tension meters and gypsum blocks. As shown in figure 4.13 Soil moisture Sensor wired on a circuit board.



Fig: 4.13: Soil sensor on Circuit Board.

Precisely estimates soil dampness utilizing licensed altered TDT innovation Self-adjusts to all dirt kinds and conditions. Soil dampness readings are inside 3% of the real volumetric soil dampness content. Estimation goes from 5% dampness to completely immersed soil. Equipped for estimating changes of under 0.1%. Measures soil temperature. Dampness readings are reliable in pungent conditions. Sensor is totally fixed no electrical contact with soil wipes out any electrostatic corruption or galvanic

consumption of the detecting component. Force flood safe. Stun safe. Not influenced by salts or manures.

Wi-Fi Module

The Wi-Fi module used here is ESP8266. As shown figure 4.14 is the pinout diagram of Wi-Fi module. When power applied to the module, It will show red power light turn on and the blue serial indicator light flicker briefly. If you have a 3.3V FTDI Serial to USB. It will begin unafraid of annihilating your new ESP8266 Wi-Fi module. Do take note of that numerous FTDI sheets have a bind jumper to change over from 3.3V to 5V activity.




Fig: 4.14: Wi-Fi Module

Wi-Fi Module – ESP8266

- It is a wireless SoC.
- It has GPIO, I2C, ADC, SPI, PWM and some more.
- It runs at 80MHz.
- 64KBytes of instruction RAM.
- 96KBytes of data RAM.
- 64KBytes boot ROM.
- It has a Win bond W25Q40BVNIG SPI flash.
- It is a RISC architecture.

The center is a 106micro Diamond Standard center (LX3) made by Tensilica. The ESP8266 chip made by Espressif. Modules bearing this chip made different producers.

The ESP8266 Wi-Fi Module is Self-contained SOC with joined TCP/IP show stack that can give any microcontroller induction to your Wi-Fi association. The ESP8266 is able to do either facilitating an application or offloading all Wi-Fi organizing capacities from another application processor. This module has an amazing enough ready preparing and capacity ability that permits it to be incorporated with the sensors and other application explicit gadgets through its GPIOs with insignificant improvement in advance and negligible stacking during runtime. Its serious level of on-chip combination takes into consideration insignificant outer hardware, including the front-end module, intended to possess negligible PCB territory. The ESP8266 upholds APSD for VoIP applications and Bluetooth interfaces, it contains a self-aligned RF permitting it to work under every single working condition, and requires no outer RF parts. There is a for all intents and purposes unlimited wellspring of information open for the ESP8266, all of which has given by dazzling neighborhood. In the Documents fragment under you will find various resources for help you in using the ESP8266, even headings on the most capable strategy to changing this module into an IoT (Internet of Things) course of action.

The ESP8266 Module not fit for 5-3V rationale moving and will require an outside Logic Level Converter. Kindly don't control it straightforwardly from your 5V dev board. This new form of the ESP8266 Wi-Fi Module has expanded the glimmer circle size from 512k to 1MB. Highlights: 802.11 b/g/n Wi-Fi Direct (P2P), delicate AP Integrated TCP/IP convention stack Integrated TR switch, balun, LNA, power speaker and coordinating with network Integrated PLLs, controllers, DCXO and force the board units +19.5dBm yield power in 802.11b. ESP8266 when the gadget is mounted and as the solitary use of the application processor, the glimmer memory can began straightforwardly from an outside Move. Underlying reserve memory will help improve framework execution and diminish memory necessities.

The ESP8266 as shown in fig 4.15 profoundly incorporated chip, including recieving wire switch balun, power the board converter, so with negligible outer hardware, and incorporates front-end module, including the whole arrangement intended to limit the space involved by PCB. The framework is furnished with ESP8266 showed driving highlights are: energy saving VoIP rapidly switch between the rest/wake designs, with

low-power activity versatile radio inclination, front-end signal preparing capacities, investigating and radio frameworks. ESP8266 radio receiver mainly includes the following modules 2.4GHz receiver. 2.4GHz transmitter. High-speed clock generator and crystal oscillator. Real-time clock. Bias and regulators.




Fig: 4.15: WI-FI Module on circuit board.

This energy-effective development in three modes: dynamic mode, rest mode and profound rest mode type. At the point when ESP8266 utilizing top of the line power the board innovation and rationale frameworks to diminish trivial elements of the force transformation control rest examples and work modes, in rest mode, it devours not exactly the current 12uA, is associated, it burns-through less capacity to 1.0mW (DTIM = 3) or 0.5mW (DTIM = 10). Rest mode, just aligned continuous check and guard dog in working condition. Continuous clock can customized to wake ESP8266 inside a particular period time.

CPU can I-Bus, D-Bus and AHB interface to access the storage controller. Any one of these interfaces can apply for access to ROM or RAM cells, memory arbiter to determine the running order in the order of arrival.

SP8266 radio receiver mainly includes the following modules 2.4GHz receiver. 2.4GHz transmitter. High-speed clock generator and crystal oscillator. Real-time clock. Bias and regulators.

Power Management

(OFF): CHIP_PD pin is in a low power state. RTC failure

(DEEP_SLEEP): RTC open, different pieces of the chip are shut. RTC inside recuperation memory to save the essential Wi-Fi association data. (Rest): Only RTC running. Precious stone oscillator stops. Any piece of the wake (MAC, have, RTC clock) will make the wake of the chip. (WAKEUP): In this express, the framework from a rest state to begin (PWR) status. Precious stone oscillator and PLL are changed over empowered state.

(ON): High-speed clock can run, and shipped off each clock control register is empowered Modules. Every module, including the CPU, including the execution of moderately low-level clock gating. Clock Management High Frequency Clock.

ESP8266 on high recurrence clock is utilized to drive two T x and R x blender, which is produced by the interior oscillator and an outer oscillator. Outer Reference Requirements At 26MHz outside clock recurrence between 52MHz.

GSM MODULE

The GSM used here is SIM800L as shown in figure 4.16. TDMA (time division multiple access) is an innovation utilized in computerized cell phone correspondence to isolate each cell channel into three schedule openings to expand the measure of information that can be conveyed. TDMA (time division multiple access) is an innovation utilized in advanced cell phone correspondence to isolate each cell channel into three time allotments to expand the measure of information that can be conveyed. TDMA works by time-division multiplexing: conveying various messages (every one of which has its own schedule opening) at the same time on a solitary transporter as an unpredictable sign, and afterward recuperating the different signs at the less than desirable end. For TDMA, the transporter partitioned into three time allotments, every one of which serves one supporter. The data is broken into small information bundles, which communicated in coordinated rushes in the 30-megahertz range.




Fig: 4.16 GSM Module

TDMA can be executed consistently across both 800-and 1900-MHz organizations. Its progressive cell structure permits specialist organizations to build limit where request is most noteworthy, in high-use regions. TDMA applied in Digital-American Mobile Phone Service, Global System for Mobile interchanges, and Personal Digital Cellular (PDC). In any case, every one of these frameworks carries out TDMA in a to some degree unique and inconsistent way. TDMA previously indicated as a norm in EIA/TIA Interim Standard 54 (IS-54). IS-136, a developed rendition of IS-54, is the United States standard for TDMA for both the cell (850 MHz) and individual interchanges administrations (1.9 GHz) ranges. TDMA utilized for Digital Enhanced Cordless Telecommunications.

Code Division Multiple Access (CDMA):

The term CDMA alludes to any of a few conventions utilized in supposed second-age (2G) and third-age (3G) remote interchanges. As the term infers, CDMA is a type of multiplexing, which permits various signs to involve a solitary transmission channel, advancing the utilization of accessible data transfer capacity. The innovation utilized in super high-recurrence (UHF) cell phone frameworks in the 800-MHz and 1.9-GHz groups. CDMA utilizes Analog-to-computerized transformation (ADC) in blend with spread range innovation. Sound information initially digitized into paired components. The recurrence of the communicated signal made to differ as per a characterized design (code). It can be blocked simply by a recipient whose recurrence reaction modified with a similar code, so it follows precisely alongside the transmitter recurrence. There are trillions of conceivable

recurrence sequencing codes; this improves security and makes cloning troublesome. The CDMA channel is ostensibly 1.23 MHz wide. CDMA networks utilize a plan called delicate handoff, which limits signal separation as a handset passes starting with one cell then onto the next. The mix of advanced and spread-range modes upholds a few fold the number of signs per unit data transfer capacity as Analog modes. CDMA is viable with other cell advancements; this takes into account cross country meandering. The first CDMA standard, in any case called CDMA one and still ordinary in mobile phones in the U.S., offers a transmission speed of just up to 14.4 Kbps in its single channel structure and up to 115 Kbps in an eight-channel structure. CDMA2000 and wideband CDMA pass on data ordinarily speedier. Worldwide System for Mobile Communication The Global System for Mobile correspondence, as a rule called GSM, Telecommunications Standards Institute (ETSI) to portray conventions for second era (2G) advanced cell networks utilized by cell phones. The GSM standard created as a trade for original (1G) Analog cell organizations, and initially portrayed an advanced, circuit exchanged organization improved for full duplex voice communication. This was extended over the long run to incorporate information interchanges, first by circuit exchanged vehicle, at that point parcel information transport by means of GPRS (General Packet Radio Services) and EDGE (Enhanced Data rates for GSM Evolution or EGPRS). Further enhancements made when the 3GPP grew third era (3G) UMTS norms followed by fourth era (4G) LTE Advanced guidelines. "GSM" is a brand name possessed by the GSM Association.

As shown in figure 4.17 Wi-Fi module ESP8266 wired on a circuit board



Fig: 4.17: SIM800L on Circuit Board.

The pervasiveness of the GSM standard makes worldwide meandering extremely regular between Mobile telephone administrators, empowering supporters of utilization their telephones in numerous pieces of the world. GSM varies altogether from its archetypes in that both flagging and discourse channels are Digital call quality, which implies that it thought about Second Generation (2G) cell phone framework. This reality has additionally implied that information correspondence incorporated into the framework from third Generation Partnership Project (3GPP). GSM is a modernized wireless structure that is comprehensively used in Europe and various bits of the world. GSM uses an assortment of time division distinctive access (Time Division Multiple Access) and is the most extensively used of the three progressed far off telephone advancements (TDMA, GSM, and CDMA). GSM digitizes and packs information, at that point sends it down a channel with two different floods of client information, each time permitting space. It works at either the 900 MHz or 1800 MHz recurrence band. GSM is the true remote phone standard in Europe. A GSM network is made out of a few practical substances, whose capacities and interfaces determined. Figure 4.18 shows the design of a conventional GSM organization. The GSM organization can partitioned into three wide parts.




Fig: 4.18 GSM architecture

Versatile Station conveyed by the endorser. The Base Station Subsystem controls the radio connection with the Mobile Station. The Network Subsystem, the primary piece of which is the Mobile administrations Switching Center (MSC), plays out the exchanging of

calls between the versatile clients, and among portable and fixed organization clients. The MSC likewise handles the versatility the executives activities. The Mobile Station and the Base Station Subsystem convey across the Um interface, otherwise called the air interface or radio connection. The Base Station Subsystem talks with the Mobile organizations Switching Center across the An interface, GSM design Mobile Station The portable station (MS) comprises of the versatile gear (the terminal) and a brilliant card called the Subscriber Identity Module (SIM). The SIM gives individual portability, with the goal that the client can approach bought in administrations independent of a particular terminal. By embeddings the SIM card into another GSM terminal, the client can get calls at that terminal, settle on decisions from that terminal, and get other bought in administrations. The compact equipment strangely recognized by the International Mobile Equipment Identity (IMEI). The SIM card contains the International Mobile Subscriber Identity (IMSI) used to recognize the endorser of the framework, a mysterious key for verification, and other data. The IMEI and the IMSI are free, in this way permitting individual versatility. The SIM card may secured against unapproved use by a secret phrase or individual personality number. Base Station Subsystem The Base Station Subsystem is made out of two sections, the Base Transceiver Station (BTS) and the Base Station Controller (BSC). These convey across the normalized interface, permitting (as in the remainder of the framework) activity between segments made by various providers. The Base Transceiver Station houses the radio handsets that characterize a cell and handles the radio-connect conventions with the Mobile Station. In an enormous metropolitan territory, there will possibly be countless BTSs sent, in this manner the prerequisites for a BTS are roughness, unwavering quality, compactness, and least expense. The Base Station Controller deals with the radio assets for at least one BTS. It handles radio-channel arrangement, recurrence bouncing, and handovers. The BSC is the association between the portable station and the Mobile assistance Switching Center (MSC). Organization Subsystem The focal part of the Network Subsystem is the Mobile administrations Switching Center (MSC). It acts like an ordinary exchanging hub of the PSTN or ISDN, and furthermore gives all the usefulness expected to deal with a portable supporter, like enrollment, confirmation, area refreshing, handovers, and call directing to

a meandering endorser. The MSC gives the association with the fixed organizations (like the PSTN or ISDN).

Motioning between practical elements in the Network Subsystem utilizes Signaling System Number 7 (SS7), utilized for trunk motioning in ISDN and broadly utilized in current public organizations. The Home Location Register (HLR) and Visitor Location Register (VLR), alongside the MSC, give the call-coordinating and meandering capacities of GSM. The HLR contains all the authoritative data of every supporter enlisted in the relating GSM organization, alongside the current area of the portable. The area of the versatile is regularly as the flagging location of the VLR related with the portable station. There is sensibly one HLR per GSM organization, despite the fact that it might be executed as a dispersed information base. The Visitor Location Register (VLR) contains chosen authoritative data from the HLR, fundamental for call control and arrangement of the bought-in administrations, for every portable as of now situated in the geological territory constrained by the VLR. The geological region constrained by the MSC compares to that constrained by the VLR. Note that the MSC contains no data about specific portable stations - this data is put away in the GSM frequencies utilizing all throughout the planet: In North America, GSM works on the essential versatile correspondence groups 850 MHz and 1,900 MHz. In Canada, GSM-1900 is the essential band utilized in metropolitan regions with 850 as a reinforcement, and GSM-850 being the essential country band. In the United States, administrative prerequisites figure out which region can utilize which band.

GSM-1900 and GSM-850 are utilized in the vast majority of South and Central America, and both Ecuador and Panama use GSM-850 only (Note: Since November 2008, a Panamanian administrator has started to bring to the table GSM-1900 assistance). Venezuela and Brazil use GSM-850 and GSM-900/1800 blending the European and American groups. In Brazil, the 1,900 MHz band combined with 2,100 MHz to shape the IMT-consistent 2,100 MHz band for 3G administrations. The outcome is a combination of utilization in the Americas that expects explorers to affirm that the telephones they have are viable with the band of the organizations at their objections. Recurrence similarity

issues can kept away from through the utilization multi-band (tri-band or, particularly, quad-band) telephones.

RELAY

Transfer Relay is electromagnetic gadget, used to detach two circuits electrically and associate them attractively as demonstrated in figure 4.19. They are extremely valuable gadgets and permit one circuit to switch another while they are totally isolated. They regularly used to interface an electronic circuit (working at a low voltage) to an electrical circuit works at high voltage. For instance, a transfer can make a 5V DC battery circuit to switch a 230V AC mains circuit. Hence a little sensor circuit can drive, say, a fan or an electric bulb. Fig: 4.19 Relay A hand-off switch can isolated into two sections: info and yield. The data fragment has circle, makes alluring field when a little voltage from an electronic circuit applied to it. This voltage than called the functioning voltage. Regularly utilized transfers are accessible in various design of working voltages like 6V, 9V, 12V, 24V. The yield segment comprises of contactors, which associate or detach precisely.



Fig: 4.19 Relay

Essential exchange there are three contactors: Normally open (NO) Normally shut (NC) Common (COM). At no data express, the COM related with NC. At the point when the working voltage applied transfer curl will invigorated and the COM changes contact to

NO. Diverse transfer arrangements are accessible like SPST, SPDT, DPDT. Which have diverse number of changeover contacts. By using suitable mix of contactors, the electrical circuit can be turned on and off conditions.

WATER PUMP:

The siphoning of water is a fundamental and viable strategy, definitely more useful than scooping it up with one's hands or lifting it in a hand-held can. This is genuine whether the water drawn from a new source, moved to a required area, decontaminated, or utilized for water system, washing, or sewage treatment, or for emptying water from an unwanted area. Notwithstanding the result, the energy needed to siphon water as demonstrated in figure 4.20, is a very requesting segment of water utilization. Any remaining cycles depend on advantage either water diving from a higher rise or some compressed pipes framework. The old idea of the reservoir conduit took straightforward and expressive benefit of keeping up height of water for as long and far a distance as could really be expected. Accordingly, as water moves over huge spans, it holds a bigger segment of its likely energy by spending little bits of this energy streaming down a slight degree. A helpful reservoir conduit framework at last relies upon a new water source existing at a higher height than the area where the water can be useful. Gravity accomplishes practically everything. In any remaining examples, siphons are important.



Fig: 4.20: Water Pump

Water Pump another water source in a lower stream, stream, lake, or lake is as often as possible guided to higher ground for water framework, creatures, cooking, cleaning or various uses by individuals, who regularly need new water. This will purge for the most

part new water and the treatment of to a great extent polluted water allude interminably to siphoning. A loop siphon is a low lift siphon is made out of a cylinder, molded as a curl and mounted on a pivoting hub fueled by a motor or a creature fit for turning the hub around quickly. Because of the turn, water at that point got by the cylinder and siphoned upwards in the hose. The curl siphon, as many low lift siphons, generally utilized for water system purposes. As demonstrated in figure 4.21 Water engine wired on a circuit board

Fig: 4.21: Water siphon and hand-off on Circuit board The loop siphon worked as an option in contrast to the Archimedean screw. Not at all like the Archimedean screw, it can run on a level plane while the Archimedean screw moved at around 30. The curl siphon, fitted with an appropriate turning seal, can convey water to a more noteworthy stature, regularly 5-10m, over their release opening.

As shown in figure 4.21 Water motor wired on a circuit board




Fig: 4.21: Water pump and relay on Circuit board

Regardless of the rise of new siphons that work on different standards, the curl siphon stays a significant device as some of its different advantages are that they can be fabricated and fixed effectively at an extremely minimal effort. This is feasible for the segments can be worked from neighborhood assets as metal. Which can be acquired and project into the ideal structure without any problem. For any situation, as referred to already, the siphon simply allows the lifting of water over a little height. This makes it inadmissible for water waste or water framework over greater height contrasts or various other siphoning applications other than leakage and water framework. A winding siphon, now and again called a Wirtz siphon, a low lift siphon made out of a long piece of metal plating, which twisted into a loop and fixed at the top and back limits as to look like a chamber. The external cavity fills in as the gulf, while the internal (halfway) tube fills in as

the power source. A snaked plastic cylinder will get the job done for this plan. The power source pipe is fixed to a water wheel, motor or creature which equipped for turning the siphon rapidly. Because of this pivot, water got by the external depression and siphoned upwards in the house.

POWER SUPPLY

Force supply, 230V from the mains supply is venture somewhere near the transformer to 12V and took care of to a rectifier. The yield got from the rectifier is a throbbing D.C voltage. So to get an unadulterated D.C voltage, the yield voltage from the rectifier took care of to a channel to eliminate any A.C parts present even after correction. Presently, this voltage given to a voltage controller to get an unadulterated consistent dc voltage. The square outline of managed power supply. Power Supply Transformer Usually, DC voltages are needed to work different electronic gear and these voltages are 5V, 9V or 12V.




Fig: 4.22: Power Supply

The supply info open at the mains supply i.e., 230V is been brought down to the fundamental voltage level. This done by a transformer. Thus, a phase down transformer used to reduce the voltage to a vital level. Rectifier: The yield from the transformer took care of to the rectifier. It changes over A.C. into throbbing D.C. The rectifier might be a half wave or a full wave rectifier. In this undertaking, an extension rectifier utilized in light of its benefits like great strength and full wave correction. Channel: Capacitive channel

utilized in this task. It eliminates the waves from the yield of rectifier and smoothenes the D.C Yield got from this channel is predictable until the mains voltage and weight is cared for consistent. In any case, if both of the two is changed, D.C. voltage got now changes. A regulator applied at the yield stage. A voltage regulator is an electrical regulator arranged thus keep a predictable voltage level. In this endeavor, power supply of 5V and 12V are required To get these voltage levels, 7805 and 7812 voltage controllers are utilized. The primary number 78 addresses positive inventory and the numbers 05, 12 address the necessary yield voltage level. As demonstrated in figure 4.23 the battery for Power Supply wired on a circuit board Fig: 4.23: Power Supply Battery



Fig: 4.23: Power Supply Battery

4.6 Thing Speak Server/Cloud

Thing Speak Server / Cloud ThingSpeak is an IoT examination stage administration that permits you to total, imagine, and investigate live information streams in the cloud as demonstrated in figure 4.24 you can send data to ThingSpeak from your devices, create instant visualization of live data, and send alerts. ThingSpeak™ is an IoT investigation stage administration that permits you to total, envision, and dissect live information streams. When you send information to ThingSpeak from your gadgets, you

can make moment representations of live information without composing any code. With MATLAB® investigation inside ThingSpeak, you can compose and execute MATLAB code to perform further developed preprocessing, representations, and examinations. Begin with building your IoT frameworks without setting up workers or creating web programming. The Integration with The Things Network permits consistently advance information from The Things Network to ThingSpeak for investigation and perception.

ThingSpeak for Smart Farming

Smart Farming will be cultivating the executives that utilizes information advancements to improve the productivity and nature of ranch yield. ThingSpeak™ gives information ingestion and capacity to your agrarian sensors and controls. At that point you to utilize MATLAB® in ThingSpeak to assemble the calculations that make your homestead more intelligent.

- See moment perceptions of information posted by your gadgets or gear, for example, live soil dampness information or harvest heath data.
- Perform online examination and information preparing with live information, and see programmed perceptions.
- Construct Internet of Things (IoT) frameworks at your area without setting up workers or creating web programming.
- ThingSpeak enables you to work with agricultural data from devices such as weather stations and moisture sensors.

Communicate with ThingSpeak using:

- REST API
- MQTT API
- Third-party integrations, including The Things Network, Senet, and Libelium.

Features

- Build predictions with ThingSpeak as shown in fig 4.24 in the MATLAB interface. Use data from your own sensors (stored in private channels) or public data (stored in public channels) to generate predictions and visualizations. The Growing Degree Days Public ThingSpeak channel shows collect expectations for Corn planted in Natick MA, USA. When they made in ThingSpeak, you can share your investigation and representations
- ThingSpeak always runs the latest version of MATLAB, so you can process your cloud data in MATLAB.
- Access the most recent plots in MATLAB such as swarm plots, bubble charts, bubblechart3, and polar bubble charts.
- Use MATLAB in ThingSpeak to generate custom plots such as location, temperature, and soil moisture all on the same map.
- Access your data from the cloud to generate insights, or import data from other services and then trigger alerts.




Fig: 4.24: ThingSpeak

CHAPTER-5

RESULT AND DISCUSSION

5.1 Data Processed in Server

After setting up all the connection as for demonstration as shown in the figure 5.1 and the sensors sense the data and send the data to the server through Wi-Fi module as code embedded in the Arduino UNO functioning the data analysis graph shown in the server.




Fig: 5.1: Demonstration

The Data received by the sensors sent into the server. Connecting to the power supply the data been processed into the server. Graph analysis made in the ThingSpeak cloud.

5.2 IDEAL VIEW

The images shown below used for Ideal view showing the working and Data Processed in the server. The field with both dry and wet conditions were applied accordingly and data been processed. If any sudden change in climatic conditions and insufficient measures for the field for crop growth, SMS will be terminated to the user or farmer and if water management is taken care of the soil in the field.

IDEAL VIEW WITH WATER




Fig: 5.2: Ideal view with water

As shown in fig 5.2 when water observed and sufficient for the soil, the water motor will be in OFF condition.

IDEAL VIEW WITHOUT WATER



Fig: 5.3: Ideal view without water

As shown in fig 5.3 when the Insufficient water in the field the motor turns to ON condition.

5.3 OUTPUT ANALYSIS

The data in the ThingSpeak will have the generated data from the sensors. The graphs shows the date, time and values of Temperature, Humidity, Soil, LDR for smart irrigation. Hence this report useful for analysis and predictions for Farmers. The Fields in the Server were Temp, Humidity, Soil, LDR.

The link for the server as follows: <https://thingspeak.com/channels/1295896>




Fig: 5.4: Temperature Chart

As shown in fig 5.4 the graph of the temperature depends on the field and values displayed accordingly.




Fig: 5.5: Humidity Chart

As shown in fig 5.5 the graph of the Humidity depends on the field and values displayed accordingly.




Fig: 5.6: LDR Chart

As shown in fig 5.6 the graph of the LDR depends on the field and values displayed accordingly.




Fig: 5.7: Soil Chart

As shown in fig 5.7 the graph of the Soil sensor depends on the field and values displayed accordingly.

These, Fields will be push backed to ensure the data processed and get the new data accordingly.

CHAPTER-6

CONCLUSIONS AND FUTURE WORKS

6.1 CONCLUSION

In Conclusion, a data within the server is been pushed back so that it will be readily to take the new value to the chart. The Smart framing with Smart data and auto pumping of managing the Water and Alerting System through SMS mode is useful for the farmers or the user. The data been processed through Wi-Fi module is sent into the ThingSpeak server or cloud. It enhances the data and verifies it to the crop needed sources. If any high or of sudden changes in the field notices the limit and send an alert message to user. So needed certain measures were taken. The data processed in the chart of thingspeak server help for analysis and predictions accordingly to the seasonal crop growth. We hope that this novel surly inspire the Agriculture sector and help to sustainable development for the future generations.

6.2 FUTURE SCOPE

As, we all know the Agriculture is the backbone for Indian Economy. The future scope of this particularly inspire the people that they can process or take up the framing using this Smart techniques with IoT measures as it makes the things to work smarter and better. The Smart Framing will help for the farmers those you are lacking or busy in their daily needs can refer the land by their smartphone. This makes the productivity in maintaining the quality to the crop growth. The further modification that this can afford by making an Application of the data processed. That it is useful for illiteracy people. So, the data been processed and can enhance and have great impact to the smart innovations in large manner.

REFERENCES

- [1] Ahmed. N and Hussain. I, "Internet of Things (IoT) for smart precision agriculture and farming in rural areas," IEEE Internet Things J., vol. 5, no. 6, pp. 4890–4899, Dec. 2018.
- [2] Anand Nayyar and Vikram Puri," Smart Farming: IoT Based Smart Sensors Agriculture Stick for Live Temperature and Moisture Monitoring using Arduino, Cloud Computing & Solar Technology", November 2016.
- [3] Anusha. A, Guptha. A, Sivanageswar Rao, Ravi Kumar Tenali, "A Model for Smart Agriculture Using IOT", International Journal of Innovative Technology and Exploring Engineering (IJITEE), ISSN: 2278-3075, Volume-8 Issue-6, April 2019.
- [4] Brian Gilmore,"The Next Step in Internet Evolution: The Internet of Things", Internet of Things, cmswire, Jan 2014.
- [5] Brun-Laguna. K, Diedrichs. A. L, Chaar. J. E, Dujovne, Taffernaberry. J C, "A demo of the PEACH IoT-based frost event prediction system for precision agriculture," in Proc. 13th Annu. IEEE Int. Conf. Jun. 2016, pp. 1–3.
- [6] Karan kansara, PG Student, "Sensor based Automated Irrigation System with IOT [2015]".
- [7] Muthunoori Naresh, Munaswamy. P, "Smart Agriculture System using IoT Technology", International Journal of Recent Technology and Engineering (IJRTE), ISSN: 2277-3878, Volume-7 Issue-5, January 2019.
- [8] Nikesh Gondchawar, Prof. Dr. Kawitkar. J. C, "IOT based smart agriculture", International Journal of Advanced Research in Computer and Communication Engineering, Vol. 5, Issue 6, June 2016.
- [9] Pradyumna Gokhale, Omkar Bhat, Sagar Bhat,"Introduction to IOT", International Advanced Research Journal in Science, Engineering and Technology (IARJ SET), Vol. 5, Issue 1, January 2018.
- [10] Sweksha Goyal, Unnathi Mundra, Prof. Sahana Shetty," SMART AGRICULTURE USING IOT", International Journal of Computer Science and Mobile Computing, Vol.8 Issue.5, pg. 143-148, May 2019.