

AN EFFICIENT CNN FOR IDENTIFICATION OF COVID 19 USING X-RAY IMAGE

Submitted in partial fulfillment of the requirements for the award of

Bachelor of Engineering / Technology degree in Electronics and communication engineering

by

KAVERI .R (37130195)

GOWSALYA .G (37130147)



DEPARTMENT OF ELECTRONICS AND COMMUNICATION

ENGINEERING

SCHOOL OF ELECTRICAL AND ELECTRONICS

SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY (DEEMED TO BE UNIVERSITY)

Accredited with Grade "A" by NAAC 12B Status by UGC I Approved by AICTE

JEPPIAARNAGAR, RAJIV GANDHI SALAI,

CHENNAI-600119

March- 2021



SATHYABAMA
INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)
Accredited with "A" grade by NAAC
Jeppiaar Nagar, Rajiv Gandhi Salai, Chennai – 600 119
www.sathyabama.ac.in



DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING

BONAFIDECERTIFICATE

This is to certify that this Project Report is the bonafide work of **KAVERI .R (37130195), GOWSALYA.G (37130195)** who carried out the project entitled **AN EFFICIENT CNN FOR IDENTIFICATION OF COVID 19 USING X-RAY IMAGES** under my /our supervision from August 2020 to April 2021.

Internal Guide

(Mr.Muthaih)

Dr.T.RAVI,M.E,Ph.D

Head of the Department

Submitted for Viva-voce Examination held on_____

Internal Examiner

ExternalExaminer

DECLARATION


We **KAVERI.R (37130195)**, **GOWSALYA.G (37130147)** here by declare that the Project Report entitled **AN EFFICIENT CNN FOR IDENTIFICATION OF COVID 19 USING X-RAY IMAGES** done by me under the guidance of **Mr.(Muthiah)** at Sathyabama Institute of Science And Technology. **Chennai- 600119** is submitted in partial fulfillment of there quirements for the award of Bachelor of Engineering degree in Electronics and Communication Engineering.

DATE:


PLACE:

SIGNATUREOFTHECANDIDATE

1.

A rectangular box containing a handwritten signature in blue ink that reads "R. Kaveri".

2.

A rectangular box containing a handwritten signature in blue ink that reads "G. Gowsalya".

ACKNOWLEDGEMENT

We are pleased to acknowledge my sincere thanks to Board of Management of **SATHYABAMA** for their kind encouragement in doing this project and for completing it successfully .We are grateful to them.

We convey my thanks to **Dr. N .M . Nandhith , Dean, School of Electrical and Electronic Engineering** and **Dr.T.RAVI, Head of the Department, Dept. of Electrical and Electronic Engineering** for providing me necessary support and details at the right time during the progressive reviews.

We would like to express my sincere and deep sense of gratitude to our Internal guide **Mr. Muthiah** for his valuable guidance, suggestions and constant encouragement paved way for the successful completion of my project work. We wish to express my thanks to all Teaching and Non-teaching staff members of the Department of who were helpful in many ways for the completion of the project.

ABSTRACT

Covid-19 continues to own a devastating impact on the lives of individually everywhere the globe. It is important to screen the infected patients in a timely and cost-effective manner in order to combat this disease. CXR is that the initial imaging procedure that plays a very important role with in the diagnosis of COVID-19 sickness and is one amongst the only ways that to diagnose it. Convolutional neural networks (CNNs) for image recognition and classification have had a lot of success due to the abundance of large-scale annotated image datasets. The classification of the medical images is still the most difficult aspect of medical diagnosis.

TABLE OF CONTENT

CHAPTER NO	TITLE	PAGE NO
	List of figure	8
1	Introduction	9
2	Literature survey 2.1. Automatic COVID-19 Detection from X-Ray images using Ensemble Learning with Convolutional Neural Network 2.2. COVID-19 detection from CXR images using Deep Learning and Convolutional Neural Networks 2.3. Classification of COVID-19 in CXR images using DeTraC deep convolutional neural network 2.4. A combined deep CNN-LSTM network for the detection of novel corona virus (COVID-19) using X-ray images 2.5. Computer - aided detection in chest radiography based on artificial intelligence a survey	10-12
3	Aim	13
4	Material and methods: 4.1. Convolution neural network 4.1.1. Convolution 4.2.1. Convolution layer	15-25

	4.2.2.Pooling layer 4.2.3.Full Connected layer 4.2.4.RELU Layer 4.2.5.Softmax Layer 4.3.Data Generation 4.4.Pre-Trained Model 4.5.Block diagram 4.6.Darknet-19 Architectures description: 4.7.Darknet-19 architecture diagram: 4.8. The proposed DarkNet -19 model 4.9.Algorithm	
5	5.1.Result 5.2.Discussion	26-27
6	Conclusion	28

LIST OF FIGURES

FIGURE .NO	DESCRIPTION	PAGE NO
1	Convolution neural network	14
2	Convolution layer	15
3	Pooling layer	16
4	Full Connected Layer	16
5	RELU Layer	17
6	Soft max layer	17
7	Reference data set	18
8	Block diagram	19
9	Architecture darknet-19 neural network	21
10	A schematic presentation of convolution and max pooling layer operation	22
11	The architecture of the proposal model	23
12	Confusion matrix and ROX curve	24
13	Result	25

CHAPTER-1

1.INTRODUCTION:

In the first official case of Corona virus was discovered in Wuhan, China's largest metropolitan area and the province's capital. Thousands of people have died as a result of it, and there have been millions of cases registered all over the world. An pandemic outbreak has a destroying the effect on the global population's being. Then disease is known as corona virus disease 2019, the result is the corona virus Severe Acute Respiratory Syndrome. While it is similar to SARS and MERS, this corona virus is more virulent and destructive (2019-nCoV). This highly infectious virus spreads even more quickly than the normal flu virus. RTPCR (Reverse Transcription Polymerase Chain Reaction) genetic tests are now a days used to diagnose Covid-19 (RT-PCR). These equations are extremely precise. Even if the amount of virus in the patient sample is very small, the virus can be detected and calculated.

The PCR test, on the other hand, is extremely complicated, time-consuming, and expensive. As a result, not every medical facility is equipped to handle it. Because of these drawbacks, radiography scanning can be used as a stand-in for other methods of disease detection. The presence of, or symptoms of, the novel corona virus can be detected using chest radiography images. According to studies, viruses in this family have a major impact on radiographic pictures. As a result, radiographic scans, a CXR, are more accurate than PCR examinations while still being much faster and less expensive. Furthermore, CXRs are less costly and more readily available than other radiological tests such as CT scans. The only drawback to using x-rays to diagnose patients with Covid-19 is that qualified physicians, especially in rural areas, are not always available. Moreover, many scientists had never before seen a patient Covid-19 positive x-ray chest, so Covid-19 has a different and enigmatic radiological manifestation. For Covid19 +ve and -ve instances using CXR Ray images, we suggested a simple, low cost, deep learning technique.

In a matter of seconds this procedure allows Covid-19 positive patients to be detected with almost perfect precision. We have contributed a method for detecting supportive patients with Covid-19 as part of this study. And if a radiologist is not present or if physicians had different views, this approach to profound learning will have an opinion without human involvement. In this article, we used open-source data to demonstrate the effective rating accuracy and sensitivity of the proposed method. A lot of other things have since been applied.

CHAPTER-2

2.LITERATURE SURVEY:

2.1.AUTOMATIC COVID-19 DETECTION FROM X-RAY IMAGES USING ENSEMBLE LEARNING WITH CONVOLUTIONAL NEURAL NETWORK

This article proposes to use CXR to recognize the use of a Deep Convolution Neural Networking method for the Covid-19 +ve patients. We have taken public CXR images from both Covid-19 +ve case and -ve cases to measure the feasibility of the approach. The particular number of trainable images and particular number research images were made using the particular images of Covid +ve patients and number images of Covid -ve patients. The aim of this research was to create a straightforward and cheap method for the detection of Covid+ CXR patients.

Three levels of the art profound learning method are implemented are put together in the study discussed in this article. The classification precision of the proposed model is 95.7 percent. More impressive is its 98% sensitivity, that is, 98% of patients are detected in Covid + V. Patients. 98 of them will be correctly diagnosed using the model we have suggested. This study, together with the GUI app, could enable doctors to use computer-aided analysis to diagnose the patients affected in seconds. This will have an important impact on the industry.

2.2.COVID-19 DETECTION FROM CXR IMAGES USING DEEP LEARNING AND CONVOLUTIONAL NEURAL NETWORK

This physiology explains an analysis to find positive COVID-19 patients which in the first half of 2020 affected a much are of the human population. The thesis introduced and used well-known Convolution Neural Networks for classification (CNNs). Since the COVID class is so sensitive, precise, and reliable, these models can accurately detect the category COVID-19 events which limit the spread of the virus as far as possible. COVID-19.

In deciding the best model for the classification task, the findings show many efficiency indicators. Moreover, the appreciable results in the potential for the aforesaid Network to attain large amount of sensitivity and precision. This implies in the ordinary category that false positive effects are minimized in illness classes, which will reduce the pressure on the health care system. Finally, we would like to emphasize that without consulting the practitioner these approaches cannot be used. In future, we are planning to train CNNetwork on additional information and explore many COVID-19 detection architectures.

2.3.CLASSIFICATION OF COVID-19 IN CXR IMAGES DETRACT DEEP CONVOLUTIONAL NEURAL NETWORK

The CXR is the old imaging procedure essential for the diagnosis of COVID-19. Because of the vast number of annotated image data sets, neural networks (CNN) have been effective for image identification and classification. However, the naming of the media is attributable to the lack of annotated medical photos. Transfer learning can be a viable alternative for sharing the knowledge .

For the difference of COVID-19 CXR images we validate and adapt a deep CNN is know as DeTraC. Investing in DeTraC will address any anomalies in the image dataset. The tests showed DeTraC's capability of distinguishing COVID-19 disease from a large amount of CXT dataset from multiple hospitals worldwide. COVID-19 photographs from normal to extreme acute respiratory syndrome have been observed with an accuracy of 95,12 per cent. Finally, model cutting and quantizing would be used to improve efficiently and it will be easy to carry the method.

2.4.A COMBINED DEEP CNN-LSTM NETWORK FOR THE DETECTION OF NOVEL CORONO VIRUS(COVID-19)USING X-RAY IMAGES

As a result of accelerated population growth, pre programmed disease identification will become a major topic of clinical investigation. An automatic illness identification framework helps physicians in the diagnosis of diseases by producing precise, consistent and quick outcomes while reducing mortality levels. Corona virus (COVID-19) in the last few years has become one of the world's most severe acute and dangerous diseases. An automatic detection system may also be used as the quickest diagnostic tool in order to prevent dissemination of COVID-19. Our aims at implementing of the deep learning methodology using in the CNNetwork and a LSTM to find COVID-19 from radiation depiction (LSTM). CNNetwork is used in the deep functionality of this system. 4,575 images including 1525 COVID-19 image, were included in the data set for this method. According to the experimental findings, the methodology we have presented was 99.4% accurate, AUC 99.9% accurate, 99.2% accurate, 99.3% sensitive and F1 98.9%. There are a few inconveniences of the current system. In order to evaluate the method's generalizability, the sample size is initially small and must be expanded. This will be resolved if there are further pictures in the next few days. Second, the X-ray view is just investigated posterior (PA) and is not distinguishable from other X-ray views such as a lateral (AP) and so forth. Finally, the COVID-19 photos contain them.

2.5.COMPUTER-AIDED DETECTION IN CHEST RADIOGRAPHY BASED ON ARTIFICIAL INTELLIGENCE A SURVEY

Many common CXR datasets have been displayed and general image preparation strategies, including contrast enhancement and segmentation, and bone suppression techniques, have been briefly explored in chest radiography. The function of the CAD-system is then discussed in the detection of particular diseases (pulmonary nodules, TB, interstitial pulmonary diseases) and multiple conditions, with a focus on pulmonary nodules, tuberculosis and interstitial lung diseases. The paper further addresses recent issues and progress in chest radiography using a method built on artificial intelligence. The CAD scheme has four stages: algorithms, extraction of ROI areas, extraction of the ROI functions and the classification of diseases depending on the characteristics.

Enhancement techniques are used for pre-processing algorithms and extracting ROI. While bone control techniques in the literature are less common, removing the belt and clavicle that hinder lung anomalies can make the device function more effectively. Traditional machine learning algorithms derive properties of geometrics, texture and form ,which then minimize dimensionality by their complexity. In the other hand, hand-made features are gradually being phased out in favor of deep learning methods that include mistakes affecting classification precision. While the performance of the support vector and altered forest can be superior for classifier selection in conventional algorithms, deep learning approaches are being employed more and more because of their superior image classification performance.

Traditional machine learning algorithms derive properties of geometrics, texture and form, which then minimize dimensionality by their complexity. In the other hand, hand-made features are gradually being phased out in favor of deep learning methods that include mistakes affecting classification precision. While the performance of the support vector and altered forest can be superior for classifier selection in conventional algorithms, deep learning approaches are being employed more and more because of their superior image classification performance.

CHAPTER–3

3.1.AIM:

For COVID-19 control due to their high transmissibility, early identification of the corona virus is critical. The diagnostic diagnosis of corona virus by gene sequencing should be verified as the primary reverse transcription indicator for respiratory or blood samples according to Chinese government guidelines. Chain reaction of polymerase, polymerase, polymerase-polymerase- (RT-PCR).

The RT-PC treatment takes 4–6 hours to complete, unlike the fast spread rate of COVID-19. Not only are RT-PCR test kits inefficient, they are still not readily available. As a consequence, often infected people go untreated for a long time and unwittingly infect others. Radiological images as X-rays can be used to diagnose COVID-19 infections in this modeling process.

Various approaches to finding the COVID-19 by using CXR images have been demonstrated by many researchers. As a consequence, often infected people go untreated for a long time and unwittingly infect others. Radiological images as X-rays can be used to diagnose COVID-19 infections in this modeling process. Several investigators have shown different detection methods of X-ray images using COVID-19.

CHAPTER-4:

4.MATERIAL AND METHOD:

Our research approach CXR image, dark net 19 transfer learning and extraction features are all part of convolution neural networks. The subsequent chapters would then be further clarified.

4.1.CONVOLUTIONAL NEURAL NETWORKS:

It is a form of deep organization, and most often used to study visual symbolization in this network. These are also known as spatially invariant fake neural organisations. These programmes are used to process images, to recommend structures, characterise images, divide images, to analyse images in clinics, to manage characteristic languages and to schedule time. It has its own unique features integrated and optimized throughout its evolution. They still have some special characteristics that are more simple and peculiar, in contrast to computer education which is part of artificial intelligence. It controls its own features and even blocks noise on its own. It examines its own features and also removes noise by itself. Each part of the input is also deleted from the corresponding register. For instance, the human body is divided into an input that separates the muscles, the bones and the blood from each layer.





Fig 1. CONVOLUTIONAL NEURAL NETWORK

4.1.1.Convolution:

Convolution is an orderly procedure where two sources of information are intertwined; it's an operation that changes a function into something else. Convolutions have been used for a long time typically in image processing to blur and sharpen images, but also to perform other operations. (e.g. enhance

edges and emboss) CNNs enforce a local connectivity pattern between neurons of adjacent layers.



CNNs make use of filters (also known as kernels), to detect what features, such as edges, are present throughout an image. There are four main operations in a CNN:

- Convolution
- Non Linearity (ReLU)
- Pooling or Sub Sampling
- Classification (Fully Connected Layer)


The first layer of a Convolutional Neural Network is always a **Convolutional Layer**. Convolutional layers apply a convolution operation to the input, passing the result to the next layer. A convolution converts all the pixels in its receptive field into a single value. For example, if you would apply a convolution to an image, you will be decreasing the image size as well as bringing all the information in the field together into a single pixel. The final output of the convolutional layer is a vector. Based on the type of problem we need to solve and on the kind of features we are looking to learn, we can use different kinds of convolutions.

4.2.LAYERS OF CNN:

4.2.1.CONVOLUTIONAL LAYER:

It consists of several filters, and the basic building block of a convolutionary network. The network has filters that can be used in order to detect a feature from the data set in the input.


Fig 2 Convolution layer



4.2.2.POOLING LAYER:

The following layer at Cnn is the layer of pooling that has the indirect kind. There are some indirect capabilities that can be used to perform complete pooling. The data base is an exposed array on each sub-site, which produces the most drastic effects.


Fig 3 POOLING LAYER:



4.2.3.FULLY CONNECTED LAYER:

The last sheet in a standard grid is the absolutely connected to the layer; the undeniable neural system is carried out across entirely connected layers. Neurons are completely connected levels, as in traditional non-constructive neural organisations, and are related to the last layer of action. They are stored, beginning with network replication and ending with a counterbalance of predisposition.


Fig 4:



4.2.4.RELU LAYER:

This layer is the truncation of the right segment which has initial function. It effectively eliminates false qualities from initiation by setting it to zero. Develops non-linear optional power and general organization properties without disrupting sensitive fields of the convolution layer.


Fig 5



4.2.5.SOFTMAX LAYER:

Softmax's work is a capability that transforms a K-value vector into a K-value vector, up to 1. The annexation of softmax is consequently natural as the final neural structure layer.

Fig 6 SOFTMAX LAYER



4.3. DATA AND GENERATION:

X-rays were collected and made accessible on the web from a variety of open sources. For the analysis, data were analysed for confirmed COVID-19 cases, viral pneume (except COVID-19) infections, and 'healthy' cases. Neural networks Convolution is used to solve the problems of classification and design, and achieved the aim of the analysis. The algorithm must be incredibly accurate, since people's lives are online. The evidence in the studies included cases of COVID-19, viral pneumonia and healthy human beings. The compilation of data has been prepared and double-checked with the assistance of chest experts. Finally, case studies are suitable for the COVID-19 cases obtained. The x-ray files have been resized to a resolution of 256 256. CNN tends to overlook minor spatial changes. It looked for similarities in movements as well as picture locations in particular. This data set was divided into two sections: training (70%) and validation (30%), with a training set for classification and a valide set for the best performance selection. X-rays were collected and made accessible on the web from a variety of open source



(a)

Fig 7: Reference image Data set

(a) Covid Positive

(b) Covid Negative


4.4.PRE-TRAINED MODEL:

In this analysis, which was applied using ImageNet data, a technique of transfer learning was employed to overcome insufficient data and preparation time. For each model, you downloaded the ImageNet trained weights. In the applied layer training method, the function maps are used in the initial size. In addition, of convolution base performed extremely well, as it will perform on the minimum data and it derived functionality as an input was used. As a result, the CNNs used for automatic detection were provided for fine tuning. a brief summary. The CNN was used for the different set of performance and transferring knowing parameters . Following multiple experiments of that parameters were calculated. There were endless opportunities and future research might examine how they led to increased efficiency. Layer frozen corresponds to the amount of unworkable layers that start at the bottom of the CNNetwork, which will be good then they were unable to modify their weight due to the model preparation. Then the boot end characteristics are derived from the latest activating characteristic of the pre-trained model, that can be perform into a fully connected deep neural network classification system. Then other layers will be closest to that display wherever ready to receive

additional input from late coevolutionary layers. The rectified linear unit allowed all of the convolution layers (ReLU). A drop-out layer was introduced to avoid overlap of neural networks in convolution of two hidden layers.

4.5.BLOCK DIAGRAM:

Fig 8



4.6.DARKNET-19 ARCHITECTURE DESCRIPTION:

See the architecture and operation of YOLO 2 and YOLO 3. The neural network architecture of Darknet-19 is used for extracting features from object representations in YOLO 2. The network

contains 19 convergence layers, as well as 5 max pooling layers, an approximate global max pooling layer and soft max layer. Mainly Dark network-19 uses three convolution filter. In Darknet-19 an average global pooling layer is placed opposite the soft max layer, rather than fully linked layers. This is a strictly convolutions layer in a convolution neural network system. It can be used without altering any configuration on images of varying resolutions. For regularization, convergence and stabilization preparation, Dark network 19 and YOLO 2 use batch standardization. Darknet-19 has been educated in ImageNet 306 data across six epochs. In the planning process, the writers employed conventional techniques to expand the collection of training examples artificially. It will increased the resolution tomore data set and trained the network after their testing in pictures with a resolution of 224224 for 6 epochs. The developers of [20] updated Darknet-19 in order to resolve the detection issue by eliminating the ultimate convolution layer.

Three coalescing layers with 1024 filters and a 3 3 scale coefficient are applied. The final coagulation layer with the coatings size 11 and the number of outputs required to detect and classify NC groups is then applied. Artifacts small in proportion to the scale of the image are difficult to identify, since convolutionary layers decrease the dimensions of the characteristic charts across time. This combines the output of the 13th convolutionary layer with the output of layer 20 with a feed into the input of layer 21 that makes it possible for the model to use fine grain characteristics.

The input image will be separated into a grid of SS cells before it is transferred to network input. YOLO 2, the location of the bounding boxes is as it does not predict the anchor boxes will be displaced in each cell of SS. The k-means approach is used to create anchor boxes before training begins depend up on the training data collection. The network forecasts the following for each anchor box: The space and location of the anchor box and the one cell with B as number of anchor boxes is given with B values .During the YOLO 2 training session, the resolution of the images can shift randomly. This purpose allows the detection of artifacts of various sizes.

In 32-point increments, the scale may be modified. The soft max function in YOLO 2 calculates the likelihoods of classes. The chances are added on both. Class labels would not be in harmony with. Soft max layer is used under the basically have only one class is used for each bounding box. YOLO 3 forecasts multiple classes for every bounding box using individual logistic classifiers. This is how the sorting of several labels is done.


This approach makes data modeling more accurate. For each mark, a binary cross entropy is used

to calculate losses. The calculation load is minimized by this method. The box is predicted to use logistic regression in the presence of an entity for any border. As one of the bounding boxes (boxes overlap more than the other box), the object value is 1. the object value. If a certain limit value is reached by the overlap of other anchor boxes, these forecasts are not used .The 3-scale predictions are made in YOLO 3 using the same principle as that employed in the work of the FPN (functional pyramid network). Different sizes can be obtained by reducing the input image sampling dimensions to 32, 16 and 8 respectively. The function maps are sampled twice on two scales after projections. Therefore, previous maps are concatenated with characteristics of the same size. This allows the simultaneous use of both low- and high-level functions.

The outcomes of the 3 scales are to be controlled using the no limit deletion methods. The algorithm for clusters k-means is used as in the case of YOLO 2, to construct anchor boxes. There are nine rectangles divided into three according to their height. YOLO 3 uses Dark net 53, which has 53 convolution layers, to isolate and classify features. It consists of 33 and 11 layers and blocks which allow the result values of the previous layers to be combined with the output from the current layer. This technique can be used in deep neural networks to address the issue of the disappearance.

4.7.DARKNET-19 ARCHITECTURE DIAGRAM:

Fig 9:



ARCHITECTURE OF DARKNET-19 MODEL

4.8. THE DARKNET-19 MODEL:

Artificial intelligence has been transformed with the introduction of profound learning technologies. The term deep refers to a network growing in scale with increasing layer numbers. Convolution is the math operator named after the form. A standard CNN configuration comprises a convolution layer, which removes input characteristics from the filters it uses. It also contains a pooling layer, which

decreases computer function and a completely linked layer, in a neural network. In order to fulfil a mission, such as classification or object identification, the internal parameters of a model CNN are modified by integrating one or more of these layers. A more realistic approach consists of a product architecture using already validated models, instead of using a deep model construction from scratch. The Darknet-19 model[59] has therefore been selected as its starting point for the deep model used in this analysis. The real-time object identification system for YOLO (Your Just Look Once) is built on the concept classification of Darknet-19. The latest object detection technology is incorporated into this computer.

This powerful architecture uses the Dark Net classifier. We have developed the Dark Covid Net architecture made by the Dark Net organisation that has proved them self to be profoundly learning instead of creating a scratch model. We used fewer layers and filters than in the original Dark Net architectures. From eight to sixteen to thirty-two filters, we gradually increased the number. Study the fundamentals of the Darknet-19, which uses Max pool to build 19 convolution layers and five pooling layers, to gain a deeper understanding of this new architecture. There are fundamental CNN layers of filter numbers, sizes and stride values. The letter C is a convolutionary node, the letter P represents a layer of Max pool. The two-dimensional converting operation can be described as follows for input signal X (image) and kernel .

Use the step Parameter to slide the Kernel matrix into the input table. The rectified linear device Leaky ReLu is used in the DarkNet Architecture as an access function. Equation is used to calculate the leaky ReLu function .

The outputs of the model are regulated by the Avgpool and Softmax layers. Finally, if we need to develop the process in the real-time object detection system, a deep model with maximum number of layers is required. In this thesis the photographs with subtle details have become difficult to distinguish. Rather than being really profound it should have a mechanism that can catch and learn small distinctions, such as ResNets or ResNext[60]. This proposed model used in this analysis. There are 17 layers of convolution in the proposed model. The ex pool process, analogous to the trained model, is used for every grouping function. Max pool limits the size of an input by taking a filter-defined area limit. The model suggested covers two classes and carries out the identification mission COVID-19. When there are three distinct image categories used in the input, the classification of the data entering panel labels such as COVID-19, Pneumonia or No-Findings is performed using that same model..




Fig. 9 A schematic presentation of convolution and max pooling layer operation




Fig 10 The architecture of the proposed model (DarkCovidNet).

4.9.Algorithm:

Step 1: Start

Step 2: Load initial input image file name

Step 3: Initial preprocessing

Step 4: Run the code

Step 5: Convolutional matrix

Step 6: In result it will classify the image and give the accuracy

Step 7: Calculate sensitivity and specificity

Fig 11

Confusion Matrix and ROC Curve

		Predicted Class	
		No	Yes
Observed Class	No	TN	FP
	Yes	FN	TP

TN True Negative
FP False Positive
FN False Negative
TP True Positive

Model Performance

Accuracy $= (TN+TP)/(TN+FP+FN+TP)$

Precision $= TP/(FP+TP)$

Sensitivity $= TP/(TP+FN)$


Specificity $= TN/(TN+FP)$


CHAPTER-5:

5.1.RESULT:

The findings were obtained by looking at the photographs and using Darknet-19 for our tests for COVID-19 classification, and the results reached the highest mean specificity rates.

Fig 12:





5.2.DISCUSSION:

As CNNs, various approaches can be used. In situations where many annotational images are required, we can use an end-to-end network. On the other hand, transfer training is usually an effective solution where annotated photographs are scarce because it translates information that can be obtained from the pre-trained CNNs to specific medical imaging missions. Shallow-tuning, sophistication and deep-tuning are three distinct types of learning transfers. However, data abnormalities, particularly in medical imaging applications, continue to be a difficult issue, resulting in miscalibration between the dataset's different groups. In order to detect COVID-20 cases from CXR-based images, CNNs will provide an ease and the reliability solution to track disease transmission.

In a COVID-19 dataset, deep convolutionary neural networks use the advantages of CNN class decomposition to address inconsistencies in image classification. In order to verify the modulate darknet-19, we use a COVID data package with unbalanced classes (including 306 COVID-19+v, -ve cases). Darknet-19 achieved high precision of 90.13 percent with a pre-trained Image data CNN model, proving that it is effective with actual CXR images.

The CNN templates we used in some type of Experimental studies have shown great precision in the case of COVID-19, which are used with all pre-trained models trained in deep tuning. In particular, darknet-19 showed significant changes in comparison with pre-trained models without the decomposition of the class. At last, that research indicates that a decomposition of the layer within the pre-trained CNN Image model is needed for transfer learning.

CHAPTER-6:

6.1.CONCLUSION:

For doctors and patients, the ability to diagnose the covid 19 thoroughly CXR images is critical to minimise the time and expense of the procedure. Deep learning can identify pictures of the activities taught. In this research, COVID-19 was detected in CXR images with great precision with ConvNets by several experiments. Different groups of COVID-19 +ve and -ve. Different picture lengths, network architectures, cutting-edge pretrained networks and models of dark net 19 were applied and analysed using images and statistical evidence. If Covid take into consideration the number of images in this data base and the detection time of COVID-19

It can be inferred that the architectures being considered reduce computer costs while keeping them highly efficient. The findings showed that COVID-19 images can also be identified within two-class COVID-19 + ve -ve classification ranges with high precision 97 percent, across a neuronal network that has minimised convolutionary and fully connected layers. More analysis will include the many information can get from the CNN with the COVID-19 X-ray chest images and improve the conclusions on the basis of the results of this report.

REFERENCES:

1. Rubin, G. D., Ryerson, C. J., Haramati, L. B.; et al. The Role of Chest Imaging in Patient Management during the COVID-19 Pandemic: A Multinational Consensus Statement from the Fleischner Society [published online ahead of print, 2020 Apr 7]. Chest. 2020, S0012-3692, 30673-30675. doi:[10.1016/j.chest.2020.04.003](https://doi.org/10.1016/j.chest.2020.04.003).
[Google Scholar](#) | [Crossref](#)
2. Ozsahin, I., Sekeroglu, B., Mok, G. S. P. The Use of Back Propagation Neural Networks and 18F-Florbetapir PET for Early Detection of Alzheimer's Disease Using Alzheimer's Disease Neuroimaging Initiative Database. PLoS One. 2019, 14, e0226577.
[Google Scholar](#) | [Crossref](#) | [Medline](#)
3. Dai, S., Li, L., Li, Z. Modeling Vehicle Interactions via Modified LSTM Models for Trajectory Prediction. IEEE Access. 2019, 7, 38287–38296.
[Google Scholar](#) | [Crossref](#)
4. Yilmaz, N., Sekeroglu, B. Student Performance Classification Using Artificial Intelligence Techniques. In: 10th International Conference on Theory and Application of Soft Computing Computing with Words and Perceptions (ICSCCW) [2019]. Adv. Intel Sys. Comm. 2019, 1095, 596-603.

[Google Scholar](#)

5. Meng, C., Zhao, X. Webcam-Based Eye Movement Analysis Using CNN. IEEE Access. 2017, 5, 19581–19587. doi:[10.1109/ACCESS.2017.2754299](#).

[Google Scholar](#) | [Crossref](#)

6. Deng, X., Zhang, Y., Yang, S.; et al. Joint Hand Detection and Rotation Estimation Using CNN. IEEE Trans. Image Proc. 2018, 27, 1888–1900, doi:[10.1109/TIP.2017.2779600](#).

[Google Scholar](#) | [Crossref](#) | [Medline](#)

7. LeCun, Y., Haffner, P., Bottou, L.; et al. Object Recognition with Gradient-Based Learning: Shape, Contour and Grouping in Computer Vision. Lect. Notes Comput. Sci. 1999, 1681, 319–345.

[Google Scholar](#) | [Crossref](#)

8. Roy, S. K., Krishna, G., Dubey, S. R.; et al. HybridSN: Exploring 3-D–2-D CNN Feature Hierarchy for Hyperspectral Image Classification. IEEE Geosci. Remote. Sens. Lett. 2020, 17, 277–281.

[Google Scholar](#) | [Crossref](#)

9. Hartenstein, A., Lübke, F., Baur, A. D. J.; et al. Prostate Cancer Nodal Staging: Using Deep Learning to Predict 68Ga-PSMA-Positivity from CT Imaging Alone. Sci. Rep. 2020, 10, 3398.

[Google Scholar](#) | [Crossref](#) | [Medline](#)

10. Yoon, H., Lee, J., Oh, J. E.; et al. Tumor Identification in Colorectal Histology Images Using a Convolutional Neural Network. J. Digit. Imaging. 2018, 32, 131–140.

[Google Scholar](#) | [Crossref](#)

11. Simonyan, K., Zisserman, A. Very Deep Convolutional Networks for Large-Scale Image Recognition. ArXiv. 2015, arXiv:14091556.

[Google Scholar](#)

12. Kaiming, H., Xiangyu, Z., Shaoqing, R.; et al. Deep Residual Learning for Image Recognition. ArXiv. 2015, arXiv:1512.03385.

[Google Scholar](#)

13. Szegedy, C., Vanhoucke, V., Ioffe, S.; et al. Rethinking the Inception Architecture for Computer Vision. ArXiv. 2015, arXiv:1512.00567v3.

[Google Scholar](#)

14. Howard, A. G., Zhu, M., Chen, B.; et al. MobileNets: Efficient Convolutional Neural Networks for Mobile Vision Applications. ArXiv. 2015, arXiv:1704.0486.

[Google Scholar](#)

15. Huang, G., Liu, Z., van der Maaten, L.; et al. Densely Connected Convolutional Networks. ArXiv. 2018, arXiv:1608.06993v5.

[Google Scholar](#)

16. Cohen, J. P. COVID-19 Image Data Collection. ArXiv. 2020, arXiv:2003.11597.

[Google Scholar](#)

17. <https://github.com/ieee8023/covid-chestxray-dataset>.

[Google Scholar](#)

18. Kermany, D. S., Goldbaum, M., Cai, W.; et al. Identifying Medical Diagnoses and Treatable Diseases by Image-Based Deep Learning. Cell. 2018, 172, 1122–1131.

[Google Scholar](#) | [Crossref](#) | [Medline](#)

19. Haralick, R., Shapiro, L. Computer and Robot Vision, Vol. 1. Addison-Wesley: Reading (MA), 1992; pp 346–351.

[Google Scholar](#)

20. Melo, F . Area under the ROC Curve. In: Dubitzky, W.; Wolkenhauer, O.; Cho, K. H.; Yokota, H. (eds.), Encyclopedia of Systems Biology. Springer: New York, 2013.

[Google Scholar](#) | [Crossref](#)

21. Sun, Y., Wang, B., Jin, J.; et al. Deep Convolutional Network Method for Automatic Sleep Stage Classification Based on Neurophysiological Signals. In: 2018 11th International Congress on Image and Signal Processing, BioMedical Engineering and Informatics (CISP-BMEI), Beijing, China, 2018; pp 1–5. doi:[10.1109/CISP-BMEI.2018.8633058](https://doi.org/10.1109/CISP-BMEI.2018.8633058).

[Google Scholar](#) | [Crossref](#)

22. Refaeilzadeh, P., Tang, L., Liu, H. Cross-Validation . In: Liu, L., Özsu, M. T. (eds.), Encyclopedia of Database Systems. Springer: Boston, 2009.
[Google Scholar](#)
23. Yang, T., Kan, P., Lin, C.; et al. Using Polar Expression Features and Nonlinear Machine Learning Classifier for Automated Parkinson's Disease Screening. IEEE Sensors J. 2020, 20, 501-514. doi:[10.1109/JSEN.2019.2940694](#).
[Google Scholar](#) | [Crossref](#)
24. Xiang, W., Ran, H., Zhenan, S.; et al. A Light CNN for Deep Face Representation with Noisy Labels. IEEE Trans. Info. Forens. Sec. 2018, 13, 1. doi:[10.1109/TIFS.2018.2833032](#).
[Google Scholar](#) | [Crossref](#)
25. Hong, Z., Yun, Z. A Normalized Light CNN for Face Recognition. J. Phys. Conf. Ser. 2018, 1087, 062015. doi:[10.1088/1742-6596/1087/6/062015](#).
[Google Scholar](#) | [Crossref](#)
26. Yang, Z., Li, D. WasNet: A Neural Network-Based Garbage Collection Management System. IEEE Access. 2020, 8, 103984–103993. doi:[10.1109/ACCESS.2020.2999678](#).
[Google Scholar](#) | [Crossref](#)

plagiarism report

ORIGINALITY REPORT

4%

SIMILARITY INDEX

2%

INTERNET SOURCES

4%

PUBLICATIONS

1%

STUDENT PAPERS

PRIMARY SOURCES

1

Tulin Ozturk, Muhammed Talo, Eylul Azra Yildirim, Ulas Baran Baloglu, Ozal Yildirim, U. Rajendra Acharya. "Automated detection of COVID-19 cases using deep neural networks with X-ray images", Computers in Biology and Medicine, 2020

Publication

2%

2

github.com

Internet Source

1%

3

[ijmtst.com](https://www.ijmtst.com)

Internet Source

1%

4

www.researchsquare.com

Internet Source

1%

5

Amit Kumar Das, Sayantani Ghosh, Samiruddin Thunder, Rohit Dutta, Sachin Agarwal, Amlan Chakrabarti. "Automatic COVID-19 detection from X-ray images using ensemble learning with convolutional neural network", Pattern Analysis and Applications, 2021

Publication

<1%
