

OBJECT DETECTION AND GESTURE CONTROL OF FOUR-WHEEL MOBILE ROBOT

Submitted in partial fulfillment of the requirements for the award of Bachelor of
Engineering Degree in
Electronics and Communication Engineering

by

TADIBOINA MANI VENKATA SAI KUMAR
(37130403)

TADIBOINA SAI GOWTHAM
(37130404)



**DEPARTMENT OF ELECTRONICS AND COMMUNICATION
ENGINEERING SCHOOL OF ELECTRICAL AND ELECTRONICS**

SATHYABAMA

**INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)**

Accredited with Grade "A" by NAAC

JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI - 600 119

APRIL - 2021



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)

Accredited with "A" grade by NAAC
Jeppiaar Nagar, Rajiv Gandhi Salai, Chennai - 600 119
www.sathyabama.ac.in



DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of TADIBOINA MANI VENKATA SAI KUMAR (37130403), TADIBOINA SAI GOWTHAM(37130404) who carried out the project entitled "OBJECT DETECTION AND GESTURE CONTROL OF FOUR-WHEEL MOBILE ROBOT " under our supervision from November 2020 to April 2021.

Internal Guide

Mrs.K.SRILATHA.,M.E.,(Ph.D).,

Head of the Department

Dr. T.RAVI.,M.E.,Ph.D.,

Submitted for Viva voce Examination heldon_____

Internal Examiner

External Examiner

DECLARATION

We TADIBOINA MANI VENKATA SAI KUMAR and TADIBOINA SAI GOWTHAM here by declare that the Project Report entitled “OBJECT DETECTION AND GESTURE CONTROL OF FOUR-WHEEL MOBILE ROBOT” done by us under the guidance of Mrs.K.SRILATHA,M.E.,(Ph.D)., Assistant Professor, Department of Electronics and Communication Engineering is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in ELECTRONICS AND COMMUNICATION ENGINEERING.

DATE:
PLACE: CHENNAI

SIGNATURE OF THE CANDIDATE

1.

2.

.

ACKNOWLEDGEMENT

We are pleased to acknowledge our sincere thanks to Board of Management of SATHYABAMA for their kind encouragement in doing this project and for completing it successfully. We are grateful to them.

We convey thanks to Dr.N.M.NANDHITHA.,M.E.,Ph.D., Dean, School of ELECTRICAL AND ELECTRONICS and Dr.T.RAVI.,M.E.,Ph.D., Head of the Department, Dept. of Electronics and Communication Engineering for providing me necessary support and details at the right time during the progressive reviews.

We would like to express our sincere and deep sense of gratitude to our Project Guide Mrs.K.SRILATHA.,M.E.,(Ph.D)., Assistant Professor, Dept of Electronics and Communication Engineering for her valuable guidance, suggestions and constant encouragement paved way for the successful completion of us project work.

We wish to express our thanks to all Teaching and Non-teaching staff members of the Department of Electronics and Communication Engineering who were helpful in many ways for the completion of the project.

ABSTRACT

Gestures may come from any bodily motion or condition, but they most commonly come from the face or the hand. Emotion recognition from a face or hand gesture recognition are two of the field's current hot topics. A camera finds the human body's movements and sends the recorded data to a computer in gesture recognition. The computer then uses this information as input to run applications.. Gesture recognition may also be referred to as gesture control.

Hand gestures are a strong interhuman communication modality; they can also be considered an intuitive and practical means of communication between humans and machines. This explains why the research community is so interested in the creation and advancement of hand gesture technologies.

Unique capabilities of a good natural user interface is the ability to identify hand movements in real time. Computers can understand human body language with the aid of gesture recognition. Rather than using simple text or graphical user interfaces, this helps to create a more powerful bond between humans and machines (GUIs).

INDEX

CHAPTER NUMBER	TITLE	PAGE NO
	ABSTRACT	v
	LIST OF FIGURES	viii
	LIST OF TABLES	viii
	INTRODUCTION	
1	1.1 EXISTING SYSTEM	1
	1.2 PROPOSED SYSTEM	2
	REQUIREMENTS	
2	2.1 SOFTWARE UNIT BLOCK DIAGRAM	3
	2.2 HARDWARE UNIT BLOCK DIAGRAM	4
	2.3 HARDWARE UNIT REQUIREMENTS	5
	2.4 SOFTWARE UNIT REQUIREMENTS	5
	MODULE DESCRIPTION HARDWARE UNIT	
3	3.1 POWER SUPPLY UNIT	6
	3.2 ARDUION UNO	10
	3.3 RELAY	14
	3.4 DC MOTOR	19
	3.5 ULTRA SONIC SENSOR	24
	3.6 UART	27
	3.7 BUZZER	31
	LITERATURE SURVEY	36
4	SOFTWARE DESCRIPTION	
5	5.1 EMBEDDED C	41
	5.2 ADVANTAGES	42
	5.3 DIFFERENCE BETWEEN C AND EMBEDDED C	46
	5.4 MATLAB	46
	5.5 USES OF MATLAB	48
	5.6 DIGITAL IMAGE PROCESSING	48
	5.7 WORKING	48
	5.8 SIGNAL PROCESSING	48
	5.9 ANALOG IMAGE PROCESSING	49
	5.10 OVERLAPPING FIELDS	49
	5.11 ARTIFICIAL INTELLIGENCE	50
	5.12 SIGNALS	50
	5.13 COMPUTER KEY BOARD	51
	5.14 DIFFERENCE BETWEEN ANALOG AND DIGITAL SIGNALS	52
	5.15 SYSTEMS	53
6	RESULTS AND DISCUSSION	56

7	CONCLUSION	61
8	REFERENCES	62

LIST OF FIGURES

FIGURE NUMBER	FIGURE NAME	PAGE NUMBER
2.1	SOFTWARE UNIT BLOCK DIAGRAM	3
2.2	HARDWARE UNIT BLOCK DIAGRAM	4
3.1	POWER SUPPLY UNIT	6
3.1.1	STEPDOWN TRANSFORMER	7
3.1.2	BRIDGE RECTIFIER	7
3.1.3	FILTER CIRCUIT	8
3.1.4.1	REGULATOR	9
3.1.4.2	POWER SUPPLY CIRCUIT	10
3.2.1	ARDUINO ARCHITECTURE	11
3.2.2	ARDUINO PIN DIAGRAM	11
3.3	RELAY	14
3.3.1	RELAY OPERATION	16
3.3.1.2	DE-ENERGIZED RELAY(OFF)	17
3.4.1	MOTOR CONSTRUCTION	21
3.5.5	MODULE OPERATING PRINCIPLE	27
3.6.3	TTL LEVEL UART	29
3.7	BUZZER	32
3.7.1	BUZZER CIRCUIT	32
3.7.2	PIEZO BUZZER	34
3.7.2.2	MAGNETIC BUZZER	34
5.7.1	PROCESSING OF IMAGE	48
5.10.2	COMPUTER GRAPHICS	50
5.12.1	ANALOG SIGNALS	51
5.19	LINE FOLLOWER ROBOT	55

LIST OF TABLES

TABLE NUMBER	TABLE NAME	PAGE NUMBER
3.6.3	VOLTAGE LEVEL FOR TTL LEVEL UART	29
3.6.4	VOLTAGE LEVEL FOR RS-232	30
3.6.4	PINOUTS AND DESCRIPTION OF A SERIAL PORT	31
5.15	DIFFERENCE BETWEEN ANALOG AND DIGITAL SIGNALS	52

CHAPTER 1

INTRODUCTION

In this proposed work we have implemented the gesture controlled home automation using MATLAB simulation software through the microcontroller. Taking in concern the day today challenges in the world with growing technologies in normal life, the following proposed work was create

The problem of disability is gaining more and more importance all over the world. At the time there is a network of Non governmental Organisations working for the development of persons with physical disabilities. Therefore providing solution for the inabilities is the prime motto of this work. Gesture plays a major role in this proposed work. A gesture is a form of non-vocal communication in that human body actions can be able to communicate the particular speech or communication or even messages.

Gestures are movements of the hands, lips, or other body parts. Individuals may use gestures to express a different range of emotions and thoughts, from disdain and animosity to acceptance and love.

Other applications that could be managed by gestures include media and navigation. Players, remote controls, and robots, for example. Gesture recognition is the statistical process of recognising a person's gestures. translation of a human movement by a registering device. In different words, interface with PCs or other hardware utilizing offers of the human body, typically hand developments. In the motion acknowledgment innovation, a camera peruses the movements of the human body and conveys the data to a computer that uses the gestures as a input to control devices or applications.

Now a days, automation and advancement in the system is implemented everywhere. All the automobile industries are working to compete with the others. Also there is much more advancement in technologies, which are commonly available in the vehicles.

The offices gave the vehicles like self-start, auto-gear, battery chargers, remote controls, and so forth are usually given every one of the vehicles. Everyone uses his own vehicle for travelling and transportation as there is a vast development in the nearby areas of the cities. The road accidents in metropolitan areas as well as in countryside areas have increased to an uncertain level due to these developments. The system can also be implemented for the rescue of the accident victims. Many issues like arrival of ambulance, the investigations made by the police department and operating the victim by the hospitals can be minimized by implementing the proposed system in every vehicle, including two wheelers and three wheelers.

1.1 EXISTING SYSTEM:

Existing framework follow the limit based picture division. This acknowledgment technique normally requires the area of the signaling hands or the beginning and end casings of each motion. Requiring such contribution to be accessible is regularly unrealistic,thus making it hard to convey signal acknowledgment frameworks in some genuine universes cenarios.

1.1.1 DISADVANTAGES:

In characteristic settings, hand areas can be uncertain within the sight of messiness, foundation movement, and the presence of others or skin-hued objects. Signals regularly show up inside a consistent stream of movement and consequently recognizing where a signal beginnings and finishes is a difficult issue

In this venture we present a strong and successful strategy for hand division by Super pixel grouping. First we utilized the movement location of super pixels and solo picture division to recognize the moving objective hand utilizing the initial not many casings of the info video arrangement.

At that point the hand appearance model is developed from its encompassing super pixels. By fusing the disappointment recuperation and layout coordinating in the following cycle, the objective hand is divided by a super pixel based order calculation. Here, MALAB unit is utilized to perceive the client finger to check the number. In view of raising of fingers demonstrate the robot will move. It is utilized to control equipment apparatuses like fan, light and engine moreover. In the event that the First finger raised, the robot will push ahead. On the off chance that subsequent robot will move invert, for third finger robot will turn left and for fourth robot will turn right and for fifth the robot will get stop. The Ultrasonic sensor is utilized to recognize the hindrances in the street.

1.1.2 ADVANTAGES:

- Overcomes problems such as skin color detection, complex background removal, complexity from multiple gesturers in front of the camera and variable lighting condition.
- Fast and accurate method than existing method.

CHAPTER-2

2.1 BLOCK DIAGRAM: SOFTWARE UNIT





Fig:2.1 block diagram software unit

2.2 BLOCK DIAGRAM: HARDWARE UNIT



RECEIVER UNIT



Fig:2.2 block diagram hardware unit

2.3 HARDWARE REQUIREMENTS:

- Power Supply Unit
- Arduino uno
- Ultrasonic sensor
- Relay
- Motor
- Buzzer

2.4 SOFTWARE REQUIREMENTS:

- Matlab
- Arduino IDE
- Embedded

CHAPTER-3

MODULE DESCRIPTION

HARDWARE UNIT

3.1 POWER SUPPLY UNIT:

The expression "power supply" alludes to a wellspring of electrical energy. A force supply unit, or PSU, is a gadget or framework that gives electrical or different types of energy to a yield burden or gathering of burdens. The term is most regularly applied to electrical energy supplies, less frequently to mechanical ones, and seldom to other people.




Fig 3.1. Power Supply unit

3.1.1 STEP DOWN TRANSFORMER

The term is most generally used to depict electrical fuel sources, with mechanical fuel sources being utilized less regularly and others being utilized just sporadically. Fig. 3.1.1 Unit of Power Supply 3.1.1 DOWNTRANSFORMER Phase Power supply is significant. The essential twisting of the information power transformer is associated with the mains (line) supply. To deliver an AC volt, an optional winding that is electromagnetically coupled yet electrically isolated from the principle is used.of reasonable adequacy, and after additional handling by the PSU, to drive the hardware circuit it is to supply.

The transformer stage should have the option to supply the current required. In the event that too little a transformer is utilized, all things considered, the force supply's capacity to keep up full yield voltage at full yield current will be weakened. With too little a transformer, the misfortunes will increment significantly as full burden is set on the transformer. As the transformer is probably going to be the most expensive thing in the force supply unit, cautious thought should be given to offsetting cost with

likely current necessity. There may also be a need for safety devices such as thermal fuses to disconnect the transformer if overheating occurs, and electrical isolation between primary and secondary windings, for electrical safety.




Fig 3.1.1 Step down Transformer

3.1.2 THE RECTIFIER STAGE

The AC input is changed over to DC utilizing the rectifier circuit. The full wave connect rectifier disposes of the requirement for a middle tapped transformer by utilizing four diodes in an extension circuit to give full wave correction. Moreover, since two diodes are leading simultaneously, the diodes just need a large portion of the converse breakdown voltage limit of diodes utilized for a large portion of the time. the turn around breakdown voltage capacity of diodes utilized for half and ordinary full wave amendment. The scaffold rectifier can be worked from independent diodes or a joined extension rectifier can be utilized.

It can be seen that on each half cycle, opposite pairs of diodes conduct, but the current through the load remains in the same polarity for both half cycles.




Fig 3.1.2 Bridge Rectifier

3.1.3 FILTER:

A typical power supply filter circuit can be best understood by dividing the circuit into two parts, the reservoir capacitor and

The low pass filter each of these parts contributes to removing the remaining AC pulses, but in different ways.

Electrolytic capacitor utilized as a repository capacitor, alleged in light of the fact that it goes about as a The force supply yield current is incidentally put away. On each progression of the info wave, the rectifier diode gives current to charge a repository capacitor. The supply capacitor in many mains recurrence PSUs is a major electrolytic capacitor with an estimation of a few hundred or even at least 1,000 microfarads. The repository capacitor requires a capacitance of this extent, when charged, should give sufficient DC to keep a consistent PSU yield without an info current; for example during the holes between the positive half cycles when the rectifier isn't directing.

Electrolytic capacitor utilized as a repository capacitor, alleged in light of the fact that it goes about as a The force supply yield current is incidentally put away. On each progression of the info wave, the rectifier diode gives current to charge a repository capacitor. The supply capacitor in many mains recurrence PSUs is a major electrolytic capacitor with an estimation of a few hundred or even at least 1,000 microfarads. The repository capacitor requires a capacitance of this extent, when charged, should give sufficient DC to keep a consistent PSU yield without an info current; for example during the holes between the positive half cycles when the rectifier isn't directing

Of course, despite its large value, the reservoir capacitor discharges as it supplies the load, and its voltage drops slightly. The rectifier input voltage increases above the voltage on the partially discharged capacitor over the next step of the mains input, and the reservoir is re-charged to the peak




Fig 3.1.3 Filter Circuit

3.1.4 VOLTAGE REGULATOR

The output voltages of voltage regulator ICs may be fixed or variable. They're also ranked according to how much current they can handle. Negative voltage regulators are available, primarily

for dual supply applications. Most regulators provide some kind of automatic defence against excessive current and voltage and overheating.

The LM78XX arrangement of three terminal controllers is accessible with They can be utilized in a wide assortment of utilizations since they have many fixed yield voltages. One of these is neighborhood on-card control, which kills the appropriation gives that solitary point guideline causes. These controllers can be utilized in rationale frameworks, instrumentation, Hi-Fi, and other strong state electronic gear due to the voltages accessible. Albeit planned fundamentally as fixed voltage controllers, these gadgets can be utilized with outer parts to get flexible voltages and current.

1. Positive regulator

1. Input pin
2. Ground pin
3. Output pin

2. It regulates the positive voltage

3. Negative regulator

4. Ground pin
5. Input pin
6. Output pin

It regulates the negative voltage. The regulated DC output is very smooth with no ripple. It is suitable for all electronic circuits.




Fig 3.1.4.1 Regulator Circuit




Fig 3.1.4.2 Power Supply Circuit

3.2 ARDUINO UNO

An Arduino is really a microcontroller based unit which can be either utilized straightforwardly by buying from the merchant or can be made at home utilizing the segments, attributable to its open source equipment include. It is essentially utilized in correspondences and in controlling or working numerous gadgets. It was established by Massimo Banzi and David Cuartielles in 2005.

The Arduino Uno is a microcontroller board a board dependent on the ATmega328 microcontroller. There are 14 computerized input/output pins (six of which can be utilized as PWM yields), six simple information sources, a 16 MHz gem oscillator, a USB connect, a force jack, an ICSP header, and a reset button on this board.

It accompanies all you'll require to begin with the microcontroller; basically plug it into a gadget with a USB link or force it with an AC-to-DC connector or battery. The Uno is extraordinary in that it doesn't utilize the FTDI USB-to-chronic driver chip utilized on past sheets. All things considered, it utilizes an Atmega8U2 that has been customized to go about as a USB-to-sequential converter. The name "Uno" comes from the Italian word "uno," which signifies "one." It was picked to celebrate the forthcoming arrival of Arduino 1.0. Going ahead, the Uno and adaptation 1.0 will be the reference forms of Arduino.


The Uno is the latest in a series of USB Arduino boards, and the reference model for the Arduino platform; for a comparison with previous versions.

3.2.1 ARDUINO ARCHITECTURE:


Arduino's processor essentially utilizes the Harvard engineering where the program code and the program information is put away in its own memory. There are two recollections in it: the program memory and the information memory. The information is put away in the information memory, while the code is put away in the glimmer program memory. The ATmega328 has 32 KB of flash memory for storing code (0.5 KB of which is used for the bootloader), 2 KB of RAM, and 2 KB of flash memory for the bootloader.

With a clock speed of 16MHz, it has 1 KB of SRAM and 1 KB of EEPROM.

The main advantage of Arduino is that projects can be straightforwardly stacked onto the PC without the requirement for an equipment developer. This is because of the incorporation of a 0.5KB Bootloader, which empowers the program to race to be carved into the circuit. All we need to do now is download the Arduino program and begin composing the code.



3.2.2 ARDUINO PIN DIAGRAM



A 16 MHz crystal oscillator, 14 digital input/output pins (of which 6 can be used as PWM outputs), 6 analogue inputs, a USB link, a power jack, an ICSP header, and a reset button are all found on the Arduino Uno.

3.2.3 POWER JACK

Arduino can be power either from the pc through a USB or through outside source like connector or a battery. It can work on an outer stock of 7 to 12V. Force can be applied remotely through the pin Vin or by giving voltage reference through the IO Ref pin.

The Arduino Uno can be driven either by USB or an outside power supply. The force source is naturally picked. An AC-to-DC connector (divider mole) or a battery can give outside (non-USB) power. TheConnecting the connector is pretty much as straightforward as connecting it. The board can be controlled by an outside power supply Voltage goes from 6 to 20 voltsIf under 7V is provided, the 5V pin can supply under five volts, making the board precarious. The voltage controller may overheat and harm the board if more than 12V is utilized. 7 to 12 volts is the suggested range.

3.2.4 DIGITAL INPUTS

It has 14 digital input/output pins, each of which can supply or consume 40mA of current. Some of them have unique features, such as pins 0 and 1, which serve as Rx and Tx, respectively. Pins 2 and 3 are external interrupts, and pins 2 and 3 are for serial communication. PWM output is provided by pins 3, 5, 6, 9, 11, and LED is connected to pin 13.

3.2.5 ANALOG INPUTS:

It has 6 analog input/output pins, each providing a resolution of 10 bits.

AREF

It provides reference to the analog inputs

RESET

It resets the microcontroller when low

5 STEPS TO PROGRAM AN ARDUINO

Programs written in Arduino are known as sketches. A basic sketch consists of 3 parts

1. Declaration of Variables
2. Initialization: It is written in the setup () function.

3. Control code: It is written in the loop () function.

The sketch is saved with .in augmentation. Any tasks like checking, opening a sketch, saving a sketch should be possible utilizing the catches on the toolbar or utilizing the instrument menu. The sketch ought to be put away in the sketchbook catalog. Picked the legitimate board from the apparatuses menu and the sequential port numbers. Snap on the transfer button or picked transfer from the instruments menu. In this manner the code is transferred by the bootloader onto the microcontroller

BASIC ADRUINO FUNCTIONS

- **digitalRead(pin):** Reads the digital value at the given pin.
- **digitalWrite(pin, value):** Writes the digital value to the given pin.
- **pinMode(pin, mode):** Sets the pin to input or output mode.
- **analogRead(pin):** Reads and returns the value.
- **analogWrite(pin, value):** Writes the value to that pin.
- **serial.begin(baud rate):** Sets the beginning of serial communication by setting the bit rate.

FEATURES

It is cheap It accompanies an open source equipment highlight which empowers clients to build up their own unit utilizing effectively accessible one as a kind of perspective source.

The Arduino programming is viable with a wide range of working frameworks like Windows, Linux, and Macintosh and so on

It additionally accompanies open source programming highlight which empowers experienced programming designers to utilize the Arduino code to converge with the current programming language libraries and can be stretched out and modified. It is not difficult to use for beginners. We can build up an Arduino based undertaking which can be totally remain solitary or tasks which include direct correspondence with the product stacked in the computer. It accompanies a simple arrangement of associating with the CPU of the PC utilizing sequential correspondence over USB as it contains worked in force and reset hardware.

3.3 RELAY

We know that most high-end industrial application devices rely on relays to function properly. Relays are basic switches that can be regulated electrically or mechanically. A relay is made up of two parts: an electromagnet and a series of contacts. The electromagnet is used to carry out the switching mechanism. In addition, there are certain standards of operation and its operation. But they differ according to their applications. Most of the devices have the application of relays.



mechanism. In addition, there are certain standards of operation and its operation. But they differ according to their applications. Most of the devices have the application of relays.

They do, however, vary in terms of their implementations.

Relays are used in almost all of the units. 14 A relay's main function is to operate a circuit using only a low-power signal. In addition, it is

At the point when just one sign can handle an enormous number of circuits, this sort of sign is utilized.. The utilization of transfers traces all the way back to the development of phones. They were vital in the exchanging of brings in phone trades. Significant distance telecommunication was likewise conceivable with them. They were utilized to change the sign from one source to another.a distinctive



area They were additionally used to perform assignments after the creation of computers.Logic activities like Boolean and others. The very good quality uses of transfers require high ability to be driven by electric engines, etc. Such transfers are called contactors.

3.3.1 RELAY BASICS

The rudiments for every one of the transfers are something very similar. Investigate a 4 – pin transfer appeared underneath. There are two tones appeared. The control circuit is addressed by green, while the heap circuit is addressed by red. The control circuit is connected to a little control curl. The heap is associated with a switch. The curl in the switch controls this switch circuit of

control Let's gander at the different advances that happen during a transfer.




Fig:3.3.1relay operation

3.3.1.1 ENERGIZED RELAY (ON)

The current moving through the loops characterized by pins 1 and 3 makes an attractive field, as found in the circuit. The pins 2 and 4 close because of the attractive field. Thus, the switch is basic to the transfer's activity. Since it is a segment of the credit It is utilized to work an electrical circuit that is associated with it through a circuit. Therefore, when in an empowered relay the current stream will be through the pins 2 and 4.




Fig:3.3.1.2 Energized Relay (ON)

3.3.1.2 DE – ENERGIZED RELAY (OFF)

The switch opens when the current flow through pins 1 and 3 ceases, and the open circuit prevents current flow through pins 2 and 4. As a result, the relay is de-energized and in the off place.





Fig:3.3.1.2 De-Energized Relay (OFF)

Basically, when a voltage is applied to stick 1, the electromagnet enacts, making an attractive field that closes pins 2 and 4, bringing about a shut circuit. There is no voltage on nail 1 when there is no voltage to stick 2. There would be no electromagnetic energy, and no attractive field accordingly. Subsequently, the switches stay set up reachable.

3.2.2 WORKING PRINCIPLE



The chart shows an internal segment graph of a hand-off. A control curl is circled by an iron heart. The force source is given to the electromagnet through a control switch and contacts to the heap, as appeared. The electromagnet 17 empowers and in this way strengthens the attractive field as current

moves through the control loop. Accordingly, the upper contact arm is attracted to the lower fixed arm, shutting the contacts and causing a short out

for the stock of energy to the heap If the hand-off, then again, has effectively been de-empowered, T was shut when the contacts were shut, at that point the contact move oppositely and make an open circuit.

At the point when the curl current is turned off, a power returns the mobile armature to its unique area. The force of this power would be almost a large portion of that of the attractive power. Two components are principally liable for this power. They are the spring and gravity, respectively. Relays are generally utilized for two capacities. One is low voltage application and the High voltage is the other choice. For low voltage applications, more inclination will be given to decrease the clamor of the entire circuit. . For low-voltage applications, a more prominent accentuation will be set on diminishing in general circuit commotion. They are essentially intended to lessen the event of arcing in high-voltage applications.

FEATURES:

- They are quick acting and can be reset fast.
- They are simple in construction.
- They are reliable.
- The values can be easily set. No special programming device is required.
- People can be trained on these relays easily
-

3.2.3 RELAY APPLICATIONS

- Relays are used to realize logic functions. They play a very important role in providing safety critical logic.
- Relays are used to provide time delay functions. They are used to time the delay open and delay close of contacts.
- Relays are used to control high voltage circuits with the help of low voltage signals. Similarly they are used to control high current circuits with the help of low current signals.
- They are also used as protective relays. By this function all the faults during transmission and reception can be detected and isolated.
- Relay Drive by Means of a Transistor

- Relay Drive by Means of SCR
- Relay Drive from External Contacts
- LED Series and Parallel Connections
- Electronic Circuit Drive by Means of a Relay
- Power Source Circuit
- PC Board Design Considerations.

3.3 DC MOTOR


A DC engine is an electrical machine that changes direct flow electrical energy into mechanical energy. The most well known sorts rely upon the powers delivered by the environment. fields of attraction Since they could be fueled by a battery, DC engines were quick to be normally utilized. Force conveyance frameworks for direct-current lighting are as of now set up.

The speed of a DC engine can be shifted over a wide reach by changing the inventory voltage or changing the current force in the field windings. Apparatuses, toys, and machines all utilization little DC engines. The general engine can run on either immediate or exchanging current. However, it is a little engine that is utilized in convenient force apparatuses and machines. Bigger DC engines are utilized in electric vehicle impetus, lift and crane drives, and steel moving plant drives. The presentation of force gadgets has delivered DC engines obsolete. Many applications are conceivable with AC engines.

The stator of a basic DC engine contains a fixed assortment of magnets, and the armature contains at least one windings of protected wire folded over a delicate iron center, which focuses the attractive field. Much of the time, the windings have various pivots the center, and now and again, the windings have different pivots the core. motors that are enormous Several equal current ways are conceivable. The wire-closes wrapping's are wired into a commutator

. The commutator energises each armature coil in turn and uses brushes to connect the rotating coils to the external power supply. (Electronics in brushless DC motors convert DC current to AC current.) There are no brushes and each coil can be turned on and off.)

3.3.1 PRINCIPLE OF DC MOTOR



A component that changes electric energy into mechanical energy is known as an electric DC engine. A DC engine works on the possibility that when a current-conveying conductor is mounted in an attractive field, it produces an attractive field.

It is exposed to a mechanical power. The - hand Rule decides the course of mechanical power. F B I L Newton computes its extent. There is no principal differentiation between the two. the structure of a DC generator and a DC engine. Truth be told, a similar D.C. machine can be utilized conversely as a generator or as an engine. Like generators DC engines are additionally arranged in to shunt-wound, arrangement wound and compound-injury.

A wire loop with a flow moving through it delivers an electric field that is related with the curl's base. With the bearing and size of the current moving through the loop, the course and size of the attractive field shaped by the curl might be altered. Since all electric inventory organizations have substituting flow, DC engines are only here and there utilized in ordinary applications. However, for explicit applications, for example, steel plants, mines, and electric trains, changing exchanging flow over to coordinate flow and utilizing dc engines is ideal. The clarification for this is that d.c. engines have much better speed/force characteristics. superior to the yield of a.c. engines accordingly, it's obvious to discover that for modern Drives and d.c. engines are just about as well known as 3D printers.- stage acceptance engines.




Figure 8 - Motor Construction

A machine which transforms the DC power into mechanical power is called as a DC motor. Its operation relies on the principle that once a current carrying conductor is placed in a very magnetic field, the conductor experiences a mechanical force. The direction of this force is given by [Fleming's left hand rule](#) and magnitude is given by;

$$F = BIl \text{ Newton's}$$

Fundamentally, there's no constructional distinction between a DC motor and a DC generator. The same DC motor will be run as a generator or motor.

It is based on the idea that when a current-carrying conductor is put in a magnetic field, it is subjected to a mechanical force whose direction is determined by

Force, $F = B I l$ newton

Where B is the magnetic field in weber/m².

I is the current in amperes and


l is the length of the coil in meter.

The force, current and the magnetic field are all in different directions.

3.3.2 WORKING OF DC MOTOR

Consider a part of a multipolar d.c. motor as shown in Figure below.

Currents are carried by the armature conductors. Under an N-pole, all conductors carry current in one direction, while under an S-pole, all conductors carry current in the opposite direction.



Accept that the N-shaft conductors carry flows into the plane of the paper and the S-post conductors do flows of the plane of the paper, as demonstrated in Figure. Since every armature conductor is a current conductor, As it is placed in an attractive field, it is exposed to mechanical power. With regards to applying each The conductor tends to pivot the armature counterclockwise. The armature conductors convey flows. The two conductors beneath the N-post convey current one way, while those underneath the S-shaft convey current the other way. Expect that the conductors beneath the N-shaft carry flows into the plane of the paper and those underneath the S-post do flows of the plane of the paper out of the paper's plane, as portrayed in Fig. Since every armature conductor is special, It is mounted inside a current-conveying unit. he attractive field, mechanical power follows up on that. Expressing to the Fig and applying Fleming's left hand rule, obviously power on each conductor is having a tendency to pivot the armature anticlockwise way. Every one of these powers add along to give a driving twist that sets the armature pivoting.

3.3.3 BRUSHED DC ELECTRIC MOTOR

Inward recompense, fixed magnets (lasting or electromagnets), and turning electrical magnets are utilized in the brushed DC electric engine to create force straightforwardly from DC power provided to the engine. A brushed DC engine has numerous benefits, including a low introductory expense, high dependability, and simple speed control. High support and a short life expectancy for extreme focus utilizes are detriments. Upkeep incorporates routinely changing the carbon brushes and springs which convey the electric flow, just as cleaning or supplanting the commutate. These segments are needed for communicating electrical force from an external perspective of the engine to the rotor's turning wire windings. Conductors make up brushes.

3.3.4 BRUSHLESS DC ELECTRIC MOTOR

Brushless DC engines generally have a couple of perpetual magnets in the rotor and electromagnets for the stator on the engine packaging. An engine regulator is a gadget that changes DC over to AC. Since it eliminates the difficulty of 22 sending power from outside the engine to the turning rotor, this plan is precisely less difficult than brushed engines. The rotor's position can be recognized by the engine controller. via through Hall impact sensors or comparable gadgets, and can unequivocally screen the circumstance, stage, and different qualities of the current in the rotor loops to expand force, save power,

manage speed, and even apply braking. Brushless engines have a long life expectancy, need practically zero upkeep, and hush up. solid adequacy High starting expenses and more mind boggling engine speed regulators are disadvantages. While brushless engines needn't bother with an outside power supply to be synchronized, they are regularly alluded to as "coordinated motors." in the instance of standard AC simultaneous engines

3.3.5 ELECTROMAGNETIC MOTORS

The aggregate sum of current shipped off the curl, the loop's size and what it's folded over direct the strength of the electromagnetic field made.

The request in which a loop is turned on or off decides the heading where the compelling electromagnetic fields are coordinated. A pivoting attractive field can be framed by consecutively turning on and off loops. The attractive field collaborates with these turning attractive fields. Magnet fields (perpetual or electromagnets) in the engine's fixed part (stator) to make a power on the armature which makes it pivot. In some DC engine plans the stator fields use electromagnets to make their attractive fields which permit more prominent power over the engine.

In the event that outside power is applied to a DC engine it goes about as a DC generator, a dynamo When a half breed vehicle or electric vehicle eases back down, this capacity is utilized to re-energize the batteries, or to return energy to the electric framework utilized on a road vehicle or electric fueled train line. On half breed and electric vehicles, this is known as regenerative slowing down. Diesel electric trains utilize their DC engines as generators to diminish speed while scattering steam. in resistor stacks. Fresher plans are adding enormous battery packs to recover a portion of this energy.

3.3.6 APPLICATIONS OF DC MOTORS

3.3.6.1 D.C SHUNT MOTORS

It is a constant speed motor. Where the speed is required to remain almost constant from no-load to full load. Where the load has to be driven at a number of speeds and any one of which is nearly constant.

3.3.6.2 INDUSTRIAL USE:

- Lathes
- Drills
- Boring mills
- Shapers
- Spinning and weaving machines.

3.3.6.3 D.C SERIES MOTOR:

It is a variable speed motor. The speed is low at high torque. At light or no load ,the motor speed attains dangerously high speed. The motor has a high starting torque.(elevators, electric traction)

3.3.6.4 INDUSTRIAL USES:

- Electric traction
- Cranes
- Elevators
- Air compressor
- Vacuum cleaner
- Hair drier
- Sewing machine

3.3.6.5 D.C COMPOUND MOTOR:

Differential compound motors are rarely used because of its poor torque characteristics.

Industrial uses:

- Presses Shears
- Reciprocating machine.

3.5 ULTRASONIC SENSOR

At the point when the ultrasonic transmitter was dispatched, it discharged a ultrasonic wave one way and started timing. At the point when it met hindrances in its way, ultrasonic scattered through the air and returned right away. At the point when the ultrasonic beneficiary at last got the reflected wave, it will abstain from timing. The ultrasonic distance estimation hypothesis depended on the notable air spreading speed. In this way, the rule of ultrasonic distance estimation is something very similar with radar.

3.5.1 DESCRIPTION

The HC-SR04 ultrasonic sensor uses sonar to determine distance to an object like bats do. Its operation is not affected by sunlight or black material like. It comes complete with ultrasonic transmitter and receiver module

PINS



- VCC: +5VDC
- Trig : Trigger (INPUT)
- Echo: Echo (OUTPUT)
- GND: GND

3.5.2 PRODUCT FEATURES:

Ultrasonic running module HC - SR04 gives 2cm - 400cm non-contact estimation work, the going exactness can reach to 3mm. The modules incorporates ultrasonic transmitters, recipient and control circuit. The essential guideline of work:

Utilizing IO trigger for at any rate 10us significant level sign,

The Module consequently sends eight 40 kHz and distinguish whether there is a heartbeat signal back.

In the event that the sign back, through undeniable level , season of high yield IO length is the time from sending ultrasonic to returning.

3.5.3 ULTRASONIC APPLICATION

Ultrasonic Application Technology is the thing which developed in recent decades. With the ultrasonic advance, and the electronic technology development, especially as high-power semiconductor device technology matures, the application of ultrasonic has become increasingly widespread:

- Ultrasonic measurement of distance, depth and thickness;

- Ultrasonic testing;
- Ultrasound imaging; Ultrasonic machining, such as polishing, drilling;
- Ultrasonic cleaning;
- Ultrasonic welding;

3.5.4 APPLICATION AREAS:

- Robotics barrier
- Object distance measurement
- Level detection
- Public security
- Parking detection

3.5.5 MODULE OPERATING PRINCIPLE

Set low the Trig and Echo port when the module instates , first and foremost, communicate in any event 10us undeniable level heartbeat to the Trig pin (module naturally sends eight 40K square wave), and afterward hold on to catch the rising edge yield by reverberation port, simultaneously, open the clock to begin timing. Then, by and by catch the falling edge yield by reverberation port, simultaneously, read the hour of the counter, which is the ultrasonic running time noticeable all around. Need to supply a short 10uS heartbeat to the trigger contribution to begin the going, and afterward the module will convey a 8 cycle eruption of ultrasound at 40 kHz and raise its reverberation.

The Echo is a distance object that is beat width and the reach in extent .You can figure the reach through the time span between conveying trigger message and getting reverberation signal. Equation: $\mu\text{S}/58 = \text{centimeters}$ or $\mu\text{S}/148 = \text{inch}$; or: the reach = undeniable level time * speed (340M/S)/2; we recommend to use over 60ms estimation cycle, to forestall trigger sign to the reverberation signal.





Fig:3.5.5 MODULE OPERATING PRINCIPLE

3.6 UART

A PC's sequential correspondences subsystem is driven by the Universal Asynchronous Receiver/Transmitter (UART) regulator. UART is additionally a standard element found in many microcontrollers. The UART gets bytes of information and converts them to characters.transmits the pieces individually in a successive request. A second UART shows up at the target.the pieces are reassembled into full bytes The expense of sequential transmission of advanced data (bits) over a solitary wire or other medium is a lot of lower than concurrent transmission over numerous wires. It is feasible to convey twoly: sending and accepting.



A UART (Universal Asynchronous Receiver/Transmitter) is a programming-controlled central processor that controls a PC's sequential gadget interface.

It explicitly gives the RS-232C Data Terminal Equipment to the gadget (DTE It has a sequential

interface that permits it to "talk" to and share information with modems and other sequential gadgets. mechanical assemblies The UART is likewise a piece of this gui. Converts the bytes it gets from the PC along equal circuits into a solitary sequential cycle stream for outbound transmission

On inbound transmission, changes over the sequential digit stream into the bytes that the PC handles

Adds an equality digit (if it's been chosen) on outbound transmissions and checks the equality of approaching bytes (whenever chose) and disposes of the equality cycle

Adds start and stop delineators on outbound and takes them from inbound transmissions

Handles intrude on s from the console and mouse (which are sequential gadgets with specialport s)

May deal with different sorts of hinder and gadget the executives that require planning the PC's speed of activity with gadget speeds

3.6.1 THE ASYNCHRONOUS RECEIVING AND TRANSMITTING PROTOCOL

Information can be sent without the sender conveying a clock message to the collector utilizing offbeat transmission. The sender and recipient should concur on the circumstance in this situation.prior to transmission (Baud Rate) and uncommon pieces are applied to each word to the sending and accepting units should be synchronized The sender is the person who starts nonconcurrent transmission.sends a Start bit, 5 to 8 information bits, and a Stop bit (LSB initial), a discretionary Parity spot, and afterward 1, 1.5 or 2 Stop bits.

The Start bit is applied to the start of a word as it is passed to the UART for nonconcurrent transmissions. The Start bit is utilized to caution the beneficiary that an expression of information is going to be sent, making the recipient's clock line up with the transmitter's clock. It's essential to recollect that the recurrence float between these two timekeepers can't be more than 10%.In different words, both the transmitter and recipient should have indistinguishable baud rate.

7 The individual pieces of the information word are sent after the Start bit, beginning with the Least Significant Bit (LSB). A discretionary equality bit is shipped off the transmitter until the information has been totally sent. The recipient as a rule utilizes this piece to perform fundamental blunder checking.Finally, a Stop spot will be shipped off show that transmission has reached a conclusion. At the point when the recipient has acquired the entirety of the pieces in the information term, it will search

for the Parity Bits (the sender and collector should concur on whether to utilize a Parity Bit). In the event that the Stop Bit isn't present, The UART discover the entire word to be confused and doesn't show up when it is implied to. When the information word is perused, the host processor will get a Framing Error.

3.6.2 THE PHYSICAL LAYER STANDARDS

There are actually quite a number of different standards that utilizes similar protocol. For instances, TTL level UART, RS-232, RS-422, RS-485 and etc. We will only discuss about TTL level UART and RS-232 in this article.

3.6.3 TTL level UART

TTL (Transistor-Transistor Logic) level UART is used by the majority of microcontrollers with UART. It is the most basic kind of UART. 5V and 0V are used to represent logic 1 and 0, respectively.

Logic	Voltage
Low	0V
High	5V

Voltage level for TTL level UART

The TTL level UART is commonly used in the communications between microcontrollers and ICs. Only 2 wires are required for the full duplex communications as illustrated in the picture below.




Fig:3.6.3 TTL level UART


The RS-232 (Recommended Standard 232) protocol is a serial binary data signalling standard used to link a Data Terminal Equipment (DTE) to a Data Communication Equipment (DCE) (DCE). It's usually found in serial ports on computers. The voltage level is one of the major differences between TTL level

UART and RS-232. Signals between 3 and –15V are true in RS-232, but signals near 0V are not.

Logic	Voltage
Low	+3 to +15V
High	-3 to -15V

Voltage level for RS-232

Besides voltage level, the RS-232 also has a few extra pins specifically designed for the communication between PC and modem. The pinouts of the DB-9 and their functions are shown below.



3.6.4 PINOUTS AND DESCRIPTION OF A SERIAL PORT

Name	Pin	Description
Transmitted Data (TxD)	3	Serial data output
Received Data (RxD)	2	Serial data input

Request to Send (RTS)	7	This line informs the DCE (Modem) that the DTE (PC) is ready to exchange data
Clear to Send (CTS)	8	This line indicates that the DCE is ready to exchange data
Data Terminal Ready (DTR)	4	Asserted by DTE to indicate that it is ready to be connected
Data Set Ready (DSR)	6	Asserted by DCE to indicate the DCE is powered on and is ready to receive commands or data for transmission from the DTE
Data Carrier Detect (DCD)	1	Asserted by DCE when a connection has been established with remote equipment
Ring Indicator (RI)	9	Asserted by DCE when it detects a ring signal from the telephone line

3.6.5 FEATURES:

The capacity to change information from chronic over to resemble, and from corresponding to sequential, utilizing shift registers. An on-chip bit rate (baud rate) generator to control send and get information rate. Handshake lines for control of an outside modem, controllable by programming. An intrude on capacity to the host chip. chip FIFO cradle for both approaching and active information; this gives the host framework more opportunity to react to a hinder created by the UART, without loss of information.

3.7 BUZZER

A bell is a sound flagging framework that can be mechanical, electromechanical, electrical, electromagnetic, electro-acoustic, or piezoelectric. A wavering electronic circuit can control a Piezo electric buzzer.or some other sort of sound sign. A tick, signal or ring can show that a catch has been squeezed.

A signal takes a type of information and transmits a sound in light of it. They may utilize different intends to create the sound; everything from metal clappers to electromechanical gadgets. A bell should have the option to take in energy and change it to acoustic energy here and there. Numerous ringers are incorporated into bigger cases; be that as it may, a few bells are battery-controlled and will

kill in case of a force disappointment. A bell, otherwise called a beeper, is a flagging gadget. The expression "signal" gets from the scratching sound that ringers made when they were electromechanical, worked from ventured down AC line voltage at 50 or 60 cycles. Different sounds generally used to demonstrate that a catch has been squeezed are a ring or a signal



fig:3.7 buzzer

3.7.1 BUZZER CIRCUIT




Fig :3.7.1 Buzzer Circuit

A hand-off is associated in arrangement with a little sound transformer and speaker in this novel ringer circuit. The hand-off will work through the transformer essential and shut transfer contact when the switch is squeezed. When the hand-off is complete, When the hand-off is turned on, the normally shut

contact opens, extricating power from the relay. The contacts close and the cycle refreshes, all quickly, to where the current heartbeat is disturbed. varies the transformer principle and, therefore, the optional. Thus, the speaker's tone is corresponding to the transfer's working recurrence. To "tune" the note, utilize the capacitor C. The ostensible capacitance esteem is 0.001uF, and expanding it lessens the bell's sound.

3.7.2 TYPES OF BUZZER

ELECTROMECHANICAL

The first devices used an electromechanical mechanism similar to that of an electric bell, but without the metal gong. A relay, for example, may be wired to interrupt its own actuating current, allowing the contacts to close. there's a noise These units were often anchored to a wall or ceiling in order to serve as a sounding board. The word "buzzer" comes from the rasping noise that electromechanical buzzers made.

MECHANICAL

A joy buzzer is an example of a purely mechanical buzzer. They require drivers.

PIEZOELECTRIC

An oscillating electronic circuit or another audio signal source may drive a piezoelectric element, which is then powered by a piezoelectric audio amplifier.

A click, a ring, or a beep are typical sounds used to signify that a button has been pressed. There was a beep. Buzzers are commonly used for detection and warning purposes in a variety of applications industries of importance

INDUSTRIES SERVED

- Safety and Security
- Automotive Electronics
- Office Automation
- Medical Equipment
- Industrial
- Consumer Electronics

PIEZO VS. MAGNETIC BUZZERS

CUI's buzzer line utilizes two main technologies. Each technology has specific advantages and tradeoffs that must be taken into consideration depending on the application requirements.

PIEZO BUZZER CHARACTERISTICS

- Wide operating voltage: 3~250V

- Lower current consumption: less than 30mA
- Higher rated frequency
- Larger footprint
- Higher sound pressure level



Fig:3.7.2.1PIEZO BUZZER

MAGNETIC BUZZER CHARACTERISTICS

- Narrow operating voltage: 1~16V
- Higher current consumption: 30~100mA
- Lower rated frequency
- Smaller footprint
- Lower sound pressure level



Fig:3.7.2.2magnetic buzzer

BENEFITS OF BUZZER

The utilization of caution frameworks like delta-larm or electric ringers could be useful in limiting loss of lives during a calamity or mishap. They are significant gadgets in any structure or offices to caution and inform individuals if an ideal clearing is fundamental.

➤ Specialized electric alert frameworks could go about as notice about undermining fluid level conditions in lift siphon chambers, sewage, and other non-consumable water applications. It is fundamental that you realize how effectively your house is or business site's sewer framework works and this can be measured all the more precisely on the off chance that it is joined by an electric sewage alert.

➤ Most electro mechanical signals are not difficult to set up. Truth be told, you don't have to enlist

an electrical technician to introduce it, since no hard wiring is generally required. This implies eliminating consumption for employing an expert installer.

- In work environment, electric signals, particularly those with timing programming, offers a bigger number of advantages and highlights than conventional clocks and costly chime. They could be synchronized with programmed programming through PC to control and switch times or channels inside the day.
- Electric ringers could even be utilized in a wide cluster of apparatuses. A few bells are currently utilized in exchanging hints of electric home apparatuses like microwaves, clothes washers, mini-computers, smoke alarms, and phone ringers, transmitters, and some more.
- With the assistance of electro-mechanical ringers, you can be advised of a car entering your home or business when you're in distant regions, so you never miss an admonition.

3.7.4 MODERN APPLICATION

- Novelty uses
- Judging Panels
- Educational purposes
- Annunciator panels
- Electronic metronomes
- Game show lock-out device
- Microwave ovens and other household appliances
- Sporting events such as basketball games
- Electrical alarms
- Joy buzzer- a mechanical buzzer used for pranks

CHAPTER- 4

LITERATURE SURVEY

Title: Depth-based hand gesture recognition for home appliance control

Author: Chih-Hung Wu, Chang Hong Lin

Year: 2013

Using only the depth camera, this paper presented a dynamic hand gesture recognition framework for home appliance control. Static hand postures and hand trajectory are used to understand the dynamic hand gesture. The proposed system is capable of recognising seven common dynamic hand gestures.. Experimental results show that the system is effective for home appliance control.

Title: A Two-Hand Multi-Point Gesture Recognition System Based on Adaptive Skin Color Model

Author: Chueh-Wei Chang Chun-Hao Chang

Year: 2011

Many studies in recent years have centred on using hand movements to monitor appliances remotely. It has the potential to bridge the gap between humans and computers. The skin colours of various humans and the sizes of their hands are used in most gesture recognition systems. The lighting conditions of clutter background environments are the most serious issues for the photographer. Segmentation of hand shapes. . We propose a two-hand multipoint gesture recognition system in this paper that can model various skin colours in various locations without any pre-defined training procedure. To find user both by, we use the Haar-Like function start pose is the heatmap of the gesture signal.. Then, we collect the color distribution of both hands to construct the user's skin color model. With this adaptive skin color model, our system can extract the shape of both hands, and recognize the static and dynamic hand gesture command according to the number of finger and the finger's moving trajectory. We also design a gesture command set that can simulate as the multi-point touch panel. Results of experiments performed on live video for media player control have demonstrated the effectiveness of the proposed method.

Title: Hand gesture based remote control for home appliances: Hand mote

Author: Utpal V. Solanki, Nilesh H. Desai

Year: 2011

Controlling the home appliances and electronics gadgets through an Infrared remote control is now in general. However, the same monitoring tasks can be accomplished more quickly. The primary motivation for proposing the new hand gesture remote control system is to eliminate the need to look

into the hand held remote and look for a specific key for a specific purpose. This is a paper aboutdemonstrates a novel method for controlling home appliances using hand gestures as a remote control kit for controlling. In this article, the device will be referred to as Hand mote. It uses the Blobscanner library and the Arduino microcontroller development board to perform real-time image processing for hand gesture recognition in infrared vision. This paper proposes a possible solution to control the gadgets for physically challenged and blind people

Title: Wearable armband for real time hand gesture recognition

Author: kuang-yow lian, chun-chieh chiu, yong-jie hong and wen-tsai sung

Year: 2017

This paper presents a framework for hand gesture recognition based on 3-channel electromyography (EMG) sensors. In the framework, the start and the end points of meaningful gesture segments are detected automatically by checking the cross points of EMG signals and their moving average curves. Then, a classifier combining k-Nearest Neighbor (kNN) and Decision Tree algorithms is used for achieving gesture recognition. For gesture-based control application, a real-time interactive system has been built up for household appliance using 10 kinds of hand gestures as control commands. Our proposed framework facilitates intelligent and natural control in gesture-based interaction.

Title: Gesture based home automation system

Author: Arathi P.N,S.Arthika,S.Ponmithra, K.Srinivasan*,V.Rukkumani

Year: 2017

Computerization is the fundamental requirement for the current world. There are different sorts of mechanizations like structure computerization, modern robotization, Home robotization, Artificial Intelligence, and so forth Savvy can be a potential application which offers help to older or crippled people. Home mechanization is the utilization and control of home machines distantly or naturally. Step by step the hole among machines and people is being diminished. These days hand motion based home mechanization is getting more significance. Signal acknowledgment alludes to perceiving the movement of the human parts like hand, face, and so on A large portion of the electronic parts fabricates centers around the hand motion premise. In this proposed work MATLAB based calculation is utilized. This proposed work utilizes this apparatus for the acknowledgment and handling of the hand motion. The calculation utilized for this proposed work is the item location calculation. From the outset the picture is caught by the camera and it is handled by the MATLAB, if the preloaded motion is coordinated with the current signal the information will be shipped off the microcontroller, at that point

the home machines are controlled. There are different applications which could be constrained by a signal, for example, media players, robots and virtual objects. The camera, PIC microcontroller, fan, light, power supply, LED, and GSM module make up the equipment module. A USB to chronic converter transport, which comes a day and a half driver programming, is utilized to connect this equipment module to reenactment programming.

Title: A continuous hand gestures recognition technique for human-machine interaction using accelerometer and gyroscope sensors

Author: Hari Prabhat Gupta, Haresh S Chudgar, Siddhartha Mukherjee, Tanima Dutta, and Kulwant Sharma

Year: 2016

Since they are fitted with an accelerometer sensor, recent developments in smart devices have maintained them as a safer alternative for the design of human-machine interaction. An integrated operating system, and a gyroscope sensor. This paper provides a continuous flow of information. A technique for recognising hand movements that is capable of continuous recognition. gestures in a mobile device using three-axis accelerometer and gyroscope sensors. A gesture coding algorithm is being developed to reduce the impact of the unstableness of the hand making the gesture and compress the data. An algorithm for detecting gestures automatically is a tool for detecting the beginning and end of significant gesture segments. Lastly, The gesture code is compared to identify the gesture. It uses a dynamic time warping algorithm with a gesture database. In addition, a prototype system for recognising continuous hand movements based human-machine interaction is being developed. With the support of The user of a smartphone can perform predefined movements and monitor smart devices. Samsung's AllShare protocol is used by appliances.

Title: A method of two-handed gesture interactions with applications based on commodity devices

Author: Jiaqing Lin, Hiroaki NISHINO, Tsuneo KAGAWA, and Kouichi UTSUMIYA

Year: 2011

In some fields, such as game interaction and medical image processing, recent advances in human-computer interface have enabled more intuitive and natural interactions between humans and sensor-based devices. However, the most

Since the conventional human-computer interface continues to influence our everyday lives, we suggest a new approach. centred on a new two-handed gesture interaction approach for controlling applications. Wiimote is an example of a commonplace unit.

Our main aim is to create a single interface for communicating with devices, application systems, and home appliances. Users will monitor their progress using the proposed system. finger movements in 3D

space and describe the role of each gesture using the devices that are commonplace.

Title: Facilitating gesture-based actions for a smart home concept

Author: A. Batool, S. Rauf, T. Zia, T. Siddiqui, J. A. Shamsi, T. Q. Syed, A. U. Khan

Year: 2014

4 Smart Home Technologies are changing the way people communicate with their environment through digital interfaces. These activities, on the other hand, are difficult. We look at the problem of using complex mechanical interfaces in this paper. The user-friendly, 37 ubiquitous, low-cost, and unified digital interface mobile phone. This is accomplished by programming smart phones at the application level to understand hand signals, which will enable mobility-impaired and elderly users to interact with their home appliances remotely. We also have remote access for versatility and control when running these appliances. We demonstrate this principle by practising with visual examples of hand signs and reporting a correct response recognition of over 88%, and test the viability of the concept under continued use by noting ordinary power consumption for uses of up to 90 minutes.

Title: A framework for hand gesture recognition and spotting using sub-gesture modeling

Author: Manavender R. Malgireddy, Jason J. Corso, Srirangaraj Setlur

Year: 2010

Hand motion discernment is an open examination issue in Human Computer Interaction (HCI), and it involves spotting motion limits in a persistent video arrangement (Gesture Spotting). and liking the gesture. Each motion is as of now demonstrated as a transient grouping of visual highlights utilizing existing techniques. due to the wide fluctuation of the information, separated from singular casings is wasteful. an image which isn't effective because of the huge fluctuation of casings at various timestamps. In this paper, we propose another sub-motion demonstrating approach which addresses each signal as a succession of fixed sub-motions (a gathering of back to back outlines with locally sound setting) and gives a vigorous displaying of the visual highlights.

Title: Hand Gesture Recognition for Indian Sign Language

Author: Archana S. Ghotkar, 2Rucha Khatal , 3 Sanjana Khupase, 4 Surbhi Asati & 5Mithila Hadap

Year: 2012

We present a hand gesture recognition scheme for recognising the alphabets of Indian Sign Language in this paper. Real-time hand monitoring, hand segmentation, feature extraction, and gesture recognition are the four modules in our proposed framework. For hand painting, the Camshift system and the Hue, Saturation, Intensity (HSV) colour model are used for segmentation and monitoring. The Genetic Algorithm is used to recognise gestures. We suggest a simple and low-cost method for accurately recognising single-handed and double-handed gestures. This

device has the potential to assist millions of deaf people in communicating with others. Ordinary people.

CHAPTER-5

SOFTWARE DESCRIPTION

5.1 EMBEDDED C

The C Standards committee created Embedded C as a collection of language extensions for the C programming language to solve commonality issues that exist between C extensions for different languages. Embedded software. Embedded C programming has traditionally necessitated nonstandard solutions. extensions to the C programming language to support exotic features including fixed-point math, as well as simple I/O operations and several distinct memory banks.

The C Standards Committee extended the C language in 2008 to address these worries by setting up an overall standard that all executions would follow. It contains a There are an assortment of highlights not accessible in standard C, for example, fixed-point math and named factors. Fundamental I/O equipment tending to and address spaces Embedded C utilizes the

of the grammar and semantics of standard C, e.g., principle() work, variable definition, datatype affirmation, restrictive explanations (if, switch, case), circles (while, for), capacities, exhibits and strings, constructions and association, digit tasks, macros, and so on

A Technical Report was distributed in 2004 and a second update in 2006.

5.1.1 NECESSITY

During infancy years of microprocessor based systems, programs were developed using assemblers and fused into the EPROMs. There used to be no mechanism to find what the program was doing. LEDs, switches, etc. were used to check for correct execution of the program. Some ‘very fortunate’ developers had In-circuit Simulators (ICEs), but they were too costly and were not quite reliable as well. As time went by, the use of microprocessor-specific assembly-only as a programming language declined, and embedded systems shifted to C as the preferred language. The most commonly used programming language is C.

a programming language for embedded processors and controllers Assembly is often used, but it is mostly for implementing certain parts of the code that are extremely complex. high timing precision, small code size performance, etc. are prime requirements.

As assembly language programs are specific to a processor, assembly language didn't offer portability across systems. Several high-level languages, including C, were developed to address this disadvantage. Other languages such as PLM, Modula-2, Pascal, and others are accepted by a lot of people. Among them, C received a lot of attention. Not only embedded systems, but even desktop applications have gained acceptance. Even though C has lost its lustre as a general-purpose programming language, it continues to have a stronghold in embedded programming. Because of the widespread use of C in embedded systems, a variety of support tools, such as compilers, have emerged. & cross-compilers, ICE, and other tools appeared, all of which aided the development of embedded systems. C-based systems For programming embedded devices, assembly language appears to be a natural option. The use of assembly language, on the other hand, is limited to creating small and quick codes. Furthermore, assembly codes increase software development costs and reduce code portability. There isn't any. Small codes aren't difficult to write, however big ones are. Programs/projects are becoming more difficult. in assembly language to handle. It's also getting harder to find decent assembly programmers these days. As a result, high-level languages are favoured for programming embedded systems.

5.2 ADVANTAGES

- It is little and less complex to learn, get, program and troubleshoot.
- Compared to low level computing construct, C code composed is more dependable and versatile, more compact between various stages.
- C compilers are accessible for practically completely implanted gadgets being used today, and there is an enormous pool of experienced C developers.
- Unlike get together, C has benefit of processor-autonomy and isn't explicit to a specific chip/microcontroller or any framework. This makes it helpful for a client to create programs that can run on the vast majority of the frameworks.
- As C joins usefulness of low level computing construct and highlights of undeniable level dialects, C is treated as a 'center level code' or 'significant level low level computing construct'.
- It is genuinely effective.

- It upholds admittance to I/O and gives simplicity of the board of huge installed projects.
- Java is additionally utilized in many implanted frameworks however Java programs require the Java Virtual Machine (JVM), which devours a ton of assets. Henceforth it isn't utilized for more modest installed gadgets.
- Other High-level programming language like Pascal, FORTRAN additionally give a portion of the benefits.

5.2.1 EMBEDDED SYSTEMS PROGRAMMING

Installed frameworks writing computer programs is not quite the same as creating applications on a work stations. Key qualities of an installed framework, when contrasted with PCs, are as per the following:

- Embedded gadgets have asset constraints(limited ROM, restricted RAM, restricted stack space, less preparing power)
- Components utilized in inserted framework and PCs are unique; implanted frameworks normally utilizes more modest, less force burning-through segments. · Embedded frameworks are more attached to the equipment.

Code speed and code size are two significant qualities of implanted programming. The handling force and timing limitations decide code speed, while code size is dictated by the size of the code. is controlled by the measure of program memory accessible and the programming language utilized. The point of installed gadget writing computer programs is to get the most usefulness at all measure of existence.

Implanted frameworks are customized utilizing distinctive sort of dialects:

- Machine Code
- Low level language, i.e., gathering
- High level language like C, C++, Java, Ada, and so forth

- Application level language like Visual Basic, contents, Access, and so forth

For programming implanted gadgets, low level computing construct has all the earmarks of being a characteristic choice. The utilization of low level computing construct, then again, is restricted to making little and speedy codes. Moreover, gathering codes bring about higher programming advancement expenses and need code compactness. More modest projects/projects are simpler to oversee, yet bigger projects/projects become more difficult to manage in low level computing construct. Discovering great get together developers has likewise become troublesome these days. Henceforth significant level dialects are liked for installed frameworks programming.

Utilization of C in implanted frameworks is driven by following benefits

- It is little and sensibly more straightforward to learn, get, program and investigate.
- C Compilers are accessible for practically totally installed gadgets being used today, and there is a huge pool of experienced C developers.
- Unlike get together, C has benefit of processor-autonomy and isn't explicit to a specific chip/microcontroller or any framework. This makes it advantageous for a client to create programs that can run on the vast majority of the frameworks.
- As C joins usefulness of low level computing construct and highlights of undeniable level dialects, C is treated as a 'center level code' or 'significant level low level computing construct'
- It is genuinely proficient
- It upholds admittance to I/O and gives simplicity of the executives of enormous implanted tasks.

Large numbers of these benefits are offered by different dialects additionally, however what separates C from others like Pascal, FORTRAN, and so on is the way that it is a center level language; it gives direct equipment control without forfeiting advantages of undeniable level dialects.

Contrasted with other significant level dialects, C offers greater adaptability since C is moderately little, organized language; it upholds low-level piece savvy information control.

When contrasted with low level computing construct, C code is more reliable, adaptable, and flexible across stages (for certain changes). Moreover, C-based frameworks are additionally simpler to understand, oversee, and investigate. Likewise, since they can be Codes are composed all the more effectively, and just the expectations should be referenced unmistakably. It's true. It's simpler to compose solid C code and make an interpretation of it to different dialects. Maybe than composing powerful get together code in gathering, it is changed over to a proficient get together code (utilizing great compilers). As contrasted with the simplicity with which C projects are made by software engineers, the benefits of low level computing construct programming over C are irrelevant. C++ is an item situated programming language that isn't appropriate for establishing gainful projects in asset compelled conditions like inserted gadgets.

Virtual capacities and exemption treatment of C++ are some particular highlights that are not proficient as far as space and speed in installed frameworks. Here and there C++ is utilized distinctly with not many highlights, especially as C.

It's additionally an article arranged language, yet it's not equivalent to C++. Initially planned by the United States of America (Ada95). The Ada programming language, then again, has various highlights that make creating inserted programming simpler. Another dialect for implanted frameworks is Java.

programmable It is mostly utilized in top of the line PDAs due to its versatility. It's likewise valuable for perusing applications through frameworks.

Java programs require Java Virtual Machine (JVM), which burn-through parcel of assets. Henceforth it isn't utilized for more modest installed gadgets.

Dynamic C and B# are some restrictive dialects which are likewise being utilized in implanted applications.

Effective installed C projects should be kept little and proficient; they should be advanced for code speed and code size. Great comprehension of processor design installed C programming and investigating d

5.3 DIFFERENCE BETWEEN C AND EMBEDDED C

Despite the fact that C and embedded C tend to be distinct and are used in different ways, they have more in common than they do not. The majority of the structures are the same; the difference is in how they are used. The letter C stands for laptop. Embedded C is for microcontroller-based applications, while computer C is for computer-based applications. As a result, C has the privilege of using desktop PC resources such as memory, operating system, and so on.

programming on desktop systems, we need not bother about memory. Embedded C, on the other hand, must work with the limited resources (RAM, ROM, and I/Os) available on an embedded processor. As a result, computer code must fit into the programme memory available. The device is likely to crash if the code reaches the cap. Compilers for C (ANSI C) are commonly used. create executables that are OS-dependent. Compilers for embedded C must generate files that can be downloaded to microcontrollers and microprocessors.

where it is needed to run. Embedded compilers have access to all tools that are not available in desktop computer compilers. Real-time constraints are common in embedded systems. this isn't always the case for desktop computer programmes. Embedded systems also lack the console that is available on desktop computers. the apps So, what's the main difference between the two?

programming with embedded C is the mindset; for embedded applications, we need to optimally use the resources, make the program code efficient, and satisfy real time constraints, if any. All this is done using the basic constructs, syntaxes, and function libraries of 'C'.

5.4 MATLAB:

MathWorks created the MATLAB programming language. It began as a matrix programming language with basic linear algebra programming. It can be used in collaborative sessions as well as as a batch task. MATLAB is a programming language that can be utilized to (matrix laboratory) is a high-level programming language and immersive environment for the fourth generation Numerical computation, visualisation, and programming are all possible with this tool.. MathWorks is the company that produced MATLAB. Matrix manipulations, plotting of capacities and data, algorithm implementation, user interface creation, and interfacing with programmes written in different dialects like C, C++, Java, and FORTRAN are all possible. It also helps you to analyse data, build algorithms, and construct models and applications. It comes with a number of built-in commands and math functions to assist you with mathematical calculations, generating plots and performing numerical methods.

5.4.1 MATLAB'S POWER OF COMPUTATIONAL MATHEMATICS:

Every aspect of computational mathematics makes use of MATLAB. The following are some of the most frequently used mathematical equations:

- Dealing with Matrices and Arrays.
- Plotting and graphics.
- Linear Algebra.
- Algebraic Equations.
- Non-linear Functions.
- Statistics.
- Data Analysis.
- Calculus and Differential Equations.
- Numerical Calculations.
- Integration.
- Transforms.
- Curve Fitting

5.4.2FEATURES OF MATLAB:

It's a high-level programming language for mathematical calculation, visualisation, and app creation. It also offers an immersive platform for iterative problem solving, design, and discovery. It has a large library of numerical capacities for direct polynomial math, measurements, and other subjects. Filtering, optimization, numerical integration, and solving ordinary problems are all examples of Fourier analysis, a system of differential equations. It comes with built-in graphics for visualising data as well as tools for making custom plots. The programming interface in MATLAB provides developers with devices for improving code quality, viability, and performance. It includes software for creating custom graphical user interfaces for applications. It has functions for combining MATLAB-based algorithms with other programmes and languages, such as Python, C, Java, .NET & Microsoft Excel.

5.5 USES OF MATLAB:

MATLAB is a common analytical instrument in science and engineering, with applications in physics, chemistry, math, and all engineering disciplines.

It is utilized in a scope of utilizations including:

- signal processing and Communications.
- image and video Processing.
- computational biology.
- control systems.
- computational finance.
- test and measurement.

5.6 DIGITAL IMAGE PROCESSING:

Computerized picture handling is the technique for controlling advanced pictures utilizing a computer. It is a sign and frameworks that centers around pictures specifically. DIP is working on designing a computer device that can perform image processing. The device takes a digital image as an information and cycles it using powerful algorithms to produce an image as an output. The most famous illustration is Photoshop is a software programme created by Adobe. It is widely used application for processing digital images.

5.7.1 WORKING:



Fig:5.7.1 processing of image

In the illustration above, an image was taken by a camera and sent to a digital system to delete all other information and concentrate solely on the water drop by zooming it in such a way that the image quality is preserved. the same

5.8 SIGNAL PROCESSING:

Signal processing branch of electrical engineering and mathematics concerned with the study and processing of analogue and digital signals, as well as signal storage, filtering, and other operations. These signals include the following: signals of transmission, sound or voice signals, image

signals, and other signals, etc. Out of both of these signals, image processing is the area that deals with the types of signals where the input is an image and the output is also an image. As the name implies,As the name implies, it is concerned with image processing. Analog image processing & digital image processing, are two types of image processing.

5.9ANALOG IMAGE PROCESSING:

analog signals, analog image processing is performed. It requires two-dimensional analogue signal processing. The pictures are controlled by electrical methods by shifting the electrical sign in this form of processing. The picture on television is a typical example.With the passing of time, digital image processing surpassed analogue image processing due to its broader variety of application

5.10OVERLAPPING FIELDS

5.10.1MACHINE/COMPUTER VISION

The developing of a device in which the input is an image and the output is some informationis known as machine vision or computer vision.Consider developing a device that scans a person's face and unlocks any kind of lock.. This is how the machine will appear




Fig:5.10.1 machine vision or computer vision

5.10.2 COMPUTER GRAPHICS

Computer graphics deals with the development of images from object models rather than the image being captured by software. Consider the example below: The creation of artefacts. Creating a picture from an entity's model. This is how a computer like this would look.




Fig: 5.10.2 Computer graphics

5.11.1 ARTIFICIAL INTELLIGENCE

Artificial intelligence is essentially the study of imbuing robots with human intelligence. In image analysis, artificial intelligence has wide range of applications. For instance, creating computer-assisted diagnostic programmes that assist doctors in reading X-ray, MRI, and other photographs and then highlighting noticeable sections to be checked by the doctor.

5.12 SIGNALS

A signal is the basic quantity for expressing any knowledge in electrical engineering. It makes no difference whether the information is analogue or digital. A signal is a feature in mathematics that conveys certain detail. In truth, any quantity that can be measured over time, space, or a higher dimension can be considered a signal. A signal can have any dimension and have any shape.

5.12.1 ANALOG SIGNALS

A signal is an analogue number, which means it is determined in terms of time. It's a never-ending signal. These signals are represented over a set of independent variables that are continuous.

They are difficult to interpret due to the large number of values they contain. Due to a wide sample of values, they are very reliable. You'll need an unlimited memory to store these signals so it can achieve On a real graph, there are infinite values. Sin waves used to represent analogue signals.




Fig:5.12.1 analoge signals

5.13.1DIGITAL SIGNALS

Digital signals are much easier to interpret than analogue signals. They're messages that come and go. They are analogue signs that have been appropriated. The term "digital" refers to discrete values, which means they use unique values to display data. Just two numbers, 1 and 0, are used to describe everything in a digital signal (binary values). Since digital signals are discrete copies of an analogue signal obtained over a span of time, they are less reliable than analogue signals. Digital signals, on other hand, are not affected by 64 noise. As a result, they last a long time and are simple to understand. Square waves are to represent digital signals.

5.14COMPUTER KEYBOARD

When a key on the keyboard is pressed, an electrical signal is transmitted to keyboard controller, which contains the ASCII value for that key. When key is pressed, for example, the electrical signal contains of digit 97 as 0 & 1, which are ASCII estimation of character

5.15 DIFFERENCES BETWEEN ANALOG & DIGITAL SIGNALS:

Comparison element	Analog signal	Digital signal
Analysis	Difficult	Possible to analyse
Representation	Continuous	Discontinuous
Accuracy	More accurate	Less accurate
Storage	Infinite memory	Easily stored
Subject to Noise	Yes	No
Recording Technique	The original signal has been restored.	Signal samples are collected and stored.
Examples	Human voice, Thermometer, Analog phones e.t.c	Computers, Digital Phones, Digital pens, e.t.c

5.16 SYSTEMS

The kind of input and output that a machine interacts with defines it. Since we're concerned with signals, our machine will be a logical model, a piece of code/software, a physical unit, or a black box whose input is a signal, which it processes, and whose output is another signal. The input is referred to as excitation, while the output is referred to as reaction.



In the diagram above, a device is depicted in which the input/output are also symbols, but the input is an analogue signal. The OP signal is a digital signal. It basically means that our system is a conversion system that transforms analogue signals to digital signals.

5.17 CONVERSION OF ANALOG TO DIGITAL SIGNALS

Since there are so many concepts involved in converting analogue to digital and vice versa. Only those that are relevant digital image processing will be discussed. In the case of conversion, there are two major principles to consider.

- Sampling
- Quantization

5.17.1 APPLICATIONS OF DIGITAL IMAGE PROCESSING

The below are some of the main areas in which digital image processing commonly used.

- Medical field
- Sharpening and reproduction of images
- Remote sensing
- Transmission and encoding
- Machine/Robot vision
- Color processing
- Pattern recognition
- Video processing
- Microscopic Imaging
- Others

5.18 MACHINE/ROBOT VISION

Apart from the many problems that a robot faces today, the most pressing is to improve the robot's vision. Make a robot that can see objects, recognise them, and recognise obstacles, among other things. This research has made significant contributions, and a new field in computer vision has been created to work on it.

5.19 Hurdle Detection

Detection of Obstacles Hurdle detection is a simple image processing task that involves detecting various types of objects in an image and then measuring the distance between the robot and hurdles. Robot that follows a line The majority of today's robots operate by following a grid, and hence are referred to as line follower robots.





Fig:5.19.Line follower robot



This help a robot to move on its path and perform some tasks. This has also been achieved through image processing.



6.CHAPTER

RESULT AND DISCUSSION

In this project, we will discuss have tried to control the robot in a novel method. Signal control being a more regular method of controlling gadgets, makes control of robots more productive and simple. We used finger count Techniques for interacting with gestures.. Each finger count defines an instruction for the robot to move in a certain direction in the environment. After gesture recognition command signal is generated and passed to the robot, it moves in aspecified direction.








Discussions:

- A. Capturing Gesture Movements: Image from the control station's webcam, and each input frame is processed further to identify hand movement palm.. This includes certain limits in the

past to identify the hand palm correctly with minimum noise and image

- B. Detection of palm of the hands Following the capture of the image frame from the webcam, several simple operations are conducted on the frame to ready it for command detection processing..
- C. Command Detection Using a Specific Method: Following the pre-processing of an input frame, the extracted image is further processed using a specific technique. The method of giving gesture commands are as follows

Robot is moved in all possible directions in the environment using five possible types of commands which are Forward, Backward, Right, Left and Stop for the finger count of 1, 2, 3, 4 & 5 respectively as shown in the above figure.



D. Generate Specific Signal:

Following the detection of a gesture command, a signal value is created that is relevant to that gesture command. This signal value is saved in a file with the following command MATLAB functions.

E. ZIGBEE:

As soon as possible, the command is generated on the control station, It has been published in a file with tagged word with it. This file is read by ZigBee after regular interval. As it is a wireless communication, so ZigBee communicates with the control station where control station is also in the same network. Both control station and ZigBee is provided with an IP address by using this IP address ZigBee accesses the information from the control station.

F. Micro-Controller: PICF816XX & Arduino

ZigBee is connected to the PIC board through stackable pins as shown in Figure .When the process of communication starts; ZigBee tries to connect itself with the control station, with the provided IP address of the control station. As soon as ZigBee gets connected to the control station, it continuously sends the command signals to the receiver. These received signal values are then handed over to PIC which extracts command and calls which are specified for that command. PIC sends five digital signals as a component of the motor driver.

G. . DC Motors in Robot:

This is the robot's final product, which includes all of the hardware (ZigBee, PIC frame, and L293D motor driver circuit and the pick-and-place robot are mounted on the robot frame, which is driven by rechargeable batteries. As shown in Figure, Two DC motors are attached to the robot chassis. The user at the control station controls this with gestures..

7 CONCLUSION

A universal self-adaption workspace mapping approach is presented in this project. on Kinect to control a robot is presented. The position and orientation of the robot end point are controlled by extracting and calculating the shoulder, elbow, wrist, tip of index finger and thumb. First, to solve the problems that the human does not stand straight or do not keep the body facing the Kinect and the hand and the lower arm are not on the same plane, a modified coordinate of the human wrist is proposed. Then, in practical situations, the data of points-based Kinect joints may not be stable, leading to the dithering phenomenon in the control data. This paper introduces the Kalman filter to eliminate the previously mentioned dither. Different from traditional methods, to make the system adapt to different operators and robots in workspace, a SAW method is proposed, which uses the mapping quantity Q to automatically obtain the mapping matrix after some iteration processes. Then, experiments were conducted out, and an analysis of the results verified the feasibility and excellent performance of the universal control system. Afterwards, the universal control system is successfully applied to ademonstration of controlling a cooperative robot to pick-and-place. To better express our method, we compared our method with the method mentioned in the application section. Although errors of this method is slightly smaller than that method, our method is more general, which further demonstrates the practicability of the universal control system for HRI.

Further research will focus on the recognition and classification of human movements. The method of deep learning is used to train body movements in the video such as the clamp opening and closing and the robot movement. In this way, the system can control the robot more flexibly and accurately

REFERENCES

- [1] Chih-Hung Wu, Chang Hong Lin, ‘Depth-based hand gesture recognition used for home appliance control. The official journal of the International Society for Equity in Health 2013 15:64
- [2] Chueh-Wei Chang Chun-Hao Chang. ‘Hand Gesture Recognition with Several Points System Based on Adaptive Skin Color Model’. Aust J Prim Health. 2011;10:21–9
- [3] Utpall V. Solaki, Nilles H. Desai, Remote control of home appliances based on hand gestures: Hand mote 2011 Oct 10;17(10). pii: E2294. doi: 10.3390/s17102294.
- [4] Kuang-Yow Lian, Chun-Chieh Chiu, Yong-Jie Hong and Wen-Tsai Sung ‘wearable armband for real time hand gesture recognition’. (accessed on 15 february 2017).
- [5] Arathi p.n, s.arthika, s.ponmithra, k.srinivasan*, v.rukkumani. (2017). gesture based home automation system, 8(2-3), 73–272. <http://doi.org/10.1561/11000000049>
- [6] Jiaqing lin, hiroaki nishino, tsuneo kagawa, and kouichi utsumiya ‘a means of interacting with applications using two-handed gestures using commonplace devices in’ w. m. wells, a. colchester, and s. delp, editors, miccai’98: proc. 1st int’l conf. medical image computing and computer-assisted intervention, vol. 1496 of LNCS, pp. 934–943, Cambridge, MA, USA, Oct. 11-13 1998. Springer-Verlag. ISBN 3-540-65136-5(2014).
- [7] Manavender R. Malgireddy, Jason J. Corso, Srirangaraj Setlur, ‘A Framework for Recognizing and Spotting Hand Gestures Using Subspace-gesture Modeling’ E77-D(12):1321–1329, Dec2010.
- [8] Archana S. Ghotkar, 2Rucha Khatal , 3 Sanjana Khupase, 4 Surbhi Asati & 5Mithila Hadap, ‘Hand Gesture Recognition in Indian Sign Language’ E77-D(12):1321–1329, Dec2012