

# **Smart waste management using IoT to support “Swachh Bharat Abhiyan” – in shopping malls**

**Submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in Electronics and Communication Engineering**

by

**P.BHANUPRAKASH (37130296)**

**P.JAGADEESH (37130300)**



**DEPARTMENT OF ELECTRONICS AND COMMUNICATION  
ENGINEERING**

**SCHOOL OF ELECTRICAL AND ELECTRONICS ENGINEERING**

## **SATHYABAMA**

**INSTITUTE OF SCIENCE AND TECHNOLOGY  
(DEEMED TO BE UNIVERSITY)**

**Accredited with Grade “A” by NAAC**

**JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI - 600 119**

**APRIL - 2021**



# **SATHYABAMA**

**INSTITUTE OF SCIENCE AND TECHNOLOGY**

**(DEEMED TO BE UNIVERSITY)**

**Accredited "A" Grade by NAAC | 12B Status by UGC | Approved by AICTE**

**[www.sathyabama.ac.in](http://www.sathyabama.ac.in)**

---

## **DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING**

### **BONAFIDE CERTIFICATE**

This is to certify that this Project Report is the bonafide work of **P.BHANUPRAKASH (37130296)** and **P.JAGADEESH (37130300)** who carried out the project entitled "Smart waste management using IoT to support "Swachh Bharat Abhiyan" – in shopping malls " under my supervision from November 2020 to April 2021.

#### **Internal Guide**

**Ms.T.THAI MARY DELSY,M.E.,(Ph.D)**

#### **Head of the department**

**Dr. T. RAVI, ME., Ph.D.,**

---

**Submitted for Viva voce Examination held on\_\_\_\_\_**

**Internal Examiner**

**External Examiner**

## **DECLARATION**

WE, **P.BHANUPRAKASH (37130296)** and **P.JAGADEESH (37130300)** hereby declare that the Project Report entitled **Smart waste management using IoT to support “Swachh Bharat Abhiyan” – in shopping malls** done by me under the guidance of **Ms.T.THAJ MARY DELSY,M.E.,(Ph.D)** is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in ELECTRONICS AND COMMUNICATION ENGINEERING.

**DATE:**

**PLACE: CHENNAI**

**BHANUPRAKASH(37130296)**

**JAGADEESH(37130300)**

**SIGNATURE OF THE CANDIDATE**

## ACKNOWLEDGEMENT

I am pleased to acknowledge my sincere thanks to Board of Management of SATHYABAMA for their kind encouragement in doing this project and for completing it successfully. I am grateful to them.

I convey my thanks to **Dr. NANDHITHA, M.E., Ph.D.**, Dean, School of ELECTRONIC AND COMMUNICATION ENGINEERING & **Dr.T.RAVI,M.E.,Ph.D**, Head of the Department, Department of ELECTRONIC AND COMMUNICATION ENGINEERING for providing me necessary support and details at the right time during the progressive reviews.

I would like to express my sincere and deep sense of gratitude to my Project guide **Ms.T.THAJ MARY DELSY, M.E., Ph.D.**, for his valuable guidance, suggestions and constant encouragement paved way for the successful completion of my project work.

I wish to express my thanks to all Teaching and Non-teaching staff members of the Department of ELECTRONIC AND COMMUNICATION ENGINEERING who were helpful in many ways for the completion of the project.

## **ABSTRACT**

Squander the executives is an administration which can include in created nations as well as in the non-industrial nations

The general waste administration includes three primary sorts of substances: clients who produce squander, squander gatherers and city organization, partners. It is essential to have a reasonable method of overseeing waste, all together that not just the burn through status is advised in-time when to be gathered, yet in addition, every one of the partners are made mindful in ideal design that what kind of waste in the thing amount is emerging at what specific time.

It is indispensable to have a reasonable method of overseeing waste, all together that not just the burn through status is told in-time when to be gathered, yet additionally, every one of the partners are made mindful in opportune design that what kind of waste in the thing amount is emerging at what specific time.

The execution of keen trash the executives framework utilizing sensors, miniature regulators, WIFI module and with the assistance of engines, it guarantees the cleaning of garbage cans soon when the trash level arrives at its most extreme.

This diminish the unhygienic condition and dodges medical problems, here in the event of wet waste, we are changing it over to excrement, thus complete number of outings of trash pickup vehicle is decreased, accordingly generally speaking consumption identified with the garbage assortment additionally will be limit.

## **CONTENT**

| <b>CHAPTER<br/>NO.</b> | <b>TITLE</b>                               | <b>PAGE<br/>NO.</b> |
|------------------------|--------------------------------------------|---------------------|
|                        | <b>ABSTRACT</b>                            | <b>v</b>            |
|                        | <b>LIST OF FIGURES</b>                     | <b>vii</b>          |
|                        | <b>LIST OF TABLES</b>                      | <b>x</b>            |
| <b>1</b>               | <b>INTRODUCTION</b>                        | <b>1</b>            |
| <b>2</b>               | <b>LITERATURE SURVEY</b>                   | <b>2</b>            |
| <b>3</b>               | <b>AIM AND SCOPE</b>                       | <b>4</b>            |
| <b>4</b>               | <b>METHODS, ALGORITHMS AND MATERIALS</b>   | <b>5</b>            |
|                        | 4.1 EXISTING SYSTEM                        | <b>5</b>            |
|                        | 4.2 PROPOSED SYSTEM                        | <b>6</b>            |
|                        | 4.3 CIRCUIT DIAGRAM                        | <b>7</b>            |
|                        | 4.4 FLOW CHART                             | <b>8</b>            |
|                        | 4.5 HARDWARE USED                          | <b>8</b>            |
|                        | 4.5.1 NODEMCU                              | <b>8</b>            |
|                        | 4.5.2 TEMPERATURE SENSOR                   | <b>11</b>           |
|                        | 4.5.3 SMOKE SENSORS MODULE                 | <b>13</b>           |
|                        | 4.5.4 ULTRASONIC SENSORS                   | <b>14</b>           |
|                        | 4.5.5 PROXIMITY SENSORS                    | <b>15</b>           |
|                        | 4.5.5.1 OBJECTIVE                          | <b>15</b>           |
|                        | 4.5.5.2 NORMAL INFORMATION                 | <b>16</b>           |
|                        | 4.5.5.3 CLASSIFICATIONS                    | <b>17</b>           |
|                        | 4.5.5.4 TYPICAL USAGE                      | <b>18</b>           |
|                        | 4.5.5.5 TYPES                              | <b>20</b>           |
|                        | 4.5.6 METAL DETECTOR SELECTION<br>CRITERIA | <b>23</b>           |

| <b>CHAPTER<br/>NO.</b> | <b>TITLE</b>                       | <b>PAGE<br/>NO.</b> |
|------------------------|------------------------------------|---------------------|
|                        | 4.5.6.1 PROTECTION CLASSES         | 24                  |
|                        | 4.6 SOFTWARE USED                  | 25                  |
|                        | 4.6.1 ARDUINO IDE PROGRAMMING      | 25                  |
|                        | 4.6.2 OVERVIEW                     | 25                  |
|                        | 4.6.3 ARDUINO SOFTWARE(IDE)        | 27                  |
|                        | 4.6.4 WRITING SKETCHES             | 27                  |
|                        | 4.6.4.1 FILE                       | 29                  |
|                        | 4.6.4.2 EDIT                       | 30                  |
|                        | 4.6.4.3 SKETCH                     | 31                  |
|                        | 4.6.4.4 TOOLS                      | 32                  |
|                        | 4.6.4.5 HELP                       | 33                  |
|                        | 4.6.4.6 UPLOADING                  | 33                  |
|                        | 4.6.4.7 LIBRARIES                  | 33                  |
|                        | 4.6.4.8 LANGUAGE SUPPORT           | 34                  |
|                        | 4.6.4.9 SERIAL MONITORING          | 34                  |
|                        | 4.6.5 UBIDOTS EXPLORER             | 35                  |
|                        | 4.6.5.1 INTRODUCTION               | 35                  |
|                        | 4.6.5.2 DEMO DASHBOARD             | 36                  |
|                        | 4.6.5.3 API CREDENTIALS            | 37                  |
|                        | 4.6.5.4 DEVICES IN UBIDOTS         | 37                  |
| <b>5</b>               | <b>RESULT &amp; DISCUSSION</b>     | <b>38</b>           |
| <b>6</b>               | <b>CONCLUSION AND FUTURE SCOPE</b> | <b>42</b>           |
|                        | <b>REFERENCES</b>                  | <b>43</b>           |

## LIST OF FIGURES

| FIGURE<br>NO. | FIGURE TITLE                                       | PAGE NO.  |
|---------------|----------------------------------------------------|-----------|
| 4.1           | EXISTING SYSTEM BLOCK DIAGRAM                      | 5         |
| 4.2           | PROPOSED SYSTEM BLOCK DIAGRAM                      | 6         |
| 4.3           | CIRCUIT DIAGRAM                                    | 7         |
| 4.4           | FLOW CHART                                         | 8         |
| 4.5           | PIN OUTS OF NODEMCU                                | 9         |
| 4.6           | EXPLANATION OF NODEMCU                             | 10        |
| 4.7           | DHT11 SENSOR                                       | 12        |
| 4.8           | GAS SENSOR                                         | 13        |
| 4.9           | ULTRASONIC SENSOR                                  | 14        |
| 4.10          | PROXIMITY SENSOR SETUP TABLE                       | 15        |
| 4.11          | DETECTING AN OBJECT EXISTS IN AN DEFINED<br>OBJECT | 18        |
| 4.12          | POSITIONING OF AN OBJECT                           | 18        |
| 4.13          | COUNTING THE NO OF PARTS                           | 18        |
| 4.14          | DETERMINING THE ROTATIONAL SPEED                   | 19        |
| 4.15          | DETERMINING THE LINEAR SPEED                       | 19        |
| 4.16          | SELECTION CRITERIA                                 | 23        |
| 4.17          | ARDUINO IDE LABEL                                  | 26        |
| 4.18          | LOOKING OPENED PORTION OF IDE                      | 26        |
| 4.19          | REQUIRED FOR IDE                                   | 27        |
| 4.20          | SKETCH CONTAINER                                   | 27        |
| 4.21          | FILE CONTAINER                                     | 29        |
| 4.22          | EDIT CONTAINER                                     | <b>30</b> |
| 4.23          | SKETCH CONTAINER                                   | 31        |
| 4.24          | TOOL CONTAINER                                     | 32        |
| 4.25          | HELP CONTAINER                                     | 33        |
| 4.26          | LANGUAGE SUPPORT                                   | 34        |
| 4.27          | SERIAL MONITOR                                     | 35        |
| 4.28          | UBIDOTS DATA HIERACHY                              | 35        |

| <b>FIGURE<br/>NO.</b> | <b>FIGURE TITLE</b>            | <b>PAGE NO.</b> |
|-----------------------|--------------------------------|-----------------|
| 4.29                  | DASH BOARD                     | 36              |
| 4.30                  | INFORMATION OF API             | 37              |
| 4.31                  | DEVICES LIST                   | 37              |
| 5.2                   | BIN LEVEL DETECTION            | 38              |
| 5.4                   | IR SENSOR FOR MOTION DETECTION | 39              |
| 5.6                   | SMOKE DETECTION                | 39              |
| 5.8                   | METAL DETECTOR                 | 40              |
| 5.10                  | DHT11 SENSOR                   | 40              |
| 5.12                  | OVER ALL SENSORS               | 41              |
| 5.13                  | CLOUD SAVING                   | 41              |

## LIST OF TABLES

| TABLE<br>NO. | TABLE TITLE                                 | PAGE<br>NO. |
|--------------|---------------------------------------------|-------------|
| 4.1          | CONFIGURATION OF DHT11                      | 12          |
| 4.2          | FEATURES OF MQ2                             | 14          |
| 4.3          | PROTECTION AGAINST DUST & FORCED<br>CONTACT | 24          |
| 4.4          | PROTECTION AGAINST WATER                    | 24          |

# **CHAPTER 1**

## **INTRODUCTION**

As the world is during a phase of up degree, there's one smelling issue we've to influence . Trash! In our way of life , we see the photos of trash canisters being overfull and each one the refuse pours out. This outcomes in the measure of sicknesses as sizable measure of bugs and mosquitoes breed there on . A tremendous test inside the metropolitan urban communities is strong waste administration not just in India aside from the vast majority of the nations inside the world. Thus, such a framework must be assemble which may annihilate this issue or at least diminish it to the base level. The task gives us one among the chief proficient approaches to remain our environmental factors perfect and green. The brilliant city idea stays new in India, despite the fact that it's gotten huge loads of consideration in couple of years when our current head administrator gave the possibility of building 100 shrewd urban areas all through India. Presently, with the impending sizable measure of keen urban communities, enormous quantities of duties additionally are needed to be satisfied. The great need of a reasonable way of life starts with neatness and tidiness starts with dustbin. A general public will get its waste dispatched appropriately as long as the dustbins are set well and gotten well. the most issue inside the current waste administration framework in a large portion of the Indian urban communities is that the unfortunate status of dustbins.

In this task we've done to overhaul the trifling yet imperative segment of the metropolitan waste administration framework, for example dustbin. Presently with the increment of innovation it's time that we ought to consistently utilize innovation for squander the executives frameworks. As we've seen that innovation with investigation has made the planet an obviously better spot to quantify by its application inside the field of hereditary qualities, protection, promoting, designing, banking and so forth in past a couple of years . Thus, during this undertaking I've incorporated investigation and hardware in order to roll out ideal improvements inside the ordinary procedure of waste assortment with the gigantic measure of information that is being delivered by the keen canister organizations.

## **CHAPTER 2**

### **LITERATURE SURVEY**

Tejashree Kadus, Pawankumar Nirmal, Kartikey Kulkarni 2020 executed Keen Waste Administration Framework utilizing IOT. The paper depends on the idea of Robotization utilized in squander the board framework under the area of Neatness and Cleanliness. Unloading trash onto the roads and in open zones is a typical summary found in every single agricultural nation and this chiefly wind up influencing the climate and making a few unhygienic conditions. To manage these issues Brilliant netbin is a philosophy advanced which a blend of equipment and programming innovations is for example associating Wi-Fi framework to the ordinary dustbin to give free web offices to the client for a specific timeframe.

Shivam Jagtap, Aditya Gandh, Raviraj Bochar, Ashwinkumar Patil. 2020 executed Waste Administration Improvement in Urban communities utilizing IoT. Trash assortment is quite possibly the most basic issues looked by Civil Enterprise. While executing the waste administration in urban communities the greatest test is the administration of waste in cost ideal manner with superior. The current interaction of gathering the waste, isolating it and moving the compartments regular which is a muddled cycle. This paper manages the idea of waste administration and the shrewd framework for squander the board with higher advantages to the general public.

Chitluri Sai Srikanth, Tadivaka Bhupathi Rayudu, Javvaji Radhika, Raju Anitha 2020 Keen Waste Administration utilizing Web of-Things. To stay away from each such condition, we intend to propose a response for this issue "Sharp Trash Canister", which will ready and set up the kept up person when the waste compartment will fill. By then message will be ship off the understood individual to accumulate the difficulty from the particular domain. The declared individual will send the message from his web application to the waste experts by sending a SMS. In this endeavor we use strain check to know the robbery of the report. This will lessen the surge of the waste compartment and reasonably keeping nature clean.

Web of Things: Difficulties and condition of-the-art arrangements in Web scale Sensor Data The board and Versatile examination by Arkady Zaslavsky, Dimitrios Georgakopoulos. 2019 This paper gave us the insights regarding versatile investigation and sensor data the board that will help in information isolation of different dustbins.

City Trash assortment pointer utilizing RF(Zigbee) and GSM innovation. 2019 This paper gave the subtleties for the module needed for the transmission of the information to the recipient side and furthermore the principle channel follow of the venture. At first we utilized GSM innovation for our venture yet later on chose to us Wi-Fi module for the simplicity of information transmission.

Top-k Question based powerful booking for IoT-enabled little city squander assortment by Theodoros Anagnostopoulos, Arkady Zaslavsky, Alexey Medvedev, Sergei Khoruzhnicov 2019. This paper discloses to us the idea of dynamic planning needed for the cleaning of dustbin and the Top-k question drove us to need based cleaning of dustbins

Jeet Shah<sup>1</sup>, Abhijeet Patil<sup>2</sup>, Prasad Nanavare<sup>3</sup>, Vineet Patidar<sup>4</sup>, Prof. H. A. Bhute<sup>5</sup> 2019 executed Brilliant CITY Squander The executives Framework Utilizing IOT As the number of inhabitants in world is expanding step by step, the climate ought to be spotless and sterile for our better life leads. Squander the board is one of the essential issue that the world faces independent of the instance of created or non-industrial nation. In the majority of the urban areas the flooded trash receptacles are making an offensive smell and making an unhygienic climate. Also, this is prompting the fast development of microbes and infections which are causing various kinds of illnesses. To defeat these circumstances productive trash assortment frameworks are getting created dependent on IOT. In this paper, we move and propose a Web of Things (IOT) utilizing Trash Checking And Waste Administration Framework For Shrewd Urban communities.

## **CHAPTER 3**

### **AIM AND SCOPE**

Point of the current work is to develop a savvy squander the board framework for supporting the districts and furthermore the executives who are under this segment. In our undertaking, NODEMCU is the core of our task and all sensors are associated with the NODEMCU for controlling. Ultrasonic sensor is utilized to quantify the level of the dustbin. Smoke sensor is to distinguish the degree of poisonous gasses. DHT11 is utilized to quantify the temperature and stickiness of the dustbin if any fire is identified. Metal identifier is utilized to distinguish the metal article like bombs with in the scope of 3000. Servo engine is utilized to lift the top of dustbin. Movement sensor is utilized to distinguish the article inside the scope of 30 cm to offer directions to the servo engine to open the cover of the dustbin.

## CHAPTER 4


### METHODS,ALGORITHMS AND MATERIALS

#### 4.1 EXISTING SYSTEM:

- In a smart bin using some kind of sensor like gas sensor and Ultrasonic sensor is used to identify the bin is filled or not and any dangerous gasses having.
- If it is filled means it sends message to garbage management contractor or office in IOT technology or GSM based technology.
- This bin can separates dry waste, wet waste and e-waste.


#### Disadvantages

- Metal detection is not available.
- Temperature sensing is not available.
- Motion detection to open the lid of dustbin also not available.



**Fig 4.1 EXISTING BLOCK DIAGRAM**

#### 4.2 PROPOSED SYSTEM:




**Fig 4.2 PROPOSED BLOCK DIAGRAM**

Here the NODEMCU is the core of this task, here in the above graph every one of the sensors are associated with the NODEMCU for controlling the whole capacities. This will send sms to the administration when the dustbin was full and any metal discovery.

- In this proposed framework it separates the loss into dry waste, wet waste and e-squander
- Using ultrasound sensor used to distinguish the degree of waste in trash container. At the point when the canister loaded up with half at that point ready messages ship off the ward part, and it will loaded up with 90% the alarm message ship off the public authority.
- The container is ceaselessly checking the degree of trash if it's full methods it offers alarm to the executives in shopping center. At the point when an enterprise separate the loss for reuse measure.
- After the reusing cycle is finished when an administration association offers warning to some corporate organization, NGO and so forth
- It is additionally have another benefit to decrease natural contamination and it increment the monetary help in government association.
- Benefits
- Metal identifier is accessible.
- Temperature and stickiness sensor is accessible.

- Motion recognition to open the cover of dustbin is additionally accessible.


#### 4.3 CIRCUIT DIAGRAM



**Fig 4.3: CIRCUIT DIAGRAM**

The force supply pins of all mixtures are associated with the force source in NODEMCU and the ground pins of the relative multitude of mixtures are associated with the ground of the force source. The advanced pins of all parts are associated with every one of the necessary computerized pins. The simple pin is likewise associated with the necessary simple in the NODEMCU. Here in this circuit chart the all sensors are trustworthy to the miniature regulator. So that implies every one of the sensors work under the miniature regulator. The smoke sensor will work like detecting the destructive gases and refreshed in the cloud. While in the temperature and dampness sensor will work like that with fire identification. As like the metal indicator additionally be same like recognizing any metals over 3000 degree of metal. In the event that any like that it will caution the individual who is dealing with. As the fundamental sensor is utilized in my task that is ultrasonic sensor is utilized to recognize the degree of residue container by utilizing vibration signals. IR sensor will function as like recognizing warm warmth created our body, by identifying that the IR sensor will attempt to lift the top of the dustbin with the assistance of servomotor.

#### 4.4: FLOW CHART:



**Fig 4.4: FLOW CHART**


#### 4.5 HARDWARE USED:

- NODEMCU
- ultrasonic sensor
- DHT11 sensor
- smoke sensor
- metal detector

##### **4.5.1 nodemcu:**

In nodemcu having the esp8266 wifi module which can be used as transferring the information from connected components to the cloud server with the help of RISC processor. As in the market it is very cheap and sensitivity, if any one of the pin is gone the total esp8266 will be damaged and not further used in the experiments or in iot's. It has the usb port which is used to dump the code by using usb cable.

Actually the golden lines, which is on the nodemcu is behaving as an antenna. It has only one analog pin which is used for analog sensors like metal detector which we used in the project. Also having 8 digital pins which is used for digital sensors. The nodemcu is same like arduino but not fully similar, the performance of nodemcu is lesser than the arduino. Actually nodemcu is a development board which can access many inputs upto 4 at a time. Nodemcu has 4mb of flash memory which is used to store large data at a time. The range of temperature of nodemcu -40-125 degrees.



**Fig 4.5 PIN OUTS OF NODEMCU**

NodeMCU ESP8266

NodeMCU ESP8266 Pinout


NodeMCU Improvement Board Pinout Setup

NodeMCU ESP8266 Particulars and Highlights

Microcontroller: Tensilica 32-bit RISC computer processor Xtensa LX106

- Operating Voltage: 3.3V
- Input Voltage: 7-12V
- Digital I/O Pins (DIO): 16
- Analog Information Pins (ADC): 1
- UARTs: 1

- SPIs: 1
- I2Cs: 1
- Flash Memory: 4 MB
- SRAM: 64 KB
- Clock Speed: 80 MHz
- USB-TTL dependent on CP2102 is incorporated installed, Empowering Fitting n Play
- PCB Recieving wire
- Small Estimated module to fit shrewdly inside your IoT projects



**Fig 4.6 EXPLANATION OF NODE MCU**

#### Programming Nodemcu ESP8266 with Arduino IDE

The Nodemcu Development Board are often easily programmed with Arduino IDE since it's easy to use.

Programming Nodemcu with the Arduino IDE will scarcely require 5-10 minutes. All you would like is that the Arduino IDE, a USB link and therefore the NodeMCU board itself. you'll check this Getting Began Instructional exercise for NodeMCU to line up your Arduino IDE for NodeMCU.

## Transferring your first program


When Arduino IDE is introduced in PC, interfacing the board with the help of PC utilizing the USB link. If you want to work with ide we have to ready for choosing Tools>Boards>NodeMCU1.0 (ESP-12E Module), and pick the right Port by choosing Tools>Port. To kick it off with the NodeMCU board and flicker the inherent Drove, load the model code by choosing Files>Examples>Basics>Blink. When the model code is stacked into your IDE, click on the 'transfer' button given on the top bar. When the transfer is done, you should see the implicit Drove of the board flickering. Utilizations of NodeMCU

### Uploading of the program in nodemcu

When the program is injecting in nodemcu, the inbuilt blue led will blink continuously. After that the led will stops blinking and set ready to control the entire sensors connected to it.

#### **4.5.2 TEMPERATURE SENSOR**

In each and every machine,electronics,body temperature and environmental temperatures, the high temperatures are regular in these usages. Hence the humans created the detection of temperature that can sense how much temperature that the thing is producing in each and every minute. In certain cases the sensing/detecting of temperature is more when we compare to the previous one which was invented at the year of 1952 the thermometer by galileo. Later and all the sensors came by using current or battery. Here in this project we used DHT11 sensor which can sense the temperature and humidity simultaneously. It has 3 pins, one is vcc at 3.3 - 5v, the second one is data pin also called as digital pin which can transfer the information of detecting temperature and humidity as well. The another one is the ground which is very important for not to short circuit the device it will protect when high and low currents occurs. It also having led which can says that the device is in working condition or not.



**Fig 4.7 DHT11 sensor**

**Table 4.1 configuration of dht11**

**Pin Identification and Configuration:**

| No:                            | Pin Name | Description                                               |
|--------------------------------|----------|-----------------------------------------------------------|
| <b>For DHT11 Sensor</b>        |          |                                                           |
| 1                              | Vcc      | Power supply 3.5V to 5.5V                                 |
| 2                              | Data     | Outputs both Temperature and Humidity through serial Data |
| 3                              | NC       | No Connection and hence not used                          |
| 4                              | Ground   | Connected to the ground of the circuit                    |
| <b>For DHT11 Sensor module</b> |          |                                                           |
| 1                              | Vcc      | Power supply 3.5V to 5.5V                                 |
| 2                              | Data     | Outputs both Temperature and Humidity through serial Data |
| 3                              | Ground   | Connected to the ground of the circuit                    |

#### **4.5.3 smoke sensor module**

The smoke sensor is the sensor which can sense the dangerous hazard gasses produced by the waste food, leaking chemical gasses and so..on. As like that the main feature in gas sensor is the methane sensing.when it detect the huge amount of methane it sense the signal to the microcontroller which can control all the components connected to it.

The top of the smoke sensor is protected by the metal which cannot break when it fell down unfortunately. Actually the smoke sensor having four pins that are

The first one is vcc(voltage), the second one is analog I/p, the third one is digital input, and the fourth one is ground. All this four pins are different in performance.

The required voltage for operating the sensor is about 5 volts. The range of sensing is 0.04 mg/l to 4 mg/l.

All the gas sensors having difference in performance and ranging level.



**Fig 4.8 GAS SENSOR**

**Table 4.2 features of mq2**

Here are the complete specifications

|                     |                               |
|---------------------|-------------------------------|
| Operating voltage   | 5V                            |
| Load resistance     | 20 K $\Omega$                 |
| Heater resistance   | 33 $\Omega \pm 5\%$           |
| Heating consumption | <800mw                        |
| Sensing Resistance  | 10 K $\Omega$ – 60 K $\Omega$ |
| Concentration Scope | 200 – 10000ppm                |
| Preheat Time        | Over 24 hour                  |

#### **4.5.4 Ultrasonic (UV) Sensors or Ultrasound Sensors**

Generally ultrasonic sensors are used for detecting the objects by producing sounds from the sensor. The ultrasonic sensor will demand lot of energy when it creates a sound. In this the ultrasonic sensor having 4 pins which are useful for sound generating and sound receiving from their inputs and outputs. In this trig is the sound creating and the echo is the sound receiving. When the trig generate the sound to the ground and that sound goes through the transmitter and it gets some of the information at what range it got reflected and that signal I received by the echo the receiver. The performance of the ultrasonic sensor will work under that method.. the range of sensing is 30cm. Which is to detect nearest object.



**Fig 4.9 ULTRONIC SENSOR**

## 4.5.5 PROXIMITY SENSORS


### 4.5.5.1 OBJECTIVE

Expanding mechanization of complex creation frameworks requires the utilization of segments which are fit for obtaining and sending data identifying with the creation interaction. Sensors satisfy these prerequisites and have subsequently over the most recent couple of years become progressively significant parts in estimating and in open and shut circle innovation. Sensors give data to a regulator as individual cycle factors.

Vicinity sensors are the most essential information procurement gadgets in mechanization. They measure/identify actual info like temperature, pressure, power, length, and closeness of an article. Transducers are commonly a sensorial framework fit for signal preparing, furnished with electronic instrumentation. Position sensors give a "yes" or "no" reaction as per the spot of the item.

The point of this analysis is to delineate the parts of various sorts of

vicinity sensors, their properties, and to analyze them. For this, an arrangement table containing Attractive, Inductive, Capacitive, and Optical sensors is utilized. A situating slide combined with a vernier caliper is utilized to quantify exchanging distances.



**Fig 4.10: Proximity sensors setup table**

#### 4.5.5.2 *NORMAL INFORMATION*

Sensors are the first of the four achievements of Mechanization:

1.Sensing

2.Signal Preparing

3.Planning and Reaction

4.Memory

They as a rule convert some actual information into a voltage contrast for additional preparing by a PC, PLC or I/O Card. The upsides of nearness sensors are:

- They decide the mathematical positions consequently and delicately.
- They don't need of an immediate contact with the workpiece.
- They don't have mobile parts that can wear out.
- They are generally furnished with electronic circuits for disappointment security.
- They have different sorts that can be utilized under various circumstances.
- They give the safe working of the cycle.
- They are utilized for the framework disappointment investigation.

Their regular use regions are:

- Automotive industry,

- Packaging industry,
- Printing and paper industry
- Ceramic industry
- Wood-working industry
- Food preparing industry

#### 4.5.5.3 Classifications

As indicated by I/O handling:

Binary: Convert an actual estimation worth to a twofold code (as ON/OFF signals in a chose voltage range)


Analog: Convert an actual estimation into a simple sign (for example temperature readings to variable voltage contrasts)

As per actual contemplations:

- Mechanical switches
- Magnetic (with/without contacts, pneumatic yield)
- Inductive (inductive sensors)
- Capacitive (capacitive sensors)
- Optical (light obstructions, reflection sensors)
- Ultrasonic (ultrasonic obstructions, ultrasonic sensors)
- Pneumatic (back-pressure spouts, air reflection sensors, air obstructions)


#### 4.5.5.4 TYPICAL USAGE

Detecting whether an object exists in a defined position;




**Fig 4.11 Detecting whether an object exists in a defined position**

Positioning of an object:




**Fig 4.12 Positioning of an object**

Counting the number of parts:




**Fig 4.13 Counting the number of parts**

Determining the rotational speed:



**Fig 4.14 Determining the rotational speed**

Determining the linear speed:



**Fig 4.15 Determining the linear speed**

#### 4.5.5.5 TYPES

##### Mechanical switches:

Mechanical switches are basic GO/NoGO pointers. They have actual contact with the article, generally combined with transfers and contactors to drive a circuit. Broadly utilized in the business to check the end-start points of chambers, cylinders, straight and rotational drives, to detect entryways. They are less delicate and have lower most extreme exchanging recurrence contrasted with nearness switches. In light of the actual contact with the article, they require support and substitution.

##### Attractive Closeness Switches:

Attractive switches (likewise called as Reed-contacts) utilize the bending of the attractive field. In the event that a ferromagnetic material (Fe-Ni compound) comes nearby, the attractive field misshapes and gives a contribution to the switch. Along these lines, they are simply touchy to ferromagnetic materials and attractive fields. Earth and stickiness is of little significance. They protect high hysteresis (undefinite scope of actual information). They are generally utilized two by two of machine parts, for example, cylinder chamber game plans.

##### Inductive Nearness switches:

Inductive vicinity switches additionally work on the standards of attractive fields and enlistment. They reaction to conductive materials, normally metals. The plain information on exchanging distance relies upon gentle steel (typically Fe37); consequently, a decrease coefficient should be characterized for various metals. For the metals like Cr-Ni, metal, aluminum, and copper this worth should be altered with the trial decrease coefficient discovered for the most part in the scope of 0.25-0.9. Additionally the decrease coefficient relies upon the size of the deliberate item. They are generally utilized in the large scale manufacturing lines

and transports to identify metallic workpieces, moving pieces of apparatus, for estimating straight, rotational rates, presses, and encoders.

#### Capacitive Nearness switches:

In contrast to the attractive and inductive sorts, capacitive vicinity changes reaction to a wide range of materials. The decrease coefficient is resolved tentatively in the scope of 0.1 to 1 (metals =1 and water =1). Note that fluids can likewise be distinguished by capacitive switches. They are touchy to ecological factors like residue, soil and dampness. Subsequently they can be utilized to recognize object properties like tone, thickness, water section tallness, and vibration. Test application territories are underway lines and transports to tally workpieces, sense bundling abandons and so forth

#### Optical Nearness switches:

Optical nearness switches utilize the presence of noticeable (with frequency of 660nm - red-) or undetectable (with frequency of 880nm - super red-), light for input. They give a NPN or PNP yield to the circuit. Here, rather than the decrease coefficient the activity save is characterized as the proportion of sign power in the contribution of the sensor to the necessary force for exchanging. Note that in right working conditions, activity hold should have an estimation of more prominent than one. The activity save relies upon surrounding conditions like residue, earth, encompassing light tone and power, distance from part, reflect-point and so forth

#### Optical sensors are separated into two primary parts:

Light sensors (can be outfitted with fiber-optic cabling for significant distance transmission, may utilize surrounding light or the light delivered in a coupled unit)

Reflected light sensors (can be outfitted with fiber-optic cabling for significant distance transmission, utilizes the mirrored light created in a similar unit from the part or a reflector sheet)

Optical sensors have a generally more noteworthy exchanging distance. Along these lines they might be utilized in distinguishing surface inconsistencies, disappointment identification, recognition of transmissive surfaces, colors and so on Fiber optic cabling for transmission additionally gives an adaptability to utilize little units at troublesome areas.

Ultrasonic Closeness switches:

They utilize the reflected sound force for input. Note that over the sensors expressed here, ultrasonic nearness switches have the best exchanging distance and recurrence. Consequently, they are utilized to recognize inaccessible articles with extremely high velocities. They are generally heartless toward encompassing conditions and ought to be liked in exceptionally outrageous conditions, while they are pricey.

Pneumatic Closeness switches:


They utilize the reflected back-pressure provided from a spout at or inaccessible from the switch unit. By and large liked in the space of:

- Very messy and dusty spots,
- At high temperatures,
- In the area of touchy materials where electrical flows might be perilous,

At places where escalated attractive fields are available, nearby huge engines, siphons, turbines and so forth

The sensor unit and spout unit might be implicit one bundle or as various units. Can be utilized to drive a pneumatic cylinder straightforwardly.

#### 4.5.6 metal detector selection criteria



**Fig 4.16 SELECTION CRITERIA**

#### 4.5.6.1 protection classes

The protection classes of the mechanical elements are defined in DIN 40050. For example, IP67 represents a device with protection against contact and foreign material according to 6 (Table A1) and against water and humidity according to 7 (Table A2).

**Table 4.3: Protection against dust & forced contact.**

| First digit | Protection Class                                                                                                                                                                                        |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 0           | No special protection                                                                                                                                                                                   |
| 1           | Protection against solid objects larger than 50 mm diameter. Unprotected against forced contacts (eg. via hand). Should be kept apart from the body                                                     |
| 2           | Protection against solid objects larger than 12 mm diameter. Should be kept apart from the fingers                                                                                                      |
| 3           | Protection against solid objects larger than 2.5 mm diameter. Should be kept apart from the devices (wire, hand tools etc.)                                                                             |
| 4           | Protection against solid objects larger than 1 mm diameter. Should be kept apart from the devices (wire, hand tools etc.)                                                                               |
| 5           | Protection against hazardous dust accumulation. Dust protection is not totally achieved, but inner dust accumulation does not affect functioning of the device. Full protection against forced contact. |
| 6           | Full protection against dust accumulation. Full protection against forced contact.                                                                                                                      |

**Table 4.4: Protection against water**

| Second digit | Protection Class                                                                                 |
|--------------|--------------------------------------------------------------------------------------------------|
| 0            | No special protection                                                                            |
| 1            | Protection against vertically tipping water. The water has no hazardous effects (tipping water). |

|   |                                                                                                                                                       |
|---|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2 | Protection against vertically tipping water at 15 ° to the normal of the device surface. The water has no hazardous effects (inclined tipping water). |
| 3 | Protection against water tipping at 60° to the normal of the device. The water has no hazardous effects (sprinkling water)                            |
| 4 | Protection against water from any direction to the device. The water has no hazardous effects (flowing water)                                         |
| 5 | Protection against water from a nozzle coming from any direction to the device. The water has no hazardous effects (flowing water)                    |
| 6 | Protection against water forced water coming from any direction to the device. The water has no hazardous effects (forced water)                      |
| 7 | Protection against water in case of immersion at certain pressure for a specific time Leakage of the water into the device is avoided.                |
| 8 | Full protection against water in case of immersion for a predetermined period of time (permanent immersion).                                          |

#### 4.6 SOFTWARE USED ARE:

- Arduino IDE
- Embedded C
- UBIDOTS

##### **4.6.1 Arduino IDE programming**

The arduino ide is only for c and c++ with special indication of structures with required libraries of the functions.

##### **4.6.2 Overview**

The overview of the arduino ide is, it has the special boards which can required for our project or for sake. All The special types of boards are included in the board manager. From that board manager we can install the required board what we need at present. It has the libraries which can control the board of features in it or for the components we need.

For example/: for dht11sensor we need to install dht library from manage library, it is located in sketch>include library.

This is what the Arduino IDE resembles.



**Fig 4.17 Arduino IDE label**

In arduino ide they are having different types of tools which can conform the component is suitable for ide in their range.



**Fig 4.18 looking opened portion of ide**


### 4.6.3 Arduino Software (IDE)



**Fig 4.19 required for ide**

The Arduino Coordinated Improvement Climate - or Arduino Programming (IDE) - contains a word processor for composing code , a message region, a book reassurance, a toolbar with catches for basic capacities and a progression of menus. It associates with the Arduino and Genuino equipment to transfer programs and speak with them.

### 4.6.4 Writing Sketches



**Fig 4.20 sketch container**

In this sketch the extension of the saved file will be in .ino form. Which can sense that directly open to its arduino ide application.



### *Verify*

Checks your code for errors compiling it.



### *Upload*

Compiles your code and uploads it to the configured board. See uploading below for details.

Note: If you are using an external programmer with your board, you can hold down the "shift" key on your computer when using this icon. The text will change to "Upload using Programmer"



### *New*

Creates a new sketch.



### *Open*

Presents a menu of all the sketches in your sketchbook. Clicking one will open it within the current window overwriting its content.

Note: due to a bug in Java, this menu doesn't scroll; if you need to open a sketch late in the list, use the File | Sketchbook menu instead.



### *Save*


Saves your sketch.



### *Serial Monitor*

Opens the serial monitor.

#### 4.6.4.1 File




**Fig 4.21 file container**

In this file container having new,open,open recent,sketch book, examples,close,save,save as, page setup,print, preferences and quit

- In new the new file will be opened
- In open the saved file will be opened
- In open recent the recent files will be opened
- In sketch book the running program block will display
- In examples the tested codes will be done
- The close is used to close the present block of the ide
- The save is used to save the file in the .ino format
- The save as is used to save the new file in .ino format
- The page setup is used to set up the page in required format
- The print is used to print the code
- The quit is used to close the ide

#### 4.6.4.2 Edit




**Fig 4.22 edit container**

In this edit container it contains the editable things which is very useful for programming.

- The undo is used to retrieve the information of deleted one
- The redo is used to retrieve the information one by one
- The cut is used to transfer the information from one place to another
- The copy is used to duplicate the information
- The paste is used to fill the document or the program
- The comment and uncomment is used to declare the used things
- The increase font size is used to increase the size of letters
- The decrease font size is used to decrease the size of letters
- The find is used to find the highlighted letters
- The find next is used to find the next highlighted letters
- The find previous is used to find the previously highlighted letters

#### 4.6.4.3 Sketch




**Fig 4.23 sketch container**

In this the main instructions can be done

- The verify/compiler is used to verify the program which is written in editor
- The upload is used to upload the program to the specified microcontroller
- The upload using programmer is used to upload the program with right things
- The include library is the one which can allow sensors to access
- The add file I used to add the files of simulated one

#### 4.6.4.4 Tools




**Fig 4.24 tools container**

In this tools are the main things in ide

- The auto format is used to generate the format in automatically
- The manage libraries are the one use to manage the library of sensors
- The serial monitor is used to monitor the things happening with all the sensors which is connected through usb
- The remaining all are the board equipments
- The burn bootloader is used to load the software if any error occurs

#### 4.6.4.5 Help



**Fig 4.25 help container**

In this the help is used if you don't know how to use it and errors troubleshooters

#### 4.6.4.6 Uploading

The Uploading is used to upload the file of the program in a specific connected micro controller


If you want to upload the program from ide just connect the micro controller to the laptop that can be used to access the micro controller through the port enable. Then the uploading of your program will be done by clicking upload button

#### 4.6.4.7 Libraries

The libraries are the main functions used in programming with c,c++ and also for accessing the outer sensors

Actually the libraries are the things used in all conditions.

#### 4.6.4.8 Language Support




**Fig 4.26 language support in IDE**

Many languages are supportable by the ide but the default one is english.

#### 4.4.4.9 serial monitoring

In this serial monitoring the update of the sensors and its values will be seen in this. So that for the monitoring purpose we will be seeing this dialog box.

It will works when the usb port is connected to the microcontroller.




**Fig 4.27 serial monitor**

### **4.6.5 UBIDOTS EXPLORER:**

#### **4.6.5.1 Introduction**

The ubidots are the cloud storage which will save all the information of the connected components

In this the ubidots are having the access of different sources like HTTP,chrome,edge etc.




**Fig 4.28 UBIDOTS DATA HIERACHY**

Each dot contains these items:

| Item      | Description                                                                     | Mandatory |
|-----------|---------------------------------------------------------------------------------|-----------|
| value     | Here in the ubidots it can access only 16 floating points                       | YES       |
| timestamp | If the time in not in milliseconds then the servers will goes on one to another | NO        |
| context   | It is used to store the location of places with data                            | NO        |

#### 4.6.5.2 Demo dashboard:




**Fig 4.29 dashboard**

In this demo dashboard consists of demo tools given automatically when you created the ubidots account. It is in data when we press the down symbol on the data the dashboard is shown in that

We can also create the new dashboard by any of our name keeping device variables as our project

Actually ubidots is mainly for iot devices, so all the iot sensors can be added to this dashboard in devices.


#### 4.6.5.3 API credentials



**Fig 4.30 information of API**

In this api credentials the api token key is available which is used for our project to update the information of the sensors and any other connected to it by program  
With out this token sensors don't update any of the information to the cloud

#### 4.6.5.4 Devices in ubidots



**Fig 4.31 devices list**

In this device list we can add many no of devices which is used for IOT projects  
In the above diagram there is my device list which is included in it that is the present using device list for our project

## CHAPTER 5

### RESULT & DISCUSSION


In this the nodemcu is the miniature regulator which can handle every one of the sensors all at once. Which implies that the sensors should interface with the hub mcu for controlling. Here In ultrasonic sensor which can detect the trash level, that implies the degree of sign of the canister up to 30cm.

The smoke sensor is utilized to identify the harmful level brought about by the wet waste. In this IR sensor is utilized for recognizing the movement of the body that implies dependent on the warm of our body. Metal finder is utilized to recognize the metals which is inside the receptacle at the scope of 3000 at least level max level up to 10000.




**Fig 5.1 BIN LEVEL DETECTION**

Here in this sensor it detects the level of waste using ultrasonic vibrations and the monitored readings sent to the cloud.




**Fig 5.2 IR SENSOR FOR MOTION DETECTION**

In this IR sensor it detects the motion of the object by using thermal heat inside our body. In our project i used it to lift the lid of the dustbin using servo motor.




**Fig 5.3 SMOKE DETECTION**

It is a sensor used to detect the harmful gasses caused by the wet waste, e waste and sent the alert message to the registered mail or number.




**Fig 5.4 METAL DETECTOR**

This will detects the metal which is above 3000 at range level




**Fig 5.5 DHT11 SENSOR**

This sensor is used to detect the temperature and humidity when fire occur in dust bin.



**Fig 5.6 OVERALL SENSORS**

Here we used the over all sensors that are implemented in my project.



**Fig 5.13 CLOUD SAVING**

It is used as a cloud saving of all the data sent by my sensors and also used for refer the previously detected gases or temperature or any other which is connected to this cloud management.

## **CHAPTER 6**

### **CONCLUSION AND FUTURE SCOPE:**

When working with attractive closeness sensors, one needs to consider that there might be a few exchanging regions. This can prompt numerous tallying when counters are utilized. This impact relies upon the field strength of the perpetual magnet utilized, and additionally the distance of the magnet to the nearness sensor. As can be seen from the reaction chart, two or even three exchanging regions might be noticed, contingent upon the direction of the hub of the attractive shafts. This vagueness of the yield signs can be forestalled by appending the magnet with the right direction of the pivot and, invigorated a particular field, at the right distance.

The shrewd bushel assists us with diminishing contamination. Commonly, the trash bin is flooding and a ton.

Creatures like the canine or the mouse enter in or close to the garbage bin. This causes an awful situation. Indeed, even a few birds additionally attempt to eliminate trash from the waste. This task can stay away from such circumstances. Also, the message can be sent straightforwardly to the cleaning vehicle rather than the worker for hire's office.

## REFERENCES

- 1] Theodoras Anagnostopoulos, Member, IEEE, Arkay Zaslavsky, Senior Member, IEEE, Kostas Kolomvatsos, Alexey Medvedev, Pouria Amirian, Jeremy Morley, and International Journal of Pure and Applied Mathematics Special Issue Stathes Hadjieftymiades "Challenges and Opportunities of Waste Management in IOT-Enabled Smart Cities: A Survey", Vol 2, No 3, July-September 2017.
- [2] IoT based solid waste management system for smart city, Krishna Nirde, Prashant S. Mulay, Uttam M. Chaskar; International Conference on Intelligent Computing and Control Systems ICICCS 2017.
- [3] Solid Waste Management Architecture using Wireless Sensor Network technology Sauro Longhi, Davide Marzoni†, Emanuele Alidori†, Gianluca Di Buo`, Mario Prist, Massimo Grisostomi and Matteo Pirro, Universita Politecnica delle Marche, Dipartimento di Ingegneria dell'Informazione ` Via Brecce Bianche. snc, 60131 Ancona, Italy
- [4] C. K. M. Lee and T. Wu, "Design and development waste management system in Hong Kong," 2014 IEEE International Conference on Industrial Engineering and Engineering Management, Bandar Sunway, 2014, pp. 798-802. doi: 10.1109/IEEM.2014.7058748
- [5] Big Data Analytics For Efficient Waste Management Parag Kedia; IJRET: International Journal of Research in Engineering and Technology, Volume: 05 Issue: 10 | Oct-2016
- [6] IOT Based Smart Garbage alert system using Arduino UNO; Dr. N. Sathish Kumar, B. Vijayalakshmi, R. Jennifer Prarthana, A. Shankar 2016 IEEE Region 10 Conference (TENCON) — Proceedings of the International Conference

# final1658

*by Ww Qqq*

---

**Submission date:** 16-Apr-2021 04:29AM (UTC-0700)

**Submission ID:** 1560874043

**File name:** plagiarism\_check1658.pdf (5.42M)

**Word count:** 6404

**Character count:** 32241

---

final1658

---

ORIGINALITY REPORT

---

|                  |                  |              |                |
|------------------|------------------|--------------|----------------|
| <b>11</b> %      | <b>9</b> %       | <b>2</b> %   | <b>7</b> %     |
| SIMILARITY INDEX | INTERNET SOURCES | PUBLICATIONS | STUDENT PAPERS |

---

PRIMARY SOURCES

---

|          |                                                                                             |                |
|----------|---------------------------------------------------------------------------------------------|----------------|
| <b>1</b> | <b>www.coursehero.com</b><br>Internet Source                                                | <b>2</b> %     |
| <b>2</b> | <b>components101.com</b><br>Internet Source                                                 | <b>2</b> %     |
| <b>3</b> | <b>acadpubl.eu</b><br>Internet Source                                                       | <b>1</b> %     |
| <b>4</b> | <b>www.ijitee.org</b><br>Internet Source                                                    | <b>1</b> %     |
| <b>5</b> | <b>Submitted to Govind Ballabh Pant Engineering College, Pauri-Garhwal</b><br>Student Paper | <b>1</b> %     |
| <b>6</b> | <b>Submitted to K Ramakrishna College of Engineering</b><br>Student Paper                   | <b>1</b> %     |
| <b>7</b> | <b>www.optical-encoders.eu</b><br>Internet Source                                           | <b>&lt;1</b> % |
| <b>8</b> | <b>Submitted to Middle East Technical University</b><br>Student Paper                       | <b>&lt;1</b> % |
| <b>9</b> | <b>Submitted to University of Leeds</b>                                                     |                |

---