

**SMART IRRIGATION SYSTEM (SIS) AND PROTECTION OF CROPS DURING RAINY
SEASON USING INTERNET OF THINGS (IoT) FOR CONSERVATION OF WATER**

Submitted in partial fulfillment of the requirements for the award
of Bachelor of Engineering degree in Electronics and
Communication Engineering

by

PENIKALAPATI VARSHA (Reg.No.37130309)

ONTELA ANUJA (Reg.No.37130291)



DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING

SCHOOL OF ELECTRICAL AND ELECTRONICS

SATHYABAMA

**INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)**

Accredited with Grade "A" by NAAC

JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI - 600 119

APRIL 2021



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY

(DEEMED TO BE UNIVERSITY)

Accredited "A" Grade NAAC I 12B Status by uec I A, -ove AICTE

DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of **PENIKALAPATI VARSHA (Reg.No.37130309)** and **ONTELA ANUJA (Reg.No.37130291)** who carried out the project entitled "SMART IRRIGATION SYSTEM (SIS) AND PROTECTION OF CROPS DURING RAINY SEASON USING INTERNET OF THINGS (IOT) FOR CONSERVATION OF WATER" under our supervision from **September 2020 to April 2021**.

Internal Guide
Dr. R. M. Joany, Ph.D.,

Head of the Department
Dr. T. RAVI M.E., Ph.D.

Submitted for Viva voce Examination held on **17.04.2021**

Internal Examiner

External Examiner



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY

(DEEMED TO BE UNIVERSITY)

Accredited "A" Grade NAAC I 12B Status of UEC I A, -ove AICTE

DECLARATION

We, PENIKALAPATI VARSHA (Reg.No.37130309) and ONTELA ANUJA (Reg.No.37130291) hereby declare that the Project Report entitled **"SMART IRRIGATION SYSTEM (SIS) AND PROTECTION OF CROPS DURING RAINY SEASON USING INTERNET OF THINGS (IOT) FOR CONSERVATION OF WATER"** done by us under the guidance of **Dr. R. M. Joany, Ph.D.**, is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in Electronics and Communication Engineering.

DATE: 16.04.2021

1. PENIKALAPATI VARSHA

2. ONTELA ANUJA

PLACE:

SIGNATURE OF THE CANDIDATES

ACKNOWLEDGEMENT

We are pleased to acknowledge our sincere thanks to Board of Management of **SATHYABAMA** for their kind encouragement in doing this project and for completing it successfully. We are grateful to them.

We convey our thanks to **Dr. N. M. NANDHITHA M.E., Ph.D.** Dean, School of Electronics and Communication Engineering and **Dr. T. RAVI M.E., Ph.D.** Head of the Department, Department of Electronics and Communication Engineering for providing me necessary support and details at the right time during the progressive reviews.

We would like to express our sincere and deep sense of gratitude to our Project Guide **Dr. R. M. Joany, M.E., Ph.D.**, for her valuable guidance, suggestions and constant encouragement paved way for the successful completion of our project work.

We wish to express our thanks to all Teaching and Non-teaching staff members of the Department of **Electronics and Communication Engineering** who were helpful in many ways for the completion of the project.

We would like to thank our beloved **PARENTS** for their constant love and support, without whom this wouldn't be possible and finally we would like to thank the **ALMIGHTY** for his wonderful blessing.

ABSTRACT

Water is progressively turning into the most restricting asset expected to meet the developing populace. Its pivotal job in human existence is featured in parched terrains, where is perceived by low yearly precipitation just as lopsided fleeting and spatial appropriation, coming about to dry and wet periods. Such climatic condition impacts water accessibility and harvest yield steadiness. Consequently cultivating is dangerous because of unfavorable water access. The main part of farming in bone-dry terrains is horticulture water use productivity. Under low and variable rainfall conditions, efficient irrigation management may be a great way for improving water-use efficiency. The Internet of Things (IoT) is an upcoming technology that connects various devices through the internet. In the field of agriculture, the IoT technology provides numerous benefits to the farms by addressing various issues faced by them. Such techniques help to improve the quality, quantity and sustainability of agricultural products. In this paper we have proposed an innovative approach for irrigating and pest monitoring and controlling for the crops. Towards this objective, an IoT based smart irrigation system is proposed that computes precise crop water requirement based on its life cycle and climatic conditions. Utilizing this figured harvest water necessity, a siphon engine is worked naturally at whatever point soil dampness diminishes underneath lasting welting point. The motor is shutdown once the required water is pumped out to crops. This ensures appropriate level of water is used for watering the crops that may aid in better quality crop production. In this work, various parameters like moisture, humidity and temperature are being monitored continuously using appropriate sensors. The data acquired by these sensors are collected using Arduino microcontroller. The pump motors and the RF / GSM transceivers are operated using AT Mega controllers.

TABLE OF CONTENTS

CHAPTER NAME	PAGE NO.
1. INTRODUCTION	1
1.1 OBJECTIVES	1
1.2 EXISTING SYSTEM	1
1.3 PROPOSED SYSTEM	1
1.4 HARDWARE REQUIREMENTS	2
1.5 SOFTWARE REQUIREMENTS	2
1.6 SOIL MOISTURE PREDICTION	10
1.7 SERVICE LAYER	15
1.8 FRAMEWORK IMPLEMENTATION	17
2. LITERATURE SURVEY	19
3 .SYSTEM MODEL	25
3.1 ARCHITECTURE OF SMART IRRIGATION SYSTEM	25
3.2 SENSORS BASED DATA COLLECTION	26
3.3 FUZZY LOGIC BASED SMART IRRIGATION SYSTEM	27
3.3.1 THE FUZZICZTION MODULE	28
3.3.2 THE FUZZY INTERFERENCE MODULE	29
3.3.3 THE DEFUZZICATION MODULE	30
3.4 IMPLEMENTATION DETAILS	30
3.4.1 USED HARDWARE	30
3.4.2 IMPLEMENTATION DETAILS	31
3.4.3 AM2302 DHT22 SENSOR	32
3.4.4 BH1750 FVI LIGHT SENSOR	33
3.5 DESIGN OF A MEDIUM SIZE TUNNEL FARM	34

4. RESULTS AND DISCUSSION	39
4.1 RAIN WATER TANK LEVEL SENSOR	43
4.2 RAIN SENSOR	44
4.3 DC MOTOR	45
4.4 SOIL SENSOR	45
5. CONCLUSION AND FUTURE WORKS	46
REFERENCES	

LIST OF FIGURES

FIGURE NAME	PAGE NO.
1.1 MODIFIED BLOCK DIAGRAM	2
1.2 ARCHITECTURE OF THE SMART & GREEN IOT FRAMEWORK	12
1.3 SMART & GREEN MODULE FOR SOIL MOISTURE PREDICTION	15
1.4 INTERACTION BETWEEN COMMUNICATION, PHYSICAL, SERVICE LAYERS	17
1.5 DETAILS OF THE EXPERIMENTAL FIELD	18
3.1 A HL-69 SOIL HYDROMETER	31
3.2 AM2302 DHT22 SENSOR OF LIGHT AND HUMIDITY	31
3.3 BH1750 FVI LIGHT LENSOR	32
3.4 SMART IRRIGATION	33
3.5 TEST BED OF SMART IRRIGATION SYSTEM	35
3.6 SENSORS DATA WITH VARIATIONS	36
4.1 SOFTWARE CONNECTION RESULTS	39
4.2 HARDWARE CONNECTION	40
4.3 SOIL SENSOR	41
4.4 MOTOR IS ON	41
4.5 SOIL, HUMIDITY, TEMPERATURE SENSOR ARE INTERFACED USING PROTEUS	42
4.6 ARDUINO BOARD	42
4.7 CONNECTIONS OF ARDUINO BOARD	43
4.8 RAIN SENSOR	44
4.9 SOIL SENSOR	45

CHAPTER 1

INTRODUCTION

1.1 OBJECTIVES:

The aim of this project is to make crop monitor and irrigation and efficient and Conserves water used for irrigation.

1.2 EXISTING SYSTEM:

Existing practices of crop irrigation is manual and based on generic traditional recommendations. Crops when provided lesser water, shows reduced growth an reduced intake of calcium. Excessive irrigation results in root death and water wastage. Hence, irrigating crops with precise water becomes an important problem.

1.3 PROPOSED SYSTEM:

In the field of agriculture, the IoT technology provides numerous benefits to the farms by addressing various issues faced by them. Such techniques help to improve the quality, quantity and sustainability of agricultural products. In this paper we have proposed an innovative approach for irrigating and pest monitoring and controlling for the crops. Towards this objective, an IoT based smart irrigation system is proposed that computes precise crop water requirement based on its life cycle and climatic conditions. Using this computed crop water requirement, a pump motor is operated automatically whenever soil moisture decreases below permanent wilting point. The motor is shutdown once the required water is pumped out to crops. This ensures appropriate level of water is used for watering the crops that may aid in better quality crop production.

BLOCK DIAGRAM:




Figure 1.1 modified block diagram

1.4 HARDWARE REQUIREMENTS:

1. Arduinio
2. Relay 12volt
3. DC Submersible Motor (9v or 12v) with pipe
4. Soil Moisture Sensor
5. Temperature Sensor LM35
6. ESP 8266

7. DC 12V Motor
9. APR VOICE IC
10. Rain fall detection sensor
11. ULN2000a driver
12. Soil moisture Sensor
13. Battery 1amps (6v battery) and Mica Board
14. Regulator 5V
15. Male and Female bug
17. Mica board

1.5 SOFTWARE REQUIREMENTS:

1. Embedded C

2. Aurdino Software

The term automation is introduced used first D.S Harder in 1936. He defined it as, automation is handling of parts progressive production processes. Since the term has been applied to big variety of automatic machinery and automatic systems and action for human efforts of intelligence. Water security is an essential element of domestic as well as agricultural application. Irrigation plays a crucial role in assuring quality crop production and contributes to economic development of a rustic .In some countries, agriculture **is** taken into account together of the main source of economic progress. The income of the many countries depends directly on agriculture advancement. 85% of worldwide available water resources is used in agriculture and this percentage will not decrease keeping in mind the rate of population growth and hence leading to high demand of crop productions. Irrigation in agriculture is one of the main task. It is very much important to water the crops as per their need. Very less watering or an excessive amount of watering pot damages the crops. In present irrigation system, a farmer cannot check the moisture level of soil. A new idea for saving each drop of water by the thanks to test the soil condition before supplying water to the crop field. Hence sometimes it may

happen that the watering is more than the need of the crop and sometimes water doesn't reach upto the roots of the plants. This will waste the water and efforts. If water doesn't reach upto the plants roots then it'll directly affect the plant growth and profit. Traditional irrigation system requires manpower. Hence, it become necessary to do something so that the irrigation will become more convenient. Automatic Drip Irrigation System is a project which is developed to automate the traditional irrigation system. It is a simple system, using Arduino to automate the irrigation and watering of crops. The system becomes more flexible by using solenoid valve which is operated on electric principle. This system contains mainly Arduino, GSM module, Solenoid Valve, Humidity Sensor also Filter and Pump. In proposed system the human factor is reduced by Arduino which specially programmed to monitor any parameter changes in sensor. In our system, if we will press number 1 in our smartphone that time GSM send signal to Arduino for turning ON motor according to program burn into Arduino kit. As well as motor will activate that point water will flow through the pipeline and reach the plot that we'll referred as 1. Proposed system having two different plots of farm and every plot contains different electronic kit which contain GSM module, Arduino and Sensor. In the plot 1 we will placed Humidity sensor for checking the moisture content of soil. As water sucking capacity of soil will get fulfil that point sensor send signal to Arduino for turning OFF valve and with the assistance of corresponding GSM module the signal send back to smartphone. In this system the soil moisture sensor having fixed threshold value which can programmed into corresponding Arduino, if actual value but that of threshold value then motor ON as it is and sending update to user through corresponding GSM module and if actual value greater than that of fixed threshold value then also it will send message to user through GSM. As the water sucking capacity of plot 1 get fulfill we have to turn ON the valve 2 and at the same time we have to turn OFF valve 1 with the help of smartphone. Again sensor present in plot number 2 start the same operation as plot number 1. In this way user will be operate this system from anywhere by smartphone . The proposed system will use the screen filter to filter out organic and inorganic debris, sand, Silt and general soil particles. The pressure

reducing valve will be reduces the pressure of the water that goes through pipeline and will use to obtain a regulated and constant value at its outlet. Irrigation is one of the most water-intensive agricultural activities in the world, which has been increasing over time. Choosing an optimal irrigation management plan depends on having available data within the monitoring field. A smart agriculture system gathers data from several sources; however, the data are not guaranteed to be free of discrepant values (i.e., outliers), which can damage the precision of irrigation management. Furthermore, data from different sources must fit into an equivalent temporal window required for irrigation management and therefore the data preprocessing must be dynamic and automatic to profit users of the irrigation management plan. In this paper, we propose the Smart& Green framework to offer services for smart irrigation, such as data monitoring, preprocessing, fusion, synchronization, storage, and irrigation management enriched by the prediction of soil moisture. Outlier removal techniques allow for more precise irrigation management. For fields without soil moisture sensors, the prediction model estimates the matric potential using weather, crop, and irrigation information. We apply the anticipated matric potential approach to the Van Genuchten model to work out the moisture utilized in an irrigation management scheme. We can save, on average, between 56.4% and 90% of the irrigation water needed by applying the Zscore, MZscore and Chauvenet outlier removal techniques to the predicted data. Agricultural activities presently use 70% of the withdrawn freshwater within the world. Therefore, it's of fundamental importance that we apply irrigation management, especially in semiarid regions with a scarcity of rainfall. Irrigation management may be a part of precision agriculture, during which the right amount of water artificially delivered to a field to satisfy the crop needs and therefore the real production of the users is analyzed. The irrigation must supply the crop water needs at different developmental stages during a given local. Irrigation management is employed to detect when to irrigate, the quantity of water needed, and therefore the irrigation frequency, supported the monitoring of crop evapotranspiration and soil moisture conditions. Crop evapotranspiration measures the water consumption by crops, consistent with the

developmental stage of the crop and therefore the weather. The dirt dampness impacts the measure of water system water given to the yield, as water system the executives considers the degree of water maintenance in the dirt. In this way, exactness agribusiness can diminish water utilization in water system by considering the groundwater accessible to the yield. The choice of the simplest irrigation management plan depends on the info available from the monitoring field. A smart agriculture system gathers and processes data for irrigation management from several sources using computing and knowledge technology. Users can provide the features of various sorts of crop, soil, and irrigation system, also because the readings of analog tensiometers. Tensiometers are soil sensors that detect the matric potential, which are wont to estimate the moisture at different depths and monitoring points during a field. Automatic weather stations can provide public data through the Internet. Moreover, the sector may have sensors and actuators which may interact with one another as objects of the web of Things (IoT) so as to supply services transparently to the users. Such services are associated with irrigation management for monitoring (i.e., water, soil, and air) and prediction (weather and soil conditions). However, data aren't freed from discrepant values (i.e., outliers), which may negatively affect the precision of irrigation management. Furthermore, data from different sources must fit into an equivalent temporal window required for the irrigation management and therefore the data preprocessing must be dynamic and automatic for researchers, engineers, and owners or farmers to profit from the irrigation management plan. Data fusion also informs the choice whether to start out irrigation or not in irrigation management that creates use of other sorts of data (such as weather or crop data). In this work, we propose the Smart & Green framework to offer services for smart irrigation, such as data monitoring and control, preprocessing, fusion, synchronization, storage, and irrigation management enriched by the prediction of soil moisture. The Smart & Green services are modular components which facilitate the reuse and customization of code, which are challenges/limitations to applying IoT in the smart agriculture context. Our framework allows users to line the

info sources: the closest meteorological observation post, the moisture sensors (analog or digital), the sort of crop, and therefore the features of the irrigation system in the monitored field. Therefore, Smart Green also contributes to the answer of another challenge in applying IoT for the aim of smart agriculture: the mixing of the particular infrastructure of the users (i.e., devices, machines, and software).

Smart Green recommends the simplest irrigation management plan, consistent with the configuration of the monitored field. The framework also synchronizes weather and soil data, also because the crop stage for the chosen irrigation management plan. The Fusion service allows for the definition of outlier removal criteria for the weather and soil data. The fusion service also applies the outlier removal techniques Chauvenet, Z-Score, Modified Z-Score, and Generalized ESD before data aggregation, so as to get general information about the soil conditions of a field. Our results show that it makes irrigation management more precise, therefore saving water.

For fields without soil moisture sensors, the prediction module estimates the soil moisture to form the quantity of water irrigated more precise. In this work, we propose a computational model to predict the matric potential based on weather data available at public stations, crop information, and the amount of irrigation water used. As another contribution, we offer to the scientific community a public data set containing the matric potential and irrigation data for cashew cultivation in an experimental field. The matric potential is the critical variable in measuring the soil moisture.

The computational model reduces the value of kit and energy, because the model allows farms to estimate the moisture without soil sensors for an equivalent soil type. We evaluate the performance of a group of popular machine learning techniques which are widely applied to unravel regression problems. We measure the standard of the models without feature selection using the RMSE (Root Mean Squared Error) and therefore the MAE (Mean Absolute Error) as metrics. Our results show that the combination of predicted data and the outlier removal techniques can save an average between 56.4% and 90% of irrigation water,

estimated by water balance management.

Different methodologies have prepared soil information to recognize anomalies and treat information utilizing commotion separating strategies. One framework applied an EKF (Extended Kalman Filter) to the dirt dampness information before the execution of water system the executives, to keep away from the actuators improperly beginning the water system.

The example acknowledgment of water utilization by a yield radicular framework, introduced in, is an exception discovery strategy dependent on a period arrangement investigation of soil dampness assembled at a few profundities previously, during, and after water system. This procedure takes into consideration the ID of sensors with helpless activity, which demonstrates the requirement for alignment or change.

Our proposed structure permits clients to characterize rules for anomaly expulsion for each kind of climate and soil information utilized in water system the board. Our system likewise gives the alternative to execute such calculations as Chauvenet, Z-Score, Modified Z-Score, and Generalized ESD (Extreme Studentized Deviation) to eliminate anomalies and wire soil dampness information, for the situation when a field has a few soil sensors checking at various profundities.

Different works have naturally begun water system by executing calculations for breaking down the information accumulated by a remote sensor hub. In one investigation, a calculation dependent on choice trees utilized the dirt temperature and dampness to decide the water system time and the required measure of water. Fresh standards (IF-THEN) were utilized to contrast limit esteems and the dirt dampness assembled by sensors, to conclude whether to turn on the sprinklers of a water system framework.

Choice help stages for the execution of conventional water system the board, like the matric potential and water balance, have been presented. These frameworks permit agronomists and ranch proprietors to oversee Internet of Things (IoT) segments for field observing. The matric potential administration utilizes soil information accumulated by sensor hubs and pictures caught by automated airborne vehicles to effectively gauge the water system water need.

Web frameworks have been utilized for the arranging and execution of water system the

board. Past the perception of soil dampness and climate information accumulated by remote sensor hubs, these frameworks utilize fresh principles for information examination and, when it is essential, the frameworks send messages to their clients to advise about water system times or enact the water system framework consequently. In different methodologies, the framework takes the precipitation figure (accessible on the Internet) into account when concluding whether to actuate the water system framework. A remote sensor organization can likewise design and execute water system the executives. For this situation, the sensor hubs accumulate and dissect soil dampness information and turn the water system framework on until the dampness accomplishes the field limit.

A SCADA (Supervisory Control and Data Acquisition) framework can consequently complete the information get-together, arranging, and execution of the water balance the board. The dirt sensor hubs are additionally actuators, which control the water system and send information constantly to an administration framework. The framework gets information from a climate station on the ranch to gauge the reference evapotranspiration ETo . The framework additionally uses the bend of the harvest coefficient k_c , picking its worth as indicated by the current formative phase of the yield. The water equilibrium and matric potential methodologies frequently should consider information synchronization. Along these lines, a few applications have synchronized the information of recently enrolled crops, just as soil and climate information, to definitely decide the water system water need for the momentum formative phase of the harvest.

The current frameworks portrayed in this part are not adaptable enough to permit clients to set the highlights of a checked field, like the sort of harvest, the sort and number of soil sensors, and water system framework boundaries utilized. The frameworks ordinarily work with a predefined setup and foundation. Hence, code reuse is unrealistic for the water system the board of agrarian fields which don't fit to the current framework design. Our proposition permits clients to enroll significant data for water system the executives: Different sorts of harvests, soil highlights, water system frameworks, information sources (climate or soil), and exception expulsion standards. In this work, the structure designs the water system the board utilizing the matric potential and water

balance draws near.

Besides, none of the frameworks could estimate the dampness levels in fields without soil sensors. Our proposition executes computational models to foresee soil dampness dependent on climate information, crop data, and water system water need (IWN). In this work, we remember the anticipated information for the water balance the executives, acquiring somewhere in the range of 56.4% and 90% of IWN investment funds more than a half year .

1.6 SOIL MOISTURE PREDICTION:

In the Linear Regression, Decision Tree, Random Forest, and Gradient Boosting with Regression Tree (GBRT) machine learning (ML) techniques were applied to weather and soil sensor data (moisture and drought stress) to predict the simplest irrigation plan for a jojoba crop. The GBRT model outperformed the others and, so, the choice support service incorporated it as a module of the system. A model supported support vector regression (SVR) and k-means ML techniques which used weather data and forecasts, also the soil data (temperature and moisture), to forecast the soil moisture has also been investigated . In an integrated system to monitor drought in northern China using satellite images (NOAA, MODIS, and FY3A), weather stations, and soil data has been discussed. The drought forecasting used the matric potential at the depth of the crop root, the water balance model, depletion indices, and measurements of crop stress to estimate the soil moisture and therefore the water quantity needed for an extended period.

In this work, we apply weather data, crop information, and the amount of irrigation water used in a computational model, in order to estimate the daily matric potential of the most superficial soil layer, which signals when the crop needs irrigation. We apply the predicted value in the Van Genuchten model to obtain the soil moisture used in irrigation management for fields without soil moisture sensors (i.e., Field 1). We present two different approaches: Local and global prediction models. In the local method, we create a prediction model for each monitoring point in an experimental field. In the global approach, we create one model which may be

generalized to any monitoring point. We have evaluated the performance of a set of popular ML techniques which have been widely applied to solve regression problems: Linear Regression, Decision Stump, M5 Model Trees and Rules, Random Tree, Random Forest, Rep Tree, and GBRT. Our results show that GBRT outperforms the other evaluated techniques in both approaches. SWAMP (Smart Water Management Platform), introduced in [10], is one of the related methods which is most similar to our proposal. SWAMP has components to permit for the implementation of various IoT applications for irrigation management, supported the crop and soil moisture approaches. Users can customize the services for the gathering (MQTT or LoRa), processing, and synchronization of knowledge with differing types of crops, weather, and country. Therefore, different field configurations can reuse these services for data analysis and storage, highlighting the excellent flexibility of SWAMP. However, their techniques for the processing and therefore the fusion of knowledge haven't been detailed, and no application or service for the prediction of soil moisture has been provided.

The Agro-IoT framework, introduced in [11], is also related to our proposal, which provides users real-time data gathering, aggregation (fusion), and analysis in the context of smart farming. Agro-IoT reuses several components to implement IoT applications, consistent with the requirements of the monitored field. Agro-IoT provides similar services to our proposed method; that's, it also provides the management of devices (i.e., registration of sensors and actuators) and event detection through data analysis. However, it doesn't contain modules for data synchronization and outlier removal or soil moisture prediction. In this work, we propose Smart Green: An Internet of Things (IoT) framework for the smart agriculture domain. A framework consists of “a specific implementation of a skeleton of infrastructure used for the conception of a work. Work is any activity performed by users or software. In this proposal, the work consists of the design of irrigation management. In fields where there are not any soil moisture sensors, a computational model can estimate the soil moisture for an equivalent soil type using weather, crop, and irrigation data. Agronomists, researchers, and farmers conduct

irrigation management through software which uses Smart& Green presents the conceptual architecture of Smart &Green, divided into four layers: Application, Services, Communication, and Physical.




Figure 1.2. Conceptual architecture of the Smart &Green IoT Framework for Smart Agriculture.

In software engineering, a framework also can be “a mini architecture which will be reused which provides behaviour and a generic structure for a family of software abstractions in a context that specifies the collaboration and use of them into a given domain”. Therefore, given the smart agriculture domain and the context of smart irrigation, the Smart& Green framework specifies the structure of a set of concrete and abstract classes to implement modules for the gathering, storage, synchronization, and fusion of data, as well as mathematical models which describe irrigation management. Irrigation management determines the behaviours of the classes and modules. As a mini architecture, the proposed framework can be reused with different smart agriculture software with the generic functionalities of irrigation management.

The application layer provides facilities for the automatization of irrigation management and soil moisture prediction. Through this layer, users of an

agriculture management system can insert information about the farm infrastructure: the kinds of crops and irrigation system to every monitored field, the monitored soil layers, and therefore the weather stations closest to the farm. The Matric Potential and Water Balance modules implement well-known irrigation management methods . These modules use information registered by users as well as that from weather and soil data sources. Smart &Green selects the best irrigation management based on the data available. The principal functions of the Register Module are as follows:

- User register: Smart &Green framework allows two types of users: Specialist and regular. Specialist users can provide agronomic information, such as different types of crops, soil, and irrigation system features. They can also register outlier removal criteria for weather and soil data and choose algorithms for the fusion service. Regular users can register farms and fields.
- Farm Register: Users provide information about the farm, such as address and geographical co-ordinates (latitude and altitude) for the Smart& Green framework, and select the weather station closest to the farm.
- Crop register: A specialist user can create types of crops using information such as a description, the curve of the crop coefficient, and the critical moisture condition.
- System Irrigation Register: A specialist user inserts the type of irrigation systems, such as “micro-sprinkler”.
- Weather Station Register: Smart &Green automatically selects the weather station closest to the farm using the geographical co-ordinates. Users can confirm this or choose another one.
- Soil Sensor Register: The user can insert the types of soil sensors used. Smart& Green already has analog and digital tensiometers.
- Field Register: Users set the field configuration features , such as the type of crop, irrigation system, soil, and if there are soil monitoring points. The developmental stage of the crop represents the amount of days since the initial cultivation. Effective precipitation (mm/h) and efficiency of the irrigation system are necessary for irrigation management, so as to compute the irrigation time. In the case of monitoring points, users can register the type of soil moisture sensor (analog or

digital) and the depth z monitored for each monitoring point in the field.

- Field Communication register: In the case where the monitored fields have sensor nodes that automatically gather soil data, users can define the type of communication to send the data to the framework. Users set the IP address and specific configuration (COAP or MQTT).
- Outlier Removal Criteria Register: Specialist users can create a threshold for minimum and maximum values of each type of weather and soil moisture data used in irrigation management.

The Smart &Green framework suggests an irrigation management plan, according to the data of a registered field. For fields without soil moisture sensors, Smart &Green indicates the water balance without soil moisture data or the water balance with the soil moisture data created by the soil moisture prediction module. For fields with soil moisture sensors the framework calculates the matric potential or water balance using the soil moisture data. In this work, we address a large field (over 7500 m²) to produce one type of crop on a large scale, in which the soil is monitored by a hundred tensiometers (i.e., soil moisture sensors) at three different depths. To investigate this scenario, we present the local and global approaches, which can be used to learn a prediction function $f^{\wedge}$. The local approach creates a different prediction function $f_i^{\wedge}$ for each tensiometer at the superficial soil layer of the field. For this, it uses the observations recorded by a tensiometer b_i and a weather station m_s , as well the water amount w_i given to the crop and the crop coefficient k_c related to the current life stage of the crop. The local approach defines the prediction $f^{\wedge}$ in terms of n different functions $f_i^{\wedge}$ for local predictions. However, if a field has a large number of tensiometers, a large number of distinctive prediction models must be trained. The global approach creates only one prediction function $f_i^{\wedge}$ using the information from all tensiometers. Therefore, the global prediction model might not fit some individual tensiometers. The Smart &Green framework implements the prediction model as a modular service to complement the irrigation management of fields without soil moisture sensors. The framework automatically retrieves and stores the meteorological data set M_{ms} published on the Internet by weather stations.




Figure 1.3. Smart & Green Module for soil moisture prediction.

The framework daily pre-processes the Mms data to remove possible outliers. The module of soil moisture prediction estimates the matric potential ψ_p of a field. The irrigation management module computes the current soil moisture θ_c by applying ψ_p on the model. Then, the obtained θ_c is applied to Equation 2 or 3 to calculate the irrigation water need (IWN).

In the Internet of Things (IoT) context, the framework sends the IWN value to an actuator to start the irrigation system. The irrigation system stops when the sector receives the quantity of water specified by the IWN. Although this present work does not handle an automatic irrigation system, this issue is a concern for the full implementation of an IoT system for smart farms.

1.7 Service Layer

The Service layer supports the Application layer by storing data provided by Smart& Green users and synchronizing crop, weather station, and soil data when required by any irrigation management module. The Service layer also carries out fusion tasks for data of soil moisture sensors or the soil moisture prediction. The Storage service provides centralized data persistence for the monitoring of weather, crop, and soil data in the fields. The Synchronization service selects the crop coefficient k_c which is appropriate to the current development stage of the crop.

and retrieves the weather data Mms for the period needed for irrigation management. The service also requests the Communication layer for new data from the Internet, if needed. In the case of soil data, the Synchronization service selects data from all monitoring points BTc in the field, taking into account the period of irrigation management. If there are no data available, the service requests new data from the or the Communication layer. Finally, the Synchronization service makes the data set composed of { kc, current, Mms, period, BTc, period} available. The Irrigation Management Modules use the Fusion service if there is a field with monitoring points, each with one or more soil moisture sensors (e.g., tensiometers) at different depths z. The Fusion service can also treat data created in soil moisture prediction when irrigation management is required for fields without soil moisture sensors. Data fusion consists of processing the data to detect and remove outliers (DRO) and submitting data to a co-operative function (CF), according to multilevel data fusion architecture. DRO tasks apply criteria and algorithms defined by specialist users to right away detect and take away outliers. The Register module of the appliance layer allows for the creation of threshold values for soil data. DRO algorithms are specific to the soil layer monitored. the Z-score is more efficient for data series at the most superficial soil layer (e.g., z=15 cm). In contrast, the Generalized ESD (Extreme Studentized Deviate) algorithm works well with data at depth of z=45 cm. The Smart& Green framework has implementations of the Chauvinist, Z-Score, Modified Z-Score, and Generalized ESD algorithms. A co-operative function (CF) aggregates one type of data gathered at different monitoring points of a field. Smart& Green uses the mean function as the CF to aggregate soil moisture data at the same depth. For example, has six monitoring points at two depths. Therefore, the framework calculates the mean of each set of six samples gathered at a given depth z. After fusion, the data are ready for irrigation management at the Application layer, which decides whether irrigation should be started. The Communication Layer has a set of software to gather weather and soil data through network protocols. This includes a weather client, four soil clients, three soil

servers, and a gateway. The weather client consists of an HTTP client which downloads meteorological observation post data from the web and stores them. Smart& Green offers an API to gather data from Brazilian automatic weather stations .




Figure 1.4. Interaction between the Communication Layer and the Physical and Services Layers.

The soil client gathers the matric potential data ψ_m if the field has tensiometers installed. If the tensiometers are analog, users have to manually collect the ψ_m data, using a mobile application that sends it to the framework via HTTP. If the tensiometers are digital, they're integrated into sensor nodes that send the info to a gateway near the sector . The gateway hosts CoAP and MQTT clients, which forward the ψ_m data to the servers of the framework.

1.8 FRAMEWORK IMPLEMENTATION:

For ranch fields with sensor hubs, for example, field 3 , we utilized an Arduino Pro Mini and three Irrometer Watermark 200SS computerized tensiometers to execute a sensor hub which assembles soil dampness information at 15, 45, and 75 cm. The watermark estimates the dirt water strain (i.e., matric potential), which goes from 0 to 200 CBar/KPa. The sensor hubs utilize four AA antacid batteries of 1.5 v on the grounds that the force source. We change the Arduino eliminating the voltage regulator and LEDs to the hub has a more drawn out working life. Sensor hubs send soil information through a nRF24L01 with an outer hymn and force enhancer. The nRF24L01 might be a solitary chip radio handset for the two .4–2.5 GHz ISM band. After information transmission, the sensor hub sleeps for an hour to save loads of force . We utilized a

Raspberry Pi 3 with the Raspbian OS as the doorway to get soil dampness information and send them by the CoAP or MQTT customer to capacity.

We got an informational collection of soil dampness from a trial cashew field with other tropical crude materials in the city of Paraibapa, Brazil . The field had roughly 250 cashew trees with nine observing spots. Each spot had three tensiometers that permitted manual perusing of the matric potential at profundities of 15, 45, and 75 cm. Shows the subtleties of the simple tensiometers (soil dampness sensors), which gave the informational collection from 2016, 2017, and 2018, with 234, 245, and 138 every day tests, separately. It merits referencing that, in 2016, the field had salvation water system in which we gave 5 liters of water for each bud at whatever point the introduced tensiometer at a profundity of 15 cm read a matric capability of 60 kPa. Salvation water system keeps plants from kicking the bucket.



(a) Tensiometers at 15, 45, and 75 cm depths near a cashew bud.



(b) Cashew buds.

Figure 1.5. Details of the Experimental Field.

The meteorological informational index was acquired from a Brazilian public climate station at Itapipoca city, Ceara (height 102 m; scope 03°29' S; longitude 39°35' W). Notwithstanding, we choose to utilize the pluviometer sensor information of the field, as

the precipitation sensor of the climate station had missing qualities over an all-inclusive period. Presents the abbreviations, the portrayal of the factors, and the estimation information units utilized in our expectation issue. We discharge the amassed informational index to established researchers to guarantee the reproducibility of our outcomes and advance exploration improvements in this field.

CHAPTER 2

LITERATURE SURVEY

In 2005, C.M. Burt Proposed Selection of Irrigation Methods for Agriculture: Drip/Micro Irrigation. Trickle/Micro water system Refers to a Variety of Irrigation techniques in which water is conveyed to straightforwardly to little territories through producers. The emanation gadgets are separated intently enough with the goal that the narrow activity of soil gives water to each plants root zone. Chemigation is for the most part needed to try not to plug because of bacterial development as well as compound precipitation in the laterals and discharge gadgets. Because of utilization of dribble water system framework work cost diminishes however capital expense is high. In 2009, Yandong Zhao, Jinfeng Guan, Junfu Zhang, Weilun Yin proposed concentrate on Precision Water-saving Irrigation Automatic Control System by Plant Physiology. In this framework BD-1 soil dampness sensor is utilized for detecting the dampness the dirt. This paper depicts framework structure on to parts of equipment and programming plan. For programming planning they utilized multithreading method with the assistance of regulator. They utilized GSM for modernization in correspondence, likewise they control electromagnetic valve, understand the trickle water system, sprinkler water system, miniature water system and low-pressure pipe water system strategy like mechanization of water system mode. This framework accomplish motivation behind exceptionally effective accuracy. Additionally this framework gives constant location of soil water content. In 2011, Tom Gill, Brian Wahlin, John Replogle Proposed Venturi Meters Constructed with Pipe Fitting: an Under-Appriciated Option for Measuring Agriculture water. Venturi Meters developed of line fittings can be a down to earth methods for estimating stream with dependable exactness for a reach applications. Real head misfortune through an endeavor meter is ordinarily tiny. Line Venturi meters are generally perceived as an estimation innovation in funneled framework offering a serious level of precision while inposing similarly little head misfortune.

In 2014, T. Veeramanikandasamy, K. Rajendran, K.Sambath, D. Sangeetha proposed Remote Monitoring and Closed Loop Control System for Social Modernization in

Agricultural System utilizing GSM and Zigbee innovation. In this framework they utilized GSM for Modernization and remote correspondence. With the assistance of GSM client can work the framework from anyplace. They utilized RS232 for interfacing GSM module and microcontroller. In this framework zigbee innovation is utilized in water system control community for better remote information transmission. The primary benefits of this framework, one can save labor, water and force consumption is diminished by 20% and 30% when contrast with existing strategy. The zigbee innovation having restricted scope of remote information transmission, so client can't utilize this framework for significant distance this is the burden of this framework.

In 2015, Prof. R.R.Jadhav, Prathamesh P. Pandit, Shubham D.Pal, Vineet H. Risbud Proposed Three Phase Motor Control Using GSM. The framework guarantees assurance of engine against over-burdens, overheating and stage imbalances. It additionally give computerized restarting if ordinary conditions are re-established. The framework ends up being extraordinary help to ranchers whose siphon sets are situated far away from their homes because of ability of controller utilizing PDA and hint about any unusual conditions.

In 2015, Lala Bhaskar, Barkha Koli, Punit Kumar, Vivek Gaur Proposed Automatic Crop Irrigation System. The proposed configuration is a programmed framework that guides the rancher water system measure. In that proposed framework ranch mechanization incorporates moistness, temperature, water level of wells and uniform inventory of water utilizing water sprinkler and dribble irrigation. In that framework additionally keeps the rancher refreshed with all foundation exercises through SIM900 module that ships off message enrolled number as per sensor yield to turn ON/OFF water supply. LCD show is likewise advising the rancher. This framework have an ease and effectively moderate by the rancher of country. The weakness of this undertaking it is simply restricted to cultivating that is at home.

In 2017, Ateeq Ur Rehman, Rao Muhammad Asif, Rizwan Tariq, Ahmed Javed proposed GSM Based Solar Automatic Irrigation System utilizing Moisture, Temperature and Humidity Sensors. In that YL69 soil dampness sensor is utilized. It sense the water substance of the dirt. Soil dampness is a vital variable in controlling the trading of water and warmth energy between the land surface and environment through vanishing of

plant happening. The fundamental benefit of this framework is that utilization of smaller than usual assets, the framework can save parcel of water and power consequently framework turns out to be monetarily positive. Client can undoubtedly realize water sucking limit of soil with the assistance of soil dampness sensor YL69. Cost is the principle factor of any framework so as sun based is expensive, so it isn't reasonable to rancher, this is impediment of framework.

In 2017, Kriti Taneja, Sanmeet Bhatia proposed Automatic Irrigation System utilizing Arduino UNO. In this framework soil dampness sensor is utilized to detect the water sucking limit of soil or dampness level of soil. Additionally they utilized water level sensor . LCD is associated with Arduino and all the sensor to show the situation with dampness content in the dirt and water level in tank. The fundamental benefits of this framework, framework helps in water system regions with low water level and prompts supportability. This framework is extremely unpredictable and low upkeep and could be changed by different sort of harvests absent a lot of human endeavors. Other than cost decrease this undertaking assists with saving fundamental component of life that is water. The inconvenience of this framework, is that this undertaking simply restricted to cultivating at home, client can't make a difference this task to greater degree of agribusiness.

In 2017, Prateek Jain, Prakash Kumar, D.K. palwalia Proposed Irrigation Management System with Micro-regulator Application. The proposed framework depends on miniature regulator based computerization based mechanization for advancing usage of water assets and diminishing work cost in agribusiness applications. Framework comprise of Arduino stage and useful segments like dampness sensor and engine load. A dampness sensor distinguishes the stickiness level of soil. Soil dampness and temperature foreordained reach is set especially for explicit plants prerequisites, and as per that framework is being operated. The framework isn't close the current status of field.

In 2017, R. Nandhini, Poovizhi, Priyanka Joshe, R. Ranjitha Proposed Arduino Based Smart Irrigation System Using IOT. The primary target of this keen water system framework is to make it more inventive, easy to understand, efficient and more effective than the current framework. On the off chance that the detected worth goes past the

edge esteems set in program, the siphon will be associated with driver circuit which assists with exchanging the voltage. The rancher will be insinuated about the current field condition through GSM module. By utilizing this framework, the rancher can get to the insights concerning the state of the field anyplace whenever. The framework isn't utilized for number of plots.

Balaji Banu planned a remote sensor organizations to notice the states of the cultivating and expanding the harvest yield and quality. Sensors are utilized to screen various states of climate like water level, mugginess, temperature and so forth, The processors ATMEGA8535 and ICS8817 BS, simple to computerized transformation and remote sensor hubs with remote handset module dependent on Zig honey bee convention are utilized in the planning the framework. Information base and web application is utilized to recover and store information. In this examination the sensor hub disappointment and energy productivity are overseen. Liu Dan, Joseph Haule, Kisangiri Michael and Wang Weihong, Cao Shuntian did investigates wise horticulture nursery observing framework dependent on ZigBee innovation. The framework performs information securing, preparing, transmission and gathering capacities.

The point of their trials is to acknowledge nursery climate framework, where the of framework proficiency to deal with the climate territory and diminish the cash and cultivating cost and furthermore save energy. IOT innovation here depends on the B-S structure and cc2530 utilized like handling chip to work for remote sensor hub and organizer. The door has Linux working framework and cortex A8 processor go about as center. By and large the plan acknowledges far off wise checking and control of nursery and furthermore replaces the customary wired innovation to remote, likewise diminishes labor cost. Joseph haule, Dragoş Mihai Ofrim, Bogdan Alexandru Ofrim and Dragoş loan have proposed a trial that clarifies the utilization of wsn utilized in mechanizing water system. Water system control and rescheduling dependent on wsn are amazing answers for ideal water the board through programmed correspondence to know the dirt dampness states of water system plan. The interaction utilized here is to decide the appropriate recurrence and season of watering are essential to guarantee the proficient utilization of water, top caliber of harvest location postpone throughput and burden. Reproduction is accomplished for horticulture by OPNET.

Another design of wsn is deployed for irrigation system using Zig bee protocol which will impact battery life. There are some drawbacks as wsn is still under development stage with unreliable communication times, fragile, power consumption and communication can be lost in agricultural field. so automate irrigation system and scheduling based on wireless sensor networks are used. WSN uses low power and a low data rate and hence energy efficient technology. All the devices and machines controlled with the help of inputs received via sensors which are mixed with soil. Farmers can analyze whether the system performs in normally or some actions are need to be performed.

Vijay Kumar, Lin Zhang, Min yuan, Deyi Tai, Xia Oweixu, Xiang Zhan, Yuanyuan Zhang studied the work of rural farming community that replaces some of the traditional techniques. The sensor nodes have several external sensors namely leaf wetness, soil moisture sensor, soil pH, atmospheric pressure sensors attached to it. Based on the soil moisture sensor the mote triggers the water sprinkling during the period of water scarcity and switches off after adequate water is sprinkled. This results in water conservation and soil pH is sent to the base station and in turn base station intimates the farmer about soil pH via SMS using GSM model. This information helps the farmers to reduce quantity of fertilizers used. A development of rice crop monitoring using WSN is proposed to provide a helping hand to farmers in real time monitoring and increasing the rice production. The automated control of water sprinkling and ultimate supply of information is implemented using wireless sensor network.

G. Nisha , Chun-ling Fan, Yuan Guo proposed a wireless sensor based automated irrigation system to optimize water use for agricultural purpose. The system consists of distributed wireless sensor network of soil moisture, and temperature sensors mounted in the crop field. Zigbee protocol is used to handle the sensor information and water quantity programming using algorithm with threshold values of the sensors sent to a micro controller for irrigation system. Data inspection is done using by using solar panel and cellular internet interface. A wireless camera is fixed in crop field to monitor the disease area using image processing technique. Meng Ji-hua conducted a research on growth of cereal crop seedlings, as well as the status and trend of their growth. This paper introduced the design, methods used and implementation of a global crop growth monitoring system, which satisfies the need of the global crop monitoring in the world.

The system uses two methods of monitoring, which are real-time crop growth monitoring and crop growing process monitoring. Real-time crop growth monitoring could get the crop growing status for certain period by comparing the remote sensed data (NDVI, for example) of the period with the data of the period in the history (last year, mostly). The differential result was classified into several categories to reflect the condition at difference level of crop growing. In this system, both real-time crop growth monitoring and crop growing process monitoring are carried out at three scales, which are state (province) scale, country scale and continent scale. Global crop growth monitoring system was found in this design and built a system that can monitor the global crop characteristics of fast, effective, high credibility and operational in its run.

Alan Main-waring , A. Sivasankari, S. Gandhimathi have provided an in-depth study of applying wireless sensor networks to real-world habitat monitoring. A set of system design requirements are developed that cover the hardware design of the nodes, the design of the sensor network, and the capabilities for remote data access and management. To evaluate this implementation, have deployed an initial prototype network at the James San Jacinto Mountains Reserve (JMR) in Idyllwild, California. JMR is a 29-acre ecological preserve, representing just one of the University of California System Natural Reserve System's 34 land holdings. JMR climate is different from GD and weather changes can exists for long time.

The data collection can be made easy from previously inaccessible using a micro-measurement scale. Lei Xiao Fiona Edwards Murphy, Emanuel Popovici, adraig Whelan, and Michele Magno Proposed agriculture monitoring system using wireless sensor network (WSN). The conditions can be monitored in real time are temperature, light intensity, and humidity. The experiment involves the hardware and software design of the built modules, network topology and network communication protocol with the challenges. Design explains how the node can achieve agricultural condition information collection and transmission. The system is compact in frame work, light weight, good in performance and operation. It improves the agricultural production efficiency automatically.

CHAPTER 3

SYSTEM MODEL

3.1 ARCHITECTURE OF SMART IRRIGATION SYSTEM:

The proposed savvy water system framework is planned with the capacity of wise dynamic as far as watering the plant or not based on considering highlights like the plant type, climate conditions, soil dampness level, mugginess, temperature, and so forth. Our methodology centers around effective energy utilization as it doesn't turn ON every one of the sensors constantly. The sensors are occasionally turned ON and killed depending on the situation. A wise calculation handles the effective usage of sensors to guarantee proficient energy utilization and to keep the working expense of this framework low. The proposed approach explicitly addresses the water system issues of passage cultivating and can be similarly productively when utilized with either a sprinkling strategy or a trickle water system technique. The design of the proposed framework is appeared in Figure .The proposed framework works in correspondence with a bunch of implanted and outside sensors, an IoT worker, Cloud stockpiling and entryways' help. These four layers of the proposed brilliant water system framework are the Application layer, Management layer, Network and Connectivity layer and Device and Perception layer.

3.2 SENSORS BASED DATA COLLECTION:

The initial phase in the proposed framework is to gather information from sensors, for example, soil dampness, air stickiness, air temperature, light force, and so forth. The proposed framework has a gadget and insight layer that incorporates all the equipment gadgets like sensors, actuators, microcontrollers and Wi-Fi gadgets. All the systems administration parts, WiFi and Bluetooth modules are overseen at the organization and network layer. At that point the gadget the executives, distributed storage is taken care of at the administration layer to give channels to transmission of information between clients (ranchers) and equipment gadgets and cloud through far off worker additionally gives asset dealing with and significant level handling. An application layer dwells at top

that give highlights like water system planning, plant observing, light controlling and other suggestion administrations. The working of sensors and the cycle of assortment of information and capacity at information worker for additional investigation.

Figure 3.1 addresses the building configuration perspective on the actual parts of the framework. It contains all the equipment gadgets and design of the brilliant passage ranch framework as conveyed in a genuine climate. As demonstrated in Figure 3.1 on the furthest left side there are light and dampness sensors which are associated through a simple contribution with a microcontroller equivalent to mugginess and temperature sensors are associated through a computerized input. Here, the microcontroller functions as a unified gadget that takes contributions from different sensors and sends the qualities to a worker through the web. The worker measures the information gave by microcontroller so clients can see it through an Android application or an internet browser because of a client playing out certain activities which will be sent to the worker through the web, at that point the worker sends the predefined orders to the microcontroller lastly the actuators play out the activity.

The accompanying area clarifies the functions of a fluffy rationale based choice emotionally supportive network that is conveyed at the worker and helps the shrewd water system framework settle on choices in regards to water booking and water amount as for the kind of a plant and the sort of soil. Utilizing fluffy rationale to choose water planning and water amount concerning the kind of a plant and sort of the dirt is an original thought. This framework is completely programmed. The accompanying areas depict the specialized subtleties of the proposed shrewd water system framework for burrow cultivating.

3.3. FUZZY LOGIC BASED SMART IRRIGATION SYSTEM:

The brilliant water system framework gets constant contributions from sensors embedded in a savvy burrow ranch to make suggestions for water system booking, amount. A microcontroller snatches information from sensors and communicates it to a web worker where a fluffy rationale based choice emotionally supportive network settles on a choice based on the predefined conditions and present status of plants got through sensors. At that point the estimations of the sensors are

handled on the worker and rundown of plants with their plausibility rating is shipped off the client's portable, from where clients can design a watering plan for the plants. At the point when the date and season of an anticipated timetable shows up, or the water level gets lower in the passage ranch, our framework tells the client and sets a water siphon to its ON state for adequate watering of plants. The working of the proposed fluffy rationale framework intended for the keen water system framework.

The dynamic capacity of a fluffy rationale framework is upheld by a characterized rule set. Previously mentioned Equations (2) and (3) help in registering the strength of a choice guideline. Ordinarily, estimation of an etymological variable is portrayed as a fluffy set. in the characterized universe of talk of a fluffy rationale framework, each information esteem is planned to a participation esteem in the scope of 0 and 1 by a regular enrollment work. Here, assuming guidelines are utilized to carry out the fluffy standard set that address information in the proposed keen watering framework. The parts and work process of the fluffy rationale module is appeared as it has the three essential segments: fuzzifier, rule and surmising, and defuzzifier.

3.3.1. THE FUZZICATION MODULE:

The proposed fluffy rationale framework works by following a commonplace system. A fuzzification module gets input fresh qualities from a bunch of sensors. The cycles of changing these fresh qualities over to the fluffy qualities is coached by a participation work. The pre-owned enrollment work handles different factors, for example, temperature change rate, stickiness change rate, light change rate, and dampness change rate. The estimations of these factors trait as low, medium, and high, while estimation of clock variable is credits as short or long. The utilized fuzzified esteem set is addressed in Equation (4):

$$\tilde{A} = \mu_1 K(x_1) + \mu_2 K(x_2) + \mu_3 K(x_3) + \dots + \mu_n K(x_n) \quad (3)$$

The idea of "piece of fuzzification" is carried out utilizing connection of fluffy set $K(x_i)$ as demonstrated in Equation (3). The fluffy set $K(x_i)$ is carried out utilizing μ_i consistent and x_i . The utilized fluffy rationale module in keen water system framework the cycle of fuzzification is carried out utilizing the three-sided enrollment work. The three-sided enrollment work is a normal decision in multivariate choice emotionally supportive networks. The Equation (4) shows the ordinary construction of a three-sided

participation work that handles three esteemed fuzzification framework:

$$\mu A(x) = \begin{cases} 0, & x \leq a \\ \frac{x-a}{b-a}, & a < x < b \\ 1, & x \geq b \end{cases} \quad (4)$$

The three boundaries meant in Equation (4) address an enrollment capacity's lower limit with variable a, top with variable m and upper limit with variable b. To track down the base and most extreme ownership of these factors Equation (5), given beneath, is regularly utilized: Triangle (x; a, b, m) = max(min(x-a, b-m), min(m-x, b-a))

In our proposed fluffy rationale module for the shrewd water system framework, Equations (4) and (5) assume a significant part in the fuzzification stage. We have executed these conditions in MATLAB. These conditions help in building up a bunch of four enrollment capacities focused on a bunch of info etymological factors and a participation work for a yield variable. The four participation capacities are intended for the info boundaries, for example, temperature change rate, dampness change rate, light change rate, and dampness change rate. A participation work is additionally characterized for the yield phonetic variable water need. The MATLAB Fuzzy Logic tool kit is utilized to characterize every one of these six enrollment capacities help in the fuzzification cycle of every one of these six semantic factors

3.3.2. THE FUZZY INFERENCE MODULE:

A fluffy surmising module assumes a significant part in the dynamic interaction of the proposed savvy watering framework. A bunch of assuming standards were characterized to work with the enrollment capacities characterized in the past segment. The fluffy induction module utilized in our fluffy rationale framework is planned utilizing Mamdani fluffy surmising framework idea and it maps the fluffy contributions to a fluffy yield. The quantity of steps were followed to carry out the proposed induction module utilizing Mamdani fluffy deduction idea such to join the fuzzified inputs, assemble a bunch of fluffy standards, consolidate rule strength, apply yield enrollment work, at long last consolidate yields to produce a yield conveyance and defuzzify the yield participation work. The cycle of defuzzification is clarified . The characterized fluffy guidelines are executed utilizing an assuming assertion for each standard. Conditions (6) and (7) address the pre-owned induction module conduct of four data sources and two standards put away in a standard base:

On the off chance that (W_1 is $A1_1$ AND X_1 is $A1_2$ AND Y_1 is $A1_3$ AND Z_1 is $A1_4$) THEN (w is $B1$) (6)

In the event that (W_2 is $A2_1$ AND X_2 is $A2_2$ AND Y_2 is $A2_3$ AND Z_2 is $A2_4$) THEN (w is $B2$) (7)

The fluffy induction module fills in as depicted. When the four data sources are fuzzified by handling of the four info participation works, the fuzzified inputs are consolidated to discover the standard strength with the assistance of AND administrator. The yield enrollment work follows the in the past segment. The fluffy derivation module utilized in our fluffy rationale framework is planned utilizing Mamdani fluffy induction framework idea to handle each standard lastly finishes up a fuzzy field.

3.3.3. THE DEFUZZICATION MODULE:

The last advance in execution of the keen water system framework is defuzzification. Since, a standard set is utilized to assess the yield. The principles are applied to the fuzzified values and a fluffy yield is produced by a solitary fluffy guideline and that fluffy yield is changed over to a scalar amount. The proposed defuzzification module depends on centroid defuzzification strategy is as it furnishes with exact outcome as demonstrated in Equation (8):

$$x^* = \frac{\int \mu_i(x) \cdot x dx}{\int \mu_i(x) \cdot dx} \quad (8)$$

As demonstrated in Equation (8), the defuzzified yield is signified by x^* that is created by $\mu_i(x)$ for the yield variable x .

3.4 IMPLEMENTATION DETAILS:

The keen water system framework for burrow cultivating was executed in MATLAB. The framework carried out in lab utilizes an Arduino UNO (ATmega328P) regulator. The microcontroller gets information from sensors and forward to the fluffy rationale choice emotionally supportive network that is conveyed the primary worker. Following area briefs the subtleties of the sensors used to execute the proposed keen water system framework for burrow cultivating

3.4.1. USED HARDWARE:

The proposed savvy water system framework for burrow cultivating utilizes a bunch of

sensors to gather information from soil and air. For soil dampness, we have utilized the HL-69 Soil Hygrometer sensor. Also, for temperature and mugginess, we have utilized an AM2302 DHT22 sensor. For light, the BH1750 FVI light sensor is utilized. A concise depiction of these sensors is given underneath:

3.4.2. HL-69 Soil Hygrometer Moisture Sensor

The HL-69 hygrometer is used to detect the humidity of the soil. It provides better reading than other soil moisture sensors. Experts recommend this sensor for real-time monitoring of the soil moisture of plants in a tunnel farm and to build an automatic irrigation system. A typical HL-69 hygrometer.




Figure 3.1 A HL-69 Soil Hygrometer for soil moisture sending.

The following are a few key features of the HL-69 Soil Hygrometer used for soil moisture sensing in a tunnel farm:

- Operating voltage: 3.3~5 V
- Dual output mode—digital or analog—analogue output more accurate
- LM393 comparator chip, stable

- Fixed bolt hole for easy installation
- Power indicator (red) and digital switching output indicator (green)
- Soil probe dimension: approx. 6 cm × 3 cm
- Cable length: approx. 21 cm
- Panel PCB dimensions: approx. 3 cm × 1.5 cm

3.4.3 AM2302 DHT22 Sensor

The DHT22 is a common and cheap sensor used for detecting the humidity in air and temperature. In our experiments, we have used AM2302 model of DHT22 sensors that provides a calibrated and accurate output. A typical AM2302 DGT22 sensor is shown in Figure 3.2.




Figure 3.2 AM2302 DHT22 sensor for light and humidity.

- 3 to 5 V power and I/O
- Good for 0–100% humidity readings with 2–5% accuracy
- 2.5 mA max current use during conversion (while requesting data)
- No more than 0.5 Hz sampling rate (once every 2 s)
- Good for –40 to 80 °C temperature readings ± 0.5 °C accuracy
- 4 pins with 0.1" spacing
- Body size 15.1 mm × 25 mm × 7.7 mm

3.4.4. BH1750 FVI LIGHT SENSOR:

The BH1750 is a common sensor that can detect the light intensity. For implementation of the proposed system, the Bh1750 FVI light sensor is also used. A typical BH1750 FVI sensor is shown in Figure 3.3.




Figure 3.3 BH1750 FVI light sensor.

The BH1750 is a calibrated digital light sensor and it can measure the even small traces of light and can convert it into a 16-bit digital numeric value. It measures light intensity in the range of 0 to 65,535 Lux (L). In our experiments, we have used the H-resolution mode. The following are key features of BH1750 light sensor:

- Chip: BH1750FVI
- Power Supply: 3.3–5 V
- Sensor Built-in: 16 bit AD converter
- Light Range: 0–65,535 lx(Lux)
- Direct digital output, bypassing the complex calculation, bypassing the calibration

- Size (L × W): approx. 3.2 cm × 1.5 cm
- Widely used to 1-lux high precision measurement
- Close to the spectral characteristics of visible light

3.5 DESIGN OF A MEDIUM SIZE TUNNEL FARM:

There is no standard size for a high passage, yet it ought to be huge enough for the cultivator to plant, screen and reap the harvest from inside the construction. Passages are normally 14 to 28 feet wide, 7 to 12 feet tall at the middle (contingent upon width), and 48 to 96 feet in length, or a length in any four-foot span. It is normally suggested that passages ought to be no more extensive than 30 feet for cross ventilation and to keep away from snow amassing on the rooftop. Plan of the testbed burrow ranch for shrewd water system is appeared in Figure 3.4.




Figure 3.4 A tunnel form of 14 × 48 feet planned with smart irrigation.

A common dampness sensor typically peruses measurement of 10–15 cm around the test. Nonetheless, the HL-69 hygrometer with long needles is adequate to cover space of 2–3 feet in distance across. Here, the length of the sensor bar and number of sensors on the pole decides the space of inclusion by a sensor. The estimations by HL-69 hygrometer are ordinarily taken from 30 cm to 150 cm profound. To cover a space of 14 × 48 feet of a passage structure, 30 to 36 sensors are adequate. Essentially, two

AM2302 sensors for every field are recommended for detecting temperature and stickiness. In a field of 14 × 48 feet, two BH1750 sensors are adequate. An exploratory testbed was set up at the open air horticulture lab at the Islamia University of Bahawalpur. Figure 3.5 a,b show the outer and interior perspective on the testbed produced for the shrewd water system framework tests.



Figure 3.5 . Proving ground of the savvy water system framework. (a) External view; (b) turner stage (15 days); (c) mid-age plant (50 days); (d) develop age plant (100 days). shows the various phases of a green bean stew plant. The space of investigation was Bahawalpur and the hour of test was July to September and in these months outside temperature goes from 35–40 °C during the daytime and 30–35 °C at evening. Table 3 shows the insights of the proposed plan of a 14 × 48 passage structure. The savvy water system framework for burrow cultivating is a shrewd framework that appreciates the advantages of the genuine dynamic capacity of the fluffy rationale approach. The utilization of canny methodologies for sensor-based water system frameworks is a novel thought. The engineering of the proposed framework and its execution subtleties are

given in the past segments. To test the presentation of the proposed framework, three kinds of sensors (light, temperature and dampness and dampness sensors) were planted on a testing field. The info information got from the sensors is sent to the worker and results are appeared at an Android application and an internet browser and accordingly a client can play out certain activities. This framework is completely programmed. The four kinds of sensor information is gotten from three sensors and the aligned yield is handled utilizing fluffy rationale approach with the assistance of order tables appeared underneath. It shows three classes (high/wet, ordinary, low/dry) for different degrees of soil dampness recognized by the HL-69 Hygrometer sensor. A common HL-69 Hygrometer sensor gives yield in the scope of 0 to 870.





Figure 3.6 . Sensor's data with variation.

When the info information is aligned, the fluffy rationale approach was utilized to choose the watering needs of a plant. Table shows the aligned yield of sensor's information and the choice taken by the fluffy rationale and the exactness of the choice adopted by the fluffy rationale strategy. As it very well may be seen from Table that the precision of proposed SWS in close to 100%, which implies that the framework is working as indicated by our characterized rules for SWS. The general exactness of the proposed SWS is determined utilizing Equation (9): $SWS\ Accuracy = \sum \mu(a_i)n$

Condition (9) is utilized to determined the precision of shrewd water system framework where $\mu(a_i)$ addresses the exactness level of each trial and n addresses the complete

number of investigations. As per tests we accomplished a normal precision of 98.0%.

The presentation of the framework was tried. Table shows the consequences of three cases that show the saving of water at three phases of plant's development, for example, turner stage, mid-age and develop stage. In Case 1, the water utilization with the ordinary technique is 935.22 at the turner stage and 591.51 with the savvy water system stage. Generally the all out reserve funds of water in Case 1 was 864 $\text{m}^3\cdot\text{m}^{-3}$. Essentially, the investment funds of water in Case 2 were 982 and in Case 3 the investment funds were 898. The saving of water is more than every one of the past investigations, especially those appeared in Table 10. The aftereffects of three contextual analyses are additionally graphically addressed in Figure 11.



The aftereffects of the trials uncover that the utilization of a canny methodology for productive dynamic surely helps in improving the consequences of a sensor-based framework. A methodology that is insightful cannot just improve the exhibition of IoT- and sensor-based frameworks yet additionally the throughput of such frameworks can be upgraded yet more exact and savvy choices taken by such brilliant frameworks. Figure 3.4 plainly features the manner in which the savvy water system framework is helping in saving water in burrow cultivating and accomplishing high profitability. As examined in Section 2, there are numerous sensor-based water system frameworks yet none of them explicitly address water system for burrow cultivating. Moreover, past approaches don't utilize smart methodologies with IoT to get precise choices for proficient watering of plants. Our methodology presents an original thought of utilizing

fluffy rationale for effective dynamic of watering amount and watering plan. The outcomes show that our methodology saves more water than the past approaches. Our methodology for keen water system of passage cultivating has the accompanying oddities and commitments:

- This is the primary methodology that presents a shrewd water system framework for burrow cultivating.
- Previous sensor-base water system frameworks depend on shortsighted dynamic methodologies, we propose the utilization of fluffy rationale and accomplished much better outcomes.
- None of the past approaches address the issue of energy utilization in savvy water system frameworks.
- Previous approaches generally depend on soil dampness to choose the water needs of a plant. Our methodology thinks about four boundaries (soil dampness, temperature, moistness, and light force) for more exact dynamic that is a clever thought.
- A information base of plants and their watering needs regarding the dirt sort (mud, residue, sand, and so forth) is utilized for proficient watering and it is an original thought.
- The results given in Table 9 obviously show that our framework is more proficient and viable in saving more water and accomplishing greater profitability in burrow cultivating. The consequences of our methodology (Table 9) beat every one of the past approaches in productive water saving.

CHAPTER 4 RESULTS AND DISCUSSION

RESULTS




FIGURE 4.1 SOFTWARE CONNECTION RESULTS



FIGURE 4.2 HARDWARE CONNECTION

The Humidity sensor and Temperature sensor and its association with

Arduino is set up in the above figure created utilizing Proteus.

DHT11 Humidity/Temperature sensor is utilized to gauge the Temperature and Humidity. DHT11 can be utilized at a few better places for example home machines, climate stations, shopper products and so on In this undertaking, interface DHT11 Sensor with Arduino in proteus window and the estimation of temperature/mugginess showing in virtual terminal as chronic screen. DHT11 estimates relative stickiness.

Relative dampness is the measure of water fume noticeable all around versus water fume noticeable all around. DHT11 recognizes water fume by estimating electrical opposition between two cathodes.

The moistness detecting segment is the dampness holding substrate with anodes applied to the surface.

DHT11 has a ton of highlights including ease, long haul soundness, quick reaction time, fantastic quality, significant distance signal transmission and some more. For more data about DHT11 Sensor.




FIGURE 4.3 SOIL SENSOR



FIGURE 4.4 MOTOR IS ON

Soil sensor is interfacing with arduino uno for sensing soil characteristics of land.




FIGURE 4.5 Soil, Humidity and Temperature sensor are interfaced using Proteus




FIGURE 4.6 AURDIUNO BOARD

The Arduino UNO is the best board to get started with electronics and coding. The UNO is the most used and documented board of the whole Arduino family.



FIGURE 4.7 AURDINO BOARD

4.1 RAIN WATER TANK LEVEL SENSOR:

The sensor has a progression of ten uncovered copper follows, five of which are power follows and five are sense follows. These follows are intertwined so that there is one sense follow between each two force follows. Normally these follows are not associated however are spanned by water when lowered.



FIGURE 4.8 RAIN SENSOR

4.2 RAIN SENSOR:

A straightforward Rain Detection System can be effectively worked by interfacing an Arduino with Rain Sensor. The sensor will recognize any precipitation falling on it and the Arduino board will detect it and can perform required activities. A framework like this can be utilized in various fields, for example, horticulture and car fields.



Figure 1.17

4.3 DC Motor

DC engine changes over electrical energy as Direct Current into mechanical energy as rotational movement of the engine shaft. The DC engine speed can be constrained by applying shifting DC voltage; while the bearing of revolution of the engine can be altered by turning around the course of current through it.




FIGURE 4.9 SOIL SENSOR

4.4 SOIL SENSOR:

The Soil Moisture Sensor utilizes capacitance to gauge dielectric permittivity of the encompassing medium. In soil, dielectric permittivity is a component of the water content. The sensor makes a voltage relative to the dielectric permittivity, and in this manner the water substance of the dirt.

CHAPTER 5

CONCLUSION AND FUTURE WORK

The proposed approaches utilize four sensors soil dampness sensor, mugginess sensor, temperature sensor and a light sensor for better proficiency. Moreover, the watering needs of a plant are likewise put away in an information base. Our methodology utilizes an insightful strategy dependent on a fluffy rationale way to deal with choose watering amount and timetable of a plant considering plant type, climate conditions, soil dampness level, stickiness, temperature, and so forth Our methodology centers around productive energy utilization as it doesn't turn ON every one of the sensors constantly. The sensors are occasionally turned ON and killed on a case by case basis. A wise calculation handles the effective use of sensors to guarantee proficient energy utilization and to keep the working expense of this framework low. The proposed approach explicitly addresses water system issues of passage framing and can be similarly productively utilized with either a sprinkling strategy or a trickle water system technique. The consequences of this investigation are not difficult to imitate as the sensors utilized are modest and simple to get to. The investigation talks about in this paper was tried on a little territory, (for example, little passage ranches, home nurseries, and so forth) yet the consequences of the tests show that the pre-owned methodology can be summed up and can be utilized for productive water system of huge size fields. The aftereffects of the trials support the viability of the proposed approach and its execution with the assistance of a fluffy rationale approach.

REFERENCES

- [1] Al-Radaideh, A.; Al-Ali, A.R.; Bheiry, S.; Alawnah, S. A wireless sensor network monitoring system for highway bridges. In Proceedings of the 2015 International Conference on Electrical and Information Technologies (ICEIT), Marrakech, Morocco, 25–27 March 2015.
- [2] Arvindan, A.N.; Keerthika, D. Experimental investigation of remote control via Android smart phone of arduino-based automated irrigation system using moisture sensor. In Proceedings of the 2016 3rd International Conference on Electrical Energy Systems (ICEES), Chennai, India, 17–19 March 2016.
- [3] Blonquist, J.M.; Jones, S.B.; Robinson, D.A. Precise irrigation scheduling for turfgrass using a subsurface electromagnetic soil moisture sensor. *Agric. Water Manag.* 2006, 84, 153–165.
- [4] Bonanomi, G.; D'Ascoli, R.; Antignani, V.; Capodilupo, M.; Cozzolino, L.; Marzaioli, R.; Rao, M.A. Assessing soil quality under intensive cultivation and tree orchards in Southern Italy. *Appl. Soil Ecol.* 2011, 47, 184–194.] .
- [5] Cancela, J.J.; Fandino, M.; Rey, B.J.; Martínez, E.M. Automatic irrigation system based on dual crop coefficient, soil and plant water status for *Vitis vinifera* (cv Godello and cv Mencía). *Agric. Water Manag.* 2015, 151, 52–63.
- [6] Cardenas-Lailhacar, B.; Dukes, M.D.; Miller, G.L. Sensor-based automation of irrigation on bermudagrass, during dry weather conditions. *J. Irrig. Drain. Eng.* 2008, 134, 184–193.
- [7] Chikankar, P.B.; Mehetre, D.; Das, S. An automatic irrigation system using ZigBee in wireless sensor network. In Proceedings of the 2015 International Conference on Pervasive Computing (ICPC), Pune, India, 8–10 January 2015.
- [8] Dukes, M.D. Water conservation potential of landscape irrigation smart controllers. *Trans. ASABE* 2012, 55, 563–569.
- [9] Dursun, M.; Oden, S. An efficient improved photovoltaic irrigation system with artificial neural network based modeling of soil moisture distribution—A case study in Turkey. *Comput. Electron. Agric.* 2014, 102, 120–126.

- [10] Ferrarezi, R.S.; Dove, S.K.; van Iersel, M.W. An automated system for monitoring soil moisture and controlling irrigation using low-cost open-source microcontrollers. *HortTechnology* 2015, 25, 110–118.
- [11] Gutiérrez, J.; Villa-Medina, J.F.; Nieto-Garibay, A.; Porta-Gándara, M.Á. Automated irrigation system using a wireless sensor network and GPRS module. *IEEE Trans. Instrum. Meas.* 2014, 63, 166–176.
- [12] Kansara, K.; Zaveri, V.; Shah, S.; Delwadkar, S.; Jani, K. Sensor based Automated Irrigation System with IOT: A Technical Review. *Int. J. Comput. Sci. Inf. Technol.* 2015, 6, 5331–5333.
- [13] Kim, Y.; Evans, R.G. Software design for wireless sensor-based site-specific irrigation. *Comput. Electron. Agric.* 2009, 66, 159–165.
- [14] Kim, Y.; Evans, R.G.; Iversen, W.M. Remote sensing and control of an irrigation system using a distributed wireless sensor network. *IEEE Trans. Instrum. Meas.* 2008, 57, 1379–1387.
- [15] Konyha, J.; Bányai, T. Sensor networks for smart manufacturing processes. *Solid State Phenom.* 2017, 261, 456–462.
- [16] Kumar, A.; Kamal, K.; Arshad, M.O.; Mathavan, S.; Vadamala, T. Smart irrigation using low-cost moisture sensors and XBee-based communication. In *Proceedings of the Global Humanitarian Technology Conference (GHTC)*, San Jose, CA, USA, 10–13 October 2014.
- [17] Liu, J.; Zhang, W.; Chu, X.; Liu, Y. Fuzzy logic controller for energy savings in a smart LED lighting system considering lighting comfort and daylight. *Energy Build.* 2016, 127, 95–104.
- [18] Logambigai, R.; Kannan, A. Fuzzy logic based unequal clustering for wireless sensor networks. *Wirel. Netw.* 2016, 22, 945–957.
- [19] Mahmood, N.; Anees, M.; Ahmad, S.; Zakaullah. Effect of mulching on vegetables production in tunnel farming. *Mycopathologia* 2011, 9, 21–24.
- [20] Mamdani, E.H. Application of fuzzy logic to approximate reasoning using linguistic synthesis. *IEEE Trans. Comput.* 1977, 26, 1182–1191.

- [21] McCready, M.S.; Dukes, M.D.; Miller, G.L. Water conservation potential of smart irrigation controllers on St. Augustinegrass. *Agric. Water Manag.* 2009, 96, 1623–1632.
- [22] Navarro-Hellín, H.; Torres-Sánchez, R.; Soto-Valles, F.; Albaladejo-Pérez, C.; López-Riquelme, J.A.; Domingo-Miguel, R. A wireless sensors architecture for efficient irrigation water management. *Agric. Water Manag.* 2015, 151, 64–74.
- [23] Nikolidakis, S.A.; Kandris, D.; Vergados, D.D.; Douligeris, C. Energy efficient automated control of irrigation in agriculture by using wireless sensor networks. *Comput. Electron. Agric.* 2015, 113, 154–163.
- [24] Olson, T.C. Microprocessor-Based Irrigation System with Moisture Sensors in Multiple Zones. U.S. Patent 5,337,957, 16 August 2018.
- [25] Parameswaran, G.; Sivaprasath, K. Arduino Based Smart Drip Irrigation System Using Internet of Things. *Int. J. Eng. Sci.* 2016, 6, 5518.
- [26] Pavithra, D.S.; Srinath, M.S. GSM based automatic irrigation control system for efficient use of resources and crop planning by using an Android mobile. *IOSR J. Mech. Civ. Eng.* 2014, 11, 49–55.
- [27] Qualls, R.J.; Scott, J.M.; DeOreo, W.B. Soil moisture sensors for urban landscape irrigation: Effectiveness and reliability. *J. Am. Water Res. Assoc.* 2001, 37, 547–559.
- [28] Rani, M.U.; Kamalesh, S. Web based service to monitor automatic irrigation system for the agriculture field using sensors. In *Proceedings of the 2014 International Conference on Advances in Electrical Engineering (ICAEE)*, Vellore, India, 9–11 January 2014.
- [29] Rawal, S. IOT based Smart Irrigation System. *Int. J. Comput. Appl.* 2017, 159.
- [30] Rodriguez, S.A.B.; Hamann, H.F.; Klein, L.; Marianno, F.J. Targeted Irrigation Using a Central Pivot Irrigation System with a Sensor Network. U.S. Patent 9,943,046, 17 April 2018.
- [31] Sales, N.; Remedies, O.; Arsenio, A. Wireless sensor and actuator system for smart irrigation on the cloud. In *Proceedings of the 2015 IEEE 2nd World Forum on Internet of Things (WF-IoT)*, Milan, Italy, 14–16 December 2015.

- [32] Sarwar, B.; Bajwa, I.; Ramzan, S.; Ramzan, B.; Kausar, M. Design and Application of Fuzzy Logic Based Fire Monitoring and Warning Systems for Smart Buildings. *Symmetry* 2018, 10, 615.
- [33] Soulis, K.X.; Elmaloglou, S.; Dercas, N. Investigating the effects of soil moisture sensors positioning and accuracy on soil moisture based drip irrigation scheduling systems. *Agric. Water Manag.* 2015, 148, 258–268.
- [34] Tarange, P.H.; Mevekari, R.G.; Shinde, P.A. Web based automatic irrigation system using wireless sensor network and embedded Linux board. In *Proceedings of the 2015 International Conference on Circuits, Power and Computing Technologies [ICCPCT-2015]*, Nagercoil, India, 19–20 March 2015.
- [35] Vasanth, A.; Grabow, G.L.; Bowman, D.; Huffman, R.L.; Miller, G.L. Evaluation of evapotranspiration-based and soilmoisture-based irrigation control in turf. *Biol. Agric. Eng.* 2008.
- [36] Xiao, K.; Xiao, D.; Luo, X. Smart water-saving irrigation system in precision agriculture based on wireless sensor network. *Trans. Chin. Soc. Agric. Eng.* 2010, 26, 170–175.