

A HEURISTIC SOLUTION FOR TRUST BASED ENERGY EFFICIENT DATA COLLECTION IN WIRELESS SENSOR NETWORKS

Submitted in partial fulfilment of the requirements for the award of
**Bachelor of Engineering Degree in
Electronics and Communication Engineering**

BY

**CHERUKUMALLI NIKHIL (37130283)
PODUGU VENKATA SAI GANESH (37130317)**



**DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING
SCHOOL OF ELECTRICAL AND ELECTRONICS**

SATHYABAMA

**INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)**

Accredited with Grade “A” by NAAC

JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI - 600 119

APRIL 2021



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY

(DEEMED TO BE UNIVERSITY)

Accredited "A" Grade by NAAC | 12B Status by UGC | Approved by AICTE

www.sathyabama.ac.in

DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of **CHERUKUMALLI NIKHIL (37130283), PODUGU VENKATA SAI GANESH (37130317)** who carried out the project entitled **"A HEURISTIC SOLUTION FOR TRUST BASED ENERGY EFFICIENT DATA COLLECTION IN WIRELESS SENSOR NETWORKS"** under my supervision from AUG 2020 to MARCH 2021.

Internal Guide

Dr. S. EMALDA ROSLIN, M.E., Ph.D.,

Head of the Department

Dr. T.RAVI, M.E., Ph.D.,

Submitted for Viva voce Examination held on _____

Internal Examiner

External Examiner

DECLARATION

We **CHERUKUMALLI NIKHIL (37130283), PODUGU VENKATA SAI GANESH (37130317)** hereby declare that the Project Report entitled **“A HEURISTIC SOLUTION FOR TRUST BASED ENERGY EFFICIENT DATA COLLECTION IN WIRELESS SENSOR NETWORKS”** done by us under the guidance of **Dr. S. EMALDA ROSLIN, M.E., Ph.D.,** at **SATHYABAMA INSTITUTE OF SCIENCE AND TECHNOLOGY** is submitted in partial fulfilment of the requirements for the award of Bachelor of Engineering degree in Electronics and Communication Engineering.


DATE : 17.04.2021

1.



PLACE : CHENNAI

2.



SIGNATURE OF THE CANDIDATE

ACKNOWLEDGEMENT

We are pleased to acknowledge our sincere thanks to Board of Management of **SATHYABAMA** for their kind encouragement in doing this project and for completing it successfully. We are grateful to them.

I convey my thanks to **Dr. N. M.NANDHITHA, M.E., Ph.D.**, Prof. & Dean, School of Electrical and Electronics Engineering and **Dr. T. RAVI, M.E., Ph.D.**, Head of the Department, Dept. of Electronics and Communication Engineering for providing me necessary support and details at the right time during the progressive reviews.

I would like to express my sincere and deep sense of gratitude to my Project Guide **Dr. S. EMALDA ROSLIN, M.E., Ph.D.**, for her valuable guidance, suggestions and constant encouragement paved way for the successful completion of my project work.

I wish to express my thanks to all Teaching and Non-teaching staff members of the Department of **Electronics and Communication Engineering** who were helpful in many ways for the completion of the project.

ABSTRACT

Wireless sensor networks are being used more frequently (WSNs). As a result, the major issues in WSNs are overhead connectivity and sensor node power consumption. It is important that the information transmitted is genuine in order to avoid any significant device performance degradation caused by false or inaccurate information. Create the presumption that the information to be shared will be used by two machines, with the assurance that the information will be right. It will have a secure and reliable system that recognises all devices and prevents data from being sent to unauthorised devices. The key contribution to this task is a new, dynamic, and confidence-based clustering system, in which nodes can connect and begin securely transferring data to a dish as soon as it becomes usable. We developed cluster head trust propagation (CHTP) software to increase network data collection cycles while reducing the time required to differentiate malicious network faith-attacking activities from stable, malicious confidence-resistant WSNs. Data processing times, data isolation intervals, and the remaining battery are all phases in the performance monitoring phase. The proposed performance evaluations were created with the goal of reducing overhead access, grid energy consumption, and avoiding trade-offs between personal data and current practises.

TABLE OF CONTENTS

CHAPTER NO.	TITLE	PAGE NO.
	ABSTRACT	v
	LIST OF FIGURES	viii
	LIST OF TABLES	ix
	LIST OF ABBREVIATION	x
1.	INTRODUCTION	1
	1.1 OBJECTIVES	6
2.	LITERATURE SURVEY	8
	2.1 COMPARISON OF LITERATURE SURVEY	12
3.	DESIGN GOALS FOR WIRELESS MICRO SENSOR	13
	3.1 MEETING THE DESIGN GOALS	14
	3.2 SYSTEM ARCHITECTURE OF A SENSOR NODE	14
	3.3 RADIO ENERGY DISSIPATION MODEL	15
4.	ROUTING PROTOCOLS	18
	4.1 MULTI HOP ROUTING PROTOCOLS	18
	4.2 QUALITY OF SERVICE IN WSNS	18
5.	EXISTING TECHNIQUE	22
	5.1 ENERGY EFFICIENT ROUTING PROTOCOL	22
	5.2 SELECTION OF CLUSTER HEAD	22
	5.3 DATA TRANSMISSION PHASE	23
6.	PROPOSED TECHNIQUE	24
	6.1 LEACH	24
	6.2 SET UP PHASE	26
	6.3 STEADY STATE PHASE	26

CHAPTER NO.	TITLE	PAGE NO.
	6.4 RESIDUAL ENERGY SCAN	26
	6.5 DETERMINING LOCAL E SCANS	27
	6.6 AGGREGATING E SCANS	27
	6.7 ALGORITHM	27
7.	IMPLEMENTATION	29
8.	RESULTS AND DISCUSSION	31
9.	CONCLUSION AND FUTURE WORK	39
	REFERENCES	40

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE NO.
1.1	CONFIGURATION OF WIRELESS SENSOR NETWORK	2
3.1	BLOCK DIAGRAM OF A SENSOR NODE	31
3.2	RADIO MODEL	16
8.1	PERFORMANCE FOR SELECTION OF CH	31
8.2	REMAINING ENERGY	32
8.3	PERFORMANCE OF NODES ALIVE IN WSN	33
8.4	ROUTING PROTOCOL WITH EFFICIENT ENERGY	34
8.5	ENERGY CONSUMPTION	35
8.6	ERROR DETECTION AT THE RECEIVER	36
8.7	CLUSTERING OF NODES	37
8.8	CLUSTERING OF WSN NETWORK	38

LIST OF TABLES

TABLE NO.	TITLE	PAGE NO.
2.1	COMPARISON OF LITERATURE SURVEY	12
8.1	SUMMARY OF GRAPHS IN TABULATION	38

LIST OF ABBREVIATIONS

BPA	-	Basic Probability Assignment
BS	-	Base Stations
CHTP	-	Cluster Head Trust Propagation
DFS	-	Dynamic Frequency Scaling
DPM	-	Dynamic Power Management
DVS	-	Dynamic Voltage Scaling
ECHC	-	Energy and Node Concentration Hierarchical Clustering Algorithm
LEACH	-	Low-Energy Adaptive Clustering Hierarchy
MAC	-	Medium Access Layer
MANET	-	Mobile Ad-Hoc Networks
MCMP	-	Multi-Constraint MultiPath
QoS	-	Quality of Service
SAR	-	Sequential Assignment Routing
SNR	-	Signal-to-Noise Ratio
UAV	-	Unmanned Aerial Vehicle
WSN	-	Wireless Sensor Network

CHAPTER 1

INTRODUCTION

The wireless network of sensors consists of small sensor nodes, computing and wireless communication. Many WSN routing protocols have taken the energy response as a core strategic challenge specifically now. In order that physical and environmental conditions such as temperature, sound, vibrations, friction and turning are monitoring at various locations in a wireless sensor network (WSN) hundreds or even thousands of small sensor sensors are distributed. Energy is crucial for wireless sensor networks as battery-powered hubs.

Several protocols were therefore established to reduce their energy use. The energy sources in the most wireless sensor networks are battery, and energy is essential to the wireless sensor network. Each node of the sensor network has one or more sensors, a radio transceiver or a wireless communication device, a small microcontroller or an electricity supply. The literature has used such routing protocols as leaching.

This paper proposes to upgrade the Leach Protocol even further to increase the power efficiency; the simulation results show that our protocol, in terms of energy use and global performance, is superior to the Leach Protocol. Leach has built a protocol using cluster-based routing to save space. Figure 1.1 shows the configuration of WSNs, a network of sensors with different sensor nodes.

The database or sink node transfers all of these nodes. Data from sensor nodes to the network is collected and forwarded to the sink. The sink node sends customer information through the Internet.

Functions and limitations like MANET mobile devices, such as a low energy consumption, battery life and memory capacity, are similar to Wireless Sensor Networks (WSNs). The WSNs are almost the same.




Fig. 1.1: Configuration of Wireless Sensor Network

A front-end software starts the network of wireless sensors. There was no point-to-point coordination of the routing protocols. New opportunities have expanded in the fields of health, production and other tracking technologies and more efficient routing protocols are required.

The programmers have to address two problems when developing wireless sensor networks: lower memory and higher power consumption. The WSNs are basic applications, with nodes that detect, save, and aggregate data before it is sent to the destination. In order to perform these functions, it should also be included in the WSN routing protocol.

Awareness of space, scalability in a limited energy and climate and adaptation to a small memory environment are key applications for calculating an effective routing protocol. Such instances are as follows: Because of limited energy resources, clustering routing protocols are more essential. Flexible, energy-intense and difficult to use direct transfer and flat routing protocols.

Cluster formation is a two-stage predictor, with higher levels set by the CH nodes and lower levels set by the cluster nodes. The sensor nodes irregularly transmit data to the relevant CH nodes. CH nodes link data to a base station bed and send it either straight or in an intermediate rating to other CH nodes (reduce the total number of relayed packets). Wisdom is supplemented with CH nodes.

Cluster formation is a two-stage predictor, with higher levels set by the CH nodes and lower levels set by the cluster nodes. The sensor nodes irregularly transmit data to the relevant CH nodes. CH nodes link data to a base station bed and send it either straight or in an intermediate rating to other CH nodes (reduce the total number of relayed packets). Wisdom is supplemented with CH nodes.

Heinzelman will present the protocol. It uses a dense network of identical, unnatural nodes of energy. These nodes are responsible for the transfer to a sink node of their data. This protocol uses the TDMA MAC protocol to build a unified clustering approach. Nodes are divided into groups in LEACH. Each group has a cluster head which creates and manages TDMA and all other nodes belong to each group.

All member nodes were assigned TDMA schedules. This list is useful for the cluster head exchange of data. Cluster nodes of the members send their CH data and send them to the drain. The main research concern was the power capacity of wireless sensor networks (WSN). Thus, it is necessary for WSN routing to establish an energy-efficient protocol.

Two remote routing protocol implementations are currently underway. The first is a flat routing, with a similar function performed by any sensor node and transmitting its Information to a sinking node, which often leads to useless data.

Redundancy of electricity and use of speed. The other choice is to follow the procedure. The whole system is divided into many clusters of hierarchic routing. Several root nodes and a cluster head exist in any cluster.

Sensor nodes, also known as source nodes, can collect and send data from the area detected. The cluster head is chosen in a cluster based on these

parameters from all sensor nodes and is responsible for data collection from source nodes.

After collection of data from sources, the cluster head usually collects data to minimise the data size before transferring data to the sink, thereby reducing the data transfer capacity further.

Data from different parameters are collected from the sensor nodes and transmitted through the wireless sensor network to the base station. However, recent improvements in MEMS sensor technology, low power electronics and the low power architecture have produced cost-effective wireless micro sensors, but their cost and scale have made the acquisition of defect-tolerant and high-quality sensing networks possible for hundreds or thousands of network applications.

The sensor gathers information on a particular parameter, including pressure, temperature, moisture, movement, etc. Four main components are included in the wireless sensor node: a connector sensor unit, a data processing unit, a wireless radio and a power supply unit. Sensor nodes are frequently powered by energy as they rely on it as a battery power source. At the base station, the estimated volume of the parameter is then processed.

Sensor nodes are not prefabricated or fixed in these networks, which allows intermittent distribution of unavailable soil or disaster relief operations. Understanding each portion of the network and the resources available can be used in forecasting corrective measures such as the re-deployment of new nodes before energy exhaustion spreads over many segments of the grid. In order to save its resources for further work, routing protocols may also use the energy map information to re-track residual nodes.

The energy efficiency of protocols can also be estimated with this knowledge. An energy diagram depicts the amount of residual energy in the network. To correct calculations such as redeploying new nodes, an energy survey should be carried out on each part of the grid until any parts of the grid can recover from energy depletion.

Routing protocols may also use information from an energy map to re-route nodes with high residual energy to conservation of energy. This data can also be used to estimate protocols' energy efficiency. The next phase in the further evolution in the production, operation, industrial, home, shipboard and transport automation systems are replaced by intelligent conditions.

Like any conscious human, intelligent situations are mostly based on sensory data from today's world. In various assigned locations sensor data were obtained from different sensors. Specifics of the environment and internal functioning of the intelligent world are required; exteroceptors and proprioceptors separate them into biological systems. For an analysis of rationalised deployment strategies of these sensing networks for wireless network efficiency, the data processing capacity and lifetime of the sensor systems are important.

There are some substantial open problems due to the fundamental constraint of these two main performance parameters. In the first place, what is the optimal potential of the network? Secondly, how much time will the network last? Typically these questions include a list of the network sensor parameters to help you navigate your network better. In addition to the number of sensor nodes in the network and the area of the network sensor, the various parameters are implemented in the sensor network.

The complexities of the network infrastructure usually involve packet routing, storage, and congestion management, which have important effects on the quality of service. Sharing quality (SAR) was one of the first service reliability routing protocols (QoS). The SAR model trees are from a sink one-hop district, and they take into account two types of QoS metrics: energy resource resources and priority levels for each packet are constructed from sink to source, and routes can be selected based on QoS metrics.

In contrast, SAR is committed to maintaining an overhead tolerance node state. The reliability of various MAC systems, based on CSMA and polling technology for WSNs, which can be easily supplied by the use of energy collectors, is studied by Zhi Ang Eu et al. Zhi Ang Eu and his associates The survey is focused on I of the transmission network (S) at the rate of sensor data collected on the drin,

(ii) the fairness index (F), which measures if the bandwidth is equal at each sensor node, and (iii) the inter-arrival time used to measure the medium time difference from the source node between two packets.

They are differentiated by the slotted and unslotted forms of CSMA. The polling is recognised for the first time. Then design a probabilistic survey protocol that takes into account the unknown energy selection mechanism in order to achieve good results. They also present a high-efficiency theoretical MAC protocol survey. The analytical designs are validated by extensive models which incorporate preliminary effects from the characterisation of multiple energy collectors.

With respect to results, fairness and lower interarrival times in probabilistic surveys, progress appears to be high. RenShiou Liu et al. prefer a low-level MAC approach to deal with the highest containment problem, enhance performance of the device and reduce energy consumption. Low-conflict scattering times of adjacent nodes are used to remove backlogs and improve CSMA efficiency efficiently. They differ on the basis of the analytical design, the predicted performance improvement.

The selected system can be shown to increase throughput by up to four factor using a comprehensive NS-2 simulation and a TinyOS 49 knots sensor network test bed experiment (Kansei). Zhi Ang Eu et al. have established a likely polling procedure which represents the uncertain energy harvesting method. To achieve good results. They implemented a MAC polling protocol with theoretical high performance. The research architecture was characterised by extensive simulations that included experimental results from the characterisation of different energy harvesters. In probably polls, the accuracy, fairness and interval times of the results remained high.

1.1 OBJECTIVE

Enhance data collection for an energy efficient, confidence-based wireless sensor network. Improvement of a trust-based clustering process that allows nodes to link and send data securely to a disc as long as they are accessible. To provide a stable, malicious, confidential WSN through the Cluster Head Trust

Propagation (CHTP) system to extend network data collection cycles and to reduce the time needed to isolate the network's malicious trust performance. The data processing times, data breakdown cycles and battery percentage need to be understood to estimate the performance assessments overhead network access, power usage, and the provision of secure private network data.

CHAPTER 2

LITERATURE SURVEY

Kamil Samara has suggested energy efficiency, load control and a wireless network routing protocol. The led diffusion algorithm saves power by hop-transference of data packets and flood prevention routes. The goal is not to find the best or the most healthy routes in the directed diffusion algorithm (healthier paths are paths that utilise less total energy than others and avoid critical nodes). The quality of energy use can be increased by the use of healthier roads. He suggested an ideal WSN routing protocol based on the total energy available on the route, running time and avoiding critical nodes to ensure that the safe routes are respected. This decision is taken with information about possible routes, and with non-incremental computer planning, we introduce paths that connect our parameters. Small networks did not show a substantial difference between the selected protocol and the specified algorithm for the simulation performance. The performance of the project protocol has increased as the network size increases.

Cumar Pradeep ATREY² implemented reliable, safe data collection in Puneth and Muralidhar Kulakarni¹'s wireless sensor networks. By randomization and dispersal routing, the feature compensates for H-SPREAD deficiencies. This method enhanced security with unequal dispersion compared to H-SPREAD. The network lifecycle and security are all taken into consideration for an unpredictable and deterministic combination. As a simple implementation process, i.e. nodes (circular) and BS, the approach was very specific (center of the network area). The research looks at the SSR architecture, which allows for secure, energy efficient wireless networks for group communications. This method increases energy efficiency, but does not manage the assault by CN. They have high security and cn attack is not feasible. They have high protection. This process is taking place.

As an alternative to the Wireless sensor networks with handheld dishes, Jesse Whitehead suggested cluster-based confidence proliferation and energising data collection. When it is not possible to find vital and engaged core stations such as tornado or volcanic eruption, mobile sinks should be given to capture data. In order to link nodes securely on the basis of confidence and network clusters, Jesse Whitehead suggested a smooth clustered structure. Jesse Whitehead, the emulation display, shows that the energy conservation and networking life of this project exceeds anyone.

Wireless network sensor management had been implemented by Ahmed Khana, Hassaan Khaliq Qureshia and Adnan Iqbalb Energy. Wired batteries are also used to power the nodes. Any battery powered network service energy saving devices are implemented. The limitation linked to the low power of the battery forced the research trend to find new sources through environmental collection. This study determines a high degree of classification in WSNs for energy efficiency. They list a number of schemes focused on battery power and energy collection schemes. The most recent change to the wireless power transmission in the sensor node is also illuminated as an alternative to conventional batteries. Alternatively, they proposed the conventional energy savings that the sensor network would make when designing energy efficient systems, taking account of recent energy allotments.

In order to collect positive and enthusiastic data on unused wireless networks, Farah Kandah, Jesse Whitehead and Peyton Ball launched it. It is important that important degradation of the system caused by incorrect or inaccurate transfer of data be ignored. Building trust - assurance between two devices guarantees the confidence and accuracy of data, providing a safe mechanism to identify all devices confidently and authorising no particulars in uncertified user details. The output showed that the impact of malicious nodes on the network must be isolated or reduced as the number of loops decreases and therefore decreases energy consumption in the network and increases its lifespan. The benefit of clustering is also the distribution of energy demand across nodes, which prevents node drop and network difficulties at an early stage.

Guosheng Huang has generated a number of energy-efficient data for unmanned aircraft. The maximised trajectory algorithm ant-colony (UAV), which forms the fewest possible data anchors in the field of operation, is given. Secondly, trust and process assessment schemes will be used to identify the trust rating of sensor nodes and only credible data to certify the quality of data collection will be collected. Finally we will find an effective data collection process that would contribute to achieving a much better network power consumption in our TEEDC-UAV scheme, which has been tested on a wide range of experimental output. The network life has increased by 48.9 percent relative to previous approaches. Meanwhile, the trust feature in this article will improve the established precision of a degree of node trust that affects 91 percent of the life of the network.

For the wireless sensor networks, Khalid Haseeb created a heuristic protocol. The proposed protocol allows for heuristic surveys on artificial intelligence to resolve the need for a system for dependence and smart learning. Secondly, transmissions with the least complexity compared with opponent classes are protected for protection. Traffic exploration can help to reduce the loss and network disconnectivity of the pathways management approach. Simulation results indicate that the SEHR protocol increases the efficiency of the network performance by average of 18%, a 42% packet reduction rate, at 26%, a 36% energy consumption of faulty routes, and a 43% numerical rate compared to current work.

Naveed Islam implemented the Lightweight Safe and Efficient Sensor Network Routing Protocol. This work enhances the energy efficiency, utilises the Service Quality (QoS) factor and makes time sensitive applications at network edges more accessible. This protocol is centralised on two primitive layers of encryption, ensuring data in real-time. Cluster heads and fog nodes have a lightweight data confidentiality system first, and an asymmetric high performance framework is introduced to define the layers of cloud and fog. In terms of routing, reliability and network control, the survey of simulation-based research has found important results in relation to current technologies.

Liangrui Tang, Zhilin Lu and Bing Fan suggested that the wireless sensor network routing algorithm be energy efficient and reliable. DS-EERA creates three

guides as residual electricity, traffic, and so forth. They gain entropy weight to monitor the weight of three guides objectively. The DS proof theory fusion rule registers to fuse each index value with the BPA function to pick a next hop after the intent of the basic probability assigning (BPA). Each network node transfers data via this routing approach. DS-EERA is a very promising theoretical paper and simulation result, enabling it to extend its network life effectively. In the meantime, the loss rate of packets can also be reduced and data transfer reliability increased.

Muhammad Ilyas suggested an energy-efficient protocol for Internet routing for trust-based sensor networks. They also implemented a three-tier clustering system with an integrated authentication function to recognise and blacklist malicious sensor nodes. Clustering protocol with the sinknote used for the cluster head and grid head on the same priority. For testing link performance and enhancing routing reliability, hardware-based link level estimators are used. In the end of the day, the effectiveness of the introduced technique was assessed by unnecessary experiments. It exceeds many related protocols such as the futile logic of the hybrid ants-based clusters and colony-based optimization.

A survey on data collection and targeted methods of energy-efficient routing in WSN has been introduced by U.Nilabar Nisha, S.Velmurugan, L.Raja, G.Shanthi. However, energy usage did not decrease and network lifetime was not improved in working methods during the processing, data collection and goal surveillance. Our main goal is to reduce energy consumption and the reliability of data collection in WSN data collection and monitoring. In this study, a survey is carried out using methods to achieve greater energy efficiency and maximum efficiency in data collection with a minimum target monitoring time in WSN.

Venkateswara Rao M has implemented a Zone based Wireless Sensor Network Safe Energy Efficient Attack Resilient Process. This work provides a secure, energy-efficient, and aggressive routing solution for zone-based wireless sensor networks including proactive monitoring and malicious attack prevention. This study divides the network into areas and gives the profit rate of the spreading packet across the region, a probabilistic and fused score that differs from previous studies in the observation of any malignant node. The routing can be

changed to accommodate continuing treatments for energy and protection. A strong evaluation that can influence the network operations cannot determine the interaction of the systems over the life cycle of the network. In NS2, the solution applied is checked and work alternatives compared to demonstrate the effectiveness of the method.

2.1 COMPARISON OF LITERATURE SURVEY

AUTHOR	PROBLEM ADDRESSED	METHODOLOGY PROPOSED	REMARKS
Kamil Samara (2020)	Routing Algorithm	Direct diffusion algorithm	Simulation result did not point out a significant difference in smaller networks
Deepa Puneeth, Nishanth Joshi, Pradeedp Kumar Atrey, Muralidhar Kulakarni (2020)	Security	H-Spread	In this method we can achieve low security
Jesse Whitehead (2020)	Time Management	Cluster based mechanism	Inference high performance
Junaid Ahmed Khana, Hassaan Khaliq Qureshine, Adan Iqbalb (2019)	Energy Management	Battery driven energy consumption	High performance
Farah Kandah, Jesse Whitehead, Peyton Ball (2019)	Energy consumption	Reducing number of nodes	High performance

CHAPTER 3

DESIGN GOALS FOR WIRELESS MICRO SENSOR

Network protocols: In order to develop better wireless sensor network protocols. The sensor network's core parameters must be recognized. There are several areas in which the Protocols support the software. The following metrics were employed.

Easy deployment: Hundreds of thousands of nodes may need to be installed in wireless sensor networks and in remote locations. If these nodes are small and inexpensive, we can fly hundreds or thousands of sensor nodes over a treatment area in ways that would not have been possible otherwise.

Lifetime of the system: Wireless sensor networks must operate for as long as possible in order for devices to last. Application parameters such as the time before the sensor network produces appropriate standard results, as well as general parameters such as the time before nodes die, can be determined.

Latency: Sensor network data should be collected promptly Long detention may not be acceptable because of processing or contact.

Quality: This parameter computes the exactness of the sensor network response to what actually occurs in the region. This is not a standard-setting approach, despite the fact that it is a single application with a range of possible applications based on results.

3.1 CHALLENGE: MEETING THE DESIGN GOALS

To abstract wireless micro sensor network protocol is should be:-

- Self-configuring for relive of establishment of the sensor node.
- Energy efficient and robust to expand system lifespan.
- Latency aware to get the details as soon as possible.
- Cognizant of the application particular nature of sensor network standard.

Sensors may be inadvertently or manually installed in remote areas on the wireless sensor network sensor system. Data for a specific sensor parameter such as temperature, strain, moisture, etc. may be collected from a sensor. Data analysis and a limited number of useful data were obtained after collecting the database station. Since the battery capacity is decreased because sensors are small electric devices. The sensor node battery cannot be replaced, since it is located at a great distance away from the base station. The node of the sensor is then delayed, used and moved. As a consequence, our main objective is to reduce the use of nodes while growing the existence of nodes.

3.2 SYSTEM ARCHITECTURE OF A SENSOR NODE

A sensor node is composed of the following main components :

- Processor
- Memory
- Radio unit (Transceiver)
- Sensor unit (Sensor and ADC)
- Power unit




Fig 3.1 Block diagram of a sensor node

This figure shows the essential elements and interactions of a sensor node. Sensor nodes are observed in their sensor devices to adjust environmental conditions. Until further calculation, the analogue signal from the sensors is converted into digital via analogue to digital converter (ADC). The selection of hardware components for sensor nodes depends on the application determined for the specifications determines the size and the cost of a sensor node and its energy consumption. Few basic nodes with volume of less than 1cc and weight of less than 100g are applied.

3.3 RADIO ENERGY DISSIPATION MODEL

The main activities of a sensor node which causes energy depletion are sensing, processing and data communication. Data communication tracks the consumption of the bulk of energy stored in the battery, but no energy is discarded in sensing and processing. The energy stored in your batteries is powered by the sensor nodes. Battery sensor nodes may be renewable or not. Few sensor nodes use mechanisms of energy collection to produce thermal, solar and vibration energy. Energy collection adds little to the sensor node model since it is complex.

Power generation circuits are used.

Sensor nodes use multiple methods to conserve energy. Some examples of the power consume techniques are:

- Dynamic power management (DPM)
- Dynamic voltage scaling(DVS)
- Dynamic frequency scaling (DFS)

A sensor node with DPM aims to reduce its energy consumption as much as possible by modifying its components. Components may be irregular or a pre-defined time table may be used. The downside of DPM consists of the substantial amount of power consumed by turning on and off the sensor node modules. DVS is a process whereby the input voltage level varies from its components from the sensor node. At times the components of the node do nothing in this production decrease in energy consumption. Differs the function frequency of the processor for the DFS power conservation. Because of the straightening relationship between processor energy consumption and frequency, the frequency increases the processor electricity consumption and vice versa. Slow processing of data in the processor uses lower frequencies performance.

The energy dissipation that shows where and how much power is used for the nodes of the transmitter and receiver and receives them from a node or base station other than that, is the result of changed designs in the first order using radio architecture for the RH.




Fig 3.2 Block diagram of Radio model

Not only radio features but also energy dissipation in communications and modes affect the efficiency of different protocols. The accepted model of energy is as follows in this analysis: The radio for the transmitter or receiver circuit and the transmitter amplifier is 50 NJ/bit (Electric) and 120pJ/bit/m² (Eamp). The energy dispersed from a node for the k-bit signal (k,d) radio transmission over a distance of d is the product of the circuitries running both the ETx-Elec (k) and ETx-amp (k,d).

$$ETx(k,d) = ES-Amp(k,d) = EST + ES-Amp(k,d) \quad (3.1)$$

Where Elec is equivalent to the dissipation of the receiver circuit per bit and Eamp the dissipation of the transmitter amplifier per square metre per bit. Though ETx(k, d) is reduced as a consequence of a decrease in distance by using multi-hop routing. Likewise, an ERx(k) receiving node of k bits is caused to disapply energy by running the ERx-elec(k) receiving circuit and shows:

$$=ERx-elec(k) =Elect.k \quad ERx(k) \quad (3.2)$$

CHAPTER 4

ROUTING PROTOCOLS

The routing in WSN is based on infrastructure, reliability and energy limitations from routing mechanisms in normal computer networks. Taking into account the energy limitation in sensor nodes, more protocols for routing and power management are created. In several respects, WSN routing protocols were classified: place-based, multi-hop, hierarchical, and more. However, these protocols can be described further as QOS, multi-path, question, etc. Each protocol has its own advantages and problems in terms of efficiency.

4.1 MULTI-HOP ROUTING PROTOCOLS

Almost every node acts in the same way in this grouping of protocols. The base station normally transfers queries and keeps data in the target source node. The coding and data-centered algorithms are primarily used in this group. Flooding algorithms operate on the assumption that their data is moved closest to everything, which results in many redundant data. The data-centric algorithms, for example the direct debate, defend the principle of avoiding the transfer of data to the previous nodes. Data is recorded by a name mechanism based on an attribute. The benefit of this proposal is to keep the redundant information away but to not provide it with certainty.

4.2 QUALITY OF SERVICE IN WSNS

While in recent years the WSNs have developed into an advanced area of science, QoS has been a highly unreleased area. In a network, QoS is closely linked to data rate, energy efficiency of the network and network life. Whilst the increasing introduction of WSNs has now seen the quality of service as crucial.

Consumer consumerism. A new approach to nodes reporting is implemented using a combined theory block model principle. To date, at the network routing level, only a few protocols had been implemented. Many other QoS works focused on the optimum number of sensor knots from which a dish can ask for information. The definition is based on gur theory, considering holes and additions, and the removal of sensor nodes. This principle was studied by M. Aykut Yigitel and colleagues. Focus on support for the QoS on the MAC layer that serves as the basis for a touch stack, and can alter key QoS parameters, including the time of the sensor.

You quest QoS problems and prospects for wireless sensory networks; you research QoS procedures and the advantages and disadvantages of modern QoS-aware MAC protocols. This report states that data packets are evaluated using the asses based on their form (or class), and that packets of many classes are processed using the ass according to their demands by modifying the network parameters in the MAC layer rather than guaranteeing deterrent QoSs.

There are two components in a cluster-based hierarchical network: I intra-cluster data reporting (IDRC) and II inter-cluster access; access (IDRC). The successful management system for data detailing was developed by Hyun Jung Choea et al. The IntraDRC Scheme monitors the traffic generated throughout the cluster by selecting a number of data reporting nodes based on the appropriate device throughput. On the other hand, the InterDRC architecture offers separate reports on the features of traffic from a cluster to a drain.

InterDRC evaluated two parameters: one was the end-to-end count of the sink and the other was a traffic quantities generated in a cluster, carried by its neighbouring clusters to resolve IntraDRC energy hire in the initial reporting schedule for node sets given by block designs.

If a line size of a surveillance node exceeds a predefined threshold, the schedule will be modified. The initial model studied homogeneous networks, each node being connected with a multi-shop operation, and each node having the same set of skills. The role of the two network models was examined. The second model

examined heterogeneous networks, in which cluster heads in a single hop method were using their intensity and propagation capacity for neighbouring cluster heads.

The results of the simulation show that this system is effective in ensuring robust, non-network-based reporting of data. The system can also save time by the use of load-stable data reporting paths. A well trained, energy-based real-time travel system was proposed by Abinash Mahapatra et al. to help stabilise use of node energy to improve network durability, to consider grid congest to minimise network routing interruptions and to increase the performance of the packs by ensuring minimum redundancy.

In addition, this study suggests a distinction in the service model with an adaptive priority medium access layer for real time packaging (MAC). The quality of the simulation supports our demands. The operational division concept enables the approach of a sink node in the right time and removes the end-to-end delay by spraying by implementing an integrated energy and quota overhaul of energy efficiency and the quoting process multichannel routing protocol (shortly abbreviated as EQSR).

During the path creation process, EQSR uses the remaining capability, node buffer accessible and noise ratio(SNR) In line with the isolation principle, the EQSR protocol uses a paradigm for queuing both in real-time and in non-real time. You use simulations and comparisons to test the efficiency of the routing.

WSNs are frequently distributed networks with a range of cheap, scattered computers that are independent of each other. This process does not affect encoding, memory, communications and control. Sensor nodes accumulate interest measures around a specific space and display them through sink nodes to external systems or networks. The technique for saving power is used to optimise the independence of each node, so that nodes are allowed to sleep much of the time.

The longer these conditions exist, the lower the power communications, the more usual the transfer to sink nodes from multihop data becomes. WSN employs an event driven data collection architecture that is based on the network

sensor node organised activity. The conventional, event-driven sensing architecture leads to greater sensitivity, better coverage and a lack of located components.

It is important to reliably transport the preferred projects to the sink if these potential benefits are to be grasped. A range of applications may be used for WSN, such as habitat mapping, indoor inspections and target location, as well as perimeter monitoring. WSNs have few issues to deal with, such as energy efficiency, congestion control, data delivery, security and the management of WSN. These problems also involve one or more layers from implementation to physical layer; independently and jointly, each subsequent layer may be examined.

The congestion limit for the samples can only be aligned to the transport layer. The physical layer, data connection layer, network layer, and higher phases can therefore involve an energy saving. The reliability principle is a pump-slow, retrievable feature in transport layers. The Event-to-Sink protocol (PSFQ) Confident Protocol on Transport On the other hand, ESRT is a solution for efficient energy-saving event surveying and a solution that guarantees data flows is used in the single aspect of supply assurance.

Fuzzy wireless and ad hoc network logic-based access and control has previously been investigated. The Transport Layer pattern for a dependable data transport infrastructure is a data transmission based on sensor networks (RMST). PSFQ, the protocol on NACK, has skipped first timer driven detection and restore mechanisms. It produces no congestion management. The Transport-Controlled MAC (TC-MAC) mechanism to connect the Transportation Protocol with the MAC Protocol should be advised to increase speed of transmission and energy consumption in multihops. Kim Jaesub & colleagues.

As per TC-MAC employs a regular listening and sleep scheme, its low end-to-end latency is achieved by saving data transmission schedules over multi-hop nodes during listening periods and transferring information through sleep, thereby enhancing performance by continuously maintaining a follow-on data transmission schedule on recent data transmissions. In addition, TC-MAC provides a lightweight, fairness management system focused on the benefits of MAC layer use.

CHAPTER 5

EXISTING TECHNIQUE

5.1 ENERGY EFFICIENT ROUTING PROTOCOL

The Energy Efficient Routing Protocol is designed to build clusters for distributed irregular knots with a group of associated known as headsets controlled by each cluster. First of all, a cluster is created and a hierarchical model is followed. The cluster head (CH) is a list of numerous effective nodes in each cluster with a selection algorithm. After a certain number of transmissions a collection of new clusters generate the sorting algorithm. The clusters are left in place for a brief moment. A round includes the selection of cluster heads and data transfer processes. For selecting the cluster head, the energy parameter and the space of the base station are all used. The cluster heads migrate data to bases in the random base station during the data transmission process (BS). Clustering is one of the key routing systems in EERP. Add to the clustering a partitioning stage by using the algorithm for cluster head selection.

5.2 SELECTION OF CLUSTER HEAD

The battery power required for diffusion and the distance from the BS during the cluster selection determines the selection of the cluster head for one period from other nodes. This information shows the energy in each node and the most energy-efficient node chosen for the cluster head (CH). When the cluster heads form, they sleep because of the lack of interest in routing and the need for conservation of resources. This technique ends with sleep and wake-up algorithm, which allows every node to sleep and wake up as needed. If requested, select a new CH after one round in each cluster. Power of the battery is usually absorbed in sleep, but retains electricity. A new cluster will be generated after the data is passed and the process of selection begins.

5.3 DATA TRANSMISSION PHASE

Member nodes send information to their CHs and the combined CH information will be sent to the base station (BS). Initially, the distribution of data to neighbours. Members of the nodes. Second, submit the data to the head of the cluster from the neighbour. Finally, the combined data is transferred to BS by CH. Fourthly, CH investigates and distributes the remaining power to neighbours. When the energy needed exceeds the residual power, a process of selection is required and the CH is removed from the headset. 5. The outgoing CH shall notify the new CH, and the new CH shall resume the protocol and update all other headset members as necessary; the new CH shall transmit all data.

CHAPTER 6

PROPOSED TECHNIQUE

6.1 LEACH

Adaptive low-capacity hierarchy clustering. Heads in this algorithm cluster are selected randomly from network nodes. A random number between 0 and 1 is issued in each network node. The node will appoint itself to be the cluster leader if its value is greater than the expected value using Formula 2.1. A cluster head node once picked. Using the following classification model in the LEACH protocol: Few people choose between the nodes a cluster head. The cluster head collects data and sends it to the base station from various nodes around the cluster head. The cluster head is replaced at every round in order to adapt the energy usage of both knots and increase their lifespan. In the analysis, the LEACH clusterhead array has been revised to reduce energy consumption, based on unfinished node resources and a distance from a base point. The following are our projections for a microsensor network:

- The base station (BS) is situated far from the sensors or may be in the center.
- All nodes are homogeneous and have restricted energy.
- All nodes are good to reach BS
- Symmetric propagation channel
- Cluster-heads functioning data compression.

The heads of clusters collect nk -bits from cluster nodes and compress data to cnk -bit data and send them via cnk -bit to base stations. LEACH hires round groups with two phases in each round: the first is formed and the second phase is

stationary. In the initialization phases, clusters are clustered while the data is forwarded to the base station at a constant stage. Each node decides whether or not it will be a cluster head for the current round during the establishment round. This work reinforces LEACH cluster selection and assessment.

The Low Energy Adaptive Hierarchy (Leach) of Heinzelman is a self-organizing and adaptive clustering protocol (LEACH). LEACH is divided into rounds with a cluster evaluation set up starting every round, followed by a static stage where data is transferred to the sink node. Although LEACH uses a misuse of cluster heads to balance the burden between sensor nodes, there are still a number of defects, to which reference is made below.

For the sensor node in LEACH, the cluster head is selected for a distributed probabilistic result. Non-cluster nodes decide which cluster to link on the basis of signal frequency. This ensures low overhead messages but does not ensure the cluster heads are equally distributed throughout the network or the network is divided into clusters of the same dimensions. The load is not balanced as long as there is a short network life.

LEACH assumes that each node and each node has the same amount of energy during each selection round and that the contributions to the head of the cluster should be the same energy consumed by each node. This statement is not practical in some implementation contexts. LEACH can then be extended to include node heterogeneity.

To send data directly to the heads of the clusters, Leach requires source nodes. However, if the head of the cluster is far from the source nodes, the communication will waste energy. LEACH requires cluster heads also for a one-hop connection to transmit its combined information to the sink. However, a one-stop drive can be very expensive if the sink is far from the cluster heads. LEACH also believes that all sensors are powerful enough to approach the drain which with strong sensor nodes could not be effective. The ECHC (Algorithm for the Hierarchical Energy Clustering and Node Concentration) is used in this research to resolve the deficiencies mentioned above. The ECHC selection of the cluster head examines the concentration of the nodes as well as their residual energies, and a

cluster head is based on the residual energy and the cluster head designation for the non-cluster node.

6.2 SET-UP PHASE

Either node ends up with CH or not, unrelated to other nodes. This assumption is considered when the node was last used as a CH (the node that has not been a CH for long time is more likely to select itself than nodes that have been a CH recently). The CHs remember that during the following marketing process they are CHs with an advertising package. Non-CH nodes capture the most efficient signal intensity from the advertisement packet. In the next item, participant nodes inform CH that their IDs are based on CSMA programmes and are a member of the 'Join Packet' cluster. The CH shall record the number of nodes and their IDs after the initialization of the cluster. Based on all information submitted through the cluster, CH will create a TDMA schedule and collect a CSMA code and send a table of TDMA to cluster members. This is the beginning of the stable stage.

6.3 STEADY-STATE PHASE

The data transmission starts; the CH transfers data to the nodes during their TDMA slots located there. This drive is the least energy consumed (chosen based on the delivered strength of the CH advertisement). The radio can be switched off in all non-CH nodes until the TDMA slot nodes are found. Before the data is generated, CH aggregates the data and sends the data to BS. LEACH will deal with local data combinations in each cluster in order to reduce the amount of data sent to the base station.

6.4 RESIDUAL ENERGY SCAN

The spatial distribution of residual energy within a network is shown by weather map or air trace pictures. The work shows how residual energy scanning (eScan) is to be collected in a sensor network. An energy-efficient network collection algorithms are used instead of collecting local scans centrally. The build of an eScan of a sensor network consists of 3 major steps.

6.5 DETERMINING LOCAL ESCANS

With their unfinished energy levels and geographic location, all nodes in the network restrict their own scans. Only when there is a major energy depletion as the node captured its previous scan, the local eScans are registered. Distributing eScans: In order to create a network combined eScan, the individual nodes are broadcast eScans. An _rst tree should be set to combine with the sink node as root. The tree construction begins with interesting details from the drain. Flooding is used for the transfer to any node in the network of INTEREST data.

6.6 AGGREGATING ESCANS:

Knots receiving eScan from the same geographical area sources will combine them if the scanning has the same energy level. However, eScan imposes a strong overload on the network, as there is still a large use of energy in the network. The track generated is proportional to the grid size for n nodes in the network, $O(n)$. The bandwidth and the energy of the network are observed to observe its efficiency and lifetime.

6.7 ALGORITHM

We have begun with the subject of building confidence, mixing trust and building trust. In response to our appeal to the WSN, the computer design explains its performance. The hierarchical protocol on faith management maintains two confidences: SN confidence and CH confidence. Each SN in a single cluster is evaluated by other SNs and each CH in its cluster evaluates a specific CH and SN. The analyses of peer to peer trust are modified regularly based on results, whether direct or indirect. If two nodes are radio spectral similar, they are observation based on snooping or overhearing. The results of trust evaluations are transferred to the other SNs by each SN in the same group. Each CH carries out a confidence analysis on all of its SNs. Also, each CH shall transmit the trust assessment results to other WSN CHs to the CH Commander who, if a CH is present, may reside at the base station, or to a CH chosen when the base station has no base station available. The CH commander evaluates the trust level of all CHs in the system.

Algorithm

Proposed routing protocol. Input: number of alive nodes Output: a set of k clusters while $t \leq t_{\max}$

Select cluster heads according to the search strategy

if the distance from a sensor node to the nearest cluster head is shorter than to the base station

Assign the sensor node to the nearest cluster head else

The sensor node will transmit directly to the base station end if

else

Calculate the objective function of the current cluster network configuration If $f(C^t) < f(C^{\text{opt}})$

Update the cluster head If $f(C^{\text{opt}}) < f(C^t)$

end if end while

CHAPTER 7

IMPLEMENTATION

We examine a WSN cluster of various clusters with cluster heads (CH) and a number of SNs in each geographical region. The CH nodes have more power and energy than those in SN nodes. The CH can be selected with a selection protocol like HEED during operation, for a predictable energy consumption versus the CH feature.

The calculation of the CH sensor has been transferred by an SN via the inside of the cluster to its CH, and CH sends the measuring data via another CH to the base station or the target node. By leveraging a two-stage WSN hierarchy, a daily peer-to-peer trust analysis between two SNs and two CHs co-ordinates this security management protocol. A device model parameter is the confidence update interval.

At SN, the results of each SN are expected to be reported to the CH by another SN in the same cluster, which carries out CH-to-SN trust analyses for each SN in its cluster. Similarly, CH report to the base station performing station-to-CH confidence analysis on peer-to-peer analyses against other CHs inside the system to all system CHs. The protocols for peer-to-peer, C H-by-SN and station-by-CH analysis will be discussed in Part IV.

Unlike previous study, we construct our trust index by comparing social and social trust to take account of the trust effects of both. Social confidence includes confidentiality, honesty, anonymity, centralism and networking under wireless sensors conditions. QoS confidence will boost ability, teamwork, confidence, completion of missions and so on. We design our confidence protocol to be standard, with social confidence and QoS confidence measures in the confidence metric overall.

We test familiarity (to evaluate close relations based on experience of communication) and authenticity (to calculate regularity/anomaly) in order to measure mutual self-confidence based upon social networks. For calculating the QoS confidence derived from communication networks we choose energy (for numerical competence) and selfishness (for the calculation of cooperation). The share of mutual trust represents how expertly two knots are experienced. This is consistent with the maturity model that SN A introduces with SN B, with the hope and confidence of SN A reaching SN B.

The element of honesty shows strongly if a node is wrong. The hypothesis is that a node of understanding is a disappointment. As the SNs differ in the pressure of energy, energy is vital to the WSNs. In order to assess if an SN completes its deliberate task, we use energy as a QoS Confidence test. The confidence factor indicates whether the SN will co-operate with the deliberate protocol. Our Trust Management Protocol allows you to monitor any WSN that contains heterogeneous SNs with vastly different energy levels and varying degrees.

In response to working and environmental conditions we are asking that a cluster of WSN adjust dynamically its behaviour. The protocol for secrecy It is autonomous if an SN has less control or more narrow-knots. Moreover, it will most likely become a solution once an SN has been compromised as soon as possible. A CH is more fuel consuming than an SN. Further energy can be used to strike in an SN and CH arrangement. A selfish node consumes less energy than a selfless node on the other hand, since its selfishness is expressed in disrupting sensory processes and spontaneously revealing knowledge.

CHAPTER 8

RESULTS AND DISCUSSION




Fig 8.1 Performance for selection of CH

Performance for selection of cluster head is very high compare to the previous works on X-AXIS, we take number of rounds and on Y-AXIS, we take selected CH count. The performance is very high at X-AXIS ranges 10 and on Y-AXIS ranges 13.




Fig 8.2 Remaining Energy

We improved energy remaining in our work compare to the previous work on X-AXIS, we take number of nodes and on Y-AXIS, we take energy remaining. From the graph we can find that energy remain constant from nodes 11-80.




Fig 8.3 Performance of nodes alive in WSN

In our work performance of nodes alive in WSN is very high compare to the previous works. On X-AXIS, we take number of rounds and on Y-AXIS, we take alive nodes. From the graph we can see that highest alive nodes is 93 and the number of rounds is 7.




Fig 8.4 Routing protocol with Efficient Energy

In the graph Red plus indicates Leadership nodes, Green square indicates base station, Circle indicates normal nodes, Magenta indicates elected cluster heads. This graph shows about the routing protocol with efficient energy.




Fig 8.5 Energy consumption

From the above graph, it indicates energy consumption is very less compared from the other works. On X-AXIS, we take number of nodes and on Y-AXIS, we take energy consumed. From the node 1 to 93 the energy consumed is 0.9 Joules.




Fig 8.6 Error Detection at the Receiver

Error detection at the receiver is very high compare to the previous works on X-AXIS, we take number of rounds and on Y-AXIS, we take number of nodes.




Fig 8.7 Clustering of Nodes

From the graph, it indicates that from one node to the another node are connected and form the cluster.




Fig 8.8 Clustering of WSN Network

Clustering of WSN is made based on the energy remaining of nodes.

Table 8.1: Summary of graphs in Tabulation

Content	X-AXIS	Y-AXIS
Performance of selection of Cluster Head	Number of Rounds : 10	Selected CH count : 13
Remaining Energy	Number of Nodes : 11-91	Energy remaining : 0.5
Performance of Nodes alive in WSN	Number of Rounds : 7	Alive nodes : 93
Energy consumption	Number of Nodes : 1-93	Energy consumed : 0.99
Error detection at the Receiver	Number of Rounds : 0-84	Number of Nodes : 1

CHAPTER 9

CONCLUSION AND FUTURE WORK

In recent years WSNs have found a variety of applications. The increasing control of WSN has accelerated WSN routing protocols investigation and implementation. The routing protocols in the WSNs in this study are divided into data-centered, hierarchical or network-driven. The metadata structure is used for the transport of sensed messages to the BS for data-centered protocols. The data name allows for the development of a query with only certain information attributes, such as routing methods based on data. In addition, sensor nodes can be assembled to disseminate data efficiently into the drain. The clustering strategy is possible through hierarchical routing protocols which assemble the sensor node. Since this technology is highly adjustable, it is used in a variety of uses.

REFERENCES

- [1] Al-Shargabi, Bassam, and Mohammed Aleswid. "Performance of RPL in Healthcare Wireless Sensor Network." *International Journal of Emerging Trends in Engineering Research* 8.3, 2020.
- [2] An, J.; Hu, M.; Fu, L.; Jan, J. A Novel Fuzzy Approach for Combining Uncertain Conflict Evidences in the Dempster-Shafer Theory. *IEEE Access* 2019.
- [3] Dong M, Ota K, Liu A. RMER: Reliable and energy-efficient data collection for large-scale wireless sensor networks. *IEEE Internet Things* 2016.
- [4] Hamidreza Salarian, Kwan-Wu Chin, and Fazel Naghdy, An Energy - Efficient Mobile-Sink Path Selection Strategy for Wireless Sensor Networks, *IEEE Transactions on Vehicular Technology*, Volume 63, Issue 5, June 2014.
- [5] Haseeb, K., Islam, N., Almogren, A., Din, I.U., Almajed, H.N., and Guizani, N. Secret Sharing-Based Energy-Aware and Multi-Hop Routing Protocol for IoT Based WSNs. *IEEE Access* 2019.
- [6] Jiang, J., Han, G., Wang, F., Shu, L. and Guizani. M. An efficient distributed trust model for wireless sensor networks. *Parallel and Distributed Systems*, *IEEE Transactions on*, PP (99):1–1, 2014.
- [7] Junbin Liang, Ming Liu, and Xiaoyan Kui. A survey of coverage problems in wireless sensor networks. *Sensors & Transducers* (1726-5479), 163(1), 2014.
- [8] Kamil Samara, Hossein Hosseini, - Aware Diffusion: A Low Power and Reliable Delivery Routing Protocol for Wireless Sensor Networks, *International Journal of Research in Wireless Systems (IJRWS)*, December 2015 (Accepted).
- [9] Khalaf, O.I. and B.M. Sabbar, An overview on wireless sensor networks and finding optimal location of nodes. *Periodicals of Engineering and Natural Sciences*, 2019
- [10] Kharrufa H, Al-Kashoash HA and Kemp AH. RPLbased routing protocols in IoT applications: a review. *IEEE Sens J* 2019.

- [11] Lin, J., Jung, H., Chang, Y. J., Jung, J. W., & Weitnauer, M. A.(2015). On cooperative transmission range extension in multi-hop wireless ad-hoc and sensor networks: A review. *Ad Hoc Networks*, 29, 117–134.
- [12] Talzi, I. Hasler, A., Gruber, S., Tschudin, C. Permasense: investigating permafrost with a wsn in the swiss alps, in *Proceedings of the 4th workshop on Embedded networked sensors*, ACM, 2007.

A HEURISTIC SOLUTION FOR TRUST BASED ENERGY EFFICIENT DATA COLLECTION IN WIRELESS SENSOR NETWORKS

ORIGINALITY REPORT

8%	3%	6%	3%
SIMILARITY INDEX	INTERNET SOURCES	PUBLICATIONS	STUDENT PAPERS

PRIMARY SOURCES

1	Saad A. Munir, Yu Wen Bin, Ren Biao, Ma Jian. "Fuzzy Logic Based Congestion Estimation for QoS in Wireless Sensor Network", 2007 IEEE Wireless Communications and Networking Conference, 2007 Publication	1%
2	Zhi Ang Eu, Hwee-Pink Tan, Winston K.G. Seah. "Design and performance analysis of MAC schemes for Wireless Sensor Networks Powered by Ambient Energy Harvesting", Ad Hoc Networks, 2011 Publication	1%
3	Submitted to Arab Open University Student Paper	1%
4	Choe, H.J.. "QoS-aware data reporting control in cluster-based wireless sensor networks", Computer Communications, 20100701 Publication	1%
5	mtlweb.mit.edu Internet Source	<1%

6	Submitted to S.P. Jain Institute of Management and Research, Mumbai Student Paper	<1 %
7	Farah Kandah, Jesse Whitehead, Peyton Ball. "Towards trusted and energy-efficient data collection in unattended wireless sensor networks", Wireless Networks, 2020 Publication	<1 %
8	Abderrahmen Belfkih, Claude Duvallet, Bruno Sadeg. "A survey on wireless sensor network databases", Wireless Networks, 2019 Publication	<1 %
9	krishikosh.egranth.ac.in Internet Source	<1 %
10	Hsiao-Lan Hsu, Qilian Liang. "An energy-efficient protocol for wireless sensor networks", VTC-2005-Fall. 2005 IEEE 62nd Vehicular Technology Conference, 2005., 2005 Publication	<1 %
11	cloudportal.sathyabama.ac.in Internet Source	<1 %
12	dc.uwm.edu Internet Source	<1 %
13	www.sathyabama.ac.in Internet Source	<1 %

14	Jing Feng, Yung-Hsiang Lu, Byunghoo Jung, Dimitrios Peroulis, Y. Charlie Hu. "Energy-efficient data dissemination using beamforming in wireless sensor networks", ACM Transactions on Sensor Networks, 2013 Publication	<1 %
15	Submitted to National Institute of Technology, Rourkela Student Paper	<1 %
16	Koushika, A M, and S Thamarai Selvi. "Load valancing Using Software Defined Networking in cloud environment", 2014 International Conference on Recent Trends in Information Technology, 2014. Publication	<1 %
17	Sathyapriya Loganathan, Jawahar Arumugam. "Energy centroid clustering algorithm to enhance the network lifetime of wireless sensor networks", Multidimensional Systems and Signal Processing, 2019 Publication	<1 %
18	Abdullah Said Alkalbani, Teddy Mantoro. "Residual Energy Effects on Wireless Sensor Networks (REE-WSN)", 2016 International Conference on Informatics and Computing (ICIC), 2016 Publication	<1 %

19	Marwa Sharawi, Eid Emary. "Chapter 6 Clustering Optimization for WSN Based on Nature-Inspired Algorithms", Springer Science and Business Media LLC, 2016 Publication	<1 %
20	www.ijarcce.com Internet Source	<1 %
21	Submitted to RDI Distance Learning Student Paper	<1 %
22	www.atlantis-press.com Internet Source	<1 %
23	Chong Han, Qing Lin, Jian Guo, Lijuan Sun, Zhuo Tao. "A Clustering Algorithm for Heterogeneous Wireless Sensor Networks Based on Solar Energy Supply", Electronics, 2018 Publication	<1 %
24	Venkateswara Rao M, Srinivas Malladi. "Secure Energy Efficient Attack Resilient Routing Technique for Zone based Wireless Sensor Network", International Journal of Advanced Computer Science and Applications, 2020 Publication	<1 %
25	A. Manjeshwar, D.P. Agrawal. "TEEN: a routing protocol for enhanced efficiency in wireless sensor networks", Proceedings 15th	<1 %

International Parallel and Distributed
Processing Symposium. IPDPS 2001, 2001

Publication

26	Submitted to KUMARAGURU COLLEGE OF TECHNOLOGY Student Paper	<1 %
27	Submitted to Middlesex University Student Paper	<1 %
28	Submitted to Myongji University Graduate School Student Paper	<1 %
29	Submitted to National Institute of Technology Karnataka Surathkal Student Paper	<1 %
30	Submitted to Government Engineering College, Thrissur Student Paper	<1 %
31	Submitted to The Hong Kong Polytechnic University Student Paper	<1 %
32	docplayer.net Internet Source	<1 %
33	prer.hec.gov.pk Internet Source	<1 %