

Feasibility studies and possible selection of deep learning techniques for ensuring reliable data transmission in wireless sensor network

Submitted in partial fulfillment of the requirements for the award of Bachelor of
Engineering Degree in Electronics and Communication Engineering

by

Avula Manoj Kumar Reddy (37130040)

Bantu Naveen (37130045)



**DEPARTMENT OF ELECTRONICS AND COMMUNICATION
ENGINEERING
SCHOOL OF ELECTRICAL AND ELECTRONICS ENGINEERING**

SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY (DEEMED TO BE UNIVERSITY)

Accredited with Grade "A" by NAAC | 12B Status by UGC |

Approved by AICTE JEPPIAAR NAGAR, RAJIV GANDHI

SALAI, CHENNAI - 600 119

MARCH - 2021



SATHYABAMA

**INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)**

Accredited with Grade “A” by NAAC

JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI - 600 119

www.sathyabama.ac.in



DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of A.MANOJ KUAMAR REDDY (37130040) and BANTU NAVEEN (37130045) who carried out the project entitled **“FEASIBILITY STUDIES ON DEEP LEARNING TECHNIQUES FOR ENSURING RELIABLE DATA TRANSMISSION IN WSN”** under our supervision from December 2020 to March 2021.

Internal Guide

Dr. N. M. NANDHITHA, M.E., Ph.D

Dean, School of electronics and electrical engineering

Head of the Department

Dr. T. RAVI, M.E., Ph.D.

Submitted for Viva voce examination held on _____

Internal Examiner

External Examiner

DECLARATION

We, **A. MANOJ KUMAR REDDY (37130040)** and **BANTU NAVEEN (37130045)** hereby declare that the Project Report entitled **“FEASIBILITY STUDIES ON DEEP LEARNING TECHNIQUES FOR ENSURING RELIABLE DATA TRANSMISSION IN WSN”** done by us under the guidance of **Dr.N.M.NANDHITHA,ME,PHD.** is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering degree in Electronics and Communication Engineering.

1)

2)

DATE:

PLACE:

SIGNATURE OF THE CANDIDATES

ACKNOWLEDGEMENT

We are pleased to acknowledge our sincere thanks to Board of Management of **SATHYABAMA** for their kind encouragement in doing this project and for completing it successfully. We are grateful to them.

We convey our thanks to **Dr. N. M. NANDHITHA, M.E., Ph.D. Dean, School of Electrical and Electronics Engineering** and **Dr. T. RAVI, M.E., Ph.D. Head of the Department, Department of Electronics and Communication Engineering** for providing us necessary support and details at the right time during the progressive reviews.

We would like to express our sincere and deep sense of gratitude to our Project Guide **Dr. N. M. NANDHITHA, M.E., Ph.D. Dean, School of Electrical and Electronics Engineering** for her valuable guidance, suggestions and constant encouragement paved way for the successful completion of the project work.

We wish to express our thanks to all teaching and Non-teaching staff members of the **Department of Electronics and Communication Engineering** who were helpful in many ways for the completion of the project.

We express our gratitude to our parents for their constant encouragement and support for the completion of the project.

ABSTRACT

Wireless sensor networks refer to a group of closely arranged sensors which are time driven or event driven and are used for transmitting the signals/ images/data. In recent years, these sensor networks are used extensively in telemedicine, meteorological department, remote sensing etc. The major limitation of sensor networks is the energy constraint of the sensor nodes which drastically affects the lifetime of the network. Also it poses a severe threat on the security techniques developed for reliable data transmission as these algorithms deplete the sensor energy. Hence a trade off is needed in such a way that optimized security algorithm is developed that results in reliable data transmission and also does not cause a major impact on the energy depletion of sensor nodes. The proposed work aims at studying the feasibility of deep learning techniques for developing security algorithm and determining a suitable network for a suitable encryption and decryption technique and thereby coming out with an optimized number of layers that result in reduced energy consumption.

Keywords-Wireless Sensor Network, Internet of Things, Sensor Nodes, Energy Efficiency

TABLE OF CONTENTS

TITLE	PAGE NO
ABTRACT	V
LIST OF ABBREVIATIONS	VII

CHAPTER NO.	TITLE	PAGE NO
1.	INTRODUCTION	1
	1.1 WIRELESS SENSOR NETWORK	1
	1.2 PROBLEM STATEMENT	2
	1.3 IDEA OF ORIGIN	2
2.	LITERATURE REVIEW	3
	2.1 LITERATURE SURVEY	3
	2.2 PROBLEM STATEMENTS FROM SURVEY	4
	2.3 OBJECTIVE	4
3.	AIM AND SCOPE OF THE PRESENT INVESTIGATION	5
	3.1 PROPOSED METHODOLOGIES	5
	3.2 AREA OF PROJECT WORK AND APPLICATION	5
	3.2.1 SECURITY IN WSN	5
	3.2.2 DATA PRIVACY MANAGEMENT	6
	3.2.3 DEEP LEARNING	7
	3.2.4 CONVOLUTIONAL NEURAL NETWORK	10
	3.2.5 LOGICAL STRUCTURE OF AES	15
	3.2.6 ADVANCED ENCRYPTION STANDARD	16
	3.2.7 LSTM	17
	3.2.8 OVERVIEW	21
	3.3 MATLAB OVERVIEW	21
	3.3.1 MATLAB POWER OF COMPUTATIONAL MATH	22
	3.3.2 FEATURES OF MATLAB	22
	3.3.3 USES OF MATLAB	23

3.3.4 COMMANDS	26
3.3.5 COMMANDS FOR MANAGING A SESSION	27
3.3.6 INPUTS AND OUTPUT COMMANDS	28
4. MATERIALS AND METHODS	29
4.1 ALGORITHM	29
4.2 WORKFLOW	30
4.3 CODE	31
5. RESULTS AND DISCUSSION	32
5.1 RESULT	32
5.2 DISCUSSION	33
5.2.1 INPUTS	33
5.2.2 TRAIN DATASET	33
5.2.3 TEST DATASET	34
6. CONCLUSION AND FUTURE WORK	35
6.1 CONCLUSION	35
REFERENCES	36

LIST OF ABBREVIATIONS


WSN	WIRELESS SENSOR NETWORKS
AES	ADVANCED ENCRYPTION STANDARD
LSTM	LONG SHORT TERM MEMORY
CNN	CONVOLUTIONAL NEURAL NETWORK
RNN	RECURRENT NEURAL NETWORK
LINPACK	LINEAR SYSTEM PACKAGE
EISPACK	LINEAR SYSTEM PACKAGE
DES	DATA ENCRYPTION STANDARD
CBC mode	Cipher Block Chaining mode.
CFB mode	Cipher FeedBack mode.
OFB mode	Output FeedBack mode

CHAPTER-1

INTRODUCTION

1.1 Wireless sensor network

A distant sensor network includes sensors which are spatially appropriated inside a locale to screen a short time later give these recognized information to an essential region. From the outset the far off sensor network was used for military applications like combat area observation; yet nowadays far off sensor networks are used for a wide extent of usages. The WSN involves a couple of number of centers from hundreds to thousand dependent upon the application for which it is used. All the centers inside the association potentially connected with each other inside the association. Each center point includes a radio handset with an inside receiving wire or an outside receiving wire, a smaller than usual controller, an electronic circuit for interfacing with the sensors in addition, a fuel source ordinarily batteries. WSN can take any topography from a clear star association to an undeniable level multi-bounce far off cross segment association



Generally the hubs that we used in a WSN are little (are equal to the size of a grains), and these are controlled utilizing either batteries or sun based on supplies. In a remote sensor organization, there are two significant plan standards that ought to be dealt with. They are the prolongation of organization lifetime and energy-efficient information transmission. In the greater part of the applications the hubs are fueled utilizing battery. Since these battery have an extremely restricted energies supply, we need to utilize energy as low as could be expected. This is on the grounds that the lifetime of a hub for the most part relies on the lifetime of the batteries. The hubs that are available close to the sink will bite the dust sooner than different hubs in the organization. This is on the grounds that the hubs that are nearer to the sink will be

intensely stacked with information from any remaining hubs inside the organization. Thus they will require more energy to handle every one of these information and subsequently they bite the dust soon. Because of which every one of these information doesn't arrive at the objective. This situation is known as 'energy opening'.

1.2 PROBLEM STATEMENT

At the point when occasion happens the source hubs produce a lot remote squanders remote transfer speed, yet in addition devours a great deal Force occasion improve the remote organization, minimum dispersal significant thought unwavering quality. Occasion parcel to the should effectively disappointment. Way disappointment Hub disappointment prompts parcel misfortune. A few techniques utilize various ways to beat the IEEE Global Meeting on PC, Correspondence and Control (IC4-2015). issue of way disappointment however this prompts the energy dissemination and information repetition. Additionally different way use prompts correspondence overhead.

1.3 Idea Of Origin

Our team has always been interested in the field of WSN . The WSN major limitation is the energy limitation, which drastically affects the lifetime of the network that causes the security problems. So we came up with the idea to make a security algorithm that helps the sensor node to use less energy and also the reliable data transmission.

CHAPTER - 2

LITERATURE REVIEW

2.1 LITERATURE SURVEY

Authors	Title of the Paper	Details	Problem Definition	Methodology	Remarks
A. Bhavve and S. R. Jajoo,	Secure communication in Wireless Sensor Networks using hybrid encryption scheme and cooperative diversity technique	2015 IEEE 9th International Conference on Intelligent Systems and Control (ISCO), Coimbatore, India, 2015, pp. 1 - 6, doi: 10.1109/ISCO.2015.7282235.	Development of hybrid encryption scheme	A symmetric and asymmetric encryption algorithms are combined for secure key exchange and enhanced cipher text security	Extended space time block codes (ECBSTBC) have better SNR improvement when compared with sensor selection scheme. Proposed system uses ECBSTBC codes for transmission
Notom Ajaykumar Mrinal Sarvagya, Parag Parandkar	A novel security algorithm ECC-L for wireless sensor network	Vol.3, Issue3, May/June 2020, https://doi.org/10.1002/itl2.150	Assesses the performance of Wireless Sensor Network In terms of the power consumption and security, for accessing	A novel security algorithm Rabin based Elliptic Curve Cryptosystem - Linear (ECC-L) has been designed, implemented and compared with existing ECC algorithm	In Rabin ECC-L algorithm, reduction of control overheads by 21%, reduction in energy consumption by 27%, decrease in packet losses by 13%, increase in throughput by 32% and decrease in average delay by 32%

Authors	Title of the Paper	Details	Problem Definition	Methodology	Remarks
Abdullah Al Hayajneh, Md Zakirul Alam Bhuiyan, Ian McAndrew	A Novel Security Protocol for Wireless Sensor Networks with Cooperative Communication	Computers 2020, 9(1), https://doi.org/10.3390/computers9010004	A technique is proposed which operates by transmitting packets of data to neighboring relay nodes in a cooperative fashion to reach the destination	This protocol also adds a secure and reliable transmission of data from the source node, through the relay nodes, to the destination node	Cooperative communication improves the network resiliency and reliability
H. Rathore, V. Badarlapati, S. Jha and A. Gupta,	Novel approach for security in Wireless Sensor Network using bio-inspirations	2014 Sixth International Conference on Communication Systems and Networks (COMSNETS), Bangalore, India, 2014, pp. 1-8, doi: 10.1109/COMSNETS.2014.6734875.	To develop biologically inspired machine learning techniques for adding security against threats	Uses machine learning techniques to identify the fraudulent nodes, consecutively by deriving inspiration from human immune system it effectively nullifies the impact of the fraudulent ones on the network	If the same type of maliciousness occurs in the sensor network, the antibody production increases at a faster rate

Authors	Title of the Paper	Details	Problem Definition	Methodology	Remarks
Z. Qin et al.,	A Novel Identity-Based Security Scheme for Wireless Sensor Networks	2014 Tenth International Conference on Computational Intelligence and Security, Kunming, China, 2014, pp. 662-666, doi: 10.1109/CIS.2014.99.	A novel identity-based security scheme is proposed on the basis of IBE	Each cluster head can perform as a private key generator (PKG) in case that the only PKG is captured, which will lead to the entire network disabled	The analysis shows that the scheme is more secure and efficient by comparing with traditional public key and symmetric key techniques
Hayouni, Haythem	A novel energy-efficient encryption algorithm for secure data in WSNs.	The Journal of Supercomputing. 77. 10.1007/s11227-020-03465-x. , 2021	To develop less complex encryption algorithm	A novel ultra-lightweight encryption algorithm, named ULEA is proposed. Besides diffusion and confusion of data, ULEA assumes minor encryption rounds with simplified transformations and functions to complex the cipher	ULEA algorithm is an appropriate, low storage space, energy-efficient encryption process with high security for WSNs

2.2 PROBLEM STATEMENTS FROM SURVEY

Many Algorithms and works have been proposed and developed to achieve a better Energy efficient. Nevertheless, every proposed system lacks a few features. Even though the drawbacks of one system have been compensated in the other, No system as a whole can work autonomously, reducing the effort put in by the user.

2.3 OBJECTIVE

The main objective of these conventions is to Energy effective routing protocols are needed to limit the usage of the force assets and drawing out the organization lifetime way while moving information productively scatter perceptions accumulated by individual sensor nodes to all the sensor nodes in the network. Straightforward conventions, for example, flooding and tattling are usually proposed to accomplish data scattering in WSNs.

CHAPTER-3

AIM AND SCOPE OF THE PRESENT INVESTIGATION

3.1 PROPOSED METHODOLOGIES

The proposed work aims at developing feasibility studies and possible selection of deep learning techniques for ensuring reliable data transmission in wireless sensor network

3.2 AREA OF PROJECT WORK AND APPLICATION

3.2.1 Security in WSN

The points of interest of remote sensor networks open them to weaknesses exploitable by assailants. In reality, the actual weakness is a mean of assault, which permits the assailant to substitute a sensor, by adjusting its source code, or by replicating the security keys to reuse them in another assault. A sensor network is additionally helpless against changes in its current circumstance, where an assailant can adjust the estimations of a neighborhood sensor, permitting him to approach the control orders of the organization. Concerning the consistent weakness, it lives in projects and conventions. It is identified with configuration imperfections, execution defects, arrangement mistakes, and asset consumption. Thus, many examination subjects are arising lately to give security answers for address these weaknesses and give security administrations in sensor organizations. Regardless of the significant endeavors made to propose crypto-frameworks that adjusts power and requirements saw in these organizations, cryptographic conventions and libraries being given, it is critical to call attention to that the issue identified with the mysterious key trade stays intricate and the proposed systems are not ideal for an execution in a compelling climate. It will be in our improvement to propose an engineering characterized on three levels featuring the particular limitations of sensor organizations, at that point, through a heuristic investigation of it, to deliver the different weaknesses to which they are uncovered in the optics of proposing a crypto framework for the security of information traded among the distinctive conveying substances.



3.2.2Data Privacy Management

Given the picked engineering and the various requirements recognized by level, we decide on a cross breed cryptographic component permitting level 3, to carry out an even cycle. For sure, secret key cryptography is known for its properties when time limitations are required. From these time requirements, a few outcomes can result. Our decision is on the AES in counter mode which gives a parallelization permitting to encode in a sensible time autonomous squares of information. This is a method that utilizes the properties of constant encryption to encode squares of information. It depends on the utilization of an irregular that can be considered as an instatement vector, related with a counter. A fascinating element of the counter mode is that it very well may be resembled, one reason why its execution decidedly affects time-compelled networks.

3.2.3 DEEP LEARNING


Given the picked planning and the various essentials saw by level, we choose a cross assortment cryptographic section permitting level 3, to finish an in reality, even cycle. In actuality, secret key cryptography is known for its properties when time hindrances are required. From these time, a few outcomes can result. Our decision is on the AES in counter mode which gives a parallelization permitting to encode in a sensible time free squares of information. This is a procedure that utilizes the properties of consistent encryption to encode squares of information. It depends upon the use of an unusual that can be considered as an instatement vector, related with a counter. A charming part of the counter mode is that it may be taken after, one inspiration driving why its execution decidedly impacts time-compelled associations.

Data handling and dispersed correspondence hubs in natural frameworks inspired the development of fake neural organisations (ANNs). ANNs and organic cerebrums have distinct contrasts. The natural cerebrum of most living organic entities is dynamic (plastic) and basic, so neural organisations will be static and representative in general.

The term "profound" in the phrase "profound learning" refers to the organization's use of various layers. Early research demonstrated that a direct perceptron cannot be used as a general classifier, but that an entity using a nonpolynomial actuation system with one hidden layer of unbounded width may. Profound learning is a cutting-edge form that is concerned with an infinite number of small layers that allow for useful implementation and advanced execution while maintaining hypothetical all-inclusiveness under benign conditions. For proficiency, the layers in profound learning are also permitted to be heterogeneous and to deviate widely from organically educated connectionist models. teachability and understandability, whence the "organized" part.

Addressing Images on Multiple Layers of Abstraction in

Learning from the Ground Up Profound learning is a form of AI calculation that employs multiple layers to continually isolate more important level highlights from the raw data. For example, in image processing, lower layers may recognise edges, while higher layers may recognise human-relevant concepts such as digits, letters, and faces.



Although they may also integrate propositional recipes or dormant factors organised layer-wise in profound generative models, such as the hubs in profound conviction organisations and profound Boltzmann machines, most current profound learning models depend on fake neural organisations, specifically convolutional neural organisations (CNNs).

In deep learning, each level works out how to transform its data into a slightly more theoretical and composite image. The raw data in a picture recognition programme could be a lattice of pixels; the first illustrative layer could extract the pixels and encode edges; the next layer could create and encode plans out of edges. The third layer may encode the presence of a nose, while the fourth layer may detect the presence of a face in the picture. Significantly, a thorough learning cycle will independently determine which highlights should be placed in which level. (Obviously, hand-tuning is still required; adjusting the number of layers and layer sizes, for example, will result in different levels of abstraction.

The word "profound" in "profound learning" refers to the number of layers from which the data is transformed. Moreover, profound learning systems have a substantial credit task way (CAP) profundity. The contribution to yield chain is represented by the CAP. The covers represent possible causal relationships between information and yield. The depth of the CAPs in a feedforward neural organisation is the same as the organization's and is the number of covered up layers plus one (as the yield layer is also defined). The CAP profundity may be infinite for repetitive neural organisations in which a sign may engender through a layer multiple times. More layers, on the other hand, do not increase the organization's capacity approximator

capacity. In comparison to shallow models, profound models can extract preferred highlights, and as a result, additional layers aid in learning the highlights effectively.

An insatiable layer-by-layer approach can be used to create profound learning designs. Deep learning will help you decipher these reflections and choose which highlights that help you execute better.

Deep learning strategies reduce highlight design in administered learning projects by converting information into conservative halfway portrayals akin to head segments and determining layered constructions that eliminate excess in portrayal.

Solo learning errands will benefit from profound learning estimates. Since unlabeled information is more abundant than branded information, this is a major benefit. Neural history blowers and profound belief organisations are examples of profound constructions that can be prepared without assistance

Alexey Ivakhnenko and Lapa published the first general working learning calculation for guided, profound, feedforward, multi-facet perceptrons in 1967. In a 1971 paper, the gathering technique for knowledge management was used to create a deep organisation of eight layers. Other significant learning curves in working designs, especially for PC vision, Kunihiro Fukushima first introduced the Neocognitron in 1980.


Rina Dechter introduced the word "deep learning" to the AI community in 1986, and Igor Aizenberg and colleagues introduced the term "fake neural networks" to Boolean edge neurons in 2000.

3.2.4 CONVOLUTIONAL NEURAL NETWORKS – AN OVERVIEW

A spatial network structure orchestrates the states in each layer in convolutional neural organisations. Since each component's dependent neighbourhood district these spatial relations are acquired beginning with one layer and progressing to the next. Since the convolution activity and the transition to the next layer are both dependent on these connections, it is critical to connections lattice. three-dimensional framework structure with dimensions of and depth

Convolutional organisation functions similarly to organisation; however, activities in organised, few (purposefully planned). Convolution, pooling, and ReLU are the in a organisation. The enactment of the ReLU is identical to that of a traditional neural organisation. Furthermore, a final collection associated to a number of yield hubs in an application-specific path.

For example, Info $[32 \times 32 \times 3]$ would store the picture's rough pixel estimates, in this case a picture with a width of 32, a height of 32, and three shading channels R, G, and B. The yield of neurons associated with neighbourhood areas in the data will be processed by the CONV layer, with each neuron recording a dab item between their loads and a small district they are associated with in the data volume. If we were to use 12 channels, this might result in a volume of $[32 \times 32 \times 12]$. At nothing, the RELU layer will add component astute actuation work, such as the $\max(0, x)$ thresholding. The volume's size remains unchanged as a result of this $([32 \times 32 \times 12])$.¹⁴ The POOL layer will perform a down examination along the spatial dimensions (width, height), resulting in a volume of $[16 \times 16 \times 12]$. The FC (for example, fully associated) layer will record the class size $[1 \times 1 \times 10]$, where each of the ten numbers corresponds to a class score, such as among the CIFAR-10 classifications. As with regular Neural Organizations, every neuron in this layer will be correlated with each of the numbers in the previous volume, as the name implies. The boundaries are coordinated into collections of primary channels bits, in convolutional neural organisation. The channel is typically somewhat that sheet on which it is applied. In the channel often the as depth . $F_q F_q d_q$ should be the components of the channel in the q th layer. It's common for F_q 's estimate to be small and irregular. The most commonly used F_q estimates are 3 and 5, though $F_q = 1$ can be used in some interesting situations. The channel is placed in every imaginable scenario in the picture due to the convolution operation (or covered up layer). As a result, the channel entirely covers the image and acts out a speck object between the $F_q F_q d_q$ channel borders and the coordinating with matrix in the information volume (both of which have the same size $F_q F_q d_q$). The dab item is accomplished portions of important district information channel $F_q F_q d_q$, with the aim of requesting the components in the two vectors locations ordered.



This is achieved by using five distinct networks, each with its own set of boundaries. A component map is any of these five arrangements of spatially orchestrated highlights obtained from the yield of a single channel. A larger number of highlight maps is unmistakably the product channels (boundary impression), F2qddq+ sheet. channels determines since. enlarging The channels one determines highlight map in the next layer.

which initiations districts enact, are inferred by convolution operation. Distinguished, extended to of due to convolutional neural organisations. Furthermore, prior layers' channels will generally discern more rough shapes, while later layers' channels will allow more unpredictable arrangements of these crude shapes. This isn't surprising, given that the vast majority of profound neural organisations are appropriate at different levels of highlight architecture. Convolution has the property of displaying equal differences in perception. This is due to the channel's common boundaries in the convolution. each portion in the subsequent .channel convolutions gradually for example. According to one theory. shrinkage isn't appealing. When all is said and done, and in light of the fact that it will lose some data around the picture's edges (or of the component map, on account of covered up layers). Cushioning can be used to solve this problem. Cushioning involves adding "pixels" all over the component map's borders to maintain the spatial impression. will decrease after convolution is completed. Since their qualities are set to 0, the cushioned segments do not contribute to the last speck object. As it stands, cushioning allows convolution to take place with

a portion of the channel that extends outside the layer's borders, followed by the data being played out just over the layer's characterization bit. Since a large portion of the channel this type of cushioning referred to as half-cushioning. Half-cushioning is used to maintain a consistent spatial impression. When cushioning is not used, the "cushioning" that follows is often referred to as legal cushioning. Genuine cushioning, for the most part, does not perform admirably when it comes to exploratory purposes. Using half-cushioning ensures that a portion of the basic data at the layer's boundaries is handled in a separate manner. Due to proper cushioning, the obligations of the pixels on the layer's borders would be under-addressed in comparison to the focal pixels on the following inconvenient. then decreases after the convolution is completed. Convolution can be used in a variety of ways to reduce the spatial impression of an image. The convolution is performed at each location in the component map's spatial region using the method described above. In any case, performing the convolution at each spatial situation in the layer isn't necessary. Using the concept of measures, one may reduce the degree. It is also possible to incorporate inclinations to the forward operations, just as in any other neural organisation. The estimate of this item whenever some the predisposition. The predisposition is learned during back spread, just like any other remaining boundaries. The pooling and ReLU activities are interspersed with the convolution activity. The ReLU enactment isn't dissimilar to how it's used in a traditional neural organisation. The ReLU actuation work is applied to each of the values in a layer to render thresholded values. The following layer is then given. As a result, applying the ReLU has no effect on the data. The enactment work is connected with a direct shift with a system of loads to render the next layer of actuations in traditional neural organisations. Furthermore, and the ReLU layer is seldom explicitly depicted in pictorial representations of convolution neural organisation designs. Regardless, the pooling activity is one-of-a-kind. Each layer's pooling operation removes small matrix areas of size $P_q \times P_q$ and replaces them with another layer of similar depth (in contrast to channels). The limit of these qualities is returned for each square locale of size $P_q \times P_q$ in each of the actuation maps. Max-pooling is the term used to describe this process. If a step of 1 is used, it will result in the creation of a new layer of size. It is, however, more common to use an. instances, duration and expansiveness would be and respectively. Pooling components initiation in this


way. Pooling is performed at the level of each initiation diagram, unlike with convolution tasks. While element guide generate a new element map. As a result, pooling has no effect on the number of highlight maps. Overall. Since shifting the picture slightly doesn't alter the initiation map basically, pooling introduces invariance to interpretation. Interpretation invariance is a term used to describe this property. using measures larger than one. Larger sensitive fields should have been available Pooling activities are responsible for the vast majority of the rapid decreases in spatial experiences of the layers. Except when the stage is greater than 1, convolutions gently increase the sensitive area. Each hidden state in the main fully associated layer is associated with each element in the last spatial layer. This layer has the same capabilities as the previous one.

in feedforward networks. As a rule, can be used force of calculations associated, completely associated layers include the vast majority of boundaries. Associated loads. Essentially, there will be several boundaries between main full connect. Despite the fact that convolutional layers have more initiations, full connect more associations. In . In traditional neural organisations, the frequently initiation work frequently follow direct speck object.

3.2.5 Logical structure of AES

NIST standardised the Progressed Encryption Standard in November 2001. It is an iterative square crypto structure. The overall scheme consists of a series of substitutions and renderings. The amount of emphasis is determined by the main size. During each round, We note four reformist modifications in addition to the final three that are applied :

- 1) Substituting bytes in the status table (Byte Sub);
- 2) Shifting bytes in the status table (Shift Row);
- 3) Moving status table columns (Mix Column);
- 4) A round key that changes with each round was added (Add Round Key)



Logical structure of AES


3.2.6 Advanced Encryption Standard

The General Encryption Standard (AES) is a symmetric square code chosen to ensure the confidentiality of described data. AES is used to encrypt sensitive data all over the world, both in programming and hardware. It's important for PC safety, network protection, and electronic data verification.

To scramble and unscramble a square of messages, AES-128 uses a 128-bit key length, while AES-192 uses a 192-piece key length and AES-256 uses a 256-digit key length. Each code scrambles and decrypts data in 128-piece squares using separate cryptographic keys of 128, 192, and 256 bits.

Symmetric, in like manner known as secret key, figures use a comparative key for encoding and unscrambling, so the sender and the recipient must both use a comparable secret key. The public power orders information in three classes: Characterized, Secret or Top Secret. All key lengths can be used to get the Levels are divided into two categories: Characterized and Secret. 192- or 256-cycle key

lengths are needed for extremely private data. For 128-digit keys, there are 10 rounds, 12 rounds for 192-piece keys, and 14 rounds for 256-cycle keys. A round is made up of several steps that combine substitution, translation, and mixing of the input plain text to produce the final yield of cipher text.



The AES encryption computation specifies the various operations to be carried out on data stored in an array. The code's underlying advance is to group the records, after which the code changes are replicated over several encryption changes.

The replacement of data using a substitution table is the first adjustment in the AES encryption figure; the second changes data lines, and the third blends parts. Using a replacement piece of the encryption key, the continue to go adjustment is done on each section. To wrap up longer buttons, you'll need more acclimates.

3.2.7 LSTM

The sensor hub gather the information and that information should be Encoded. The information encoded utilizing LSTM or RNN , however LSTM is better for encoding . In LSTM hub utilizes input esteem ,past yield and inward state utilizes for estimation .The outcome computation give yield esteem as well as update the inner state . LSTM has boundaries know as entryway boundaries that control the progression of data with in hub. The LSTM information ought to be prepared prior to going to check the yield .The information is taken from the information sheet in exe.file in that information sheet it has 16 qualities and each estimation of 8 bit information. In the 16 qualities all odd ones are train information and levels are for trying .Subsequent to finishing the preparation the LSTM the exactness should be check if information is solid. The exactness need to check step by step if need the precise worth. Subsequent to checking the precision the information should be test . All levels are should be tried .After need to notice the real information or not. By taking the outcome the precision diagram is gotten

The German analysts Sepp Hochreiter and Juergen Schmidhuber suggested an irregular network of supposed Long Short-Term Memory units, or LSTMs in the 1990s.

Lstm aid in prevention of errors propagated across. stable blunder, dreary learning a large number of cause effect . This is one of the most important obstacles to machine learning and artificial intelligence, since calculations are often hampered by situations under which prize signals are small and delayed, just like life itself. (Exacting minds have dealt with a similar problem with musings on karma or magnificent honour, speculating on imperceptible and remote outcomes of our efforts.)

LOutside of the average movement of the repetitive organisation LSTMs contain detail. Via entryways that open and shut, the cell makes choices on what to store and what to accept scrutinises, creations, and cancellations. Rather than sophisticated computerised storage, these entryways are plain, involving part informative replication by sigmoids, all of over advanced.

Entryways circle back to the signs they get, and like the neural organizations' hubs, they subject to fortitude channel game plans loads. loads manage covered , are changed through repetitive organizations measure. pattern and changing loads through angle slip.




Figure 4.6- LSTM

There are a ton of moving parts here, so in the event that your. Following couple of moments, it will start to uncover it's mysteries.

Beginning base, bolts data streams at numerous focuses. mix of information and past cell state is taken care of not exclusively to the actual yet in addition to every one it threes entryways, whih wills choose how the information dealt with.

dark spots simply the entryways, whichs decide individually allow news to enter, delete current potentially let states sway organization's yield right is the present status of the memory call, and of the current contribution. Recall entryway can be open or closed. fail to remember be composed perused these streams addressed .

various jobs expansion augmentation change. focal addition to sign in the two graphs is basically the mystery of LSTMs. Moronically basic as it might appear, this fundamental change assists them with saving a steady blunder when it should be backpropagated at profundity. Rather than deciding the ensuing increasing present status information, straightforwardly has effect. (neglect entryway actually depends on increase, obviously.)

Various arrangements of loads channel the contribution for information, yield and neglecting. The neglect door is addressed as a direct personality work, since, in such a case that the entryway, present status just increased engender once again .

Moreover, subject straightforward predisposition neglect door each lstm cells likewise appeared execution. (then again, suggests a predisposition of 5.)

You may ask why LSTMs have a neglect entryway when their motivation is to connect far off events to a last output. All things considered, at times it's acceptable to neglect. In case you investigating book corpora report, instance, motivation accept following archive and consequently ought .

outline underneath, the doors addressing shut entryways, clear addressing

LSTM Overview

It ought to be noticed that while feed backward network maps one contribution ones outputs, intermittent net plan 1 and more, as over , numerous to more (interpretation), or numerous one (grouping a voice).

3.2.8 OVERVIEW

Our proposed project coordinates every one of the necessities to remunerate the predefined disadvantages. The significant limit of sensor networks is the energy impediment of the sensor hubs which radically influences the lifetime of the organization. it represents a serious danger on the security procedures created for solid information transmission as these calculations exhaust the sensor energy.


CHAPTER - 4

MATERIALS AND METHODS USED

4.1 ALGORITHM


- Plain Text is converted into cipher using encryption algorithm with the help of Key.
- Using the LSTM read the input file
- LSTM nodes uses input value previous output and internal state for
- calculation.Result calculation not only provide output value but also update internal state
- Divide into training and testing in the LSTM and design a layer for the LSTM.
- Initially we need to train the LSTM with the trained data set.
- Check the Accuracy and It get satisfied with the Accuracy
- Then we need to obtain the test dataset and also the Accuracy
- Compare the results.
- The we measure the performance

4.2 WORK FLOW



The sensor hub gather the information and that information should be Encoded. The information encoded utilizing LSTM or RNN , yet LSTM is better for encoding . In LSTM hub utilizes input esteem ,past yield and interior state utilizes for computation .The outcome estimation give yield esteem as well as update the inward state . LSTM has boundaries know as door boundaries that control the progression of data with in hub. The LSTM information ought to be prepared prior to going to check the yield .The information is taken from the information sheet in exe.file in that information sheet it has 16 qualities and each estimation of 8 cycle information. In the 16 qualities all odd ones are train information and levels are for trying .Subsequent to finishing the preparation the LSTM the exactness should be check if information is dependable. The exactness need to check little by little if need the precise worth. Subsequent to checking the exactness the information should be test . All levels are should be tried .After need to notice the real information or not. By taking the outcome the precision diagram is acquired

4.3 CODE



```
HOME PLOTS APPS
New Script New Live Script New Download Find Files Import Data Clear Workspace Favorites Clear Commands Simulink Layout Parallel Add-Ons Help Community Feedback Learn MATLAB
FILE VARIABLE CODE SIMULINK ENVIRONMENT RESOURCES
CURRENT FOLDER / > MATLAB Drive >
Name
Published (my site)
>> close all;
clear all;
clc;


a=xlsread('D:\sai_aes_input.xls');
k=0;
for i=1:16
    s_2016_out(i)=(num2str(a(i,9:16)));
end
s_out=categorical(s_2016_out);
for i=1:2:16
    k=k+1;
    signal_train(k)=[round(a(i,1:8).*1)];
    out_train(k)=s_out(i);
end

k=0;
for i=2:2:16
    k=k+1;
    signal_test(k)=[round(a(i,1:8).*1)];
    out_test(k)=s_out(i);
end

%%
XTrain = signal_train';
YTrain=out_train';
XTest=signal_test';
YTest=out_test';

layers = [ ...
    sequenceInputLayer(1)
    lstmLayer(100,'OutputMode','last')
    fullyConnectedLayer(16)
    softmaxLayer
    classificationLayer
]
```

The above program is in matlab , first we have to provide the path for the exe.file . The data sheet contain the 16 values in which first 8 are input and next 8 are output .The data sheet is divided into train set and test set .The train set is all odd numbers .The test set is all even numbers. For train set we need to use for loop for all odd numbers the input is XTrain the output is taken from YTrain. For Test set also we need to take For loop the input is XTest and the Output YTest .For accuracy LSTMACCURACY has to check.




```
HOME PLOTS APPS
New Script New Live Script New Download Find Files Import Data Clear Workspace Favorites Clear Commands Simulink Layout Parallel Add-Ons Help Community Feedback Learn MATLAB
FILE VARIABLE CODE SIMULINK ENVIRONMENT RESOURCES
CURRENT FOLDER / > MATLAB Drive >
Name
Published (my site)
signal_test(k)=[round(a(i,1:8).*1)];
out_test(k)=s_out(i);
end
%%
XTrain = signal_train';
YTrain=out_train';
XTest=signal_test';
YTest=out_test';

layers = [ ...
    sequenceInputLayer(1)
    lstmLayer(100,'OutputMode','last')
    fullyConnectedLayer(16)
    softmaxLayer
    classificationLayer
]
options = trainingOptions('adam', ...
    'MaxEpochs',30, ...
    'MiniBatchSize', 37, ...
    'InitialLearnRate', 0.01, ...
    'SequenceLength', 11, ...
    'GradientThreshold', 1, ...
    'ExecutionEnvironment','auto',...
    'plots','training-progress', ...
    'Verbose',false);
net = trainNetwork(XTrain,YTrain,layers,options);
trainPred = classify(net,XTrain,'SequenceLength',11);
LSTMaccuracy = sum(trainPred == YTrain)/numel(YTrain)*100
testPred = classify(net,XTest,'SequenceLength',11);
LSTMaccuracy = sum(testPred == YTest)/numel(YTest)*100
[c order]=confusionmat(YTest,testPred);
c
```

5.1 RESULT

He obtained graph is from matlab tool. In the graph shows the accuracy and the loss. Graph is taken for the accuracy in % vs iteration .It has accuracy line and training line while observing the accuracy the graph is increasing. As it is obtained from matlab it can also calculated manually by checking bit by bit.

This calculation serves to Energy effective steering conventions are needed to limit the use of the force assets and delaying the organization lifetime way while moving information effectively scatter perceptions assembled by person sensor hubs to all the sensor hubs in the organization. Straightforward conventions, for example, flooding and tattling are normally proposed to accomplish data scattering in WSNs



5.2 DISCUSSION

5.2.1 INPUTS

0	1	0	1	0	1	0	0	0	0	1	0	1	0	0	1
0	1	1	1	0	1	1	1	1	1	0	0	0	0	1	1
0	1	1	0	1	1	1	1	0	1	0	1	0	0	0	0
0	0	1	0	0	0	0	0	0	1	0	1	1	1	1	1
0	1	0	0	1	1	1	1	0	1	0	1	0	1	1	1
0	1	1	0	1	1	1	0	0	0	0	1	0	1	0	0
0	1	1	0	0	1	0	1	0	0	1	0	0	0	0	0
0	0	1	0	0	0	0	0	1	1	1	1	0	1	1	0
0	1	0	0	1	1	1	0	0	1	0	0	0	0	0	0
0	1	1	0	1	0	0	1	0	0	1	0	0	0	1	0
0	1	1	0	1	1	1	0	1	0	0	1	1	0	0	1
0	1	1	0	0	1	0	1	1	0	1	1	0	0	1	1
0	0	1	0	0	0	0	0	0	0	0	1	1	0	1	0
0	1	0	1	0	1	0	0	0	0	0	0	0	0	1	0
0	1	1	1	0	1	1	1	1	1	0	1	0	1	1	1
0	1	1	0	1	1	1	1	0	0	1	1	1	0	1	0

In the data sheet it has the eight bit inputs datas and the eight bits outputs datas. first 8 bits are the plain text and the next 8 bits of data are the cipher text.

Cipher text, or cipher text, is a technique for cryptography where units of data, known as plain text, are supplanted by replacements as a component of a calculation. By utilizing a replacement figure, single, sets, or trios of letters (or a blend of these) are supplanted yet kept in a similar arrangement. Basic replacement figures work utilizing single letters, while those that are run on bigger gatherings of letters are poly graphic.cipher text cannot be identified or it cannot be cracked in its form.

So it need to be converted to plain text to read the data.

5.2.2 TRAIN DATASET

'0'	'0'	'0'	'1'	'1'	'0'	'0'	'0'
'0'	'1'	'0'	'1'	'0'	'1'	'0'	'1'
'0'	'1'	'0'	'1'	'0'	'1'	'0'	'1'
'0'	'0'	'1'	'0'	'0'	'0'	'0'	'0'
'0'	'0'	'0'	'0'	'1'	'0'	'0'	'0'
'0'	'0'	'0'	'0'	'1'	'0'	'0'	'1'
'0'	'0'	'0'	'1'	'1'	'0'	'1'	'0'
'1'	'1'	'0'	'1'	'0'	'1'	'0'	'1'

In the data sheet all odd ones are used for training,in data sheet it had only 16

inputs so the no of training inputs are 8 .The LSTM data need to be train before going to check the output.

5.2.3 TEST DATASET

'1'	'1'	'0'	'1'	'0'	'1'	'0'	'1'
'0'	'0'	'0'	'1'	'1'	'0'	'1'	'0'
'0'	'0'	'0'	'0'	'1'	'0'	'0'	'1'
'0'	'0'	'0'	'1'	'1'	'0'	'1'	'0'
'0'	'0'	'1'	'0'	'1'	'0'	'0'	'1'
'0'	'0'	'1'	'0'	'0'	'0'	'0'	'0'
'0'	'0'	'0'	'1'	'1'	'0'	'0'	'0'
'0'	'1'	'0'	'1'	'0'	'1'	'0'	'1'

In the data sheet all odd ones are used for testing,in data sheet it had only 16 inputs so the no of testing inputs are 8 .After checking the accuracy need to be test.All even are tested.

EXEMPLAR GENERATION

Plain text	Cipher text
54	29
77	C3
6F	50
20	5F
4F	57
6E	14
65	20
20	F6
4E	40
69	22
6E	99
65	B3
20	1A
54	2
77	D7
6F	3A

Plain Text								Cipher text							
0	1	0	1	0	1	0	0	0	0	1	0	1	0	0	1
0	1	1	1	0	1	1	1	1	1	0	0	0	0	1	1
0	1	1	0	1	1	1	1	0	1	0	1	0	0	0	0
0	0	1	0	0	0	0	0	0	1	0	1	1	1	1	1
0	1	0	0	1	1	1	1	0	1	0	1	0	1	1	1
0	1	1	0	1	1	1	0	0	0	0	1	0	1	0	0
0	1	1	0	0	1	0	1	0	0	1	0	0	0	0	0
0	0	1	0	0	0	0	0	1	1	1	1	0	1	1	0
0	1	0	0	1	1	1	0	0	1	0	0	0	0	0	0
0	1	1	0	1	0	0	1	0	0	1	0	0	0	1	0
0	1	1	0	1	1	1	0	1	0	0	1	1	0	0	1
0	1	1	0	0	1	0	1	1	0	1	1	0	0	1	1
0	0	1	0	0	0	0	0	0	0	0	1	1	0	1	0
0	1	0	1	0	1	0	0	0	0	0	0	0	0	1	0
0	1	1	1	0	1	1	1	1	1	0	1	0	1	1	1
0	1	1	0	1	1	1	1	0	0	1	1	1	0	1	0

In order to train and test LSTM, it is necessary to generate the input and the output data. In this work, AES algorithm is used for obtaining the cipher text from the plain text.

ENCRYPTION RELATIONSHIP BETWEEN DESIRED AND ACTUAL VALUES

(TRAIN DATASET)

Desired Value								Actual Value								EN CR YP TION RE LA TIONSHIP BETWEEN DESIRED AND ACTUAL VALUES (Test DATASET)
0	0	1	0	1	0	0	1	'0'	'0'	'0'	'1'	'1'	'0'	'0'	'0'	
0	1	0	1	0	0	0	0	'0'	'1'	'0'	'1'	'0'	'1'	'0'	'1'	
0	1	0	1	0	1	1	1	'0'	'1'	'0'	'1'	'0'	'1'	'0'	'1'	
0	0	1	0	0	0	0	0	'0'	'0'	'1'	'0'	'0'	'0'	'0'	'0'	
0	1	0	0	0	0	0	0	'0'	'0'	'0'	'0'	'1'	'0'	'0'	'0'	
1	0	0	1	1	0	0	1	'0'	'0'	'0'	'0'	'1'	'0'	'0'	'1'	
0	0	0	1	1	0	1	0	'0'	'0'	'0'	'1'	'1'	'0'	'1'	'0'	
1	1	0	1	0	1	1	1	'1'	'1'	'0'	'1'	'0'	'1'	'0'	'1'	

Desired Value								Actual Value							
1	1	0	0	0	0	1	1	'1'	'1'	'0'	'1'	'0'	'1'	'0'	'1'
0	1	0	1	1	1	1	1	'0'	'0'	'0'	'1'	'1'	'0'	'1'	'0'
0	0	0	1	0	1	0	0	'0'	'0'	'0'	'0'	'1'	'0'	'0'	'1'
1	1	1	1	0	1	1	0	'0'	'0'	'0'	'1'	'1'	'0'	'1'	'0'
0	0	1	0	0	0	1	0	'0'	'0'	'1'	'0'	'1'	'0'	'0'	'1'
1	0	1	1	0	0	1	1	'0'	'0'	'1'	'0'	'0'	'0'	'0'	'0'
0	0	0	0	0	0	1	0	'0'	'0'	'0'	'1'	'1'	'0'	'0'	'0'
0	0	1	1	1	0	1	0	'0'	'1'	'0'	'1'	'0'	'1'	'0'	'1'

ENCRYPTION RELATIONSHIP BETWEEN DESIRED AND ACTUAL VALUES (TRAIN & TEST DATASET)

Train dataset		Test Dataset	
Desired value	Actual value	Desired value	Actual value
29	18	C3	D5
50	55	5F	1A
57	55	14	09
20	20	F6	1A
40	08	22	29
99	09	B3	20
1A	1A	02	18
D7	D5	3A	55

**DECRYPTION RELATIONSHIP BETWEEN DESIRED
AND ACTUAL DATA (TEST DATASET)**

DESIRED VALUE								ACTUAL VALUE							
'1'	'1'	'0'	'1'	'0'	'1'	'0'	'1'	0	1	1	0	1	1	1	0
'0'	'0'	'0'	'1'	'1'	'0'	'1'	'0'	0	1	0	0	1	1	1	1
'0'	'0'	'0'	'0'	'1'	'0'	'0'	'1'	0	0	1	0	0	0	0	0
'0'	'0'	'0'	'1'	'1'	'0'	'1'	'0'	0	1	1	1	0	1	1	1
'0'	'0'	'1'	'0'	'1'	'0'	'0'	'1'	0	0	1	0	0	0	0	0
'0'	'0'	'1'	'0'	'0'	'0'	'0'	'0'	0	1	1	1	0	1	1	1
'0'	'0'	'0'	'1'	'1'	'0'	'0'	'0'	0	1	1	0	0	1	0	1
'0'	'1'	'0'	'1'	'0'	'1'	'0'	'1'	0	1	0	0	1	1	1	1

CHAPTER-5

CONCLUSION AND FUTURE WORKS

6.1 CONCLUSION

The proposed crypto framework has the benefit of consolidating an even and hilter kilter cryptographic strategy. In fact, the one symmetric dependent on the AES is utilized to get the correspondences between an exceptionally restricted asset hubs which have high security imperatives in view of their exceptionally restricted limit in memory, figuring force and energy independence. Furthermore, the utilization of AES in CTR mode by altering its crude method of activity permitted us to deal with the issue identified with the vehicle of the keys in symmetric cryptography, which permits our different imparting elements of the level 3, to have a similar mystery key to every meeting foundation. One the opposite, one hilter kilter strategy is misused at the level of the less restricting hubs. This uneven arrangement employments the Distinctive calculation key trade stage with a strategy for creating and figuring keys dependent on elliptic bends (EEC). ECC is a quicker encryption procedure when contrasted with different strategies in a similar gathering and are utilized for key trade and computerized

REFERENCES

- [1] Akyildiz, W. Su, Y. Sankarasubramaniam, E. Cayirci, "Wireless Sensor Networks: A Survey" Computer Networks (Elsevier) Journal, Pp. 393- 422, March 2002.
- [2] [2] Israel Leyva-Mayorga, Mario E. Rivero-Angeles, Chadwick CarretoArellano, "Priority-Based Multi-Event Reporting in Hybrid Wireless Sensor Networks" 28th International Conference on Advanced Information Networking and Applications, IEEE 2014.
- [3] [3] Sebastian Terence, Krishna Priya.K.C "RETP: Reliable Event Transmission Protocol in a Wireless Sensor Network" International Conference on Emerging Trends in Computing, Communication and Nanotechnology (ICECCN), IEEE 2013.
- [4] Otgonchimeg Buyanjargal and Youngmi Kwon, "Adaptive and Energy Efficient Clustering Algorithm for Event-Driven Application in Wireless Sensor Networks (AEEC)", Journal Of Networks, VOL. 5, NO. 8, pages: 904 - 911, August 2010.
- [5] Martin Enzinger "Energy-efficient communication in Wireless Sensor Networks" Network Architectures and Services, August 2012
- Juan Luo, Jinyu Hu, Di Wu, Renfa Li "Opportunistic Routing Algorithm for Relay Node Selection in Wireless Sensor Networks" IEEE Transactions on Industrial Informatic-2013.
- [6] Juan Luo, Jinyu Hu, Di Wu, Renfa Li "Opportunistic Routing Algorithm for Relay Node Selection in Wireless Sensor Networks" IEEE Transactions on Industrial Informatic-2013.
- [7] Stefanos A. Nikolidakis, Dionisis Kandris, Dimitrios D. Vergados, Christos Douligieris "Energy Efficient Routing in Wireless Sensor Networks Through Balanced Clustering"29-42; doi:10.3390/a6010029 Algorithms 2013 2013.
- [8] WEI Yunkap,2, MAO Yumingl, LENG Supengl, HUANG Wentao2 "A Low-Overhead Energy-Efficient ARQ Protocol for Wireless Sensor Networks" China Communications, October 2014.
- [9] Archana S, Saravanan.N.P "Biologically Inspired QoS Aware Routing Protocol to Optimize Lifetime in Sensor Networks" International Conference on Recent

Trends in Information Technology, IEEE 2014.

[10] Madhumathy P, Sivakumar D, "Enabling Energy Efficient Sensory Data Collection Using Multiple Mobile Sink", China Communications· October 2014.

[11] Raghavendra D. Krushnaji, Dnyaneshwar A. Rokade "A Survey on Event Detection and Transmission Protocols in Wireless Sensor Network" International Journal of Advanced Research in Electronics and Communication Engineering (IJARECE) Volume 3, Issue 11, November 2014