

SOLAR POWERED WATER PURIFICATION SYSTEM

Submitted in fulfilled of the requirement for the award of
Bachelor of Engineering Degree in
Electrical and Electrical Engineering

By

SANTHIYA M (Register No.37140071)

SARANYA R (Register No.37140073)



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)

Accredited with Grade "A" by NAAC

JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI – 600 119

MARCH 2021



SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY

(DEEMED TO BE UNIVERSITY)

Accredited "A" Grade by NAAC | 12B Status by UGC | Approved by AICTE

www.sathyabama.ac.in

DEPARTMENT OF ELECTRICAL AND ELECTRONICS ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the Bonafide work of **SANTHIYA M** (Register No. **37140070**) & **SARANYA R** (Register No. **37140073**) who carried out the project entitled "**SOLAR POWERED WATER PURIFICATION**" under our supervision from December 2020 to April 2021.

Dr. B. L. BHARATHI
Internal Guide

Dr. V. SIVACHIDAMBARANATHAN
Head of the Department

Submitted for Viva voce Examination held on _____

Name:

Signature:


Internal Examiner

External Examiner


DECLARATION

We **SANTHIYA M** (Reg. No. 37140070) and **SARANYA R** (37140073) Hereby declare that Project Report entitled “Solar powered water purification” done by us under the guidance of **Mrs. M. L. BHARATHI** is submitted in partial fulfillment of the requirements for the award of Bachelor of Engineering Degree in Electrical and Electronics Engineering.

1.

A rectangular box containing a handwritten signature in blue ink that reads "M. Santhiya".

2.

A rectangular box containing a handwritten signature in blue ink that reads "Saranya R".

DATE:

PLACE:

SIGNATURE OF THE CANDIDATES

ACKNOWLEDGEMENT

We are pleased to acknowledge our sincere thanks to Board of Management of **SATHYABAMA** for their kind encouragement in doing this project and for completing it successfully. We are grateful to them.

We convey our thanks to **Dr. N. M. NANDHITHA., Dean, School of Electrical and Electronics Engineering** and **Dr. V. SIVACHIDAMBARANATHAN, Head of the Department, Dept. of Electrical and Electronics Engineering** and **Internal Guide Dr. M. L. Bharathi**, for providing us necessary support and details at the right time during the progressive reviews.

We wish to express our thanks to all Teaching and Non-teaching staff members of the Department of Electrical and Electronics Engineering who were helpful in many ways for the completion of the project.

Abstract

This project we have a tendency to square measure coming up with a water apparatus that works on alternative energy. The essential principle behind this project is reverse diffusion. The star radiations square measure collected by solar array. This energy is then kept in a very battery through a charge controller. The charge controller prevents the battery from obtaining overcharged. The battery is connected to a purification unit through a buck boost device. The purification unit consists of an air mass motor, reverse diffusion system and therefore the storage tank. The air mass created needed the mandatory pressure required to hold out reverse diffusion. The microcontroller 8051 keeps a watch to the amount of water and therefore the pH worth of the pure water within the storage tank and prevent it from overflowing. Through this method we have a tendency to obtain the sublimate water within the storage tank. It became a recently concerned degreed plan to use solar arrays as an energy supply for cleans.

Title of content

Chapter No	Title	Page No
	Abstract	v
	Listoffigures	viii
	Listoftables	ix
1	Introduction	
	1.1 General information	1
	1.2 Literature survey	3
2	Principle and operation of proposedsystem	
	2.1 Concept of existing system	4
	2.2 Concept ofproposedsystem	5
	2.3 Proposed systemblockdiagram	5
	2.4 Working	6
	2.5 Advantages of proposed system	6
3	Introduction to embeddedC	
	3.1 Introduction to embedded C	8
	3.2 Porteous model	8
	3.3 Simulation diagram	8
4	Hardwaresetup	
	4.1 Hardwaresetup	9

4.2 Hardware implementation and results	10
4.2.1 Program for RO-purifier	11
4.2.1.1 Explanation for RO-system	13
4.2.2 Program pH sensor and water level sensor	19
4.2.2.1 Program pH sensor	20
4.3 Hardware requirement	
4.4 Component description	21
4.4.1 Node MCU	21
4.4.1.1 Features	23
4.4.1.2 Applications of node MCU	23
4.4.2 Solar panel	24
4.4.2.1 Photovoltaic effect	25
4.4.3 Battery	25
4.4.3.1 Specification	25
4.4.3.2 Features	25
4.4.5 Microcontroller 8051	26
4.4.5.1 Pin diagram	26
4.4.5.2 Application	27
4.4.6 Voltage regulator	28
4.4.6.1 Application	28
4.4.7 RO system	29
4.4.7.1 Principle of RO	30
4.4.7.2 Process of RO	30
4.4.7.3 Benefits and advantages	30
4.4.8 Water level sensor	32
4.4.8.1 Working of water level sensor	34

4.4.9 LEDdisplay	35
4.4.9.1 Features	35
4.4.9.2 Application	36
4.4.9.3 Advantages	37
4.4.10 pHsensor	38
4.4.10.1 Application	39
4.4.11 Wi-Fi module	40
4.4.11.1 Features of ESP8266	40
4.4.11.2 Use of ESP8266	41
4.4.11.3 Application	42
4.4.12 Buckboostconverter	42
4.4.12.1 Application	
4.4.12.2 Advantages of buckboost converter	
5 Conclusion and futurescope	43
5.1 Summery	43
5.2 Application	

List of figures

Figure no	Title	Page no
3.1	Simulation diagram	8
4.1	Hardware setup	9
4.2	Water purifier is detected	12
4.3	Display the pH value and water level	11
4.4	Battery	24
4.4.3	Solar panel	23
4.5.1	Pin diagram	26
4.6	Circuit diagram of 7860	27
4.7.1	RO	29
4.7.2	Process of RO	29

4.8.	Water level sensor	31
4.8.1	Working of waterlevelsensor	33
4.9.	LED display	34
4.10	pHSensor	38
4.11	ESP01 modulewire frame	39
4.12	Buckboost converter	40

CHAPTER 1

INTRODUCTION

1.1 GENERAL INFORMATION

2.2billion people need admittance to safely oversaw drinkable administrations (World Health Organisation/UNICEF 2019). Over ½ the overall populace or four.2billion people need securely oversaw sterilization administrations (WHO/UNICEF 2019). 297,000 children underneath 5 kick the bucket once every year from diarrheal sicknesses on account of helpless sterilization, helpless cleanliness, or perilous drinkable (WHO/UNICEF2019). A couple of billion people board nations encountering highwater stress (UN 2019). ninety p.c of cataclysmic events square measure climate related, along with floods and dry seasons (UNISDR). eighty p.c of waste matter streams into the plan while not being dealt with or reused (UNESCO, 2017). Around a straightforward part of the world's transboundary waterways do not have an agreeable administration system (SIWI). Horticulture represents over two thirds of world water withdrawal (FAO). About 75% of all mechanical water with drawals square measure utilized for energy creation (UNESCO, 2014). The Institute of medications board (part of the National Academy of Sciences) proposes that the normal human burns-through about eight cups of water each day to deal with a solid way. To electors of the U. S. This doesn't seem extreme to achieve because of running water is generally advertised. The plenitude of contemporary streaming water is normal in created countries, anyway, could be an advantage only from time to time rehearsed by those inside the creating scene. Indeed, the lack of water could be a developing worry in a few components of the globe, especially in creating or ruined nations. Ironically such a trouble may exist once more than seventy fifth of the Earth's surface is roofed by water. In any case, a lot of that water is sea water, that consolidates a saltiness level that is excessively high for human utilization. Through right water compound activity, the sea is a promising stock of water that may enough offer this developing need. At present, goliath speculations are a square measure vital for prudent, huge scope substance activity frameworks that non-industrial nations don't have. tragically, these squares measure the nations with the best need for contemporary drinkable, as a few of their

ebb and flow water sources square measure polluted or poor in give. Subsequently, 1.8 million people bite the dust from anyway, conjointly microorganism treatment. to deal with this disadvantage, there square measure different in progress endeavors to deliver H₂O for ruined networks. In Africa, a few of those assaults include penetrating wells to take advantage of groundwater. Be that as it may, groundwater in Africa is banished and these wells ought to be mammary organ more profound on the grounds that the asset gets drained over thelongrun. In this manner, various sources like oceanwaterwillsupplementthesubstantialcleanwaterdemandandalleivatethereliance on groundwater. A synthetic activity framework eliminates the salt from oceanwater, rebuilding it into consumable water through one among a few cleaning measures. Refining, or boilingthedirty, is most likely the solitary procedure. the technique needs bubbling salt water at temperatures over a hundred °C, a temperature at that microorganism is slaughtered. Accordingly, it's qualified to seek after AN affordable anyway cheap synthetic activity framework that may build the potential for inescapable application for water refinement. A substance activity framework will add combination with the methodology wells to help lighten difficulties felt by the shortage of new water, not exclusively in agricultural countries, anyway conjointly in nations round the world.

1.2 LITERATURE SURVEY

- [1] The Water Myth; How Many Glasses Do You Really Need?" Kaiser Permanente web.18 may2019
- [2] Carpaccio, Joe, Alberto Fonts, Ryan Harami, Yasemin Kimyacioğlu, and Stadulis. "Engineers without borders: Water purification system." Thesis. S Santa Clara University,2008.
- [3] Dovi, Efam. "Bringing Water to Africa's Poor." Africa Renewal. Oct.2007. Web. 10 Oct. 2011. H2O Africa Foundation. Web. 9 Oct. 201
- [4] Liberia: Facts and Figures. World Geography: Understanding a Changing World. ABC-CLIO, 2011. Web.7 Oct.2011
- [5] Santiago, Jason, Ryan Hinds, and Megan Ingemanson. "Team Clean Water Solar Powered Water Purification System." Thesis. Santa Clara University,2011
- [6] The Facts About the Global Drinking Water Crisis." Powering a Global

Community Creating Safe Drinking Water for the World. Blue Planet Network.

Web. 7 Oct.2011

- [7] Nena Nwachukwu, Charles P Gerba, Emerging waterborne pathogens: can we kill them all? Current Opinion in Biotechnology, Volume15, Issue3, June 2004, pages 175-180, ISSN0958-1669, 10.1016/j.copbio.2004.04.010
- [8] Penn State Study Finds Calf Milk Pasteurization Effective, but Variable. Dairy and Animal Science-Penn State University. Web. 20 May 2012.
- [9] What Chemicals Do Reverse Osmosis and Distillation Remove/Reduce?" What Chemicals Do Reverse Osmosis and Distillation Remove/Reduce? Web.20 May2012.
- [10] Smile, A., and Mrad, F. "Applied Mechatronics." USA: Oxford University Pres
- [11] Josephine Treacy, "Drinking Water Treatment and challenges in Developing Countries. 2019Ying Zhang, "
- [12] Applicationofsolarenergyinwatertreatmentprocesses.2017Abishek, " Water purification using solar thermal and solar PV. 2018
- [13] Julia Terrapon-pfaff, "The relationship between solar Thermal power plants and future development in local water demand at sustainability.2020.
- [14] Nena Nwachukwu, Charles P Gerba, emerging waterborne pathogens: can we kill them all? Current Opinion in Biotechnology, Volume 15, Issue 3, June 2004, pages 175-180, ISSN0958-1669, 10.1016/j.copbio.2004.04.010
- [15] Penn State Study Finds Calf Milk Pasteurization Effective, but Variable. Dairy and Animal Science-Penn State University. Web. 20 May 2012.

CHAPTER 2

PRINCIPLE AND OPERATION OF EXISTING AND PROPOSED SYSTEMS

EXISTING SYSTEM

Purified potable water is required for humans for his or her healthy health. The technologies gift these days for purification of water at an excessive amount of expensive. These technologies aren't cheap for rural areas due to its price and accessibility of electricity as a result of all the current water purifiers work on electric offer. These varieties of water purifiers conjointly take away all the essential minerals like Ca, iron, sodium, and metal that are needed for the body and should result in their deficiencies conjointly. actinic ray technology solely eliminates the microorganisms however doesn't flush out their dead bodies. Takes a protracted time for the purification method. Changes the style of the water as all the essential minerals are off from it and the method is thought as De-mineralization. Membranes of the RO purifiers sought to be modified oftentimes or a minimum of once a year solely fourth of the overall water that has entered the system is appropriate drinking. the opposite 3 fourth components ought to be thrown away.


PROPOSED SYSTEM

There are a few arrangements anticipated the elaborate disadvantage and everybody has some benefit over others. The water decontamination framework abuses the elective energy worried in purging the water for different capacities in house misuse the elective energy from multiple points of view. misuse this for the treatment of water, it's become extra basic since it very well might be a regularly low gear answer that attempts to catch the energy and warmth from the sun to scour the water for human use and utilization. A star water cleansing framework is particularly helpful for provincial networks, as they don't create alternate methods of water purging arrangement and also, power to run such

designs. The chief helpful component with respect to star water decontamination is that there's no need of fuel. It is accurately on account of the lack of fuel that produces star applications nearly better than conventional wellsprings of energy.

since it doesn't cause contamination) or wellbeing perils identified with contamination. Subsequently, according to our objective off this task, we will in general style a reliable gratitude to cleanse water for areas that are off network and don't have steady wellsprings of unpolluted water. This style conjointly satisfies the need of an espresso spending item considering most of the spots don't offer consumable water to their electors. Water purging through sun-oriented energy is one in everything about best developments to try not to squander energy and to claim uncontaminated water. an electrical mechanical assembly framework needs extra force and costs bounty extra as well.

PROPOSED SYSTEM BLOCKDIAGRAM



WORKING

The sun oriented radiations region unit gathered by solar battery. This energy is then continued during a battery through a charge regulator. The charge regulator

keeps the battery from acquiring cheated. The battery is furthermore associated with a transformer. The transformer converts 24V to +5V, which is required by the microcontroller. The cleansing unit comprises of an air mass engine, turn around dispersion framework and in this way the tank. The air mass makes the fundamental compel expected to hold out invert dispersion. The microcontroller 8051 holds a watch to the measure of water inside the tank and forestalls it from flooding from the water level detecting element. It gives signs to microcontroller to thwart flood. Through this strategy we will in general acquire the sublimate water inside the tank, likewise we will in general figure hydrogen particle focus cost through hydrogen particle fixation detecting component that is shipped off hub much and it is appeared in the OLED show.

ADVANTAGES OF PROPOSED SYSTEM

- As solar energy is being utilized for the sanitization of water, which is modest and bountiful.
- It can be utilized wherever where power isn't accessible, particularly Desert territories, Hilly places, storm influenced zones. Here, the microcontroller which is utilized likewise keeps from flooding. Additionally, switch assimilation is a decent sanitizer measure.

CHAPTER 3

SIMULATION MODEL AND RESULTS

INTRODUCTION TO EMBEDDED C

- Embedded C could even be a lot of language augmentations for the Communication by the C typical board to the change shared trait gives that exist between C expansions for fluctuated installed framework. verifiably implanted C programming needs nonstandard augmentations to the C language accordingly on help fascinating alternatives like mounted reason number-crunching, numerous unmistakable memory squares and fundamental I/O activities. •
- In 2008, the C Standards Committee stretched out the C language to the modify these issues by giving a typical for all executions to remain to. It incorporates skin do of decisions not offered old C, for example, fixed - point math, named address zones, and essential I/O equipment tending to. • Embedded C uses the greater part of the grammar and phonetics of old C, e.g., primary () perform, variable definition, datatype announcement, contingent articulations (if, switch, case), circles (while, for), capacities, exhibits, and strings, designs, and associations, bit activities, macros, and so on

PROTEUS MODEL

The Proteus Design Suite is an exclusive programming instrument suite utilized essentially for electronic plan computerization. The product is utilized mostly by electronic plan architects and experts to make schematics and electronic prints for assembling printed circuit sheets.

Fig 3.1 Simulation Diagram

CHAPTER 4

HARDWARE DESCRIPTION

4.1 HARDWARE SETUP



Fig.4.1 Hardware setup

The sun oriented radiations region unit gathered by solar battery. This energy is then continued during a battery through a charge regulator. The charge regulator keeps the battery from acquiring cheated. The battery is furthermore associated with a transformer. The transformer converts 24V to +5V, which is required by the microcontroller. The cleansing unit comprises of an air mass engine, turn around dispersion framework and in this way the tank. The air mass makes the fundamental compel expected to hold out invert dispersion. The microcontroller 8051 holds a watch to the measure of water inside the tank and forestalls it from flooding from the water level detecting element. It gives signs to microcontroller to thwart flood. Through this strategy we will in general acquire the sublimate water inside the tank, likewise we will in general figure hydrogen particle focus cost through hydrogen particle fixation detecting component that is shipped off hub much and it is appeared in the OLED show.

HARDWARE IMPLEMENTATION AND RESULTS

PROGRAM FOR RO PURIFIER

```
define BLYNK_PRINT Serial
```

```
#include <ESP8266WiFi.h>
```

```
#include <LiquidCrystal.h>
```

```
#include <DHT.h>
```

```
#include <BlynkSimpleEsp8266.h>
```

```
char auth []
```

```
= "dkcj3qktAStN4OBZKsfrYW8IE24W6xYX"; char ssid
```

```
[] = "IOT".
```

```
char pass [] = "IOT@1234".
```

```
void setup ()
```

```
{
```

```
pin Mode (4, INPUT);  
Serial.begin(9600);  
Blynk.begin(auth, ssid, pass).
```

```
Blynk.syncAll();  
Blynk.notify("Yaaay... Device detected!");
```

```
pinMode (16, OUTPUT);  
}
```

```
void data ()
```

```
{  
int sw=digitalRead  
(4); Serial.println(sw);  
if(sw==0)
```

```
{  
digitalWrite (16,1).  
}
```

```
else
```

```
{  
  
digitalWrite (16,0).  
}
```

```
}  
  
void loop ()
```

```
{  
Blynk.run ().  
dataa ().
```

```
}
```




Fig.4.2. Water purifier is detected

EXPLAN ATION FOR RO SYSTEM

Let consider the ESP8266 WIFI, liquid crystal, DHT, Blynk SimpleESP8266. To define Blynk print serial to print the output. In the Blynk app have the authentication to access the app. The ssid, password is set to the mobile phone that connected to the Blynk app. The input is connected to the pin mode 4. The pin 4 is read the input. The output is connected to the pin mode 16. The output pin 16 shows the message Water purifier device is detected.

If sw==0 the digital write to print the output is 1 else it prints the output is 0. The loop will continue to print the output and it will run with data then it shows the results in the Blynk app.

PROGRAM FOR PH SENSOR AND WATER LEVEL SENSOR

pH sensor

```
#include<ESP8266WiFi.>
```

```
#include <WiFiClient.h>
```

```
#include<ESP8266WebeServer.h>
```

```
#define Sensor Pin 17
```

```
unsigned long int avgValue;
```

```
float b, pHValue;
```

```
int buf [10], temp;
```

```
#define offset -0.03
```

```
constchar*ssid    ="IOT";
```

```
const char* password = "11112233";
```

```
ESP8266WebServer server (80).
```

```
String web String=" ".
```

```

void handle root () {

    server. Send (200, "text/plain", "Hello from the ph esp8266, read from /ph "); delay

    (100).

}

void setup(void)

{

    Serial. Begin (115200);

    Serial.println("Ready");

    WiFi.begin(ssid, password).

    Serial. Print ("\n\r \n\rWorking to

connect"); while (WIFI. Status ()!=

WL_CONNECTED) {

    delay (500);

    Serial.print(".").

}

    Serial.println("");

    Serial.println("PH Server");

```

```
Serial.print("Connected to ");
```

```
Serial.println(ssid);
```

```
Serial.print("IP address: ");
```

```
Serial.println(WiFi.localIP());
```

```
server. on ("/", handle_root);
```

```
server. on ("/ph", [](){
```

```
    getph ();
```

```
    webString="Ph Value: "+String((float)phValue) +" ";
```

```
    server. send (200, "text/plain", webString);
```

```
});
```

```
server. begin ();
```

```
Serial.println("HTTP server started");
```

```
}
```

```
void loop(void)
```

```
{
```

```
    server. handleClient ();
```

```
}
```

```
void getph () {  
  
    for (int i=0;i<10;i++)  
  
    {  
  
        buf[i]=analogRead  
  
        (SensorPin); delay (10);  
  
    }  
  
    for (int i=0;i<9;i++)  
  
    {  
  
        for (int j=i+1;j<10;j++)  
  
        {  
  
            if(buf[i]>buf[j])  
  
            {  
  
                temp=buf[i];  
  
                buf[i]=buf[j];  
  
                buf[j]=temp;  
  
            }  
  
        }  
  
    }  
  
}
```

```

}

avgValue=0; for

(int i=2;i<8;i++)

avgValue+=but[i];

phValue=(float)avgValue/1023*5

; phValue=0.3*phValue+offset;

Serial.print("  pH:");

Serial.print(phValue,2);

Serial.println("");

}

```

Water level sensor

```

#define BLYNK_PRINT Serial

#include <ESP8266WiFi.h>

#include <BlynkSimpleEsp8266.h>

char auth [] = "iqmvG0QDIjNQvBnpy0elZmpwdm5kHISs";

char ssid[] = "IOT";

```

```
char pass [] = "IOT@1234";
```

```
char server[] = "155.0.277.46";
```

```
const int sensorPin= A0;
```

```
float liquid_level;
```

```
int liquid_percentage;
```

```
int top_level = 100;
```

```
int bottom_level = 0;
```

```
void setup () {
```

```
  Serial.begin(9600);
```

```
  Blynk.begin(auth, ssid, pass, server);
```

```
  pinMode (sensorPin, INPUT);
```

```
  Blynk.virtualWrite(V0, liquid_level);
```

```
  Blynk.virtualWrite(V1, liquid_percentage);
```

```
  Blynk.run ();
```

```
}
```

```
void loop() {
```

```
liquid_level = analogRead(sensorPin);  
  
liquid_percentage = ((liquid_level-bottom_level)/top_level)  
  
*100; Serial.println(liquid_level);  
  
Serial.println(liquid_percentage);  
  
Blynk.virtualWrite(V0, liquid_level);  
  
Blynk.virtualWrite(V1, liquid_percentage);  
  
delay (100);  
  
Blynk.run ();  
  
}
```



Fig.4.2.2 Display the pH value and water level

HARDWARE REQUIREMENTS

- Solarpanel
- Battery
- Microcontroller
- Voltageregulator
- RO system
- Water levelsensor.
- pHSensor
- Led display.
- WIFImodule
- BuckBoostconverter

COMPONENT DESCRIPTION

NODE MCU

Node MCU is an open-source advancement board, in view of the popular ESP8266chip, which is a 32-digit regulator with worked in Wi-Fi handset. Also, it is amazingly minimal effort. The best part is that this board is Arduino IDE viable, you can use the large numbers of model code and libraries on Node MCU. Other than Arduino IDE or Arduino.

programming language, Node MCU upholds numerous different dialects like LUA content, miniature Python and so forth with these scripting dialects, you can build up your model inside a couple of content lines. This base board is intended to facilitate the prototyping utilizing Node MCU V3 board (Loin). You can additionally utilize these pins for prototyping, with the male to female jumper wires. With the locally available voltage controller, the board additionally accompanies power pointer. The Node MCU has a

more remarkable processor than the Arduino's Atmega328, a 4Mb flash memory and significantly more RAM.

4.4.1.1 FEATURES

- Eliminate the necessities of breadboard and to broaden the 5V, 3.3V, GND pins.
- Ease the interface between Node MCU to different sensor and actuator module.
- Comes with on board 5V Voltage controller that is equipped for yield greatest 1A.
- Vin: 6V to 24VDC, through DC Jack
- Comes with Power Indicator LED

4.4.1.2 APPLICATION OF NODEMCU

- Prototyping of IoT gadgets
- Low power battery worked applications .
- Network projects

SOLAR PANEL

Sunlight based energy is being gathered by utilizing a sun powered board. The gathered sunlight-based energy is being put away in the battery. If there should arise an occurrence of provincial and distant regions and the territories influenced however cataclysmic events where power is a major issue, this put away energy can be utilized for the sanitization of water. The charge regulator utilized here controls the required. utilized for the decontamination of water. The charge regulator utilized here controls the necessary measure of sun-oriented energy to be

put away in the battery. Transformation of light energy in electrical energy depends on a marvel called photovoltaic impact. At the point when semiconductor materials are presented to light, a portion of the photons of light beam are consumed by the semiconductor gem which causes a critical number of free electrons in the gem. This is the essential justification creating power because of photovoltaic impacts.



Fig.4.4.3 Solar panel

4.4.2.1 PHOTOVOLTAIC EFFECT

. In most electrical wonder applications, the radiation is light, and the gadgets are known as sunlight based cells. Inside the instance of a contact photovoltaic cell, enlightening the texture makes an electrical flow as energized electrons and the leftover openings are cleared in various ways by the natural field of the depletion region.

4.4.2.2 APPLICATION

- Rooftop and building incorporated frameworks.
- Concentrator photovoltaics
- Photovoltaic warm half breed sun oriented gatherer
- Power stations.
- In transport
- Telecommunication and flagging
- Spacecraft applications

BATTERY

solar cell module produces electricity when only the sun is shining. they are not storing energy; it's necessary to store a number of the energy generated by the solar array. it's additionally used for the powering operation system. The battery is of 12V DC. The terminal voltages of battery cells rely upon the chemicals and materials utilized in its construction, and not on its physical sizes. This is an elite fixed upkeep free battery with consistent Voltage Charge (12Volt1.3Ah). These lead corrosive batteries square measure fixed support. free batteries. This battery is fitting for crisis lights, star lighting, intersection rectifier lighting, electronic weight scales.



Fig 4.4.3 Battery

4.4.3.1 SPECIFICATION

- Model No:AT12-1.3
- working voltage:12V
- Working Current:1.3AH

4.4.3.2 FEATURES

- Used in Electronic consideration Scales.
- Used in Toys Used in Medical equipment
- Used in Electronic check equipment.
- Used in Communication equipment

MICROCONTROLLER 8051

A microcontroller is considered an independent framework with a processor, memory related peripherals and may be utilized as an implanted framework. The main part of microcontrollers being used these days are inserted in elective apparatus, similar to vehicles, phones, machines, and peripherals for PC systems.

4.4.5.1 PIN DIAGRAM




It doesn't have an in-fabricated ADC module and supports just USART correspondence. In spite of the fact that it very well may be interfaced with outside ADC ICs like the ADC084 or the ADC0808

4.4.5.2 APPLICATION

- Several DIY Projects
- Multiple I/O interfaces and interchanges are needed for projects.
- a substitute for the Arduino module

4.4 .6 VOLTAGE REGULATOR

A transformer might be a circuit that makes and keeps a firm yield voltage, paying little mind to changes to the information voltage or burden conditions. Voltage controllers (VRs) keep the voltages from an influence providing at intervals a variety that's viable with the inverse electrical components. though voltage controllers are units most normally utilized for DC/DC power change, some will perform AC/AC or AC/DC power transformation moreover. The yield current of this IC will go up to one.5A. However, the IC experiences critical warmth misfortune along these lines a conductor is generally suggested for comes that burn-through a ton of current. for example, assuming the info voltage is 12V and you're overwhelming 1A, $(12-5) \times 1 = 7W$. These seven Watts will be scattered as warmth. The information electrical condenser zero.33 μ F perhaps an artistic electrical condenser that manages input inductance issues and thusly the yield electrical condenser zero.1 μ F is also an earthenware electrical condenser that adds to the sufficiency of the circuit. These capacitors looked to put close to



the terminals for them to figure adequately. conjointly they should be of earthenware sort, since fired capacitors region unit faster than electrolytic.

Fig.4.6. circuit diagram of 7805

4.4.6.2 APPLICATION


- .In the vast majority of the comes, a constant +5V yield controller is used to power microcontrollers and sensors.
- Adjustable Regulator of Performance.
- For specific uses, there is a current electric circuit.
- Regulated twins give.

4.4.7 RO SYSTEM

Reverse diffusion is a membrane treatment technique that is used to isolate dissolved solutes from water. Reverse diffusion is best known for its application in water purification, especially in the removal of salt and other effluent materials from water molecules. Reverse diffusion, also known as Ro, is a form of filtration process for removing molecules and ions from a specific resolution. As a tissue layer is inserted between the solutions, reverse diffusion is achieved by applying pressure (usually greater than the diffusion pressure) to one part of the solution. The aim of this membrane is to distinguish contaminants.

4.4.7.1 PRINCIPLE OF REVERSE OSMOSIS

Diffusion to put a halt the process because, due to the presence of a membrane, giant molecules of the drug are unable to pass through it and remain in a controlled state. On the other side, a pure solvent may pass through the membrane. Once this occurs, the substance's molecules tend to target one side of the membrane while the opposite side becomes dilute. Furthermore, the number of solutions changes to some degree. As the solvent moves through the membrane against the concentration gradient, reverse diffusion occurs. It mainly shifts from one concentration to the next.



4.4.7.2 PROCESS OF REVERSE OSMOSIS

dispersion pressure is that the base compel expected to forestall dissolvable course through the tissue layer. Accordingly, when the appropriate response viewpoint (the angle any place the substance focus is high) is exposed to a pressing factor greater than the pressing factor., the dissolvable particles on the appropriate response perspective travel through the tissue layer to the area any place the substance fixation is low. Such converse dissolvable development through the tissue layer is named invert dispersion. Notice that the pressing factor applied to the appropriate response perspective ought to be over the pressing factor for the opposite dissemination technique to continue. pressing factor could be a colligative property, that relies upon the convergence of the appropriate response. In water cleansing, the converse dispersion technique is very indispensable. A few water purifiers utilized nowadays utilize switch dissemination inside the decontamination strategy. In show of the means.

4.4.7.3 BENEFITS OF REVERSE OSMOSIS

1. This technique will be wont to successfully remove numerous assortments of broke up and suspended synthetic particles in addition as natural elements (like microorganisms) from the water.
2. This framework consolidates a wide application in treating fluid squanders or release.
3. It is used in purging water to stop illnesses.
4. It helps inside the desalinating water.
5. It is useful inside the clinical field.

4.4.7.4 ADVANTAGES OF REVERSE OSMOSIS

- dissipation The intact membrane rejects bacteria, viruses, and pyrectic materials. In this regard, Ro water is comparable to water in terms of temperature.
- The available units are relatively small and need very little space. They share an interest in conducting qualitative research at home.
- The membrane has a lifespan of around one to two years in average use before it needs to be replaced.
- It's a good idea to sterilise the Ro device with formol or another sterilant on a regular basis.

4.4.8 WATER LEVEL SENSOR


Water level markers work by exploitation gadget tests to point water levels during a tank. In the event that you've at any point had a heated water tank detonate or at any point attempted to make sub characteristic way of thinking, at that point you perceive anyway vital it's to discover once water is near. Water level sensors are acclimated

with discover the degree of medications which will stream. Such substances embrace fluids, slurries, granular material and powders. Such estimations are familiar with affirm the quantity of materials among a shut progression of water in open channels. S(signal) pin is partner degree simple yield which will be associated with at any rate one of the simple contributions on your Arduino. + (VCC) pin gives capacity to the gadget. It's recommended to control the gadget with between three.3V – 5V. If it's not too much trouble, note that the simple yield can fluctuate waging on what voltage is accommodated the gadget. - (GND) might be a ground affiliation. The gadget incorporates a progression of 10 uncovered copper follows, 5 of that are power traces and 5 are sense follows. These follows are lattice like all together that there is one sense follow between every 2 force follows. Typically, these follows are not associated anyway are connected by water once lowered. There's an impact light-discharging diode on the board which can brighten once the board is steam-fueled.

4.4.8.1 WORKING OF WATER LEVEL SENSOR

Gadget the working of the water level gadget is really simple. The arrangement of uncovered equal conductors, along goes about as a resistor (simply kind of a potentiometer) whose obstruction fluctuates in accordance with the water level. The change in opposition relates to the space from the most elevated of the gadget to the outside of the water. The opposition is equally corresponding to the pinnacle of the water: The extra water the gadget is drenched in, winds up in higher conduction and can prompt a lower obstruction. The less water the gadget is submerged in, winds up in helpless conduction and can prompt the following obstruction. The gadget produces partner degree yield voltage in accordance with the obstruction, that by estimation we can affirm the water level.

4.4.8.2 APPLICATION OF WATER LEVEL SENSOR



4.8.1 APPLICATION OF WATER LEVEL SENSOR

- Device is used as a leveler in storage tanks, boiler stop point level of water within
- The water level device is employed in Hotels, Home flats, business advanced, and in factories.

4.4.8.3 ADVANTAGES OF WATER LEVEL SENSOR

- device Compact and stylish style.
- Ensure no overflows or empty running of pump.
- Low cost

4.4.9 LED DISPLAY

LED Driven show might be a level screen gadget during which Partner in Nursing exhibit of light-discharging diodes might be by choice enacted to show mathematical and sequential information, utilized E.S.P. in pocket number crunchers, advanced watches, movement instruments, and in certain microcomputers. Driven (Natural Light-Producing Diode) might be a self light-transmitting innovation made out of a thin, complex natural film set between Partner in Nursing anode and cathode. In differentiation to computerized show innovation, OLED needn't bother with a backdrop illumination. OLED has high application potential for pretty much every sort of presentations and is believed to be the final word innovation for sequential age of level board shows. It is a 0.96 in., White OLED module which might be interfaced with any microcontroller exploitation I2C/IIC convention. it's having a goal of 128x64. Fig.4.9 diode show OLEDs essential design comprises of natural materials situated between the cathode and the anode, that comprises of electrical semiconducting clear metallic component Tin compound (ITO). The natural materials create a complex thin film, which has the power source Moving Layer (HTL), Outflow Layer (EML) and the negatron Moving Layer (ETL). By applying the worthy electrical voltage, openings and electrons square measure infused into the EML from the anode and the cathode, severally.

The openings and electrons blend inside the EML to make excitons, when that electro glow Occurs.



Fig.4.9 LED display

4.4.9.1 FEATURES

- Work dead well while not the necessity of backlight-weight.
- 128*64 high resolution, radical wide viewing angle
- Super low power consumption—only zero.
- 08W once the entire screen lights up and zero.
- 06W once displaying characters Fully compatible with multiple dominant chips as well as Arduino and a lot of. Support a good vary of voltage input.

4.4.9.2 APPLICATION

- TV's
- Digitalcameras
- Smartwatches
- Lighting
- Signage
- Airport runwaylighting
- Computers monitor.
- Medicalequipment

4.4.9.3 ADVANTAGES

- Does not requirebacklight.
- Utilizes less power.
- Very flexible
- Wide viewing angles
- Smallsize
- Lightweight
- High durability

4.4.10 pH SENSOR

In the strategy world, pH scale is a vital boundary to be estimated and controlled. A pH scale movement circle is made from 3 sections, the pH scale indicator, which has a period conductor, a reference conductor. A pH scale action circle is fundamentally an electric battery any place the positive terminal is that the mensuration conduit and hence the negative terminal is that the reference conductor. The mensuration conductor, that is touchy to the cation, develops a possible (voltage) straight forwardly connected with the cation convergence of the appropriate response. The reference

conductor gives a steady potential against that the mensuration conductor might be looked at.



Fig .4.10 pH sensor

4.4.10.1 APPLICATION

The action of pH size of an answer is amazingly important in numerous fields like Science, Horticulture, Food and Nourishment, Backwoods and Ecological Investigations, Seas, medicine and Science and so on

- Sea water Monitoring
- Mud and Soil Analysis
- Standard Lab Measurements
- High pH Solutions
- Natural Water Analysis
- Blood Analysis
- Food Solidness and Preservation

4.4.10 WIFI MODULE

- The ESP8266 could be a moderate Wi-Fi semiconductor gadget, with a full TCP/IP stack and microcontroller ability.
- This little module grants microcontrollers to join to a Wi-Fi organize and make straight forward TCP/IP connections victimization Hayes-style commands.

Notwithstanding, at first there was basically no English-language documentation on the chip and accordingly the orders it acknowledged. The

appallingly low worth and hence the demonstrated truth that there have been a couple of outside parts on the module, that exhorted that it may at last be horribly modest in volume, pulled in a few programmers to investigate the module, the chip, and in this manner the product framework subsequently, yet on decipher the Chinese documentation. The ESP8285 is partner degree ESP8266 with one MiB of protected glimmer, allowing the structure of single-chip. Gadgets equipped for interfacing with Wi-Fi. These microcontroller chips are prevailing by the ESP32 group of gadgets, along with the pin-viable ESP32-C3.

4.4.11.1 FEATURES OF ESP8266

ESP-01 module wireframe

- Processor: L106 32-bit RISC microprocessor core based on the TensilicaXtensa Diamond Standard 106Micro running at 80MHz.
- Memory:
 - 32 KiB instructionRAM
 - 32 KiB instruction cacheRAM
 - 80 KiB user-dataRAM
 - 16 KiB ETS system-dataRAM

4.4.11.2 USE OF ESP8266-01

The ESP8266 could be an appallingly easy to use and low worth gadget to create web property to you comes. The module will work each as an Entrance reason (can deliver area of interest) and as a station (can connect with Wi-Fi), thereupon it will essentially bring information and move it to the web making web of Things as clear as potential. It can even bring information from {the web the web the net} abuse Programming interface's thus your undertaking may get to any data that is reachable inside the web, so making it more intelligent. Another energizing element of this module is that it is regularly customized abuse the Arduino IDE that makes it bounty extra easy to understand. however, this adaptation of the module has exclusively two GPIO pins (you will hack it to utilize something like 4) consequently you must utilize it next to another microcontroller like Arduino, else you will actually want to look onto the extra independent ESP-12 or ESP-32 renditions. Subsequently, in the event that you are attempting to discover a module to incite began with IOT or to create web property to your task then this module is that the correct option for you.

There is square measure such numerous ways and day reachable with Special insight modules, nonetheless, the front most unexceptionally utilized is that the Arduino IDE. In this way, permit us to examine exclusively that extra beneath.

4.4.11.3 APPLICATION

- IOT undertaking
 - Access Point Entryways
 - Wireless Information Logging
 - Smart Home Computerization
 - Learn fundamentals of systems administration
 - Portable hardware
 - Smart bulbs and attachments

4.4.12 BUCK BOOST CONVERTER

The buck boost device may be a DC-to-DC device. The yield voltage of the DC-to-DC gadget is a more modest sum than or bigger than the input voltage. The yield voltage of the extent relies upon the obligation cycle. These converters additionally {are| are} alluded to as the increase and lessening electrical gadgets and these names are getting back from the comparable to strengthen and venture down transformer. The information voltages region unit venture up/down to some degree of over or however the input voltage. By abuse the low change energy, the information power is satisfactory the yield power. The ensuing articulation shows the low of a change.



4.4.12.1 Applications of Buck boost converter

- It is utilized in self-regulating powersupplies.
- It has consumerelectronics.
- It is utilized in the Battery powersystems.
- Adaptive controlapplications.
- Power amplifierapplication.

4.4.12.2 Advantages of Buck Boost Converter

- It gives higher output voltage.
- Low operating ductcycle.
- Low voltage onMOSFETs

CHAPTER 5

CONCLUSION

5.1 Summary

Solar power is increasingly being used for water purification because it is cost-effective and plentiful. It is also being used in places where electricity is not available. In this case, the microcontroller also stops the water from overflowing. Furthermore, Reverse Osmosis can be an effective disinfectant. The project has no ongoing costs and almost none at all. As a result, it would be persuading to be useful in the future.

5.2 APPLICATIONS

- Remote areas & Islets
- Inaccessible **areas**
- Regions Far away from power grid
- Areas with high cost for transporting water.
- Areas with high cost of power
- Coastal areas with water scarcity

GEOTAGGED IMAGE – HARDWARE



REFERENCES

- [1] M. Gowtham, K. Richard Neiel, V. Nagarajan, P. ChristhuDass, andA. Thimothy Integrated Performance Analysis of Latent Heat Storage and Finned Type Solar Distiller IACSIT International Journal of Engineeringand Technology, Vol. 4, No. 5, October2012.
- [2] OzuombaJ.O.1,Edebeatu C.C.1, Opara M.F.2, Udoeye M.C.3 and Okonkwo N.A.1 The Performance of a Solar Water Distillation Kit fabricated from Local materials Research Journal of Chemical Sciences ISSN 2231-606X Vol. 2(3), 64-67, March (2012).
- [3] CarolinaS.E. SardellaEvaluation oftheimplementationofthesolarstillprincipleon runoff water reservoirs in Budunbuto, Somalia. Thematic research MSc. Hydrology January 2012 AM_450129 12 ECTS. solar still Distillation system, drinkingwater,
- [4] Prof. Alpesh Mehta¹, Arjun Vyas², Nitin Bodar³, Dharmesh Lathiya⁴ Design of Solar
- [5] DistillationSystemInternationalJournalofAdvancedScienceandTechnologyVol. 29, April 2011.solar still Distillation system, drinkingwater.
- [6] Aayush Kaushal *, Varun Solar stills: A review Renewable and SustainableEnergy Reviews 14 (2010)446–453.
- [7] K. Sampathkumara, *, T.V. Arjunanb, P. Pitchandia, P. Senthilkumarc. Active solar distillationadetailedreviewRenewableandSustainableEnergyReviews14(2010) 1503–1526.
- [8] John Ward a plastic solar water purifier with high output solar Energy 75 (2003) 433-437.
- [9] OzuombaJ.O.1,Edebeatu C.C.1, Opara M.F.2, Udoeye M.C.3 andOkonkwo N.A.1 The Performance of a Solar Water Distillation Kit fabricated from Local materials Research Journal of Chemical Sciences ISSN 2231-606X Vol. 2(3), 64-67, March (2012).
- [10] CarolinaS.E. SardellaEvaluationoftheimplementationofthesolarstillprincipleon runoff water reservoirs in Budunbuto, Somalia. Thematic research MSc. Hydrology January 2012 AM_450129 12 ECTS. solar still Distillation system, drinkingwater,

- [11] Prof. Alpesh Mehta¹, Arjun Vyas², Nitin Bodar³, Dharmesh Lathiya⁴ Design of Solar
- [12] DistillationSystemInternationalJournalofAdvancedScienceandTechnologyVol. 29, April 2011.solar still Distillation system, drinkingwater.
- [13] Aayush Kaushal *, Varun Solar stills: A review Renewable and SustainableEnergy Reviews 14 (2010)446–453.
- [14] K. Sampathkumara, *, T.V. Arjunanb, P. Pitchandia, P. Senthilkumarc. Active solar distillationa detailed review Renewable and Sustainable Energy Reviews14(2010) 1503–1526.
- [15] John Ward a plastic solar water purifier with high output solar Energy 75 (2003) 433-437.
- [16] L.M. Flendriga, * B. Shah b, N. Subrahmaniam b, V. Ramakrishnan b Low cost thermoformed solar still water purifier for D&E countries Physics and Chemistry of the Earth 34 (2009)50–54.
- [17] Decontaminationanddisinfectionofwaterbysolarphotocatalysis:Recentoverview and trends Catalysis Today 147 (2009)1–59.
- [18] Markus Forstmeier, Wilhelm Feichter, Oliver Mayer Photovoltaic powered water purification - challenges and opportunities Desalination 221 (2008)23–28.
- [19] Ju" rgen R. Oliviera, Thomas M. Harmsa, Danie" I J. Esterhuyseb Technical and economic evaluation of the utilization of solar energy at south Africa's SANAE IV base in Antarctica Renewable Energy 33 (2008)1073–1084.
- [20] MengNi, MichaelK.H.Leung_,DennisY.C.Leung,K.SumathyAreviewandrecent
- [21] developments in photocatalytic water-splitting using TiO₂ for hydrogen production Renewable and Sustainable Energy Reviews 11 (2007)401–425.
- [22] Soteris A. Kalogirou* Seawater desalination using renewable energy sources Progress in Energy and Combustion Science 31 (2005)242–281.
- [23] D.A. Haralambopoulos *, G. Biskos, C. Halvadakis, T.D. Lekkas Dewatering of wastewater sludge through a solar still Renewable Energy 26 (2002)247–256.
- [24] Saleh H. Alawaji * evaluation of solar energy research and its application in Saudi Arabia- 20 years of experience Renewable and sustainable Energy reviews 5 (2001)59-7

