

DESIGN AND FABRICATION OF INNOVATIVE ROBOT FOR MEDICAL APPLICATION WITH UV TREATMENT

Submitted in partial fulfilment of the requirements for the award of
Bachelor of Engineering in Mechanical Engineering

By

EESHWAR R S (37150058)

INFANT YABESH K (37150078)



**DEPARTMENT OF MECHANICAL ENGINEERING
SCHOOL OF MECHANICAL ENGINEERING**

SATHYABAMA

**INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)**

**Accredited with Grade "A" by NAAC | 12B Status by UGC | Approved by AICTE
JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI - 600 119.**

MARCH-2021



SATHYABAMA

**INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)**

**Accredited with “A” grade by NAAC | 12B Status by UGC | Approved by AICTE
JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI – 600 119
www.sathyabama.ac.in**

DEPARTMENT OF MECHANICAL ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of **Eeshwar.R.S (37150058)**, **Infant Yabesh.K (37150078)** who carried out the project entitled **“Design and Fabrication of Innovative Robot for Medical Application with UV Treatment”** under my supervision from to **October 2020** to **March 2021**.

Dr.R.B.Durairaj, M.Tech., Ph.D.,

Internal Guide

Dr. G. Arun Kumar ME., Ph.D

Head of the Department

Submitted for Viva voce Examination held on _____

Internal Examiner

External Examiner

DECLARATION

We, **Eeshwar.R.S (37150058)** and **Infant Yabesh.K (37150078)** hereby declares that the Project Report entitled “**Design and Fabrication of Innovative Robot for Medical Application with UV Treatment**” done by us under the guidance of **Dr.R.B.Durairaj M.Tech., Ph.D.**, is submitted in partial fulfilment of the requirements for the award of Bachelor of Engineering in Mechanical Engineering.

DATE:

1.

PLACE:

2.

SIGNATURE OF THE CANDIDATES

ACKNOWLEDGEMENT

I am pleased to acknowledge my sincere thanks to **Board of Management** of **SATHYABAMA** for their kind encouragement in doing this project and for the successful completion of it. I am grateful to them.

I convey my thanks to **Dr. S. Prakash M.E., Ph.D.**, Dean, School of Mechanical and **Dr. G. Arun Kumar ME., Ph.D.**, Head of the Department, **Department of Mechanical Engineering** for providing me necessary support and details at the right time during the progressive reviews.

I would like to express my sincere and deep sense of gratitude to my Project Guide **Dr.R.B.Durairaj M.Tech., Ph.D.**, **Department of Mechanical Engineering** for his valuable guidance, suggestions and constant encouragement paved way for the successful completion of my project work.

I wish to express my thanks to all Teaching and Non-teaching staff members of the **Department of Mechanical Engineering** who were helpful in many ways for the completion of the project.

ABSTRACT

UV light has been utilized for cleansing and sanitization as ahead of schedule as the mid-twentieth century. With headways in innovation, and explicitly inside the UV bulbs themselves, its solid long-life expectancy (a great many hours) and more modest size (for example UV LED versus conventional UV bulbs) has widened the area for where it is regularly utilized. It is frequently wont to sanitize water, air, organic products, vegetables, careful utensils, tablet PCs, toys and a spread of surfaces. At the point when it includes UV disinfection, not a wide range of UV are compelling.

For UV sanitization, just UVC (100-280nm) has sufficiently high energy to viably murder microorganisms. UV cleansing is a profoundly successful technique for infections and bacteria, Studies have shown that UVC at 254 nm is viable against all food-borne microorganisms, common microbiota, molds, and yeasts. Since microorganisms go with various sizes and shapes that influence their UV ingestion, the predetermined time for killing every species shifts. UV sanitization likewise alluded to as UV sterilization or bright germicidal light (UVGI) works by separating certain substance bonds and scrambling the construction of DNA, RNA and proteins, making a microorganism be not able to duplicate. At the point when a microorganism can't duplicate, it's viewed as dead since it can't imitate inside a number and isn't any more drawn out infectious.

The UV sanitization strategy are frequently adequately used to the specialists' advantage, simply in the event of an individual being tainted by a lethal illness which will spread on contact with the patient, the specialist's prosperity goes under hazard while treating the patient. during this undertaking we build up a robot with an UV light, the robot is constrained by the client from a versatile application. Utilizing the versatile application, the development of the robot is frequently seen through live observing. The portable application is created to act in light of the fact that the far-off regulator of the robot, the robot is guided by the orders from the versatile application on the course towards which the robot must move and furthermore where to utilize the UV radiation to treat the surface. By this strategy the specialist can treat the patient without coming in direct contact to the patient.

TABLE OF CONTENTS

CHAPTER NO.	TITLE	PAGE NO.
	ABSTRACT	[i]
	LIST OF FIGURES	[vii]
	LIST OF ABBREVIATIONS	[viii]
1.	INTRODUCTION	1
	1.1 GENERAL	1
	1.2 TECHNOLOGY USED	2
	1.2.1 ROBOTICS	2
	1.2.2 OPENCV	3
	1.2.3 EMBEDDED SYSTEMS	6
	1.2.4 MQTT	7
	1.2.5 REACT NATIVE APP DEVELOPMENT	10
	1.3 OBJECTIVE	11
2.	LITERATURE SURVEY	12
	2.1 INTRODUCTION	12
	2.2 LITERATURE SURVEY	12
	2.2.1 HAIBING WU, BO TAO, MEMBER, IEEE, ZEYU GONG, MEMBER, IEEE, ZHOUPING YIN, MEMBER, IEEE, AND HAN DING, SENIOR MEMBER, IEEE," A STANDALONE RFID-BASED MOBILE ROBOT NAVIGATION METHOD USING SINGLE PASSIVE TAG"	12

2.2.2 ASIF KHAN, BERNHARD RINNER, SENIOR MEMBER, IEEE, AND ANDREA CAVALLARO," COOPERATIVE ROBOTS TO OBSERVE MOVING TARGETS: REVIEW"	13
2.2.3 SHUAI LI, RUOFAN KONG, AND YI GUO, SENIOR MEMBER, IEEE," COOPERATIVE DISTRIBUTED SOURCE SEEKING BY MULTIPLE ROBOTS: ALGORITHMS AND EXPERIMENTS"	14
2.2.4 OLZHAS ADIYATOV, STUDENT MEMBER, IEEE, BEXULTAN RAKHIM, ALTAY ZHAKATAYEV, MEMBER, IEEE, AND HUSEYIN ATAKAN VAROL, SENIOR MEMBER, IEEE," SENSOR REDUCTION OF VARIABLE STIFFNESS ACTUATED ROBOTS USING MOVING HORIZON ESTIMATION"	15
2.2.5 J. GARCÍA, A. BOHÓRQUEZ, AND A. VALERO," SUSPENSION EFFECT IN TIP-OVER STABILITY AND STEERABILITY OF ROBOTS MOVING ON SLOPING TERRAINS"	16
2.2.6 MILAN LUKIC, AHMED BARNAWI, MEMBER, IEEE, AND IVAN STOJMENOVIC, FELLOW, IEEE," ROBOT COORDINATION FOR ENERGY-BALANCED MATCHING AND SEQUENCE DISPATCH OF ROBOTS TO EVENTS"	16
2.2.7 JING LI; QIANG HUANG; ZHANGGUO YU; XUECHAO CHEN; WEIMIN ZHANG; HUAXIN LIU; JUNYAO GAO; YINGXIAN DUO," INTEGRAL ACCELERATION GENERATION FOR SLIP AVOIDANCE IN A PLANAR HUMANOID ROBOT"	17

2.2.8 GUILLAUME DOISY; JOACHIM MEYER; Yael EDAN," THE IMPACT OF HUMAN-ROBOT INTERFACE DESIGN ON THE USE OF A LEARNING ROBOT SYSTEM "	18
2.2.9 FENG GU; YUQING HE; JIANDA HAN," ACTIVE PERSISTENT LOCALIZATION OF A THREE-DIMENSIONAL MOVING TARGET UNDER SET-MEMBERSHIP UNCERTAINTY DESCRIPTION THROUGH COOPERATION OF MULTIPLE MOBILE ROBOTS"	19
2.2.10 C. SERKAN KARAGÖZ; H. IŞIL BOZMA; DANIEL E. KODITSCHKEK," COORDINATED NAVIGATION OF MULTIPLE INDEPENDENT DISK-SHAPED ROBOTS"	20
2.2.11 GUANGLONG DU; MINGXUAN CHEN; CAIBING LIU; BO ZHANG; PING ZHANG," ONLINE ROBOT TEACHING WITH NATURAL HUMAN-ROBOT INTERACTION"	21
2.2.12 P.H.L. SILVA; A.M.F. BURLAMAQUI," SYSTEM FOR CREATION, PROGRAMMING AND AVAILABILITY OF DISTRIBUTED ROBOT TEAMS USING COLLECTIVE KNOWLEDGE"	22
2.2.13 F.A.G. BECERRA; A. B. ORTEGA; C. D. G. BELTRÁN; C. G. VALDIVIA; R.O.D. ARCEGA," DESIGN AND CONTROL OF A NEW PARALLEL ROBOT FOR THE REHABILITATION OF THE HIP-KNEE"	23
2.2.14 TAKAYUKI KANDA, MEMBER, IEEE, DYLAN F. GLAS, MASAHIRO SHIOMI, AND NORIHIRO HAGITA, SENIOR MEMBER, IEEE," ABSTRACTING PEOPLE'S TRAJECTORIES FOR SOCIAL ROBOTS TO PROACTIVELY APPROACH CUSTOMERS"	23

2.2.15	MATTHEW FIELD; DAVID STIRLING; ZENGXI PAN; FAZEL NAGHDY," LEARNING TRAJECTORIES FOR ROBOT PROGRAMING BY DEMONSTRATION USING A COORDINATED MIXTURE OF FACTOR ANALYZERS"	24
	2.3 DISADVANTAGES IN EXISTING SYSTEM	25
3.	SYSTEM ANALYSIS	26
	3.1 EXISTING SYSTEM	26
	3.2 DISADVANTAGE OF EXISTING SYSTEM	26
	3.3 PROPOSED SYSTEM	27
	3.4 ADVANTAGE OF PROPOSED SYSTEM	28
	3.5 APPLICATIONS	28
4.	SYSTEM DESIGN	29
	4.1 SYSTEM ARCHITECTURE	29
	4.2 WORKING	29
	4.3 MODULE DESCRIPTION	30
	4.3.1 BATTERY SUPPLY MODULE	30
	4.3.2 MOTOR DRIVER MODULE	31
	4.3.3 RELAY MODULE	32
	4.3.4 SERVO MOTOR MODULE	33
	4.3.5 AVR MICROCONTROLLER DEVELOPMENT	34
	4.3.6 GATEWAY MODULE	35
	4.3.7 MOBILE APPLICATION DEVELOPMENT	37
5.	SOFTWARE DESCRIPTION	39
	5.1. VISUAL STUDIO	39

	5.2. ANDROID STUDIO	40
	5.3. EMBEDDED C	41
6.	RESULTS AND DISCUSSION	44
	6.1 FINAL RESULTS OBTAINED	44
7.	CONCLUSION AND FUTURE WORK	47
	7.1 CONCLUSION	47
	7.2 FUTURE WORK	47
	REFERENCES	48

LIST OF FIGURES

FIGURE NO.	NAME OF THE FIGURE	PAGE NO.
1.1	OpenCV software architecture	5
1.2	Structure of embedded systems	7
1.3	MQTT architecture diagram	9
4.1	System Architecture	29
4.2	Power supply	31
4.3	Motor driver	32
4.4	Relay	33
4.5	Servo motor	34
4.6	Architecture of AVR	35
4.7	Circuit diagram of ESP8266	36
4.8	Mobile App Development	38
6.1	Top view of the robotic setup	44
6.2	Side view of the robotic setup	44
6.3	Login page of the mobile application	45
6.4	Home page of the mobile application	46
6.5	Complete robotic setup of the UV robot	46

LIST OF ABBREVIATIONS

- | | | |
|----|--------|---|
| 1. | CNN | Convolutional Neural Network |
| 2. | DDPG | Deep Deterministic Policy Gradient |
| 3. | ILSVRC | ImageNet Large Scale Visual Recognition Challenge |
| 4. | ReLU | Rectified Linear Unit |
| 5. | RNNS | Recurrent Neural Network |
| 6. | SARSA | State-Action-Reward-State-Action |

CHAPTER - 1

INTRODUCTION

1.1 GENERAL

India's medical care situation is by all accounts at the intersection, where there are some certain accomplishments on the wellbeing pointer however endures some genuine inadequacies in care conveyance. The nation has been effective in annihilating polio, lessening scourges brought about by tropical infections, and controlled HIV generally. In any case, it actually faces an immense monetary weight because of NCDs, battles to adjust availability, reasonableness, and quality, and can't climb general wellbeing financial plans.

To fortify medical services conveyance and improve business possibilities, policymakers, medical services suppliers, business pioneers, innovation suppliers, and pharma organizations should devise systems that change a flash into a manageable fire. Here are experiences from medical care pioneers that can lead India towards a solid tomorrow.

Alongside the financial development over the most recent couple of many years, there has likewise been a flood of sicknesses influencing the wellbeing of the Indian populace. Albeit the level of individuals living in destitution has decreased, there has been an ascent in transmittable and non-transferable infections or way of life sicknesses (which represented 60% of passing in 2015 from 40% in 2003). Alongside different ventures, medical services in India have additionally developed complex with respect to both business and income. As per research by Deloitte, medical care will be a \$280 billion industry by 2020. In spite of this development, there are a few difficulties that the clinical area needs to defeat to serve its gigantic patient populace.

As indicated by measurements from 2014, India spends just about 4% of its GDP on medical care while the US assigns around multiple times more. Because of this, 60% of the clinical costs of Indians were met through close to home reserve funds contrasted with just 13% in the US. The proportion of the specialists, emergency clinic beds, medical attendants to the number of patients is disturbing. There is one bed for every 2000 patients, one specialist for more than 10000

individuals in an administration medical clinic. There is one state-run clinic for every 90000 individuals.

These numbers are baffling when contrasted with those of companion nations. India likewise has a lower number of expert specialists, particularly in country regions and local area wellbeing focuses according to insights.

1.2 TECHNOLOGY USED

1.2.1 ROBOTICS

Robotics is an interdisciplinary assessment domain at the interface of programming and planning. Progressed mechanics incorporates the arrangement, advancement, movement, and use of robots. The goal of cutting-edge mechanics is to design wise machines that can help and help individuals in their regular daily existences and gatekeeper everyone. Progressed mechanics draws on the achievement of information planning, PC planning, mechanical planning, electronic planning, and others.

Mechanical innovation makes machines that can fill in for individuals and emulate human exercises. Robots can be used when in doubt and for certain reasons, be that as it may, today many are used in dangerous conditions (checking audit of radioactive materials, bomb revelation, and deactivation), manufacturing measures, or where individuals can't suffer (for instance in space, lowered, in high warmth, and clean up and control of unsafe materials and radiation). Robots can take on any design anyway some have appeared. This is said to help in the affirmation of a robot in certain replicative practices when in doubt performed by people. Such robots try to emulate walking, lifting, talk, perception, or some other human activity. An enormous number of the current robots are impelled normally, adding to the field of bio-breathed life into mechanical innovation.

Making robots that can work self-rulingly follows right back to old-style times, yet an examination concerning the convenience and potential jobs of robots didn't grow liberally until the 20th century. Since the start, it has been routinely acknowledged by various scientists, trailblazers, draftsmen, and experts that

robots can one day reflect human direct and supervise tasks in a human-like plan. Today, mechanical innovation is a rapidly creating field, as inventive advances continue; investigating, arranging, and building new robots fill diverse sensible necessities, whether or not locally, monetarily, or militarily. Various robots are attempted to oversee obligations that are risky to people, such as defusing bombs, finding survivors in shaky obliterated, and examining mines and wrecks. Progressed mechanics is moreover used in STEM (science, development, engineering, and mathematics) as a training help.

1.2.2 OPEN CV

OpenCV was begun at Intel in 1999 by Gary Bradsky and the central delivery turned out in 2000. Vadim Pisarevsky joined Gary Bradsky to deal with Intel's Russian programming OpenCV gathering. In 2005, OpenCV was utilized on Stanley, the vehicle who won 2005 DARPA Grand Challenge. Later its dynamic progress proceeded under the help of Willow Garage, with Gary Bradsky and Vadim Pisarevsky driving the endeavour. At the present time, OpenCV underpins a great deal of calculations identified with Computer Vision and Machine Learning and it is growing step by step.

As of now OpenCV upholds a wide assortment of programming tongues like C++, Python, Java, and so on and is accessible on various stages including Windows, Linux, OS X, Android, iOS, and so forth. Additionally, interfaces subject to CUDA and OpenCL are also under incredible progress for quick GPU works out.

OpenCV-Python is the Python API of OpenCV. It joins the best ascribes of OpenCV C++ API and Python language.

OpenCV is the essential open-source library for PC vision, picture managing and AI, and now joins GPU speed increase for n"art-8">It has C++, C, Python and Java interfaces and supports Windows, Linux, Mac OS, iOS and Android. OpenCV was normal for computational sufficiency and with a solid spotlight on consistent applications. Written in improved C/C++, the library can manhandle multi-centre preparing. Gotten all round the world, OpenCV has very 47 thousand individuals of

client area reviewed number of downloads beating 6 million. Use goes from natural craftsmanship, to mines assessment, sewing maps on the web or through bleeding edge advanced mechanics.

Open CV-Python

Python is an all around helpful programming language started by Guido van Rossum, which ended up being particularly celebrated in a nutshell time span generally because of its straightforwardness and code rationality. It enables the programmer to convey his considerations in less lines of code without reducing any understandability.

Stood out from various lingos like C/C++, Python is all the more lethargic. However, another critical component of Python is that it might be helpfully loosened up with C/C++. This segment urges us to create computationally gathered codes in C/C++ and make a Python covering for it so we can use these covers as Python modules. This gives us two advantages: first, our code is just comparably speedy as exceptional C/C++ code (since it is the certified C++ code working in establishment) and second, it isn't hard to code in Python. This is the way OpenCV-Python works, it is a Python covering around one of a kind C++ execution.

Additionally, the assistance of Numpy makes the task more less complex. Numpy is a significantly redesigned library for numerical undertakings. It gives a MATLAB-style accentuation. All the OpenCV bunch structures are changed over to and-from Numpy displays. So whatever exercises you can do in Numpy, you can solidify it with OpenCV, which constructs number of weapons in your arms reserve. Other than that, couple of various libraries like SciPy, Matplotlib which supports Numpy can be used with this.

So OpenCV-Python is a fitting gadget for brisk prototyping of PC vision issues.




Fig: 1.1 OpenCV software architecture

Open CV Applications

OpenCV is being used for a very wide range of applications which include:

- Street view image stitching
- Automated inspection and surveillance
- Robot and driver-less car navigation and control
- Medical image analysis
- Video/image search and retrieval
- Movies - 3D structure from motion
- Interactive art installations

Open CV Functionality

- Image/video I/O, processing, display (*core, imgproc, highgui*)
- Object/feature detection (*objdetect, features2d, nonfree*)
- Geometry-based monocular or stereo computer vision (*calib3d, stitching, video stab*)
- Computational photography (*photo, video, superres*)
- Machine learning & clustering (*ml, flann*)
- CUDA acceleration (*gpu*).

1.2.3 EMBEDDED SYSTEMS

An embedded system is a chip-based PC gear structure with programming that is proposed to play out a submitted limit, either as a self-sufficient system or as a piece of a huge structure. At the middle is a planned circuit expected to finish figuring for progressing undertakings.

Complexities range from a single microcontroller to a set-up of processors with related peripherals and associations; from no UI to complex graphical UIs. The unpredictability of an embedded structure varies in a general sense depending upon the task for which it is arranged.

Introduced systems are directed by microcontrollers or progressed sign processors (DSP), application-unequivocal joined circuits (ASIC), field-programmable doorway bunches (FPGA), GPU development, and entryway shows.

These getting ready systems are consolidated with parts dedicated to dealing with electric just as mechanical interfacing.

Introduced systems programming rules, insinuated as firmware, are taken care of in read-just memory or gleam memory chips, running with confined PC gear resources. Embedded systems interface with the remainder of the world through peripherals, associating data, and yield devices.

STRUCTURE OF EMBEDDED SYSTEMS

The essential design of an installed framework incorporates the accompanying segments:

Sensor: The sensor measures and converts the actual amount to an electrical sign, which would then be able to be perused by an installed frameworks engineer or any electronic instrument. A sensor stores the deliberate amount to the memory.

A-D Converter: A simple to-computerized converter changes over the simple sign sent by the sensor into an advanced sign.

Processor and ASICs: Processors evaluate the information to quantify the yield and store it in memory.

D-A Converter: An advanced to-simple converter changes the computerized information took care of by the processor to simple information

Actuator: An actuator looks at the yield given by the D-A Converter to the genuine yield put away and stores the endorsed yield.




Fig: 1.2 Structure of embedded systems

1.2.4 MQTT

MQTT (MQ Telemetry Transport or Message Queuing Telemetry Transport) is an open OASIS and ISO standard lightweight, distribute buy in network convention that transports messages between gadgets. The convention for the most part runs over TCP/IP; in any case, any organization convention that gives requested, lossless, bi-directional associations can uphold MQTT. It is intended for associations with far off areas where a "little code impression" is required or the organization transmission capacity is restricted.

The MQTT convention characterizes two sorts of organization elements: a message specialist and various customers. A MQTT merchant is a worker that gets all messages from the customers and afterward courses the messages to the proper objective customers. A MQTT customer is any gadget (from a miniature regulator up to an undeniable worker) that runs a MQTT library and associates with a MQTT dealer over an organization.

Data is coordinated in a progression of themes. At the point when a distributor has another thing of information to disperse, it sends a control message with the information to the associated merchant. The merchant at that point conveys the data to any customers that have bought in to that theme. The distributor doesn't have to have any information on the number or areas of supporters, and endorsers, thusly, don't need to be arranged with any information about the distributors.

In the event that a merchant gets a message on a point for which there are no current supporters, the dealer disposes of the message except if the distributor of the message assigned the message as a held message. A held message is a typical MQTT message with the held banner set to valid. The dealer stores the last held message and the comparing QoS for the chose point. Every customer that buys in to a theme design that coordinates with the subject of the held message gets the held message following they buy in. The dealer stores just one held message for every point. This permits new supporters of a subject to get the most current worth instead of sitting tight for the following update from a distributor.




Fig: 1.3 MQTT architecture diagram

At the point when a distributing customer initially interfaces with the specialist, it can set up a default message to be shipped off endorsers if the dealer identifies that the distributing customer has surprisingly separated from the merchant. Customers just collaborate with a representative; however, a framework may contain a few specialist workers that trade information dependent on their present supporters' themes. A negligible MQTT control message can be just two bytes of information.

A control message can convey almost 256 megabytes of information if necessary. There are fourteen characterized message types used to associate and disengage a customer from a merchant, to distribute information, to recognize receipt of information, and to administer the association among customer and worker. MQTT depends on the TCP convention for information transmission.

A variation, MQTT-SN, is utilized over different vehicles like UDP or Bluetooth. MQTT sends association certifications in plain content configuration and does exclude any actions for security or confirmation. This can be given by utilizing TLS to scramble and ensure the moved data against block attempt, change or phony. The default decoded MQTT port is 1883. The encoded port is 8883.

1.2.5 REACT NATIVE APP DEVELOPMENT

Cross-stage progression has gotten a phenomenal alternative rather than totally neighbourhood adaptable application improvement. Following the nearby flexible improvement approach, you make separate applications for Android and iOS. The cross-stage improvement grants you to reduce expenses and save time by using comparable code across the two phases. The React Native design is a rising flexible course of action and is seen as the destiny of cross-stage versatile application improvement.

React Native is an open-source structure that grants to collect a flexible application with just JavaScript. It was introduced by Jordan Walke, a Facebook software engineer, as another advancement for less troublesome unforeseen development and a prevalent customer experience. The essential undeniable of this framework is that React Native applications work really like neighbourhood applications. They don't fluctuate from applications dependent on Java, Objective-C or Swift and they use a comparable UI building blocks as nearby iOS or Android applications. However, with React Native, manufacturing a compact application is much speedier and more reasonable.

Reusable code and pre-created portions

This is likely the primary advantage of React Native. With the solace of this framework, engineers don't need to manufacture an alternate adaptable application for each stage, as practically 90% of React Native code can be reused among iOS and Android. React Native is about the adaptable UI. Standing out this framework from AngularJS or meteor JS, it looks more like a JavaScript library than a construction.

It's crucial for make a progression of exercises while creating a versatile application, and React Native makes an executing demand just magnificent.

Besides, UIs arranged in React Native are more responsive, decrease load time, and give a smoother feel.

The React Native framework is at this point advancing, so it might don't have a couple of portions in the middle construction. To fill this opening, React Native gives two sorts of outcast modules: nearby modules and JavaScript modules.

1.3 OBJECTIVE

- The objective of the project is to design a robot that can save the doctor from coming in contact with a patient by treating him/her with UV lighting.
- To develop a mobile application that can lively monitor and control the movement of the robot.

CHAPTER - 2

LITERATURE REVIEW

2.1 INTRODUCTION

The following shows survey on robots. The most popular of the existing techniques used for building of robots.

2.2 LITERATURE SURVEY

2.2.1 Haibing Wu, Bo Tao, Member, IEEE, Zeyu Gong, Member, IEEE, Zhouping Yin, Member, IEEE, and Han Ding, Senior Member, IEEE," A Standalone RFID-Based Mobile Robot Navigation Method Using Single Passive Tag" [24 Jul 2020] [Pages 1-9].

This article proposes an independent radio recurrence ID (RFID)- based versatile robot route technique, in which a portable robot outfitted with per user reception apparatuses can be consistently guided to a static item set apart with a solitary aloof UHF RFID tag. A perception model dependent on the RFID stage distinction is fabricated and incorporated into a molecule channel, by which the prompt relative situation between the portable robot and the labelled article can be distinguished progressively. In light of the position data extricated from the RFID framework, the versatile robot changes its posture to push toward the RFID-labelled article. Contrasted and the current RFID-based versatile robot route strategies, the proposed technique requires no outer sensors other than the RFID and requires just a solitary detached tag. Trials utilizing business off-the-rack (COTS) RFID gadgets are performed, and the outcomes show that the portable robot can acceptably acknowledge route tasks with a distance precision of 4.04 cm and an orientation exactness of 2.23°. The proposed strategy is well pertinent for the route scenes in which the outright situation of the labelled objective article isn't known beforehand.

Pros:

The method requires no external sensors other than the RFID and requires only a single passive tag.

Cons:

The system is not applicable for medical purposes, it cannot be used to treat patients.

2.2.2 Asif Khan, Bernhard Rinner, Senior Member, IEEE, and Andrea Cavallaro," Cooperative Robots to Observe Moving Targets: Review"

The sending of numerous robots for accomplishing a shared objective assists with improving the presentation, effectiveness, as well as strength in an assortment of undertakings. Specifically, the perception of moving targets is a significant multi-robot application that actually displays various open difficulties, including the viable coordination of the robots. This paper surveys control methods for agreeable portable robots checking various targets.

The synchronous development of robots and targets makes this issue especially intriguing, and our audit methodically addresses this helpful multi robot issue interestingly. We characterize and fundamentally talk about the control methods: agreeable multi robot perception of numerous moving targets, helpful hunt, procurement, and track, agreeable following, and multi robot pursuit avoidance. We likewise recognize the five significant components that describe this issue, to be specific, the coordination strategy, the climate, the objective, the robot and its sensor(s).

These components are utilized to efficiently break down the control procedures. Most of the examined work depends on reproduction and research facility contemplates, which may not precisely reflect genuine operational conditions. Significantly, while our methodical investigation is centred around multitarget perception, our proposed order is valuable additionally for related multirobot applications.

Pros:

The system is useful also for related multi-robot applications.

Cons:

The system does not provide an option for remote controlled movement.

2.2.3 Shuai Li, Ruofan Kong, and Yi Guo, Senior Member, IEEE, "Cooperative Distributed Source Seeking by Multiple Robots: Algorithms and Experiments"

We consider the issue of source looking for utilizing a gathering of portable robots furnished with sensors for source focus estimation. In the plan, the robot group agreeably appraises the slope of the source field, moves to the source by following the angle rising heading, and keeps a predefined development in development. We present two control calculations with all-to-all and restricted interchanges, individually. For instance, of all-to-all correspondence, thorough insightful investigation demonstrates that the arrangement focal point of the robots unites to the source within the sight of assessment blunders with a limited mistake, the upper bound of which is unequivocally given. On account of restricted correspondence where concentrated amounts are not accessible, circulated agreement channels are utilized to distributively appraise the unified amounts, and afterward installed in the appropriated control laws. Mathematical re-enactments are given to approve the viability of the proposed approaches. Test results on the E-puck robot stage exhibit agreeable exhibitions in a light source looking for an application.

Pros:

Results on the E-puck robot platform demonstrate satisfactory performances in a light source seeking application.

Cons:

The system involves multiple robots, hence is not applicable.

2.2.4 Olzhas Adiyatov, Student Member, IEEE, Bexultan Rakhim, Altay Zhakatayev, Member, IEEE, and Huseyin Atakan Varol, Senior Member, IEEE,” Sensor Reduction of Variable Stiffness Actuated Robots Using Moving Horizon Estimation”

Variable solidness incited (VSA) robots are required to assume a significant part in actual human–robot association, because of their characteristic wellbeing highlights. These frameworks can control the position and firmness simultaneously by consolidating at least two actuators for each joint. Sadly, the requirement for additional sensors to gauge the condition of these actuators diminishes the unwavering quality of these frameworks. In this paper, we present a sensor decrease plot for VSA robots. In particular, we use moving skyline assessment (MHE) to gauge the unmeasured conditions of the framework. Because of its capacity to deal with requirements, MHE is picked as the assessment calculation. The assessed states are then utilized by a nonlinear model prescient regulator to execute a shut circle control framework. To show the adequacy of our structure, we led broad recreation and real-world explores different avenues regarding a response wheel enlarged VSA framework. The target of these examinations was to think about the control execution of the sensor diminished framework (from four encoders to two encoders) with the framework utilizing the full arrangement of states for control. The consequences of these trials show the practicality of the MHE-based sensor decrease. Sensor decrease may build the unwavering quality of VSA robots and might encourage their prior prologue to the modern conditions.

Pros:

Produces very good accuracy compared to other state-of-the-art methods

Cons:

It inflexible for movement, hence is not feasible for large scale usage.

2.2.5 J. García, A. Bohórquez, and A. Valero,” *Suspension Effect in Tip-Over Stability and Steerability of Robots Moving on Sloping Terrains*”

This article depicts a model for a pallet steer robot that evaluates the response powers between the haggles ground, which incorporates the impact of the latent suspension when the robot proceeds onward level and slanted landscapes. Notwithstanding the inward boundaries of the suspension, this model included outer boundaries identified with different segments of the robot and the robot landscape relationship.

With this model, which was approved through re-enactment, it was considered the impact that suspension produces in tip-over soundness and steerability of the robot when it proceeds onward unique landscape tendencies, explicitly when the boundaries of suspension framework and wheel-ground contact are changed.

Pros:

The results are very satisfying, making it applicable for real time applications.

Cons:

The robot cannot be directed to move in the desired direction making it not feasible.

2.2.6 Milan Lukic, Ahmed Barnawi, Member, IEEE, and Ivan Stojmenovic, Fellow, IEEE,” *Robot Coordination for Energy-Balanced Matching and Sequence Dispatch of Robots to Events*”

Given a bunch of occasions and a bunch of robots, the dispatch issue is to dispense one robot for every occasion to visit it. In a solitary round, every robot might be permitted to visit just a single occasion (coordinating with dispatch), or a few occasions in an arrangement (grouping dispatch). In an appropriated setting, every occasion is found by a sensor and answered to a robot. Here, we present novel calculations pointed toward defeating the inadequacies of a few existing arrangements. We propose pairwise distance-based coordinating with calculation

(PDM) to kill long edges by pairwise trades between coordinating with sets. Our arrangement dispatch calculation (SQD) iteratively tracks down the nearest occasion robot pair, remembers the occasion for dispatch timetable of the chose robot and updates its position likewise. At the point when occasion robot distances are increased by robot obstruction (opposite of the leftover energy), the relating energy-adjusted variations are acquired. We additionally present speculations which handle numerous visits and timing imperatives. Our restricted calculation MAD depends on data network foundation and neighbourhood barter inside the robot network for acquiring the ideal dispatch plan for every robot. The re-enactments directed affirm the upsides of our calculations over other existing arrangements as far as normal robot-occasion distance and lifetime.

Pros:

The simulations conducted confirm the advantages of our algorithms over other existing solutions in terms of average robot-event distance and lifetime.

Cons:

The system cannot be used for the betterment of general applications.

2.2.7 Jing Li; Qiang Huang; Zhangguo Yu; Xuechao Chen; Weimin Zhang; Huaxin Liu; Junyao Gao; Yingxian Duo," Integral Acceleration Generation for Slip Avoidance in a Planar Humanoid Robot"

Slip event puts the people as well as the humanoid robots into perilous circumstances. Albeit the discovery and the assessment of slip have been well-informed, concentrates on slip shirking control in a humanoid robot are uncommon. Past strategies used to limit the even movement or direct the vertical movement of the humanoid robot didn't consider the significant rotational movement.

This investigation proposes a necessary speed increase age strategy for slip shirking that meets the ongoing prerequisites, utilizing the sagittal plane for instance. The proposed technique utilizes every one of the movements identified

with the slip in the sagittal plane to forestall the slip, including the translational and the rotational movements. The re-enactments and investigations on the actual humanoid robot exhibit the viability of the introduced strategy.

Pros:

The proposed method makes full use of all the motions related to the slip in the sagittal plane to prevent the slip, including the translational and the rotational motions.

Cons:

Although the detection and the estimation of slip have been well researched, studies on slip avoidance control in a humanoid robot are rare.

2.2.8 Guillaume Doisy; Joachim Meyer; Yael Edan," The Impact of Human–Robot Interface Design on the Use of a Learning Robot System "

There is restricted information on the best way to plan successful interfaces to empower non-expert clients to collaborate with robot learning calculations. This paper centres around an interface configuration challenge: How to give the client adequate data about the learned conduct. A recreated automated assignment where the robot has web-based learning abilities was created.

This stage was utilized to contemplate the effect of the changeability of the ecological conditions, the data gave on the connection between the learned robot conduct and the conditions in the climate, and the presence of a see of the learned robot conduct on the utilization of the framework and on task execution. The outcomes show huge impacts of the kind and the amount of showed data. 42 members utilized brief and contextualized warnings about changes in the climate: their quality improved the general exhibition and the utilization of the mechanization and diminished the responsibility. Conversely, adding reviews of the learned conduct shockingly weakened execution and decreased the utilization of computerization.

Pros:

In contrast, adding previews of the learned behaviour surprisingly impaired performance and reduced the use of automation.

Cons:

The results are not accurate enough, making it not practical for real time applications.

2.2.9 Feng Gu; Yuqing He; Jianda Han," Active Persistent Localization of a Three-Dimensional Moving Target Under Set-Membership Uncertainty Description Through Cooperation of Multiple Mobile Robots"

The relentless confinement of moving targets is perhaps the main utilizations of portable robot frameworks. Be that as it may, the sensors on every individual robot are frequently not adequately precise for this errand, introducing an extreme restriction on the utilization of robots to numerous circumstances. To conquer this issue, frameworks of different robots have been set up. These frameworks improve the limitation exactness of portable focuses by intertwining numerous detecting information. Various examinations have exhibited that the relative movement (or explicitly, the relative posture) between the robot and the objective, just as that among various robots, emphatically impacts the last restriction exactness of the information combination calculation. All in all, the guideline of movement in a numerous robot framework will prompt better confinement results. Hence, in this paper, another dynamic constant confinement (APL) plot is proposed. The hidden idea of this plan depends on set-enrollment depictions of vulnerabilities. The essential issue is defined in the system of an upgraded set-enrollment channel, and another information combination calculation with improved exactness and intermingling properties is planned. A movement arranging calculation is then joined under the purported ideal limitation condition to finish the APL conspire. Recreations utilizing numerous 3-D versatile robot frameworks and analyses on a different rotor-flying-robots proving ground show that the proposed calculation effectively upgrades the precision of the tireless limitation of the moving objective.

Pros:

Experiments on a multiple rotor-flying-robots test bed show that the proposed algorithm successfully enhances the accuracy of the persistent localization of the moving target.

Cons:

The sensors on each individual robot are often not sufficiently accurate for this task.

2.2.10 C. Serkan Karagöz; H. Isil Bozma; Daniel E. Koditschek," Coordinated Navigation of Multiple Independent Disk-Shaped Robots"

This paper tends to the planned route of numerous freely incited plate molded robots-all positioned inside a similar circle formed workspace. Expecting wonderful detecting, shared-brought together correspondences and calculation, just as amazing incitation, we encode total data about the objective, snags, and workspace limit utilizing a counterfeit likely capacity over the setup space of the robots' synchronous nonoverlapping positions.

The shut circle elements administering the movement of every (speed controlled) robot appear as the proper projection of the angle of this capacity. We force (moderate) limitations on the suitable objective places that yield adequate conditions for combination: We demonstrate that this development is a fundamental route work that ensures impact-free movement of every robot to its objective from practically all underlying free arrangements.

The after effects of a broad re-enactment study examine useful issues, for example, normal coming about direction length and heartiness against recreated sensor commotion

Pros:

The results of an extensive simulation study investigate practical issues such as average resulting trajectory length and robustness against simulated sensor noise.

Cons:

The results are not up to the realistic expectations.

***2.2.11 Guanglong Du; Mingxuan Chen; Caibing Liu; Bo Zhang; Ping Zhang,”
Online Robot Teaching With Natural Human–Robot Interaction”***

With the improvement of Industry 4.0, robots will in general be smart and cooperative. For one, robots can associate normally with people. For another, robots can work cooperatively with people in a typical territory. The customary instructing strategy is not, at this point reasonable for the creation mode with human-robot joint effort. Since the conventional encouraging cycles are confounded, they need profoundly talented staffs. This paper centres around the normal method of web-based instructing, which can be applied to the errands like welding, painting, and stepping. This paper gives an internet showing strategy the combination of discourse and motion. A profundity camera (Kinect) and an inertial estimation unit are utilized to catch the discourse and offer of the human. Interval Kalman filter and improved molecule channel are utilized to assess the signal. To incorporate discourse and motion data all the more profoundly, a novel strategy for general media combination dependent on text is proposed, which can remove the most helpful data from the discourse and motions by changing them into text. At last, a greatest entropy calculation is utilized to manage the combination text into the comparing robot guidelines. The common sense and viability of the proposed approach were approved by five subjects without robot educating abilities. The outcomes demonstrate that the online robot instructing situation can effectively show robot controllers.

Pros:

The results indicate that the online robot teaching system can successfully teach robot manipulators.

Cons:

The traditional teaching method is no longer suitable for the production mode with human-robot collaboration.

2.2.12 P.H.L. Silva; A.M.F. Burlamaqui,” System for Creation, Programming and Availability of Distributed Robot Teams using Collective Knowledge”

This paper tends to the issue of programming, control and accessibility of disseminated robots' groups. Frameworks dependent on robots cooperating cooperatively has been the subject of much exploration as of late. Since the quick spread of advances in cell phones and Internet, just as the advantages that mechanical technology adds to the different ordinary applications, the pattern is that increasingly more it is available in different exercises of individuals. For conveyed robots frameworks there is a dormant requirement for examination to empower the utilization of such frameworks by end clients with no or basically no involvement in programming or advanced mechanics. Accordingly, this paper proposes a framework engineering that permits the creation and programming of robots' groups, permitting and clients to oversee them as a solitary framework and basic way utilizing aggregate information obtained the two developers as of the and clients. The tests are performed by an application that was created under the ideas of this engineering. It gives a bunch of extraordinary tasks by which and clients can associate, make and control robots' groups at significant level. The investigations use LEGO Mindstorms robots as individuals from two robot groups. The cycle of creation, programming and control of the groups is introduced in all around characterized steps. The outcomes are palatable and show that the working methodology of the proposed framework meets key viewpoints at the framework level like particularity, adaptability and simple entry for end clients.

Pros:

The results are satisfactory and show that the operating strategy of the proposed system meets fundamental aspects at the system level such as modularity, flexibility and ease of access for end users

Cons:

This project is not feasible for automated robots.

2.2.13 F.A.G. Becerra; A. B. Ortega; C. D. G. Beltrán; C. G. Valdivia; R.O.D. Arcega,” Design and control of a new parallel robot for the rehabilitation of the hip-knee”

The utilization of robots for uninjured clinical recovery has increased generously lately because of the significance of accomplishing ordinariness in the wake of having endured a physical issue in any joint of the human body. In the current work we propose another robot of restoration for hip flexion development that comprises of two straight guide frameworks in the Z and Y tomahawks. The dynamic examination of the robot is made, proposing another kinematic model of five Links. The mathematical connection between the direct guide and the flexion point is utilized so that it would be simply important to quantify the situation of the straight guide without the estimation of the flexion point of the hip. The numerical model of the straight guides incorporates the elements of the CD engines, and a law of control GPI vigorous is proposed to control the position of the guide.

Pros:

The mathematical model of the linear guides includes the dynamics of the CD motors, and a law of control GPI robust is proposed to control the position of the guides.

Cons:

The robot positioning is not properly identified leaving more scope for improvement.

2.2.14 Takayuki Kanda, Member, IEEE, Dylan F. Glas, Masahiro Shiomi, and Norihiro Hagita, Senior Member, IEEE,” Abstracting People’s Trajectories for Social Robots to Proactively Approach Customers”

For a robot offering types of assistance to individuals in a public space like a shopping center, it is essential to recognize expected clients, like window customers, from others, like occupied workers. In this paper, we present a progression of deliberation strategies for individuals' directions and an assistance structure for utilizing these methods in a social robot, which empowers a planner to make the robot proactively approach clients by just giving data about target nearby conduct. We set a universal sensor network comprising of six laser range

locaters in a shopping arcade. The framework tracks individuals' situations just as their nearby practices, like quick strolling, inactive strolling, meandering, or halting. We gathered individuals' directions for seven days, applying a grouping method to the aggregated directions to remove data about the utilization of room and individuals' regular worldwide practices. This data empowers the robot to focus on its administrations to individuals who are strolling inactively or halting. The robot expects both the territories in which individuals are probably going to play out these practices just as the likely nearby practices of people a couple of moments later on. In a field test, we exhibit that this help system empowers the robot to serve individuals effectively.

Pros:

The system provides a framework to assess engineering risk and the wider financial implications of the new technologies as they are introduced.

Cons:

The system is not recommended, the vehicles are not accurately recognized using this feature.

2.2.15 Matthew Field; David Stirling; Zengxi Pan; Fazel Naghdy," Learning Trajectories for Robot Programming by Demonstration Using a Coordinated Mixture of Factor Analysers"

This paper presents a methodology for learning hearty models of humanoid robot directions from showing. In this plan, a model of the joint space direction is addressed as a grouping of movement natives where a nonlinear dynamical framework is learned by developing a secret Markov model (HMM) foreseeing the likelihood of dwelling in each movement crude. With a planned combination of factor analysers as the outflow likelihood thickness of the HMM, we can blend movement from a powerful framework acting along a complex common by both demonstrator and robot. This gives huge benefits in model intricacy for kinematically excess robots and can diminish the quantity of comparing perceptions needed for additional learning. A solidness investigation shows that the framework is vigorous to deviations from the normal direction just as temporary

movement between manifolds. This methodology is shown tentatively by recording human movement with inertial sensors, learning a movement crude model and correspondence map between the human and robot, and integrating movement from the complex to control a 19 level of-opportunity humanoid robot.

Pros:

This approach is demonstrated experimentally by recording human motion with inertial sensors, learning a motion primitive model and correspondence map between the human and robot, and synthesizing motion from the manifold to control a 19 degree-of-freedom humanoid robot.

Cons:

Accuracy is not up to the mark, leaving larger scope for improvement.

2.3 DISADVANTAGES IN EXISTING SYSTEM

- The system is RFID based making it not flexible for movement.
- The system reader antennas making it nor feasible for extensive real time applications.
- The system is not applicable for medical purposes, it cannot be used to treat patients.
- The movement of the robot cannot be lively monitored or controlled.

CHAPTER - 3

SYSTEM ANALYSIS

3.1 EXISTING SYSTEM

This article proposes a standalone radio recurrence ID (RFID)- based portable robot route technique, in which a versatile robot outfitted with per user reception apparatuses can be ceaselessly guided to a static item set apart with a solitary inactive UHF RFID tag. A perception model dependent on the RFID stage contrast is fabricated and coordinated into a molecule channel, by which the immediate relative situation between the portable robot and the labelled item can be distinguished continuously. In light of the position data extricated from the RFID framework, the versatile robot changes its posture to push toward the RFID-labelled item. Contrasted and the current RFID-based versatile robot route techniques, the proposed strategy requires no outside sensors other than the RFID and requires just a solitary latent tag. Trials utilizing business off-the-rack (COTS) RFID gadgets are performed, and the outcomes show that the versatile robot can agreeably acknowledge route task with a distance precision of 4.04 cm and an orientation exactness of 2.23°. The proposed strategy is well material for the route scenes in which the supreme situation of the labelled objective article isn't known already.

3.2 DISADVANTAGES OF EXISTING SYSTEM

- The system is RFID based making it inflexible for movement.
- The system reader antennas making it not feasible for extensive real time applications.
- The system is not applicable for medical purposes, it cannot be used to treat patients.
- The movement of the robot cannot be lively monitored or controlled.

3.3 PROPOSED SYSTEM

UV light has been utilized for sanitization and sterilization as right on time as the mid-twentieth century. With progressions in innovation, and explicitly in the UV bulbs themselves, its solid long-life expectancy (a large number of hours) and more modest size (for example UV LED versus customary UV bulbs) has widened the field for where it very well may be utilized. It tends to be utilized to clean water, air, organic products, vegetables, careful utensils, tablet PCs, toys and an assortment of surfaces. With regards to UV disinfection, not a wide range of UV are viable. For UV disinfection, just UVC (100-280nm) has sufficiently high energy to viably slaughter microorganisms. UV cleansing is a profoundly compelling strategy for infections and bacteria, Studies have shown that UVC at 254 nm is powerful against all food-borne microorganisms, characteristic microbiota, molds, and yeasts. Since microorganisms accompany various sizes and shapes that influence their UV ingestion, the necessary time for killing every species changes. UV cleansing otherwise called UV sanitization or bright germicidal light (UVGI) works by separating certain synthetic bonds and scrambling the construction of DNA, RNA and proteins, making a microorganism be not able to duplicate. At the point when a microorganism can't increase, it is viewed as dead since it can't replicate inside a host and is no longer infectious. The UV cleansing technique can be successfully used to the specialists' advantage, in the event of an individual being contaminated by a lethal sickness that can spread on contact with the patient, the specialist's prosperity goes under hazard while treating the patient. In this venture we build up a robot with an UV light, the robot is constrained by the client from a versatile application. Utilizing the versatile application, the development of the robot can be seen through live observing. The versatile application is created to go about as the far-off regulator of the robot, the robot is guided by the orders from the portable application on the course towards which the robot needs to move and furthermore where to utilize the UV radiation to treat the surface. By this strategy the specialist can treat the patient without coming in direct contact to the patient.

3.4 ADVANTAGES:

- Safe and effective solution to treat the patient without coming in direct contact with the patient.
- The movement of the robot can be lively monitored and controlled using a mobile application.
- The UV radiation can be used to disinfect surfaces and patients.

3.5 APPLICATIONS:

- Applicable in hospitals.
- Applicable in public place disinfection.
- Applicable in medical laboratories.

CHAPTER - 4

SYSTEM DESIGN

DETAILED DESIGN OF THE PROJECT

This part depicts the by and large and the definite structural plan. It likewise depicts every module that will be carried out alongside Data Flow diagram.

4.1 ARCHITECTURE DIAGRAM




Fig: 4.1 System Architecture

4.2 WORKING

In this project we build up a robot with an UV light, the robot is constrained by the client from a versatile application. Utilizing the versatile application, the development of the robot can be seen through live observing. The portable application is created to go about as the far-off regulator of the robot, the robot is guided by the orders from the versatile application on the heading towards which the robot needs to move and furthermore where to utilize the UV radiation to treat the surface. By this technique the specialist can treat the patient without coming in direct contact to the patient.

4.3 MODULE DESCRIPTION

- Battery supply module
- Motor driver module
- Relay module
- Servo motor module
- AVR microcontroller development
- Gateway module
- Mobile application development

4.3.1 BATTERY SUPPLY

Batteries are the most widely recognized force hotspot for essential handheld gadgets to huge scope mechanical applications. A battery can be characterized as; it is a blend of at least one electrochemical cell that are fit for changing over put away substance energy into electrical energy.

SMF is a fixed upkeep free battery, intended to offer solid, predictable and low support power for UPS applications. These batteries can be liable to profound cycle applications and least support in country and force deficiency regions. These batteries are accessible from 12V.

In the present instructive world, one can't ignore the necessity for battery frameworks are intended to recuperate significant qualified information and data and run fundamental instrumentations for wanted lengths. Batteries are needed to convey moment power. Temperamental and mediocre batteries can bring about the deficiency of information and hardware closures that can cost organizations extensive monetary misfortunes. Accordingly, the UPS sections requires the use of a dependable and demonstrated battery framework.

SMF is a fixed upkeep free battery, intended to offer solid, predictable and low support power for UPS applications. These batteries can be liable to profound cycle applications and least support in country and force deficiency regions. These batteries are accessible from 12V.

In the present useful world, one can't neglect the prerequisite for battery frameworks are intended to recuperate pivotal qualified information and data and run essential instrumentations for wanted terms. Batteries are needed to convey moment power. Temperamental and second-rate batteries can bring about the deficiency of information and hardware closures that can cost organizations significant monetary misfortunes. Thusly, the UPS sections requires the use of a solid and demonstrated battery framework.



Fig: 4.2 SMF Battery

4.3.2 MOTOR DRIVER

L298N 2A Based Motor Driver is a powerful engine driver ideal for driving DC Motors and Stepper Motors. It utilizes the famous L298 engine driver IC and has a locally available 5V controller which it can supply to an outer circuit. It can handle up to 4 DC engines, or 2 DC engines with directional and speed control. This engine driver is ideal for advanced mechanics and mechatronics ventures and ideal for controlling engines from microcontrollers, switches, transfers, and so on Ideal for driving DC and Stepper engines for miniature mouse, line following robots, robot arms, and so forth H-spans are commonly utilized in controlling engines speed and heading however can be utilized for different undertakings, for example, driving the splendour of certain lighting tasks like powerful LED exhibits. A H-Bridge is a circuit that can drive a current in one or the other extremity and be constrained by *Pulse Width Modulation (PWM).

Heartbeat Width Modulation is a method in controlling the term of an electronic heartbeat. In engines attempt to envision the brush as a water haggle as the streaming drops of water. The voltage would be the water streaming over the wheel at a steady rate, the more water streaming the higher the voltage. Engines are appraised at specific voltages and can be harmed if the voltage is applied to intensely or on the off chance that it is dropped rapidly to back the engine off. Hence PWM. Take the water wheel similarity and think about the water hitting it in beats however at a consistent stream. The more extended the beats the quicker the wheel will turn, the more limited the beats, the slower the water wheel will turn. Engines will last any longer and be more dependable whenever controlled through PWM.




Fig: 4.3 Motor Driver

4.3.3 RELAY MODULE

A relay module is an electrically worked switch. Numerous transfers utilize an electromagnet to precisely work a switch, however other working standards are additionally utilized, like strong state transfers. Transfers are utilized where it is important to control a circuit by a different low-power signal, or where a few circuits should be constrained by one sign. The principal transfers are utilized in significant

distance broadcast circuits as intensifiers: they rehashed the sign rolling in from one circuit and re-sent it on another circuit. Transfers are utilized widely in phone trades and early PCs to perform coherent activities. The fig shows the picture of a transfer.

A sort of hand-off that can deal with the high force needed to straightforwardly control an electric engine or different burdens is known as a contactor. Strong state gives control power circuits with no moving parts, rather utilizing a semiconductor gadget to perform exchanging. Transfers with adjusted working attributes and in some cases various working curls are utilized to shield electrical circuits from over-burden or blames; in present day electric force frameworks these capacities are performed by computerized instruments actually called "defensive transfers". Attractive locking transfers require one beat of loop ability to move their contacts a single way, and another, diverted heartbeat to move them back. Rehashed beats a similar information have no impact. Attractive locking transfers are valuable in applications where interfered with force ought not have the option to progress the contacts.



Fig: 4.4 Relay Module

4.3.4 SERVO MOTOR MODULE

A servo motor is an electrical gadget which can push or pivot an article with extraordinary exactness. On the off chance that you need to pivot and protest

at some particular points or distance, at that point you utilize servo engine. It is simply comprised of straightforward engine which go through servo component. On the off chance that engine is utilized is DC controlled, it is called DC servo engine, and assuming if it is AC powered engine, it is called AC servo engine. We can get a high force servo engine in a little and light weight bundles. Due to these highlights they're being utilized in numerous applications like toy vehicle, RC helicopters and planes, Robotics, Machine and so on.



Fig: 4.5 Servo Motor

4.3.5 AVR MICRO-CONTROLLER DEVELOPMENT

AVR is gathering microcontrollers made since 1996 by Atmel, acquired by Microchip Technology in 2016. These are changed Harvard plan 8-cycle RISC single-chip microcontrollers. AVR was one among the primary microcontroller families to use on-chip streak memory for program storing, as against one-time programmable ROM, EPROM, or EEPROM employed by other microcontrollers by then. AVR microcontrollers discover various applications as embedded structures. they're especially essential in trained professional and informative introduced applications, advanced by their thought in a huge number of the Arduino line of open gear headway sheets.

AVR microcontroller executes far and away most of the principles in single execution cycle. AVR's are around numerous occasions speedier than PICs, they eat up less power and may be worked in several power saving modes. AVR may

be a 8-cycle microcontroller having a spot with the gathering of Reduced Instruction Set Computer (RISC). In RISC plan the direction set of the PC are less in number even as simpler and speedier in movement. the opposite kind of game plan is CISC (Complex Instruction Set Computers).




Fig: 4.6 Architecture of AVR

The AVR microcontrollers depend on the high-level RISC design and comprise of 32 x 8-bit broadly useful working registers. Inside one single clock cycle, AVR can take contributions from two broadly useful registers and put them to ALU for doing the mentioned activity, and move back the outcome to a discretionary register. The ALU can perform number-crunching just as consistent activities over the contributions from the register or between the register and a steady. Single register activities like taking a supplement can likewise be executed in ALU. Obviously, AVR doesn't have any register like a collector as in 8051 group of microcontrollers; the activities can be performed between any of the registers and can be put away in both of them.

4.3.6 GATEWAY MODULE

The ESP8266 is a minimal effort Wi-Fi chip with full TCP/IP stack and MCU (microcontroller unit) capacity created by Shanghai-based Chinese producer, Espresso. The chip originally went for the consideration of western producers in August 2014 with the ESP-01 module, made by an outsider maker, AI-Thinker. This little module permits microcontrollers to interface with a Wi-Fi organization

and simplify TCP/IP associations utilizing Hayes-style orders. Nonetheless, at the time there was practically no English-language documentation on the chip and the orders it acknowledged. The extremely low cost and the way that there were not very many outer segments on the module which recommended that it could in the end be exceptionally modest in volume, pulled in numerous programmers to investigate the module, chip, and the product on it, just as to interpret the Chinese documentation. The ESP8285 is an ESP8266 with 1 MiB of underlying blaze, taking into account single-chip gadgets fit for associating with Wi-Fi.

The replacement to the microcontroller chips is the ESP32. ESP8266 (by and by ESP8266EX) is a chip with which makers are making remotely networkable miniature regulator modules. All the more explicitly, ESP8266 is a framework on-a-chip (SoC) with capacities for 2.4 GHz Wi-Fi (802.11 b/g/n, supporting WPA/WPA2), broadly useful info/yield (16 GPIO), Inter-Integrated Circuit (I²C), simple to-advanced transformation (10-cycle ADC), Serial Peripheral Interface (SPI), I²S interfaces with DMA (imparting pins to GPIO), UART (on committed pins, in addition to a send just UART can be empowered on GPIO2), and heartbeat width regulation (PWM). The processor centre which is called "L106" by Espressif, depends on Tensilica's Diamond Standard 106Micro 32-digit processor regulator center and runs at 80 MHz (or overclocked to 160 MHz). It has a 64 KB boot ROM, 64 KB guidance RAM and 96 KB information RAM. Outer blaze memory could be gotten to through SPI.




Fig: 4.7 Circuit Diagram of ESP8266

4.3.7 MOBILE APP DEVELOPMENT

React Native is a structure that forms a progressive system of UI parts to fabricate the JavaScript code. It has a bunch of segments for the two iOS and Android stages to construct a portable application with a local look and feel. Versatile advancement has seen extraordinary development. As per insights, portable applications will create an expected 188 billion U.S. dollars in income through application stores, publicizing and in-application buys continuously 2020. Single and business clients require exclusive expectation applications with faultless execution, different screens, simple route and great plan. On the opposite side, high-performing, great quality local applications are tedious to create contrasted with cross-stage applications that give quicker turn of events yet bargain on execution and backing. Respond Native is by all accounts a suitable answer for building great applications in a brief timeframe with a similar exhibition and client experience principles that local applications give.

Respond Native applications are gathered into locally composed code, which empowers React Native to chip away at both working frameworks, yet in addition have same highlights on the two stages with no slack. Respond Native will likewise expand your ability pool: engineers can assemble versatile applications utilizing JavaScript. JavaScript is very basic among front-end engineers and moderately simple for back-end designers to get. This way more front-end engineers get a chance to take a shot at versatile improvement interestingly.




Fig: 4.8 Mobile App Development

CHAPTER - 5

SOFTWARE DESCRIPTION

5.1 VISUAL STUDIO

In this undertaking Microsoft visual studio is utilized as IDE. Visual Studio Code joins the straightforwardness of a source code proof reader with incredible engineer tooling, as IntelliSense code consummation and investigating. As a matter of first importance, it is a manager that moves. The brilliantly frictionless alter construct troubleshoot cycle implies less time tinkering with the climate, and additional time executing on thoughts. Visual Studio Code upholds macOS, Linux, and Windows - permitting the ground running, regardless of the stage. At its heart, Visual Studio Code includes a lightning quick source code supervisor, ideal for everyday use. With help for many dialects, VS Code helps in being immediately beneficial with linguistic structure featuring, section coordinating, auto-space, box-determination, pieces, and then some. Instinctive console alternate ways, simple customization and local area contributed console easy route mappings lets route of code effortlessly. For genuine coding, the advantage is from devices with more code understanding than simply squares of text. Visual Studio Code remembers worked for help for IntelliSense code culmination, rich semantic code comprehension and route, and code refactoring.

What's more, when the coding gets extreme, the intense get troubleshooting. Investigating is frequently the one component that designers miss most in a more slender coding experience, so it is gotten to going. Visual Studio Code incorporates an intelligent debugger, so one can venture through source code, investigate factors, see call stacks, and execute orders in the comfort. Visual Studio Code additionally incorporates with construct and scripting devices to perform basic undertakings making regular work processes quicker. Visual Studio Code has uphold for Git so anybody can work with source control without leaving the manager including seeing forthcoming changes diffs. Permits customization of each element to the preferring of the client and introduce quite a few outsider expansions. While most situations work "out of the case" with no design, VS Code

likewise develops alongside the client, and urges client to upgrade your experience to suit his/her interesting necessities. Visual Studio Code remembers enhanced worked for help for Node.js improvement with JavaScript and TypeScript, fueled by the very basic advances that drive Visual Studio. Visual Studio Code likewise incorporates extraordinary tooling for web innovations like JSX/React, HTML, CSS, SCSS, Less, and JSON.

Structurally, Visual Studio Code consolidates the most awesome aspect web, local, and language-explicit advancements. Utilizing Electron, VS Code joins web innovations, for example, JavaScript and Node.js with the speed and adaptability of local applications. Visual Studio Code utilizes a fresher, quicker form of a similar modern strength HTML-based supervisor that has controlled the "Monaco" cloud editorial manager, Internet Explorer's F12 Tools, and different undertakings. Also, VS Code utilizes an instruments administration design that empowers it to incorporate with a large number of the very innovations that power Visual Studio, including Roslyn for .NET, TypeScript, the Visual Studio troubleshooting motor, and that's only the tip of the iceberg. Visual Studio Code incorporates a public extensibility model that allows designers to assemble and utilize expansions, and lavishly tweak their alter construct troubleshoot insight.

5.2 ANDROID STUDIO

In this venture android studio is utilized as the IDE for versatile application improvement. Android Studio is the authority incorporated advancement climate (IDE) for Google's Android working framework, based on JetBrains IntelliJ IDEA programming and planned explicitly for Android improvement. It is accessible for download on Windows, macOS and Linux based working frameworks or as a membership-based help in 2020. It is a swap for the Eclipse Android Development Tools (E-ADT) as the essential IDE for local Android application improvement. To keep in touch with some code for an Android application, some sort of climate or code proof-reader is necessitated that will make the errand simple. Still code can be written in a typical content manager yet that will build the responsibility. In this way, Android Studio is an Integrated Development Environment (IDE) for Android

application advancement. It depends on Intelligence IDEA. To improve profitability while building Android application, Android Studio gives various highlights, they are

1. Instant sudden spike in demand for a cell phone or any virtual gadget to check the working of the application
2. Extensive testing apparatuses that can be utilized for better testing prior to dispatching an application on the Play Store
3. Flexible Gradle-based form framework
4. Code autocomplete.

Data set examiner: Enables a client to see the condition of and make changes to the on-gadget information base (utilizing Jetpack Room or crude SQLite questions) in the IDE. New undertaking layouts have been refreshed to utilize Material Design Components.

Coordinated emulator window: The emulator can be run straightforwardly in the IDE rather than its own, independent window. Knife/Hilt code route: Click on the new drain activities to discover more about Dagger and Hilt types in your code.

ML Model Binding: Studio can produce code for an imported Tensor Flow Lite model which makes it simpler to interface with that model from the application code.

5.3 EMBEDDED C

In this undertaking the installed C is utilized. Installed C is most well-known programming language in programming field for creating electronic contraptions. Every processor utilized in electronic framework is related with inserted programming. Inserted C programming assumes a critical part in performing explicit capacity by the processor. In everyday life we utilized numerous electronic

gadgets like cell phone, clothes washer, computerized camera, and so forth. These all gadget working depends on microcontroller that are customized by installed C. Installed C is maybe the most famous dialects among Embedded Programmers for programming Embedded Systems. There are numerous well known programming dialects like Assembly, BASIC, C++ and so forth that are frequently utilized for creating Embedded Systems however Embedded C remaining parts mainstream because of its effectiveness, less improvement time and versatility.

Remarks: Comments are decipherable content that are composed to help us (the per user) comprehend the code without any problem. They are disregarded by the compiler and don't take up any memory in the last code (after assemblage).

There are two different ways you can compose remarks: one is the single line remarks meant by/and the other is multiline remarks indicated by/*....*/.

Pre-processor Directive: A Pre-processor Directive in Embedded C is a sign to the compiler that it should glance in to this document for images that are not characterized in the program.

In C Programming Language (likewise in Embedded C), Pre-processor Directives are generally addressed utilizing `#include...` or `#define....`. In Embedded C Programming, we generally utilize the pre-processor order to demonstrate a header record explicit to the microcontroller, which contains all the SFRs and the pieces in those SFRs. In the event of 8051, Keil Compiler has the record "reg51.h", which should be composed toward the start of each Embedded C Program.

Worldwide Variables: Global Variables, as the name proposes, are Global to the program for example they can be gotten to anyplace in the program.

Neighbourhood Variables: Local Variables, as opposed to Global Variables, are limited to their individual capacity.

Primary Function: Every C or Embedded C Program has one fundamental capacity, from where the execution of the program starts.

CHAPTER-6

RESULTS & DISCUSSIONS

6.1 FINAL OUTPUTS OBTAINED

The below image shows the top view of the UV robot hardware setup of the project:




Fig 6.1 Top View of The Robotic Setup

The below image shows the side view of the UV robot hardware setup of the project:




Fig 6.2 Side View of The Robotic Setup

A mobile application using a java script framework react native is developed to effectively control the robotic hardware setup. The below image shows the login page of the mobile application:




Fig 6.3 Login Page of The Mobile Application

On successful login to the mobile application the home page of the mobile application is shown.

The below image shows the home page of the mobile application:




Fig 6.4 Home Page of The Mobile Application

The below image shows the complete assembled robotic setup of the UV robot project:



Fig 6.5 Complete Setup of The UV Robot

Thus, from the above images and discussions it is clear the UV robot project has been successfully implemented.

CHAPTER – 7

CONCLUSION AND FUTURE WORK

7.1 CONCLUSION

This undertaking is utilized to adequately treat public spaces with UV radiation with an automated arrangement that has been successfully incorporated to a versatile application. This likewise help in giving proficient treatment in a most modest way and ultimately diminish the time and labour needed for treatment of public spaces. If it is done physically which burns-through additional time and furthermore includes human blunder rate. Thus, lessens the time needed for manual characterization and kills the human mistake rate by this undertaking.

7.2 FUTURE WORK

In the coming future, we survey the utilization of the UV robot decide innovation in the wellbeing office field and it can advance for treatment of public spaces with more exactness. In clinical field they are more opportunity to create or change over this venture from numerous points of view. Along these lines, this undertaking has an effective extension in coming future where manual treatment of public spaces can be changed over to electronic creation in a modest manner.

REFERENCE

- [1] Haibing Wu, Bo Tao, Member, IEEE, Zeyu Gong, Member, IEEE, Zhouping Yin, Member, IEEE, and Han Ding, Senior Member, IEEE, "A Standalone RFID-Based Mobile Robot Navigation Method Using Single Passive Tag" [24 July 2020].
- [2] Asif Khan, Bernhard Rinner, Senior Member, IEEE, and Andrea Cavallaro, "Cooperative Robots to Observe Moving Targets: Review" [01 December 2016].
- [3] Shuai Li, Ruofan Kong, and Yi Guo, Senior Member, IEEE, "Cooperative Distributed Source Seeking by Multiple Robots: Algorithms and Experiments" [06 January 2014].
- [4] Olzhas Adiyatov, Student Member, IEEE, Bexultan Rakhim, Altay Zhakatayev, Member, IEEE, and Huseyin Atakan Varol, Senior Member, IEEE, "Sensor Reduction of Variable Stiffness Actuated Robots Using Moving Horizon Estimation" [11 July 2019].
- [5] J. García, A. Bohórquez, and A. Valero, "Suspension Effect in Tip-Over Stability and Steerability of Robots Moving on Sloping Terrains" [09 June 2020].
- [6] Milan Lukic, Ahmed Barnawi, Member, IEEE, and Ivan Stojmenovic, Fellow, IEEE, "Robot Coordination for Energy-Balanced Matching and Sequence Dispatch of Robots to Events" [09 June 2014].
- [7] Jing Li; Qiang Huang; Zhangguo Yu; Xuechao Chen; Weimin Zhang; Huaxin Liu; Junyao Gao; Yingxian Duo, "Integral Acceleration Generation for Slip Avoidance in a Planar Humanoid Robot" [01 June 2015].
- [8] Guillaume Doisy; Joachim Meyer; Yael Edan, "The Impact of Human–Robot Interface Design on the Use of a Learning Robot System" [24 July 2014].
- [9] Feng Gu; Yuqing He; Jianda Han, "Active Persistent Localization of a Three-Dimensional Moving Target Under Set-Membership Uncertainty Description Through Cooperation of Multiple Mobile Robots" [19 February 2015].

- [10] C. Serkan Karagöz; H. Isil Bozma; Daniel E. Koditschek," Coordinated Navigation of Multiple Independent Disk-Shaped Robots" [17 September 2014].
- [11] Guanglong Du; Mingxuan Chen; Caibing Liu; Bo Zhang; Ping Zhang," Online Robot Teaching with Natural Human–Robot Interaction" [05 April 2018].
- [12] P.H.L. Silva; A.M.F. Burlamaqui," System for Creation, Programming and Availability of Distributed Robot Teams using Collective Knowledge" [16 December 2016].
- [13] F.A.G. Becerra; A. B. Ortega; C. D. G. Beltrán; C. G. Valdivia; R.O.D. Arcega," Design and control of a new parallel robot for the rehabilitation of the hip-knee" [09 July 2018].
- [14] Takayuki Kanda, Member, IEEE, Dylan F. Glas, Masahiro Shiomi, and Norihiro Hagita, Senior Member, IEEE," Abstracting People's Trajectories for Social Robots to Proactively Approach Customers" [30 October 2009].
- [15] Matthew Field; David Stirling; Zengxi Pan; Fazel Naghdy," Learning Trajectories for Robot programming by Demonstration Using a Coordinated Mixture of Factor analysers" [26 March 2015].