

Investigation and Application of Forward Swept Wing Design in Inter Continental Ballistic Missiles

Submitted in partial fulfilment of the requirements for the award of

Bachelor of Engineering degree in
Aeronautical Engineering

By

Y.Leelaprasad (Reg. No. 37260020)

G.Durgaprasad (Reg. No. 37260011)



DEPARTMENT OF AERONAUTICAL ENGINEERING

SCHOOL OF MECHANICAL ENGINEERING

SATHYABAMA

INSTITUTE OF SCIENCE AND TECHNOLOGY

(DEEMED TO BE UNIVERSITY)

Accredited with grade “A” by NAAC

JEPPIAAR NAGAR, RAJIV GANDHI SALAI, CHENNAI – 600119

MARCH 2021



SATHYABAMA
INSTITUTE OF SCIENCE AND TECHNOLOGY
(DEEMED TO BE UNIVERSITY)
Accredited with "A" grade by NAAC
Jeppiaar Nagar, Rajiv Gandhi Salai, Chennai - 600 119
www.sathyabama.ac.in



DEPARTMENT OF AERONAUTICAL ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that this Project Report is the bonafide work of **Y.Leelaprasad (Reg. No. 37260020)** and **G.Durgaprasad (Reg. No. 37260011)** who carried out the project entitled "**Design, Analysis and Experimental testing of a new wing morphing structure**" under our supervision from November 2020 to March 2021.

Internal Guide
Mr. Gunasekhar

Head of the Department
Dr. Boomadevi, PhD.,

Submitted for Viva voce Examination held on _____

Internal Examiner

External Examiner

DECLARATION

I **Y.Leelaprasad (Reg. No. 37260020) and G.Durgaprasad (Reg. No. 37260011)** hereby declare that the Project Report entitled “**Design, Analysis and Experimental testing of a new wing morphing structure**” done by me under the guidance of **Mr. Gunasekhar** is submitted in partial fulfilment of the requirements for the award of Bachelor of Engineering degree in Mechanical Engineering.

DATE:

PLACE: CHENNAI

SIGNATURE OF THE CANDIDATE

ACKNOWLEDGEMENT

I am pleased to acknowledge my sincere thanks to Board of Management of **SATHYABAMA** for their kind encouragement in doing this project and for completing it successfully. I am grateful to them.

I convey my sincere thanks to **Mr. Venkatesh** and **Dr. Boomadevi, Ph.D., Head of the Department, Department of Aeronautical Engineering** for providing me necessary support and details at the right time during the progressive reviews.

I would like to express my sincere and deep sense of gratitude to my Project Guide **Mr. Gunasekhar** for his valuable guidance, suggestions and constant encouragement paved way for the successful completion of my project work.

I also express my thanks to all Teaching and Non-teaching staff members of the Department of Aeronautical Engineering who were helpful in many ways for the completion of the project.

Abstract :-

An intercontinental ballistic missile (ICBM) is a rocket with a base degree of five thousand five hundred kilometers basically expected for atomic weapons transport. Essentially, standard, designed, and normal weapons can also be passed on with fluctuating abundance, in any case have never been sent on ICBMs. Most present day plans keep up different autonomously targetable return vehicles (MIRVs), permitting a particular rocket to pass a few warheads, all can strike a substitute objective. Top nations all have operational ICBMs. Early ICBMs had limited exactness, which made them reasonable for utilize just against the best focuses, as metropolitan locales. They were viewed as a "safe" basing choice, one that would keep the check power valuable where it is hard to assault. Assaults against military targets (particularly established ones) truly referenced the use of a more precise, noticed plane. Second-and third-age plans, (for example, the LGM-118 Peacekeeper) generally improved exactness to where even the most small point targets can be feasibly assaulted.

Diminishing the collaboration time in arrangement is one of the huge models for any field and hence robotization with the help of CAD gadgets is amazingly basic in diminishing time. This assessment also targets developing a forward swept wing modeled integrated ballistic missile with various sweep angles, canard angles and spacing and different wing tip models can be produced using CAD advancement focused in on diminishing arrangement time during the fundamental arrangement measure. Data based approach is used in this work and every one of the models are characterized so each model could be varied with related limits. The collective model made would take different shapes and changes in-between different kinds of wingtip models for the forward swept wing as the customer's need with open limits. Data Pattern (KP) approach is utilized to develop the computerization cycle. Customer Defined Features (UDFs) are made for every sort of Wing and the rocket body features. CATIA V5 R18 writing computer programs is used to develop the models of the rocket or ICBM's with various patterned gadgets to be produced.



Fig 1

Catchphrases (Keywords):-

CATIA V5, ICBM, Forward Swept wing, Canard, Knowledge Pattern, Parameterization.

Rundown of Symbols and Abbrevations :-

NASA – National Aeronautics and Space Administration

CATIA - Computer Aided Three dimensional Interactive Application

VB – Visual Basic KP – Knowledge Pattern

Programming interface – Aviation Partner Inc.

APB – Aviation Partners Boeing

CAE – Computer Aided Engineering

ICBM – Inter Continental Ballistic Missile

$Cd0$ – Profile drag coefficient

Cdi – Induced drag coefficient

Compact disc Total drag coefficient

F – Form factor

Q – Interference factor

Re - Reynolds number of the part

V - Velocity

l - part attributes length

u - kinematic thickness for that flight condition

e – Ostwald's productivity factor

AR – Aspect proportion

Cl – Lift coefficient

Λ – Sweep point

UDF – User Defined Feature

CONTENTS

Chapters

- 1 Introduction (Pg 11-24)**
 - 1.0 Motivation**
 - 1.1 Aerodynamic Forces and Movements acting on Missile**
 - 1.2 Classification of Missiles**
 - 1.3 Missile Aerodynamic Design Parameters**
 - 1.3.1 Lift to Drag ratio**
 - 1.3.2 Stability**
 - 1.3.3 Maneuverability**
 - 1.3.4 Control effectiveness**
 - 1.3.5 Introduction to forward swept wing**
- 2 Literature Survey (Pg 25-27)**
 - 2.1 Aim**
 - 2.2 Organization of thesis**
- 3 Scope and Design (Pg 28-31)**
 - 3.1 Scope in Administering Forward Swept wing**
 - 3.1 Design of the Ballistic missile with Forward Swept wing**
 - 3.1.1 Design 1**
 - 3.1.2 Second Design**
 - 3.1.3 Third Design**
 - 3.1.4 Fourth Design**
- 4 Computational Analysis (Pg 32-43)**
 - 4.1 Introduction to Ansys Fluent**
 - 4.1.1 Ansys work seat application**
 - 4.1.2 Ansys CFD**
 - 4.1.3 Ansys ICEM CFD**

4.1.4 Ansys LS-DYNA

4.2 Procedure to solution by Ansys

4.2.1 Geometry

4.2.2 Meshing

4.2.3 Solver setup

4.2.3.1 Flow Solver

4.2.3.1.1 Pressure based solver

4.2.3.1.2 Thickness based solver

4.2.3.2 Discretization (Interpolation method)

4.2.3.3 Interpolation Methods (Gradients)

4.2.3.4 Interpolation Methods for Pressure

4.2.3.5 Pressure Velocity coupling

4.2.3.6 Hybrid Initialization

4.2.3.7 Modifying the courant number

4.3 Lift and Drag Coefficient

5 Results (Pg 44-45)

6 Conclusion and Reference (Pg 46-50)

6.1 Conclusion

6.2 References

LIST OF FIGURES

- 1 Fig 1
- 1.1 Iterative Missile Design Process
- 1.2 Forces and Moments acting on Missile
- 1.3 Control Alternatives for Missiles
- 1.4 Static Stability
- 1.5 Statically Stable Missile Configuration
- 1.6 Forward Swept Wing
- 1.7 First Design View
- 1.8 Second Design View
- 1.9 Third Design View
- 1.10 Fourth Design View
- 1.11 Pressure Contour 1
- 1.12 Pressure Contour 2
- 1.13 Velocity Contour 1
- 1.14 Velocity Contour 2
- 1.15 Drag Coefficient
- 1.16 Lift Coefficient
- 1.17 Flow testing 1
- 1.18 Flow testing 2
- 1.19 Supersonic wind tunnel air compression tanks
- 1.20 Flow in Supersonic wind tunnel
- 1.21 Fabricated model
- 1.22 Flow Analysis Graph

LIST OF TABLES

- 1.1 Classification of the Missiles Based on Platform and Target Location
- 1.2 Advantages and Disadvantages of Missile Control Types

CHAPTER 1

1 INTRODUCTION

In current Period, a rocket, is also called a guided rocket or guided missile, is a controlled flying run weapon suitable for self-propelled flight generally by a rocket engine or a flying turbine engine. Rockets have a total four parts of framework they are flight framework, focusing on/direction framework, motor and warhead. Rockets come in different types for different purposes: air to plane/surface and plane to plane rockets, surface-to-air rockets, aerial rockets, and menacing to satellite weapons. In flight delicate devices without impulse are insinuated as carapaces at whatever point shot by an arms piece and bombs at whatever point dropped by a plane. Haphazard fly affected rockets are for the most part depicted as rocket arms. Truly, the term rocket alluded for any shot that is thrown, shot or impelled towards an goal; this utilization is as yet perceived today.

1.0 Motivation :-

A designing plan streamlining issue can be characterized as getting the best conceivable designing framework under given framework requirements, execution necessities and time limits. Planners for the most part need an instrument to beat the plan advancement issue, where an investigation/test system is combined with an advancement technique [1]. The results of the advancement issue are characterized as target capacities which may address primary, streamlined or synthetic execution boundaries or effects. Targets of issue are elements of plan factors which make the properties of designing framework (1).


In rocket streamlined plan, it's important to research huge plan area. Intricacy of a plan area is subject to quantity of information factors. Rocket width, body, nose and rearward shape length, number of balance harmonizes, no. of blades for every balance size, set and state of every balance as-well-as balance cross-area can also be given as certain guides to plan factors. Mathematical impediments are forced to the plan issue

when dispatch stage similarity, cost issues and other subsystem reconciliations are considered. Streamlined execution boundaries like mobility, control adequacy, dynamic and static strength, lift to drag proportion are the goals for plan issue. Appropriately, in rocket streamlined plan improvement issues, there exist various boundaries, factors and requirements which make the issue hard to tackle in terms of computational exertion and time. Furthermore, execution boundaries got as results of the plan interaction by and large clash with one another. Therefore, it is hard to get the most ideal arrangement except if the fashioner has sufficient computational asset for looking through the entire plan 2 space or he/she is utilizing numerical improvement techniques along with designing examination/reproduction apparatuses. In this postulation, it is intended to build up a plan improvement technique that can be utilized to defeat challenges of rocket streamlined plan issue and lessen time spent in theoretical plan period of rockets.

Point based and stochastic streamlining techniques are generally utilized in arranging plan streamlining issues. Inclination type techniques pick the maximum or min of the target segments of the game plan issue by utilizing point data of the cutoff. Newton's framework, steepest drop methodology furthermore, Sequential Quadratic Programming (SQP) several counsels for inclination based improvement strategies and are completely utilized in the arrangement for arranging issues like streamlined or essential model improvement. A basic necessity portrayal of SQP technique is given in Chapter 2. These improvement strategies are by and large seen as energetic and sales low computational assets. In the long run, they are infrequently called neighborhood streamlining experts since they will by and large join to the nearby least of the course of action volume and may cause lopsided consequences as they to require a beginning stage to begin the streamlining cycle. In like manner, point based systems may wind up with infeasible courses of action since arranging streamlining issues are everything viewed as exceptionally nonlinear and wild in nature. Fittingly, stochastic overhaul strategies that needn't mess with inclination data of the issue are utilized in game plan improvement issues to conquer negative impacts of point based frameworks. Irregular Search (RS) techniques, Genetic Algorithms (GA) and also Simulated Annealing (SA) are events of sttimedependent progress frameworks (2). A point by point depiction of a RS framework can be found in Section 2. Stochastic frameworks are more fruitful for picking by and large

least, anyway they for the most part require more computational assets as opposed to the propensity based strategies [3].

In speculative course of action of rockets, an iterative participation appeared in Figure 1.1 is come after. A benchmark plan that has comparable mission necessities and motivation framework is picked as a beginning stage. Plan factors that sway 3 ideal arrangement, power, weight and flight orientation of the action course of action are changed repeatedly to meet the assignment necessities set up for plan cycle [4]. Here, as the streamlined features were needed over other plan attributes, portraying a strategy that is streamlined concerning streamlined execution diminishes the general no. of rescaling cycles and reduces time spent on the course of action affiliation. Fig (1.1) Iterative Missile Design Process (4) Streamlined course of action of missile/rocket plans depend upon the appraisal of elective outside shapes [4]. Rocket streamlined execution limits are by and large like restricts that are utilized for plane course of action.4






Figure 1.1 Iterative Missile Design Process

Since missiles/rockets are barren and extra, raised speed levels, height and moving rate increments can be contemplated in the arrangement cycle. In any case, these raised levels get together for certain smoothed out issues like nonlinearity of smoothed out coefficients at high methodologies and high wing packs in these raised flight path (5). As rockets are empty, it is practicable to utilize sweeping move improvement in flight that outcomes in extra remarkable adequacy assessments. Course frameworks that survey pilot input are central for rockets a few issues of unwavering quality and control that are not educated about plane arrangement are given these designs.

Rockets/missiles are for the most part slim, subsequently thin body hypothesis is adequate for understanding streamlined qualities of rocket setups (5).

1.1 Aerodynamic Forces and Moments Acting on a Missile

Rocket smoothed out highlights are contemplated under three smoothed out forces and 3 minutes for 6 degrees of chance assessment and the body-fixed orchestrate structure. In Fig 1.2, headings of the force and minutes in concomitant structure are specified (6). Account that, powers isolated by the free flow dynamic squeezing factor and the testimonial zone gives power coefficient (for instance) while second coefficients (for instance) are controlled by apportioning the minutes with the free flow dynamic squeezing factor, ref length and the ref district. Here, the reference length it is generally taken as the rocket width and ref an area of cross-section locale of rocket body.

$$C_N = \frac{N}{q S_{ref}} \quad (1.1)$$

$$C_m = \frac{M}{q S_{ref} L_{ref}} \quad (1.2)$$




Figure 1.2 Forces and Moments Acting on a Missile

(1.1) (1.2)5 Fig 1.2 Force and Moment Acting on Missile Force coefficient for rocket appeared in Fig 1.2 as C_A , C_N , and C_Y . Axial power coefficient, C_A , is positive negative x way while side power coefficient, C_Y , is positive in the y heading and ordinary power coefficient, C_N , is positive in the negative z bearing. In Figure 1.2, second coefficients are given as C_l , C_m , and C_n . Moving second, C_l , are about x-hub, pitching second coefficient, C_m , is about y-hub and yawing second coefficient, C_n , is about z axis, appeared in their positive faculties in the figure.

1.2 Classification of Missiles:-

Missile classification is based on the launching platform, propulsion system, mission and the type of target, target location, type of control, design drivers and etc. {4.5}. An ex of classification of missiles is given based on the launch pad and target locations and distance for the state of the art given in the table [1.1](4).

Platform and Target Location	Range / Mission	Example
Air to Air (ATA)	Short Range ATA	AIM-9
	Medium Range ATA	AIM-120
	Long Range ATA	AIM-54
Air to Surface (ATS)	Short Range ATS	AGM-65
	Antiradar ATS	AGM-88
	Medium Range ATS	Apache
	Antitank ATS	AGM-114
	Long Range ATS	AGM-86
Surface to Surface (STS)	Long Range STS	BGM-109
	Long Range Anti-armor STS	MGM-140
	Man-portable STS	Javelin
Surface to Air (STA)	Short Range STA	FIM-92
	Medium Range STA	MIM-23
	Long Range STA	MIM-104
	Missile Defense	PAC-3

Table 1.1 Classification of Missiles Based on Platform and Target Location [4]

Another order can be made dependent on sort of control. Aside from flighty control frameworks, for example, push vector or response fly control, rockets are constrained by avoiding streamlined lifting surfaces [4]. In like manner, streamlined attributes and the general exhibition of a rocket are gigantically influenced by control surface area. Predominantly, rockets are designated tail, canard and wing controlled (Fig 1.3) [4].

Each sort of control elective has benefits and hindrances that should be considered in rocket plan. These benefits and hindrances are summed up in Table 1.2 [4].




Figure 1.3 Control Alternatives for Missiles



Control Type	Advantages	Disadvantages	Examples
Tail Control	- Efficient packaging - Low actuator torque - Low induced rolling moment - Efficient at high angles of attack	Decreased lift at low angles of attack	Maverick AGM-65 [4]  AMRAAM AIM-120 [4] 
Canard Control	- Efficient packaging - Simplified manufacturing - Increased lift at low angles of attack	- Stall at high angles of attack - High induced roll	AIM-9L [4]  Gopher SA-13 [4] 
Wing Control	- Fast response - Maneuverability at low angles of attack - Small trim angle	- Poor packaging - High hinge moments - Large wing size - Large induced roll	Sparrow AIM-7 [4]  HARM AGM-88 [4] 

Table 1.2 Advantages and Disadvantages of Missile Control Types [4]

1.3 Missile Aerodynamic Design Parameters:-

Lift-drag proportion, solidness, control adequacy and mobility are the fundamental plan boundaries for rocket streamlined plan issues [7].

1.3.1 Lift-to-Drag Ratio (L/D):-

Lift-drag extent, in any case called smoothed out capability, is one of most huge limits in rocket plan. It basically influences range and moreover impacts versatility (4). It's described as extent of tot lift to supreme drag of rocket. It can also similarly can be written in the coefficient design structure. In the coefficient structure, association of the lift-drag to the center point and customary forces can also be created as;

$$\begin{aligned}C_D &= C_N \sin \alpha + C_A \cos \alpha \\C_L &= C_N \cos \alpha - C_A \sin \alpha\end{aligned}\tag{1.3}$$

In these equations, α represents the missile angle of attack. Range of a missile is a function of lift-to-drag ratio according to the Breguet range equation [4];

$$R = (v I_{sp}) \cdot \left(\frac{C_L}{C_D}\right) \cdot \ln \left(\frac{W_{BC}}{W_{BC} - W_P}\right)\tag{1.4}$$

where journey speed is meant as , explicit motivation indicated and weight of the rocket before dispatch and the weight of fuel are signified as and separately.

1.3.2 Stability:-

Steadiness of the rocket is contemplate as far as static solidness and dynamic security. A statically steady rocket can create some measure of the pitching second with expanding approach in restricting way [4]. As such, a statically steady rocket weathercocks to stream course when the flight conditions are to changed.

To get this streamlined trademark, indication of $C_{m\alpha}$ pitch firmness subordinate should be negative as demonstrated in Fig (1.4(8)).

$$C_{m\alpha} \approx \frac{\Delta C_m}{\Delta \alpha} < 0 \quad 1.5$$




Fig 1.4 Static Stability




Fig 1.5 Statically Stable Missile Configuration

Static solidness is by and large evaluated with the static edge, distance between focus of pressing factor (x_{cp}) and focal point of gravity (x_{cg}) isolated by the rocket width (D) [4];

$$\mathbf{SM} = \frac{x_{CG} - x_{CP}}{D} \quad \mathbf{1.6}$$

Positive, Negative and Zero estimations of static edge addresses stable, hardly steady as well as shaky rocket arrangements, separately. A more modest negative static edge implies a steady rocket that can be managed ($C_m = 0$) at high approaches, as needs be can create high ordinary power and has expanded mobility.

1.3.3 Maneuverability:-

Ability of the rocket to alter course and speed in given time is named as mobility [9]. Burden factor is a proportion of this streamlined presentation boundary and characterized as the proportion of the typical speed increase because of streamlined power to the gravitational speed increase [8].

$$n = \frac{N/m}{g} \quad 1.7$$

Where,

$$N = C_N S_{\gamma_{ef}} \left(\frac{1}{2} \rho v^2 \right) \quad 1.8$$

At a described speed, a rocket with high load factor can accomplish higher ordinary power; in like manner, it have high turn rate and low turn span (10).

1.3.4 Control Effectiveness :-

Control viability of rocket is characterized as proportion of control surface diversion at the trim condition to approach (8).

$$CE = \frac{\delta_{trim}}{\alpha} \quad 1.9$$

In rocket plan, for the most part a control viability esteem that is under 1 is wanted [7]. A rocket with more modest control adequacy can be managed at a higher approach, likewise has better control force and mobility [8].

Right when rocket smoothed out arrangement limits are considered in the pitch of the plane, smoothed out the coefficients like center force coefficient (CA), regular coefficient of force (CN), pitching second coefficient (Cm) and the flight conditions like speed, Mach number, approach (α), control surface redirection (δ) are the central factors that impact ideal plan of a rocket.

1.3.5 Introduction to forward swept wing

A forward-cleared wing is an airplane wing setup in which the quarter-harmony line of the wing has a forward clear. Ordinarily, the main edge likewise clears forward.

Air gushing over any cleared wing will move by and large spanwise towards rearmost summit of wing. On a while later cleared wing this is outward towards the tip, while on forward cleared wing it is internal towards the root. In like manner, the unstable tip hinder condition of a toward the back cleared arrangement transforms into more controllable and safer root delayed down on forward clear arrangement. It licenses full control over aileron paying little heed to loss of the lift, and also besides infers that drag-starting driving edge spaces or various machines are not required.

With air flowing inwards, the wingtip vortices are going with drag being diminished. Considering everything, the fuselage will go probably as a colossal wing divider and, since the wings generally are greater at root, this raises the best lift coefficient allowing more humble wing.

Appropriately, versatility is improved, especially at high methodologies.




Fig 1.6 Forward Swept wing

Chapter 2

Literature Survey

In writing, a few investigations on rocket shape enhancement are accessible. These reads are directed for various plan targets, utilizing both probabalistic and slope from the procedures for streamlining. Genetic Algorithm and Recreated Annealings strategies are liked in the greater part of the investigations.

By pareto's GA's, Jenkins, Burkhalter and Anderson [11] explored rocket smoothed out shape improvement. A smoothed out assumption code is joined with a GA analyzer. Different arrangement factors concerning the rocket shape and smoothed out execution objectives are associated with his examination. Even more lately, Tanil (12) has developed the external arrangement design model gadget that uses the GA as progress method. The procedure put forward can gauge rockets depending upon the flight execution objectives. Karakoç [13] managed rocket outside course of action upgrade using GA. Essential fixation for his work keeps boosting flight execution and restricting cross-fragmentation of radar of rockets. Yong-et-al. (14) read smoothed out shaped headway for a canard of controlled rockets to grow flight travel range. The GA smoothing out specialist is utilized alongside a three degree-of freedom flight re-enactment code and a smoothed out examination mechanical assembly. Tekinalp and Bingöl [15] developed a rocket heading headway procedure. SA progression procedure is used as the smoothing out specialist. A two degree of-chance flight reenactment model and a smoothed out solver code have been used together in proposed procedure. Öztürk [2] worked on multi-target plan smoothing out of missiles and rockets. Objectives of the range, flight-time, hit point and speed, smoothed out coefficients can be seen as together. A perpetual System Anneling upgrade computation called the Hide and Seek is used. Despite all these adventitious arrangement improvement procedures, there are some that

are made by Ercan and Tanrikulu (16) which uses slant-based upgrade. They suggested a procedure to be used for the external arrangement progression of the unguided rockets at the sensible arrangement stage. A gradient based headway figuring is used to choose ideal arrangements. Objectives of smoothing out are described considered as flight execution of the plans.

As analyzed over, most of the work on rocket shape smoothing out relies upon inherited figures and reenacted hardening method. Reputation of those procedures can be seen through different fields of the sciences and development. As another choice for these adventitious methodologies, R.S approaches can also be taken as improvement. Especially the limits which are irregular and not smooth, the R.S procedure isn't hard to execute. There exist several applications that shows RS approaches are solid regardless of the way that association to the overall ideal isn't promised (17). Computational resources requirements of the RS approach are similarly seen palatable (17). Silveira Jr. et al. (18) has suggested Adaptively Random Search (ARS), which is such a RS, superior to next adventitious procedures, for instance, GA's. Ragaris and Tsoulos (19) differentiated some Random Search counts and SA on assorted test works and showed that the RS yields snappier game plans in most cases. Continuous employment of RS is be found in the composing (17,18,20).

Beside stochastic strategies, incline based procedures are used in arrangement improvement issues. Potentially the most actually made procedures is Sequential Quadratic Programming and is considered conceivably the most proper for the tendency-based upgrade (21). SQP systems are viably used for smoothed out shape improvement in the composing (22,23).

2.1 Aim

The aim of the project is to develop a design of missile with the installation of forward swept wing model in it which will increase the maximum distance it can travel before touching the ground.

The procedure depends on molding outside math of the rocket under given requirements in a computerized way. It intends to decide the most ideal setup regarding pre-characterized streamlined plan goals inside the plan space. Above all, the proposed plan enhancement strategy decreases the time spent for rocket outer arrangement plan in applied plan measure when contrasted with the traditional plan approach. In this work ideal streamlined arrangements are resolved utilizing examination programming.

In order to examine each of the configurations during the optimization, one aerodynamic solver code is used. Using ANSYS software we have analyzed the design variations and analysed lift and drag estimation and as well as flow analysis.

2.2 Organization of the Thesis :-

This proposition comprises of a complete 6 section. Foundation information on rocket applied plan and rocket streamlined features are given in Chapter 1.

A few techniques that can be applied for rocket plan improvement along with existing works in writing are additionally talked about. Point of the postulation is additionally given in Chapter 2. Verification of the developed models investigation and Model Designing of the models are discussed in chapter 3.

In Chapter 4, we discuss about the analysis methods and analysis result we get.

In chapter 5 we finalize the investigation with concluding remarks and in chapter 6 we give recommendations for future studies.

Chapter 3

3.1 Scope in administering Forward Swept Wing

Air will in everyday go to the rearmost completion of wing. On a standard plan, this clearly moves from wing tip to the wing root. In case of forward-cleared wing, in any case, this moves from wing root to the wing tip. Along these lines, the perilous tip hinder condition of backward cleared arrangement transforms into a more controllable and safer root delayed down on a forward cleared arrangement. It will grant full control of aileron paying little heed to loss in lift, and moreover infers that the drag-inciting driving edge openings or various machines aren't required. With air streaming inner ward, wingtip vortices and going with drag will diminished, rather the fuselage goes probably as an enormous wing divider and, since wings generally are greater at the root, this improves lift allowing more humble wing. Hence versatility is improved, especially at high methodologies.

As rockets additionally travel at exceptionally fast and gets into slows down that can be feasible to stay away from by the establishment of the forward cleared wing plan onto the canard of the rocket.

3.2 Design of the ballistic missile with the Forward swept wing

A design for the development of the missile with forward swept wing is designed using catia v5 software. These designs which have been designed are of different canard angles and with different wing tip designs. The designs were made by taking AIM-9 as the reference model.

3.2.1 Design 1

The first design has a forward swept wing fixed at the top end with a canard angle of 120 degrees and has the shape at the tip as a triangular instance. Which has made the design lighter with only three wings. The total number of instances we got are three.




Fig: 1.7 First Design View

3.2.2 Second Design

The second design has a forward swept wing fixed at the top end with a canard angle of 90 degrees and has the shape at the tip as a triangular instance. In this design we just changed the canard angle by 30 deg which has given us the opportunity to place another instance whose presence is essential for balanced flow. The total number of instances in this model are four.




Fig 1.8 Second Design View

3.2.3 Third Design

The third design has a forward swept wing fixed at the top end with a canard angle of 90 degrees and has the shape at the tip as a rectangular instance. In this design we just changed the canard angle by 30 deg which has given us the opportunity to place another instance whose presence is essential for balanced flow. The total number of instances in this model are four.



Fig 1.9 Third Design View

3.2.4 Fourth Design

The fourth design has a forward swept wing fixed at the top end with a canard angle of 120 degrees and has the shape at the tip as a rectangular instance. Which has made the design lighter with only three wings. The total number of instances we got are three. This design has given the optimum values required when the analysis is carried out. The material used to make the 3d model is PLU which made the design even lighter.




Fig 1.10 Fourth Design view

Chapter 4

COMPUTATIONAL ANALYSIS

4.1 INTRODUCTION TO ANSYS-FLUENT

ANSYS INC: Creates of Ansys group of items. Central command is in Canonsburg, PA-USA. This group of items incorporate the accompanying.

4.1.1 Ansys work seat application:

Improvement outline work where ANSYS applications are fabricated. This application is accessible in zones of primary, mechanics, calculation, CFD and so forth...

4.1.2 Ansys CFD:

Containing CFD coinciding devices with an overall pre and post preparing highlights.

4.1.3 Ansys ICEM CFD:

Condition of act CFD solver incorporates CFX and FLUENT.

4.1.4 Ansys LS-DYNA:

Express solver innovation with pre/post processor force of ANSYS programming
Utilized in recreation meta fashioning, stepping and so on At present we will utilize ANSYS CFD apparatus to run our recreations.

4.2 PROCEDURE TO SOLUTION BY ANSYS:

4.2.1 Geometry:

This is where we make calculation of required issue We can plan in some other programming like CATIA, SOLIDWORKS, AUTO-CAD and so forth... and import them here in "igs" design. We by and large use plan particular for it's easy to understand GUI. Here I utilized CATIA for planning of Y-conduit and plan particular for s-channel.

4.2.2 Meshing:

The area here is isolated into a few sections called components. Every component is joined by hubs. The more modest the component is the ideal the outcome is. Lattice can be either as quads or triangles in 2d calculation Symmetrical quality, Aspect proportion, skewness are the elements that are utilized to check the nature of the lattice.

4.2.3 Solver Set up:

To begin an answer for a given space we need to surrender solver set condition. Here in this solver set up everything depends on our necessity.

4.2.3.1 Flow Solvers:

Effectively, the squeezing factor based strategy was delivered to the low speed incompressible streams, while thickness based framework are used for high speed compressible streams. Anyway the two procedures have been as of late improved and redeveloped to handle and work for wide range of extents of the streaming conditions

above their regular or interesting arrangement. In these two strategies the speed of the field is gotten from all the energy conditions.

In thickness base approach, the movement condition is utilized to obtain the thickness field while the squeezing factor field has settled from the state of state. On other hand, in the squeezing factor based philosophy, the squeezing factor field was isolated by settling a squeezing component or squeezing factor correction condition which can be obtained by controlling congruity and energy conditions.

In these two cases a control volume base technique is used which includes: Division of space into separate control volumes using computational structure. Mix of the administering conditions on individual control volumes to create arithmetical conditions for discrete ward factors like rates, squeezing component and observed scalars and temperature. Linearization of discretized conditions and course of action of resultant straight condition structure to yield invigorated assessments of the dependent components. The two of the numerical systems use a relative discretization measure, anyway the way used to linearize and settle discretized conditions is remarkable.

4.2.3.1.1 Pressure-Based Solver:

The squeezing factor based solver has spot with general class of procedures called projection methodology. In projection procedure, the necessity of mass-insurance (movement) of the speed-field is refined by settling a squeezing variable condition. The squeezing factor condition is gotten from the congruity and the power conditions so the speed field, corrected the squeezing factor, satisfies the movement. Since managing conditions are nonlinear and also coupled to one another, the course of action cycle incorporates emphasess wherein the entire plan of directing conditions is settled reliably until the plan blends.




Fig 1.11 Pressure contour

4.2.3.1.2. Thickness Based Solver:

The thickness based solver addresses the overseeing conditions of coherence, force, energy, species transport all the while. Overseeing conditions for extra scalars will be tackled a short time later and successively using the philosophy depicted in Discretization and Solution. Since the regulating conditions are non straight, a couple emphasess of the game plan circle ought to be performed before a joined course of action is gotten.

4.2.3.2. Discretization (Interpolation Methods):

Field factors should be interjected to essences of control volumes. Interjection plans for concordat term: First Order Upwind is Easiest to combine, just first-request exact. Force Law More exact than the first-request for streams when Reynolds cell < 5 and Second Order Upwind it Uses bigger stencils for second request exactness, fundamental with tri/Tet network or when stream isn't lined up with lattice; combination might be more slow. Droning Upstream Cantered Plans for the Conservation Laws Locally third solicitation convection discretization plot for the unstructured cross areas; more exact in guessing discretionary streams, vortices, powers, etc such as Quadratic Upwind Interpolation Applies to quad/hex and cross variety organizations, accommodating for turning/whirling streams, third solicitation exact on uniform grid

4.2.3.3 Interpolation Methods (Gradients)

Angles of arrangement factors are needed to assess diffusive transitions, speed subsidiaries, and for the higher request quantization plans. The slopes of arrangement factors at the cell Centers that can be resolved utilizing 3 methodologies: Green Gauss Cell Based Least computationally thought. Plan may have the false scattering. Green Gauss Node Based More exact/computational heightened; limits sham scattering; recommended for the unstructured cross sections. Least Squares of Cell Based Default strategy; has comparative precision and properties such as Node based Gradients and it is less genuine computationally.

4.2.3.4 Interpolation Methods for Pressure:

Introduction plans for figuring cells face pressure, when utilizing pressing factor base solver in FLUENT are accessible as follows the Standard default plot; decreased

exactness for streams displaying huge surface-ordinary pressing factor angles close to limits ought to be utilized all things considered. Voila! – Use for exceptionally twirling streams, streams including steep pressing factor slopes (permeable media, fan model, and so forth), or in emphatically bended areas. Direct Use when different choices bring about intermingling troubles or un physical conduct Second Order Use for the compressible streams; not to utilized with permeable media, bounce, fans, and so forth or VOF/Mixture of multiphase models. Body Force Weighted Use when body powers are huge, ex., high Ra regular convection/exceptionally whirling streams.

4.2.3.5 Pressure-Velocity Coupling:

Pressing factor speed coupling alludes to the mathematical calculation which utilizes a blend of congruity and energy conditions to determine a condition for pressing factor (or pressing factor rectification) when utilizing the pressing factor based solver Five figs are open in FLUENT. The default plot, fiery Straightforward Consistent (SIMPLEC) Permits speedier association for fundamental issues. Squeezing factor Implicit with Splitting of Operators Valuable for wobbly stream issues or for networks containing the cells with the higher than typical lopsidedness Fragmentary Step Method for shaky streams. Used with NITA plot; equivalent ascribes as PISO.




Fig 1.12 Pressure Contour

4.2.3.6 Hybrid Initialization:

- New element at R13 has been Hybrid Initialized.
- This is chosen in GUI from the Initialization menu.
- This gives a brisk estimation of stream field, by an assortment of strategies.
- It settles Laplace's condition to decide the speed and pressing factor fields.
- All different factors, like temperature, disturbance species divisions, volume choppiness, species portions, volume portions, and so forth, will be naturally fixed dependent on area found the middle value of qualities or a specific insertion strategy.




Fig 1.13 Velocity Contour 1




Fig 1.14 Velocity Contour 2

4.2.3.7 Modifying the Courant Number:

. The Courant number it is the essential control for strength while using the coupled solvers.

- The transient term which is associated with the thickness base solver regardless, for reliable state issues.

- The CN portrays time step size.

- For thickness based express solver:

- Stability necessities power a most limit cutoff on the CN.

- Cannot be more significant than 2.

- For thickness based certain solver:

- The Courant number isn't limited by security goals

4.3 Lift and Drag Coefficient

In ansys the lift-drag coefficients of missile are calculated and are represented as graphs.




Fig 1.15 Drag Coefficient




Fig 1.16 Lift Coefficient

4.4 Testing in Wind Tunnel

The 3d printed/ metallic model which was developed has to be placed in wind tunnel test section to check for the flow visualization. The flow visualization can be done using fog oil which is generated and sent into the wind tunnel for testing the flow over the model designed. The fog liquid which is used will create a dense fog and it is sent into the test section and the turbine of the wind tunnel is turned on to the required speed to

let the fog travel at that speed while the test section is fixed in the middle of the flow. The fog generated will flow over the test model and the flow pattern can be seen by doing this we can consider the flow over the model can be seen as a rigid flow or a streamlined flow.



Fig 1.17 Flow testing 1




Fig 1.18 Flow testing 2

The rocket travels at speeds more than 2.5Mach number so that the model has to be placed in the Supersonic wind tunnel and tested. This will get to know variables in the existed models and the designed models.




Fig 1.19 Supersonic wind tunnel air compression tanks



Fig 1.2 Flow in Super sonic wind tunnel

Chapter 5

Result

5.1 Result

The model which is used to make the 3d print is the 3rd model which has the highest flow stability and streamlined flow. The pressure contours and the velocity contours of the 3d model analysis compared with the analysis of the actual model fabricated model analysis are getting approximately the same results as the missiles are released and they first accelerate and then decelerates to reach the targets. The actual model and the fabricated model have some slight variations when the testing has been conducted but on an overall estimate the result which was obtained is satisfactory.



1.21 Fabricated model




Fig 1.22 Flow analysis graph

Chapter 6

Conclusion and References

6.1 Conclusion

Detailed flow distribution over the model and lift-drag coefficient and pressure-velocity gradients have been noted and the model can be applied to use in the real life operations.

6.2 REFERENCES

- [1] Aircraft Performance and Design. London: McGraw-Hill, 1999 by J. D. Anderson.
- [2] Dynamics of Flight: Stability and Control. New York: John Wiley and Sons, 1995 by L. D. Reid and B. Etkin.
- [3] Missile Configuration Design. Orlando, Florida: McGraw-Hill, 1961 by S. S. Chin.
- [4] "Missile DATCOM User's Manual," United States Air Force, Ohio, 2011 by L. Auman, J. Doyle, W. Blake C. Rosema, and M. Underwood.
- [5] Tactical Missile Design. Reston, Virginia: American Institute of Aeronautics and Astronautics Inc., 2001 by E.L. Fleeman.
- [6] Missile Aerodynamics. Palo Alto, California: McGraw-Hill, 1960 by J. N. Nielsen.
- [7] "Enhancement of Aerodynamic Fast Prediction Methods for Slotted Rockets/Missiles," Istanbul Technical University, Istanbul, 2012 by B. Atak.
- [8] "Comparison of Deterministic and Stochastic Optimization Algorithms for Generic Wing Design Problems," Journal of Aircraft, vol. 37, no. 5, pp. 929-932, 2000 by M. Damodaran and X. Wang.

- [9] "Multi objective Design Optimization of Missiles," by M. Y. Öztürk Middle East Technical University, Ankara, 2009.
- [10] "GADO: A Genetic Algorithm for Continuous Design Optimization," The State University of New Jersey, New Brunswick, New Jersey, 1998 by K. M. Rasheed.
- [11] J. E. Burkhalter, R. M. Jenkins and M. B. Anderson, Journal of Spacecraft and Rockets, vol. 37, no. 5, pp. 663-669 "Missile Aerodynamic Shape Optimization Using Genetic Algorithms," September-October 2000.
- [12] "Optimal External Configuration of a Missile," Middle East Technical University, Ankara, 2009 by Ç. Tanıl.
- [13] "Optimization of Aerodynamic Properties of Tactical Missiles," Ankara, Middle East Technical University, 2011 by A. Karakoç.
- [14] "Aerodynamic Shape Optimization System of a Canard-Controlled Missile Using Trajectory Dependent Aerodynamic Coefficients," Journal of Spacecraft and Rockets, vol. 49, no. 2, pp. 243-249, March-April 2012 by S. K. Jung, Y. R. Yang, T. H. Cho and R. S. Myong.
- [15] "Simulated Annealing for Missile Optimization: Developing Method and Formulation Techniques," Journal of Guidance, Control and Dynamics, vol. 27, no. 4, pp. 616-626, 2004 by M. Bingöl and O. Tekinalp.
- [16] Journal of Spacecraft and Rockets "Optimal External Configuration Design of Unguided Missiles," vol. 35, no. 3, pp. 312-316, 1998 by V. Ercan and Ö. Tanrıkul.
- [17] R. Bochenek, J. Jezowski, and G. Ziomek, "Random Search Optimization Approach for Highly Multi-modal Nonlinear Problems," Advances in Engineering Software, vol. 36, pp. 504-517, 2005.
- [18] N. J. Silveira, K. Wada, N. S. M. Cardozo, A. R. Secchi, "Adaptive Random Search: A Promising Method for Determining the Stability of Mixtures," in 10th International Symposium on Process Systems Engineering, 2009, pp. 321-326.

- [19] I. E. Lagaris and I. G. Tsoulos, "Genetically Controlled Random Search: A Global Optimization Method for Continuous Multidimensional Functions," *Computer Physics Communications*, no. 174, pp. 152-159, 2006.
- [20] A. Abakarov, R. Simpson, and A. Teixeira, "Variable Retort Temperature Optimization Using Adaptive Random Search Techniques," *Food Control*, no. 19, pp. 1023-1032, 2008.
- [21] *Engineering Optimization, Theory and Practice*. Hoboken, New Jersey: John Wiley and Sons, 2009 by S. S. Rao.
- [22] "Comparison of Optimization Algorithms Applied to Aerodynamic Design," in 42nd AIAA Aerospace Sciences Meeting and Exhibit, Reno, Nevada, 2004 by D. W. Zingg and P. J. Lin.
- [23] D. W. Zingg, J. E. Hicken, N. B. Kuntawala "Preliminary Aerodynamic Shape Optimization of a Blended-Wing-Body Aircraft Configuration," in 49th AIAA Aerospace Sciences Meeting, Orlando, 2011.
- [24] *Practical Mathematical Optimization: An Introduction to Basic Optimization Theory and New Gradient Based Algorithms.*: Springer, 2005 by J. A. Snyman.
- [25] *Application of Metal Processing Simulations.*: ASM Handbook Volume 22B, 2010 by Simulia.
- [26] M. De Felice Ciccoli, G. Di Pillo, P. Brachetti and S. Lucidi, "A New Version of the Price's Algorithm for Global Optimization," *Journal of Global Optimization*, no. 10, pp. 165-184, 1997.
- [27] "DONLP2 Users Manual," Technical University at Darmstadt, Darmstadt, 1988 by P. Spellucci.
- [28] "Component Build-Up Method for Engineering Analysis of Missiles at Low-to-High Angle of Attack," Virginia, Hampton, 1992 by M. J. Hemsch, S. R. Vukelich and J. E. Jenkins.

- [29] In AIAA 22nd Aerospace Sciences Meeting, Reno, "Missile DATCOM: Aerodynamic Prediction of Conventional Missiles Using Component Build-Up Techniques," 1984.
- [30] Towards Global Optimization 2. NorthHolland, Amsterdam, 1978 by L.C.W. Dixon and G.P. Szegő.
- [31] "NASA Dual Control Missile Denek Taşı için Hesaplamalı Akışkanlar Dinamiği Analizleri ve Doğrulanması," in IV. Ulusal Havacılık ve Uzay Konferansı, İstanbul, 2012 by A. E. Çetiner, B. Atak, A. Akgül, and D. C. Oral.
- [32] "Experimental Test Cases," 2005 by M. R., Leavitt, L. D., Leopold, F. Mendenhall.
- [33] "Recent Applications and Improvements to the Engineering Level Aerodynamic Prediction Software MISL3," in 40th AIAA Aerospace Sciences Meeting & Exhibit, Reno, NV, 2002 by D. Lesieutre, J. Love, and M. Dillenius.